

# **University Microfilms Inc.**

300 N. Zeeb Road, Ann Arbor, MI 48106

## **INFORMATION TO USERS**

This reproduction was made from a copy of a manuscript sent to us for publication and microfilming. While the most advanced technology has been used to photograph and reproduce this manuscript, the quality of the reproduction is heavily dependent upon the quality of the material submitted. Pages in any manuscript may have indistinct print. In all cases the best available copy has been filmed.

The following explanation of techniques is provided to help clarify notations which may appear on this reproduction.

- 1. Manuscripts may not always be complete. When it is not possible to obtain missing pages, a note appears to indicate this.
- 2. When copyrighted materials are removed from the manuscript, a note appears to indicate this.
- 3. Oversize materials (maps, drawings, and charts) are photographed by sectioning the original, beginning at the upper left hand corner and continuing from left to right in equal sections with small overlaps. Each oversize page is also filmed as one exposure and is available, for an additional charge, as a standard 35mm slide or in black and white paper format.\*
- 4. Most photographs reproduce acceptably on positive microfilm or microfiche but lack clarity on xerographic copies made from the microfilm. For an additional charge, all photographs are available in black and white standard 35mm slide format.\*

\*For more information about black and white slides or enlarged paper reproductions, please contact the Dissertations Customer Services Department.

## UMI Dissertation Information Service

University Microfilms International A Bell & Howell Information Company 300 N. Zeeb Road, Ann Arbor, Michigan 48106

## 8618863

÷ -

Wang, Cou-Way

OPTIMIZATION OF ORBITAL ASSIGNMENT AND SPECIFICATION OF SERVICE AREAS IN SATELLITE COMMUNICATIONS

The Ohio State University

Рн.D. 1986

University Microfilms International 300 N. Zeeb Road, Ann Arbor, MI 48106

# Copyright 1986

by

Wang, Cou-Way

# All Rights Reserved

# OPTIMIZATION OF ORBITAL ASSIGNMENT AND SPECIFICATION OF SERVICE AREAS IN SATELLITE COMMUNICATIONS

## DISSERTATION

Presented in Partial Fulfillment of the Requirements for the Degree Doctor of Philosophy in the Graduate School of the Ohio State University

By

Cou-Way Wang, M.S.

\* \* \* \* \*

## The Ohio State University

**1986** 

## **Dissertation Committee:**

Professor Curt A. Levis

Professor Dean Davis

Professor Charles H. Reilly

Approved by:

Curt

Adviser Department of Electrical Engineering

©1986

.

COU-WAY WANG

All Rights Reserved

## TO MOM AND DAD

.

.

•

•

٠

•

.

.

·

.

#### ACKNOWLEDGMENTS

I would like to thank my advisor, professor emeritus Curt A. Levis, for his guidance through my graduate study. Many of his comments and criticism toward this work make it more presentable. I would also like to thank professor Clarence H. Martin of the Department of Industrial and Systems Engineering. He and professor Levis formulated the objective function which was used in Chapter III of this report. Special thanks to professor Charles H. Reilly of the Department of Industrial and Systems Engineering. He provided the mixed-integer and linear programming formulations that were used in the  $\Delta S$  concept; only with these formulations could the  $\Delta S$  concept be a scientific package.

Many thanks to Dr. Edward Miller of NASA Lewis Research Center. He provided much of the information that was used in this study.

Thanks to Dr. Osman Merih Buyukdura of the Department of Electrical Engineering. He reviewed this report and made many valuable suggestions and comments.

Thanks to Mr. David J. Gonsalvez of the Department of Industrial and Systems Engineering. He wrote the codes of the extended gradient search, the cyclic coordinate search, the mixed integer program and the linear program; he also provided the data calculated from these codes.

Thanks to Ms. Rebecca Thornton. She did excellent editorial work.

iii

Many thanks to my parents, my sister and brother. Their support and encouragement helped me go through many difficulties.

Special gratitude to my wife. She has been a good spiritual supporter. She is also the best assistant anyone can ask for; she did the drafting and much more; without her effort, this work would have taken much longer to finish.

Finally, I would like to thank NASA for its support under Grant NAG 3-159.

## VITA

July 13, 1954	Born, Taipei, Taiwan, Republic of China
1976	B.S., Physics, National Tsing-Hua University, Republic of China
1978	M.S., Applied Physics, National Tsing-Hua University, Republic of China
1978-1980	Reserved officer, Army, ROC
1982	M.S., Electrical Engineering, Ohio State University
1981–1985	Graduate Research Associate, The ElectroScience Laboratory, Ohio State University

### PUBLICATIONS

- (1) "The Role of Service Areas in the Optimization of FSS Orbital and Frequency Assignment", Curt A. Levis, Cou-Way Wang, Yoshikazu Yamamura, Charles H. Reilly and David Gonsalvez, The Eleventh American Institute of Aeronautics and Astronautics Communication Satellite Systems Conference, San Diego, March 1986.
- (2) "Frequency Sharing Between ISS and BSS Systems Near 23 GHz", Cou-Way Wang and Curt. A. Levis, URSI North American Radio Science Meetings, Vancouver, Canada, June 1985.
- (3) "On the 'Mean' Temperature Tm for Inferring Atmospheric Attenuation from Radiometric Measurement", Rick E. Leonard, Curt A. Levis, Kuan-Ting Lin and Cou-Way Wang, URSI North American Radio Science Meetings, Vancouver, Canada, June 1985.
- (4) "Engineering Calculation for Communication Satellite System Planning", Curt A. Levis, Cou-Way Wang, Clarence H. Martin and David Gonsalvez, Report 71-3533-2, ElectroScience Laboratory, The Ohio State University, March 1983.
- (5) "Calculation of the Allowable Orbit Geometry for BSS Systems and ISS Systems with Frequency Sharing", Cou-Way Wang, Master thesis, Department of Electrical Engineering, The Ohio State University, June 1982.

## FIELDS OF STUDY

.

. .

Major: Electromagnetics

.

.

Minor: Communications Solid State Electronics Mathematics

## TABLE OF CONTENTS

DEDIC	CATI	ON		ii
ACKNOWLEDGMENTS ii				ii
VITA				v
LIST	0F	TABLE	ES	tx
LIST	0F	FIGU	RES x1	11
CHAP1	TER			
I.	INT	RODUC	CTION	1
II.	DES	CRIP	TION OF PARAMETERS AND FACTORS IN C/I CALCULATIONS	10
	A. B. C. D. E. F. G.	Intr Sate Serv Mini Ante Rece Sigr	roduction ellite vice area mum elliptical beam enna reference patterns and protection ratio eived-power calculation hal quality requirement	10 11 13 14 17 25 33
III.	THE	OBJ	ECTIVE FUNCTION OF THE EXTENDED-GRADIENT AND CYCLIC	
	<b>CO</b> 0	RDIN/	ATE SEARCH METHODS	35
	A.	A. Introduction General discussion of the gradient and cyclic-coordinate		35
		sear	ch methods and their objective function	36
		1. 2. 3.	Introduction The gradient and cyclic-coordinate search methods An objective function for satellite	36 36
		4.	orbital/frequency assignments Numerical exercise using the extended gradient	39
		search method 5. Numerical exercise using the cyclic co	search method Numerical exercise using the cyclic coordinate	44
		~•	search method	51

	C.	Empirical examination of the objective-function topography	51
		<ol> <li>The importance of the objective-function surface topography to the gradient and cyclic-coordinate search methods</li> <li>Relation between variations of orbital/frequency separations and single-entry C/I<sub>e</sub> value</li> </ol>	51 56
		3. Topographic features of the objective function	58
		a) Objective-function topography of three- satellite example, orbital variables only b) Objective-function topography of n-satellite	58
		case case c) Possibility of one local minimum for a fixed	68
		permutation of orbital/frequency assignments	71
		(1) Introduction	71
		(2) Locations of global maximum and local minima of objective function (3) Topography of the worst single_entry C/I	72
		value	77
		(4) Numerical test	83
	D.	Discussion and conclusion	84
IV.	OPTI	MAL ORBITAL ASSIGNMENTS BY MEANS OF THE $\Delta S$ CONCEPT	86
	Α.	Introduction	86
	В.	Relation between single-entry C/Le protection	00
	C.	Calculation of $\Delta s$ value	95
		1. Exact method	95
		2. Approximate method	97
		3. Validity of approximate method	103
		4. Relation between service-area adjacency and $\Delta S(1)$ value	104
	D. E. F.	Relation between single-entry and total acceptable C/I <sub>e</sub> protection requirements Permutational aspect of the orbital-assignment problem Orbital assignment optimization formulations	106 108 111

•

•

•

÷.

viii

•

		1. 2.	∆s(1) constraint and objective function Mixed-integer and restricted-basis linear programming formulations	111
	_	•		
	G.	Num	erical examples	113
		1. 2. 3. 4. 5.	Definition of the problem MIP and RBLP results Comparison between MIP and RBLP techniques Suggestions for future improvement Possible extensions of the method	113 117 119 120 123
	Η.	Con	clusion and recommendation	124
۷.	A SI	ERVI	CE-AREA SPECIFICATION PROCEDURE	125
	A. B.	Int His	roduction torical perspective	125 125
		1.	service area assignment	125
		2. 2	limited spectrum and orbit resources	127
		J.	specification	131
	C.	Ser com	vice area specification by $\Delta S$ concept and munications-demand density	132
		1. 2.	Role of $\Delta S$ concept in service-area specification Role of communications-demand in service-area	132
		3.	specification General consideration	133 134
	D.	App a 1	lication of service-area specification concept to arge administration or group of administrations	135
	•	1.	General description Procedure of service-area specification and	135
		2	satellite assignment	136
		J.	systems	138
	E.	Num	erical example	139
		1.	Description of parameters Specifying four service areas according to AS	139
		<b></b> • ·	consideration and traffic-demand density	146

•

.

	<ol> <li>Improvemen service-ar</li> <li>Discussion</li> </ol>	t of traffic-supply matrix with ea specification concept of numerical example	156 170
	F. Discussion and	conclusion	171
VI.	CONCLUSION		173
APEN	DICES		
A	STREAMLINED SOUP C	ODE	175
B	CONCAVE, QUASI-CON	CAVE AND PSEUDO-CONCAVE FUNCTIONS	200
С	CONTOUR PLOTS OF O	BJECTIVE-FUNCTION SURFACE	204
D	<b>∆S CALCULATION COD</b>	E	216
Ε	FORMULATIONS OF MI	XED-INTEGER AND LINEAR PROGRAMS	225
	A. Algorithms B. Parameters and C. Formulation I D. Formulation II E. Formulation II F. Formulation IV G. Comparison bet	variables I ween formulation III and IV	225 227 229 231 232 233 233
F	C/I CALCULATION OF	MIXED INTEGER PROGRAM RESULT	237
REFE	RENCES		244

.

.

•

•

•

-

•

## LIST OF TABLES

.

•

· •

.

TABLE		PAGE
3.1	Test points of seven administrations	46
3.2	List of objective-function values	65
4.1	Example of <b>\s(l)</b> calculation procedure	99
4.2	$\Delta s(1)$ values of six South American administrations	101
4.3	C/I <sub>e</sub> results to show validity of approximate method	105
4.4	Satellite preferred locations of six administrations	116
4.5	$\Delta S$ parameters of six administrations	116
4.6	Mixed-integer and linear program results	118
5.1	U.S. domestic FSS communications demand in year 2000	128
5.2	Long distance telephone demand between top 28 cities in U.S. in year 2000	141
5.3	C/I results of two CONUS-beam satellites with 2.5-degree spacing	145
5.4	ΔS matrix of four regions	149
5.5	C/I results of collocating satellites serving East, West and South Central regions	150
5.6	C/I results of collocating satellites serving North Central, West and South Central regions	151
5.7	$\Delta s$ calculation for East and North Central regions	152
5.8	Telephone communications demand between major cities in four regions	154

5.9	Complete requirement matrix	155
5.10	Supply matrix without regional-beam satellites	157
5.11	Requirement matrix of four regions	159
5.12	Supply of regional beams to four regions	161
5.13	Percentage of satisfaction of demand by means of regional beams	162
5.14	Supply matrix adjustment	164
5.15	Supply matrix without regional beams	167
5.16	Supply matrix with regional beams	167
E.1	Satellite preferred locations of six administrations	234
E.2	$\Delta S$ parameters of six administrations	234
E.3	Mixed-integer and linear program results	236

•

.

s,

## LIST OF FIGURES

.

FIGURE		PAGE
2.1	Minimum ellipse configuration	15
2.2	BSS satellite transmitting reference patterns	19
2.3	BSS ground receiving reference patterns	20
2.4	FSS satellite transmitting reference pattern	22
2.5	FSS ground receiving reference pattern	23
2.6	BSS frequency protection ratio	24
2.7	Configuration of received-power calculation	26
3.1	Geographic relation of seven South American administrations	45
3.2	Numerical example of the extended gradient search process	48
3.3	Numerical example of the cyclic coordinate search process	52
3.4	Configuration space of three-satellite case	60
3.5	Typical shape of objective function	62
3.6	Selected area to calculate objective-function value	64
3.7	Topography of objective function	66
<u>3.</u> 8	Typical topography of objective function	67
3.9	Linear expansion of orbital assignments	75
3.10	Hypothetical case where two maxima occur in a linear trajectory	80
4.1	Configuration of received-power calculation	89

.

4.2	Configuration of $\Delta s(1)$ value calculation	96
4.3	Typical ∆s(l) value variation vs. mean satellite location	102
4.4	Geographic relation of four service areas	110
4.5	Geographic relation of six South American administrations	114
4.6	Satellite locations from mixed integer program result	122
5.1	Projected U.S. domestic FSS communications demand for the year 2000	129
5.2	Allocation of frequency channels in 6/4 GHz band	130
5.3	Locations of top 28 cities in U.S. with largest long- distance telephone demand in year 2000	144
5.4	Four selected regions with proper service-area separation and large communications demand	147
5.5	Possible beam arrangement for four regions	168
5.6	Possible communications distribution for four regions	169

.

.

.

·

#### CHAPTER I

## INTRODUCTION

Since the launch of the first commercial communications satellite, the INTELSAT I, in April 1965, satellite communications have become more and more popular internationally [1,2,3]. Not only does the number of satellites continue to increase, but the demand for future satellite services is growing rapidly [3,4]. This situation creates a problem of how to provide enough satellite communications capacity to satisfy all the potential users. The study of this report is devoted to contributions toward solving this problem by developing methods that can efficiently utilize the spectrum and orbit resources.

The most popular satellite orbit for the civil communications services is the geostationary orbit [5,6]. The idea of using this orbit was proposed by Arthur C. Clarke [1]. However, the geostationary orbit can accommodate only a limited number of satellites for a given frequency channel because satellites that have the same frequency channel must be properly separated from one another in space for acceptable interference protection [6]. When the geostationary orbit is considered "crowded" with satellites, it is crowded in terms of electromagnetic compatibility. This requirement greatly limits the satellite capacity of the geostationary orbit.

A method of increasing the communications capacity is to increase the spectral band available for satellite communications use. The

spectral region of interest lies between the maximum usable frequency (MUF) for reflection by the ionosphere and the first oxygen absorption line (about 60 GHz) [7]. By international agreement, this spectral region is divided into many bands for various services, e.g., the broadcasting-satellite service (BSS), the fixed-satellite service (FSS), the military service, navigation, weather detection, etc [2,8]. As a result, only a limited number of spectral bands are available for the civil communications services.

As an example of the large demand for satellite communications, when the 11 to 12 GHz spectral band for civil satellite service was opened for use on an international basis, every administration requested some frequency channels [4]. Even those administrations that do not need, or cannot afford, a satellite at the present time requested channel assignments for future use. Therefore, lack of enough spectrum and orbit resources becomes a serious problem with regard to planning for future communications satellite traffic, i.e., orbital and frequency allocations.

The goal of the orbital and frequency planning task is to use the limited amount of resources to provide enough communications capacity to satisfy every potential user. The main concern of the planning task is to ensure that mutual interference between different satellite systems is acceptable; a poorly planned scenario would be likely to result in unacceptable carrier-to-interference ratios (C/I), and hence unacceptable signal quality, for at least some users. To avoid this, the satellite orbital locations and frequency channel allocations should

be carefully planned. This planning task becomes very difficult when the number of satellites and channels to be assigned becomes large.

Moreover, since the demand for present and future communications satellites is large, it is important to use the available spectrum and orbit resources efficiently. In other words, the objective is to achieve the maximum information-transfer capacity for the resources allocated.

In 1977, the spectral band 11.7 to 12.5 GHz was assigned to Region 1 and the band 11.7 to 12.2 GHz to regions 2 and 3 for the planning of the BSS. The administrations in Regions 1 and 3 completed the planning in the 1977 World Administrative Radio Conference (WARC-77) [9]. The plan was based generally on spacing the satellites uniformly at 6 degrees, when they are assigned the same frequency channel [10]. The administrations in Region 2 delayed the planning process in WARC-77, with the intention of making the most efficient use of the geostationary orbit and the spectral band [11,12]; then proposed a plan at the Regional Administrative Radio Conference in 1983 (RARC-83) [13,14]. Planning for the fixed-satellite communications service (FSS) has been deferred to conferences in 1988 or beyond. Therefore, a method is needed to solve the assignment problem in as near an optimal way with regard to this objective as possible.

Much work has been done on this problem. Several studies discuss some important factors that should be considered in the assignment problem. A study by D. J. Withers identifies three areas that should be exercised in order to achieve effective resource utilization [15]. The

first area is engineering for an interference-limited environment by properly using the antenna characteristics, signal modulation, and multiple-access techniques to minimize the interference power. The second area is effective inter-system coordination. It includes: 1) proper pairing of the up- and down-link bands, 2) a standard frequency translation between up- and down-link bands, 3) an agreed scale of permissible single-entry interference noise allocation, 4) maximization of the satellite service arc by easing the satellite elevation angle constraint. The third area is the reduction of inhomogeneity in orbit-spectrum sharing. Also in the Final Acts of the WARC-77, the importance of placing satellites as close as possible for efficient orbit utilization is expressed [16]: the satellite spacing should be small, while still keeping the mutual interference acceptable.

Some studies deal with the orbital assignment problem alone. A Japanese study tackles the problem of orbit utilization through a non-linear programming optimization procedure with the objective of minimizing the total orbital arc used for a scenario [17]. The basic approach is to relate the satellite geocentric angular separation to the interference power; the problem is formulated as a non-linear programming problem and the sequential unconstrained minimization technique is applied to solve it numerically. Another Japanese study modified the above program so that it can find the optimal orbital assignment for a new satellite when it is inserted into an existing scenario [18]. The result is optimal in the sense of finding the best location for the new satellite, while making some modification to the

existing scenario, such that the satellite separations or, equivalently, the interference powers still meet the requirements. The best location for inserting the new satellite is chosen so that the total orbital arc occupied by the final result is minimized. To carry out rigid planning of many satellites, an evolutional model is used by repeatedly using the modified program to assign satellite locations one by one, and the ordering of insertion must first be chosen. It is not obvious, and appears unlikely, that the quality of the result is independent of this ordering.

Some studies deal with the frequency assignment problem alone. The methods of map-coloring and dot-linkage have been proposed to achieve the most conservational use of the spectrum resource [19,20,21,22]. A Japanese study tackles this problem by rearranging the frequency assignment of a given scenario that has an initial optimal orbital assignment [23]; e.g., orbital assignment is obtained from [17] with the frequency assignments assumed the same for all satellites. Therefore, in this Japanese study the frequency assignment, identified as a permutation problem, is handled independently of the orbital assignment: it is formulated as an integer program and the optimal permutation is obtained via the branch-and-bound method. When the new frequency assignments are made, the required satellite orbital separations may be reduced. The objective is the minimization of the total orbital arc occupied by the final scenario. Note that the combination of the two Japanese studies [17,23] becomes a complete package that solves the orbital and frequency assignments in two steps.

Some studies deal with both the orbital and frequency assignments. Some of these are aimed more at obtaining a better understanding of the problem than at actually solving it [24,25]. An application-oriented research group in Canada developed a software package for planning synthesis in connection with RARC-83 [26,27,28]. It is a multiple-stage process, and one of the objectives spelled out in the report is the minimization of the total orbital arc occupied by the scenario. First the minimum required orbital separations that meet the single-entry protection ratio are calculated for all pairs of satellites. These data are calculated in the following four cases: co-polarization and co-channel, co-polarization and adjacent channel, cross-polarization and co-channel, cross-polarization and adjacent channel. The initial scenario is an equal-spaced orbital assignment with co-channel, co-polarization frequency assignment. Then, the computer program can let the planner make changes both manually and automatically in the channel and/or polarization assignments, and manually in the orbital assignments. The program always produces a scenario, even if it turns out not to meet the required protection ratios. The result is a local optimum and not necessarily a global optimum.

Two methods have been proposed by a research group at the Ohio State University. The first method uses an extended gradient search technique to improve an existing scenario [29]. A sum of negative exponentials of the aggregate effective C/I ratios is used as the objective function to be minimized; therefore the procedure seeks to maximize the smallest of all such C/I ratios. The gradient direction of the objective function at the point representing the existing scenario

is calculated; then the objective function values at some discrete points along the negative of this direction are found. The point yielding the most favorable (minimum) objective function value is chosen as a new scenario to start another search process. The iterative process stops when a better scenario can not be found. The second method is called the cyclic coordinate search method [30]. In this method each orbital and frequency variable is varied in turn. Each time a set of points is examined, the point yielding the most favorable objective function value is selected as the new coordinate value for that variable. A cycle is completed when all the orbital and frequency variables have been varied once. The cyclic process is repeated with suitably adjusted step sizes until it reaches a solution where the improvement of C/I results halts. The detailed description of the two methods is given in Chapter III.

Transmission of a signal from the Earth terminal and its reception at a satellite constitutes an up-link; and transmission of a signal from a satellite and its reception at the Earth terminal constitutes a down-link. By international agreement, the up-link signals and the down-link signals are not in the same spectral band, so that the signals will not interfere with each other [31]. In this study only the regulation of the down-link traffic is considered. The up-link problem can be implemented similarly in another spectral band. Note that the above studies [17,26,27,28,29,30] also deal only with the down-link communications traffic regulation.

In Chapter II, some of the important factors and parameters involved in the carrier and interference power calculations are

discussed. Note that in this study an effective carrier-to-interference power ratio is used to evaluate the feasibility of a scenario; in Section II.F it will be shown that this is equivalent to the more usual margin calculation.

In Chapter III, the objective function to be minimized in the extended-gradient and cyclic-coordinate search techniques to improve a given scenario is analyzed [29]. It is shown that this function has large values when two (or more) orbital or frequency assignments are collocated; this indicates that both the signal quality requirement and the permutation of the orbital/frequency assignments need to be looked into in order to find the globally optimal scenario. Furthermore, some arguments are given which indicate that the objective function is likely to be a function with only one local minimum for a fixed permutation of orbital and frequency assignments; even though a definitive proof has eluded us, a set of numerical examples are presented which support these arguments. This suggests that a sufficient condition for obtaining the globally optimal solution by the extended-gradient search method is that it should terminate as an ordinary gradient search with the optimal permutation in orbital and frequency assignments.

In Chapter IV, a different approach, the  $\Delta S$  concept, is presented. It is shown that the single-entry C/I protection requirement is equivalent to a required minimum satellite separation; hence the highly non-linear C/I requirement can be viewed as constraints on the satellite locations. With this approach the orbital assignment can be formulated as a mixed-integer program and solved by the branch-and-bound method; or

it can be formulated as a linear program with non-linear side constraints and solved by a version of the simplex method for linear programming with restricted basis entry.

Chapter V intends to show that an important body of information for choosing FSS service areas is the communications-demand density. It is proposed that the service areas of an FSS system should be specified according to the communications-demand density in conjunction with the concept of small-beam design; the frequency re-use scheme can be implemented through small beams and well-separated service areas. A case study demonstrates that the communications supply for the United States could be significantly increased if the service areas are specified according to these principles. The  $\Delta$ S concept presented in Chapter IV is used in this case study.

## CHAPTER II

## DESCRIPTION OF PARAMETERS AND FACTORS IN C/I CALCULATIONS

## A. INTRODUCTION

The feasibility of a scenario is evaluated according to the signal quality [32], which is usually expressed in terms of the signal-to-noise ratio (S/N) [33]. For instance, the unweighted signal quality requirement for 625-line, color-television signal is suggested to be a S/N ratio of 33 dB for 99% of the worst month [34]. The signal power (S) is measured in the baseband channel after modulation improvement and baseband processing [35,36]. For the purpose of planning the broadcasting-satellite service (BSS), the requirement is that the pre-detection carrier-to-noise ratio (C/N) at the receiver input should equal or exceed 14 dB for 99% of the worst month or 10 dB for 99.9% of the worst month [37,38].

The noise power includes the receiver thermal noise  $(N_t)$  and all the interference powers from other communications systems [39]. In order that the interference powers from other communications systems will not further degrade the C/N level, the total (or aggregate) interference power level should be weak enough so that its contribution to the total noise power is negligible.

There are several criteria how weak the total interference power should be [40,41]; two which are commonly used are the interference-to-thermal noise ratio (I/N<sub>t</sub>) and the carrier-to-interference power ratio (C/I) [40]. In this study the C/I criterion is used to evaluate the feasibility of a scenario, with a minor modification. Account must be taken of the fact that a given interference level at the same frequency as the desired carrier is more damaging than the same level of interference at a far removed frequency. This can be done by multiplying each interference power at a non-carrier frequency by a relative protection factor (less than unity) before adding the interference powers to obtain an effective ratio (C/I<sub>e</sub>). This is discussed in more detail in Section II.F, where it is also shown that this formulation is fully equivalent to the more usual, but less convenient, representation in terms of margins.

In the following sections some of the important factors and parameters involved in the  $C/I_e$  calculation are discussed.

## B. SATELLITE

A satellite is a relay terminal, its basic function is to receive signals from some Earth stations and to re-transmit them to other Earth stations. It has receiving and transmitting antennas, and a frequency translator [42,43] or, in some cases, more sophisticated signalprocessing circuits which include frequency shifting.

A satellite may use any orbit to travel [2], but the geostationary orbit is the most popular orbit for civil communications. In this orbit

the satellite position is almost stationary with respect to any place on Earth; thus complicated satellite tracking systems at the Earth terminals may be avoided. This orbit is directly above the equator at a height of 37,165 kilometers above the Earth surface [2]. By international agreement this will be the main orbit for civil communications services [5,6]. Therefore, in this study only this orbit is considered.

Because the satellite is away from the Earth, it is possible to control its position and attitude only to a certain precision. A satellite drifts away from its designated orbital location and its position needs to be adjusted from time to time [44,45]. With present technology, a satellite orbital location may be maintained within 0.1 degree in the north-south and east-west directions, resulting in 0.14 degree of maximum excursion [44]. As for attitude control, the transmitting antenna pointing error may be kept within 0.1 degree, and the tolerance in the rotation about the beam axis is typically two degrees [44,45]. For the calculations of this report, the pointing error may be taken into account through the minimum elliptical beam calculation to be discussed in Section II.D, or through the antenna discrimination function to be discussed in Section II.E. The satellite rotational error may be taken into account through the minimum elliptical beam calculation to be discussed in Section II.D.

## C. SERVICE AREA

A service area is a designated area on the Earth surface to which a corresponding satellite directs its signals. Actually an antenna transmits its signal in all directions according to its pattern function, even though its target area is of limited size. By international agreement, a service area should be illuminated by its satellite main beam within the -3 dB contour of that beam [46,47]. This means that the received power density at any point in the service area should be within 3 dB of the power density at the antenna aim point.

For simplicity, a service area is represented by a set of test points at its boundary. To evaluate the  $C/I_e$  results of a scenario, one calculates the  $C/I_e$  values at all the test points of all the service areas, and compares them with the  $C/I_e$  requirement level. Because the interference is likely to be the worst on the service area boundaries, a scenario with satisfactory  $C/I_e$  values at all the test points should guarantee that the  $C/I_e$  values will be good at all the places inside all the service areas. The test points are also used to generate the minimum elliptical beam parameters to be discussed in Section II.D.

In this study a satellite and its corresponding service area(s) are viewed as a communications system. A service area may have several satellites, but all of these satellites are treated independently of one another.

### D. MINIMUM ELLIPTICAL BEAM

The antenna main beam (-3 dB contour) of a satellite to its designated service area should be shaped, using available antenna technology, to fit the shape of the service area as suitably as possible [48]. However, a reference antenna pattern for shaped beams is still unavailable, i.e., there exists no internationally agreed method for predicting, for regulatory purposes, the discrimination to be expected from shaped beams outside their respective service areas. In order to analyze a scenario in terms of  $C/I_e$  results, the interference powers are therefore calculated by assuming that a service area is illuminated by a minimum elliptical beam from the satellite position that covers all the test points of that service area [47].

This minimum ellipse is specified by five parameters: the longitude and latitude of the beam aim point, the orientation angle, and the major- and minor-axis beam widths. In Figure 2.1, the aim point, which is on the Earth surface, is denoted as A. The antenna beam plane is a plane perpendicular to the satellite beam axis, SA, and passing through the aim point A. The vectors AM and AN denote the major and minor axes. The beam widths in the directions of these two axes, viewed from the satellite, are  $\psi_{max}$  and  $\psi_{min}$ , respectively. The orientation angle, which is not shown, is the angle measured anti-clockwise in the antenna beam plane from a line parallel to the equatorial plane to the major axis of the ellipse. The more detailed descriptions of these parameters can be found in a National Telecommunication and Information Administration (NTIA) document [49].



Figure 2.1. Minimum ellipse configuration.

To generate the ellipse data, one needs to specify the nominal satellite location and the locations of a set of test points; other parameters that can be specified are the minimum beam width, minimum elevation angle, satellite pointing error and rotational error. The resulting elliptical cone covers all the test points that are used to generate this ellipse; in a worst-case calculation that includes the specified satellite pointing error and rotational error. A computer program developed by Akima was used to generate the five ellipse parameters for the calculations of this report [49].

With these parameters, the half-power beam width (HPBW),  $\psi_{to}$ , with respect to any test point, T, on the Earth surface can be calculated by means of a somewhat involved procedure. First the vector AP of Figure 2.1 is calculated, where P is the intersection of the line ST and the antenna beam plane. Then, the angle  $\sigma$  between the vector AP and the major axis AM is calculated. The length of AR is calculated from

$$AR = AM \cdot [\cos^{2}(\sigma) + A_{r}^{2} \cdot \sin^{2}(\sigma)]^{-1/2} , \qquad (2.1)$$

where  $A_r$ , called the axial ratio of the elliptical beam, is the ratio between AM and AN. Then it is assumed that the ratios between the angles  $\psi_{max}$ ,  $\psi_{min}$ ,  $\psi_{to}$  and their corresponding arcs AM, AN, AR are the same; this is a very good approximation when the angles are not large. With this approximation, the angle  $\psi_{to}$  is calculated from

$$\Psi_{to} = \Psi_{max} \cdot [\cos^2(\sigma) + A_r^2 \cdot \sin^2(\sigma)]^{-1/2} , \qquad (2.2)$$

where A<sub>r</sub> can be seen as the ratio between  $\psi_{max}$  and  $\psi_{min}$ .

The off-axis angle,  $\psi_{t}$ , toward the point T is calculated by the cosine law

$$\cos(\psi_t) = (ST^2 + SA^2 - AT^2)/(2 \cdot ST \cdot SA),$$
 (2.3)

where ST, SA, AT denote distances in Figure 2.1.

The off-axis angle  $\psi_t$  and the corresponding HPBW  $\psi_{to}$  will be used to calculate the directivity of the antenna toward the specific point, T. The antenna pattern envelopes used to calculate the directivity will be described in Section II.E.

The detailed description of all the parameters and the formulations of all the calculations can be found in the Spectrum Orbit Utilization Program (SOUP) manual [50]. A streamlined SOUP code is listed in Appendix A. It is much less complicated than the original SOUP code. The basic calculation is exactly the same, but with fewer options. For instance, the streamlined version does not consider propagation loss.

## E. ANTENNA REFERENCE PATTERNS AND PROTECTION RATIO

Two sets of antenna reference patterns are used in the study. They are representations, adopted by the International Radio Consultative Committee (CCIR), of the envelopes of real antenna patterns. Their use therefore should result in a near worst-case interference power calculation. The first set includes the satellite transmitting antenna reference patterns and the ground receiving antenna reference patterns suggested in the International Radio Consultative Committee Conference

Preparatory Meeting in 1982 (CCIR-CPM-82) for the Regional Administration Radio Conference for Region 2 in 1983 (RARC-83) [10,51,52]. These are the BSS patterns. The gain, G, of the transmitting antenna is calculated from [53,54]

$$G = e \left[ (\pi/\psi_{max}) / (180/223) \right]^2 \cdot A_r , \qquad (2.4)$$

where the symbols mean

e : the beam efficiency, taken as 0.6 in this study,

 $\psi_{max}$  : the beam width of the major axis, in radians,

 $A_r$  : the axial ratio of the elliptical beam.

The ground receiving antenna gain in the BSS calculations is taken as 40.2 dB, corresponding to a circular-beam antenna of 1-meter diameter, 12 GHz carrier frequency and 0.6 beam efficiency. The reference patterns are shown in Figures 2.2 and 2.3, and are used in the calculation of the objective function values in Chapter III.

In Figures 2.2 and 2.3, both the transmitting and receiving antennas have two reference patterns with mutually orthogonal polarizations. The transmitting antenna transmits signals of the designated polarization according to the co-polarization pattern, at the same time it also transmits orthogonally polarized signals according to the cross-polarization pattern. The receiving antenna receives the wanted signals according to the co-polarization pattern by aligning its polarization parallel to that of the wanted signal. Any signal that is co-polarized with the wanted signal is received according to the






A: co-polar component without side-lobe suppression (dB)

0	for	ψ/ψο	< 0.25
$-12(\psi/\psi_{0})^{2}$	for 0.25	< ψ/ψο	< 0.94
$-11.3 - 25.\log(\psi/\psi_0)$	for 0.94	< \u03cm/\u03cm	< 18.88
-43.2dB (-3dBi)	for 18.88	< \u03cm/\u03cm	

B: cross-polar component (dB)

-25	for	0	< ψ/ψο	<	0.25	
$-30-40 \cdot \log[1-\log(\psi/\psi_{c})]$	for	0.25	$\langle \psi/\psi_0$	<	0.44	
-20	for	0.44	< ψ/ψο	<	1.28	
$-17.3-25 \cdot \log(\psi/\psi_{0})$	for	1.28	< ψ/ψο	<	3.22	
-30 until intersection with	co-po	lar co	omponent	CI	urve;	
then as for co-polar component						

Figure 2.3. BSS ground receiving reference patterns.

co-polarization pattern, and any signal that is cross-polarized with the wanted signal is received according to the cross-polarization pattern. These unwanted signals constitute the interference power at the receiver input.

In the second set of reference antenna patterns, intended for the fixed-satellite service (FSS) calculations, the satellite transmitting antenna reference pattern given in Figure 2.4 is a modified version of the fast fall-off reference pattern from CCIR-CPM-82/RARC-83 [55]. This modified reference pattern had been suggested as useful for the FSS systems [56,57]. The transmitting antenna gain is again calculated from Equation (2.4). The ground receiving antenna reference pattern, shown in Figure 2.5, is a modified version of the reference pattern from the International Radio Consultative Committee (CCIR-82) Report 391-4 [58]. The modification is suggested in a CCIR-82 Recommendation and in the CCIR-CPM-82/RARC-83 Report [59,60], and should become the standard in year 1987. The receiving antenna gain is 43.2 dB, corresponding to a circular-beam antenna of 4.5-meter diameter, 4 GHz carrier frequency and 0.6 beam efficiency. Note that there is no cross-polarization pattern in Figure 2.4 because such a pattern has not been adopted by the international committee.

The relative protection ratio,  $PR(dB)-PR_0(dB)$ , used in Chapter III is taken from a CCIR-CPM-82 Report [61] and is shown in Figure 2.6. The value of  $PR_0$  is the co-channel protection ratio, the value of the actual protection ratio  $PR(dB)-PR_0(dB)$  depends on the carrier frequency offset between the wanted and unwanted signals as well as on the modulation



relative gain below on-axis gain (dB)





relative gain below on axis gain (dB)

-12 $(\psi/\psi_0)^2$  for  $0 < \psi < \psi_1$ (29-G)-25·log $(\psi)$  for  $\psi_1 < \psi$ after intersection with -G-10: as -G-10

 $\psi$ : off-axis angle  $\psi_0$ : half-power beam width G.: on-axis gain Half-power beam width = 1.17 degrees G: 43.2 dB

Figure 2.5. FSS ground receiving reference pattern.



Figure 2.6. BSS frequency protection ratio.

method of the signals [62]. The Carson bandwidth will be taken as 25.2 MHz, which is appropriate for the BSS TV/FM case.

#### F. RECEIVED-POWER CALCULATION

Refer to Figure 2.7 for the geometry, but note that the radius of the Earth relative to that of the geostationary orbit is exaggerated greatly for clarity. In this figure, the satellites assigned to service areas A, B are designated  $S_A$ ,  $S_B$ , respectively. The aim points of  $S_A$ ,  $S_B$  are the points a, b. The point d is one of the test points in A. The test points are normally chosen on the boundary of their service areas because interference is likely to be the worst there. The minimum ellipses of A, B from  $S_A$ ,  $S_B$  are labeled E(A), E(B). For the test point d, the off-axis angle of the  $S_A$  signal and the corresponding HPBW in the direction toward d are  $\psi_{tc}$ ,  $\psi_{tco}$ ; the subscript c is meant as a mnemonic for carrier. The distance from  $S_A$  to d is x. These values are used to calculate the carrier power received from  $S_A$  at d. Also, for test point d, off-axis angle of the S $_{\sf B}$  signal and the corresponding HPBW are designated  $\psi_{ti}$ ,  $\psi_{tio}$ , respectively. Since the receiving antenna at the test point d is pointed at  $S_A$ , its off-axis angle toward  $S_B$  is  $\psi_{ri}$ . The distance from SB to d is y. These values are used to calculate the interference power received from SB at d.

Referring to Figure 2.7, the carrier power, C, at d is calculated by means of the Friis transmission equation [63,64]:



Figure 2.7. Configuration of received-power calculation.

$$C = \frac{P_{A} \cdot G_{A} \cdot D_{A}(\psi_{tc}) \cdot G_{d} \cdot c^{2}}{f_{A}^{2} \cdot (4\pi)^{2} \cdot x^{2}},$$

where the symbols mean

- $P_A$  : the transmitting power of  $S_A$ ,
- $G_A$  : the transmitting antenna gain of  $S_A$ ,
- $D_A$  : the co-polarization transmitting antenna discrimination

(2.5)

from  $S_A$  in the direction toward d,

Gd : the receiving antenna gain at d,

- .c : the velocity of light,
- $f_A$  : the carrier frequency.

In Chapter III, the effective isotropic radiated powers are assumed constant for all the satellites. In Chapters IV and V, it is assumed that the carrier power densities at the aim points are equal for all the service areas [65]; therefore, all the satellite transmitting powers are adjusted to meet this requirement.

The interference power received at d must be calculated with care because there may be a polarization mismatch between the wanted and unwanted signals. Both of the orthogonally polarized signals transmitted from  $S_B$  must be decomposed into two components, one that is parallel to the wanted signal of the receiver and the other that is orthogonal. With the proper choice of the antenna reference patterns, the received interference power from each component is calculated from

$$I = \frac{P_{B} \cdot G_{B} \cdot D_{B}(\psi_{ti}) \cdot G_{d} \cdot D_{d}(\psi_{ri}) \cdot c^{2}}{f_{B}^{2} \cdot (4\pi)^{2} \cdot y^{2}}$$
(2.6)

where the symbols mean

 $P_B$  : the transmitting power of  $S_B$ ,

 $G_B$  : the transmitting antenna gain of  $S_B$ ,

- $D_B$  : the transmitting discrimination from  $S_B$  to d,
- G<sub>d</sub> : the receiving antenna gain at d,
- $D_d$  : the receiving antenna discrimination from d in the direction toward  $S_B$  when the antenna is pointed at  $S_A$ ,  $f_B$  : the interference frequency.

The total interference power is the summation of all the components. For instance when the signals of  $S_A$  and  $S_B$  are co-polarized, the received interference power at d from  $S_B$  is calculated from [64,66]

$$I_{cp} = I_{tc,rc} + I_{tx,rx} + (I_{tc,rx} + I_{tx,rc}) \cdot D_{x}$$
, (2.7a)

when they are cross-polarized, the received interference power is calculated from

$$I_{xp} = I_{tc,rx} + I_{tx,rc} + (I_{tc,rc} + I_{tx,rx}) \cdot D_{x}$$
 (2.7b)

Here the subscripts mean

cp : wanted and unwanted signals are co-polarized,

xp : wanted and unwanted signals are cross-polarized,

- tc : signal transmitted according to the co-polarized reference
   pattern,
- tx : signal transmitted according to the cross-polarized reference pattern,
- rc : signal received according to the co-polarized reference pattern,

# rx : signal received according to the cross-polarized reference pattern.

The term  $D_X$  is the rain depolarization factor [66,67]. Since the propagation effect is not considered in this report, the term  $D_X$  is taken to be zero. Also, Equation (2.7a) is further simplified as

$$I_{cp} = I_{tc,rc} , \qquad (2.7c)$$

because the cross-polarization component, which arises from the crosspolarized patterns of both the transmitting and receiving antennas, is negligible compared to the co-polarization component. Finally it should be noted that Equation (2.7b) is an approximation. In an actual case, these terms should add as phasors, not in a power sense; but to perform that calculation the relative phases of the tc, tx patterns and that of the rc, rx patterns would have to be known. So, without the term  $D_X$ , a worst-case formula would be

$$I_{xp} = \left(\sqrt{I_{tc,rx}} + \sqrt{I_{tx,rc}}\right)^2 . \qquad (2.7d)$$

When the carrier frequencies of the wanted and unwanted signals are different, a frequency filtering factor must be included in the effective interference power calculation. The proper expression for such a filtering factor can be easily obtained as follows. When evaluating the effect of the unwanted signal, the usual procedure is to calculate a term called the protection margin M; from

$$M_i(dB) = (C/I_i)(dB) - PR_i(dB),$$
 (2.8)

where the symbols mean

- i : index of frequency channel of the wanted signal,
- I<sub>j</sub> : total interference power in channel i,
- $PR_i$ : protection ratio against interference power in channel i.

The interference power is acceptable when the value of M<sub>i</sub>(dB) is positive. (When there are several interference signals of the same carrier frequency, their total interference power is obtained by decomposing every polarized signal into parallel and orthogonal components with respect to the wanted signal, then calculating each interference power and summing them, as discussed above.) When there are several unwanted signals of different carrier frequencies, the equivalent protection margin, M, that evaluates the over-all effect of the interference power is calculated from [68,69]

$$M(dB) = -10 \cdot \log \left[ \sum_{i} 10^{-M_{i}(dB)/10} \right], \qquad (2.9)$$

where each term  $M_i$  is the protection margin in one frequency channel, and the summation is over all frequency channels. Equation (2.9) can be re-written as

$$M(dB) = -10 \cdot \log(\sum_{i} 10^{-\{(C/I_{i})(dB) - PR_{i}(dB)\}/10})$$

$$= -10 \cdot \log(\sum_{i} 10^{-\{(C/I_{i})(dB) - [PR_{i}(dB) - PR_{0}(dB)]\}/10} \cdot 10^{PR_{0}(dB)/10})$$

$$= -10 \cdot \log(\sum_{i} 10^{-\{(C/I_{i})(dB) - [PR_{i}(dB) - PR_{0}(dB)]\}/10}) - PR_{0}(dB)$$

$$= C(dB) - 10 \cdot \log(\sum_{i} 10^{\{I_{i}(dB) + [PR_{i}(dB) - PR_{0}(dB)]\}/10}) - PR_{0}(dB)$$

$$(2.10)$$

If the equivalent total, or aggregate effective interference power,  $I_e$ , is defined from the expression of the equivalent protection margin, M, as

$$M(dB) = (C/I_e)(dB) - PR_O(dB)$$
  
= C(dB) - I\_e(dB) - PR\_O(dB) , (2.11)

then the equivalent aggregate interference power can be expressed as

$$I_{e}(dB) = 10 \cdot \log(\Sigma 10^{\{I_{i}(dB) + [PR_{i}(dB) - PR_{0}(dB)]\}/10})$$
(2.12)

Therefore, the quantity  $[PR_i(dB)-PR_o(dB)]$ , which is the relative protection ratio in Figure 2.6, can be interpreted as a filtering factor operating on the interference power when the carrier frequencies of the wanted and unwanted signals are different, and denoted as  $F(f_{wanted}, f_{unwanted})(dB)$ . This approach will be taken throughout Chapter III. For a scenario of many satellites and where each satellite has many frequency channels, the aggregate effective interference power,  $I_{knj}^{e}$ , received in channel n at test point j in service area k is calculated from a power summation of terms of the type given in Equation (2.12),

$$I_{knj}^{e}(dB) = 10 \cdot \log\{ \sum_{i \in K/k} \sum_{m \in N_{i}} 10^{\lfloor I_{im,knj}(dB) + F(f_{n},f_{m})(dB) \rfloor / 10} + I_{i \in K/k} \sum_{m \in N_{i}} I_{i} + I_$$

$$\Sigma = 10^{[I_{km,knj}(dB) + F(f_n,f_m)(dB)]/10}$$
  
meN<sub>k</sub>/n (2.13a)

or

$$I_{knj}^{e} = \sum_{i \in K/k} \sum_{m \in N_{i}} I_{im,knj} F(f_{n},f_{m}) + \sum_{m \in N_{k}/n} I_{km,knj} F(f_{n},f_{m})$$
(2.13b)

where the symbols mean

- K/k : the index set of all the satellites, excluding satellite Sk,
- N<sub>i</sub> : the index set of all the channels assigned to satellite i,
- Iim,knj : the single-entry interference power from channel m of S<sub>i</sub>, received at channel n of test point j in service area k,
- $F(f_n, f_m)$  : the relative protection ratio between the carrier frequency  $f_n$  and interference frequency  $f_m$ , as shown in Figure 2.6.

The aggregate  $(C/I_e)$  value in a channel at test point d is obtained by calculating the values of C using Equation (2.5) and  $I_e$  using Equation (2.13b) and dividing.

#### G. SIGNAL QUALITY REQUIREMENT

When the signal quality requirement is stated as "S/N be no less than 30 dB for 99% of the worst month" [38], the main concern is to obtain satisfactory performance except during rare, large attenuation of signals due to heavy rains [70]. The prediction of statistical rain rate distributions as a function of geography will not be adressed in this study. In this study the carrier and interference powers are calculated without considering atmospheric absorption and rain attenuation. As for the assumption that the carrier power densities are the same at all satellite antenna aim points, the satellite transmitting powers can be adjusted to allow for these propagation effects so that the power density requirements are still satisfied; but this has not been done in the calculations which will be presented.

Most satellites function as a repeater [71]: they receive a signal, change the signal carrier frequency, and transmit it back to Earth. In such a design, any interference power generated on the up-link remains in the signal when re-transmitted in the down-link [72]. In this study, only the interference power generated in the down-link is considered; any interference power from the up-link is not included in the calculation. For BSS, it has been proposed in international telecommunication meetings that the  $C/I_e$  requirement value in the up-link be 10 dB higher (better) than that of the down-link [73,74,75]. Therefore for the BSS the interference power in the up-link should make an insignificant contribution to the overall interference power, and can be neglected. For FSS, the  $C/I_e$  requirement values for the up- and

down-links may not differ much [76,77]. Therefore for the FSS case the  $C/I_e$  requirement value for each half link must be specified with care so that the total interference power does not degrade the signal quality excessively.

In evaluating the feasibility of a scenario, first one calculates the C/I<sub>e</sub> values at all the test points; then compares them with the pre-determined C/Ie requirement value. A scenario is said to be good when all the resulting  $C/I_e$  values exceed the requirement value [78,79]. In Chapter III, a C/Ie requirement value of 30 dB will be used to evaluate the quality of the extended gradient search results; the precise required value depends on the modulations, but 30 dB is typical [78]. In Chapter IV, the requirement value is arbitrarily set at 25 dB in the numerical calculation; the precise value is relatively unimportant because the main goal of the numerical calculations in Chapter IV is to demonstrate the feasibility of the method. In Chapter V, the requirement value is set at 20 dB in the numerical calculation, where the U.S. is used as a case study, for the following reason. For the U.S. domestic satellite systems in the 6/4 GHz band, four-degree spacing between two satellites was used initially to regulate the orbital assignments. However, in order to better utilize the orbit resource, the Federal Communication Commission (FCC) has decided to adopt two-degree spacing in the satellite planning task in the 6/4 GHz band, to be effective beginning in 1987 [80]. Since the method proposed in Chapter V is not meant only for the U.S., the  $C/I_e$  requirement is set at 20 dB in the numerical calculations so that it could appear more reasonable on the international basis.

#### CHAPTER III

### THE OBJECTIVE FUNCTION OF THE EXTENDED-GRADIENT AND CYCLIC-COORDINATE SEARCH METHODS

#### A. INTRODUCTION

The main purpose of the study in this chapter is to explore the mathematical nature of the orbital/frequency assignment problem by investigating an objective function used in the extended-gradient and cyclic-coordinate search methods to solve the satellite planning problem. It is shown that in order to find the global optimum solution one must deal with both the permutation of the orbital/frequency assignments and the signal quality requirement, e.g., the C/I ratio, in the optimization process. It is also shown that for a given set of scenarios with fixed orbital permutation (frequencies fixed) the function defined by the smallest single-entry C/I value has at most one local maximum. This strongly suggests that the objective function has only one local minimum for a given orbital permutation, as supported by some numerical evidence; this indicates that the extended gradient search process is highly likely to find the global optimal solution if it terminates as an ordinary gradient search with optimal orbital/frequency permutation.

# **B. GENERAL DISCUSSION OF THE GRADIENT AND CYCLIC-COORDINATE SEARCH METHODS AND THEIR OBJECTIVE FUNCTIONS**

#### 1. Introduction

The purpose of including this section is to introduce the basic principles of the gradient and cyclic-coordinate search methods, and to demonstrate how they perform for a particular objective function. Using the gradient search method for the assignment problem was proposed by Professor Clarence H. Martin of the Department of Industrial and Systems Engineering [29]; using the cyclic coordinate search method was proposed by Professor Clark A. Mount-Campbell of the Department of Industrial and Systems Engineering [30]; the objective function used in both methods was formulated by Professor Curt A. Levis of the Department of Electrical Engineering and Professor Clarence H. Martin of the Department of Industrial and Systems Engineering [29]; the numerical calculations discussed in Section III.B were performed by Professor Charles H. Reilly and Mr. David J. Gonsalvez of the Department of Industrial and Systems Engineering [30].

#### 2. The Gradient and Cyclic-Coordinate Search Methods

The gradient and cyclic-coordinate search methods are two techniques commonly used by systems engineers to find an optimal condition for system performance [81,82]. In applying either method, an objective function, which is a function of a set of decision variables, is constructed in order to rank candidate solutions. The decision

co

variables represent the controllable operating conditions of the system; in the present application, they are the satellite orbital location and frequency channel assignments. The objective function should be a measure of the performance of the system under the conditions specified by the values of the decision variables. For instance, one solution, or specification of values for the decision variables, should represent more attractive operating conditions than a second solution if the former solution yields a greater (smaller) value when evaluated in an objective function which is to be maximized (minimized). The optimal solution (operating conditions) should be that solution which provides the greatest (smallest) objective-function value, when the objective function is to be maximized (minimized).

With such an objective function, the gradient search is performed in the following way [29,81]. Assume that the function is concave (convex) and is to be maximized (minimized). First a point that represents an initial operating condition is located, and the gradient components of the objective function at that point are calculated. Then a proper step size is chosen in the gradient (negative-gradient) direction so as to reach another point representing another operating condition. Because the objective-function value predicts the system performance, a sufficiently small step in the gradient (negativegradient) direction should always lead to a new condition that is better than the initial condition, at least according to the chosen objective function. Then, the same procedure is repeated with the improved operating condition as the new initial point and the search step size

properly adjusted according to the magnitude of the gradient: the smaller the gradient, the smaller the step size. This procedure should be repeated until a point is reached at which the gradient search does not yield improvement in system performance. This final solution will correspond to the optimal operating condition.

When the objective function is not concave (convex), global optimality of the solution is not guaranteed; instead the solution may converge to a local optimum, with the choice of the initial starting point influencing strongly which local optimum is selected. To reduce this influence and enhance the likelihood of finding a global or nearglobal optimum, a modified gradient search procedure, called an extended gradient serach, was used in the present application [86]. Consider the objective function as one to be minimized. First, the gradient direction at the initial point is calculated. Then from this point on the search line is extended in the negative-gradient direction to the boundary of the feasible region; the objective function is calculated at a set of ten equally-spaced points along that search line. The point with the most favorable objective-function value is chosen as the new starting point to do another calculation. If the starting solution is the most favorable solution, another ten equally-spaced points between the starting solution and the first tested point are examined, the point yielding the most favorable objective-function value is chosen as the new starting solution. The procedure stops when no solution can be found that yields a more favorable objective-function value.

Since the search line is extended, the method may allow the search process to go from a region with one local minimum to another region; this reduces the likelihood of the search being "trapped" at an undesirable minimum, i.e., one much greater than the global minimum.

The cyclic coordinate search method, with a given objective function, proceeds as follows [30,82]. First, an initial operating condition is assumed. Then the decision variables are varied in turn, one at a time. Each time a set of points, where the corresponding variable is varied along its feasible coordinate range, is examined; the point yielding the most favorable objective-function value is identified, and the search continues from this new solution with another decision variable and the same search process. A cycle is completed when every decision variable has been allowed to vary; once a cycle is completed, another cycle can begin. When there is no more improvement in the objective-function value, the process is repeated within a smaller region and with smaller step-sizes. The whole search process terminates when no more improvement is obtained with a step size commensurate with the accuracy to be obtained.

## 3. An Objective Function for Satellite Orbital/Frequency Assignments

For the satellite planning problem, a suitable objective function is formulated as [29]

$$Z = \sum_{k \in K} \sum_{n \in N_{k}} Z_{knj}$$

$$= \sum_{k \in K} \sum_{n \in N_{k}} \exp \{a - [C_{knj}(dB) - I_{knj}^{e}(dB)]\}, \quad (3.1)$$

where the symbols mean

- K : the index set of all satellites,
- N<sub>k</sub> : the index set of all frequency channels assigned to satellite k,
- $J_k$  : the index set of test points of service area k,
- a : arbitrary parameter used to avoid overflow in computer
   calculation,

 $I_{knj}^e$ : the effective interference power at channel n of test point j in service area k, in dB.

It is assumed that each satellite is associated with one service area; thus the index k that represents a satellite also represents its corresponding service area. Note that it is the satellites that are counted in the index set K; one service area may be served by several satellites and each satellite is treated as an individual unit. The value of  $C_{knj}$  is calculated from Equation (2.5). The value of  $I_{knj}^{e}$  is calculated from Equation (2.13a), reproduced here

$$I_{knj}^{e}(dB) = 10 \cdot \log_{10} \{ \sum_{i \in K/k} \sum_{m \in N_{i}} 10^{[Iim,knj(dB)+F(f_{n},f_{m})(dB)]/10} + i \in K/k \mod N_{i}$$

$$\sum_{m \in N_{k}/n} 10^{[Ikm,knj(dB)+F(f_{n},f_{m})(dB)]/10} \}, \qquad (3.2)$$

where  $I_{im,knj}$ , calculated from Equation (2.6), is the interference from channel m of satellite i into channel n of test point j in a service area served by satellite k. In Equation (3.1) the exponentially weighted summation is over all the frequency channels, at all the test points, in all the service areas. In Equation (3.2), the doublesummation adds the interference from all other satellites, and the single-summation adds the interference from other channels of the same satellite.

The satellite locations, denoted by  $o_1$  for satellite 1, and the carrier frequencies, denoted by  $f_{1h}$  for channel h of satellite 1, are the decision variables. The limits of the orbital variables are usually determined by elevation angle constraints [83]; sometimes an eclipse-protection requirement may impose additional restrictions [84]. The limits of the frequency variables are determined by the limits of the available spectral band [4].

It is clear that the orbital variables are continuous variables; however, this is not necessarily true for the frequency variables. In past international conferences, generally the available spectral bands were each divided into channels of equal bandwidth, with each channel specified by its center frequency [85]. This is likely to be true for future conferences also; then the frequency variables will be discrete.

In the gradient search method, the derivatives with respect to all the decision variables need to be calculated; since it is impossible to differentiate with respect to a discrete variable, it is assumed here that in the frequency assignment the center frequencies of all the channels are allowed to vary continuously while each channel still has the same, fixed bandwidth. With this assumption, differentiation with respect to the frequency variables is allowed, and the frequency protection ratio of Figure 2.6 can be used. It is hoped, but cannot be guaranteed, that the optimization of the continuous-varying channel problem will lead to at least a near-optimum of the discrete channel problem.

Note in Figure 2.6 that there is a plateau in the frequency protection ratio. When two satellites are assigned frequencies with the frequency offset in this range, the gradient search method would find variation of these frequency assignments not useful because it would not change the objective-function value. This is definitely not the result the system planner wants, because separating the frequency assignments sufficiently could produce better  $C/I_e$  results. To avoid this problem, the plateau is deformed to form an isosceles triangle with small slopes  $(\pm 0.05 \text{ dB/unit } \beta)$ ; this modification allows the frequency assignments to be separated if the frequency offset is located in the plateau region.

From Equation (3.1) it is clear that the value of  $Z_{knj}$  is small for large  $(C/I_e)_{knj}(dB)$  values. Since a good scenario should have large  $C/I_e$  at all test points, the global minimum of the objective function is likely to be a good solution for the assignment problem.

The gradient components of Z are

$$\nabla Z = \left(\frac{\partial}{\partial o_1} Z, \frac{\partial}{\partial o_2} Z, \dots, \frac{\partial}{\partial f_{11}} Z, \dots\right)$$
 (3.3)

where the partial derivatives have been taken for all the decision variables; also

$$\frac{\partial}{\partial o_{1}} Z = k \varepsilon K n \varepsilon N_{k} j \varepsilon J_{k} Z_{knj} \frac{-\partial (C/I_{e})_{knj} (dB)}{\partial o_{1}} , \qquad (3.4)$$

$$\frac{\partial}{\partial f} Z = k \varepsilon K n \varepsilon N_{k} j \varepsilon J_{k} Z_{knj} \frac{-\partial (C/I_{e})_{knj} (dB)}{\partial f_{1h}} , \qquad (3.5)$$

Referring to Figure 2.5 and Equations (2.5), (2.6), moving  $S_A$  clearly changes  $\psi_{tc}$ ,  $\psi_{ri}$ , and x, moving  $S_B$  changes also parameters  $\psi_{ti}$ ,  $\psi_{ri}$ , and y. Every satellite acts both as a desired and interfering source, so it affects the parameters associated with  $S_A$  in some terms, and those with  $S_B$  in others, and both in a few terms. As one moves  $S_A$  and  $S_B$ , the effective isotropic radiated powers, i.e., the products  $P_A \cdot G_A$ ,  $P_B \cdot G_B$ of satellites  $S_A$  and  $S_B$  respectively, are kept constant; but the carrier powers calculated from Equation (2.5) change somewhat at the test points, causing some contribution to  $\partial z / \partial o_1$ . Also, the minimum ellipses must be recomputed for new satellite locations; the change in ellipse changes  $\psi_{tco}$ ,  $\psi_{tio}$  and therefore  $D_A$  ( $\psi_{tc}$ ),  $D_B$  ( $\psi_{ti}$ ) since  $D_A$  depends on  $\psi_{tc}/\psi_{tco}$  and similarly for  $D_B$ .

Here one sees that in Equation (3.4) or (3.5),  $Z_{knj}$  is the weighting factor for the terms  $\partial/\partial \sigma_1[(C/I_e)_{knj}(dB)]$  and  $\partial/\partial f_{1h}[(C/I_e)_{knj}(dB)]$ . Since the term  $Z_{knj}$  is a negative exponential function of  $(C/I_e)_{knj}(dB)$ , it will be largest for the values k, n, and j

for which  $(C/I_e)_{knj}(dB)$  is smallest; so the weight serves to emphasize the contribution from those test points and channels which need improvement most urgently. With such an objective function, the gradient search method tends to relocate most strongly the orbital/frequency assignments that are responsible for the worst  $C/I_e$ terms, and the result is an increase of these  $C/I_e$  values. This, of course, was the rationale for choosing the exponential function. A numerical example, below, will illustrate this point.

#### 4. Numerical Exercise Using the Extended Gradient Search Method

A numerical exercise will now be given to show that the properties associated with the objective function are indeed as discussed, and that the performance of the extended gradient search method with respect to this objective function is as predicted.

In this exercise seven administrations are under consideration; they are Argentina, Bolivia, Brazil, Chile, Paraguay, Peru and Uruguay (denoted as ARG, BOL, BRZ, CHL, PRG, PRU, and URG respectively) with the geographic relation shown in Figure 3.1 and the test points listed in Table 3.1. It is assumed that every administration has requested one orbital location and three contiguous frequency channels, with cross polarizations for adjacent channels, for its satellite; the orbital locations and the carrier frequencies of the leading (lowest) channels are the decision variables, and these leading channels all have the same polarization. The feasible orbital arc was taken from 90 to 110 degrees west, and the spectral band from 12,200 to 12,300 MHz, for all satellites; the bandwidth of each channel is assumed to be 12 MHz, with



Figure 3.1. Geographic relation of the seven South American administrations.

### Table 3.1

#### Test Points of Seven Administrations

ARGENT	INA	PARAGU	PARAGUAY	
LON.	LAT.	LON.	LAT.	
-66.2	-21.8	-57.6	-25.3	
-62.8	-22.0	-58.6	-27.3	
~53.8	-2/.2	-56.2	-27.2	
-63.8	-54.7	-54.2	-24.1	
-68.3	-54.8	-58.1	-20.2	
-73.2	-50.9	-59.1	-19.3	
-78.5	-31.4	-62.7	-22.2	
-68.6	-24.8	-58.7	-27.2	
BOLIVI	Α	PERU		
	10.0	70 4	10.0	
-65.5	-9.8	- 10.4	-18.3	
-69.Ø	-11.2	-70.5	-9.4	
-60.0	-16.1	-74.0	-7.6	
-67.5	-22.7	-75.2	-2.7 -Ø.Ø	
		-80.3	-3.4	
DD 4 77 1		-81.3	-4.4	
BRAZIL		-76.1	-13.4	
-60.5	4.5			
-52.Ø	3.0	IRICIAN		
-46.0	-7.5	UKUGUA	T	
-42.Ø	-22.5	-56.2	-34.9	
-53.0	-32.5	-54.9	-35.0	
-70.8	-10.5	-53.5	-34.0	
-73.Ø	-7.0	-55.6	-30.8	
-69.0	1.0	-56.9	-30.1	
		-58.2	-31.9	
CHILE		-58.4	-33.9	
-60 5	17 6	-57.9	-34.5	
-67.1	-23.0			
-78.8	-34.2			
-71.7	-43.2			
-72.8	-52.3			
-75.7	-46.8			
-74.Ø	-28.9			
-/10.4	-18.3			

.

.

.

.

a 2.58 MHz guardband between two channels. The carrier and interference powers are calculated from Equations (2.5), (2.6) and (2.13a); the antenna reference patterns are from Figures 2.2 and 2.3; the frequency protection ratio is from Figure 2.6; the ellipse data are calculated from [49].

In this calculation the initial scenario is that all satellites are collocated at 110 degrees west, and the initial frequency assignments extend from 12,235 to 12,265 MHz in 5 MHz intervals. The intermediate solutions at all the search steps and the final solution after ten search processes are shown in Figure 3.2 to demonstrate how the search process proceeds. In Figure 3.2(c), only the worst aggregate C/I<sub>e</sub> values for these administrations are shown. In these figures the administrations are denoted by numbers according to alphabetic order: 1 for Argentina, 2 for Bolivia, 3 for Brazil, 4 for Chile, 5 for Paraguay, 6 for Peru and 7 for Uruguay. The improvement of the C/I<sub>e</sub> results is clearly seen as the iteration process proceeds. The orbital assignments are almost steady after iteration 7, and the frequency assignments are almost steady after iteration 5; this indicates that the search process may have reached the vicinity of a local minimum.

The improvement mechanism of the extended-gradient search method can be observed as follows. Note that the  $C/I_e$  results of administrations 3, 4, 6 and 7 are the worst after iteration 1; then at iteration 2, the orbital and frequency assignments of these four satellites make a very significant change, while that of the other three satellites are almost unchanged. This is exactly the purpose of the



(a) Orbital assignment variation





Figure 3.2. Continued.

.





exponentiation in the objective function as discussed in Section III.B.3.

The purpose of modifying the ordinary gradient search method can be seen as follows. It is known that the objective function takes on large values when some of the orbital and/or frequency assignments are identical (for reason to be explained in Section III.C); hence exchanging the position of two satellites means jumping over such a region. In Figure 3.2(a) the orbital order established in iteration 1 is disturbed by the extended search process: the order of satellites 2 and 5 is changed at iteration 7. Thus the extended gradient search method can move from a region with one local minimum to another region.

#### 5. Numerical Exercise Using the Cyclic Coordinate Search Method

The performance of the cyclic coordinate search method is demonstrated here; the same objective function is used to solve the same assignment problem. The initial scenario is changed as follows: all satellites are at 110 degrees west and 12,250 MHz. The results are shown in Figure 3.3. The improvement in the  $C/I_e$  results is obvious.

#### C. EMPIRICAL EXAMINATION OF THE OBJECTIVE-FUNCTION TOPOGRAPHY

### 1. The Importance of the Objective-Function Surface Topography to the Gradient and Cyclic-Coordinate Search Methods

The topography of the objective function greatly influences the outcome of the search methods. An objective function has only one





Figure 3.3. Continued.



Figure 3.3. Continued.
local maximum (minimum) if it is strictly concave (convex) or pseudo-concave (pseudo-convex). (See Appendix B for the definitions and properties of strictly-concave and pseudo-concave functions.) The gradient and cyclic-coordinate search methods should lead one to a point very close to this maximum (minimum), if not directly locate it. If the objective function is not strictly concave, strictly convex, pseudo-concave, or pseudo-convex, it may have several local maxima or minima. The greatest maximum (least minimum) is called the global maximum (minimum), or simply maximum (minimum). The best operating conditions correspond to the global maximum (minimum), when the objective function is to be maximized (minimized). For such a function, both the gradient and the cyclic-coordinate search procedures will almost certainly give improvement to an initial operating conditions. However, both procedures may eventually be trapped at a local optimum instead of reaching the global optimum.

Therefore, knowledge of the mathematical properties of the objective function is important in determining whether the gradient and cyclic-coordinate search methods are to succeed. For instance, when the objective function has only one local maximum (minimum), or if the local maxima (minima) all correspond to nearly equal objective-function values, then it will be relatively easy to obtain a near-optimal solution by either method. If, on the other hand, there exist many local maxima (minima) at which the objective-function value is much smaller (greater) than its global maximum (minimum) value, then there is a greater likelihood of arriving at a solution which is much poorer than the true optimum.

Therefore, the topography of the objective function used for the satellite orbital and frequency assignment synthesis, i.e., Equation (3.1), will be examined next.

#### 2. Relation Between Variations of Orbital/Frequency Separations and Single-Entry C/I<sub>e</sub> Value

A very important concept should be pointed out first: for two satellites and their corresponding service areas, the single-entry  $C/I_e$  values at all the test points increase as the satellite orbital/ frequency separations increase.

In the C/I<sub>e</sub> calculation several terms are relatively invariant when satellite locations change. The received carrier powers are calculated from Equation (2.5), and the interference powers are calculated from Equations (2.6) and (2.13a). The satellite effective isotropic radiated powers (EIRP), defined as the product of the transmitting power and the transmitting antenna gain, are assumed the same for both satellites, regardless of orbital locations. Because the service areas are covered by the main beams within the -3 dB contour, the carrier transmitting discrimination factor at the test point is always larger than, and close to -3 dB. Because the geostationary orbit radius is 6.6 times the Earth radius, the propagation distances from the satellites to all the test points vary little when satellite locations are changed.

One factor that dominates the variations of the single-entry  $C/I_e$ values is the receiving discrimination term  $D_d(\psi_{ri})$  in the interference power, and that variation depends chiefly on the satellite spacing. Any relative change of the two satellite locations will change the ground antenna off-axis angles toward the interfering satellite. Through the reference pattern in Figure 2.3, this angular change induces a substantial change in the interference power. The further the two satellites are separated, the lower the discrimination factors, and thus the lower the interference. Another factor, the interference transmit discrimination term  $D_B(\psi_{ti})$ , also varies when the satellite locations are changed; however, the change of  $D_B(\psi_{ti})$  is much less than the change of  $D_d(\psi_{ri})$  because  $\psi_{ti}$  (seen from the geostationary satellite toward the Earth) changes much less than  $\psi_{ri}$  (seen from the ground upward to the sky) when the location of the interfering satellite is changed. The single-entry C/I<sub>e</sub> values increase when the corresponding satellite spacing increases until the discrimination factor  $D_d(\psi_{\mbox{ri}})$  is in the far side-lobe of the reference pattern; then the C/Ie values become almost constant as the spacing keeps on increasing. This will be called "quasi-monotonic" variation: C/Ie values decrease (increase) continuously or remain constant when satellite spacing decreases (increases) continuously.

For a given service-area pair, the single-entry  $C/I_e$  value depends mainly on the magnitude of the satellite spacing, and slightly on the mean satellite orbital location. (It will be shown in Chapter IV that it varies only slightly for a large range of this mean satellite

location.) Therefore, for the purpose of the discussion in this section, an approximation is made by assuming that, for a given service-area pair, the single-entry  $C/I_e$  values at all the test points depend only on the magnitude of the satellite spacing and are independent of the mean satellite location.

Another factor that dominates the variation of the single-entry  $C/I_e$  values is the frequency offset in the frequency assignments. As explained in Section II.F, the frequency filtering factor of Figure 2.6 must be included in the effective interference calculation when the carrier frequencies of the wanted and unwanted signals are different. The larger the frequency offset, the lower the filtering factor, and the lower the interference. Therefore, the variations of the single-entry  $C/I_e$  values also depend strongly on the separation of the frequency assignments: for given orbital assignments, the further the frequency assignments are separated, the higher the single-entry  $C/I_e$  values.

#### 3. Topographic features of the objective function

# a) Objective-function topography of three-satellite example, orbital variables only

For simplicity a three-satellite system will be used to demonstrate some key points. The three satellites are  $S_1$ ,  $S_2$ ,  $S_3$ , and these symbols will also be used to designate their orbital locations. A single channel will be considered so that no frequency variables are involved; in this case I and  $I_e$  are identical.

The configuration space for this example is described here. First one draws the three orbital variable axes and indicates the feasible region, as in Figure 3.4. The line segment HB measures the feasible range for S<sub>1</sub>, HD for S<sub>2</sub>, HF for S<sub>3</sub>. In this figure the three satellites are assumed to have the same feasible orbital range, i.e., HB = HD = HF; therefore the feasible region is a cube. Any point in this cube represents an assignment scenario; its coordinates S<sub>1</sub>, S<sub>2</sub>, S<sub>3</sub> are the satellite orbital locations of this assignment. For example, the point H represents the assignment in which all three satellites are collocated at one end of the orbital arc; the point A is for three satellites collocated at the other end; the point B is for S<sub>1</sub> located at one end while S<sub>2</sub> and S<sub>3</sub> are collocated at the other. Note that associated with every point in the configuration space there is an objective-function value which can be calculated by Equation (3.1).

Several important features need to be mentioned. First, any point on the line AH indicates a three-satellite collocation. Then, all the points in the shaded plane ABHE correspond to S<sub>2</sub>, S<sub>3</sub> collocation; those in the plane ACHF to S<sub>1</sub>, S<sub>2</sub> collocation; those in the plane ADHG to S<sub>1</sub>, S<sub>3</sub> collocation. Points within any one of the six sub-regions separated by the three collocation planes have the same satellite permutation. For example within the sub-region bounded by the planes AHB, AHC, ABC and HBC, all the points have the satellite permutation S<sub>1</sub>>S<sub>2</sub>>S<sub>3</sub>; this is indicated by the notation 1-2-3 in Figure 3.4. Since the objectivefunction value is large when the C/I values are small, the objective function should have the highest values along the line AH because the





Figure 3.4. Configuration space of three-satellite case.

C/I values are the smallest for collocated satellites. Near the pairwise collocation planes ABHE, ACHF, ADHG the objective function should be moderately high, while between these planes the objective function falls off to form valleys because all the satellites are spread out. Thus we can visualize the objective-function topography as dominated by a system of ridges corresponding to satellite collocations; these ridges are connected to each other at the line AH where three satellites are collocated. Of course, the ridges will be high if the service areas are close together and hence the transmitting discrimination factor  $D_B$  in Equation (2.6) is large; they will be small when the service areas are well separated.

An arbitrary plane in this cube may be chosen to show the objective-function values corresponding to points on this plane. The plane chosen here is the plane CJKLFMNP shown in Figure 3.5(a). The objective function might have the shape shown in Figure 3.5(b). The base plane is divided into six sub-regions by its intersection with the shaded planes in Figure 3.4. Each intersection line represents the collocation of two satellites, and each sub-region represents one permutation of the three satellites. The objective-function topography sketch shows these sub-regions separated by the ridges representing two-satellite collocation.

The objective-function values of a real set of scenarios will now be calculated here to confirm the above arguments. The three administrations are:  $S_1$  for Peru,  $S_2$  for Bolivia,  $S_3$  for Paraguay. The orbital locations chosen for the calculation constitute the shaded plane



Figure 3.5. Typical shape of objective function.

RSTU shown in Figure 3.6; it is inside the region of permutation  $S_1>S_2>S_3$ , and is a plane for which the value of  $S_2$  is constant at 60°W. The value of  $S_1$  ranges from 60 to 64 degrees west, while the value of  $S_3$  ranges from 57 to 60 degrees west. The objective-function value is calculated from Equation (3.1), the values of C and I are calculated from Equations (2.5), (2.6) and (2.13a), the antenna reference patterns are taken from Figures 2.2 and 2.3, the ellipse data are calculated from [49]; the test points are those given in Table 3.1 for these administrations. The results are listed in Table 3.2, and the topography is plotted in Figure 3.7. As predicted, the maximum of the objective function in this plane occurs at R, the three-satellite collocation, the objective function rises to apparent ridges above the lines RS and RU which lie in the planes ABH and ADH of two-satellite collocation the objective function falls off and forms a valley.

The typical topography of the objective-function surface for points lying on a plane inside any region of fixed permutation is shown in Figure 3.8. The point R' will be on the line AH, the lines R'S' and R'U' will be in the planes of two-satellite collocation, the points T' will be chosen in the R'S'U' plane. This figure illustrates the typical shape and locations of the tip, ridges and valley.



Figure 3.6. Selected area to calculate objective-function value.

## Table 3.2

.

•

.

.

z = 2 2 K J	k expla-(C	/1/ <sub>kj</sub> (aB)],	8 = 5,
S <sub>2</sub> (BOL)	= 60 degr	ees,	
s <sub>1</sub> (pru)	S <sub>3</sub> (PRG)	z	1n(z)
60.	60.	0.2625 E+4	7.873
	59.5	0.8918 E+3	6.793
	59.	0.7644 E+3	6.639
	58.	0.7606 E+3	6.634
	57.	0.7601 E+3	6.633
60.5	60.	0.1529 E+4	7.333
	59.5	0.1084 E+3	4.685
	59.	0.4488 E+2	3.804
	58.	0.4460 E+2	3.798
	57.	0.4455 E+2	3.797
61.	60.	0.1010 E+4	6.918
	59.5	0.5477 E+2	4.003
	59.	0.2781 E-1	-3.582
	58.	0.1111 E-1	-4.500
	57.	0.1104 E-1	-4.506
62.	60.	0.9673 E+3	6.874
	59.5	0.5322 E+2	3.974
	59.	0.1490 E-1	-4.206
	58.	0.1498 E-4	-11.109
	57.	0.6218 E-5	-11.989
63 <b>.</b>	60.	0.9613 E+3	6.868
	59.5	0.5289 E÷2	3.968
	59.	0.1454 E-1	-4.231
	58.	0.8250 E-5	-11.705
	57.	0.1852 E-6	-15.502
64.	60.	0.9596 E+3	6.867
	59.5	0.5277 E+2	3.966
	59.	0.1440 E-1	-4.241
	58.	0.7938 E-5	-11.744
	57.	0.1058 E-6	-16.062

List of Objective-function Values

....

65

•



.

.

.

. 66

.

.





A point made in Section III.B.3 can also be illustrated by referring to Figure 3.7. The gradient direction at the point x is almost perpendicular to the line RS. This means that when this gradient direction is followed, the orbital location of  $S_1$  is almost unchanged while  $S_3$  is placed further away from  $S_2$ . Note that points close to the line RS correspond to nearly collocating the satellites  $S_2$  and  $S_3$ ; when these satellites are close to each other, the test points of their service areas have low C/I values. This means that the corresponding weighting factors in Equation (3.4) are high, and the gradient search process will push the two responsible satellites  $S_2$  and  $S_3$  apart.

#### b) Objective-function topography of n-satellite case

The general shape of the objective-function topography for an n-satellite case will now be addressed. Note that the orbital and frequency variables are two different classes of decision variables so that their effects on the objective-function topography should be discussed separately.

In the first step only the orbital variables are discussed; it is assumed that the frequency assignments are the same for all the satellites. For a case of n satellites to be assigned orbital locations, the n orbital variables constitute an n-dimensional configuration space, and it is divided into n! regions of different orbital permutations (i.e., satellite orderings) by n(n-1)/2 (n-1)dimensional hyperplanes of two-satellite collocation. Each region of a fixed orbital permutation is surrounded by (n-1) hyperplanes of two-

satellite collocation and two (n-1)-dimensional boundary hyperplanes, each corresponding to one satellite at the boundary of its feasible orbital arc. The objective function has large values when satellites whose service areas are not well separated are collocated. For two neighbouring regions of different permutations, the corresponding permutations differ only in exchanging the relative positions of two satellites. Therefore the hyperplane between these two regions corresponds to the collocation of these two satellites, and the objective function may have large values in this hyperplane. All of these hyperplanes will connect at the line where all satellites are collocated; as a result the objective function has many local minima within the complete feasible region, and they can be characterized by their specific orbital permutations.

In general a satellite is associated with an orbital location and a set of frequency allocations. Basically, the effect of the frequency variables on the topography depends on the frequency protection ratio pattern shown in Figure 2.6. There is one important similarity between this pattern and the co-polarization antenna patterns: the relative protection ratio value is non-increasing as the frequency offset increases. So the spreading of the frequency assignments has the same effect on the objective-function value as the spreading of the orbital assignments: the further the frequency assignments are separated, the less the interference, and the smaller the objective-function value. Hence the objective function may have large values when the frequency assignments are collocated (or nearly collocated since the plateau in

Figure 2.6 has a certain bandwidth), and local minima may occur where frequency assignments are spread out.

The total number of local minima of the objective function in a case of n orbital and n frequency variables can be deduced as follows. Theoretically, the n orbital variables create n! regions with at least one local minimum in each region, then in each region the n frequency variables further create n! sub-regions with at least one local minimum in each sub-region. Therefore, there might be at least (n!)<sup>2</sup> local minima in this case. However, in reality the number of local minima is likely to be smaller, e.g., the collocation of two satellites may not result in bad C/I values to produce hyperridge of large objective-function values when the service areas are well separated.

Also, another very important thing can be deduced from the above discussion: the local minima of the objective function may be characterized by the permutations of their orbital/frequency assignments.

## c) Possibility of one local minimum for a fixed permutation of orbital/frequency assignments

#### (1) Introduction

Figures 3.6 and 3.7 also show that the objective function as a convex (or pseudo-convex) function with only one local minimum within a region of fixed orbital permutation. In this case this result should be obvious because, for a three-satellite example with only orbital variables, the objective function can be minimized by spreading the outside satellites as far as allowed by the feasible arc, i.e., until they reach the boundaries. It is interesting to speculate whether, for a general case of n satellites, there is only one local minimum in a region of fixed orbital/frequency permutation. If this conjecture could be shown to be true, or approximately true in the sense that all the minima for a fixed permutation have approximately equal objectivefunction values, then an ordinary (not extended) gradient search procedure would be sure to find an optimal, or at least near-optimal solution for a given orbital/frequency permutation. However, a definitive proof of the conjecture has eluded us. The remainder of this chapter presents evidence that it is likely to be true for the orbital variables. Therefore, in this section it is assumed that every satellite has been assigned the same frequency channel, and the discussion is confined to a region of fixed orbital permutation.

#### (2) Locations of Global Maximum and Local Minima of Objective Function

First, it is shown the global maximum of the objective function corresponds to a scenario of all-satellite collocation by showing that the objective-function value decreases quasi-monotonically along any linear trajectory starting from all-satellite collocation.

#### **Definition 1**

For two scenarios x, y in the n-dimensional configuration space, the linear trajectory between them is specified by the set of scenarios z such that

z = ax + (1-a)y, (3.6) where a is a parameter with value 0 < a < 1.

#### Lemma 1

Assume that all the satellites have continuous feasible orbital arcs. Then given any two scenarios x, y, there exists a linear trajectory between them which is completely inside the feasible region; i.e., the feasible region is a convex set.

#### Proof

A scenario z in the n-dimensional configuration space is expressed by a 1\*n row matrix  $z=(z_1, z_2, \dots, z_n)$ , where the components are the satellite locations of satellites 1, 2, ... n respectively.

Along a lilnear trajectory of starting scenario x and final scenario y, a scenario z satisfies

$$z = ax + (1-a)y$$
, (3.7a)

where O<a<1, or

$$(z_1, z_2, \dots, z_n) = a(x_1, x_2, \dots, x_n) +$$
  
(1-a)(y<sub>1</sub>, y<sub>2</sub>, ... y<sub>n</sub>), (3.7b)

or

Since all the satellites have continuous feasible orbital arcs, one has  $z_i \in F_i$  if  $x_i$ ,  $y_i \in F_i$  for 1<i<n, where  $F_i$  is the feasible arc for satellite i. Hence any scenario z along this linear trajectory is well defined, and the linear trajectory is completely inside the feasible region. So the feasible region is a convex set.

#### Lemma 2

Within a region of fixed orbital permutation in the n-dimensional configuration space all the pairwise satellite separations vary linearly along a linear trajectory.

#### Proof

From Lemma 1, for scenario z the pairwise satellite separation between satellites i, j is  $|z_i-z_j|$ . From Equation (3.7c) one has

$$(z_i - z_j) = a(x_i - x_j) + (1 - a)(y_i - y_j)$$
, (3.8a)

where  $0 \le 1$ . Since all the scenarios are of the same orbital permutation,  $(x_i - x_j)$  and  $(y_i - y_j)$  must have the same sign. Then, since

both a and (1-a) are positive,  $(z_i-z_j)$  will also have this same sign. Therefore, Equation (3.8a) can be rewritten as

$$|z_{i}-z_{j}| = a|x_{i}-x_{j}| + (1-a)|y_{i}-y_{j}|$$
, (3.8b)

i.e., all the pairwise satellite separations vary linearly when a scenario is varied along a linear trajectory.

#### Theorem 1

The global maximum of the objective function is on the line of all-satellite collocation.

#### Proof

A linear trajectory that starts with all-satellite collocation is illustrated in Figure 3.9, note that the ordering of the satellites remains the same. Since the initial pairwise spacings are all zero, from Lemma 2 all the satellite spacings increase linearly in the trajectory. As discussed in Section III.C.2, all the single-entry C/I values increase quasi-monotonically when the corresponding pairwise satellite spacings increase linearly. As a result, all the aggregate C/I values, which involve the summation of all their contributing single-entry interference powers, must also increase quasi-monotonically in the process. Thus the objective-function value, which is the summation of the exponential of the negative of the aggregate C/I values, must decrease quasi-monotonically. Hence, the global maximum of the objective function is on the line of all-satellite collocation.



Figure 3.9. Linear expansion of orbital assignments.

#### Theorem 2

Local minima of the objective function occur at boundaries of the feasible region such that all of the pairwise most widely separated satellites are at opposite limits of their respective feasible arcs.

#### Proof

Let the satellites be numbered according to their orbital positions, so that  $x_1 < x_2 < \dots x_n$ . Let the lower limits of their feasible arcs be denoted  $e_i$  (i=1,2,...,n) and the upper limits  $\omega_i$  (i=1,2,...,n).

Assume  $x_1 \neq e_1$ , i.e., satellite 1 is not at the lower limit of its feasible arc. Then

$$z = a(e_1, x_2, x_3, \dots, x_n) + (1-a)x$$
,  $0 \le a \le 1$  (3.9)

defines a linear trajectory for which all the  $|z_1-z_j|$  (j=2,3,...,n) must increase continuously away from the other satellites. All other spacings remain unchanged on the trajectory. As discussed in Section III.C.2, this increases the single-entry C/I values involving satellite 1 quasi-monotonically while all other single-entry C/I values remain unchanged; therefore the objective-function value will decrease quasi-monotonically along the trajectory. Therefore it can not be a local minimum for the scenario x with  $x_1 \neq e_1$ . This proves the theorem.

#### (3) Topography of the worst single-entry C/I value

In the following section the topography of an auxiliary function A, defined as the the worst (smallest) single-entry C/I value, will be investigated. Although it is not the objective function Z, it is hoped that these two functions may have sufficient resemblance that some of the properties about Z can be extrapolated from A. First the function is defined as

$$A = Min [(C/I)_{i,kj}], \qquad (3.10)$$
  
ieK, keK, jeJ<sub>k</sub>

where the symbols mean

(C/I)<sub>i,kj</sub> : the single-entry C/I value at test point j of service area k and the single-entry interference power is from satellite i,

K : index set of satellites in a scenario.

The value of A for a given scenario is obtained as follows. First all the single-entry interference from any one satellite to all the test points of other satellite systems are calculated using Equation (2.6), and these values are denoted as  $I_{i,kj}$  when i is the interfering satellite and j is the test point in service area k. The carrier power at any test point is calculated using Equation (2.5), and is denoted  $C_{kj}$ when j is the test point in service area k. The value of  $(C/I)_{i,kj}$  is calculated by taking the ratio of  $C_{kj}$  and  $I_{i,kj}$ . The value of A is obtained from choosing the smallest of all the  $(C/I)_{i,kj}$  terms for that scenario (note that a scenario is a point in the configuration space).

Note that, if this function is used as the objective function for the extended-gradient or cyclic-coordinate search method, then the most favorable assignment is that for which the objective function is the global maximum.

Considering only the orbital variables, we wish to show that this function has at most one local maximum (hence a global maximum when it exists) for each ordering (permutation) of the satellites, and that such a maximum must lie on a boundary of the feasible region. Some lemmas and definitions will be useful in the proof of this theorem.

#### Lemma 3

Within a region of fixed permutation in the feasible region, all the  $(C/I)_{i,jk}$  terms are quasi-monotonic functions along any linear trajectory (orbital variables only).

#### Proof

As discussed in Section III.C.2, for a service-area pair, the single-entry C/I values at all the test points vary quasi-monotonically as the satellite spacing varies. According to Lemma 2 all the pairwise satellite spacings either increase or decrease linearly, or remain constant along a linear trajectory within a region of fixed permutation. Therefore all the single-entry  $(C/I)_{i,kj}$  functions along that trajectory vary quasi-monotonically.

#### Definition 2

For two curves that have a countable number of common points, a vertex of the two curves is a common point of the two curves.

Let a function Y(x) be defined from a set of quasi-monotonic functions  $Y_i(x)$ , is I in a finite range as

$$Y(x) = Min [Y_i(x)].$$
 (3.11)  
i \varepsilon I

#### Lemma 4

If the local maximum of Y(x) exists, it must occur at a vertex or at the boundary of the allowed range.

#### Proof

Assume that  $Y(x_0)$  is a local maximum (minimum) of Y(x), and it is not a vertex of  $Y_1(x)$ , isI, nor is it at the boundary. Then Y(x) is equal to one of the  $Y_1(x)$  in the vicinity of  $x_0$ ; hence Y(x) is monotonic in the vicinity of  $x_0$ . Being a local maximum (minimum) means that  $Y(x) \langle Y(x_0) (Y(x) \rangle Y(x_0))$  for x in the vicinity of  $x_0$ , which contradicts the fact that Y(x) is monotonic in the vicinity of  $x_0$ . Hence the local maxima (minima) of Y(x) occur at the vertices or at the boundary.

#### Lemma 5

Y(x) can not have more than one local maximum.

#### Proof

Suppose that, as shown in Figure 3.10, the function Y(x) has two separated local maxima at  $x_1$  and  $x_3$ , then there must exist a local minimum at some point  $x_2$  between  $x_1$  and  $x_3$ . By lemma 4, this local minimum must be at the vertex of two  $Y_1(x)$ , say  $Y_1(x)$  and  $Y_2(x)$ . The point  $x_2$  being a local minimum of Y(x) requires, in the vicinity of  $x_2$ ,



Figure 3.10. Hypothetical case where two maxima occur in a linear trajectory. (Proved impossible by contradiction)

$$Y(x) > Y(x_2) \quad \text{for } x > x_2 \quad \text{and } x < x_2 \quad (3.12)$$

Let  $Y_1(x)$  be the function which coincides with Y(x) for  $x < x_2$  (i.e., the curve  $l_1$ ) and  $Y_2(x)$  the function which coincides with Y(x) for  $x > x_2$  (i.e., the curve  $l_2$ ) in the vicinity of  $x_2$ , then one has

$$Y_1(x) > Y(x_2)$$
 for  $x < x_2$ . (3.13)

 $Y_1(x)$  being quasi-monotonic means that, from Equation (3.13),

$$Y_1(x) < Y(x_2)$$
 for  $x > x_2$  (3.14)

in the vicinity of  $x_2$ . The same reasoning that led to these two equations, when applied to  $Y_2(x)$ , gives in the vicinity of  $x_2$ ,

 $Y_2(x) > Y(x_2)$  for  $x > x_2$ , (3.15)

$$Y_2(x) < Y(x_2)$$
 for  $x < x_2$ . (3.16)

Remembering that Y(x) coincides with  $Y_2(x)$  (by definition of  $Y_2(x)$  above) for x>x<sub>2</sub>, Equation (3.15) can be rewritten

 $Y(x) > Y(x_2) \qquad \text{for } x > x_2 , \qquad (3.17)$ 

and together with Equation (3.14) this gives

$$Y_1(x) < Y(x) \qquad \text{for } x > x_2 \qquad (3.18)$$

in the vicinity of  $x_2$ . This contradicts the definition of Y(x) in Equation (3.11). Thus Y(x) can have at most one local maximum.

#### Theorem 3

Along any linear trajectory within a region of fixed permutation in the feasible region, the auxiliary function A has at most one local maximum (orbital variables only).

#### Proof

The discussion here is confined to a linear trajectory within a region of fixed permutation. From Lemma 3, all the single-entry C/I terms are quasi-monotonic functions on such a trajectory. The function A is defined as the minimum of all these C/I terms; thus the function A may be identified with Y(x) in Lemma 5 if the trajectory parameter a is identified with x in that lemma. Therefore, from Lemma 5, the function A has at most one local maximum (hence a global maximum when it exists) along a linear trajectory.

#### Theorem 4

The auxiliary function A has at most one local maximum within a region of fixed permutation in the configuration space (orbital variables only).

#### Proof

The discussion here is still confined to a region of fixed permutation. It will be shown that Theorem 3 is contradicted if the function A has two local maxima within such a region. Suppose that the function A has two local maxima at  $x_1$  and  $x_2$ , then the linear trajectory that passes through both  $x_1$  and  $x_2$  will have two local maxima at  $x_1$  and  $x_2$ ; however, this is a clear contradiction of Theorem 3. Hence within

this region the function A has at most one local maximum; hence any maximum must be global in the region. Because the C/I variations are only quasi-monotonic, there may be sub-regions in which the value of A is constant; if this value is not exceeded elsewhere in this region, A will not have a distinct maximum in this region.

#### Theorem 5

The local maxima of the auxiliary function A are located at the boundary of the feasible region in the configuration space (orbital variables only).

#### Proof

By the same argument as in Theorem 2, a scenario located in the interior of a feasible region cannot be a local maximum because it is always possible to find a scenario located at the boundary that has better or equal single-entry C/I values. Thus any maximum of A has to be at the boundary.

#### (4) Numerical test

As discussed in Section III.B.3, the objective function Z is formulated to emphasize the worst aggregate  $C/I_e$  terms by exponentiating the negative of the aggregate  $C/I_e$  value; thus it is reasonable to say that there is a direct relationship between the function Z and the negative of the worst aggregate  $C/I_e$  term, or several such terms if they are of approximately equal value. In view of Theorem 4, this suggests that the function Z is likely to have only one local minimum within a region of fixed permutation. Since a rigorous proof has eluded us, a

numerical example of a four-administration model was calculated to investigate this feature: the four administrations are Argentina, Bolivia, Paraguay, and Peru; the feasible orbital range is from 62 to 68 degrees west. The objective-function value was calculated from Equation (3.1), the values of C and I were calculated from Equations (2.5), (2.6), and (2.13a); the antenna reference patterns are from Figures 2.2 and 2.3; the ellipse data were calculated from [49]. Since it is known from Theorem 2 that the local minima must be located at the boundaries of the feasible region in the configuration space, the objective function values at all the 24 boundary planes of this numerical example were calculated; the equal-height contour plots are shown in Appendix C, where Argentina, Bolivia, Paraguay and Peru are denoted as ARG, BOL, PRG, and PRU respectively. In each figure, two satellites are located at opposite ends of the feasible arc, and the (varying) orbital locations of the other two are indicated by the coordinates. The upper triangle represents one permutation and the lower triangle another permutation. Clearly there is only one local minimum for each permutation. The results suggests that for a general case (n satellites) it is likely that there is only one local minimum within a region of fixed orbital permutation.

#### D. DISCUSSION AND CONCLUSION

Even though the objective function in Equation (3.1) is not the only one that might be formulated to solve the orbital/frequency assignment problem, it still should be representative of objective functions designed to maximize low C/I<sub>e</sub> ratios. Therefore many of the

mathematical features of the assignment problem can be inferred from this function.

Referring to Figures 3.4 and 3.5 and the discussions in Section III.C, the objective function of Equation (3.1) often has large values at points of either orbital or frequency assignment collocation, and the local minima can be characterized by the permutations of their orbital/frequency assignments. This feature indicates that there might be on the order of  $(n!)^2$  local optimum solutions for a n-satellite case of n orbital variables and n frequency variables; in reality the number of local optima is likely to be smaller because the collocation of two satellites may not result in bad C/I<sub>e</sub> ratios when the service areas or their frequencies are well separated. Still, one thing is clear: permutation of the orbital/frequency assignments is an important part of the problem. Therefore a technique for finding the globally optimal (or a near-optimal) scenario must be able to deal with both the C/I<sub>e</sub> requirement and the permutation of the orbital/frequency assignments.

Also, the discussion in Section III.C.3.c, which shows that the objective function is likely to have one local minimum within a given orbital permutation, suggests that in order for an extended gradient search method to obtain the globally optimal solution, it should terminate as an ordinary gradient search with the optimal permutation in orbital/frequency assignments.

#### CHAPTER IV

#### OPTIMAL ORBITAL ASSIGNMENTS BY MEANS OF THE △S CONCEPT

#### A. INTRODUCTION

In this chapter a direct correspondence between the single-entry  $C/I_e$  protection requirements and the necessary satellite spacings is exhibited. This relationship is used to formulate linear constraints to enforce single-entry  $C/I_e$  protection requirements between all pairs of satellites. Two new formulations are then developed under the assumption that frequency assignments are the same for all the service areas. One is a mixed integer linear program, solved by a branch-and-bound procedure; the other is a linear program with both linear and nonlinear side constraints, the simplex method with restricted basis entry can be used to find an approximate solution when this formulation is used. As a consequence, the cumbersome nonlinear  $C/I_e$  expression used for the synthesis formulation in Chapter III is avoided.

The 1977 World Administrative Radio Conference (WARC-77) suggested that for maximum orbit utilization, space stations should be placed as close to each other as is consistent with keeping the mutual interference to acceptable levels [16]. This concept was explored by a Canadian study group by relating the single-entry C/I protection requirement to the satellite spacing [26,27,28]; they formulated a

orbital/frequency assignment program, for use at the 1983 Regional Administrative Radio Conference (RARC-83), based on the satellite spacing requirement. The concept of using this relationship in conjunction with linear optimization is original, to our best knowledge. The author is indebted to Professor Charles H. Reilly of the Department of Industrial and Systems Engineering for the mixed-integer and linear programming formulations and to Mr. David J. Gonsalvez for the actual programs.

The organization of the chapter is as follows. First the relationship between the single-entry C/I<sub>e</sub> protection requirement and pairwise satellite spacing will be formulated, and the relative importance of system parameters will be discussed. Next exact and approximate methods of calculating the required spacing will be presented. This will be followed by a heuristic discussion of the relationship between single-entry and total acceptable protection requirements, in order to establish single-entry requirements which are highly likely to lead to satisfaction of the total acceptable C/Ip protection requirement. Next the principle of the methods will be elucidated with a very simple hypothetical four-service area example to show how satellite ordering (permutation) enters into the linear optimization process. Finally the results of both the mixed integer program (MIP) and restricted-basis entry linear program (RBLP) formulations will be presented for a scenario of six South American administrations.

### B. RELATION BETWEEN SINGLE-ENTRY C/I<sub>e</sub> PROTECTION REQUIREMENT AND REQUIRED SATELLITE SPACING

The relationship between single-entry  $C/I_e$  requirement and the required satellite spacing will now be derived. The general configuration of two service areas A, B and the locations of their satellites  $S_A$ ,  $S_B$  is shown in Figure 4.1 which is identical to Figure 2.7. Refer to Section II.F for detailed description of all the parameters. It is assumed that frequency assignments are the same for both satellites. The received carrier power, C, in channel n (carrier frequency  $f_n$ ) at test point d is given in Equation (2.5) as

$$C = \frac{{}^{P}_{A} \cdot {}^{G}_{A} \cdot {}^{D}_{A} (\psi_{tc}) \cdot {}^{G}_{d} \cdot {}^{c}^{2}}{f_{n}^{2} \cdot (4\pi)^{2} \cdot x^{2}} ; \qquad (4.1)$$

the effective single-entry interference power,  $I_n^e$ , from  $S_B$  to channel n of test point d can be inferred from Equation (2.6) as

$$I_{n}^{e} = \sum_{m} \frac{P_{B} \cdot G_{B} \cdot D_{B} (\Psi_{ti}) \cdot G_{d} \cdot D_{d} (\Psi_{ri}) \cdot c^{2} \cdot F(f_{n}, f_{m})}{f_{m}^{2} \cdot (4\pi)^{2} \cdot y^{2}}$$
$$= \frac{P_{B} \cdot G_{B} \cdot D_{B} (\Psi_{ti}) \cdot G_{d} \cdot D_{d} (\Psi_{ri}) \cdot c^{2}}{(4\pi)^{2} \cdot y^{2}} \cdot \sum_{m} \frac{F(f_{n}, f_{m})}{f_{m}^{2}}, \qquad (4.2)$$

where the summation is over all frequency channels assigned to  $S_B$ . The term "single-entry" is defined as the aggregate of emissions from any



Figure 4.1. Configuration of received-power calculation.

one satellite entering any receiver in the wanted service within the channel to be protected [87]. The single-entry  $I_n^e$  values are different for different channels, and the worst one is in the channel at the center of the assigned band; it is denoted as  $I_e$ , and is used to evaluate the interference effect in this chapter.

The exact single-entry  $C/I_e$  ratio (in center channel n) at test point d is therefore

$$\frac{C}{I_{e}} = \frac{P_{A} \cdot G_{A}/x^{2}}{P_{B} \cdot G_{B}/y^{2}} \cdot \frac{D_{A}(\psi_{tc})}{D_{B}(\psi_{ti}) \cdot D_{d}(\psi_{ri})} \cdot \frac{1}{f_{n}^{2} \cdot [\sum_{m} (f_{n}, f_{m})/f_{m}^{2}]} .$$
(4.3)

Even though the only independent variables in Equation (4.3) are the satellite orbital locations, there are many hidden parameters and relationships. The minimum ellipse (its size, orientation, and aim point) for  $S_A$  is a function of satellite location. It is assumed in this chapter that the carrier power flux densities at the aim points are equal for all the satellite systems. For any ellipse size there is a corresponding  $G_A$  value, and the value of  $P_A$  must be adjusted to give the required power density at the aim point. As for  $D_A(\psi_{tc})$ , the value of  $\psi_{tc}$  depends on the satellite location, and there is also an implicit parameter  $\psi_{tco}$  which is a function of the ellipse (refer to Figure 2.1). The same considerations apply to satellite  $S_B$ , and  $G_B$ ,  $P_B$ ,  $D_B$ . Strictly speaking, the values of  $G_d$ , and thus  $D_d$ , are different for different channels because they are functions of carrier frequencies; in this chapter the values of  $G_d$  for all channels are assumed the same, which is reasonable for a narrow band frequency assignment.
The exact calculation of Equation (4.3) is complicated, it is therefore worthwhile to seek an approximation to Equation (4.3). Because the geostationary orbit radius is 6.6 times the Earth radius, the propagation distances x and y are approximately equal. Then, since the power densities at the respective aim points are assumed equal [65], it follows that

$$\frac{P_{A} \cdot G_{A}}{x^{2}} \approx \frac{P_{B} \cdot G_{B}}{y^{2}} \qquad (4.4)$$

When the service-area shape can be fitted reasonably with an ellipse, the test point d should be located on or near the -3 dB contour [46,47], giving

$$D_{A}(\psi_{tc}) \approx 1/2$$
 . (4.5)

Equation (4.3) can therefore be approximated as

$$\frac{C}{I_{e}} \approx \frac{1}{2 \cdot D_{B}(\psi_{ti}) \cdot D_{d}(\psi_{ri})} \cdot \frac{1}{f_{n}^{2} \cdot [\sum_{m} F(f_{n}, f_{m})/f_{m}^{2}]}$$
(4.6)

The factor  $1/\{f_n^2 \cdot [\Sigma F(f_n, f_m)/f_m^2]\}$  is a constant since it is assumed that the frequency assignments are the same for all satellites (note that  $f_n$  is at the center channel). An internationally agreed  $F(f_n, f_m)$  reference function exists only for the BSS, but not for the FSS which is the subject of the study in this chapter. However, it is known

that numerous U.S. FSS satellites have 24 transponders in the 6/4 GHz band occupying the whole 500 MHz bandwidth, each transponder channel is 36 MHz wide and the guard band between two channels is 4 MHz (crosspolarization discrimination allows frequency re-use in a satellite). In this chapter only the co-channel interference will be considered. Thus the value of  $1/{f_n^2 \cdot [\Sigma F(f_n, f_m)/f_m^2]}$  is taken to be one. Then Equation (4.6) can be approximated as

$$\frac{C}{I_{e}} \approx \frac{1}{2 \cdot D_{B}(\psi_{ti}) \cdot D_{d}(\psi_{ri})}$$
 (4.7)

The variation of the C/I<sub>e</sub> values with respect to the satellite orbital locations will now be discussed. Because the service areas are stationary and the satellite orbit radius is 6.6 times the earth radius, the value of  $\psi_{ti}$ , and hence the value of  $D_B(\psi_{ti})$ , changes little when the location of S<sub>B</sub>, the interfering satellite, is changed by a small arc length. When the service-area pair and system parameters are given, the term  $\psi_{ri}$ , and thus  $D_d(\psi_{ri})$ , becomes the only factor that can significantly affect the C/I<sub>e</sub> values; this is done by changing the satellite spacing to vary  $\psi_{ri}$ , and thus the  $D_d(\psi_{ri})$  value.

To have an acceptable single-entry  $C/I_e$  ratio, the main contributions are seen to come from the terms  $D_B(\Psi_{ti})$  and  $D_d(\Psi_{ri})$ . The term  $D_B(\Psi_{ti})$  comes from the separation between the two service areas; the further they are separated, the less the value  $D_B(\Psi_{ti})$ . The very fact that it comes from the geographic separation of the service areas makes it a valuable resource for the system planner. The term  $D_d(\Psi_{ri})$ comes from the satellite spacing; the larger the spacing, the larger the value  $\Psi_{ri}$ , and the smaller the value  $D_d(\Psi_{ri})$ . The most important feature about the satellite spacing is that this quantity can be controlled by the system planner.

For a given single-entry  $C/I_e$  protection requirement, the system planner should first look for the term  $D_B(\psi_{ti})$  for its contribution to the margin between C and  $I_e$ ; when this is not enough, he then has to look for the term  $D_d(\psi_{ri})$  to make up the difference. For satellite  $S_A$ located at 1 and  $S_B$  located to the east of  $S_A$ , the threshold satellite spacing that lets the resulting worst single-entry  $C/I_e$  value equal the protection requirement is the local required spacing for the satellite pair, and is designated as  $\Delta s_{A(1),B(1+)}$ ; here the sign + means east of 1. For  $S_B$  to the west of  $S_A$  it would be  $\Delta s_{A(1),B(1-)}$ . With any less spacing at least one of the test points would have an unacceptable single-entry  $C/I_e$  ratio, while with any more spacing all the singleentry  $C/I_e$  ratios would be better than the requirement. Thus, the  $\Delta s(1)$ function can be viewed as the reflection of the single-entry protection requirement, eg.,  $|S_A - S_B| > \Delta s_{AB}$  would guarantee satisfactory single-entry  $C/I_e$  ratios at all the test points in service areas A and B.

Since a satellite spacing requirement given by  $\Delta s(1)$  is equivalent to the equivalent single-entry protection requirement, it can be taken as a constraint on the relative locations of the corresponding satellites. So, instead of thinking about a scenario having satisfactory single-entry C/I<sub>e</sub> values, one may think about the scenario satisfying all the  $\Delta s(1)$  constraints. One important feature about the  $\Delta s(1)$  value is that, in producing the margin between C and I<sub>e</sub>, it fully utilizes the service-area separation to minimize the necessary satellite spacing. This approach corresponds directly to the idea proposed in WARC-77: for maximum orbit utilization satellites should be placed as close to each other as is consistent with keeping the mutual interference to acceptable levels [16]; hence the set of  $\Delta s(1)$  values is exactly what the system planner should use in order to achieve this qoal. Using the  $\Delta s(1)$  value in the orbit planning task has a great advantage in terms of numerical calculations. While the  $\ensuremath{\mathsf{C/I}_{e}}$  expression involves many geometric equations and is highly nonlinear with respect to the orbital variables, the  $\Delta s(1)$  set can be calculated once and for all for each service-area pair and then used as constraints. This greatly changes the aspect of the orbital assignment task, and the methods to solve it; this will be apparent in Section IV.F.

It is suggested in WARC-77 that single-entry protection requirement can be used as a guide for determining sharing criteria [87]; still the total interference from all sources must be calculated to evaluate the scenario definitively. In this chapter, satellite orbit planning methods are developed based on single-entry protection requirements; it

will be shown in Section IV.D that this is likely to lead to adequate aggregate protection when the single-entry  $C/I_e$  protection requirement is larger than the total acceptable protection requirement by 5 dB. First, one needs to turn one's attention to algorithms for calculating the  $\Delta$ s values just defined.

### C. CALCULATION OF $\triangle$ S VALUES

#### 1. Exact Method

An exact determination of the required satellite spacings requires solution of Equation (4.3) for  $\psi_{ri}$  for various locations of S<sub>A</sub>. An explicit solution has not been found; still, a numerical value can be obtained by evaluating the right side of Equation (4.3) (or equivalently Equations (4.1) and (4.2)) for increasing separations until the required C/I<sub>e</sub> value results. Specifically, the rigorous calculation of the threshold satellite spacing for two service areas A, B may be done by the following algorithm. (Refer to Figure 4.2 for the geometric relations.)

- (1) Set the location of satellite  $S_A$  at orbital location 1.
- (2) Move the location of satellite  $S_B$  incrementally from 1 toward the east. After each move, use the streamlined Spectrum/Orbit Utilization Program (SOUP) code in Appendix A to calculate the  $C/I_p$  values at all the test points of the two service areas.



Figure 4.2. Configuration of  $\Delta s(1)$  value calculation.

- (3) There exists a satellite spacing beyond which all the C/I  $_{\rm e}$  values exceed the single-entry protection requirement, and below which at least one C/I value is worse than the protection requirement. This is the satellite spacing for the two service areas at the prescribed locations and is denoted as  $\Delta s_{A(1),B(1+)}$ , where the sign + means east of 1.
- (4) Repeat procedures (1)-(3) for  $S_B$  west of  $S_A$ ; the resulting spacing is denoted as  $\Delta s_A(1), B(1-)$ , where the sign means west of 1.
- (5) Repeat (1)-(4) with a set of new locations for satellite  $S_A$  until its feasible arc has been covered.

The above calculation is rather time consuming. For each test position, the minimum ellipse data of the service area has to be generated.

### 2. Approximate Method

To ease the computational burden, an approximate method was adopted. This method is based on the assumption that the power densities at the ground receiver locations do not change when the location of either satellite is moved away from 1 by a small arc length. The procedure is:

(1) Collocate the two satellites at 1. Use the streamlined SOUP code in Appendix A to calculate all the ground receiver C/I<sub>e</sub> values.

- (2) Pick out the test point with the worst  $C/I_e$  value, calculate the margin between this  $C/I_e$  value and the single-entry protection requirement. At this point the service-area separation factor has been accounted for, so this margin should be made up by separating the two satellites from collocation to produce the receiving discrimination loss  $D_d(\psi_{ri})$  toward the interfering satellite.
- (3) Use the receiving antenne reference pattern in Figure 2.5 to calculate the necessary off-axis angle that provides this margin; this is the topocentric angular separation (viewed from the test point with the worst  $C/I_e$  value) the two satellites should have.
- (4) Spread the satellites symmetrically apart from 1 step by step until the separation gives this necessary topocentric angle at this test point. The final geocentric separation is the approximate  $\Delta s(1)$  value when  $S_A$  and  $S_B$  are in the vicinity of orbital location 1.

The computer code for this calculation is listed in Appendix D.

An example of the  $\Delta$ s(1) calculation is shown in Table 4.1 with the two administrations being Bolivia (BOL) and Paraguay (PRG). The satellite transmitting and ground receiving reference patterns are given in Figures 2.4 and 2.5. Initially the satellites are located at 90 degrees west. The interference calculation is carried out, and the test point with the worst C/I<sub>e</sub> value, -0.66 dB, is at 62.2 degrees west

### Table 4.1

				,		
COUNTRY		SATELLITE (LON.)		FREQUENCY	(MHz)	
BOL		-90.00		4050.02	r	
PR	G	-90.01	Ø	4 <i>0e0.e</i> 0	J .	
TEST	COUNTR	Y : BOL	SATELLITE	: -90.00		
	TEST Lon.	POINT LAT.	INT. SAT.	C/I (dB)	MARGIN	(dB)
	-65.ØØ	-12.20	PRG	28.86	-1.14	
	-65.5Ø	-9.8Ø	PRG	27.51	-2.49	
	-69.00	-11.20	PRG	27.78	-2.22	
	-60.00	-16.10	PRG	8.Ø2	-21.98	
	-57.5Ø	-18.00	PRG	2.58	-27.42	
	-67.5Ø	-22.7Ø	PRG	14.88	-15.12	
TEST	COUNTR	Y : PRG	SATELLITE	: -9Ø.ØØ		
1	TEST	POINT	INT. SAT.	C/I (dB)	MARGIN	(dB)
	-57.6Ø	-25.3Ø	BOL	7.75	-22.25	
	-58.6Ø	-27.3Ø	BOL	10.58	-19.42	
	-56.2Ø	-27.2Ø	BOL	14.54	-15.46	
	-54.7Ø	-25.5Ø	BOL	13.22	-16.78	
	-54.2Ø	-24.10	BOL	11.2Ø	-18.30	
	-58.1Ø	-20.20	BOL	1.15	-28.85	
	-59.1Ø	-19.30	BOL	<b>S.</b> 18	-29.92	
	-62.2Ø	-2ø.5ø	BOL	<b>-</b> Ø.66	-30.66	
	-52.7Ø	-22.20	BOL	-£.35	-30.25	
	-58.7Ø	-27.20	BOL	10.15	-19.85	

Example of  $\Delta s(1)$  Calculation Procedure

WORST MARGIN IS -3Ø.66 dB AT PRG ( -62.2Ø, -2Ø.5Ø) REQUIRED SATELLITE SPACING : 4.9Ø AT -9Ø.0Ø FOR C/I 3Ø.Ø dB

longitude, 20.5 degrees south latitude in Paraguay. The single-entry  $C/I_e$  protection requirement is chosen to be 30 dB, hence it requires 30.66 dB attenuation from the ground receiving discrimination to provide the necessary margin between C and I<sub>e</sub>. Then the receiving reference pattern is used to calculate the required off-axis angle, i.e., the topocentric angle, of the two satellites as seen from the test point with the worst C/Ie value. The satellite geocentric spacing is obtained from step (4) of the approximate method, the result is shown in Table 4.1 which shows that, in the vicinity of 90 degrees west, the necessary satellite spacing for these two service areas is four degrees. This spacing should result in at least 30 dB single-entry C/I<sub>e</sub> values at all test points, with the worst one at 30 dB. This result can not be guaranteed precisely, since the test point which was the worst for the original satellite locations may not be the worst for the new locations, and since new ellipses were not generated for the new satellite locations.

Using the same antenna parameters and 30 dB protection requirement, some of the  $\Delta s(1)$  values for several service-area pairs at different mean satellite locations are listed in Table 4.2. The calculation is made in 10- or 20-degree increments.

An example of the curve  $\Delta s(1)$  vs. mean satellite location 1 is shown in Figure 4.3, the two administrations are Paraguay and Uruguay. The  $\Delta s(1)$  value is fairly constant within a large range of satellite locations, and starts to increase when the satellite elevation angle is small.

# Table 4.2

# △s(1) Values of Six South American Administrations

country pair	longitude	ΔS	country pair	longitude	Δs
ARG BOL	-7 <i>9</i> -8 <i>9</i>	4. <i>88</i> 4. <i>8</i> 2	CHL PRG	-2Ø -3Ø	3.Ø5 2.45
	-90	4.05		-410	1.69
	-110	4.1C A 17		- 50	1.35
	-110			- 70	1.03
ARG CHL	-78	4.18		-89	1.14
	-80	4.05		-9ø	1.25
	-9ø	4.00		-1ØØ	1.46
	-100	<b>4</b> . <i>E</i> 2		-11Ø	2.00
	-110	4.19		-12Ø	3.32
ARG PRG	-78	4.24	CHL PRU	-79	3.84
	-88	4.28		-88 00	3.83
	-90	4.32	•	-90	3.07
	-118	4.32		-110	3.94
ARG PRU	-78	Ø.94	CHL URG	-20	2.52
	-88	1.04		-3Ø	1.44.
	-9ø	1.15		-4Ø	Ø.93
	-100	1.25		-50	Ø.8Ø
	-118	1.41		-617	Ø.43
	-70	4 19		- 7 10	0.42
AKG UKG	-70	A. 1A		-90	1.03
	-98	4.06		-100	1.28
	-188	4.06		-110	1.59
	-110	3.94		-12Ø	2.1Ø
BOL CHL	-78	4.13	PRG PRU	-2Ø	Ø.45
	-80	4.28		-4Ø	Ø.47
	-90	4.28		-619	9.48
	-100	4.39		-710	Ø.49 Ø.49
	-110	4.3/		-90 -90	Ø.5Ø
BOL PRG	-78	4.88		-120	Ø.85
	-80	3.99		-110	1.10
	-9ø	4.00		-12Ø	1.76
	-188	4.03		•	
	-118	4.84	PRG URG	-28	Z.35
	70			-410	2.20
BOL PKU	- / 10	3.8/ 2.95		لاه – 20 – 70	2.13
	- 90	3.99		- 80	2.19
	-100	4.10		-90	2.20
	-110	4.26		-188	2.34
				-11Ø	2.46
BOL URG	-28	Ø.43		-128	2.64
	-40	8.42			
	-60	19.419 17.20	PRU URG	-20	Ø.45
	- / 10	0.33 0 39		-410 -60	Ω.43 β ∡1
	- 00	Ø.38		- 7 Ø	9.49
	-199	Ø.84		-89	Ø.37
	-110	Ø.94		-98	8.37
	-120	1.Ø9		-100	Ø.33
				-110	8.32
				-12Ø	Ø.36

.



Figure 4.3. Typical  $\Delta s(1)$  value variation vs. mean satellite location.

Although the  $\Delta s(1)$  values are calculated up to two decimal fractions, in practical situations only the first decimal fraction is meaningful because the typical satellite station keeping inaccuracy is 0.1 degree [44]. The reason for keeping two decimal fractions is only to show their variations more precisely.

### 3. Validity of Approximate Method

The approximate method gives the correct result if the power densities at all the test points do not change when the satellites are moved by a small arc length. Strictly speaking, the power-density invariance assumption is not correct because the carrier power densities are designed to be constant only at the beam centers [65]. However, in practise, it is a highly acceptable assumption. To demonstrate this point more clearly, Equation (4.3) is written as

$$C/I_{e} = K(I_{A}, I_{B})/D_{d}(\psi_{ri})$$
, (4.8)

where

$$K(1_{A},1_{B}) = \frac{P_{A} \cdot G_{A}/x^{2}}{P_{B} \cdot G_{B}/y^{2}} \cdot \frac{D_{A}(\psi_{tc})}{D_{B}(\psi_{ti})} \cdot \frac{1}{f_{n}^{2} \cdot [\Sigma F(f_{n},f_{m})/f_{m}^{2}]}, \quad (4.9)$$

and  $1_A$  and  $1_B$  denote the orbital locations of  $S_A$  and  $S_B$ . The approximate method consists of calculating K for collocation, i.e., K(1,1), then assuming that this value remains constant as satellite locations are shifted a few degrees from 1. The discussion in Section IV.B (specifically, the paragraphs covering Equations (4.4) to (4.7) and the one immediately following Equation (4.7)) does indicate that this is a very good approximation.

Some examples support these arguments and show that the  $C/I_e$  values at the ground receivers do not change by more than 1 dB when the satellites are moved by two degrees; an example will now be given to demonstrate this point. In this example the Bolivia and Paraguay satellites are located at 92 and 88 degrees west, respectively, a four-degree separation as suggested from the result in Table 4.1. The  $C/I_e$  results from the streamlined SOUP calculation are given in Table 4.3. Note that the worst  $C/I_e$  value is very close to the 30 dB single-entry protection requirement, which indicates that the  $\Delta s(1)$ value of the approximate method is very close to that of the exact method.

### Relation Between Service-Area Adjacency and ∆s(1) Value

For any adjacent service-area pairs the  $\Delta s(1)$  values for a given protection requirement are approximately independent of the sizes and shapes of the service areas. This can be seen best from Equation (4.7); for adjacent service areas A and B, the test point d in service area A with the worst C/I<sub>e</sub> is on or near the common border with B, and its  $D_B(\Psi_{ti})$  will be approximately 1/2 (-3dB). This determines the required  $D_d(\Psi_{ri})$ , and  $\Psi_{ri}$ , and hence  $\Delta s(1)$ . As another way of looking at it, the carrier and interference power densities along the common border are nearly equal because they are designed to be approximately 3 dB below the respective beam-center power densities, which are designed to be

# Table 4.3

 $\ensuremath{\mathsf{C/I}_{e}}$  Results to Show Validity of Approximate Method

.

COUNTRY		SATELLI	TE (LON.)	FREQUENCY		
BOL		-92	.øø	4000.0	Ø	
PRG		-88	.øø	4000.0	Ø	
TEST	COUNTR	Y : BOL	SATELLITE	: -92.00		
	TEST Lon.	POINT LAT.	INT. SAT.	C/I (dB)	MARGIN	(dB)
-	65.ØØ	-12.20	PRG	59.67	29.67	
-	65.5Ø	-9.8Ø	PRG	58.32	28.32	
. –	69.ØØ	-11.20	PRG	58.71	28.71	
-	60.ØØ	-16.1Ø	PRG	38.82	8.82	
-	·57.5Ø	-18.ØØ	PRG	33.23	3.23	
-	•67.5Ø	-22.7Ø	PRG	46.Ø3	16.Ø3	
TEST	COUNTR	RY : PRG	SATELLITE	: -88.00		
	TEST LON.	POINT LAT.	INT. SAT.	C/I (dB)	MARGIN	(dB)
-	-57.6Ø	-25.30	BOL	38.33	8.33	
-	-58.6Ø	-27.3Ø	BOL	41.27	11.27	
-	-56.2Ø	-27.20	BOL	44.88	14.88	
-	-54.7Ø	-25.50	BOL	43.33	13.33	
-	-54.2Ø	-24.10	BOL	41.26	11.26	
-	-58.1Ø	-20.20	BOL	31.79	1.79	
-	-59.1Ø	-19.30	BOL	3Ø.75	Ø.75	
-	-62.2Ø	-20.50	EOL	3Ø.£6	ø.ø6	
-	-62.7Ø	-22.20	BOL	3Ø.39	Ø.39	
	-58.7Ø	-27.20	BOL	4Ø.86	10.86	

equal. Therefore, the required margin between C and  $I_e$  is provided only by the satellite spacing. Since this is true for all adjacent servicearea pairs, the required satellite spacings are nearly the same. For the receiving reference pattern in Figure 2.5 and a 30 dB single-entry  $C/I_e$  protection requirement, these  $\Delta s(1)$  values are approximately four degrees, as can be seen from several cases in Table 4.2.

The  $\Delta s(1)$  values for two non-adjacent service areas are likely to be smaller, and depend on their shapes, sizes and the separation between them. This is evident from Equation (4.7) since  $D_B(\psi_{ti})$  is likely to be smaller numerically (also in dB) in this case compared to the adjacent case. Heuristically, because of the service-area separation, the interference power densities in these two service areas are likely to have a deeper transmitting antenna discrimination loss relative to the carrier power densities. Therefore, the system needs less receiving antenna discrimination loss,  $D_d(\psi_{ri})$ , to achieve the required C/I<sub>e</sub> ratio. This means that less satellite spacing, or a smaller  $\Delta s(1)$ value, is needed. This is shown in several cases in Table 4.2.

### D. RELATION BETWEEN SINGLE-ENTRY AND TOTAL ACCEPTABLE C/I<sub>e</sub> protection Requirements

In satellite communications, a scenario is evaluated by computing an equivalent margin (see Equations (2.8) and (2.9)), which takes into account all the interference, at all the test points. In Chapter II this was shown to be equivalent to comparing the aggregate  $C/I_e$  values with the total acceptable protection requirement. It is therefore

essential that an assignment algorithm is based ultimately on the total acceptable protection requirement. However, it was also suggested in WARC-77 that the single-entry protection requirement can be used as a guide for determining sharing criteria; of course the total interference from all sources still must be calculated to evaluate the scenario fully [87]. The extended-gradient and cyclic-coordinate search methods discussed in Chapter III are based on the aggregate C/I<sub>e</sub> values. In contrast, the methods in this chapter, using the  $\Delta$ S concept, are based on single-entry C/I<sub>e</sub> protection requirements. Clearly such an approach will be acceptable only if there exists some relationship between the single-entry and aggregate C/I<sub>e</sub> values.

Although so far no such relationship has been established rigorously, it is generally felt that the single-entry C/I<sub>e</sub> protection requirement does not need to exceed the total acceptable requirement by more than a few decibels. In order to ensure that a scenario made on the basis of single-entry C/I<sub>e</sub> protection requirement would result in acceptable aggregate C/I<sub>e</sub> values, WARC-77 suggested that the single-entry C/I<sub>e</sub> protection requirement be higher by 5 dB than the total acceptable protection requirement [78]. Note that numerically 5 dB is equal to 3, this suggestion is therefore based on the assumption that at the test point which has the worst aggregate C/I<sub>e</sub> value the aggregate interference will not exceed three times the strongest single-entry interference. This assumption is supported by the characteristics of the satellite transmitting and ground receiving antenna reference patterns. Referring to Figures 2.4, 2.5 and Equation

(2.6), because these two reference patterns are highly directional, among all the received single-entry interference powers only the few that come from the main or near side-lobe of the transmitting reference patterns and are received in the main or near side-lobe of the receiving reference pattern are relatively strong; the others are generally weak enough to be negligible. However, it is difficult to prove rigorously that 5 dB extra protection requirement is absolutely enough to cover the difference between the single-entry and aggregate  $C/I_e$  values; hence the aggregate  $C/I_e$  results must be calculated to evaluate the feasibility of a scenario.

In the numerical examples in this chapter, 5 dB extra protection was used for all service areas. In any case, the methods to be described below do not depend on the validity of 5 dB, or any universal number. If the final analysis by the streamlined SOUP program shows more than 5 dB extra protection is needed for some service areas, then a more appropriate value may be chosen to compute the  $\Delta s(1)$  values for an improved synthesis.

### E. PERMUTATIONAL ASPECT OF THE ORBITAL-ASSIGNMENT PROBLEM

With a data base of  $\Delta s(1)$  values for all the service area pairs, conceptually the planning problem could be solved by choosing a proper ordering or permutation of the satellites and completing the scenario by locating every satellite in its feasible orbital range while making

sure that the  $\Delta s(1)$  constraints are satisfied. As an example, consider a four-service area case with the geographic relation as shown in Figure 4.4 with the objective of finding a scenario that uses the least orbit resource. The satellites are denoted as  $S_{\mbox{A}},\ S_{\mbox{B}},\ S_{\mbox{C}}$  and  $S_{\mbox{D}}.$  Assume that the values of  $\Delta s_{BC}(1)$  and  $\Delta s_{BD}(1)$ , the required satellite spacings for the non-adjacent service areas, are constant and are two degrees; similarly assume that the  $\Delta s(1)$  for all the adjacent service areas are constant and are four degrees. A scenario that meets this objective would be the ordering  ${\rm S}_D {\rm -S}_B {\rm -S}_C {\rm -S}_A$  with minimum required satellite spacing because it requires only eight degrees of orbital arc. Arrangements that do not include both the  $S_B-S_C$  and  $S_B-S_D$  satellite adjacencies would have to require at least a ten-degree arc. In this example, with the objective of conserving orbit resource, the basic concept is to have adjacent satellites serve non-adjacent service areas; here it utilizes the service-area separation to reduce the need for satellite spacing, and achieves the maximum orbit utilization suggested in reference [16].



Figure 4.4. Geographic location of four service areas.

In such a brute-force procedure, it is likely that a feasible solution can not be found for a particular ordering. It could be that the available orbital arc for the task is used up before the allocation of all the satellites has been completed. Then, another ordering has to be tried.

Note that there are m! possible permutations for m satellites. This number becomes astronomical when m is large. If the goal is to find a scenario which is optimal by some criterion, theoretically all the m! permutations have to be tested. Even if each test is simple and fast, the overall workload is still enormous.

### F. ORBITAL ASSIGNMENT OPTIMIZATION FORMULATIONS

### **1.** $\Delta s(1)$ Constraint and Objective Function

The orbital assignment problem can now be formulated as the optimization of a yet unspecified objective function, subject to the  $\Delta s(1)$  constraints on pairwise satellite spacings. The protection requirements will be satisfied because of the constraints. Also, it is highly desirable if the  $\Delta s(1)$  values are linear functions of the orbital variables so that a simple optimization technique, e.g., linear programming, can be used. This is apparently not true from Table 4.2 and Figure 4.3. Still, the  $\Delta s(1)$  values can be approximated by piecewise linear functions, or the maximum value of  $\Delta s(1)$  within a given orbital range, denoted as  $\Delta S$ , can be used as a constant parameter in the optimization formulation. The objective function is in principle entirely arbitrary, but we shall restrict it to a linear function of the

orbital locations since the whole purpose of this approach was to avoid the computational complexity of nonlinear optimization.

The objective function used in the numerical examples below is the sum of the absolute deviations of the assigned satellite positions from an arbitrary prescribed set of such positions, an "ideal" set. Such an "ideal" set might arise from requests of the user administrations. Alternatively, it may be specified as a tool for the synthesis, e.g., if the westernmost end of the available orbital arc is selected as the "ideal" location for all satellites, the resulting scenario is likely to allow the insertion of additional satellites at the eastern end at a later time with a minimum of readjustment.

Other objective functions which have been proposed for minimization are the length of the occupied orbital arc and the constant zero. The latter simply seeks to find a solution which satisfies the  $\Delta$ s(l) constraints.

### 2. Mixed-Integer and Restricted-Basis Linear Programming Formulations

With the single-entry C/I<sub>e</sub> protection requirement enforced by the  $\Delta s(1)$  constraints and a linear objective function, the problem can be formulated as a mixed integer program (MIP) [88]. Either the piecewise linear  $\Delta s$  functions or the constant  $\Delta S$  parameters might be used to formulate this program; in this chapter the constant  $\Delta S$  parameters will be used. The set of satellite locations which satisfy the  $\Delta S$  constraints and the feasible orbital range constraints constitutes the

feasible region. When the problem is solved via the branch-and-bound algorithm, the globally optimal solution is guaranteed [88]. However, the computational effort required to find this solution can be prohibitively long when the problem size, i.e., the number of satellites, is large.

To ease the burden on computational effort, the same problem can be formulated as a linear program (LP) with a set of nonlinear side constraints; only the constant  $\Delta S$  parameters can be used to formulate this program. A linear program is much more readily solvable than a nonlinear program or an integer program, and is most often solved by the simplex method [81]. However, in this problem, the nonlinear side constraints prevent one from using the simplex method in its most common form. The method can be modified to handle these nonlinear side constraints through the use of restricted basis entry. In doing so, one is certain to find a local, but not necessarily a global, optimum. The computational effort required by the LP technique should be acceptable when the problem size is large.

The MIP and the restricted-basis entry LP (RBLP) formulations are given in Appendix E as formulated by Professor Charles H. Reilly of the Department of Industrial and Systems Engineering for both of the non-trivial objective functions discussed above.

### G. NUMERICAL EXAMPLES

### 1. Definition of the Problem

In this example, a model of six administrations in South America, as shown in Figure 4.5, is used; they are Argentina (ARG), Bolivia 113





(BOL), Chile (CHL), Paraguay (PRG), Peru (PRU), and Uruguay (URG). The feasible orbital ranges for all the administrations are taken to be from 80 to 110 degrees west. It is assumed that all satellites have the same frequency assignments. The antenna reference patterns are from Figures 2.4 and 2.5. The optimization requirement is to minimize the sum of the deviations of the actually assigned positions from the satellite preferred locations. Three sets of satellite preferred locations are considered, as listed in Table 4.4: in case 1, all the preferred satellite locations are at the center of the feasible range; in case 2, all the preferred satellite locations are at the western boundary; in case 3, every administration has its preferred satellite from the administration center is close to zero.

First, all the  $\Delta s(1)$  values must be calculated. They were calculated using a 30 dB single-entry protection requirement; the results are listed in Table 4.2. The  $\Delta S$  values of the six-administration problem, obtained from Table 4.2 by choosing the maximum  $\Delta s(1)$  values over the feasible range 80 to 110 degrees, are listed in Table 4.5. They are denoted as  $\Delta S_{ij}$  for satellite i and j in Appendix E. Using the  $\Delta S$  parameters instead of the approximate piecewise linear  $\Delta s$  functions results in a conservative design (C/I<sub>e</sub> will tend to be larger), at the expense of possibly not using the orbit resource with maximum efficiency; but the alternative, i.e., using the  $\Delta s$  functions instead of the  $\Delta S$  parameters as constraints, would complicate the MIP formulations; note that the piecewise linear constraints can not be used in the RBLP formulation.

### Table 4.4

### Satellite preferred locations of six

### administrations

preferred	ARG	BOL	CHL	PRG	PRU	URG
case 1	95	95	95	95	95	95
case 2	110	110	110	110	110	110
case 3	87.5	92.5	97.5	87.5	102.5	82.5

Table 4.5

.

 $\Delta S$  parameters of six administrations

۵S	ARG	BOL	CHL	PRG	PRU	URG
ARG	*	4.17	4.19	4.32	1.41	4.14
BOL		*	4.57	4.04	4.26	0.94
CHL			*	2.00	3.94	1.59
PRG				*	1.10	2.46
PRU					*	0.37
URG						*

#### 2. MIP and RBLP Results

The solutions of the MIP and RBLP fomulations for this objective function, i.e., Formulations III and IV in Appendix E, are listed in Table 4.6 together with the values of the total deviations, the occupied orbital arcs and the computer run times in seconds. These data were provided by Professor C. Reilly and Mr. D. Gonsalvez of the Department of Industrial and Systems Engineering.

Because of the  $\Delta S$  constraints, the solution is guaranteed to satisfy the single-entry C/I<sub>e</sub> protection requirements; still the aggregate C/I<sub>e</sub> values need to be checked. By assuming that the term  $1/{f_n^2 \cdot [\Sigma_m[F(f_n, f_m)/f_m^2]}$  equals one in Equation (4.3), this becomes a co-channel interference calculation. The aggregate C/Ie results of the MIP solution of case 1 (which happens to be the most densely packed solution), calculated from the streamlined SOUP code in Appendix A, are listed in Appendix F. The results show that of the total 54 test points, only three places in Chile, three places in Paraguay and one place in Peru have aggregate C/Ie values between 27 to 30 dB while all the rest of the C/I<sub>e</sub> values are above 30 dB. Note that the  $\Delta$ S values (Table 4.5) were calculated from single-entry C/I<sub>e</sub> protection requirement of 30 dB, with the objective of guaranteeing that the aggregate C/I<sub>e</sub> values be no less than 25 dB (see the discussion in Section IV.D). Clearly this objective has been achieved; in fact, the aggregate C/Ie results are better than expected.

A likely reason for the aggregate  $C/I_e$  values to be better than expected is the following. First note that in this example every

# Table 4.6

# Mixed integer and linear program results

	case 1		case 2		case 3	
satellite	MIP	LP	MIP	LP	MIP	LP
ARG	88.68	105.74	101.35	110.00	88.76	101.26
BOL	99.57	101.57	97.18	104.33	92.93	92.50
CHL	95.00	97.00	105.54	99.76	97.50	97.07
PRG	93.00	95.00	107.54	97.76	84.44	87.50
PRU	91.06	93.06	109.63	108.59	102.50	102.67
URG	96.59	92.54	110.00	105.86	81.98	82.50
deviation	18.42	23.71	28.76	33.69	5.27	14.36
arc	10.89	13.20	12.82	12.24	20.52	20.17
cpu(sec)*	25.23	1.31	13.39	1.30	2.86	1.25

\* IBM-3081 computer

administration requires only one satellite. For a satellite and its corresponding service area, usually only the first adjacent satellites on both sides are close enough to produce significant interference, and these satellites do not usually influence the same test point; interference from far-away satellites are in general negligible because the actual satellite spacings are much larger than the required minimal spacings. This can be seen from the  $C/I_e$  results in Appendix F: among the seven test points with  $C/I_e$  less than 30 dB, only two receive two strong and almost equal signal, i.e., the two in Chile with  $C/I_e$  of 27.52 dB and 28.37 dB, and none receive more than two. Therefore the 5 dB margin between single-entry and total acceptable protection requirements is adequate for these sample problems; this confirms the argument made in Section IV.D.

### 3. Comparison Between MIP and RBLP Techniques

Referring to Table 4.6, note that the total deviations in the MIP solutions are smaller than those of the RBLP solutions. This is not unexpected since the MIP solution guarantees a global optimum with respect to the objective function while the RBLP formulation does not. On the other hand, the computer run times for the MIP formulation are significantly longer, and they are known to increase more rapidly with problem size than is the case with the RBLP formulation. As stated in Section IV.F.2, the computer run time could be prohibitively long for the MIP formulation when the problem size, i.e., the number of satellites, is large. Therefore, the RBLP formulation becomes more

attractive as a practical method of solving a real-world problem. The MIP formulation is useful primarily for evaluating the performance of the RBLP formulation on small problems.

### 4. Suggestions for Further Improvement

The C/I<sub>e</sub> ratios in Appendix F suggest that a uniform 5 dB margin between the single-entry and total acceptable C/I<sub>e</sub> protection requirements may result in over-protection. This raises the concern that, for a limited orbit resource and a large number of requests, a satisfactory scenario might never be found if the orbit resource barely allows every service area to have only the threshold aggregate C/I<sub>e</sub> value.

When a feasible solution of the MIP or RBLP formulation does not exist for a given set of  $\Delta S$  constraints, the reason could be either that the  $\Delta S$  constraints are too high, or that there exists no solution that could satisfy the total acceptable C/I<sub>e</sub> protection requirement. To find out which, a progressive testing process could be used by gradually decreasing the C/I<sub>e</sub> requirement level in the  $\Delta s(1)$  calculation, and using these values in the MIP or RBLP calculation. Note that as the single-entry C/I<sub>e</sub> requirement is gradually decreased, the first point at which a feasible solution (feasible in terms of the  $\Delta S$  requirements) exists may be such that the total acceptable C/I<sub>e</sub> requirement is not satisfied at some test points. However, this does not mean that a feasible solution (feasible in terms of total acceptable C/I<sub>e</sub> requirement) does not exist; this is because the margins between the

single-entry and total acceptable C/I<sub>e</sub> protection requirements may not have to be the same for all satellite pairs. When this is the case it is proposed that the gradient search method be used to fine-tune the solution and improve those unacceptable aggregate C/I<sub>e</sub> values; this approach is discussed below. If no solution is obtainable when the  $\Delta s(1)$  values are calculated using the total acceptable C/I<sub>e</sub> protection requirement and the  $\Delta S$  parameters are the minimum (over 1) of the  $\Delta s(1)$ values, a feasible scenario definitely does not exist.

To demonstrate how the gradient search method can fix the worst  $C/I_e$  terms, the resulting satellite locations of the MIP solution of case 1 are laid out as shown in Figure 4.6; here B is for satellite of Bolivia, U of Uruguay, C of Chile, P of Paraguay, E of Peru, and A of Argentina. Indicated in the figure are the actual spacings (above the arrows) and the  $\Delta S$  values (below the arrows) between a satellite and its first and second adjacent satellites. The star (\*) sign means that the actual spacing is larger than the corresponding  $\Delta S$  value. First note that there is no star sign for the Chile satellite, while other satellites have at least one star. This means that the spacings between the Chile satellite and its first and second adjacent satellites are all at their minimal required values. This may explain why the  $C/I_e$  results for Chile are worse than the others. Then note that this scenario may be modified by moving the Peru satellite to the right (eastward) and moving the Uruguay satellite to the left (westward) by a small amount. Although this modification increases the sum of the absolute deviations from the "ideal" locations, it also improves the  $\ensuremath{\mathsf{C/I}_{e}}$  results for Chile



 $(\star:$  Actual separation larger than required separation.)

Figure 4.6. Satellite locations from mixed integer program result.

by increasing the satellite spacings for the Chile satellite; note that the Peru and Uruguay satellites are its east and west adjacent satellites. This demonstrates that the gradient search technique can be used on the MIP or RBLP solution to improve the aggregate C/I<sub>e</sub> results.

### 5. Possible Extensions of the Method

The  $\Delta S$  concept has many flexibilities. It was demonstrated here for elliptical satellite antenna beams, but it can also be applied to shaped beams if the shaped beam reference pattern is given. At present, such a pattern is not available. Also, to use the  $\Delta s$  approach the antenna reference patterns and the C/I<sub>e</sub> protection requirement need not be the same for all administrations. Such non-uniformity merely changes the interference calculations, margin calculations, and the resulting  $\Delta s(1)$  values, but the same optimization procedures are still applicable.

The formulations may be useful when new satellites need to be added into an existing scenario in which the locations of existing satellites can not be changed. The computational burden of either technique depends greatly on the number of decision variables. For a task of adding more satellites, all the information about the existing scenario constitutes fixed parameters, and the only decision variables correspond to the new satellites. Therefore, the problem size is small, and the computational burden is reasonable.

This chapter has dealt only with the orbital assignment, not the frequency assignment. This is useful for the case that every satellite uses the full complement of the available spectral band. Still, the

same procedure should work if there is an a priori frequency assignment scenario; a considerable body of literature exists on such frequency assignments [19,20,21,22]. The only modification is to use the proper protection requirement value (by referring to the frequency assignments and protection ratio) in the  $\Delta$ s(1) calculation; the planning process will be exactly the same.

### H. CONCLUSION AND RECOMMENDATION

.

In this chapter, two techniques are presented to solve the orbital assignment problem. The MIP technique guarantees to find the globally optimal solution, but may require prohibitively long computing time when the problem size is large. Still it is very useful for testing other methods on small problems and may be applicable when a few satellites are added into an existing scenario. The RBLP technique guarantees to find a locally, but not necessarily a globally optimal solution, but is more practical in terms of the computational effort.

Two approximations are used in these methods. The first one appears in the  $\Delta s(1)$  calculation; however, it is shown to be acceptable. The second one is to use maximum  $\Delta s(1)$  values,  $\Delta S$ , in the MIP and RBLP formulations; this decreases the efficiency of orbit use, but probably not seriously.

It is recommended that these methods be tried on larger scenarios, and that the extensions given in Section IV.G.5 be investigated.

#### CHAPTER V

### A SERVICE-AREA SPECIFICATION PROCEDURE

#### A. INTRODUCTION

In the previous chapters the optimization of orbital and frequency assignments was considered for communications satellites serving a given set of service areas defined by political boundaries. Now, procedures for choosing such service areas will be discussed in the fixed-satellite service (FSS) context, with the objective of increasing the communications capacity for all users. The need to study ways in which the concept of service areas should be defined was brought up in CCIR report 453-3 [89], and the study in this chapter is intended to give insight to that concept. By means of an illustrative example it will be shown that the considerations of traffic-demand density and of minimum allowable spacing ( $\Delta$ S, see Chapter IV) can serve as a basis for designing service areas for this objective.

### **B. HISTORICAL PERSPECTIVE**

### 1. Service Area Assignment

In the broadcasting-satellite service (BSS) planning, a satellite service area is usually specified by the territories of an administration, a subdivision of an administration, or (in some cases) a

grouping of administrations [9,13]. Thus there appeared to be no need for a procedure for defining service areas for the WARC-77 and RARC-83 deliberations.

The situation is quite different with respect to FSS. The FSS satellites were initially used primarily for inter-administration communications. International consortia operated such satellites, with service areas chosen on the basis of demand (or market), technological considerations, and the composition of the consortium. The Intelsat satellites are examples of this type of operation. More recently, satellites have also been employed for intra-administration (Domsat) communications, e.g., satellite communications in U.S., Canada and the U.S.S.R. (if the latter is considered as a single entity; technically the International Telecommunication Union (ITU) regards each separate Soviet Republic as an administration) [90]. The simplest technology leads to large service areas; e.g., the whole contiguous continental U.S. (CONUS). While an experimental FSS satellite using regional and switched spot beams is at the heart of the NASA Advanced Communications Technology Satellite (ACTS) program [91], most civilian U.S. operational and planned systems are based on CONUS coverage. So in current approaches to the orbital and frequency assignments for the FSS, the idea of specifying service areas by the territories of the administrations seems to be still prevalent.
# 2. Insufficiency of Communications Supply from Limited Spectrum and Orbit Resources

As FSS planning proceeds, it has become clear that the communications demand is very large [92,93]. As an example, the U.S. fixed-service communications supply appears to be in great mismatch with the demand [80,94]. The projected U.S. domestic FSS communications demand in the year 2000, as estimated in a COMSAT Laboratory report, is shown in Table 5.1, and is also shown as a "pie chart" in Figure 5.1 [94]; the total communications demand is equivalent to 2,474 transponders.

By international agreement the total bandwidth of the 6/4 GHz spectral band assigned to the FSS is 480 MHz [94,95] (note that at present this is the only band in the planning stage). This band is divided into 12 slots, each consisting of a frequency channel 36 MHz wide followed by a guard band of 4 MHz. Therefore, including the cross-polarization channels, there are 24 frequency channels in this band [94,95]; this is shown in Figure 5.2. A typical U.S. FSS satellite has 24 transponders transmitting the signals in these 24 channels. Therefore the total estimated demand of 2,474 transponders implies a need for 103 satellites to fulfill the demand with the 6/4 GHz band.

Because of interference between satellite systems, satellites must be separated from each other to have proper protection [16,96,97]. For the antenna technology available up to the year 1982, satellites with CONUS beams for systems proposed at that time needed to be separated by more than three degrees [98]. However, the amount of communications capacity so provided in the 6/4 GHz band is far from enough to satisfy

#### U.S. Domestic FSS Communications Demand in the Year 2000

#### US Domestic TRAFFIC FORECAST SUMMARY - YEAR 2000

SERVICE	TRAFFIC	BW EFFICIENCY	TRANSPONDERS (36 MHz)
TRUNKING Voice Data Videoconf	6816 x 10 <sup>3</sup> Channe 3348 Mbits/ 7814 Channe	els 120 Channels/MII <sub>z</sub> 's 2.0 Mbits/MIIz els 1.1 Channels/MII <sub>z</sub>	1578 41 203
CPS <sup>*</sup> Voice Data Videoconf	35 x 10 <sup>3</sup> Channe 25038 Mbits/ 411 Channe	els 60 Channels/MHz 's 1.5 Mbits/MHz els 0.68 Channels/MHz	16 477 17
BROADCAST VIDEO Distribution DBS	233 Channe 50 Channe	ls 0.069 Channels/MII <sub>z</sub> ls 0.028 Channels/MII <sub>z</sub>	92 

\* CPS : Customer Premises Service



Figure 5.1. Projected U.S. Domestic FSS coommunications demand for the year 2000. CPS stands for Customer Premises Service. The number in parentheses indicates number of transponders.



Downlink Channelization CFD1

Figure 5.2. Allocation of frequency channels in 6/4 GHz band.

the FSS demand [99]. In order to increase the communications supply, the Federal Communication Commission (FCC) decided that the orbit resource should be more efficiently utilized and announced in the year 1984 that future antenna technology should allow two-degree spacing for U.S. FSS satellites, and satellite orbital planning should be based on two-degree spacing after the year 1987 (This also applies to the 14/12 GHz band) [80]. This will enable the U.S. to have about 25 geostationary satellites in the 6/4 GHz band. Clearly this still falls far short of the projected demand of 103 satellites!

Other spectral bands, e.g., the 14/12 GHz band, have been allocated to the FSS [31]. This should help increase the U.S. FSS communications supply. Still, it is apparent that the spectrum resource is limited, and that the orbit resource should be more efficiently utilized in order. to maximally re-use the spectrum resource.

# 3. Relation Between Frequency Re-Use and Service-Area Specification

The advantage of using narrow antenna beams to achieve frequency re-use has been recognized for some time [89,100]. Thus it was noted in CCIR report 453-3 that it is necessary to study ways in which the concept of coverage area should be defined [89]. Specifically, It was brought up in this report that under certain circumstances a satellite may transmit separate information on the same frequencies twice, or even a greater number of times, using antennas serving different parts of the world. This general idea has already found practical application with

the Intelsat series of satellites; while Intelsat IV satellites used global-coverage beams, Intelsat IV-A and V satellites employ hemispherically restricted beams to allow frequency re-use [101,102].

In view of the scarcity of the spectrum/orbit resources relative to demand, it becomes necessary to develop a method of specifying service areas such that the advantages of the narrow-beam concept can be fully utilized for efficient spectrum/orbit management.

# C. SERVICE-AREA SPECIFICATION BY △S CONCEPT AND COMMUNICATIONS-DEMAND DENSITY

#### 1. Role of **AS** Concept in Service-Area Specification

In order to provide more traffic supply, the  $\Delta S$  concept discussed in Chapter IV suggests that the  $\Delta S$  values between satellite pairs should be as small as possible so that more satellites can be allocated in the orbit. As discussed in detail in Section IV.C, the margin between the carrier power, C, and the single-entry interference, I, comes mainly from the transmitting and receiving antenna discrimination factors in the interference power; the former comes from the separation between the two service areas, the latter from the separation between the two satellites. Also, as discussed in Section IV.C, for a given single-entry C/I protection requirement, the larger the transmitting discrimination loss, the less the receiving discrimination loss and thus the less satellite separation is needed. For the special case when the transmitting discrimination loss is enough for the protection

requirement to be met, the satellites can be collocated, or equivalently a satellite can have two beams serving two service areas simultaneously; this is exactly what CCIR report 453-3 means by using the same frequency band twice at one satellite [89].

Referring to Figure 2.4, the transmitting discrimination value depends on two factors: the half-power beam width (HPBW) and the off-axis angle. The value of HPBW depends on the size of the service area: the smaller the service area, the smaller the value of HPBW, and the narrower the beam; this is the narrow-beam idea stated in references [89,100]. The off-axis angle depends on the service-area separation. The combination of these two factors should be the key to the subject of service-area definition. If the system planner can control these two factors to reduce the  $\Delta S$  values between satellite pairs, more satellites can be assigned in the orbit and larger communications supply can be provided. To achieve this purpose, basically the service areas should be specified as small as possible, and their separations should be as large as possible.

#### 2. Role of Communications-Demand in Service-Area Specification

The simple demand/supply concept implies that the supply should be where the demand is; hence the communications-demand density must also be consulted in specifying service areas. There is precedent for using communications traffic-demand density quantitatively in the technical design of satellite systems. In time-division multiple access (TDMA)

system design, a simple rule is: the areas with heavy communications demand should be given more access to the communications system [103]. Similarly, service areas should specify regions with enough traffic demand to justify having satellite access as an area. Hence information about the communications traffic-demand density is an essential prerequisite to a reasonable choice of service areas.

#### 3. General Consideration

Hence, the  $\Delta S$  concept and the communications traffic-demand density should both be considered when specifying service areas. It is apparent that small and separated service areas allow the geostationary orbit to be used more efficiently; on the other hand, potential demand increases with the service-area size: a satellite which serves one metropolitan area (e.g., Boston) has less potential demand than one which serves a corresponding region (e.g., the Eastern U.S.) or the entire administration or a grouping of administrations. There has to be a compromise between these two factors. The overall rule is that the selected service areas must have enough communications demand to justify their own satellite beams.

There are, of course, other factors which need to be taken into account in a practical plan. For example, multiple-beam satellites, which may also be beam-switching, require more advanced technology and are likely to be more expensive than single-beam ones. Such economic and perhaps other operational matters will not be considered here; only the communications capacity will be addressed.

# D. APPLICATION OF SERVICE-AREA SPECIFICATION CONCEPT TO A LARGE ADMINISTRATION OR GROUP OF ADMINISTRATIONS

#### 1. General Description

The idea of service-area specification by the  $\Delta$ S concept and traffic-demand density may greatly benefit an administration, or a group of administrations, that has a large territory, when most of the traffic demand is between several small regions. When this idea is applied to such a situation, it is proposed to serve such administration(s) with a mixture of administration-coverage beams and regional beams. The administration-coverage beams are intended to serve primarily areas of relatively low demand, while the majority of traffic demand from high-demand regions would be carried on the regional beams. The necessary separations between regional-beam satellites are usually smaller than those of the administration-coverage satellites. Thus if, instead of assigning the entire available orbital arc to administration-coverage satellites, a part is used to accommodate regional-beam satellites, then more satellites can be allocated in this arc and more communications supply can be provided.

Recall the scenario which has 25 CONUS beam satellites in the 6/4 GHz band with every satellite using the full spectral band (Section V.B.2). At first look it seems that this scheme uses the spectrum and orbit resources to their full extent for Earth station antenna technology which requires two-degree satellite spacing. However, if some of the service areas are changed from CONUS to smaller, separated

regions, the  $\Delta$ S values for their satellites will be smaller than two degrees, hence some orbit resource becomes available to allocate more satellites in the orbit.

# 2. Procedure of Service-Area Specification and Satellite Assignment

When regional service areas are to be specified, first the traffic-demand density should be considered. Because of the population distribution or the commercial activities, usually there will exist some regions of relatively small size and large traffic demand. Often such regions include several large cities relatively close to each other. Such regions are good candidates for regional service areas within the administration(s). In selecting these service areas, three things should be considered simultaneously: the areas should be of small size, they should have large traffic demand, and the separations between these service areas should be large.

After the regional service areas have been selected tentatively, the  $\Delta$ S values between these service area pairs should be calculated by the method described in Chapter IV. Note that service areas for which the  $\Delta$ S values are zero can be served by a single satellite; this is the multiple-beam design described in CCIR report 453-3. Different from the multiple-beam TDMA design, in this case the two beams can be active simultaneously [104]. Also note that multiple-beam satellites can carry both inter- and intra-regional communications.

A traffic-demand matrix can be formulated for these tentative service areas. The elements in this matrix are traffic demand between

the regions that can be carried by the regional-beam satellites: the diagonal elements are the intra-regional taffic demand, the off-diagonal elements are the inter-regional traffic demand. The latter are non-zero only when the corresponding service areas can be served by multiple-beam satellites. A complete demand matrix consists of the above-described matrix plus one additional element: the traffic demand which cannot be carried by regional satellites and must be carried by administration-coverage satellites.

Examination of the  $\Delta S$  and demand matrices may suggest a revision of the regional service areas. For example, if many of the  $\Delta S$  value for a particular region are large (e.g., approaching the  $\Delta S$  value for administration-coverage satellites), this may indicate the region is too large, or too close to other regions, or both. On the other hand if many of the demand matrix elements corresponding to a region are very small, this may indicate the region is too small, or it is not a good candidate to be a regional service area. Thus a good choice of regional service areas becomes a compromise between achieving satisfactory  $\Delta S$ values and a satisfactory demand matrix, as will be evident from the example below.

A scenario including both regional and administration-coverage beams may, in principle, be constructed by any suitable method, e.g., by extensions of the methods of Chapters III and IV. Here a scenario will be generated by deassigning a series of administration-coverage satellites and then allocating regional-beam satellites in this vacated orbital arc, consistent with the  $\Delta$ S requirement. The number of

administration-coverage satellites to be deassigned and the number of regional beams to be assigned are determined by consulting the traffic-demand matrix. This procedure has the advantage of being compatible with a network of uniformly spaced administration-coverage satellites; the new scenario might even evolve out of such a system. It also has the advantage of demonstrating the important concepts without the computational complexity of optimization.

#### 3. Traffic Distribution Between Narrow- and Wide-Beam Systems

The traffic-demand problem is completely solved when the amount of traffic-supply is enough, or more than enough, to meet the demand. However, as stated earlier, the demand usually far exceeds the supply, and usually the adoption of the regional-service area idea can only improve, but not completely solve the demand/supply problem. Therefore, an important task of the procedure is to make sure all the demands have their proper share of the supply.

It will be assumed that the satellites serving the regional service areas are dedicated satellites which are not designed to provide administration-wide service. Therefore some satellites need to be preserved to provide administration-wide communications service, even though the traffic demand which can not be served on a regional basis may be small. Many criteria could be used to decide the distribution of satellite beams. It is known that, compared to a scenario with only administration-coverage beams, there will be a larger communications supply when the narrow-beam idea is implemented. Therefore, one

criterion might be that all the demands have an equal percentage of supply-increase, another criterion might be that the total communications supply has the maximum amount of increase and no one suffers any supply decrease. The latter is used to develop the scenario in Section V.E.

#### E. NUMERICAL EXAMPLE

#### 1. Description of Parameters

Since the only available detailed traffic-demand density data available to the author is the projected long-distance telephone traffic among major cities in the U.S., it will be used in an example to numerically explore the advantage of the service area specification concept. Because only the 6/4 GHz band is in the planning stage, this example considers the communications capacity only for this band. Also, only the down-link communications traffic regulation problem will be considered; the up-link problem can be implemented similarly in the up-link spectral band.

Of the total projected FSS communications demand shown in Table 5.1, more than 63% consists of long-distance telephone voice traffic [94]. The telephone voice demand will be taken as indicative of total demand. This assumption is justified in part because only telephone voice data is available to us, in part because it seems likely that the geographical distribution of other communications will be similar to that of telephone voice traffic, and in part because the objective here

is only to demonstrate a method, not to design a system. More detailed examination shows that a large portion of the voice long-distance telephone demand comes from major cities (or metropolitan areas), and there are 28 cities that share more than 75% of the voice long distance telephone demand. The list of these 28 cities, and the projected long distance voice telephone demand between them are shown in Table 5.2 [94]. The U.S. map in Figure 5.3 shows the locations of these 28 cities with their communications rankings: the cities indicated by triple circles are in the top 5 rankings, double circles are for rankings from 6 to 10, single circles for rankings from 11 to 15, and solid dots for rankings from 15 and up.

In order to arrive at  $\Delta S$  values and C/I ratios consistent with the antenna pattens shown in Figures 2.4 and 2.5, the C/I results of two CONUS beam satellites with 2.5-degree spacing were calculated and are listed in Table 5.3, and the worst single-entry C/I value is 25 dB. This value will be used as the single-entry C/I protection requirement for the U.S.; the total acceptable C/I protection requirement will then be 20 dB if 5 dB extra protection is needed to compensate for multiple interference. It is not implied here that 2.5-degree spacing or a 20 dB aggregate protection ratio is recommended. The purpose here is only to arrive at a consistent set of parameters for demonstrating a regional-coverage assignment procedure.

Long Distance Voice Telephone Demand Between Top 28 Cities in U.S. in the Year 2000

US DOMESTIC VOICE TRAFFIC

#### TRAFFIC MATRIX EARTH STATION TO EARTH STATION

TOTAL TRAFFIC FOR US

IN 2000 IS 68146 CHAINELS.

.

ES. HAME	. 01	NEW_YORK 1	LOS_ANGL 2	CHICAGO 3	SAN_FRAN 4	BOSTON - 5	DETROIT 6	WASHINGT 7	CINCINNA 8	PHILADEL 9	CI.EVELND 10
L NEW YORK			928	837	654	643	593	593	582	544	517
	2	928	0	396	312	304	281	281	274	259	247
CUICACO	<b>i</b>	837	396	0	281	274	251	251	247	232	221
SAN FRAN		654	312	281	0	213	198	198	194	183	171
BOSTON	5	643	304	274	213	0	194	194	190	179	171
DETROIT	6	593	281	251	198	194	0	179	175	164	156
WASHINGT	7	593	281	251	198	194	179	9	175	164	156
CINCINNA	i al	582	274	247	194	190	175	. 175	G	160	152
PHILADEL	9	544	259	232	183	179	164	164	160	0	145
CLEVELND	10	517	247	221	171	171	156	156	152	145	9
DALLAS	11	434	205	183	145	141	129	129	126	118	114
ATTAHETM	12	384	183	164	129	126	114	114	114	107	99
ATLANTA	13	346	164	148	114	114	103	103	103	95	91
HOUSTON	14	312	148	133	103	103	95	95	91	84	80
SYRACUSE	15	289	137	122	95	95	87	87	84	80	76
MIAMI.	16	274	129	118	91	91	. 84	84	80	76	12
STLOUIS	17	262	126	110	87	87	80	80	76	72	68
RALEIGH	18	251	118	107	84	80	76	76	72	68	60
TALIPA	19	228	107	95	76	72	68	68	68	61	51
MINNEAPL	20	217	103	91	72	68	65	65	65	5/	57
SEATTLE	21	217	103	91	72	68	65	65	65	5/	57
KANSAS_C	22	194	91	84	65	61	57	57	5/	53	19
DEHVER	23	183	84	. 76	61	57	53	53	53	19	40
MILWAUKE	24	133	65	57	46	42	38	38	38	38	34
SAN_ANTO	25	<sup>1</sup> 122	57	53	42	38	38		54	34	30
PHOENIX	26	114	53	46	38	34	54	34	30	30	27
NEW_ORLE	27	114	53	46	38	34	34	31	UC 1	10	10
SALT_LAK	26	76	34	30	27	23	• 23	23	23		
IOTAL		10041	5242	4744	3789	3696	3434	3434	3358	3158	3008

# Table 5.2 (Continued)

US DOMESTIC VOICE TRAFFIC

.

.

#### TRAFFIC MATRIX EARTH STATION TO EARTH STATION

#### TOTAL TRAFFIC FOR US

.

۰.

IN 2000 IS 68146 CHANNELS.

.

ES. HAME	NO.	DÁLLAS 11	ANAHE IM 12	ATLANTA 13	HOUSTON 14	SYRACUSE 15	141 AMI 16	ST_LOUIS 17	RALEIGH 18	ТАМРА 19	ытијеарт 20
HEW YORK	 	434	384	346	312	289	274	262	251	228	217
LOS ANGL	2	205	183	164	148	137	129	126	118	107	103
CHIČAGO	i ji	183	164	148	133	122	118	× 110 g	107	95	91
SAH_FRAM	4	145	129	114	103	95	91	87	84	76	72
BOSTON	5	141	126	114	103	95	91	87	80	72	68
DETROLT	6	129	1,14	103	95	87	84	80	76	68	65
WASHINGT	7	129	114	103	95	87	84	80	76	68	65
CINCINNA	8	126	114	103	91	84	80	76	72	68	65
PHILADEL	9	. 118	167	95	84	80	76	72	68	61	57
CLEVELHD	10	114	99	91	80	76	72	68	65	61	5/
DALLAS	1 11	0	84	76	68	61	61	57	53	49	46
AHAHE IM	12	84	0	68	61	53	53	49	49	42	42
ATLAHTA	13	76	68	0	53	49	49	46	42	28	28
HOUSTON	14	68	61	53	0	46	42	42	38	34	31.
SYRACUSE	15	61	53	49	46	0	38		34	30	20
I MA I M	16	61	53	49	- 42	38	0		34	30	30
ST_LOUIS	17	57	49	46	42	-38	34	0		30	21
RALEIGH	18	53	49	42	38	34	34	54	0	27	
ТАМРА	19	49	42	38	34	30	30	30	2/	l 0	23
MINNEAPL	20	46	42	38	- 34	30	30	2/	2/	23	
SEATTLE	21	46	42	38	34	30	30	27	27	23	23
KANSAS_C	22	42	38	34	30	27	27	23	23	23	19
DEHVER	23	38	34	30	27	27	23	23	23	19	13
MILWAUKE	24	27	27	23	19	19	19	15	15	15	15
SAN_ANTO	25	27	23	19	19	15	15	15	15		
PHOENEX	26	23	19	19	15	15	15	15			
HEW_ORLE	27	23	19	19	15	15	15	15			
SALT_LAK	28	15	15	11	11	11	8	8	8	8	l U
	+	2520	2252	2033	1832	1690	1622	1546	1468	1328	1274

## Table 5.2 (Continued)

•

US DOMESTIC VOICE TRAFFIC

#### TRAFFIC MATRIX • EARTH STATION TO EARTH STATION

TOTAL TRAFFIC FOR US

-

.

IN 2000 IS 68146 CHANNELS.

.

			•	•	· · · · · · · · · · · · · · · · · · ·			§	
ES. NAME	110.	SEATTLE 21	KANSAS_C 22	DEHVER 23 ·	MILWAUKE 24	SAN_ANTO 25	PHOEH1X 26	NEW_ORI E 27	SALT_LAK 28
NEW YORK		217	194	183	133	122	114	114	76
LOS ANGI		103	91	84	65	57	53	53	34
CHICAGO	3	91	84	76	57	53	46	46	30
SAN FRAN	Ā	72	65	61	46	42	38	38	27
ROSTON	s s	68	61	57	42	38	34	341	23
DETROIT	6	65	57	53	38	38	34	34	23
WASHINGT	7	65	57	53	38	38	34	34	23
CINCINHA	8	65	57	53	38	. 34	30	30	23
PHILADEL	9	57	53	49	38	. 34	30	· 30	19
CLEVELND	10	57	49	46	34	30	27	27	19
DALLAS	11	46	42	38	27	27	23	23	15
ANAHE IM	12	42	38	34	27	23	19	19	15
ATLANTA	13	38	34	30	23	. 19	19	19	11
HOUSTON	[ 14]	34	30 -	27.	19	19	15	15	
SYRACUSE	15	30	27	27 -	19	15	15	15	
MIAMI	16	30	27	23	19	15	15	15	8
SI_LOUIS	17	27	23	23	15	15	15	15	8
RALEIGH	18	27	23	23	15	15	11	11	8
TAMPA	19	23	23	19	15	11			8
MINHEAPL	20	23	19	19	15	11			0
SEATTLE	21	0	19	19	15	11	11		
KANSAS_C	22	19	0	15			8	0	
DEHVER	23	19	15	0	11	11	8	0	
HILWAUKE	24	15	11	11	0	8	8	8	
SAN_ANTO	25	11		11	8	9	.4		
PHOENIX	26	11	8	8	8	1	0	•	
HEM_OULE	27	11	8	. 8	8	1	1	0	۹ ۵
SALT_LAK	28	8	8	4	4	4	•		
TOTAL		1274	1134	1054	788	709	641	641	436



Figure 5.3. Locations of top 28 cities in U.S. with largest long-distance telephone demand in the year 2000.

.

.

.

C/I Results of Two CONUS-beam satellites with

2.5-degree spacing

COUN	rry	SATELLITE	(LON.)	FREQUENCY (MHz)
USI	A	-100.00	I	4000.00
USZ	A	-102.50	1	4000.00
TEST	COUNTI	RY : USA	SATELLITE	: -100.00
	TEST LON.	POINT LAT.	INT. SAT.	C/I (dB)
•	-69.20	47.40	USA	-108.35
-	-66.90	44.80	USA	-108.29
-	-69.90	41.50	USA	-107.71
-	81.80	24.40	USA	-108.44
-	97.20	26.00	USA	-107.61
-1	17.10	32.30	USA	-108.47
-1	24.20	40.40	USA	-108.50
-1	.22.80	49.00	USA	-108.39
-	95.10	49.40	USA	-107.22
TEST	COUNTR	IY : USA	SATELLITE	: -102,50
	TEST LON.	POINT LAT.	INT. SAT.	C/I (dB)
-	69.20	47.40	USA	-108.35
-	66.90	44.80	USA	-108.30
-	69.90	41.50	USA	-107.72
-	81.80	24.40	USA	-108.41
-	97.20	26.00	USA	-107.60
-1	17.10	32.30	USA	-108.51
-1	24.20	40.40	USA	-108.54
-1	22.80	49.00	USA	-108.41
-	95.10	49.40	USA	-107.19

۰.

# 2. Specifying Four Service Areas According to △S Consideration and Traffic-Demand Density

Referring to Figure 5.3 about the communications traffic-demand density, four service areas that cover most of the top 28 cities may be specified as shown in Figure 5.4. The first service area, called the East region, covers the cities New York (1), Boston (5), Washington D.C. (7), Philadelphia (9), and Raleigh (18). The second service area, called North Central, covers Chicago (3), Detroit (6), Cincinnati (8) and Cleveland (10). The third service area, called West, covers Los Angeles (2), San Francisco (4) and Anaheim (12). The fourth service area, called South Central, covers Dallas (11), Houston (14), San Antonio (25) and New Orleans (27). These regional service areas were obtained by trial and error as reasonable compromises between the  $\Delta S$ matrix and demand matrix requirements. For example, the traffic demand for the North Central region could be increased by including Syracuse (15), St. Louis (17), Minneapolis (20), Kansas City (22), and Milwaukee (24); however, this would increase its size and reduce the separation between regions, thus it would increase  $\Delta S_{E,NC}$  and  $\Delta S_{NC,SC}$  sufficiently to prohibit sufficient frequency re-use. Even as it is,  $\Delta S_{E,NC}$  turns out too large to use multiple-beam design. Its size could be reduced by eliminating Chicago (3) and Detroit (6) from this region, but then the traffic-demand might be too low to justify having its own satellite beams. This illustrates the compromise between  $\Delta S$  and traffic demand which must be the basis in specifying regional service areas.



Figure 5.4. Four selected regions with proper service-area separation and large communications demand.

The  $\Delta$ S matrix of the four service areas is shown in Table 5.4: the  $\Delta$ S values between any two of the four service areas, except between East and North Central, are zero. To demonstrate that a multiple-beam scheme is feasible, the C/I ratio of a three-beam satellite serving East, West and South Central is shown in Table 5.5, and the C/I ratio of a three-beam satellite serving North Central, West and South Central is shown in Table 5.6; in both cases, the worst aggregate C/I values are larger than 25 dB. The  $\Delta$ S value between East and North Central is 1.24 degrees, as indicated in Table 5.7; however, for numerical convenience 1.25-degree spacing will be used for the East and North Central satellites.

With this  $\Delta S$  matrix, there can be two classes of regional-beam designs for satellites serving these four regions. In the first one the service areas East, West and South Central, or any combination of these, can use one multiple-beam satellite. In the second, the service areas North Central, West, and South Central, or any combination of them, can use one multiple-beam satellite. There are two overall restrictions: satellites serving the East and North Central regions respectively need to be separated by at least 1.25 degrees, and any two satellites that serve the same service area must be separated by no less than 2.5 degrees. Aside from these restrictions, a scenario can have any combination of the two regional-beam designs. For example, two adjacent satellites that serve the regions East and North Central, respectively, can also serve the service areas West and/or South Central.

## $\Delta S$ matrix of four regions

	ΔS	East	N. Central	West	S. Central
	East	2.50	1.25	0	0
N.	Central		2.50	0	0
	West			2.50	0
s.	Central				2.50

.

.

.

.

..

#### C/I Results of collocating satellites serving

# East, West and South Central regions

REGION EAS WES SCR	SATELLITE -100.00 -100.00 -100.00	(LON.)	FREQUENCY (MHz) 4888.88 4888.88 4888.88	
TEST REGIO	N : EAS	SATELLITE	: -100.00	
TEST	POINT	INT. SAT	. C/I (dB)	MARGIN (dB)
-74.Ø2	4Ø.72	WES	44.3Ø	8.93
-74.Ø2	4Ø.72	SCR	34.35	
-74.Ø2	4Ø.72	TOTAL	33.93	
-71.Ø7	42.35	WES	42.97	8.86
-71.Ø7	42.35	SCR	34.43	
-71.Ø7	42.35	TOTAL	33.86	
-77.Ø2	38.9Ø	WES	44.29	7.21
-77.Ø2	38.9Ø	SCR	32.49	
-77.Ø2	38.9Ø	Total	32.21	
-75.12	39.95	WES	44.54	8.54
-75.12	39.95	SCR	33.9Ø	
-75.12	39.95	TOTAL	33.54	
-78.65	35.78	WES	43.28	3.76
-78.65	35.78	SCR	28.91	
-78.65	35.78	Total	28.76	
TEST REGIO	N : WES	SATELLITE	: -188.88	
TEST   -118.25 -118.25 -118.25	POINT 34.Ø5 34.Ø5	INT. SAT EAS SCR	. C/I (dB) 44.13 32.33	MARGIN (dB)
-122 40	37 80	FAS	12.55	7.05
-122.4Ø	37.8Ø	SCR	33.6Ø	8.37
-122.4Ø	37.8Ø	TOTAL	33.37	
-117.95	33.85	EAS	43.97	6.75
-117.95	33.85	SCR	32.Ø2	
-117.95	33.85	Total	31.75	
TEST REGIO	N : SCR	SATELLITE	: -10C.00	
TEST -96.8ø -96.8ø -96.8ø -90.80	POINT 32.78 32.78 32.78 32.78	INT. SAT EAS WES TOTAL	. C/I (dB) 34.90 37.02 32.82	MARGIN (dB) 7.82
-98.52	29.47	EAS	35.71	7.45
-58.52	29.47	WES	35.22	
-98.52	29.47	Total	32.45	
-90.12	29.97	EAS	28.14	2.85
-90.12	29.97	WES	39.74	
-90.12	29.97	TOTAL	27.85	

.

.

C/I results of collocating satellites serving North Central, West and South Central regions

REGION WES NCR SCR	SATELLIT -100. -100. -100.	E (LON.) ØØ ØØ	FREQUENCY () 4000.00 4000.00 4000.00	1Hz )
TEST REGION :	WES	SATELLITE	: -1ØØ.ØØ	
TEST POI		INT. SAT.	C/I (dB)	MARGIN (dB)
-118.25	34.05 34.05	NCR SCR	43.46 32.33	
-118.25	34.Ø5	TOTAL	32.ØØ	7.ØØ
-122.4Ø -122.4Ø	37.8Ø 37.8Ø	NCR SCR	43.47 33.8Ø	
-122.4Ø	37.8Ø	TOTAL	33.36	8.36
-117.95 -117.95 -117.95	33.85 33.85 33.85	NCR SCR TOTAL	43.23 32.02 31 70	5 7 <i>0</i>
TEST REGION :	NCR	SATELLITE	: -100.00	5.72
TEST PC	DINT	INT. SAT.	C/I (dB)	MARGIN (dB)
-87.63 -87.63	41.88 41.88	WES SCR	42.72 3Ø.48	
-87.63	41.88	TOTAL	30.23	5.23
-81.68 -81.68 -81.68	41.50 41.50 41.50	SCR SCR TOTAL	43.22 31.8Ø 31.5Ø	6.5Ø
-83.05	42.33	WES	43.97	
-83.05	42.33	TOTAL	32.84	7.52
-84.52	39.1Ø 39.1Ø	WES SCR	43.73	
-84.52	39.1Ø	TOTAL	29.39	4.39
TEST REGION	SCR	SATELLITE	: -100.00	
TEST PC -96.8Ø	DINT 32.78	INT. SAT. WES	C/I (dB) 37.02	MARGIN (dB)
-95.8 <i>9</i> -96.8Ø	32.78 32.78	NCR TOTAL	31.Ø8 30.Ø9	5.09
-95.37	29.77	WES	38.67	
-95.37 -95.37	29.77 29.77	NCR TOTAL	34.Ø2 32.79	7.79
-98.52	29.47	WES	35.22	
-98.52	29.47	TOTAL	31.77	6.77
-9Ø.12	29.97	WES	39.74 29.50	
-90.12	29.97	TOTAL	29.11	A 11

.

 $\Delta s$  calculation for East and North Central regions

.

				•				•	
REGIO	DN	SAT	ELLITE	(LON.)	FREQUE	NCY	(MHz)		
NCR			-7Ø.ØØ	r	4 <i>ØØ</i>	S.00	,		
EST			-70.00	r	4 <i>0</i> e	0.09			
							•		
TEST	REGION	:	NCR	SATELLITE	: -7	ø.ø0	,		
	TEST LON.	POI	NT LAT.	INT. SAT	. C/I	(dB	)	MARGIN	(dB)
	-87.63		41.88	EST	28	.66		3.66	
-	-83.Ø5		42.33	EST	14	.71		-1Ø.29	
-	-84.52		39.1Ø	EST	17	. 1ø	•	-7.9Ø	
-	-81.68		41.5Ø	EST	8	.59		-16.41	
					,				
TEST	REGION	:	EST	SATELLITE	: -7	Ø.Ø2	f		
	TEST	POI	NT	INT. SAT	r. c/I	(dB	<b>)</b>	MARGIN	(dB)
•	-71.Ø7		42.35	NCR	29	.cø		4.00	
-	-75.12		39.95	NCR	22	2.11		-2.89	
-	-78.65		35.78	NCR	12	.64		-12.36	
	-74.Ø2		4Ø.72	NCR	29	).5Ø		4.5Ø	
	-74.Ø2		4Ø.72	NCR	29	5.5Ø		4.5Ø	

WORST MARGIN IS -16.41 dB AT NCR ( -81.68, 41.5%) REQUIRED SATELLITE SPACING : 1.24 AT -7Ø.00 FOR C/I 25.0 dB

The projected long-distance telephone demand matrix between the major cities in these four areas is given in Table 5.8(a). When traffic demand for a region or between regions is computed below, we shall simply add matrix elements from Table 5.2. For instance, internal demand for the West region would be the demand from L.A. to San Francisco (2)-(4), San Francisco to L.A. (4)-(2), L.A. to Anaheim (2)-(12), Anaheim to L.A. (12)-(2), San Francisco to Anaheim (4)-(12), Anaheim to San Francisco (12)-(4). For demand from the West region to the North Central region, one would add the matrix elements corresponding to transmission from each of (2),(4),(12) to each of (3), (6), (8), (10). To make these numbers more applicable to the satellite planning task, they are converted to a corresponding number of satellite beams in the following way. From Figure 5.2, there are 24 frequency channels in the 6/4 GHz spectral band, and each channel is 36 MHz wide. Assuming that a high quality telephone channel occupies 8 KHz bandwidth, one MHz bandwidth can carry 120 telephone channels, and hence a full spectral band can carry 103,680 telephone channels. The number of satellite beams is therefore obtained from the number of telephone channels by dividing by 103,680. Table 5.8(a) is re-stated as satellite beam requirements in Table 5.8(b).

A complete requirement matrix, R, for the U.S. is shown in beam units in Table 5.9. In this matrix, the inter- and intra-regional communications demand of the four regions that can use the two regional-beam designs are listed individually, the rest of the demand, i.e., 73.15 beams, that must go through the CONUS-beam satellites is listed in one category. Note that the inter-regional demand between

Telephone communications demand between major

cities in four regions

(a) In channel units

channels	East	N. Central	West	S. Central
East	558400	514000	400200	198700
Central	514000	240400	253300	124300
West	400200	253300	124800	97800
Central	198700	124300	97800	31200
	channels East Central West Central	channels East East 558400 Central 514000 West 400200 Central 198700	channels East N. Central   East 558400 514000   Central 514000 240400   West 400200 253300   Central 198700 124300	channelsEastN. CentralWestEast558400514000400200Central514000240400253300West400200253300124800Central19870012430097800

## (b) In beam units

	beams	East	N.	Central	West	s.	Central
	East	5.38		4.95	3.85		1.91
N.	Central	4.95		2.31	2.44		1.19
	West	3.85		2.44	1.20		0.94
s.	Central	1.91		1.19	0.94		0.30

Complete requ	irement	matrix
---------------	---------	--------

.

	beams	East	N. Central	West	S. Central	CONUS
	East	5.38	*	3.85	1.91	
N.	Central	*	2.31	2.44	1.19	73.15
	West	3.85	2.44	1.20	0.94	
s.	Central	1.91	1.19	0.94	0.30	

East and North Central is included in the CONUS beam category because it can not use any of the two regional-beam designs.

# 3. Improvement of traffic-supply matrix with service-area specification

A supply matrix is used to express the traffic-supply arrangement; each element in this matrix is the amount of traffic supply from one region to another offered from a scenario up to the maximum amount of demand from the corresponding regions.

If the communications demand is supported by 25 CONUS-beam satellites, the average percentage of satisfaction, s, is

s = 25/103

Assuming that each user in the continental U.S. has equal probability of accessing to all satellites, then each user will have the same percentage of satisfaction and the corresponding supply matrix in beam numbers is given by

$$S = S \cdot R , \qquad (5.1)$$

which is shown in Table 5.10. This represents the total supply expected from the all-CONUS system. While the origin and destination of traffic by regions East, N. Central, S. Central and West are not particularly meaningful with the all CONUS-beam design, the same partitioning as in Table 5.9 has been retained in Table 5.10; this will prove convenient when this scheme is compared to the multiple-beam designs to be discussed.

۰.

# Supply matrix without regional-beam

# satellites

	beams	East	N. Central	West	S.	Central	CONUS
	East	1.305	*	0.934		0.463	
N.	Central	*	0.560	0.592		0.289	17.753
	West	0.934	0.592	0.291		0.228	
s.	Central	0.463	0.289	0.228		0.073	

When implementing the two regional-beam designs, some of the 25 CONUS beam satellites must be preserved; the criterion here is to have the maximum total increase of traffic supply and no loss for any individual. The projected total demand is 103 beams. The requirement matrix that can use the two regional-beam designs, which is simply the regionally served part of Table 5.9, is shown in Table 5.11; the regional sub-total requirement is found to be 29.85 beams. Suppose there are m CONUS satellites being replaced by the regional-beam designs. If the taffic which can be carried only by the CONUS beams does not suffer any loss after implementing the regional-beam designs, the number m must satisfy the requirement

 $(25-m)/(103-29.85) \ge (25/103).$ 

The maximum value of m, denoted by M, is 7. Replacing M consecutive CONUS satellites with regional-beam satellites will lead to the maximum total increase of traffic supply. For a general case, the value of M is calculated from

$$M = IFIX[n_{(n/t)} \cdot (t_{-r})], \qquad (5.2)$$

where the symbols are

- IFIX : a function whose value is the largest integer equal to or less than the argument,
  - n : number of satellites in a scenario before implementing regional-beam designs,
  - t : total communications demand,
  - r : communications demand that is to be satisfied by the regional-beam designs.

Ta	b1	е	5.	11

Requirement	matri	( of	four	regions
-------------	-------	------	------	---------

	beams	East	N. Central	West	S. Central	sub-total
	East	5.38	*	3.85	1.91	11.14
N.	Central	*	2.31	2.44	1.19	5.94
	West	3.85	2.44	1.20	0.94	8.43
s.	Central	1.91	1.19	0.94	0.30	4.34
					total	29.85

Reference to the  $\Delta S$  matrix in Table 5.4 shows the orbital arc that accommodates seven CONUS-beam satellites can locate thirteen satellites with 1.25-degree spacing. Of these thirteen satellites, there could be maximally seven beams illuminating the region East since satellites serving the same service area must be separated by no less than 2.5 degrees. Then, because of the  $\Delta S$  restriction which does not allow collocation of East and North Central beams, there can be at most six beams illuminating North Central. (The reason that East has been allotted more beams than North Central is that it has more demand.) The maximum numbers of beams for West and South Central are both six. They can not be seven because the beam arrangement should allow inter-regional communications from East or North Central to West and South Central; the choice of seven West beams would result in beam-collocation of the East and West beams and no communications between West and North Central. (If these statements do not seem clear, the reader is encouraged to refer to Figure 5.5, which shows the sequence of the thirteen regional-beam satellites, and to experiment with other arrangements, keeping in mind both restrictions and regional-beam designs discussed in Section V.E.2.) With these beam assignments, the supply of regional beams to these four regions is listed in Table 5.12.

With these beams, the percentages of satisfaction for the four regions are listed in Table 5.13; the corresponding supply matrix, obtained by multiplying elements of each row with the respective percentage of satisfaction, is shown in Table 5.14(a). It is assumed

.

# Supply of regional beams to four regions

	region	beams		
	East	7		
N.	Central	6		
	West	6		
s.	Central	6		
	total	25		

. 4

٠

Percentage of satisfaction of demand by means of regional beams

region p. o. s. East 7/11.14 = 0.6283 N. Central 1 West 6/8.43 = 0.7117 S. Central 1

.

.
that the satellite traffic is likely to be symmetrical, hence this matrix needs to be symmetrized. The adjustment should be dominated by the first row because the demand from/to East is the largest and the rate of successful connection depends therefore most strongly on the availability of the channels to the East. The first step is to symmetrize the first column and row, and the matrix should become as shown in Table 5.14(b). Next, the adjustment should be dominated by the third row because the communications from/to West is the second largest. Note that since the value of its first element has been decreased in step one, the available communications supply to the other three elements will increase. The total demand represented by the last three elements in row three can be seen from Table 5.9 to be 4.58 beam units. The beam supply corresponding to these elements are the six beams allotted to the West region (see Table 5.12) minus the 2.419 beam units assigned to the first element of row three in Table 5.14(b), or 3.581 beams. The percentage of satisfaction is therefore 2.419/3.581, or 0.7818, which means the matrix is adjusted as shown in Table 5.14(c). This adjustment procedure continues, but is less complicated for the remaining two rows because the amount of beam supply for North Central and South Central is larger than the demand. The adjustment is completed by satisfying the demand, i.e., inserting the corresponding elements from Table 5.11, and the final result is shown in Table 5.14(d). At this point it should be recalled that the design began by converting seven of 25 satellites to regional-beam use, see discussion above Equation (5.2); thus 18 remain for CONUS coverage. For a clear

#### Table 5.14

.

## Supply matrix adjustment

(a) Step one

.

.

beams		East N	. Central	West	S.	Central
	East	3.380	*	2.419		1.200
N.	Central	*	2.310	2.440		1.190
	West	2.740	1.736	0.854		0.669
s.	Central	1.910	1.190	0.940		0.300

## (b) Step two

	beams	East	N.	Central	West	s.	Central
	East	3.380		*	2.419		1.200
N.	Central	*					
	West	2.419					

S. Central 1.200

## Table 5.14 (Continued)

## (c) Step three

	beams	East	N. Central	West	S.	Central
	East	3.380	*	2.419		1.200
N.	Central	*		1.908		
	West	2.419	1.908	0.938		0.735
S.	Central	1.200		0.735		

# (d) Final step

	beams	East	N. Central	West	S. Central	sub-total
	East	3.380	. *	2.419	1.200	7
N.	Central	*	2.310	1.908	1.190	5.408
	West	2.419	1.908	0.938	0.735	6
s.	Central	1.200	1.190	0.735	0.300	3.425

comparison of how the regional-beam designs increase the communications supply, the supply matrix without these regional-beam designs (as shown in Table 5.10) is re-listed in Table 5.15, and the supply matrix with regional-beam designs is given in Table 5.16. It is obvious that the design has accomplished its objective: increasing the communications supply (i.e., satellite availability) to the four regions while decreasing it for no user.

One possible beam arrangement that could provide the number of beams listed in Table 5.12 is shown in Figure 5.5. One possible communications traffic distribution that could provide the supply matrix as shown in Table 5.14(d) is shown in Figure 5.6, and is derived as follows. First, one should saturate the capacity of the one-beam satellites with intra-regional traffic supply, as in satellites S2, S7, and  $S_{12}$ . Then one should try to saturate the capacity of the two-beam satellites with inter-regional traffic supply, as in S<sub>3</sub>, S<sub>4</sub>, S<sub>5</sub>, S<sub>6</sub>, S<sub>8</sub>, Sg, S<sub>10</sub>, and S<sub>11</sub>; because of the limited supply given in Table 5.14(d),  $S_5$ ,  $S_6$ , and  $S_8$  are not fully used by inter-regional traffic, and the remaining capacity in each is assigned to intra-regional traffic. The traffic of the three-beam satellites are then distributed to fulfill the remaining traffic supply quota in Table 5.14(d). Also note that as shown in Figure 5.6, additional intra-regional beams are available for North Central and South Central. Comparison of the supply matrix in Table 5.16, which is implemented by Figure 5.6, with the requirements in Table 5.9 show that this situation can be viewed as more than 100% satisfaction of the demand for these regions.

### Table 5.15

	beams	East	N. Central	West	S. Central	CONUS
	East	1.305	*	0.934	0.463	
N.	Central	*	0.560	0.592	0.289	17.753
	West	0.934	0.592	0.291	0.228	
s.	Central	0.463	0.289	0.228	0.073	

## Supply matrix without regional beams

### Table 5.16

### Supply matrix with regional beams

	beams	East	N. Central	West	S. Central	rest
	East	3.380	*	2.419	1.200	
N.	Central	*	2.310	1.908	1.190	18
	West	2.419	1.908	0.938	0.735	
s.	Centra1	1.200	1.190	0.735	0.300	



Figure 5.5. Possible beam arrangement for four regions.



Figure 5.6. Possible communications distribution for four regions.

#### 4. Discussion of Numerical Example

The above example was formulated by observing the communicationsdemand density on a map and selecting service areas intuitively according to the following criteria: the communications demand within and between the service areas should be high, the service areas should be small, and the distance between these service areas should be large. To some extent these criteria conflict, and a compromise was necessary. Although the service areas were specified intuitively, there should be ways to automate this process. The ultimate criterion for the choice of service area specification is that it should result in the maximum communications supply. Intermediate criteria in terms of the  $\Delta S$  and demand matrix elements would be useful if they can be developed.

It was fortunate that the required spacing between the East and North Central satellites turned out slightly-less than half the value for CONUS-beam satellites; this made the satellite "conversion" from CONUS to regional-beam particularly simple and straightforward. For other choices of service areas, the  $\Delta$ S matrix will be different, so will the beam arrangement and the resulting communications supply. Still the principle is the same: smaller  $\Delta$ S values means more satellites. It is hoped that this example will provide insight for generating more general and automated procedures.

The concept of replacing administration-coverage satellites with regional-beam ones may have great practical merit. At present, satellite planning work may take place many years before the actual satellite implantation. It is very difficult to make a plan that can

cope with the technologies available twenty years later; therefore, a good plan should be flexible so that the administrations will not be tied to old technologies. For example, if CONUS-beam designs are used in the U.S. planning process with the option of "converting" some to multiple-beam designs later, higher information capacity can be obtained within the framework of an existing scenario, i.e., without changes in the remaining satellites. Therefore, from the viewpoint of flexibility, the multiple-beam replacement option should be attractive as a component of the U.S. planning.

#### F. DISCUSSION AND CONCLUSION

It was suggested that service areas of the FSS system should be specified according to the communications traffic-demand density in conjunction with the  $\Delta S$  concept, because this could enable the system planner to specify more satellites and provide more communications supply. When applying this concept to specify satellites for administration(s) which has heavy traffic between several small and separated regions, it was shown that a mixture of administration coverage and intra-administration regional coverage can increase the communications capacity compared with only administration coverage. A numerical example was used to illustrate the design procedure for replacing several of a series of uniformly spaced administrationcoverage satellites with regional-beam ones. It was shown that a substantial communications capacity increase could be obtained for many users without decreasing the capacity for any user. The procedure was

intuitive in part, and it is recommended that techniques for formalizing and automating it be investigated.

The regional service-area concept in this chapter is closely related to the  $\Delta S$  concept in Chapter IV. In Chapter IV, the specification of service areas is given and fixed and the focus of the study is allocating satellite locations in the orbit. The focus in Chapter V is the specification of service areas. It is found that consideration of  $\Delta S$  and traffic demand leads to useful techniques for this specification.

An important advantage in specifying smaller (i.e., regional as opposed to administration-coverage) service areas in the case of geographically large administrations is the reduction of interference to other communications systems. A smaller service area means a smaller beam, and hence a faster drop of the field strength away from the service area. Thus, the use of regional service areas can give better interference protection to other service areas, not only within but also outside the same administration.

In this chapter, the inter-satellite service (ISS) was not considered. The adoption of the ISS might affect this study significantly.

#### CHAPTER VI

#### CONCLUSION

The purpose of this study has been to explore orbit and frequency assignment methods with which the spectrum/orbit resources can be efficiently utilized for satellite communications.

In Chapter III, the mathematical nature of the orbital/frequency assignment problem is investigated by analyzing an objective function used by the extended-gradient and cyclic-coordinate search techniques. It is shown that the permutation of the orbital/frequency assignments is an important part of the problem. This indicates that a necessary condition for a technique to be able to find the globally optimal scenario is that it should to be able to deal with both the signal quality requirement and the permutation problem. It is also shown that, at least when the frequency variables are fixed, for a given orbital permutation this objective function is likely to have only one local minimum. This suggests that a sufficient condition to obtain the globally optimal solution by a extended gradient search method is that it should terminate as the ordinary gradient search procedure with the optimal permutation in orbital and frequency assignments.

In Chapter IV, a technique for obtaining the optimal orbital assignments is presented. The idea is to convert the signal quality requirement to minimum satellite spacing requirements and use them as constraints on the relative satellite locations. With a set of these

constraints, the assignment problem can be formulated as a mixed integer program (integer programming is often used to solve a permutation problem) and solved by the branch-and-bound method. The globally optimal solution is guaranteed; however, the required computational time may be prohibitively long when the problem size (number of satellites to be assigned) is large. To overcome this difficulty, the same problem is formulated as a linear program and solved by a version of the simplex method with restricted basis entry; only a locally optimal solution is guaranteed, but the method is more practical in terms of computational effort. The solutions of both programs are guaranteed to have satisfactory single-entry C/I<sub>e</sub> (carrier-to-effective interference ratio) results.

In Chapter V, a basis of specifying service areas for the FSS system is proposed. It is suggested that while some satellites should cover large territories, some satellites should cover smaller regions where the communications demands are high. Smaller and separated service areas require smaller necessary satellite spacings, thus more satellites can be allocated in the orbit and higher communications supply can be obtained. The method involves simultaneous consideration of a requirement matrix and the  $\Delta$ S matrix for the proposed regions. A numerical example, in which projected voice telephone demand is used for the requirement matrix, demonstrates the validity of this approach.

### APPENDIX A

#### STREAMLINED SOUP CODE

,

C***	>> MAIN PROGRA	M <<				
C	THIS IS A MINI	SOUP PROGRAM				
с						
c	IMPLICIT INTEGER*4(I-N),REAL*8(A-H,O-Z) CHARACTER*6 NAMESA					
c						
С	COMMON / CONSTS/ 1	E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, PFD, ALOGE, ALN10, COIMIN, COISING				
c	COMMON / PARAMS/	NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)				
	COMMON /VECTOR/ 1 2	DSLON(10),RSLON(10),XO(10),YO(10), ROAIKJ, XOAC(10),YOAC(10),ZOAC(10),ROAC(10)				
C	COMMON / VARBLS/	<pre>FREQ(10), IPOLAR(10), GAINR(10), GAINT(10), EIRP(10), IPTNST(10), IPTNER(10)</pre>				
C	COMMON /MINELL/ 1 1	BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10), REFLAT(10), REFLON(10), AXR(10), ORIENT(10), AXMAJ(10)				
C	COMMON /TPOINT/ 1	RELON(10,20),RELAT(10,20),DELON(10,20), DELAT(10,20),XE(10,20),YE(10,20),ZE(10,20)				
	COMMON /ANGLES/	YPH IT, YPH IR, PH ITK, YPH IO				
C .	COMMON / REAL/	PIRJ, PREJ, PHFOM, FWDRCK, YPWDRC, YPWDRX, YOAKEL, YOAKEL, ZOAKEL, BOAKEL				
c	-					
C****	*************	******************				
c	OPEN (UNIT=20,F) OPEN (UNIT=6,FII	LE='INPUTO.DAT',TYPE='OLD') LE='NASAP.DAT',TYPE='NEW')				
c	CALL ICONST CALL INPUTO					
000	ASSUME POWER DEN	ISITIES AT ALL BEAM AIM POINTS ARE CONSTANT				
2	DO 2 K = 1,NUMSAR CALL GAINER(K) EIRP(K) = PFD+10.*DLOG10(4.*PI*ROAC(K)*ROAC(K))-ERDB CONTINUE					
с	CALL ZFUNCT					
С	STOP END					
С	SUBROUTINE ZFUNG	<b></b>				
C C*** C***	>> THIS ROUTINE >> STEP IN THE	IS THE OVERALL CONTROL ROUTINE AT EACH <<				
C C****	******	******				
С	IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)					

С CHARACTER\*6 NAMESA C COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPH10(10) C COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10), 1 ROAIKJ, XOAC(10), YOAC(10), ZOAC(10), ROAC(10) 2 С COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10), EIRP(10), IPTNST(10), IPTNER(10) 1 С COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10), 1 REFLAT(10), REFLON(10), AXR(10), ORIENT(10), AXMAJ(10) 1 С COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20), DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20) 1 C COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHI0 С PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX, COMMON / REAL/ XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ 1 С \* \*\*\*\*\*\*\*\*\*\*\*\*\*\*\* C\*\* C C\*\*\* INITIALIZE PARAMETER >> С DO 10 I=1, NUMSAR CALL REFCAL(I) 10 CONTINUE С OUTER SUMMATION (OVER K) FOR ALL SERVICE AREAS << C\*\*\* >> С DO 1000 K = 1, NUMSAR JNTP = NTPSA(K)WRITE(6,705) NAMESA(K,1), DSLON(K) С C\*\*\* MIDDLE SUMMATION (OVER J) FOR ALL TEST POINTS IN AREA K << >> С DO 900 J = 1, JNTPCALL KPHI (K, J) CALL XPHIO (K,K,J) CALL KPWDRC (K, J) CALL XPWFQ (FREQ(K), FREQ(K)) CALL XPOWER (K,K,J) Č\*\*\* >> CALCULATE INTERFERENCE POWER SUMP=0. DO 500 I = 1, NUMSAR IF (I.EQ.K) GO TO 500 CALL ZPHI (I,K,J) CALL XPHIO (I,K,J) IF (IPOLAR(I).EQ. IPOLAR(K)) THEN CALL 2 PWDRC (I, K, J) ELSE

```
CALL ZPWDRX (I, K, J)
               END IF
               CALL XPWFQ (FREQ(K), FREQ(I))
               CALL XPOWER (I,K,J)
               COI = PKKJ-PIKJ
               DMGN = COI - COISING
C
         WRITE (6,706) DELON (K, J), DELAT (K, J), NAMESA (I, 1), PIKJ, COI, DMGN
С
             IF (PIKJ .LT. -700.) PIKJ = -700.
С
                     TEN1 = 10. ** (PIKJ/10.)
                     SUMP = SUMP + TEN1
             CONTINUE
 500
С
         IF(NUMSAR.NE.2) THEN
         SUMPDB = 10.*DLOG10(SUMP)
         COIT = PKKJ-SUMPDB
         TDMGN = COIT-COIMIN
         WRITE (6,708) DELON (K, J), DELAT (K, J), SUMPDB, COIT, TOMGN
         END IF
С
 900
         CONTINUE
 1000 CONTINUE
С
 705
     FORMAT(//,12X,'TEST COUNTRY :',A6,5X,'SATELLITE :',F8.2,//,15X,
     1'TEST POINT',10X,'INT. SAT.',2X,'INT. PWR',3X,'C/I (dB)',
     25X, 'MARGIN')
 706 FORMAT (15X, F7.2, 2X, F7.2, 5X, A6, 4X, F8.2, 4X, F6.2, 6X, F6.2)
     FORMAT (13X, 2(2X, F7.2), 6X, 'TOTAL', 4X, F8.2, 4X, F6.2, 6X, F6.2,/)
 708
      RETURN
      END
С
      SUBROUTINE ICONST
С
C***
      >> THIS ROUTINE INPUTS CONSTANTS THAT ARE USED IN THE PROGRAM <<
С
Č*
        С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                     PFD, ALOGE, ALN10, COIMIN, COISING
С
          **********************
C*
С
      E = 2.7182818285
      PI = 3.1415926536
      RADIAN = PI / 180.0
     DEGREE = 180.0 / PI
     GCR = 6.6134
      ER = 6.371E+06
      ALOGE = 0.4342944819
      ALN10 = 2.3025850930
      ERDB = -20.0 * DLOG10(ER)
     PFD = -90.
      EAP = 0.6
С
     RETURN
      END
```

```
177
```

```
С
      SUBROUTINE INPUTO
С
C***
                                                                 <<
      >>
          THIS ROUTINE INPUTS
Č***
                         SERVICE AREA DATA
                                                                 <<
      >>
                      -
C***
                         INITIAL SATELLITE LOCATIONS
                                                                 <<
      >>
C***
                                                                 Ś
      >>
                         INITIAL FREQUENCY ASSIGNMENTS
C***
                                                                 <<
      >>
                         INITIAL POLARISATIONS
C***
      >>
                         ANTENNA PATTERN TYPE
C
                C*
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                      PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPH IO(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
                      ROAIKJ,
     3
     2
                      XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                      EIRP(10), IPTNST(10), IPTNER(10)
С
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                      REFLAT(10), REFLON(10), AXR(10),
     1
                      ORIENT(10), AXMAJ(10)
     1
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
                      DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
     1
С
              C**
C
C***
         INPUT DATA FOR SATELLITE, BEAM, EARTH STATION CHARACTERISTICS
      >>
С
      READ(20,*) COISING
        COIMIN = COISING - 5.
      READ(20,*) NUMSAR
      DO 10 N = 1, NUMSAR
           READ(20,801) (NAMESA(N,I),I=1,2)
           READ(20,*)DSLON(N), FREQ(N), IPOLAR(N), IPTNST(N), IPTNER(N)
           READ(20,*) DBCLON(N), DBCLAT(N), ORIENT(N), AXMAJ(N), AXMIN
           READ(20,*) NTP
        DO 12 N1=1,NTP
           READ(20,*)DELON(N,N1),DELAT(N,N1)
С
          RELON(N, N1) = DELON(N, N1) * RADIAN
           RELAT(N, NI) = DELAT(N, NI) * RADIAN
        CONTINUE
 12
С
           NTPSA(N) = NTP
           FREQ(N) = FREQ(N) * 1000.
           RSLON(N) = DSLON(N) * RADIAN
           AXR(N) = AXMAJ(N) / AXMIN
           ORIENT(N) = ORIENT(N) *RADIAN
           AXMAJ(N) = AXMAJ(N) * RADIAN
```

```
BCLON(N) = DBCLON(N) * RADIAN
           BCLAT(N) = DBCLAT(N) * RADIAN
С
 10
      CONTINUE
C
C***
      >> REFLECT INPUT DATA <<
С
      WRITE(6,901)
DO 20 N = 1,NUMSAR
                          NAMESA(N,1),DSLON(N),
           WRITE (6,902)
                          FREQ(N), IPOLAR(N), IPTNST(N), IPTNER(N)
     ŝ
      CONTINUE
  20
С
 801
      FORMAT (2A6)
     FORMAT (//12X, 'COUNTRY', 5X, 'SATELLITE', 5X, 'FREQUENCY', 3X,
 901
               'POLAR.', 3X, 'PTN(ST)', 3X, 'PTN(ER)',/)
     $
 902
      FORMAT (13X, A6, 5X, F9.2, 5X, F9.2, 5X, 12, 7X, 12, 8X, 12)
С
C***
      >> SET UP THE VECTORS FOR THE TEST POINTS <<
С
      DO 30 K = 1, NUMSAR
С
          XOI = DCOS(RSLON(K))
          YOI = DSIN(RSLON(K))
          XO(K) = XOI
          YO(K) = YOI
С
          BCLT = BCLAT(K)
          BCLN = BCLON(K)
          COSBLT = DCOS(BCLT)
          CXE = COSBLT*DCOS(BCLN)
          CYE = COSBLT*DS IN (BCLN)
          CZE = DSIN(BCLT)
С
          XOACI = CXE-GCR*XOI
          YOACI = CYE-GCR*YOI
          ZOAC(K) = CZE
          ROACI = DSQRT (XOACI * XOACI + YOACI * YOACI + CZE*CZE)
С
          XOAC(K) = XOACI
          YOAC(K) = YOACI
          ROAC(K) = ROACI
С
          DO 30 J = 1, NTPSA(K)
               COSLAT = DCOS(RELAT(K, J))
               ZE(K, J) = DSIN(RELAT(K, J))
      CONTINUE
  30
С
      RETURN
      END
С
        SUBROUTINE GAINER(K)
CCC
      THIS IS TO CALCULATE EARTH RECEIVER GAIN FROM ANTENNA
      DIAMETER, AND TRANSMITTER GAIN FROM HPBW.
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
```

CHARACTER\*6 NAMESA С COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10), EIRP(10), IPTNST(10), IPTNER(10) 1 С COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPH I0(10) С COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10), REFLAT(10), REFLON(10), AXR(10), 1 ORIENT(10) , AXMAJ(10) 1 С X0 = 223./180.GO TO (10,20,30,40,50), IPTNER(K) С Ĉ FSS, DIAMETER 3 METERS С 10 D = 3. WAVEL = 300. / FREQ(K) X1 = D/WAVELGAINR(K) = 10.\*DLOG10(PI\*PI\*X1\*X1\*EAP) CPHIO(K) = XO/XIGO TO 60 C C FSS, DIAMETER 3 METERS Ĉ D = 3. 20 WAVEL = 300. / FREQ(R)X1 = D/WAVELGAINR(K) = 10.\*DLOG10(PI\*PI\*X1\*X1\*EAP) CPHiu(K) = X0/X1GO TO 60 С č FSS, DIAMETER 4.5 METERS D = 4.530 WAVEL = 300. / FREQ(K) X1 = D/WAVEL GAINR(K) = 10.\*DLOG10(PI\*PI\*X1\*X1\*EAP) CPHIO(K) = XO/X1GO TO 60 C C FSS, DIAMETER 4.5 METERS č 40 D = 4.5WAVEL = 300. / FREQ(K) X1 = D/WAVELGAINR(K) = 10.\*DLOG10(PI\*PI\*X1\*X1\*EAP) CPHIO(K) = XO/XIGO TO 60 C C BSS, DIAMETER 1 METER С D = 1. 50 WAVEL = 300. / FREQ(K) X1 = D/WAVELGAINR(K) = 10.\*DLOG10(PI\*PI\*X1\*X1\*EAP) CPHIO(K) = XO/X1

```
C
C
        CALCULATE TRANSMIT GAIN FROM HPBW
С
 60
        GAINT(K) = 10.*DLOG10(EAP*AXR(K)*(PI*X0/AXMAJ(K))**2)
С
        RETURN
        END
С
      SUBROUTINE KPHI (K, J)
С
Č***
          THIS ROUTINE COMPUTES THE VECTOR COMPONENTS OF THE LINK <<
      >>
C***
            K-K-J, AND THE CORRESPONDING TRANSMITTING PHI ANGLE <<
      >>
С
Č1
                      С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
C
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                      PFD, ALOGE, ALN10, COIMIN, COISING
C
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
                      ROAIKJ,
     1
     2
                      XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
                      EIRP(10), IPTNST(10), IPTNER(10)
     1
С
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                      REFLAT(10), REFLON(10), AXR(10),
     1
     1
                      ORIENT(10), AXMAJ(10)
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
     1
                      DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
С
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
С
                      PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
      COMMON / REAL/
     1
                      XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
С
          C*
С
      XOAKKJ = XE(K, J) - GCR * XO(K)
      YOAKKJ = YE(K, J) - GCR * YO(K)
      ZOAKKJ = ZE(K, J)
      ROAKKJ = DSQRT (XOAKKJ *XOAKKJ + YOAKKJ *YOAKKJ + ZOAKKJ *ZOAKKJ)
С
 .
      COSPHI = (XOAC(K) * XOAKKJ + YOAC(K) * YOAKKJ + ZOAC(K) * ZOAKKJ)
               / (ROAC(K) * ROAKKJ)
     $
      PHITK = DARCOS(COSPHI)
С
  .
      RETURN
      END
С
      SUBROUTINE 2PHI (I,K,J)
С
         THIS ROUTINE COMPUTES THE PHI ANGLES <<
C***
      >>
```

```
181
```

```
C***
     >> (FOR I INTERFERING WITH K TEST POINT J) <<
C
C***
      ************************
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                       PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
     1
                       ROAIKJ,
                       XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
     2
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
                       EIRP(10), IPTNST(10), IPTNER(10)
     1
Ĉ
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
     1
                       REFLAT(10), REFLON(10), AXR(10),
     1
                       ORIENT(10), AXMAJ(10)
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
     1
                       DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
С
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
С
      COMMON / REAL/
                      PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
                      XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
     1
С
Č*
                  ******************
                                                               ********
С
         CALCULATE OFF AXIS VECTOR COMPONENTS (____IKJ) <<
C***
      >>
Ĉ
      XOAIKJ = XE(K, J) - GCR + XO(I)
      YOAIKJ = YE(K, J) - GCR * YO(I)
      ZOAIKJ = ZE(K, J)
      ROAIKJ = DSQRT (XOAIKJ *XOAIKJ + YOAIKJ *YOAIKJ + ZOAIKJ *ZOAIKJ)
С
C***
          COMPUTE DISCRIMINATION ANGLES
                                          <<
      >>
C***
          FOR THE TRANSMITTING ANTENNA
      >>
                                          <<
С
      TNUMER = XOAC(I) * XOAIKJ + YOAC(I) * YOAIKJ + ZOAC(I) * ZOAIKJ
      TDENOM = ROAC(I) * ROAIKJ
      TEMPU = TNUMER / TDENOM
C
      YPHIT = 0.0
      IF (DABS(TEMPU) .LT. 1.0) YPHIT = DARCOS(TEMPU)
С
C***
          COMPUTE DISCRIMINATION ANGLES
                                          <<
      >>
C***
                                          <<
            FOR THE RECEIVING ANTENNA
      >>
С
      TNUMER = XOAKKJ * XOAIKJ + YOAKKJ * YOAIKJ + 20AKKJ * ZOAIKJ
      TDENOM = ROAKKJ * ROAIKJ
      TEMPU = TNUMER / TDENOM
С
      YPHIR = 0.0
      IF (DABS(TEMPU) .LT. 1.0) YPHIR = DARCOS(TEMPU)
```

```
182
```

```
2
```

```
С
      RETURN
      END
С
      SUBROUTINE XPHIO (I,K,J)
С
      >> THIS ROUTINE COMPUTES THE ELLIPTICAL BEAM HALF POWER
C***
C***
      >> BEAM WIDTH USING THE METHOD GIVEN IN THE SOUP-3 MANUAL
Č
C*
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
                       PFD, ALOGE, ALN10, COIMIN, COISING
     1
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
                       ROAIKJ,
                       XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
     2
C,
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                       EIRP(10), IPTNST(10), IPTNER(10)
C
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                       REFLAT(10), REFLON(10), AXR(10),
                       ORIENT(10), AXMAJ(10)
     1
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
     1
                      DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
C
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
С
                      PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
      COMMON / REAL/
                      XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
     1
С
                     C
С
      PHIS = RSLON(I)
      PHIC = BCLON(I)
      THETAC = BCLAT(I)
С
      SINPHS = DSIN(PHIS)
      COSPHS = DCOS(PHIS)
      COSTC = DCOS(THETAC)
С
      COSW = COSTC * DCOS(PHIS-PHIC)
      SINW = DSIN(DARCOS(COSW))
С
      RSLAT = 0.
      IF ( BCLON(I).EQ.RSLON(I) ) GO TO 1
      IF ( BCLAT(I).EQ.RSLAT ) GO TO 2
      ARG = COSTC * DSIN(DABS(BCLON(I)-RSLON(I))) / SINW
      A = DASIN(ARG)
      IF (BCLON(I).GT.RSLON(I) .AND. BCLAT(I).GT.RSLAT) A=2.*PI-A
      IF (BCLON(I).LT.RSLON(I) .AND. BCLAT(I).LT.RSLAT) A=PI-A
      IF (BCLON(I).GT.RSLON(I) .AND. BCLAT(I).LT.RSLAT) A=PI+A
```

```
183
```

```
COSA = DCOS(A)
        SINA = DSIN(A)
        GO TO 3
        CONTINUE
  1
        \cos A = -1.
        SINA = 0.
        A = PI
        IF (BCLAT(I).LT.RSLAT) GO TO 3
        COSA = 1.
        A = 0.
        GO TO 3
  2
        CONTINUE
        \cos A = 0.
        SINA = 1.
        A = PI/2.
        IF (BCLON(I).LT.RSLON(I)) GO TO 3
        SINA = -1.
        A = 1.5 * PI
 3
        CONTINUE
C
        TANT = SINW / (GCR - COSW)
        TRAD = DATAN (TANT)
        SINT = DSIN(TRAD)
       COST = DCOS (TRAD)
С
       \begin{array}{rcl} A21 &=& - & COSA & \pm & SINPHS \\ A22 &=& & COSA & \pm & COSPHS \end{array}
       A23 =
                 SINA
С
       A31 = SINT * COSPHS + COST * SINA * SINPHS
A32 = SINT * SINPHS - COST * SINA * COSPHS
       A33 = COST * COSA
С
       FLAT = REFLAT(I)
       FLON = REFLON(I)
       CSFLAT = DCOS(FLAT)
       VR1 = CSFLAT * DCOS(FLON)
       VR2 = CSFLAT * DSIN(FLON)
       VR3 = DSIN(FLAT)
С
       BLAT = BCLAT(I)
       BLON = BCLON(I)
       CSBLAT = DCOS(BLAT)
       VC1 = CSBLAT * DCOS(BLON)
VC2 = CSBLAT * DSIN(BLON)
       VC3 = DSIN(BLAT)
С
       PHIE = RELON(K, J)
       THETAE = RELAT(K, J)
       COSTE = DCOS (THETAE)
       VEL = COSTE * DCOS(PHIE)
       VE2 = COSTE * DSIN(PHIE)
       VE3 = DSIN(THETAE)
С
       VS1 = GCR * COSPHS
       VS2 = GCR * SINPHS
       VS3 = 0.0
С
       VRMVC1 = VR1 - VC1
       VRMVC2 = VR2 - VC2
```

```
VRMVC3 = VR3 - VC3
С
      VEMVS1 = VE1 - VS1
      VEMVS2 = VE2 - VS2
      VEMVS3 = VE3
С
      SINUMR = A31*VRMVC1 + A32*VRMVC2 + A33*VRMVC3
      SIDENR = A21*VRMVC1 + A22*VRMVC2 + A23*VRMVC3
С
      S2NUMR = A31*VEMVS1 + A32*VEMVS2 + A33*VEMVS3
      S2DENR = A21*VEMVS1 + A22*VEMVS2 + A23*VEMVS3
С
      IF (SLDENR. NE .0.0) GO TO 10
      S1 = PI / 2.0
      GO TO 15
  10
      SI = DATAN(SINUMR/SIDENR)
С
  15
      IF (S2DENR. NE .0.0) GO TO 20
      S2 = PI / 2.0
      GO TO 25
  20
      S2 = DATAN (S2 NUMR / S2 DEN R)
С
  25
      SIGMA = S2 - S1
      CS = DCOS(SIGMA)
      SS = DSIN(SIGMA)
      AR = AXR(I)
      PO = AXMAJ(I) / DSQRT(CS*CS + AR*AR * SS*SS)
С
      YPHIO = PO
      RETURN
      END
С
      SUBROUTINE REFCAL(N)
С
C***
      >> THIS ROUTINE CALCULATES THE REFERENCE POINT LAT. & LON. <<
C***
      >> BASED ON THE ALGORITHM IN SOUP MANUAL 3.4, MAY 1983
                                                                  <<
С
     C*
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
C
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                      PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
                      ROAIKJ,
     1
     2
                      XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                      EIRP(10), IPTNST(10), IPTNER(10)
С
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
     1
                      REFLAT(10), REFLON(10), AXR(10),
                      ORIENT(10), AXMAJ(10)
     1
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
```

```
185
```

```
DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
      1
С
       COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
С
       COMMON / REAL/
                        PIKJ, PKKJ, FWFQM, FWDRCK, YFWDRC, YFWDRX,
      1
                        XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
C
C*1
         С
       PGMPS = BCLON(N) - RSLON(N)
       COSTG = DCOS(BCLAT(N))
       COSPP = DCOS(PGMPS)
       Q1 = COSTG * DSIN(PGMPS)
       Q2 = GCR - COSTG * COSPP
       O3 = DSORT(O1 * 2 + O2 * 2)
C
      SX = DATAN2(Q1,Q2)
       SY = DATAN2(DSIN(BCLAT(N)), 03)
С
       AMAJ2 = AXMAJ(N) \pm 0.5
       SX2 = AMAJ2 * DCOS (ORIENT (N) )
       SY2 = AMAJ2 * DSIN(ORIENT(N))
С
      X1 = SX + SX2
      Y1 = SY + SY2
С
      O4 = DARCOS(DCOS(X1) + DCOS(Y1))
      Q5 = DSIN(Q4)
      T = GCR * 05
IF (T.LE. 1.0) GO TO 10
С
      X1 = SX - SX2
      YI = SY - SY2
      Q4 = DARCOS(DCOS(X1) * DCOS(Y1))
      Q5 = DSIN(Q4)
      T = GCR * Q5
      IF (T.LE. 1.0 .AND. T.GE. -1.0)
                                           GO TO 10
      IF (T .GT. 0.) T = 1.0
IF (T .LT. 0.) T = -1.0
С
      WRITE(6,901) T
     FORMAT (/10X, '****** POSSIBLE ERROR IN ELLIPSE SELECTION ',
 901
     ŝ
               F5.1)
С
  10
      PX = DARSIN(DSIN(Y1)/05)
      IF (X1 .LT. 0.0) PX = PI - PX
      D = DARSIN(T)
      BLAM = D - Q4
REFLAT(N) = DARSIN(DSIN(BLAM) * DSIN(PX))
      AL = DARCOS(DCOS(BLAM)/DCOS(REFLAT(N)))
IF (DABS(PX).GT. PI/2.) AL = -AL
      REFLON(N) = RSLON(N) + AL
С
      RETURN
      END
С
С
      FUNCTION DARSIN(X)
С
        IMPLICIT REAL*8(A-H, O-Z)
```

```
186
```

```
DARSIN = DASIN(X)
        RETURN
        END
C
      FUNCTION DARCOS(X)
С
        IMPLICIT REAL*8(A-H, O-Z)
        DARCOS = DACOS(X)
        RETURN
        END
С
      SUBROUTINE KPWDRC (K, J)
С
C***
      >> THIS ROUTINE COMPUTES THE CARRIER SIGNAL DISCRIMINATING <<
C***
      >> FACTOR (DESIRED POWER - CO-POLARISED ONLY - PHIR=0 )
                                                                  11
Č
C*
          С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                      PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
     1
                      ROAIKJ,
     \bar{\mathbf{2}}
                      XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                      EIRP(10), IPTNST(10), IPTNER(10)
С
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                      REFLAT(10), REFLON(10), AXR(10),
     1
     1
                      ORIENT(10), AXMAJ(10)
C
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
     1
                      DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
С
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
С
                      PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
      COMMON / REAL/
     1
                      XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
С
Č*
C
              PT = PHITK
      P0 = YPHIO
С
      GO TO(10,20,30,40,50), IPTNST(K)
C
  10
     CALL PINST1 (PT, PO, GAINT(K), DISC)
      GOTO 60
С
  20
     CALL PTNST2 (PT, PO, GAINT(K), DISC)
      GOTO 60
С
  30
     CALL PTNST3 (PT, PO, GAINT(K), DISC)
```

```
GOTO 60
С
      CALL PINST4 (PT, PO, GAINT(K), DISC)
  40
      GOTO 60
С
  50
      CALL PINST5 (PT, PO, GAINT(K), DISC)
С
      YDSCT = DISC
  60
C
C
      PREVENTING INPERFECT MINIMUM ELLIPSE NOT COVERING ALL POINTS
С
С
       IF (YDSCT.LT.-3.) YDSCT=-3.
Ç
C***
      >> COMPONENT OF DESIRED POWER DEPENDENT ON ORBIT LOCATION <<
С
      PWDRCK = EIRP(K) + YDSCT + GAINR(K) - 20.0 * DLOG10(ROAKKJ)
      RETURN
С
      END
C
      SUBROUTINE ZPWDRC (I, K, J)
С
C***
          THIS ROUTINE COMPUTES THE INTERFERENCE SIGNAL
                                                                ٢٢
      >>
C***
          TRANSMITTING AND RECEIVING DISCRIMINATIONS FOR
                                                                <<
      >>
C***
          THE CO-POLARISED CASE
                                                                "
      >>
С
C**
          ***********************************
                                                         ***********
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                       PFD, ALOGE, ALN10, COIMIN, COISING
C
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
                       ROAIKJ.
     1
     2
                       XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                       EIRP(10), IPTNST(10), IPTNER(10)
С
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                       REFLAT(10), REFLON(10), AXR(10),
     1
     1
                       ORIENT(10), AXMAJ(10)
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
     1
                       DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
С
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
C
                      PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
      COMMON / REAL/
                       XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
     1
C
                          C*
0
C*
          TRANSMITTING DISCRIMINATION <<
      >>
С
```

```
18
```

PT = YPHIT P0 = YPHIO GO TO(10,20,30,40,50), IPTNST(I) C 10 CALL PTNST1(PT, PO, GAINT(I), DISC) GOTO 60 С 20 CALL PTNST2(PT, P0, GAINT(I), DISC) GOTO 60 C 30 CALL PTNST3 (PT, P0, GAINT(I), DISC) GO TO 60 С 40 CALL PINST4 (PT, PO, GAINT (I), DISC) GO TO 60 С CALL PTNST5 (PT, PO, GAINT (I), DISC) 50 С YDSCT = DISC 60 С C\*\*\* >> RECEIVING DISCRIMINATION << С PR = YPHIR PO = CPHIO(K)С GO TO(110,120,130,140,150), IPTNER(K) C CALL PINER1 (PR, PO, FREQ(I), GAINR(K), DISC) 110 GOTO 160 С 120 CALL PINER2 (PR, PO, FREQ(I), GAINR(K), DISC) GOTO 160 С 130 CALL PTNER3 (PR, P0, FREQ(I), GAINR(K), DISC) GO TO 160 С 140 CALL PTNER4(PR, P0, FREQ(1), GAINR(K), DISC) GO TO 160 С 150 CALL PINER5 (PR, P0, FREQ (I), GAINR(K), DISC) C 160 YDSCR = DISC С C\*\*\* >> COMPONENT OF POWER DEPENDENT ON THE ORBIT LOCATION \_ << C\*\*\* << CO-POLARISED CASE >> Ĉ YPWDRC = EIRP(I) + YDSCT + YDSCR Ś - 20. \* DLOG10(ROAIKJ) С RETURN END С SUBROUTINE ZPWDRX (I, K, J) С C\*\*\* THIS ROUTINE COMPUTES THE INTERFERENCE POWER << >> C\*\*\* TRANSMITTING AND RECEIVING DISCRIMINATIONS FOR << >> C\*\*\* << >> THE CROSS-POLARISED CASE С Č\* С

~	IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
C	CHARACTER*6 NAMESA
c	COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALNI0, COIMIN, COISING
	Common / Params/ Numsar, Namesa (10,2), NTPSA (10), CPH 10 (10)
	COMMON /VECTOR/ DSLON(10),RSLON(10),XO(10),YO(10),         1       ROAIKJ,         2       XOAC(10),YOAC(10),ZOAC(10),ROAC(10)
C	COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10), 1 EIRP(10), IPTNST(10), IPTNER(10)
C	COMMON /MINELL/ BCLAT(10),BCLON(10),DBCLAT(10),DBCLON(10),         1       REFLAT(10),REFLON(10),AXR(10),         1       ORIENT(10),AXMAJ(10)
c	COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20), 1
C C	COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
C	COMMON / REAL/PIKJ, PKKJ, PW FQM, PW DRCK, YPW DRC, YPW DRX,1XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
C****	***************************************
C C***	>> TRANSMITTING DISCRIMINATION <<
•	PT = YPHIT PO = YPHIO
C	GO TO (10,12,14,16,18), IPTNST(I)
C 10	CALL PINSTI(PT, P0, GAINT(I), DISC) GO TO 20
C 12	CALL PTNST2(PT, P0, GAINT(I), DISC) GO TO 20
C 14	CALL PTN ST3 (PT, P0, GAINT (I), DISC) GO TO 20
ັ 16 ເ	CALL PTNST4(PT, P0, GAINT(I), DISC) GO TO 20
č 18	CALL PINST5(PT, P0, GAINT(I), DISC)
ັ 20	YDSCT = DISC
Č*** C	>> RECEIVING DIRECTIVITY <<
c	PR = YPHIR PO = CPHIO(K)
-	CALL XPTNER1(PR, P0, GAINR(K), DISC) YDSXR = DISC

.

```
C
C***
       >>
           COMPONENT OF POWER DEPENDENT ON THE ORBIT LOCATION
                                                                    <<
C***
       >>
                           CROSS-POLARISED CASE
                                                                    <<
С
 100
      YPWDRX = EIRP(I) + YDSCT + YDSXR
                     - 20.0 * DLOGIO(ROAIKJ)
C
      RETURN
       END
С
       SUBROUTINE XPWFQ (FQD, FQI)
С
C***
       >>
           THIS ROUTINE COMPUTES THE FREQUENCY DEPENDENT PORTION
                                                                      <<
C***
          IN THE POWER EQUATION
       >>
                                                                      ٠ċ
C
C**
           ***************************
                                                         ************
С
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                        PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPH IO(10)
C
      COMMON /VECTOR/ DSLON(10), RSLON(10), XO(10), YO(10),
                        ROAIKJ,
     1
     2
                        XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                        EIRP(10), IPTNST(10), IPTNER(10)
С
      COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                        REFLAT(10), REFLON(10), AXR(10),
     1
     1
                        ORIENT(10), AXMAJ(10)
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
     1
                       DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
C
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHI0
C
                       PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
      COMMON / REAL/
     1
                       XOAKKJ, YOAKKJ, 20AKKJ, ROAKKJ
С
C*
                  *******************************
                                                              ********
C
C*
          POWER BEING CALCULATED IS INTERFERING POWER <<
      >>
C
      X = (FQI - FQD)
      ABSX = DABS(X)
      IF (ABSX. LE. 15.) THEN
        FF = 0.
        ELSE
        FF = -(ABSX-15.)*1.6
      END IF
С
      PWFQM = FF - 20.0 * DLOG10(FQI)
С
```

```
191
```

```
RETURN
      END
С
      SUBROUTINE XPOWER (I, K, J)
С
C***
      >>
          THIS ROUTINE CALCULATES ALL THE POWERS AFTER THE
                                                              <<
                                                              <٢
C***
      >>
           DIRECTIVITY AND FREQUENCY PORTIONS ARE COMPUTED
Ċ
                C*
Ċ
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
C
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                      PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(10,2), NTPSA(10), CPHI0(10)
С
      COMMON /VECTOR/ DSLON(10),RSLON(10),XO(10),YO(10),
                      ROAIKJ,
                      XOAC(10), YOAC(10), ZOAC(10), ROAC(10)
     2
С
      COMMON /VARBLS/ FREQ(10), IPOLAR(10), GAINR(10), GAINT(10),
     1
                      EIRP(10), IPTNST(10), IPTNER(10)
Ċ
     COMMON /MINELL/ BCLAT(10), BCLON(10), DBCLAT(10), DBCLON(10),
                      REFLAT(10), REFLON(10), AXR(10),
     1
                      ORIENT(10), AXMAJ(10)
     1
С
      COMMON /TPOINT/ RELON(10,20), RELAT(10,20), DELON(10,20),
                      DELAT(10,20), XE(10,20), YE(10,20), ZE(10,20)
     1
С
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHI0
C
                      PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX,
      COMMON / REAL/
     1
                      XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
С
                       ********
C*
С
      IF (K. EQ.I) GO TO 100
C
C***
      >>
         POWER BEING CALCULATED IS AN INTERFERING POWER <<
С
      IF (IPOLAR(I). EQ .IPOLAR(K)) GO TO 50
С
C***
         CROSS-POLARIZED <<
      >>
С
      PIKJ = YPWDRX + PWFQM + ERDB + 27.56
      RETURN
C
C***
      >> CO-POLARIZED <<
С
 50
     PIKJ = YPWDRC + PWFQM + ERDB + 27.56
     RETURN
С
Č***
        POWER BEING CALCULATED IS A DESIRED POWER <<
      >>
С
100
     PKKJ = PWDRCK + PWFQM + ERDB + 27.56
      RETURN
```

```
C
       END
С
         SUBROUTINE PTNST1 (PT, P0, G, DISC)
С
С
       FSS SATELLITE TX PATTERN FROM CCIR REPORT 558-2
С
       IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-2)
С
       COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
                       PFD, ALOGE, ALN10, COIMIN, COISING
      1
C
       X=PT/PO
       IF (X .LE. 1.3) GO TO 10
IF (X .LE. 3.15) GO TO 20
С
       DISC = -(7.5 + 25.0 * DLOG10(X))
      IF (DISC.LE.(-G-10.)) DISC = -G-10.
       GO TO 40
С
 10
      DISC = -12.0 * X * X
      GO TO 40
С
  20
      DISC = -20.0
С
  40
      RETURN
      END
С
         SUBROUTINE PTNST2(PT, P0, G, DISC)
С
      FSS SATELLITE TX PATTERN FROM RARC 83 $ 5.1.10.1
С
С
      IMPLICIT INTEGER*4(1-N), REAL*8(A-H, O-Z)
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                        PFD, ALOGE, ALN10, COIMIN, COISING
С
      DP0 = P0 * DEGREE
      X1 = PT/P0
      X2 =DP0/0.8
      X3 = .5 * (1. - 1. / X2)
С
      P1 = .4/DP0 + X3
      P2 =1.155/DP0 +X3
      P3 =1.60/DP0+X3
      P4 = 4.0/DP0+X3
      P5 = 6.968/DP0 + X3
      P6 = 10.**((G-11.5)/25.)/X2 + X3
С
      IF (X1 .LE. 0.5)
                          GO TO 10
                         GO TO 12
      IF (X1 .LE. P2)
      IF
         (X1 .LE. P3)
                         GO TO 14
      IF (X1 .LE. P4)
                         GO TO 16
      IF (X1 .LE. P5)
                         GO TO 18
      IF (X1 .LE. P6)
                         GO TO 20
С
      DISC = -G
      GO TO 40
С
 10
      DISC = -12.0 * X1 * X1
```

```
193
```

```
GO TO 40
С
 12
       DISC = -18.75*DP0*DP0*(X1-X3)*(X1-X3)
       GO TO 40
С
 14
       DISC = -25
       GO TO 40
С
 16
       DISC = -17.5 - 25.*DLOG10((X1-X3)*X2)
       GO TO 40
С
 18
       DISC = -35.
       GO TO 40
С
 20
       DISC = -11.5 - 25.* DLOG10((X1-X3)*X2)
Ĉ
  40
       RETURN
       END
С
         SUBROUTINE PINST3 (PT, P0, G, DISC)
С
Ĉ
       FSS SATELLITE TX PATTERN FROM RARC 83 $ 5.1.10.1
С
      WITH MODIFICATION
Ĉ
       IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
      1
                        PFD, ALOGE, ALN10, COIMIN, COISING
С
      DP0 = P0*DEGREE
       X1 = PT/P0
      X2 = DP0/0.8
      X3 = .5*(1.-1./X2)
С
      IF (X1 .LE. 0.5) GO TO 10
      P2 = 1.265/DP0 + X3
      IF (X1 .LE. P2) GO TO 12
      P3 = 10.**((30.-24.)/30.)
      IF (X1 .LE. P3) GO TO 14
P4 = 10.**((G-24.)/30.)
      IF (X1 .LE. P4) GO TO 16
С
      DISC = -G
      GO TO 40
С
 10
      DISC = -12.0 * X1 * X1
      GO TO 40
С
 12
      DISC = -18.75*DP0*DP0*(X1-X3)*(X1-X3)
      GO TO 40
С
 14
      DISC = -30.
      GO TO 40
С
 16
      DISC = -24.-30.*DLOG10(X1)
С
  40
      RETURN
      END
С
        SUBROUTINE PTN ST4 (PT, P0, G, DISC)
```

```
C
C
       FSS SATELLITE TX PATTERN FROM RARC 83 $5.10.1
C
C
       WITH MODIFICATION
       IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
       COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
                         PFD, ALOGE, ALN10, COIMIN, COISING
      1
С
       DPO = PO = DEGREE
       X1 = PT/P0
       X2 = DP0/0.8
       X3 = .5*(1.-1./X2)
С
       IF (X1 .LE. 0.5)
                          GO TO 10
       P2 = 1.265/DP0 + X3
       IF (X1 .LE. P2) GO TO 12
       P3 = 10.**((30.-24.)/30.)
       IF (X1 .LE. P3) GO TO 14
P4 = 10.**((G-24.)/30.)
       IF (X1 .LE. P4) GO TO 16
С
       DISC = -G
       GO TO 40
С
 10
       DISC = -12.0 * X1 * X1
       GO TO 40
С
       DISC = -18.75*DP0*DP0*(X1-X3)*(X1-X3)
 12
       GO TO 40
C
 14
       DISC = -30.
       GO TO 40
С
 16
      DISC = -24.-30.*DLOG10(X1)
С
 40
       RETURN
       END
С
         SUBROUTINE PINST5 (PT, P0, G, DISC)
C
C
      SATELLITE TX PATTERN FROM RARC 83 P.111,
C
C
      BSS PATTERN
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
      COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                        PFD, ALOGE, ALN10, COIMIN, COISING
С
      X1 = PT/P0
С
      IF (X1 .LE. 1.58) GO TO 10
      IF (X1 .LE, 3.16) GO TO 12
IF (X1 .LE. 10.) GO TO 14
С
      DISC = -42.5
      GO TO 40
C
10
      DISC = -12.0 * X1 * X1
      GO TO 40
```

```
С
 12
       DISC = -30.
       GO TO 40
С
 14
       DISC = -17.5-25.*DLOG10(X1)
       GO TO 40
С
   40
       RETURN
       END
С
         SUBROUTINE PINER1 (PR, P0, F, G, DISC)
С
Ċ
       FSS EARTH REVEIVER PATTERN FROM CCIR REPORT 391-4
       ANTENNA DIAMETER 3 METERS, MAIN LOBE NOT GAUSSIAN
С
С
       IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
С
       COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
                         PFD, ALOGE, ALN10, COIMIN, COISING
      1
С
       DPR = PR*DEGREE
       DPO = PO * DEGREE
       D = 3.
       WAVEL = 300./F
       X1 = D/WAVEL
       G1 = 2. + 15.* DLOG10(X1)
       PM = 20./X1* DSORT(G-G1)
PS = 15.85 / X1**0.6
С
       IF (DPR .LE. PM)
                          GO TO 50
       IF (DPR .LE. PS) GO TO 60
       IF (DPR .LE. 48.) GO TO 70
С
       DISC = -10.
       GO TO 80
С
  50 DISC = G- 2.5E-3 * X1*X1*DPR*DPR
       GO TO 80
С
  60 \text{ DISC} = G1
       GO TO 80
С
  70
      DISC = 32.-25.*DLOG10(DPR)
С
  80
      RETURN
       END
С
         SUBROUTINE PINER2(PR, P0, F, G, DISC)
С
       FSS EARTH REVEIVER PATTERN FROM CCIR REPORT 391-4
С
      MAIN LOBE GAUSSIAN, ANTENNA DIAMETER 3 METERS,
MODIFIED FOR NON US COUNTRIES
C
C
¢
      IMPLICIT INTEGER*4(I-N), REAL*8(A-H, O-Z)
C
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                         PFD, ALOGE, ALN10, COIMIN, COISING
С
      DPR = PR * DEGREE
      X = PR/PO
```

P2 = 10.\*\*((32.+10.)/25.)С IF (X.LE.0.5) THEN DISC = G - 12.\*X\*XGO TO 80 ELSE IF (DPR .GE. P2) THEN DISC = -10. GO TO 80 END IF С DISC = G - 12.\*X\*XD1 = 32. - 25.\*DLOG10(DPR) IF (D1 .GE. DISC) DISC = D1 С RETURN 80 END С SUBROUTINE PINER3 (PR, P0, F, G, DISC) C Ĉ FSS EARTH REVEIVER PATTERN FROM CCIR REPORT 391-4 Ĉ MAIN LOBE GAUSSIAN, ANTENNA DIAMETER 4.5 METERS, MODIFIED FOR US ONLY С IMPLICIT INTEGER\*4(I-N), REAL\*8(A-H, O-Z) С COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С DPR = PR\*DEGREE X = PR/P0P2 = 10.\*\*((29.+10.)/25.)С IF (X.LE.1.) THEN DISC = G - 12.\*X\*XGO TO 80 ELSE IF (DPR .GE. P2) THEN DISC = -10.GO TO 80 END IF С DISC = G - 12.\*X\*XD1 = 29. - 25.\*DLOG10(DPR)IF (D1 .GE. DISC) DISC = D1 С 80 RETURN END С SUBROUTINE PINER4 (PR, P0, F, G, DISC) С FSS EARTH REVEIVER PATTERN FROM CCIR REPORT 391-4 C C C C MAIN LOBE GAUSSIAN, ANTENNA DIAMETER 4.5 METERS, MODIFIED FOR US ONLY IMPLICIT INTEGER\*4(I-N), REAL\*8(A-H, O-Z) С COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С DPR = PR\*DEGREE X = PR/P0

P2 = 10.\*\*((29.+10.)/25.)С IF (X.LE.1.) THEN DISC = G - 12.\*X\*XGO TO 80 ELSE IF (DPR .GE. P2) THEN DISC = -10. GO TO 80 END IF С DISC = G - 12.\*X\*XD1 = 29. - 25.\*DLOG10(DPR)IF (D1 .GE. DISC) DISC = D1 С 80 RETURN END С SUBROUTINE PINER5 (PR, P0, F, G, DISC) С EARTH REVEIVER PATTERN FROM RARC-83 P.115 CURVE B С Č C **BSS PATTERN** IMPLICIT INTEGER\*4(I-N), REAL\*8(A-H, O-Z) С COMMON /CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С X = PR/P0С IF (X .LE. 0.25) GOTO 10 IF (X .LE. 0.94) GOTO 12 IF (X .LE. 18.88) GOTO 14 С DISC = G - 43.2RETURN С 10 DISC = GRETURN С 12 DISC = G -12. \* X \* X RETURN С 14 DISC = G - 11.3 - 25. \* DLOG10(X)RETURN С • END С SUBROUTINE XPTNER1 (PR, P0, G, DISC) С C CROSS POLARIZATION RECEIVER PATTERN, BSS С IMPLICIT REAL \*8 (A-H, O-Z) С X = PR/P0IF (X.LE.0.25) GO TO 40 IF (X.LE.0.44) GO TO 50 IF (X.LE.1.28) GO TO 60 IF (X.LE.3.22) GO TO 70 IF (X.LE.5.60) GO TO 80 IF (X.LE.18.88) GO TO 90
С	
	DISC = G-43.2
c	GO 10 100
40	DISC = G-25. GO TO 100
С	
50	DISC = $G-(30.+40.*DLOG10(1.0-X))$ GO TO 100
С	
60	DISC = G-20. GO TO 100
С	
70	DISC = G-(17.3+25.*DLOG10(X)) GO TO 100
С	
80	DISC = G-30. GO TO 100
С	
90	DISC = G-(11.3+25.*DLOG10(X))
<b>ັ</b> 100	RETURN EN D

•

#### **APPENDIX B**

#### CONCAVE, QUASI-CONCAVE AND PSEUDO-CONCAVE FUNCTIONS

The content in this appendix is from the book "Nonlinear Programming" written by Olvi L. Mangasarian [105]. All the page numbers appearing in the content are referred to this book. Here only the concave functions are discussed; the same discussions apply to convex functions with obvious substitution.

**Definition of convex set** (p. 39)

A set  $ICR^{n}$  is a convex set if, for x,y  $\in I$ , a  $\in R$ , 0 <a <1, one has (1-a)x+ay  $\in I$ , (B.1)

here  $R^n$  is the set of n-dimensional vector space, R is the set of real numbers.

## Definition of concave function (p. 56)

A numerical function f defined on a set IcR<sup>n</sup> is said to be concave at x ɛI if, for y ɛI, 0<a<1, (1-a)x+ay ɛI, one has

 $(1-a)f(x)+af(y) \le f[(1-a)x+ay];$  (B.2)

f is said to be concave on I if it is concave at each  $x \in I$ .

Definition of strictly concave function (p. 57)

A numerical function f defined on a set  $ICR^n$  is said to be strictly concave at xel if, for yel, x=y, 0<a<1, (1-a)x+ayel, one has

$$(1-a)f(x)+af(y) < f[(1-a)x+ay]$$
; (B.3)

f is said to be strictly concave on I if it is strictly concave at each  $x \in I$ .

#### Definition of quasi-concave function (p. 132)

A numerical function f defined on a set  $ICR^n$  is said to be quasi-concave at xeI if, for yeI, f(x) < f(y), 0 < a < 1, (1-a)x+ayeI, one has

f(x) < f[(1-a)x+ay]; (B.4) f is said to be quasi-concave on I if it is quasi-concave at each xeI.

# Definition of strictly quasi-concave function (p. 137)

A numerical function f defined on a set  $ICR^n$  is said to be strictly quasi-concave at xel if, for yel, f(x) < f(y), 0 < a < 1,  $(1-a)x + ay \in I$ , one has

$$f(x) < f[(1-a)x+ay]$$
; (B.5)

f is said to be strictly quasi-concave on I if it is strictly quasiconcave at each  $x \in I$ .

#### **Theorem 1** (p. 139)

Let f be a numerical function defined on the convex set I in  $R^n$ , and let xeI be a local maximum. If f is strictly quasi-concave at x, then f(x) is a global maximum of f on I.

#### **Definition of pseudo-concave function** (p. 141)

Let f be a numerical function defined on some open set in  $\mathbb{R}^n$ containing the set I. f is said to be pseudo-concave at xeI if it is differentiable at x, and for yeI,  $\nabla f(x)(y-x)<0$ , one has

$$f(y) < f(x)$$
; (B.6)

f is said to be pseudo-concave on I if it is pseudo-concave at each xeI.

**Theorem 2** (p. 143)

Let I be a convex set in R<sup>n</sup>, and let f be a numerical function defined on some open set containing I. If f is pseudo-concave on I, then f is strictly quasi-concave on I and hence also quasi-concave on I. The converse is not true.

**Theorem 3** (p. 144)

Let f be a numerical function defined on some open set I in  $R^n$ , let x $\in$ I, and let f be differentiable at x. If f is concave at x, then f is pseudo-concave at x, but not conversely.

## **Theorem 4** (p. 145)

Let I be a convex set in  $R^n$ , and let f be a numerical function defined on some open set containing I. If f is pseudo-concave on I, then each local maximum of f on I is also a global maximum of f on I.

A final note: a function that is strictly concave is also concave, a function that is concave is also pseudo-concave, a function that is pseudo-concave is also strictly quasi-concave, a function that is strictly quasi-concave is also quasi-concave; the converse is not true.

# APPENDIX C

.



ARG=62.	B	Ø	L=	6	8	•

•











PRG=68.

B0L=62.



PRU=68.





.



PRU=68.

212

•

•



•

.



PRU=62.

BØL=68.



.

# APPENDIX D

•

# $\Delta S$ calculation code

C*** C	>> MAIN PROGRAM << This is to calculate the necessary satellite spacing									
C	FOR TWO SERVICE AREAS.									
č	SUBROUTINES SAME AS MINI-SOUP PROGRAM, EXCEPT DI MEN SION OF									
C C****	SERVICE AREA IS TWO									
Ċ										
с	IMPLICIT REAL*8(A-H,O-Z)									
6	CHARACTER*6 NAMESA									
•	COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, PFD, ALOGE, ALN10, COIMIN, COISING									
c	COMMON / PARAMS/ NUMSAR. NAMESA (2,2), NTPSA (2), CPH IO (2)									
C	COMMON /VECTOR/ DSLON(2), RSLON(2), XD(2), YO(2),									
с <sup>.</sup>	2 XOAC(2), YOAC(2), ZOAC(2), ROAC(2)									
0	COMMON /VARBLS/ FREQ(2), IPOLAR(2), GAINR(2), GAINT(2), L EIRP(2), IPTNST(2), IPTNER(2)									
	COMMON /MINELL/ BCLAT(2),BCLON(2),DBCLAT(2),DBCLON(2), REFLAT(2),REFLON(2),AXR(2), ORIENT(2),AXMAJ(2)									
Ċ	COMMON /TPOINT/ RELON(2.20), RELAT(2.20), DELON(2.20), 1 DELAT(2.20), XE(2.20), YE(2.20), ZE(2.20)									
	COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO									
с -	COMMON /REAL/ PIKJ, PKKJ, PW FQM, FW DRCK, YFW DRC, YFW DRX, 1 XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ									
C	COMMON / SRCE/ DHGN(2,20)									
C****	***************************************									
-	OPEN (UNIT=20,FILE='INFUT0.DAT',TYPE='OLD') OPEN (UNIT=6.FILE='DSOUT.DAT',TYPE='NEW')									
С	CALL ICONST CALL INPUTO									
С	DO 2 $K = 1, NUMSAR$									
2	EIRP(K) = PFD+10.*DLOG10(4.*PI*ROAC(K)*ROAC(K))-ERDB CONTINUE									
C	CALL ZFUNCT									
С										
c	STOP END									
~	SUBROUTINE ZFUNCT									
C***	>> THIS ROUTINE IS THE OVERALL CONTROL ROUTINE FOR <<									

C\*\* С IMPLICIT REAL\*8(A-H, O-Z) С CHARACTER\*6 NAMESA С COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING C COMMON / PARAMS/ NUMSAR, NAMESA(2,2), NTPSA(2), CPH I0(2) С COMMON /VECTOR/ DSLON(2), RSLON(2), XO(2), YO(2), 1 ROAIKJ, XOAC(2), YOAC(2), ZOAC(2), ROAC(2) 2 С COMMON /VARBLS/ FREQ(2), IPOLAR(2), GAINR(2), GAINT(2), 1 EIRP(2), IPTNST(2), IPTNER(2) С COMMON /MINELL/ BCLAT(2), BCLON(2), DBCLAT(2), DBCLON(2), REFLAT(2), REFLON(2), AXR(2), 1 1 ORIENT(2), AXMAJ(2) С COMMON /TPOINT/ RELON(2.20), RELAT(2.20), DELON(2,20), 1 DELAT(2,20), XE(2,20), YE(2,20), ZE(2,20) С COMMON /ANGLES/ YPHIT, YPHIR. PHITK, YPHIO С COMMON / REAL/ PIKJ, PKKJ, PWFQM, PWDRCK, YPWDRC, YPWDRX, 1 XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ С COMMON / SRCH/ DMGN(2,20)\* C\*\* С C\*\*\* >> INITIALIZE PARAMETER С DO 10 I=1,NUMSAR CALL REFCAL(I) 10 CONTINUE. С C\*\*\* >> OUTER SUMMATION (OVER K) FOR ALL SERVICE AREAS << С DO 1000 K = 1, NUMSAR JNTP = NTPSA(K)WRITE(6,705) NAMESA(K,1), DSLON(K) С C\*\*\* >> MIDDLE SUMMATION (OVER J) FOR ALL TEST POINTS IN AREA K << С DO 900 J = 1.JNTPCALL KPHI (K, J) CALL XPHIO (K,K,J) CALL KPWDRC (K, J) CALL XPWFQ (FREQ(K), FREQ(K)) CALL XPOWER (K,K,J) Č\*\*\* >> CALCULATE INTERFERENCE POWER SUMP=0. DO 500 I = 1, NUMSAR IF (I.EQ.K) GO TO 500 CALL ZPHI (I, K, J)

```
CALL XPHIO (I, K, J)
                IF (IPOLAR(I).EQ. IPOLAR(K)) THEN
                   CALL ZPWDRC (I,K,J)
                   ELSE
                   CALL ZPWDRX (I,K,J)
                END IF
                CALL XPWFQ (FREQ(K), FREQ(I))
                CALL XPOWER (I,K,J)
                COI = PKKJ-PIKJ
                DMGN(K,J) = COI - COISING
С
       WRITE (6,706) DELON (K, J), DELAT (K, J), NAMESA (I, 1), PIKJ, COI, DMGN (K, J)
 500
             CONTINUE
С
 900
     CONTINUE
1000 CONTINUE
С
 705
     FORMAT (//,12X,'TEST COUNTRY :',A6,5X,'SATELLITE :',F8.2,//,15X,
     1'TEST POINT',10X,'INT. SAT.',2X,'INT. FWR',3X,'C/I (dB)',
     25X, 'MARGIN')
706
     FORMAT(/,15X,F7.2,2X,F7.2,5X,A6,4X,F8.2,4X,F6.2,6X,F6.2)
      RETURN
      END
С
С
        SUBROUTINE SEPAR
С
С
      THIS IS TO FIND THE MINIMAL REQUIRED SATELLITE SPACING FOR TWO
C
       SERVICE AREAS
Ċ
      **************
С
С
      IMPLICIT REAL*8(A-H,O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                       PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(2.2), NTPSA(2), CPHI0(2)
C
      COMMON /VECTOR/ DSLON(2), RSLON(2), XO(2), YO(2),
     1
                       ROAIKJ,
     2
                       XOAC(2), YOAC(2), ZOAC(2), ROAC(2)
С
      COMMON /VARBLS/ FREQ(2), IPOLAR(2), GAINR(2), GAINT(2),
     1
                       EIRP(2), IPTNST(2), IPTNER(2)
С
      COMMON /MINELL/ BCLAT(2), BCLON(2), DBCLAT(2), DBCLON(2),
                       REFLAT(2), REFLON(2), AXR(2),
     1
     1
                       ORIENT(2),AXMAJ(2)
С
      COMMON /TFOINT/ RELON(2,20), RELAT(2,20), DELON(2,20),
     1
                       DELAT(2,20), XE(2,20), YE(2,20), ZE(2,20)
С
      COMMON /ANGLES/ YPHIT, YPHIR, PHITK, YPHIO
С
      COMMON / REAL/
                       PIKJ, PKKJ, FWFQM, FWDRCK, YFWDRC, YFWDRX,
     1
                       XOAKKJ, YOAKKJ, ZOAKKJ, ROAKKJ
С
```

```
COMMON / SRCH/ DMGN(2,20)
С
C
       ******************************
Ĉ
        NTP1 = NTPSA(1)
        NTP2 = NTPSA(2)
C
      SELECT WORST MARGIN AMONG ALL C/I VALUES AT ALL TEST POINTS
C
C
        RMIN1 = DMGN(1,1)
        DO J=2,NTP1
         RMIN1 = DMIN1(RMIN1,DMGN(1,J))
        END DO
        RMIN2 = DMGN(2,1)
        DO J=2,NTP2
         RMIN2 = DMIN1(RMIN2,DMGN(2,J))
        END DO
С
С
       NO SATELLITE SPACING REQOUIRED
С
        IF (RMIN1.GE.O..AND.RMIN2.GE.O.) THEN
          WRITE(6,1)
 1
          FORMAT (//, 11X, ' **** SATELLITE SEPARATION NOT NEEDED ****')
          RETURN
        END IF
С
С
       CALCULATE TOPOCENTRIC AND GEOCENTRIC ANGLE (SATELLITE SPACING)
С
         FROM WORST TEST POINT
Ç
       PRECAUSION MADE IF TWO SYSTEMS USE DIFFERENT RECEIVING PATTERNS
С
        IF(IPTNER(1).EQ.IPTNER(2))THEN
          IF (RMIN1.LE.RMIN2) THEN
           CALL MINMGN(1,J1,RMIN1)
           WRITE (6,2) RMIN1, NAMESA(1,2), DELON(1,J1), DELAT(1,J1)
           CALL PTNANG(1, RMIN1, TOPOANG)
           CALL GEOANG(2,1,J1,TOPOANG, DELTAS)
          ELSE
           CALL MINMGN(2, J2, RMIN2)
           WRITE (6,2) RMIN2, NAMESA(2.2), DELON(2, J2), DELAT(2, J2)
           CALL PTNANG(2, RMIN2, TOPOANG)
           CALL GEOANG(1.2, J2, TOPOANG, DELTAS)
          END IF
        ELSE
          CALL MINMGN(1, J1, RMIN1)
          WRITE (6,2) RMIN1, NAMESA(1,2), DELON(1,J1), DELAT(1,J1)
          CALL PTNANG(1, RMIN1, TOPOANG1)
          CALL GEOANG(2,1,J1,TOPOANG1,DELTAS1)
          CALL MINMGN(2, J2, RMIN2)
          WRITE (6,2) RMIN2, NAMESA(2,2), DELON(2, J2), DELAT(2, J2)
          CALL PTNANG(2, RMIN2, TOPOANG2)
          CALL GEOANG(1,2,J2,TOPOANG2,DELTAS2)
          DELTAS = DMAX1(DELTAS1, DELTAS2)
        END IF
С
        WRITE(6,100) DELTAS. DSLON(1), COISING
 2
        FORMAT (//,11X,'WORST MARGIN IS ',F6.2,' AT',A6,'(',
        F7.2,',',F7.2,')')
FORMAT(/,11X,'SATELLITE SEPARATION : ',F5.2,' AT ',
     1
 100
     1
        F7.2,' FOR C/I ',F4.1,' dB')
С
```

```
219
```

RETURN END С SUBROUTINE MINMGN(K1, J1, RMIN) С Ĉ THIS IS TO FIND THE MINIMUM MARGIN AMONG THE TEST POINTS С IMPLICIT REAL\*8(A-H, O-Z) С CHARACTER\*6 NAMESA С COMMON / CONSTS/ E, PI, RADIAN. DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С COMMON / PARAMS/ NUMSAR, NAMESA(2,2), NTPSA(2), CPHI0(2) С COMMON / SRCH/ DMGN(2,20) С DO J=1,NTPSA(K1) IF(DMGN(K1,J).LE.RMIN) THEN JI = JRETURN END IF END DO RETURN END С SUBROUTINE PINANG(K1, RMIN, TOPOANG) C C THIS IS TO CALCULATE THE TOPOCENTRIC ANGLE (FROM GROUND RECEIVING REFERENCE PATTERN) NECESSARY TO PROVIDE С С THE DISCRIMINATION Ĉ IMPLICIT REAL\*8(A-H, O-Z) С CHARACTER\*6 NAMESA С COMMON / CONSTS/ E, PI, RADIAN. DEGREE, GCR, ER, ERDB, EAP, 1 PFD, ALOGE, ALN10, COIMIN, COISING С COMMON / PARAMS/ NUMSAR, NAMESA(2,2), NTPSA(2), CPHI0(2) C COMMON /VARBLS/ FREQ(2), IPOLAR(2), GAINR(2), GAINT(2), 1 EIRP(2),IPTNST(2),IPTNER(2) С COMMON / SRCH/ DMGN(2,20) С IF (IPOLAR(1).NE. IPOLAR(2)) THEN CALL XRPTNER1 (PR, CPHIO(K1), GAINR(K1), RMIN) GO TO 60 END IF С GO TO (51,53,55,57,59), IPTNER(K1) C 51 CALL RPINERI (PR, CPHIO(K1), FREQ(K1), GAINR(K1), RMIN) GO TO 60 53 CALL RPINER2 (PR. CPHIO(K1), FREQ(K1), GAINR(K1), RMIN) GO TO 60 55 CALL RPINER3 (PR. CPHIO(K1), FREQ(K1), GAINR(K1), RMIN) GO TO 60

```
57
        CALL RPINER4 (PR, CPHI0(K1), FREQ(K1), GAINR(K1), RMIN)
        GO TO 60
        CALL RPINERS (PR, CPHI0(K1), FREQ(K1), GAINR(K1), RMIN)
 59
C
        TOPOANG = PR * DEGREE
 60
        RETURN
        END
С
        SUBROUTINE GEOANG(I, K, J, TOPOANG, DELTAS)
С
С
        THIS IS TO ITERATE TO CALCULATE THE NECESSARY GEOCENTRIC
Ċ
          ANGLE FOR THE REQUIRED DISCRIMINATION
С
      IMPLICIT REAL*8(A-H,O-Z)
С
      CHARACTER*6 NAMESA
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                       PFD, ALOGE, ALN10, COIMIN, COISING
С
      COMMON / PARAMS/ NUMSAR, NAMESA(2,2), NTPSA(2), CPHI0(2)
С
      COMMON /VECTOR/ DSLON(2), RSLON(2), XO(2), YO(2),
                       ROAIKJ,
     1
2
                        XOAC(2), YOAC(2), ZOAC(2), ROAC(2)
С
      COMMON /MINELL/ BCLAT(2), BCLON(2), DBCLAT(2), DBCLON(2),
                        REFLAT(2), REFLON(2), AXR(2),
     1
     1
                        ORIENT(2), AXMAJ(2)
С
      COMMON /TPOINT/ RELON(2,20), RELAT(2,20), DELON(2,20),
                        DELAT(2,20), XE(2,20), YE(2,20), ZE(2,20)
     1
С
                       DMGN(2,20)
      COMMON / SRCH/
С
        DSLONG = DSLON(I)
С
        IF (DBCLON(K).GE.DBCLON(I)) THEN
           DELTA = 0.01
          DSK = DSLONG+TOPOANG/2.
          DSI = DSLONG-TOPOANG/2.
        ELSE
           DELTA = -0.01
           DSK = DSLONG-TOPOANG/2.
          DSI = DSLONG+TOPOANG/2.
        END IF
С
 20
        DSK = DSK-DELTA
        DSI = DSI+DELTA
        RSK = DSK*RADIAN
        RSI = DSI*RADIAN
        XOAK = XE(K, J)-GCR*DCOS(RSK)
        YOAK = YE(K, J)-GCR*DSIN(RSK)
         ZOAK = ZE(K, J)
        ROAK = DSQRT (XOAK*XOAK+YOAK*YOAK+ZOAK*ZOAK)
        XOAI = XE(K, J) - GCR * DCOS(RSI)
        YOAI = YE(K, J) -GCR *DSIN(RSI)
         ZOAI = ZE(K, J)
        ROAI = DSQRT(XOAI*XOAI+YOAI*YOAI+ZOAI*ZOAI)
        ARG = (XOAK*XOAI+YOAK*YOAI+ZOAK*ZOAI)/(ROAK*ROAI)
```

```
TOPO = DACOS (ARG) *DEGREE
         IF (TOPO. GT. TOPOANG) GOTO 20
         DELTAS = DABS(DSK-DSI)+0.02
         RETURN
         END
С
         SUBROUTINE RPINERL (PR, PO, F, G, DISC)
Ç
      FSS EARTH RECEIVER REFERENCE PATTERN FROM CCIR REPORT 391-4
ANTENNA DIAMETER 3 METERS, MAIN LOBE NOT GAUSSIAN
Ċ
С
C
      IMPLICIT REAL*8(A-H, O-Z)
С
      COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                         PFD, ALOGE, ALN10, COIMIN. COISING
С
       D = 3.
      WAVEL = 300./F
       X1 = D/WAVEL
       G1 = 2. + 15.* DLOG10(X1)
С
       IF (DISC.GE.(G1-G)) GO TO 50
       IF (DISC.GE.(-G-10.)) GO TO 60
С
       PR = PI
      GO TO 80
C
  50
      PR = RADIAN * DSQRT(-DISC*400./(X1*X1))
       GO TO 80
С
      PR = RADIAN*10.**(-(DISC+G-32.)/25.)
  60
С
  80
      RETURN
       END
С
         SUBROUTINE RPINER2 (PR, P0, F, G, DISC)
C
C
       FSS EARTH RECEIVER PATTERN FROM CCIR REPORT 391-4
         MAIN LOBE GAUSSIAN, ANTENNA DIAMETER 3 METERS,
MODIFIED FOR NON US COUNTRIES
С
С
С
       IMPLICIT REAL *8(A-H.O-Z)
С
       COMMON / CONSTS/ E, PI, RADIAN. DEGREE, GCR, ER, ERDB, EAP,
      1
                         PFD, ALOGE, ALN10, COIMIN, COISING
C
       IF (DISC.GE.-3.) THEN
       PR = P0 * DSQRT(-DISC/12.)
       GO TO 80
       ELSE IF (DISC.LE.-(G+10.)) THEN
       PR = PI
       GO TO 80
       END IF
С
       PRI = PO * DSORT(-DISC/12.)
       PR2 = RADIAN * 10.**(-(G+DISC-32.)/25.)
       PR = DMAX1(PR1, PR2)
С
  80
      RETURN
       END
```

```
С
       SUBROUTINE RPINER3 (PR. PO, F. G. DISC)
ç
С
       FSS EARTH RECEIVER PATTERN FROM CCIR REPORT 391-4
Ĉ
         MAIN LOBE GAUSSIAN, ANTENNA DIAMETER 4.5 METERS,
č
         MODIFIED FOR US ONLY
       IMPLICIT REAL*8(A-H, O-Z)
.C
       COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                        PFD, ALOGE, ALN10, COIMIN, COISING
С
       IF (DISC.GE.-12.) THEN
       PR = P0 * DSQRT(-DISC/12.)
       GO TO 80
       ELSE IF (DISC.LE.-(G+10.)) THEN
       PR = PI
       GO TO 80
       END IF
С
       PRI = PO * DSORT(-DISC/12.)
       PR2 = RADIAN + 10.**(-(G+DISC-29.)/25.)
       PR = DMAX1(PR1, PR2)
С
  80
      RETURN
       END
С
       SUBROUTINE RPINER4 (PR, P0, F, G, DISC)
С
Ĉ
       FSS EARTH RECEIVER PATTERN FROM CCIR REPORT 391-4
Ĉ
         MAIN LOBE GAUSSIAN, ANTENNA DIAMETER 4.5 METERS,
         MODIFIED FOR US ONLY
С
       IMPLICIT REAL*8(A-H.O-Z)
С
       COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                        PFD, ALOGE, ALN10, COIMIN, COISING
С
       IF (DISC.GE.-12.) THEN
PR = P0 * DSQRT(-DISC/12.)
       GO TO 80
       ELSE IF (DISC.LE.-(G+10.)) THEN
       PR = PI
       GO TO 80
       END IF
С
       PRI = PO * DSORT(-DISC/12.)
      PR2 = RADIAN * 10.**(-(G+DISC-29.)/25.)
PR = DMAX1(PR1,PR2)
Ċ
  80
       RETURN
       END
С
       SUBROUTINE RPINER5 (PR, P0, F, G, DISC)
С
Č
C
       BSS PATTERN, RARC-83.CPM, P.115 CURVE-B,
         ANTENNA DIAMETER 1 METER
Ĉ
       IMPLICIT REAL *8(A-H, O-Z)
С
```

```
223
```

```
COMMON / CONSTS/ E, PI, RADIAN, DEGREE, GCR, ER, ERDB, EAP,
     1
                       PFD, ALOGE, ALN10, COIMIN, COISING
С
      IF (DISC.GE.-10.6032) THEN
      PR = P0 + DSQRT(-DISC/12.)
      GO TO 80
      ELSE IF (DISC.LE.-43.2) THEN
      PR = PI
      GO TO 80
      END IF
С
      PR = P0 * 10.**(-(DISC+11.3)/25.)
C
80
      RETURN
      END
С
      SUBROUTINE XRPTNER1 (PR, P0, G, DISC)
С
С
      CROSS FOLARIZATION RECEIVER PATTERN
С
      IMPLICIT REAL*8(A-H, O-Z)
C
      X = PR/P0
      IF (DISC.GE.-20.) GO TO 60
      IF (DISC.GE.-30.) GO TO 70
      IF (DISC.GE.-43.2) GO TO 80
С
      PR = PI
      GO TO 100
С
 60
      PR = 0.
      GO TO 100
С
 70
      PR = 10.**(-(17.3+DISC)/25.) * P0
      GO TO 100
С
80
      PR = 10.**(-(11.3+DISC)/25.) * P0
С
 100
      RETURN
      END
```

#### APPENDIX E

#### FORMULATIONS OF MIXED-INTEGER AND LINEAR PROGRAMS

#### A. ALGORITHMS

A mixed integer program (MIP) can be solved by a branch-and-bound algorithm [66]. In such an algorithm, a linear objective function is to be optimized; the constraints of the problem are expressed as linear equalities or inequalities. Some, but not necessarily all, of the decision variables are integers. The set of feasible solutions that satisfy the constraints constitutes the feasible region. For our purpose, we can assume that the integer variables are bounded. Because the integer variables have a finite number of feasible values, the number of feasible solutions is finite; therefore an enumerative approach can be used to theoretically test all the feasible solutions in order to find the globally optimal solution(s).

To perform the enumeration by the branch-and-bound algorithm, the set of feasible solutions can be structured as a tree, and every branch represents one possible value of a particular integer variable. For the branch-and-bound concept, "branching" means testing a path that leads to a subset of feasible solutions, "bounding" means calculating the upper and lower bounds of the objective function value associated with the tested path. In the enumerative process, the upper and lower bounds of the objective function value are updated whenever more favorable values

are found in the branch-and-bound process. In the branch-and-bound process a path is tested against the updated upper and lower bounds: it finds a more favorable upper or lower bound of the objective function value and updates it, or it terminates testing that path and all its associated feasible solutions once it determines that this path can not yield a more favorable upper or lower bound of the objective function value. The process terminates when the updated upper and lower bounds are equal, or when it determines that an optimal solution does not exist. All the feasible solutions will have been considered implicitly, and hopefully very few will have been explicitly examined. A globally optimal solution is guaranteed, if one exists, by this process.

The linear program (LP) is commonly solved by the simplex method [58]. In this program a linear objective function is to be optimized; the constraints of the problem are expressed as linear equalities or inequalities. All the decision variables are continuous variables, and they must have nonnegative values. The set of feasible solutions constitutes a feasible region that is a convex set; its boundaries are the hyperplanes representing the linear constraints and nonnegativity restrictions. Because the objective function and the constraints are all linear equations, a locally optimal solution is always at a vertex which is the intersection of the bounding hyperplanes. The simplex method examines a sequence of locally optimal feasible solutions of the linear program. Each solution examined shares at least one boundary with the previous one, and has an objective function value no less

favorable than that of the previous solution. The process terminates when it is determined that no improved solution can be found.

The simplex method can be modified to handle nonlinear complementarity constraints through the use of restricted basis entry: when a complementary variable enters the basis at a non-zero value, its complement is forced to be non-basic and cannot enter the basis (except when the variable leaves). The effect of this modification is that the continuous feasible region is divided into many distinct subregions. Although the simplex method can still work, it only guarantees a local, but not necessarily a global, optimum, provided a feasible solution is found.

As the number of satellites increases, the computational time needed to find a solution typically increases exponentially for the MIP technique, but only polynomially for the restricted basis LP (RBLP) technique. Therefore, the MIP technique may take a prohibitively long time to solve a large problem; and the RBLP technique becomes an acceptable alternative, even though approximate, rather than exact, solutions are found.

#### **B. PARAMETERS AND VARIABLES**

The coordinate system here is in the reverse longitude direction of the common global system, hence the longitude values increase as one moves in the westerly direction. Or simply speaking, the new coordinate system uses the magnitude of west longitude; in this way, there are only non-negative variables in both of the new formulations.

The parameters in the formulations are:

The decision variables are:

 $x_j$ : relative location of satellite j with respect to  $E_j$ ,  $p_{ij}(n_{ij})$ : degrees west(east) of satellite i that satellite j is located,

 $x_j^+(x_j^-)$  : degrees west(east) of its preferred location that satellite j is located,

Y : length of the occupied orbital arc.

Note that the nonnegative variable  $p_{ij}$  alone can not represent the separation between satellites i and j, and another nonnegative variable,  $n_{ij}$ , is needed when i is east of j. Therefore when satellite i is west of j, the value of  $p_{ij}$  is positive, and  $n_{ij}$  should be set equal to zero; when satellite i is east of j,  $n_{ij}$  is positive and  $p_{ij}$  should be zero. Also note from the definition of  $x_j$ , the coordinate system for every satellite is re-originated at the eastern-most bound,  $E_j$ .

#### C. FORMULATION I

If the optimal criterion is to minimize the total amount of orbital arc occupied by the satellites to be synthesized, the MIP formulation is

$$Minimize f = Y$$
(E.1)

subject to

$x_{i} - x_{j} - p_{ij} + n_{ij} = 0,$	for i < j	(E.2)
p <sub>ij</sub> + n <sub>ij</sub> > ∆S <sub>ij</sub> ,	for i < j	(E.3)
$x_j < W_j - E_j,$	for all j	(E.4)
p <sub>ij</sub> + n <sub>ij</sub> - Y < 0,	for i < j	(E.5)
× <sub>j</sub> > 0,	for all j	(E.6)
p <sub>ij</sub> , n <sub>ij</sub> ≥ 0,	for i < j	(E.7)
Y > 0,		(E.8)
(E - ₩)•x <sub>ij</sub> + p <sub>ij</sub> < 0,	for i < j	(E.9)
(W - E)•x <sub>ij</sub> + n <sub>ij</sub> < (W - E),	for i < j	(E.10)
× <sub>ij</sub> ε {0,1},	for i < j	(E.11)

Equations (E.9) and (E.10) guarantee that

$$p_{ij} < 0, \text{ or } n_{ij} < 0.$$
 (E.12)

Together with Equation (E.7), one has

$$p_{ij} = 0, \text{ or } n_{ij} = 0.$$
 (E.13)

If the optimal solution can be found, the optimal values of the variables  $x_j$ 's specify the optimal orbital locations for the satellites. Otherwise, the code will tell the user that a feasible solution does not exist.

It is possible that the objective is only to have a feasible solution that satisfies the C/I protection requirements, as described in Chapter IV. Then one could reformulate the objective function of Equation (E.1) and ignore the variable Y, Equations (E.5) and (E.8). The calculation process will either stop when it finds a feasible solution, or determines that none exists.

Also, the same formulation (Equations (E.1) through (E.11)) is still applicable if the system requirement is to have the maximum C/I results for all the service areas, and there is no interest in the conservation of the orbit resource. One could progressively adjust the C/I protection requirement and repeat the  $\Delta S$  and MIP calculations until the resulting scenario uses up the whole feasible arc. This result is the scenario that offers the maximum C/I.

#### D. FORMULATION II

For the same objective as stated above, the LP formulation with the nonlinear side constraints is

$$Minimize f = Y (E.14)$$

subject to

$x_{i} - x_{j} - p_{ij} + n_{ij} = 0,$	for i < j	(E.15)
p <sub>ij</sub> + n <sub>ij</sub> ≥ ΔS <sub>ij</sub> ,	for i < j	(E.16)
$x_j < W_j - E_j$	for all j	(E.17)
p <sub>ij</sub> + n <sub>ij</sub> − Y < 0,	for i < j	(E.18)
x <sub>j</sub> > 0,	for all j	(E.19)
p <sub>ij</sub> , n <sub>ij</sub> > 0,	for i < j	(E.20)
Y > 0,		(E.21)
$p_{ij} \cdot n_{ij} = 0,$	for i < j	(E.22)

The solution to this problem is an orbital assignment.

In this formulation, Equation (E.22) is not a linear equation, thus the simplex method needs to be modified through the use of restricted basis entry: the variable  $p_{ij}$  can not be a basic variable if  $n_{ij}$  is a basic variable, and vice versa. Although the simplex method can still work, it only guarantees a locally optimal solution, provided a feasible solution is found.

#### E. FORMULATION III

It is possible that every administration has a preferred satellite location and hopes the actual assigned location will be near the preferred location. Solutions become less and less attractive as the actual location becomes further and further removed from the preferred location. A suitable objective is to minimize the sum of the absolute deviations of the satellites' actual locations from their preferred locations, i.e., to minimize the total deviation. The MIP formulation is

Minimize  $f = \sum_{j} (x_j^+ + x_j^-)$  (E.23) subject to

$x_{j} - x_{j}^{+} + x_{j}^{-} = d_{j},$	for all j	(E.24)
$x_{i} - x_{j} - p_{ij} + n_{ij} = 0,$	for i < j	(E.25)
Pij + n <sub>ij</sub> > ∆S <sub>ij</sub> ,	for i < j *	(E.26)
$x_j < W_j - E_j$ ,	for all j	(E.27)
xj, xj⁺, xj⁻ > 0,	for all j	(E.28)
Pij, n <sub>ij</sub> > 0,	for i < j	(E.29)
$(E - W) \cdot x_{ij} + p_{ij} < 0,$	for i < j	(E.30)
$(W - E) \cdot x_{ij} + n_{ij} < (W - E),$	for i < j	(E.31)
x <sub>ij</sub> ε{0,1},	for i < j	(E.32)

The optimal values of the variables  $x_j$ 's prescribe optimal locations for the satellites which minimize the total deviation of the prescribed locations from the preferred locations.

#### F. FORMULATION IV

For the same objective, the LP formulation is shown below. As before, nonlinear side constraints are to be enforced.

$$\begin{array}{ll} \text{Minimize } f = \sum_{j} (x_j^+ + x_j^-) \\ i \end{array} \tag{E.33}$$

subject to

$x_{j} - x_{j}^{+} + x_{j}^{-} = d_{j},$	for all j	(E.34)
x <sub>i</sub> - x <sub>j</sub> - p <sub>ij</sub> + n <sub>ij</sub> = 0,	for i < j	(E.35)
Pij + nij > ∆Sij,∵	for i < j	(E.36)
×j < Wj - Ej,	for all j	(E.37)
$x_{j}, x_{j}^{+}, x_{j}^{-} > 0,$	for all j	(E.38)
p <sub>ij</sub> , n <sub>ij</sub> ≥ 0,	for i < j	(E.39)
Pij.• nij = 0,	for i < j	(E.40)

An approximate solution can be found by solving this problem with the simplex method with restricted basis entry, provided a feasible solution is found.

#### G. COMPARISON BETWEEN FORMULATIONS III AND IV

Solutions were obtained when a synthesis test problem was solved using formulations III and IV. The test problem includes six administrations in South America: Argentina, Bolivia, Chile, Paraguay, Peru, Uruguay (denoted as ARG, BOL, CHL, PRG, PRU, and URG respectively). Three sets of preferred satellite locations are considered and listed in Table E.1.

# Satellite preferred locations of six administrations

country	ARG	BOL	CHL	PRG	PRU	URG
case 1	95	95	95	95	95	95
case 2	110	110	110	110	110	110
case 3	87.5	92.5	97.5	87.5	102.5	82.5

# Table E.2

# $\Delta S$ parameters of six administrations

۵S	ARG	BOL	CHL	PRG	PRU	URG
ARG	*	4.17	4.19	4.32	1.41	4.14
BOL		*	4.57	4.04	4.26	0.94
CHL			*	2.00	3.04	1.59
PRG				*	1.10	2.46
PRU					*	0.37
URG						*
The  $\Delta S$  matrix for these six countries is in Table E.2. The resulting assignments, together with the total occupied arc Y, the total deviation Z of the prescribed locations from the preferred locations, and the C.P.U. times in seconds are listed in Table E.3.

It is clear that the solutions obtained by solving the MIP formulation are better than those found by solving the LP formulation. The MIP solutions could never be worse than the corresponding LP solutions, but more computer time is required to solve the MIP formulation.

## Table E.3

Mixed-integer and linear program results

	cas	se 1 case		2 case 3		e 3	
satellite	MIP	LP	MIP	LP	MIP	LP	
ARG	88.68	105.74	101.35	110.00	88.76	101.26	
BOL	99.57	101.57	97.18	104.33	92.93	92.50	
CHL	95.00	97.00	105.54	99.76	97.50	97.07	
PRG	93.00	95.00	107.54	97.76	84.44	87.50	
PRU	91.06	93.06	109.63	108.59	102.50	102.67	
URG	96.59	92.54	110.00	105.86	81.98	82.50	
deviation	18.42	23.71	28.76	33.69	5.27	14.36	
arc	10.89	13.20	12.82	12.24	20.52	20.17	
cpu(sec)*	25.23	1.31	13.39	1.30	2.86	1.25	

\* IBM-3081 computer

## APPENDIX F

## C/I CALCULATION OF MIXED INTEGER PROGRAM RESULT

COUNTRY	SATELLITE	(LON.)	FREQUENCY	(MHz)	
ARG	-88.6	8	4999.91	7	
BOL	-99.5	7	4883.8	ð	
CHL	-95.8	8	4620.0	8	
FRG	-93.8	Ø	4853.8	3	
PRU	-91.8	6	4353.51	3	
URG	-96.5	9	4853.8	3	
TEST COUN	TRY : ARG	SATELLITE	: -88.68		
TES	POINT	INT. SAT	. C/I (dB)	) MARGIN	(dB)
LON.	LAT.				
-65.2	$3^{-21.80}$	BOLNAA	49.83	10.83	
-66.2	0 -21.80 7 -21.80	CHLØ95	37.25	7.25	
-65 20	a -21.80	PR 40 93	41 47	9.39	
-66.21	7 -21.87	lincade	41.4/ 69 87	- 11.4/	
+65.2	a -21.80	TOTAL	33.39	30.02	
03.2.		IUIAL	33.35		
-62.8	g -22.øg	BOLØ99	41.37	11.37	
-62.8	ð -22. <i>8</i> Ø	CHLØ95	51.35	21.35	
-62.8	0 -22.ØØ	PRGØ93	32.Ø3	2.Ø3	
-62.8/	0 -22.Øð	PRUØ91	53.86	23.86	
-62.8	Ø -22.ØØ	URGØ96	67.24	37.24	
-62.8	8 -22.00	TOTAL	31.48	6.48	
-53.8	g -27.2g	BOLØ99	53.05	23.85	
-53.8	g -27.2Ø	CHLØ95	63.14	33.14	
-53.8	g -27.2ø	PRG#93	31.53	1.53	
-53.8/	g -27.2g	PRUØ91	52.74	22.74	
-53.8/	8 -27.28	URGØ96	49.37	19.37	
-52.8/	g -27.2ø	TOTAL	31.39	6.39	
-56.7	a -36.9a	BOI 099	69.73	29 72	
-55.7	a -36.9ø	CHLØ95	55.57	25 57	
-56.7	Ø -36.9Ø	PRGØ93	59.61	29.61	
-55.7	Ø -36.9Ø	PRUØ91	53.45	23.45	
-56.7	Ø -36.9Ø	URGØ96	41.77	11.77	
-55.7	Ø -36.9Ø	TOTAL	41.25	16.25	
-63.8	R -54.78	801 499	72 73	12 72	
-53.8	8 -54.78		12.13	46.73	
-63.8	a -54.70	PRCARS	57 29	27 20	
-63.8	g -54.7g	PRUØ91	52.85	22 85	
-63.8	Ø -54.7Ø	URGØ96	74.65	44.65	
-63.8	8 -54.78	TOTAL	41.65	16.65	
-00.3	v -34.00 7 _54.00		/3.38	43.38	
-62.3	u -34.00 X -54.89	CUL032	33.20	9.26	
-68.3	7 -54.87	PR 11 27 3	52 1C	38.21	
-68.3	7 -54.8Ø	IRGROS	75 74	23.10	
-68.3	8 -54.88	TOTAL	39.08	4J./4 14.Ø8	
-73.2	0 -5.0.90 7 -50.90	BOLØ99	73.25	43.25	
-/3.21	0 - 50.90 7 - 57 07	CHLØ95	35.44	5.44	
-73.2	0 - 310.910 7 _ 5/7 0/7	PRGØ93	68.41	38.41	
-73.2	מכימביי ש המיהבי ה	PRUDUI	52.91	22.91	
-/3.2		06.69.30	/5.82	45.82	

-73.2Ø	-50.90	TOTAL	35.36	1Ø.36
-71.4Ø	-39.00	BOLØ99	70.45	4Ø.45
-71.4Ø	-39.ØØ	CHL395	35.45	5.45
-71.4Ø	-39.ØØ	PRGØ93	65.76	35.76
-71.4Ø	-39.00	PRUØ91	54.18	24.18
-71.40	-39.00	URGN96	71.36	41 86
-71.40	-39.ØØ	TOTAL	35.38	10.38
-717.5Ø	-31.40	BOLØ39	7ø.35	4Ø.35
-7: 5Ø	-31.4Ø	CHLØ95	35.10	5.10
-7 <i>5</i> .5ø	-31.41	PRGØ93	61.63	31.63
-7.1.5Ø	-31.4Ø	PRUØ91	54.38	24.78
-73.5Ø	-31.40	URGØ96	68.29	38 29
-7.J.5Ø	-31.4Ø	TOTAL	35.03	10.03
-63.6Ø	-24.8Ø	BOLØ99	49.ØØ	19.ØØ
-63.6Ø	-24.8Ø	CHLØ95	35.23	5.23
-63.6Ø	-24.8Ø	PRGØ93	59.37	29.37
-63.6Ø	-24.8Ø	PRUØ91	53.21	23 21
-63.60	-24.80	URGØ96	67.38	37 29
-63.6Ø	-24.80	TOTAL	34.96	9.96

.

.

IEST COUNTRY I B	OL SAIELLIE :	-99.57	
TEST POINT -65.80 -12 -65.80 -12 -65.80 -12	INT. SAT. .20 ARGØ88 .20 CHLØ95 .20 Prgø93	C/I (dB) 7ø.32 61.ø1 64.35	MARGIN (dB) 4ø.32 31.ø1 34.85
-65.00 -12 -65.00 -12 -65.00 -12	.2Ø PRUØ91 .2Ø URGØ96 .2Ø TOTAL	45.32 66.Ø8 45.11	15.32 36.Ø8 2Ø.11
-65.5Ø -9 -65.5Ø -9 -63.5Ø -9 -65.5Ø -9 -65.5Ø -9 -63.5Ø -9 -65.5Ø -9	.80 AR GØ88 .80 CHLØ95 .80 PR GØ93 .80 PR UØ91 .80 UR GØ96 .80 TOTAL	69. <i>00</i> 59.68 63.52 42.75 66.37 42.60	39.00 29.68 33.52 12.75 36.37 17.60
$\begin{array}{rrrr} -69.00 & -11 \\ -69.00 & -11 \\ -69.00 & -11 \\ -69.00 & -11 \\ -69.00 & -11 \\ -69.00 & -11 \\ -69.00 & -11 \end{array}$	.20 ARG088 .20 CHL095 .20 PRG093 .20 PRU091 .20 URG096 .20 TOTAL	69.81 60.49 64.34 38.97 66.93 38.92	39.81 3Ø.49 34.34 8.97 36.93 13.92
-60.00 -16 -60.00 -16 -60.00 -16 -60.00 -16 -60.00 -16 -60.00 -16 -60.00 -16	.1Ø ARGØ88 .1Ø CHLØ95 .1Ø PRGØ93 .1Ø PRUØ91 .1Ø URGØ96 .1Ø TOTAL	47.93 6Ø.57 43.69 67.54 62.26 42.18	17.93 3Ø.57 13.69 37.54 32.26 17.18
-57.50 -18 -57.50 -18 -57.50 -18 -57.50 -18 -57.50 -18 -57.50 -18 -57.50 -18	.88 ARG888 .88 CHL895 .88 PRG893 .88 PRU891 .88 URG896 .88 TOTAL	41.71 59.57 38.56 66.53 59.66 36.8Ø	11.71 29.57 8.56 36.53 29.66 11.8Ø

238

.

•

TEST COUNTI	RY : CHL	SATELLITE :	-95. <i>30</i>	
TEST -69.5Ø -69.5Ø -69.5Ø -69.5Ø -69.5Ø -69.5Ø	POINT -17.50 -17.50 -17.50 -17.50 -17.50 -17.50	INT. SAT. Argø88 Bolø99 Prgø93 Pruø91 Urgø96 Total	C/I (dB) 62.92 3Ø.58 5Ø.44 3Ø.53 55.17 27.52	MARGIN (dB) 32.92 Ø.58 2Ø.44 Ø.53 25.17 2.52
-67.10 -67.10 -67.10 -67.10 -67.10 -67.10 -67.10	-23.80 -23.00 -23.00 -23.00 -23.00 -23.00 -23.00	ARGØ88 BOLØ99 PRGØ93 PRUØ91 URGØ96 TOTAL	35.33 32.18 35.49 48.86 49.75 29.19	5.33 2.18 5.49 18.86 19.75 4.19
-79.88 -79.89 -79.89 -79.89 -79.89 -79.89 -79.88	-34.20 -34.20 -34.20 -34.20 -34.20 -34.20 -34.20	ARGØ88 BOLØ99 PRGØ93 PRUØ91 URGØ96 TOTAL	35.39 61.16 54.61 59.79 51.3Ø 35.2Ø	5.39 31.16 24.61 29.79 21.30 10.20
-71.70 -71.70 -71.70 -71.70 -71.70 -71.70 -71.70	-43.28 -43.28 -43.28 -43.28 -43.28 -43.28 -43.28	ARGØ88 BOLØ99 PRGØ93 PRUØ91 URGØ96 TOTAL	35.24 62.26 58.53 59.Ø9 56.ØØ 35.15	5.24 32.26 28.53 29.Ø9 26.ØØ 1Ø.15
-72.80 -72.80 -72.80 -72.80 -72.80 -72.80 -72.80	-51.30 -51.30 -51.30 -51.30 -51.30 -51.30 -51.30	ARGØ88 BOLØ99 PRGØ93 PRUØ91 URGØ96 TOTAL	34.91 63.54 59.73 58.11 58.1Ø 34.85	4.91 33.54 29.73 28.11 28.1Ø 9.85
-75.70 -75.70 -75.70 -75.70 -75.70 -75.70 -75.70	-46.80 -46.80 -46.80 -46.80 -46.80 -46.80 -46.80	ARGØ88 BOLØ99 PRGØ93 PRUØ91 URGØ96 TOTAL	36.11 63.76 60.28 58.44 58.50 36.04	6.11 33.76 3Ø.28 28.44 28.5Ø 11.Ø4
-74.88 -74.88 -74.88 -74.88 -74.88 -74.88 -74.88	-28.90 -28.90 -28.90 -28.90 -28.90 -28.90 -28.90	ARGØ88 BOLØ99 PRGØ93 PRUØ91 URGØ96 TOTAL	41.43 62.06 55.97 60.69 55.35 41.03	11.43 32.06 25.97 30.69 25.35 16.03
-79.49 -79.49	-18.3Ø -18.3Ø	AR G <i>Ø</i> 88 Bol Ø99	63.43 31.8Ø	33.43 1.8Ø

• ,

-79.40 -73.40 -73.40	-18.30 -18.30 -18.30	PRGØ93 PRUØ91 URGØ96	5Ø.94 31.J7 55.51	2Ø.94 1.Ø7 25.51	
-7 <b>.3.4</b> Ø	-18.3Ø	TOTAL	28.37	3.37	
TEST COUNTR	RY : PRG	SATELLITE :	-93.30		
TEST -57.6Ø -57.6Ø -57.6Ø -57.6Ø -57.6Ø -57.6Ø	POINT -25.3Ø -25.3Ø -25.3Ø -25.3Ø -25.3Ø -25.3Ø	INT. SAT. ARGØ88 Bolø99 Chlø95 Pruø91 URGØ96 Total	C/1 (dB) 32.1Ø 4Ø.41 52.58 52.47 46.66 31.31	MARGIN 2.1Ø 1Ø.41 22.58 22.47 16.66 6.31	(dB)
-58.6Ø -58.6Ø -58.6Ø -58.6Ø -58.6Ø -58.6Ø	-27.30 -27.30 -27.30 -27.30 -27.30 -27.30	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	3Ø.Ø7 43.33 5Ø.95 5Ø.84 35.2Ø 28.7Ø	Ø.Ø7 13.33 2Ø.95 2Ø.84 5.2Ø 3.7Ø	
-56.20 -56.20 -56.20 -56.20 -56.20 -56.20 -56.20	-27.20 -27.20 -27.20 -27.20 -27.20 -27.20	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	31.10 45.13 51.31 51.20 37.50 30.00	1.10 15.13 21.31 21.20 7.50 5.00	
-54.7Ø -54.7Ø -54.7Ø -54.7Ø -54.7Ø	-25.50 -25.50 -25.50 -25.50 -25.50 -25.50 -25.50	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	31.86 43.23 51.46 51.34 49.Ø9 31.39	1.86 13.23 21.46 21.34 19.Ø9 6.39	
-54.20 -54.20 -54.20 -54.20 -54.20 -54.20 -54.20	-24.10 -24.10 -24.10 -24.10 -24.10 -24.10 -24.10	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	31.72 41.6Ø 51.Ø3 5Ø.91 57.11 31.19	1.72 11.6Ø 21.Ø3 2Ø.91 27.11 6.19	
-58.10 -53.10 -58.10 -58.10 -58.10 -58.10	-20,20 -20,20 -20,20 -20,20 -20,20 -20,20 -20,20	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	32.21 36.69 51.87 51.75 6Ø.6Ø 3Ø.81	2.21 6.69 21.87 21.75 3Ø.6Ø 5.81	
-59.10 -59.10 -59.10 -59.10 -59.10 -59.10	-19.3Ø -19.3Ø -19.3Ø -19.3Ø -19.3Ø -19.3Ø	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	31.99 35.81 51.46 51.35 61.11 30.41	1.99 5.81 21.46 21.35 31.11 5.41	
-62.20 -62.20 -62.20 -62.20	-20.50 -20.50 -20.50 -20.50 -20.50	ARGØ88 BOLØ99 CHLØ95 PRUØ91	31.81 35.22 45.90 51.45	1.81 5.22 15.9ø 21.45	

•

.

.

:

.

240

-62.2Ø -62.2Ø	-2Ø.5Ø -2Ø.5Ø	URG <b>ø96</b> To <b>tal</b>	6Ø.Ø7 3Ø.Ø2	3Ø.Ø7 5.Ø2
-62.70 -62.70 -62.70 -62.70 -62.70 -62.70 -62.70	-22.20 -22.20 -22.20 -22.20 -22.20 -22.20 -22.20	ARGØ88 BOLØ99 Chlø95 Pruø91 Urgø96 Total	31.Ø3 35.5Ø 38.46 51.18 57.93 29.13	1.Ø3 5.5Ø 8.46 21.18 27.93 4.13
-58.70 -58.70 -58.70 -58.70 -58.70 -53.70 -58.70	-27.20 -27.20 -27.20 -27.20 -27.20 -27.20 -27.20	ARGØ88 BOLØ99 CHLØ95 PRUØ91 URGØ96 TOTAL	3Ø.12 43.Ø1 51.Ø2 5Ø.9Ø 35.62 28.82	Ø.12 13.Ø1 21.Ø2 2Ø.9Ø 5.62 3.82
TEST COUNTS	RY : PRU	SATELLITE :	-91.Ø6	
TEST -70.40 -70.40 -70.40 -70.40 -70.40 -70.40	POINT -18.30 -18.30 -18.30 -18.30 -18.30 -18.30	INT. SAT. Argø88 Bolø99 Chlø95 Prgø93 Urgø96 Total	C/I (dB) 52.44 38.18 30.25 50.24 68.67 29.54	MARGIN (dB) 22.44 8.18 Ø.25 2Ø.24 38.67 4.54
-69.88 -69.88 -69.88 -69.88 -69.88 -69.88	-12.30 -12.30 -12.30 -12.30 -12.30 -12.30 -12.30	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	53.36 38.54 48.79 51.15 73. <i>8</i> 4 37.81	23.36 8.54 18.79 21.15 43.Ø4 12.81
-70.50 -70.50 -70.50 -70.50 -70.50 -70.50	-9.48 -9.48 -9.48 -9.48 -9.48 -9.48 -9.48	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	54.10 41.74 59.68 53.03 75.81 41.14	24.10 11.74 29.68 23.03 45.81 16.14
-74.00 -74.00 -74.00 -74.00 -74.00 -74.00 -74.00	-7.68 -7.60 -7.60 -7.60 -7.60 -7.60	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	54.91 57.52 6Ø.49 56.79 78.36 5Ø.97	24.91 27.52 3Ø.49 26.79 48.36 25.97
-78.08 -78.00 -78.09 -78.09 -78.00 -78.00 -78.00	-2.78 -2.78 -2.78 -2.78 -2.78 -2.78 -2.78	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	52.37 66.3Ø 57.95 54.98 77.12 49.65	22.37 36.3Ø 27.95 24.98 47.12 24.65
-75.20 -75.20 -75.20 -75.20 -75.20 -75.20 -75.20 -75.20	8.88 8.89 8.89 8.83 8.89 8.89 8.89 8.89	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	54.94 66.68 58.34 58.41 77.5Ø 51.97	24.94 36.68 28.34 28.41 47.5Ø 26.97

.

÷

•

•

-88.38 -80.38 -81.38 -81.38 -81.38 -81.38 -81.38	-3.40 -3.40 -3.40 -3.40 -3.40 -3.40 -3.40	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	55.34 66.83 58.49 59.5Ø 77.65 52.7Ø	25.84 36.83 28.49 29.5ø 47.65 27.7ø	
-81.3Ø -81.3Ø -61.3Ø -81.3Ø -81.3Ø -81.3Ø	-4.40 -4.40 -4.40 -4.40 -4.40 -4.40 -4.40	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	55.54 66.47 58.13 59.34 77.29 52.41	25.54 36.47 28.13 29.34 47.29 27.41	
-81.20 -81.20 -81.20 -81.20 -81.20 -81.20 -81.20	-6.10 -6.10 -6.10 -6.10 -6.10 -6.10 -6.10	AR GØ88 BOLØ99 CHLØ95 PR GØ93 UR GØ96 TOTAL	55.26 66.79 58.45 59.17 77.61 52.33	25.26 36.79 28.45 29.17 47.61 27.33	
-76.1Ø -76.1Ø -76.1Ø -76.1Ø -76.1Ø -76.1Ø	-13.40 -13.40 -13.40 -13.40 -13.40 -13.40	ARGØ88 BOLØ99 CHLØ95 PRGØ93 URGØ96 TOTAL	54.34 52.75 36.94 55.68 75.66 36.69	24.34 22.75 6.94 25.68 45.66 11.69	
TEST COUNT	RY I URG	SATELLITE :	-96.59		
TEST -56.20 -56.20 -56.20 -56.20 -56.20 -56.20 -56.20	POINT -34.9Ø -34.9Ø -34.9Ø -34.9Ø -34.9Ø -34.9Ø	INT. SAT. Argø88 Bolø99 Chlø95 Prgø93 Pruø91 Total	C/I (dB) 38.13 55.95 49.15 57.89 62.9Ø 37.68	MARGIN (dB 8.13 25.95 19.15 27.89 32.9ø 12.68	
-54.90 -54.90 -54.90 -54.90 -54.90 -54.90 -54.90	-35.00 -35.00 -35.00 -35.00 -35.00 -35.00	ARGØ88 BOLØ99 CHLØ95 PRGØ93 PRUØ91	38.7Ø 56.Ø2 49.21 57.96 52.95	8.7Ø 26.Ø2 19.21 27.96 32.96	
	-35.ØØ	TOTAL	38.19	13.19	
-53.50 -53.50 -53.50 -53.50 -53.50 -53.50 -53.50	-35.00 -34.00 -34.00 -34.00 -34.00 -34.00 -34.00 -34.00	TOTAL ARGØ88 BOLØ99 CHLØ95 PRGØ93 PRUØ91 TOTAL	38.19 39.49 56.28 49.47 51.23 63.22 38.73	9.49 26.28 19.47 21.23 33.22 13.73	
-53.50 -53.50 -53.50 -53.50 -53.50 -53.50 -53.20 -53.20 -53.20 -53.20 -53.20 -53.20 -53.20	-35.00 -34.00 -34.00 -34.00 -34.00 -34.00 -34.00 -34.00 -32.70 -32.70 -32.70 -32.70 -32.70 -32.70 -32.70	TOTAL ARGØ88 BOLØ99 CHLØ95 PRGØ93 PRUØ91 TOTAL ARGØ88 BOLØ99 CHLØ95 PRGØ93 PRUØ91 TOTAL	38.19 39.49 56.28 49.47 51.23 63.22 38.73 39.27 55.99 49.18 44.41 62.93 37.71	32.19   9.49   26.28   19.47   21.23   33.22   13.73   9.27   25.99   19.18   14.41   32.93   12.71	

-55.6Ø	-30.80	BOLØ99	56.21	26.21
-55.60	-30.80	CHLØ95	49.41	19.41
-55.60	-30.80	PRCM93	37 26	7 26
-55 60	-30 80	PPII091	62 16	22 16
-55 60	-20 20	TOTAL	24 61	9 61
-33.60	-30.00	TOTAL	34.01	3.01
-56.90	-30.10	ARGØ88	37.58	7.58
-56.90	-30.10	BOL Ø99	47 88	17 88
-56 90	-30 10	CHI 095	19 02	19 02
-56 90	-74 14	000000	4J.DC 35 10	E 10
-50.50	-30.10		55.10	
	-30.10		62.//	32.11
-20.90	-30.10	IUIAL	32.90	7.90
-57.60	-30.20	ARGØ88	37.54	7.54
-57.60	-39.20	BOI 099	48.42	18 42
-57 60	-30 20	CHINGS	10.42	10.10
-57 60	-20 20	000000	26.20	13.13 C 20
-57.60	- 30 . 20		30.30	0.30
-37.60	-30.20	FRUD 51	62.94	32.94
-57.60	-30.20	TUTAL	33.59	8.59
-58.20	-31.90	ARGØ88	38.30	8.30
-58.20	-31.90	801 099	56.91	26 91
-58.20	-31.90	CHI 895	A1 35	11 25
-58.20	-31.90	PRCM93	45 82	15 92
-59 20	-21 90		43.02	13.02
-30.20	-21 90	TOTAL	26 02	11 00
-30.20	-31.90	TUTAL	30.03	11.03
-58.40	-33.90	ARGØ88	37.24	7.24
-58.40	-33.90	BOLØ99	55.83	25.83
-58.40	-33.90	CHLØ95	37.27	7.27
-58 40	-33.90	PRCM93	57 77	27 77
-58 10	-33 90	DD11001	62 77	30 77
-59 10	-22 90	TOTAL	24 19	32.77
-38.40	~33.90	TUTAL	34.15	5.13
-57.9Ø	-34.50	ARGØ88	37.13	7.13
-57.9Ø	-34.5Ø	BOLØ99	55.54	25.54
-57.9Ø	-34.5Ø	CHLØ95	38.25	8.25
-57.9Ø	-34.50	PRGØ93	57.48	27.48
-57.98	-34.50	PRUØ91	62.48	32.48
-57.90	-34.50	TOTAL	34.58	9,58

•

÷

## REFERENCES

- [1] W. L. Pritchard, "Satellite Communication-An Overview of the Problems and Programs", Proceedings of the IEEE, Vol. 65, No. 3, March 1977, pp. 294-307.
- [2] "What Is Up There?", IEEE Spectrum, Vol. 20, No. 9, Sep. 1983, p. 48. Referring from Space Log of TRW Electronics and Defense Sector, and from Telecommunications Journal.
- [3] W. L. Morgan, "Satellite Locations-1984", Proceedings of the IEEE, Vol. 72, NO. 11, Nov. 1984, pp. 1434-1444.
- [4] Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977.
- [5] Report 633-1, "Orbit and Frequency Planning in the Broadcasting-Satellite Service", Recommendations and Reports of the CCIR, 1978, Vol. XI: Broadcasting Service (Television), International Telecommunication Union, Geneva 1978, pp. 216-228.
- [6] Report 206-4, "General Considerations Relating to the Choice of Orbit Parameters in the Fixed-Satellite Service", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 8-11.
- [7] Report 205-4, "Factors Affecting the Selection of Frequencies for Telecommunications with Space Stations in the Fixed-Satellite Service", Recommendations and Reports of the CCIR, 1982, Vol. IV,

Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 5-8.

- [8] Final Acts of the World Administrative Radio Conference, International Telecommunication Union, Geneva.
- [9] Article 11, "The Plane for the Broadcasting-Satellite Service in the Frequency Bands 11.7-12.2 GHz in Region 3 and 11.7-12.5 GHz in Region 1", Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977, pp. 31-72.

- [10] Annex 8, "Technical Data Used in Establishing the Provisions and Associated Plan and Which Should Be Used for Their Application", Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977, pp. 90-104.
- [11] Article 12, "Provisions Governing the Broadcasting-Satellite Service in Region 2 Pending the Establishment of a Detailed Plan", Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977, pp. 73-74.
- [12] Annex 6, "Planning Principles in Region 2", Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977, p. 88.
- [13] "Final Acts of the Regional Administrative Conference for the Planning of the Broadcasting-Satellite Service in Region 2 (SAT-83), Geneva, 1983", International Telecommunication Union, Geneva, 1983.
- [14] Edward E. Reinhart, "An Introduction to the RARC '83 Plan for DBS Systems in the Western Hemisphere", Journal on Selected Areas in Communications, Vol. SAC-3, No. 1, Jan. 1985, pp. 13-19.
- [15] D. J. Withers, "Efficient Utilization of the Geostationary Orbit for Satellite Communication", Proceedings of the IEEE, Vol. 65, No. 3, March. 1977, pp. 308-316.
- [16] Annex 7, "Use of the Spectrum/Orbit Resource", Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977, pp. 89-90.
- [17] Y. Ito, T. Mizuno and T. Muratani, "Effective Utilization of Geostationary Orbit through Optimization", IEEE Transactions on Communications, Vol. Com-27, No. 10, Oct. 1979,
- [18] "The Orbit Spacing Minimizer (ORBIT-II) User's Manual", Kokusai Denshin Denwa Co. Ltd., Tokyo Japan, April 1984. pp. 1551-1558.

- [19] S. H. Cameron, "The Solution of the Graph-Coloring Problem as a Set-Covering Problem", IEEE Trans. Electromagnetic Compatibility, Vol. EMC-19, No. 3, Aug. 1977, pp. 320-322.
- [20] J.-F. Arnaud, "Frequency Planning for Broadcast Service in Europe", Proceedings of the IEEE, Vol. 68, No. 12, Dec. 1980, pp. 1515-1522.
- [21] J. A. Zoellner and C. L. Beall, "A Breakthrough in Spectrum Conserving Frequency Assignment Technology", IEEE Trans. Electromagnetic Compatibility, Vol. EMC-19, No. 3, Aug. 1977, pp. 313-319.
- [22] W. K. Hale, "Frequency Assignment: Theory and Applications" Proceedings of the IEEE, Vol. 68, No. 12, Dec. 1980, pp. 1497-1514.
- [23] T. Mizuike, Y. Ito and T. Muratani, "Optimization of Frequency Assignment", KDD Research and Development Laboratories, Tokyo 153, Japan. Also Presented in the International Conference on Communications, Amsterdam, The Netherland, May, 1984.
- [24] J. E. Maisel, "Investigation of the Eastern Satellite Arc for US Eastern Time Zone", Space Communications Division Internal Report, SCDIR 81-3, NASA Lewis Research Center, Sep. 1981.
- [25] H. J. Weiss, "Relating to the Efficiency of Utilization of the Geostationary Orbit/Spectrum in the Fixed-Satellite Service", Proceedings of the IEEE, Vol. 68, No. 12, Dec. 1980, pp. 1484-1496.
- [26] Robert R. Brown, Kenneth E. Brown, Harjit S. Hothi and Edward F. Miller, "Development and Use of the Computer Software Package for Planning the 12 GHz Broadcasting-Satellite service at RARC '83", Journal on Selected Areas in Communications, Vol. SAC-3, No. 1, Jan. 1985, pp. 36-43.
- [27] "Software Package for Planning the Region 2 12 GHz BSS", Inter-American Telecommunications Conference, Mexico, D. F., Mexico, Sep. 28, 1981.
- [28] J. Christensen, "BSS-CAPS, A System Description", Preparatory Seminor for RARC '83 on Broadcast Satellite Planning Principles and Methodology, May 4-8, 1981, Ottawa, Canada.

- [29] C. A. Levis, C. H. Martin, D. Gonsalvez and C. W. Wang, "Engineering Calculations for Communications Satellite Systems Planning", Second interim report 71-3533-3, NASA Grant No. NAG 3-159, NASA Lewis Research Center, June 1983.
- [30] C. H. Reilly, C. A. Mount-Campbell, D. J. Davis, C. H. Martin, C. A. Levis and C. W. Wang, "Broadcasting Satellite Service Synthesis Using Gradient and Cyclic Search Procedures", presented in the Eleventh American Institute of Aeronautics and Astronautics (AIAA) Communication Satellite Systems Conference, San Diego, March 1986.
- [31] Final Acts of the World Administrative Radio Conference, International Telecommunication Union, Geneva, 1979.
- [32] Report 215-4, "Systems for the Broadcasting-Satellite Service (Sound and Television)", Sec. 4, Recommendations and Reports of the CCIR, 1978, Vol. XI: Broadcasting Service (Television), International Telecommunication Union, Geneva 1978, P. 172.
- [33] Op. cit. [32], Sec. 4.2, p. 173.
- [34] Op. cit [32], Secs. 2.4 and 4.2.2, pp. 168 and 173.
- [35] Report 711-1, "Criteria of Efficiency of Use of the Geostationary-Satellite Orbit", Annex II, "Methodology for Relating An Orbit-Spectrum Utilization Measure to System Parameters", Sec. 2, Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, p. 409.
- [36] Op. cit. [32], Sec. 3, p. 169.
- [37] Op. cit. [10], Sec. 3.3, p. 95.
- [38] Report 811, "Broadcasting-Satellite Service", Sec. 3.3, Recommendations and Reports of the CCIR, 1978, Vol. XI: Broadcasting Service (Television), International Telecommunication Union, Geneva 1978, p. 286.
- [39] Op. cit. [35], Annex II, Sec. 4, p. 410.
- [40] Report 870, "Technical Coordination Methods for Communications-Satellite Systems", Sec. 4.2, Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, p. 313.

- [41] "Sharing between the Inter-Satellite Service and the Broadcasting-Satellite Service in the Vicinity of 23 GHz", Doc. 10-11S/26-E (U.S.A.), CCIR Document.
- [42] L. J. Ricardi, "Communication Satellite Antennas", Proceedings of the IEEE, Vol. 65, No. 3, March 1977, pp. 356-369.
- [43] R. W. Kreutel, Jr., D. F. DiFonzo, W. J. English and R. W. Gruner, "Antenna Technology for Frequency Reuse Satellite Communication", Proceedings of the IEEE, Vol. 65, No. 3, March 1977, pp. 370-378.
- [44] Report 811, "Broadcasting-Satellite Service", Recommendations and Reports of the CCIR, 1978, Vol. XI: Broadcasting Service (Television), International Telecommunication Union, Geneva 1978, pp. 285-290.
- [45] Sec. 5.1.11, "Satellite Station-Keeping and Antenna Pointing Accuracy", Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva, 1982, p.118.
- [46] Sec. 1.3, "Beam area", op. cit. [10]
- [47] Recommendation 566, "Terminology Relative to the Use of Space Communication Techniques for Broadcasting", Recommendations and Reports of the CCIR, 1978, Vol. XI: Broadcasting Service (Television), International Telecommunication Union, Geneva 1978, pp. 161-162.
- [48] Report 558-2, "Satellite Antenna Patterns in the Fixed-Satellite Service", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 369-393.
- [49] H. Akima, "A Method for Determining the Minimum Elliptical Beam of a Satellite Antenna", NTIA Report 81-88, U.S. Department of Commerce, 1981.
- [50] J. Davidson and P. Sawitz, "Spectrum/Orbit Utilization Program. User and Programmer's Manual (SOUP-3)", Prepared by ORI, Silver Spring, MD 20910 Under Contract NAS 3-22884 for NASA/Lewis Research Center, 1981.

- [51] Sec. 5.1.10.3, "Earth-Station Receiving Antenna", Fig. 5-6, Curve B, Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva, 1982, p. 115.
- [52] Sec. 5.1.10.1, "Spacecraft Transmitting Antenna Reference Pattern", Fig. 5-4, Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva 1982, p. 111.
- [53] J. Davidson, H. R. Ottey, P. Sawitz and F.S Zusman, "Spectrum Orbit Utilization Program Documentation: SOUP5 Version 3.8 Technical Manual", Eq. IV-B1, Prepared by ORI, Silver Spring, Maryland 20910 Under Contract NAS 3- 22885 for NASA Lewis Research Center, June 1984.
- [54] C. A. Balanis, Antenna Theory, Analysis and Design, Sec. 2.7, Harper & Row, Publishers, New, York.
- [55] Sec. 5.1.10.1, "Spacecraft Transmitting Antenna Reference Pattern", Fig. 5-5, Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva, 1982, pp. 112-113.
- [56] NASA Lewis Research Center, Private Communication.
- [57] Op. cit. [48], Sec. 3.3, pp. 384-385.
- [58] Report 391-4, "Radiation Diagrams of Antennas for Earth Station in the Fixed-Satellite Service for Use in Interference Studies and for the Determination of a Design Objective", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 186-200.
- [59] Recommendation 580, "Radiation Diagrams for Use as Design Objectives for Antennas of Earth Stations Operating with Geostationary Satellites", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 184-185.

- [60] Sec. 5.2.5.1, "Earth Station Transmit Antenna Side Lobes", Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva, 1982, p.137.
- [61] Sec. 5.1.7.2, "Adjacent Channel Protection Ratio (FMTV)", Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva, 1982, p. 105.
- [62] Op. cit. [62], p. 104.
- [63] W. L. Stutzman and G. A. Thiele, Antenna Theory and Design, Chapter 1, John Wiley and Sons, Inc., New York, 1981.
- [64] Op. cit. [50], Sec. III, p. III.1.
- [65] Op. cit. [44], Sec. 7, "Power Flux-Density Required".
- [66] Op. cit. [5], Sec. 6, p. 222.
- [67] Report 564-1, "Propagation Data Required for Space Telecommunication Systems", Recommendations and Reports of the CCIR, 1978, Vol. V: Propagation in Non-ionized Media, International Telecommunication Union, Geneva 1978.
- [68] Op. cit. [5], Sec. 8.2, p. 224.
- [69] Op. cit. [10], Sec. 3, p. 96.
- [70] Op. cit. [10], Sec. 2, pp. 91-92.
- [71] H. A. Rosen, "Syncom and Its Successors", Proceedings of the IEEE, Vol. 72, No. 11, Nov. 1984, pp. 1429-1434.
- [72] Op. cit. [5], Sec. 10, p. 225.
- [73] Op. cit. [38], Sec. 6, p. 288.
- [74] Op. cit. [36], Sec. 4.4, p. 175.
- [75] Sec. 5.1.5, "Carrier-to-Noise ratio", Technical Bases for the Regional Administrative Radio Conference 1983 for the Planning of the Broadcasting-Satellite Service in Region 2, Report of the CCIR Conference Preparatory Meeting, International Telecommunication Union, Geneva, 1982, p. 94.

- [76] Report 866, "Interference Allocations in Analogue FM Systems Operating at Frequencies Greater Than 10 GHz in the Fixed-Satellite Service", Sec. 3.4, Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 67-69.
- [77] Op. cit. [35], Annex II, Sec. 3, p. 410.
- [78] Annex 9, "Criteria for Sharing between Services", Final Acts of the World Administrative Radio Conference for the Planning of the Broadcasting-Satellite Service in Frequency Bands 11.7-12.2 GHz (in Regions 2 and 3) and 11.7-12.5 GHz (in Region 1), International Telecommunication Union, Geneva, 1977, pp. 104-108.
- [79] Report 867, "Maximum Permissible Interference in Single-Channel-Per-Carrier Transmissions in Networks of the Fixed-Satellite Service", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 99-102.
- [80] "FCC Adopts Reduced Satellite Orbital Spacing Criteria for 4/6 GHz and 12/14 GHz Bands", FCC News, (CC Docket 81-704), Report No. 17459, April 27, 1983.
- [81] D. G. Luenberger, Introduction to Linear and Nonlinear Programming, Sec. 7.6, 2nd Ed., Addison-Wesley Pub. Co., Readind, Mass., 1973.
- [82] Op. cit. [81], Sec. 7.8.
- [83] Op. cit [10], Sec. 3.12, p.101.
- [84] Report 808, "Broadcasting-Satellite Service", Sec. 2.1, Recommendations and Reports of the CCIR, 1978, Vol. XI: Broadcasting Service (Television), International Telecommunication Union, Geneva 1978, p. 256.
- [85] Op. cit. [9], Sec. 11.3, p.32.
- [86] C. H. Martin, D. J. Gonsalvez, C. A. Levis and C. W. Wang, "Engineering Calculations for Communications Satellite Systems Planning", Interim report 71-3533-4, NASA Grant No. NAG 3-159, NASA Lewis Research Center, Dec. 1983.
- [87] Op. cit. [78], Sec. 1.2, p. 105.
- [88] R. Garfinkel and G. Nemhauser, <u>Integer Programming</u>, John Wiley & Sons, 1972.

- [89] Report 453-3, "Technical Factors Influencing the Efficiency of Use of the Geostationary-Satellite Orbit by Radiocommunication Satellites Sharing the Same Frequency bands", Sec. 2.3, Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, p. 276.
- [90] Donald M. Jansky and Michel C. Jeruchim, <u>Communication Satellites</u> in the Geostationary Orbit, Chapter 1, Artech House Inc., Dedham MA, 1983.
- [91] Robert R. Lovell, "Communications Technology Development in NASA", Seminar on Domestic Satellite Communications, Shanghai, Oct. 5-12, 1983.
- [92] Report 711-1, "Criteria of Efficiency of Use of the Geostationary-Satellite Orbit", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 402-415.
- [93] W. L. Pritchard, "The History and Future of Commercial Satellite Communications", Fig. 9, IEEE Communications Magazine, Vol. 22, No. 5, May 1984, p. 35.
- [94] "Communications Platform Payload Definition Study; Task 1: Data Base Development", COMSAT Laboratories, RCA Astro-Electronics, Under Contract NAS 3-24236 for NASA Lewis Research Center, Oct. 11, 1984.
- [95] Report 555-2, "Discrimination by Means of Orthogonal Circular and Linear Polarizations", Recommendations and Reports of the CCIR, 1982, Vol. IV, Part 1: Fixed-Satellite Service, International Telecommunication Union, Geneva 1982, pp. 334-361.
- [96] Y. Yamamura, "Calculation of Allowable Orbital Spacings for the Fixed-Satellite Service", Thesis, Electrical Engineering Department, The Ohio State University, June 1985.
- [97] C. A. Levis and Y. Yamamura, "Calculation of Allowable Orbital Spacings for the Fixed-Satellite Service", Technical Report 716548-1, The ElectroScience Laboratory, The Ohio State University, on Grant No. NAG 3-159, for NASA Lewis Research Center.
- [98] Op. cit. [89], Sec. 8.2.2, p. 293.
- [99] Wilbur L. Pritchard, "The history and Future of Commercial Satellite Communications", IEEE Communications Magazine, Vol. 22, No. 5, May 1984.

- [100] Op. cit. [90], Sec. 5.7.
- [101] Op. cit. [48], Annex II, p. 389.
- [102] Op. cit. [90], p. 254.
- [103] F. A. Tobagi, R. Binder and B. Leiner, "Packet Radio and Satellite Networks", IEEE Communications Magazine, Vol. 22, NO. 11, Nov. 1984, PP. 24-40.
- [104] S. J. Campanella and J. V. Harrington, "Satellite Communications Networks", Proceedings of the IEEE, Vol. 72, NO. 11, Nov. 1984, pp. 1506-1519.
- [105] O. L. Mangasarian, Nonlinear Programming, McGraw-Hill Book Co.