ANATOMICAL AND PHYSIOLOGICAL EFFECTS OF
RAPID DECELERATION

Dissertation

Presented in Partial Fulfillment of the Requirements
for the Degree Doctor of Philosophy in the
Graduate School of the Ohio State
University

By

Alfred Francis Fasola, B.A., M.S.
The Ohio State University

1953

Approved by:

Adviser

TABLE OF CONTENTS

	Page
Introduction	1
Review of Literature	
I. Non-penetrating Chest Injury	7
II. Strength of Bones	15
III. General Aspects of Deceleration	20
Anatomical Description	21
Anatomical Methods and Results	
I. Static and Dynamic Loading of Sacro-Iliac	29
II. Static Loading of Femur with and without Casts	36
III. Static Loading of Middle of the Shaft of Femur	41
IV. Static Loading of Model and Human Clavicles	43
V. Dynamic Loading of Inferior Aspect of Femur with Attached and Partially Denuded Pelvis	46
VI. Dynamic Loading of Symphysis Pubis	49
VII. Dynamic Loading of Sacro-Iliac Joint in Intact Pelvis	52
VIII. Dynamic Loading of Lateral Wall of Acetabulum	54
IX. Relative Strength of Posterior and Anterior Pelvic Wall	56
Discussion - Anatomical	59
Conclusions - Anatomical	63
Physiological	
I. High Speed X-Rays	
a. Methods and Results	66
b. Discussion	72
c. Summary of High Speed X-Ray studies of Dog Thorax After Rapid Deceleration	76
d. Statistical Summary of Films	77
e. Protocols	78
f. Table I	85
II. Experiments with Abdominal Safety Belts	
a. Methods and Results	90
b. Conclusions	96
c. Electrocardiographic Summaries (Scottie)	97
d. Electrocardiographic Summaries (Hound)	105
e. Electrocardiographic Summaries (Brownie)	115
Bibliography	125 ⁶

ILLUSTRATIONS

	Page
Figure 1. Mounting of Pelvis for Static Loading	32
Figure 2. Posterior View of Pelvis Showing Fractures Under Static Loading	33
Figure 3. Pile Driver	34
Figure 4. Anterior View of Pelvis	35
Figure 5. Method of Applying Static Load to Femurs	39
Figure 6. Fractures of Femurs Produced by Static Loading with and without Casts	40
Figure 7. Method of Applying Load to Middle of Shaft of Femur .	42
Figure 8. Method of Applying Dynamic Load to Clavicles	45
Figure 9. Method of Applying Load to Inferior Surface of Femurs	48
Figure 10. Bony Pelvis Showing Regions of Fracture	51
Figure 11. Anterior View of Pelvis Showing Femoro-Sacral Arch .	64
Figure 12. Posterior View of Pelvis Showing Ischio-Sacral Arch.	65
Figure 13. Heart Size Measurements	69
Figure 14. Anterior-Posterior and Lateral View of Dogs Decelerated with Abdominal Safety Belts	70
Figure 15. Heart Shadows by High Speed X-Ray at the Instant of	
16. Deceleration	71
	71-a
Figure 17. Graphs Showing Change in $T_R + T_L$	87
Figure 18. Graph Showing Change in Transverse Diameter	88
Figure 19. Graph Showing Change in $/4 L B$	89
Figure 20 EKG (Scottie)	103
21	104
Figure 22 EKG (Hound)	112
23	113
24	114
25	115

ILLUSTRATIONS
(continued)

PAGE

Figure 26.	EKG (Brownie)	122
27.		123
28.		124
29.		125

For many years the Safety Engineer has become interested in the problem of preventing bodily injury from rapid decelerative forces. With the advent of modern high speed transportation, this problem has become extremely important, not only to the aviator, but also the automobilist, and even to the pedestrian. If man is to successfully travel in the upper atmosphere and even in space itself with reasonable assurance of safe return, we must have a thorough knowledge of the forces he will encounter and his tolerance to these forces. Furthermore, the craft in which he travels must be engineered to his physiological and anatomical tolerance.

One may actively protect himself by keeping these decelerative forces within the physiological and anatomical safe limit, but unfortunately, this safe limit has not been accurately ascertained. Added protection may be gained by the adoption of various types of devices, such as the anti-G suit, or by devices such as the abdominal and/or shoulder type safety belt. It is with the latter, the safety belt, that is of particular interest in this research. The effects of safety belts has been undertaken with consideration of both the anatomical and physiological aspects. This combination of anatomy and physiology should at once emphasize the complexity of the problem of tolerance and should emphasize the numerous aspects which one must of necessity consider in solving the problem of "how much force can the human body tolerate". At a recent meeting of the Anatomists, the fact was stressed that the solution of anatomical problems must include the safety of function; the converse is also true - "the study of function must also include the study of structure". In this research, we have a striking example of the common meeting ground of both.

The anatomical aspects have been visualized from the mechanical viewpoint, i.e., a survey of the component parts of the skeleton receiving the force and the magnitude of the force required to cause complete fracture of the structure. This in turn was approached from the standpoint of first isolating these structures, testing each separately and, secondly, testing the same structure in their true anatomical orientation.

We have also studied the thoracic and abdominal viscera from the functional viewpoint since during the early stages of this research, it became increasingly evident that the heart was extremely vulnerable to non-penetrating forces which strike the chest or to forces which were delivered to the chest, by way of the abdomen, such as happens with the abdominal type safety belt. Occasionally following accidents which involve application of severe forces to the thorax of a person, a clinical condition of congestive heart failure is observed. Our interest is in describing the mechanism which produces this symptom in controlled laboratory experiments.

This line of research was adopted first because the original sponsor of the project, the National Safety Council, was confronted with industrial accidents directly related to safety belts and harnesses in which individuals have sustained severe injury and even death. The symptoms in most cases were latent in appearance and poorly defined. The cause of injury or death was immediately attributed to the attachment of the safety belt to the inferior surface of the chondrocostal arch which resulted in the compression of the abdomen and in forcing the viscera against the diaphragm.

This research was later taken over by the Wright-Patterson Air Force Base because of their interest in the problems of the strength of the human

body in relation to both the ejection seat and the safety belt.

One might assume that certain injurious effects, both physiological and anatomical, are brought about by the use of safety belts when individuals are subjected to high peak decelerative forces of short duration. However, at least one group presently investigating the problem has minimized, and in some instances completely denied, any effects of forces applied in this manner. A cursory glance at the literature and experimental results of the various groups investigating this problem will emphasize the controversial nature of the problem. Much of this controversy has come about as a result of crash injury investigation in which hundreds of accidents were analyzed from the standpoint of location of injury and comparison of injury related to the use of, or dis-use of the lap and/or shoulder type of safety harness. It is the opinion of Hugh De Haven, Head of the National Research Council on Crash Injury Research, that seldom, if ever, has the use of the safety belt resulted in injury in the region of the body where the belt is attached and hence, the head is the most important region of injury. This is due to the head striking some hard object. Safety, therefore, can be engineered since the human body has a tolerance considerably in excess of the strength of the surrounding structures.

We are in complete agreement with the proposition that the human body can withstand extremely high peak forces of short duration. We must, however, accept with certain reservations, the proposition that safety belts are harmless. These reservations are based on evidence from this and other laboratories and from considerable evidence gained from clinical investigation which shows clearly that non-penetrating chest injuries

produce symptoms of cardiac failure; namely, the symptoms of congestive heart failure. It is not our desire to completely disagree with De Haven and certainly not to recommend the dis-use of belts. We believe, as he must surely believe, that some injury to the viscera and bones is always better than loss of life which would result if the belt were not used. We believe, nevertheless, that in order to provide complete protection, the latent symptoms which result from impact force, either with or without harness, must be fully recognized and further engineering based upon this recognition.

An example of the opposite point of view is the crash injury report of Doctor Teare which appeared in the British Medical Journal in September, 1951 concerning the Viking aircraft crash at London Airport. We wish to quote from the article appearing in Scientific American, December, 1951 as reprinted by the Crash Injury Research Council in order to elucidate the controversy more clearly.

"When an airplane crashes, the safety belt that passengers are required to fasten around their waists may become a deadly hazard. A British physician named Donald Teare examined 28 victims of a crash at London Airport and found that 16 were killed by chest and abdomen injuries resulting from acute flexion of the body over the safety belt. Eight of the victims had suffered a rupture of the aorta. An extremely rare injury, almost never found except in plane accidents".

Equally controversial is the question of man's tolerance to high peak impact forces. It has been shown by data from crash injury in aviation and in free-fall from high altitudes that under certain conditions, human being tolerate

165 g's without serious damage. On the other hand, it was the popular belief that the snubbing action of a 1000-lb. safety belt was capable of producing considerable internal injury and was even capable of cutting people in two.

Obvious difficulties arise when one attempts to understand the tolerance of the human body to high impact forces, since as one would naturally expect, human volunteers are hard to obtain in this hazardous work. This is the approach to the problem in the investigation at Muroc Lake, California, at the Edwards Air Base. Humans have to date been decelerated at a peak of 46 g's without apparent injury. In the absence of human volunteers, however, one must accept the line of investigation adopted by the Committee on Crash Injury Research which attempts to reconstruct accidents by a determination of the average 'g' force from the decelerative distance and the velocity at impact. This procedure does not, however, seem to solve the general problem because the phenomena are not controllable and only a deduction about the actual forces involved can be made. One may on the other hand, proceed as we have done by using unembalmed human cadaver material and experimental animals in laboratory controlled experiments. With Crash Injury, as with our own experiments, difficulties arise when one attempts to transfer these data to human living conditions. We feel that unembalmed cadavers approach the living state as nearly as is practicable at this time.

Four important factors must be controlled: -

1. Magnitude of the force
2. Direction of the applied force
3. Duration of the force
4. The area of the body over which the force is applied

It seems altogether believable at this point that a tolerance exists for each of the vectors resulting from the myriad positions in which the body may be placed and also for the infinite rates of deceleration which exist. It is for these many reasons that when one speaks of tolerance, the tolerance to each of the above variables must also be given.

No one laboratory is capable of providing all the data which is necessary to fully understand the resistance of the body to deceleration, or to provide an analysis of all the forces involved. The ultimate goal of the various laboratories engaged in this work is to provide complete protection to individuals subjected to high decelerative forces. Much of these data, especially that obtained from bone studies, have been used to construct a model of the human body which may be used in test equipment rather than using living human body itself.

We have pointed out that the approaches to the subject of tolerance of the human body and protective devices against high peak decelerative forces are many. Since this type of investigation can be considered to be in its infancy, we have tried at this stage to cut down trees rather than bushes. This dissertation contains several aspects of the various approaches to this problem. The three-fold objectives are listed as follows: -

1. To provide information concerning the strength of the pelvic walls inclusive of the acetabulae and femurs.
2. To describe a possible mechanism for the production of cardiac failure with the use of high speed X-ray.
3. To measure the tolerance of dogs to rapid deceleration and to provide information which would contribute to the solution of the problem concerning the possible danger resulting from the use of abdominal safety belts in rapid deceleration.

REVIEW OF LITERATURE

I. NON-PENETRATING CHEST INJURY

In this laboratory it was shown that the cardiac failure produced by high peak impact was associated with the symptoms of non-penetrating chest injury. Since the literature on cardiac failure as a result of deceleration into abdominal safety belts is practically nil, it is advisable to give a review of the literature on non-penetrating chest injury; first because the electrocardiographic changes under the conditions of our experiments were shown to be strikingly similar and secondly, it seemed important from the standpoint of determining and understanding the mechanism for the production of such injury.

At present time some believe the damage due to non-penetrating chest injury to be of relatively little importance, perhaps since only the more serious cases ever find their way into the clinic and even at this time, many more complicated symptoms seem to mask the subtle and sometimes latent appearance of heart damage.

The legal aspect of the problem has great importance in determining whether or not a given individual should receive a compensation. This question alone has given impetus for the little experimental work that has been done in this field. Hecht (11a) points out its importance from both the industrial and military point of view. Practically every paper, however, stressed to some degree its importance in determining compensation for individuals who had received some degree of non-penetrating chest injury. In this age of rapidly moving forms of transportation in which individuals may be subjected to non-penetrating chest injuries by a variety of means, the importance of this problem in protecting them financially and from the possibility of heart damage is readily apparent.

Misinterpretation and misgiving concerning the degree of cardiac damage from non-penetrating wounds is obvious from a cursory glance at the literature since most of the evidence compiled is from the clinic. For example, Bright and Beck (10) made a study of some 200 cases in which individuals were known to have sustained some degree of cardiac injury from non-penetrating chest wounds. About 90% of these cases resulted in fatal heart rupture and the obvious conclusion from this statistical analysis is that the heart is capable of withstanding only a small degree of violence and that recovery is the exception and not the general rule. These authors, however, were quick to point out that the majority of non-penetrating wounds are not recognized clinically, since as has already been pointed out, the degree of damage may be subtle or latent in appearance; therefore, the exceptions more often found their way into medical literature. The latent appearance of damage is brought out by Barber (4) who reported a case of cardiac injury, dating back to 1917.

At this point, the major problem involved may be stated in the interest of clarity. Kissane, et al, has made this clear: - "That severe trauma (non-penetrating) to the chest will cause lesions of the heart, great vessels, and pericardium is well substantiated in medical literature from autopsy reports. However, it is not generally accepted that less severe trauma will cause mild changes which have a tendency to recover". Additional papers may be cited to further elucidate the problem. Sigler (24) states - "trauma to heart is frequently overlooked because of the feeling that the chest wall and cushion effect of the lung prevents trauma". Kissane (34) (35) states - "opinions differ pertaining to production of

cardiac lesions by non-penetrating wounds of the chest", pointing out that these studies lack information concerning normal conditions of the heart prior to injury.

Since for proper evaluation of data the method used in collecting this data is important, the two methods will be described briefly. Experimentally, dogs have been used and subjected to varying degrees of chest injury. The results were recorded on electrocardiographic machines and collected from gross and microscopic autopsy findings. Because of the uncertainty with which this data could be applied to human beings, attempts were made to gather clinical cases as a result of industrial and automobile accidents in which it seemed likely that the individuals had received some degree of chest injury. Both methods are subjected to criticism.

The types of forces which cause cardiac damage was analyzed and is here presented: -

1. Blows to the precordium (11a) (26) (34) (35)
2. Lifting of heavy objects (24)
3. Sudden compression of the abdomen. This occurs with abdominal safety belts (19) (110)
4. Compression of the chest (24)
5. Sudden increase in intrabdominal pressure (24)
6. Injuries distant from the heart may also cause damage sudden compression of the legs and abdomen (10) (31)

Although the report of Bright and Beck (10) does not deal directly with non-penetrating chest wounds, this paper has been reviewed because it elucidates one mechanism or a possible mechanism of producing heart damage.

The forces cause damage by: -

1. Throwing the heart against the bony structure of the thoracic cage (18) (19)
2. This causes the heart to be torn loose from its moorings to the pericardium and the great vessels (19)
3. Forcing the blood back to the ventricle causing an increase in intracardial pressure (7) (19)
4. Causing a change in the volume and shape of the chest and a consequent displacement of the heart and mediastinum (19)

Upon receipt of injury, the heart may follow certain pathways: -

1. The heart may rupture or burst by being thrown or compressed against the sternum or vertebrae (7)
2. The myocardium may rupture (8)
3. Contusion may occur with a subsequent softening of the myocardial tissue. Rupture may occur later (8)
4. If the damage is not too severe, the heart may recover (34) (35)
5. Symptoms and electrocardiographic changes may appear at a later date (110) (11a)
6. Heart may fail completely (34) (35)
7. Symptoms may persist and be accentuated by vigorous exercise (10)

Since the same type of force does not always produce the same type of damage, certain factors have been listed that alter the nature of the force: -

1. Flexibility or resiliency of the thoracic cage. Young people seem to be less susceptible to damage to the same force.
2. Condition of the heart prior to application of force. Diseased hearts are more susceptible to the same force. (24) (25) (31)
3. Vago-sympathetic imbalance (34) (35)
4. The phase of the respiratory cycle. Prior warning of the impending force causes the individual to close the glottis and be in deep inspiration with the result that the force is transmitted directly to the thoracic contents instead of being damped (18).

5. The phase of the cardiac cycle. The heart in systole is more vulnerable to damage than is the heart to diastole (18).

To date no objective symptoms referable to heart damage are known, and it is for this reason that many cases of non-penetrating wounds do not find their way into the medical literature. However, a list of clinical symptoms have been compiled and are here listed: -

1. Irregular heart sounds
2. Slight dyspnea
3. Gallop rhythm
4. Systolic murmurs
5. Pericardial friction rub

Barber (4) has made a list of symptoms of long duration, whereas the above are usually found to be transient: -

1. Partial heart block
2. Auricular fibrillation
3. A picture of coronary thrombosis

The majority of damage seems to be confined to the myocardium and the pericardium (34) (8) (31) (26). Rupture of the valves occur to a lesser degree. Kissane states (35) - "a study of clinical cases showed that the most frequent injury was noted in the pericardium and myocardium and was related to the degree of external violence. In one case a rupture of the valves was noted".

The electrocardiographic picture is suggestive of experimental coronary artery occlusion and the disease pericarditis. This was emphatically brought out by the work of Randles (36).

It has already been pointed out that the changes in the heart do not appear immediately; therefore, the electrocardiograph provides a ready means of diagnosing injury if frequent records are made following injury to the chest. In cases where only one lead was taken, it was confined to the more diagnostic lead II. Where the course of cardiac injury was followed over a period of time, the three standard leads were taken. A very important fact was, however, brought out by Hecht (11a) in which he stressed the need for the precordial lead in addition to the others since in his study of a clinical case, changes were noted only in precordial leads.

That these changes are those associated with coronary occlusion and pericarditis has been definitely established (4) (8) (24) (34) (26), and involves changes in the QRST complex. Slurring of the R wave, temporary changes in the direction of the wave, voltage changes in the QRS, and axis deviation have also been noted. Other changes have been shown, but the list above is considered to be the most important. Evidence indicates that these changes appear from time to time and that no two cases are exactly alike.

Perhaps the main criticism of all the experimental work lies in the fact that in all cases, with one exception, was there an attempt to calculate the magnitude of the force. If, as Sigler (24) (25) points out, that the velocity of the force as it strikes the body is important, then knowledge of the forces involved is ever important. The Randolph field report represents the first attempt to do this. However, their work may be criticized from the point of view that the force which they used - 1000 g's - is too great, especially if one attempts to show which regions of the body are more vulnerable to force as compared to another region; in other words, to find the weakest link in the chain. This report,

which attempts to attribute to the vagus, the mediator of conduction disturbances, cannot stand up to a critical statistical analysis.

Much evidence was obtained from clinical cases which could be analyzed only after the accident occurred. Leinoff (19) points out - "The history of the heart is the most important factor in determining the relation and subsequent degree of cardiac disability resulting from non-penetrating chest injury". Obviously, this was not possible in the majority of cases.

Hecht (11a) emphasizes the fact that more leads than the standard leads should be taken since changes in the electrocardiogram may be confined to only the precordial leads.

The lack of carefully controlled experiments is evident. More experiments of the type performed by Kissane and his group is necessary before any definite statements can be made concerning this problem.

Though the problem of non-penetrating chest wounds is far from solved, certain conclusions can, nevertheless, be drawn from the existing information: -

1. Trauma to the heart is a frequent occurrence in bodily injury,
2. The force necessary to damage the heart need not be severe.
3. Trauma to the heart may result in recovery in one case and prove fatal in others. Factors which alter the nature of the impinging force has been listed.
4. Recovery from trauma is the general rule and not the exception.
5. Diseased heart is more vulnerable to damage from an impinging force than is a normal heart.
6. The mechanism in producing heart damage is not definitely known.

7. Electrocardiographic changes involve the QRST complex and give the picture associated with coronary artery occlusion and pericarditis.
8. Electrocardiographic changes may be transient and latent in appearance; therefore, frequent records should be taken following violence to the chest.

REVIEW OF LITERATURE

II. BONES

Until the past several years, the literature concerning the mechanical properties of bones was indeed scarce, in spite of the fact that its origin dates back to 1638 when Galileo Galelei studied the mechanical properties of bones in conjunction with studies on beam mechanics.

It was not, however, for several hundred years later that any studies of any import were undertaken. In 1867 Von Meyer made several studies concerning the internal architecture of the femur and attempted to correlate this information with the theoretical stress analysis studies of the brilliant mathematician, Culman, who in addition, described the trabeculae arrangement of the femur.

This theoretical approach gave way about ten years later, 1876 and 1880, when Rauber and Messerer investigated the mechanical properties of the femur by placing samples in a testing machine and subjecting them to static loading to their ultimate breaking strength.

In 1892, Wolff conducted investigations on the functional forms of bones and formulated what is known as WOLFF'S LAW, a theory which is still contested, but which, receives support from many investigators today. According to Wolff, the internal structure of bone is influenced directly by its external loading.

A rather extensive review of the literature up to 1917 was given by Koch who combined the literature of the past with his own original ideas into a theoretical analysis of stress distribution of the femur under vertical loading. He, in addition, calculated the stress throughout various regions of the femur as 100-lbs. from a graphical analysis of cross-section.

The difficulties encountered in bone studies were apparent to even these early investigators. Attempts were made to overcome these difficulties by the construction of models and thereby reduce the heterogeneous construction of bone to the homogeneous structure of models. The first of such models was constructed in 1885 by Roux who loaded paraffin coated rubber models and deduced mechanical properties of bones from these models.

Little of any consequence approached the scene until 1940 when Milch conducted further investigation along the line of Roux by the construction of models from polymerized phenyl formaldehyde resin. By photoelastic studies, he deduced properties which he thought characteristic of bone itself. The difficulties here are obvious: - first, can the homogeneous characteristic of the model be directly applied to the heterogeneous characteristics of the bone structure - and secondly, can the two dimensional pattern of the model be with impunity directly applied to the three dimensional characteristics of the bone?

We must, however, mention the work of Kuntscher in 1935 - 1936 since it introduces a new method for the study of stress analysis. This involves an extension of the work of Roux. In this case, bones were coated with a low tensile strength material, colophonium, which when stretched beyond its elastic limit cause cracks to appear in the region subjected to the highest tensile strain.

Probably the greatest impetus for the investigation of the mechanical properties of bones is due to the innovation of the ejection seat from high speed aircraft and the general recognition that knowledge of the tolerance

of the human body to high peak decelerative forces must be known if aviators specifically and the public generally are to survive accident forces in this age of higher speed forms of transportation.

During World War II, the Germans recognized the need for this type of information. Their experience led them to believe that the spinal cord seemed to be a critical area as a result of deceleration from the ejection. This led to an important investigation of the tolerance of the spinal cord in both the cadaver and living human subjects, and involved a study of the structures of the spinal cord in the isolated and the intact state. The following is a list of the results of the strength of the individual vertebrae under static loading: -

<u>SEGMENT OF CORD</u>	<u>BREAKING LOAD (Kg)</u>
C-4	275
T-1	450
T-6	600
T-8	600
T-9	720
T-10	770
T-11	860
T-12	800
L-1	1000
L-2	830
L-3	940
L-4	900
L-5	1000

The following data was obtained from a study of the tolerance of vertebral complexes to static loading: -

6 vertebral segments	T10 to L-3
T-12	690 Kg
T-1)	
T-2)	840 Kg
7 vertebral segments	T-7 to L-1
T-8	540 Kg

The dynamic tolerance of the body was directly related to the tolerance of the spinal cord. Experiments on human living subjects place this tolerance at 26 "g" if the force acts for .005 seconds.

The author suggests that in an entire centrally loaded spinal column the weakest link in the vertebral chain, based upon strength of and the percentage of the load carried by the individual vertebral, L-1 would collapse after the absorption of approximately 10 m/kg of energy has been absorbed.

More recent work on the study of bone structure and fracture location at Wayne University uses the coating of bones with "stress coat" and applying both static and dynamic loads to these isolated structures. Early work on the skull by "stress coat", which has a tensile stress of 0.00085 inches/inch, and by strain gauges shows the skull to deform when 615 inch pounds of energy is absorbed for a period of .0012 seconds. This same group have conducted studies on the femur and pelvic girdle.

Another group of investigators at Naval Medical Institute, Bethesda, Maryland have approached the mechanical properties by studying strength per unit volume of bone. Samples of bone from various regions were milled down to desired size and then subjected to both tensile and compressive strain.

The data on bone samples obtained from femur, tibia, fibula is as follows: -

Compressive strength	25,400 lbs./square inch
Young's Modulus in Compression	2.73×10^6 lbs./square inch
Tensile strength	22,000-lbs./square inch
Torsion	.449 lbs./inch

Studies to determine the effects of embalming showed increase in strength from 6 to 116%.

Lastly, the work done in this laboratory (48) (110) on the strength of bones has been approached by testing the ultimate breaking strength of the structures comprising both the pelvic girdle to be found in this dissertation and the pectoral girdle which was previously done under the sponsorship of the National Safety Council.

III. GENERAL ASPECTS OF DECELERATION

Considerable information concerning the tolerance of the human body to rapid deceleration has been obtained from Crash Injury Research and experiments on human volunteers at Muroc Lake, California. This involves an analysis and reconstruction of accidents, both civilian and military. From this type of research, knowledge of the tolerance is based upon the known ultimate breaking strength of the safety belt which broke during deceleration, but which produced little or no damage to the subject. On the basis of this information, the strength of safety belts has been constructed to withstand forces as high as 9000-lbs.

Analysis of accidents from free fall drops as high as 200-feet with estimated "g" force of 200-g have been survived by individuals according to the Committee on Crash Injury Research.

Perhaps the most significant research, from the standpoint of human tolerance to linear deceleration, is in progress at Muroc Lake, California under the direction of Major Stapp (162) (118). To date 53 experiments have been conducted on live human subjects who sat facing forward on a rocket propelled sled. Range of deceleration on the sled ranged from 10-g at 575 g/second to 46-g at 500-g/second. Duration of deceleration ranged from .15 to .35 seconds.

The degree of voluntary tolerance was apparently related to the type of restraint applied to the subject. With standard Air Force harness, this tolerance was approached at 17-g at 1000-g/second. With 'V' leg straps and shoulder straps, the voluntary tolerance was increased to 46-g with rate of deceleration at 500-g/second.

ANATOMICAL DESCRIPTION

In this type of research, we are interested in the more extensive problem of general safety which we have attacked in part, by an analysis of the ultimate breaking strength of bones, isolated and in intact state and the ultimate breaking strength of a series of bones, ligaments, and the muscles which comprise a joint.

Nature has assigned bones two very important functions: - First, the function of supporting the softer tissues which surround them, and in some cases forming a protective box or cage for these organs such as, for example, the brain in the skull, or the heart and lungs in the resilient thoracic cage, or the spinal cord in the backbone. If one is then to understand the body in terms of its tolerance to force suddenly and violently applied, some knowledge of the strength of these protective cages is mandatory. Secondly, bones act as levers in the performance of movement and as such transmit both tensile and compressive stresses. This function is obviously performed with negligible deformation to the bone itself. These same stresses can, however, be produced in a variety of other ways - intentionally as in the case of the ejection seat, parachute descent or safety belt - and accidentally as in the case of automobile or airplane crashes. If one is then to engineer against such stresses, knowledge of the structure, in terms of its ultimate strength, is again mandatory.

In order to give continuity to the skeleton, ligaments form thickened bands which extend between bones and we have thus formed a joint which in addition to continuity adds maneuverability to the whole skeleton. In this case, the ligament assumes a position of importance as we have seen in the research on the shoulder girdle, particularly in the case of the

coraco-acromial ligament and we have seen in tests on the sacro-iliac joint, particularly the anterior and posterior ligaments and as we have seen in tests of the hip joint, particularly in the case of the ilio-femoral ligament. Because of their anatomical moorings, ligaments are capable of producing only tensile stress.

Bone is made up of 69% inorganic matter, which is mostly calcium, phosphate, and 31% organic matter which is mostly: -

- (a) fine fibers forming and inter-lacing bundles
- (b) connective tissue cells and bone corpuscles placed between these bundles.

It is this combination of inorganic and organic matter together with the architectural arrangement of these elements which makes the bone not only a hard material, but also a structure resistant to both tensile and compressive stresses. The brittle and weak bones of old age is due mostly to a diminution of fibrous tissue and not to any change in the inorganic matter content. Joffes (110), in this laboratory, showed the strength on ribs could in no way be related to bone ash content.

Bone may be either compact or spongy. The compact bone forms the outer layer which is immediately surrounded by the periosteum. It is this layer which gives bone its inherent strength and it may be said that the strength of a bone is directly proportional to the thickness of this layer. The inner spongy layer is somewhat hard, but is extremely weak. Data on shoulder girdle shows the strength of bone can be related to thickness of the outer compact layer. Bone seems well adapted for the job which it has to perform. This it does with both strength and economy. The usual combination of organic and inorganic materials has already been mentioned with relation

to its strength. The mechanical arrangement of the tubular lamellas also provides a structure capable of resisting bending in either direction. Koch and others have analysed this bone from a mechanical standpoint and came to the conclusion that the tubular lamellae had the best possible arrangement for resisting both tensile and compressive forces. As they approach the upper end of the femur, tubular lamellae leave the compact bone, arching and reaching the head of the femur and greater trochanter. This system interposed between a second system which springs from the greater trochantera and head of the femur, crossing the former system at right angles forming a firm, rigid and inherently strong structural member.

Of special interest in this phase of the study of the tolerance of the human body to rapid deceleration are the bones which comprise the hip which is also called the pelvic girdle. Also of interest is the femur which articulates with the pelvic girdle, via the acetabulum. All these structures are important when any force is delivered from below, that is, to the inferior surface of the neck of the femur, or to the sacrum, such as one might experience in the ejection seat.

The first of the three bones comprising the hip bone is the ileum, the largest and the broadest of the three. The second is the ischium which is broad and thick behind the acetabulum forming a flat bar of bone, the lower boundry of the obturator foramen and projects to the pubic symphysis as the inferior rami. The third bone, the pubis, completes the boundary of the obturator forming the superior rami. An analysis of these structures is important when one considers a force delivered to the body of the symphysis itself. The conjoined rami of the ischium and the pubis of the two sides forms the pubic arch in front.

The bones of the pelvic girdle can be divided into three walls: -

1. The posterior wall
2. The anterior wall
3. The lateral wall

The greater part of the posterior wall is formed by the sacrum and by means of the sacro-iliac joint; this segment is firmly wedged between the medial curved elements of the ilia. By virtue of the interlocking character of this articulation, together with the interposed short and taut anterior and posterior transverse ligaments, it possesses great inherent strength. It is this joint which carries the greater part of the weight of the upper part of the body and is held in place by these broad ligaments and thus, results in very little or no movement of this joint. Through this joint both pairs of pelvic arches become confluent with the sacrum. For this reason alone this is one of the most significant and important articulations. Inside the sacrum is a canal containing roots of the sacral and coccygeal nerves, filum terminals and other important nerves. Because it contains these important structures and because it is situated in a strategically important position to support the upper frame, the ultimate strength of this joint is exceedingly important in the tolerance of the body to high impact "g" force.

It has been mentioned the innominate bone is made up of three distinct bones which fuse at the region of the acetabulum. This fact is important when one attempts to analyze the nature of the fracture from a force delivered medially to the acetabulum, via the greater trochanter of the femur. The large part of the lateral wall enters into the formation of the acetabulum, the cup-shaped socket that received the head of the femur.

The upper part of the socket is directly related to the femoro-sacral arch. The right and left sides of the innominate articulates anteriorly to form the pubic symphysis and posteriorly with the articulating surfaces of the sacrum, and has been mentioned, forms the sacro-iliac joint.

The third wall, the anterior wall, of the pelvic ring is formed by the union of the bodies of the pubic bones from which rami, the superior and inferior rami, extend laterally and backward uniting with the ilium and the ischium of the lateral pelvic walls. The anterior part of the pubic arch may be considered as a counter-arch or tie that unites the weight bearing arches and in such capacity it is vitally important in maintaining the strength of the pelvic in its entirety.

The femur itself is probably the best known of the bones, its importance in supporting the body weight as a structural member has already been discussed. It has additional importance if one considers that it is also a transmitter of force to the hip bone as in a parachute descent. The femur is considered the longest, heaviest, and strongest bone in the skeleton. Its upper end fits into the acetabulum and articulates with the hip joint; its lower end articulates with the tibia via the lateral and medial condyles. Both the upper and lower ends are cartilage clad and will be of some importance in testing the inherent strength of this bone. The head joins the shaft obliquely by the neck at an angle of 125-degrees near the trochanteric region. Because of this, the loading of the femur is eccentric loading in contrast to the concentric loading of a perfectly vertical structural member. The neck and trochanters, greater and lesser, joining the shaft and neck as they do, make them extremely vulnerable to fracture. The obliquely with which the neck joints the head, and hence approaches the acetabulum is important. The greater

the angle the more nearly the loading would approach concentric loading and away from the eccentric loading and hence the stronger the bone becomes as a structural member.

The shaft of the femur is slightly twisted, is thinnest at its middle third. The femur is firmly attached to the lateral wall of the acetabulum by a strong ligament, ligament of head of femur, attached to the pit of the head.

Some mention has already been made of the importance of ligaments in determining the strength of joints. In the region of the acetabulum, the capsular ligament with its thickened part; the ilio-femoral ligament is attached to the lower part of the anterior superior iliac spine; the pubo-femoral ligament is attached to the lateral end of the obturator crest; the ischio-femoral ligament is attached to the ischium below the acetabulum. Of these three ligaments, the ilio-femoral ligament is the most important because of the fact that it is the strongest one of the hip joint and enhances the strength of the articular capsule above and is shaped like an inverted 'Y' whose base is attached medially to the ileum, and its apex is attached to the greater trochanter and the inter-trochanteric line laterally. As this ligament fans out to make the lateral attachment, a thin area is found between the two limbs of the 'Y'. Since the capsule extends over the entire anterior surface of the neck of the femur and is inserted along the inter-trochanteric line, the neck in this region is, therefore, included as part of the joint. Behind the capsule includes about two-thirds of the neck and is, therefore, extra-capsular and should not be considered as a part of the joint.

The sacro-iliac joint is provided with a capsular investment, anterior and posterior sacro-iliac ligaments, which is lined by a synovial membrane. The anterior ligament is actually a broad and rather thin band which closes the joint in front of its entire extent. The posterior ligament is a more robust and thicker structure and is divided into three parts: -

1. Interosseous
2. Short posterior
3. Long posterior

These close the joint behind and form a dense decussation. The interosseous portion, the most directly related part of the ligament of the joint bridges transversely across from the lateral posterior surface of the sacrum to the medial aspect of the ilium adjacent to the joint and is disposed as short isolated fascicles.

Since this research to date has considered mostly the strength of the structures which comprise the joint, a cursory survey of the classification of joints is here given. As has been mentioned, it is these joints that give continuity and maneuverability to the skeleton. Depending upon their function, they may be generally classified as immovable or movable. Also, the chief kinds of joints have developmental differences and on this basis there results three main kinds of joints: -

1. Fibrous joints which are characterized by the fact that they have either arisen in membrane or were preceded by discrete cartilage but has still a membranaceous connection
2. Cartilaginous joint characterized by either continuous cartilage where cartilage has become chondrified
3. Synovial joint, characterized by a cavity surrounded by ligament lined with a synovial membrane which produces synovial fluid

Of special interest is the immovable or slightly movable, sacro-iliac joint, and the synovial joint characterized by the acetabulum or hip joint which has considerable movement.

The strength of the articular ligaments and muscle tension are important factors about a joint. In conditions of continuous stress, such as the hip joint, these ligamentous bands, already described, are most important, whereas they become less important in the weak and lax capsule of the shoulder joint. No ligaments, however, can resist continuous stress without support. Four factors limit movement of a joint: -

1. Apposition of the soft parts
2. Locking of the bones
3. Tension of ligaments
4. Muscular tension

During the initial phases of this research, the problem was first visualized from the view of strength of pelvic girdle by a force delivered to the inferior surface of the neck of the femur; hence, the muscles on the medial surface of the thigh (pectinous, the adductor group of muscles (longus, brevis, and magnus) gracilis, and obturator externus seemed of great importance. During the early stages of investigation, the analysis of this medial mass of muscles was dropped when tests proved that the combined strength of both femurs, together with their architectural attachment to the pelvis, formed an inherently strong and robust joint, irrespective of the muscles which comprise the medial mass of the thigh.

ANATOMICAL

METHODS & RESULTS:

In order to determine the strength of the pelvic girdle, tests were first conducted upon the isolated structures of the pelvis first under static and second under dynamic conditions. Preliminary tests were first conducted on the sacro-iliac joint since by virtue of its position and function it is one of the most important structures in this region.

Gradually applied forces were delivered to the sacro-iliac joint by means of the Olsen Lever Transmitting Machine. The pelvis was first denuded of all the muscles and the vertebral column was cut between the lumbar vertebrae 3 or 4. This was done to make possible the delivery of gradually applied forces to the joint without contact with the crests of the iliac. The structure was then oriented in a cement mold and the cement allowed to gain maximum tensile and compressive strength by curing under high humidity. Bone samples were also kept moist until the time of testing. A 3" x 3" x 1" steel block was then placed over the top of the vertebral segment to permit the delivery of force evenly throughout the entire surface. Reference of Figure #1 will make clear the technique involved.

Specimens were taken from robust male cadavers whose cause of death was known. No samples were tested from cadavers who showed any previous damage to bone tissue.

JOINT	ULTIMATE BREAKING STRENGTH (STATIC LOAD)
Sacro-iliac	Average - 1925-lbs.

The fracture produced under these conditions does not disrupt the sacro-iliac joint at its articulation with the ilia. The bones of the posterior

region are involved; that is, the sacral cornu around each end of the sacral canal moves laterally from the lower end of the sacral canal and splits the vertebral segments of the sacrum on the dorsal surface along the middle of the spinous tubercles. This fracture occurred in all the specimens tested under these static conditions.

This fracture is quite understandable in view of the rigid mounting of the pelvis in the cement mold, since a force now applied to the sacro-iliac joint at the level of the lumbar vertebrae creates not only a vector in the vertical direction, but also a horizontal vector causing a deformation in this direction with consequent elongation in the anterior-posterior pelvic plane. One must then visualize the resultant vector as an oblique vector which acts in the direction of the sacral cornu since it is this lower edge of the projections where the fracture first occurs. This type of fracture is herein illustrated in Figure #2.

The situation is considerably changed when the force is a dynamic one. Samples were again mounted in a cement mold as described above. Forces were dynamically applied to the sacro-iliac joint by means of a pile driver. (see Figure #3). A mass of known weight by this means was accelerated a known distance. The apparatus was especially constructed to deliver a mass in free fall (except for the small amount of friction due to the guide beams) with a means for changing the accelerating mass and height of fall. The guide also made possible the delivery of force at precisely the desired point. A strain gauge (Statham) type accelerometer was then rigidly mounted to the accelerating mass and the force in "g's" was then determined by oscillographic recording. From the formula: $F = M A$

Where F = force in pounds
M = accelerating mass in pounds
A = acceleration in terms of g's

the force in pounds necessary to cause fracture or disjunction of this joint was calculated.

This type of force produces a rupture of the sacro-iliac joint proper at its articulation with the ilia of both sides. As was expected, no fracture of the vertebral segments of the sacrum itself was seen; rather, a disruption of the ligaments, both anterior and posterior short and long ligaments occurred. Again, as was expected, the ligaments themselves were not involved, but in each case the ligaments were torn from their cartilaginous moorings to the sacrum. This seems to indicate, as was also found in the case of the coraco-acromial ligament of the shoulder joint, that ligaments are extremely rugged and capable of considerable strength.

JOINT	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Sacro-iliac joint	270-lbs.

Since this sample had been previously embalmed and somewhat dry, no definite conclusions can be drawn from this sample and additional investigation is indicated to accurately ascertain the ultimate breaking strength of this joint under dynamic conditions. It is the opinion of this investigator, however, that bilateral fracture disjunction will occur under these conditions because a suddenly and violently applied force would cause little deformation in the anterior-posterior direction and results in one main vector, that acting principally in vertical direction. It is for this reason that the breaking load and fractures differ considerably under static and dynamic conditions.

Reference is here made to Figure #4 - No. 1 for further clarification of fracture produced.

POSTERIOR VIEW OF PELVIS SHOWING FRACTURE UNDER
STATIC LOADING

SHOWING LATERAL MOVEMENT
SACRAL CORNU AND CENTRAL FRACTURE
OF SACRAL VERTEBRAE

FIGURE 2

PILE DRIVER

FIGURE 3

ANTERIOR VIEW OF PELVIS

1. SACRO-ILIAC JOINT
2. ATTACHMENT OF ANTERIOR LIGAMENTS
3. LATERAL WALL OF ACETABULUM
4. SYMPHYSIS PUBIS

FIGURE 4

A second series of tests was conducted on the femur, denuded of its muscles and under static conditions. This was done by gradually applying a force to the head of the femur with the Olsen Lever Transmitting Machine. This series was undertaken since the femur was first determined to be the most important region for the type of deceleration experienced in parachute descent and from the general consideration of the standing position in which the weight of the body is transmitted, via the sacro-iliac joint, the acetabulum to the superior and lateral surface of the head of the femur.

Preliminary tests were first conducted in the same manner as previous investigators in order to compare our data with theirs.

The denuded femur was oriented in the testing machine so that a gradually applied force made contact with the head of the femur at one point on the superior surface (point loading) and at a point on both the medial and lateral epicondyles. A force of 2000-lbs. was sufficient to cause fracture when these samples were tested to destruction.

The breaking strength of 2000-lbs. and location of fracture compares favorably with the results obtained by previous investigators.

This condition shows the greatest bending moment to be in the region of the neck of the femur between the junction of the neck with the head and greater and lesser trochanters, travelling vertically and in such a way, because of the anatomical nature of the articular capsule, that the fracture is intracapsular anteriorly since the capsule extends over the entire anterior surface of the neck of the femur and is inserted along the intertrachanteric line, and extracapsular behind the capsule includes only about two-thirds of the neck. The fracture is, therefore, included as a joint fracture in front, but not as a joint fracture behind.

JOINT	ULTIMATE BREAKING STRENGTH (STATIC)
Femur (point loading)	2000-lbs.

Observations of the results of these preliminary tests gave information which was used as the basis for another series of tests on the femur. Flat deformed areas were noted on the cartilage-clad head and epicondyles where contact was made between the femur and the heads of the Olsen Lever Transmitting Machine. Obviously, these deformed areas absorbed some energy before the ultimate breaking strength of the femur was reached. On the basis of this data, further investigation was conducted on the denuded femur by placing cement casts on the articular surfaces of the epicondyles and the head of the femur (area loading) in order to more correctly simulate the actual body condition. This method has advantage over previous methods of determining strength in that it makes possible the delivery of force over the area of the head of the femur and epicondyles normally in contact with the articular surfaces. No flattened out area of deformation were noted when these samples were subjected to gradually applied forces by this method; hence, no energy is absorbed.

JOINT	ULTIMATE BREAKING STRENGTH (STATIC)
Femur (with cast)	1600-lbs.

Since no energy is absorbed in deformation of the cartilage-clad articular surfaces, one would expect to find the ultimate breaking strength somewhat lower in the case of the femurs subjected to gradual forces with

the casts. Inspection of the above data and comparison with the breaking strength of the former shows this to be the case.

More important, however, is the difference in the nature and type of fracture under this condition. The fracture produced in the former case has already been described as being intracapsular in front and extracapsular behind. The fracture under the latter condition is completely extracapsular; that is, does not involve the joint proper since it occurs laterally to the neck and carries with it part of the trochanters, and by virtue of this fact indicates also a change in the position of the greatest bending moment.

We believe at this point that the latter method, herein described, approximates more closely the intact condition and describes more accurately the behavior of the femur both with respect to fracture and ultimate breaking strength.

Figures #5, and #6 will make the techniques used in testing this structure and the types of fractures produced clear.

FIGURE 5

FIGURE 6

— ■ FRACTURE PRODUCED BY AREA LOADING

---- ■ FRACTURE PRODUCED BY POINT LOADING

A description has already been given of the nature of the shaft of the femur (page 26) with particular reference to its being thinnest at the middle of the shaft. This at once emphasizes a weak point in its architecture and it seemed, therefore, desirable to know its strength at this point. A second factor presented itself from the consideration that subjects in the downward ejection seat with safety harness attached were subjected to an impinging force at the approximate middle of the shaft with this force acting in the anterior-posterior direction.

Casts were again placed over the articulating surfaces of the head, medial and lateral epicondyles of the femur and a gradual force was applied to this structure in the anterior-posterior direction at the middle of the shaft in the manner indicated in Figure #7.

STRUCTURE	ULTIMATE BREAKING STRENGTH (STATIC)
Middle of shaft of femur	1700-lbs.

A fracture, somewhat jagged in nature, occurred immediately below the impinging force. This fracture was similar to that obtained if a hollow wooden cylinder was subjected to a bending moment beyond its elastic limit.

FIGURE 7

On page 6 mention was made that one of our purposes in this investigation was to contribute to the vast amount of information which is ultimately to be used in the construction of an anthropomorphic dummy. This was to be used in lieu of live human subjects in the various phases of work on deceleration where it was neither desirable nor possible to use live human bodies. With proper construction, this dummy is supposed to exhibit the same tensile, compressive strength and the same damping effects as the human body.

In line with this long range plan, the strength of the clavicle was tested by means of the Olsen Lever Transmitting Machine and this data compared with the ultimate breaking strength of a model clavicles provided by the Wright-Patterson Air Force Base, Dayton, Ohio.

Samples were mounted in cement casts as indicated in Figure #8 and a gradual force was applied at the junction of the medial two-thirds with the lateral one-third. A fracture of the human clavicle is produced approximately 3 c.m. medial to the acromio-clavicular articulation. This is the area, i.e., the lateral one-third, in which the compact layer of bone becomes thin and, therefore, weak.

STRUCTURE	ULTIMATE BREAKING STRENGTH (STATIC)
Clavicle	230-lbs.
Model of Clavicle	260-lbs.

Model clavicles were subjected to gradual forces by exactly the same technique. Though both models and human clavicles have almost identical breaking strength, the location of the fracture, as was expected, was very

dissimilar. Model clavicles fractured at the junction of the medial two-thirds with the lateral one-third or immediately below the point of applied force. This points out one great difficulty in the construction of a model, the fact that the material for construction of a dummy is ultimately homogeneous in contrast to the heterogeneous construction of the elements of the human body.

FIGURE 8

In order to acquire preliminary data relative to the strength of the hip joint (inclusive of the acetabulum, head and neck of the femur, and the upper extremity of its shaft), a series of pelves have been prepared by denuding the musculature of both pelves and femurs keeping intact the ligaments of the joint, the ilio-femoral, pubo-femoral, and the ischio-femoral. These ligaments constitute the chief part of the articular capsule of the joint. Since the capsule extends over the entire surface of the neck of the femur and is inserted along the inter-trochanteric line, as has already been pointed out, the neck in this region, therefore, must be included as a part of the joint. Behind the capsule includes about two-thirds of the neck, and as a result the lateral portion of the posterior aspect of the neck is extracapsular and should not be considered as part of the joint.

The dynamic strength of the joint was investigated by application of force delivered at the inferior surface of the neck of the femur in a manner to simulate the action of a parachute harness. Figure #9 will make this method clear.

For these experiments two bodies were used. By graduated falls up to the limit of tolerance, damage was produced as follows: -

In the first case (partially denuded of muscles) the joint capsule was ruptured. This occurred in the weak area of the ilio-femoral ligament. The ilio-femoral ligament, the strongest one of the hip joint, enhances the strength of the articular capsule above, is shaped like an inverted 'Y' whose apex is attached to the ilium, and its base to the greater trochanter and the inter-trochanteric line of the femur laterally. As the ligament fans out to make the lateral attachment, a thin area is found between the two

limbs of the 'Y'. This is the vulnerable place in the joint and the area that ruptured permitting the head of the femur to escape when subjected to 600-lbs. of force.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
1st Sample (denuded)	600-lbs.
2nd Sample (completely intact)	7500-lbs.

In the second specimen (completely intact), the following results occurred by graduated free falls to the limit of tolerance: -

1. A fracture, unilateral, through the superior ramus of the pubis, thus breaking the tie or counter arch of the femero-sacral arch of the pelvis. This allowed the pelvis to spread and as a result -
2. A bilateral fracture disjunction of the sacro-iliac joint. The force necessary to cause fracture is summarized above.

Figure #10 will make clear the fracture involved in this method of testing the dynamic strength of the hip joint.

FIGURE 9

The description of the pelvis showed that the anterior part of the pelvic ring is formed by the union of the bodies of the pubic bones from which rami, superior and inferior, extend laterally and backward uniting with the ilium and ischium of the lateral pelvic walls. The anterior part of the pelvis may be considered as the counter arch or tie that unites the weight bearing arches and in such a capacity, it is vitally important in maintaining the strength of the pelvis in its entirety.

Samples of pelvis with soft tissue intact above the symphysis but with pelvic contents removed were subjected to violence by means of the pile driver (Figure #3) already described. Forces of graduated intensity were applied to the pubic region in an anterior-posterior direction to the degree where fractures were induced. By virtue of the resiliency of this part of the pelvic ring, a force of 595-lbs. was required before a fracture resulted.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Symphysis Pubis	595-lbs.

In some tests, the superior ramus fractured, and in others, both superior and inferior rami were involved in the fracture. Usually the injury was unilateral, but in one case it was bilateral and included both rami.

In these fractures, the damage was not confined altogether to the anterior wall of the pelvis, but to the posterior wall as well, i.e., the sacro-iliac joint. However, the damage to the sacro-iliac joint is a secondary involvement - fracture disjunction. The inference is that the pubic rami are damaged and the principal weight bearing arches having lost the tie which

keeps them united, spread open and only then involves the joint of the posterior wall.

Reference to Figure #10 will make clear the location of fracture under this condition of violence.

BONY PELVIS SHOWING REGIONS OF FRACTURE

1. UNILATERAL OR BILATERAL FRACTURE DISJUNCTION.
 2. FRACTURE OF MEDIAL WALL OF ACETABULUM.
 3. FRACTURE OF SUPERIOR RAMUS - BILATERAL OR UNILATERAL.
 4. FRACTURE OF INFERIOR RAMUS - BILATERAL OR UNILATERAL.
- 3 AND 4 ARE COUNTER TIES OF WEIGHT BEARING ARCHES OF PELVIS.

FIGURE 10

Another series of tests were conducted on the sacro-iliac joint in order to determine whether or not a force delivered immediately to this joint would involve fractures of the femurs. It has been ascertained that violence delivered to the inferior surface of the femur (Figure #9) produces no fractures involving the femurs, but involves rather the weight bearing arches, since the combined strength of both femurs gives an extremely rugged and strong structural member.

With this data as background, the problem at this point may be clearly stated: - "Will violence delivered to the head of the femurs, via the sacro-iliac joint and weight bearing arches, involve fractures of the femur"?

Pelves were denuded of all muscles. The ligaments of the hip joint and sacro-iliac joint were, however, kept intact. The sample was then mounted in a cement cast up to about the distal third of the femur with the sample oriented as in standing. By means of the pile driver (Figure #3) forces of graduated intensity were delivered directly to the sacro-iliac joint to the point where fractures were induced. Inspection of the data given below shows that a force of 830-lbs. is of sufficient intensity to cause fractures involving, as was expected, the sacro-iliac joint.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Sacro-iliac joint	830-lbs.

This was a bilateral disjunction as was noted in several of the preceeding tests. No rupture of ligaments occurred. Rather, they pulled loose from their cartilaginous moorings to the skeleton.

The inference from these tests shows also that the combined strength of both femurs is stronger than the weight bearing arches.

Reference is here made to Figure #10 of the preceeding sections for the location of fractures.

The formation of the lateral wall of the pelvis and the manner in which the lateral wall enters into the formation of the acetabulum, the cup-shaped socket that receives the head of the femur, has been described. The upper part of the socket is directly related to the femoro-sacral arch and on the basis of this consideration, it is advisable in determining the ultimate strength of the structure of the pelvis to know the strength of the lateral wall of the acetabulum as well. Knowledge of strength and the location of fractures is important also when one considers that the delivery of force, such as during a fall on the side of the hip, may force the head of the femur into the pelvic cavity.

In determining the strength of this wall (Figure #4) force was applied first to the greater trochanters in the dry pelvis and later to the soft tissues overlying the greater trochanters in pelvis in the recent state. The pile driver, which as already been described (Figure #3) was used to deliver a force whose acceleration and mass could be controlled up to the limit of tolerance.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Lateral wall of acetabulum	800-lbs.

The force was increased gradually increased to 800-lbs. which was of sufficient intensity to induce fractures of the medial wall of the acetabulum and to regions of its epiphyseal junctions. Thus, the fracture may be radiating in character and accompanied by the bending in of the central part of the acetabulum. In one instance, the head of the femur was driven into the pelvic cavity-acetabular fracture with central dislocations.

Since none of the tests of the lateral wall destroyed the integrity of the femoro-sacral arch, though the force was delivered directly below its anterior extremity, it follows therefore, that the sacro-iliac joint was not involved in the initial injury.

Up to this point, the individual structures of the pelvis and the hip joint have been tested for their ultimate strength and for the location and extent of the resulting fractures. The existence of weight bearing arches have already been mentioned on two occasions: -

1. Fractures involving the sacrum with a force delivered to the inferior aspect of the head of the femur
2. Fractures involving the sacrum with a force delivered to the anterior surface of the symphysis pubis.

With this definite and important inter-relationship indicated, an additional series of tests were conducted to determine the part played by both the anterior and posterior pelvic walls on the inherent strength of the entire pelvic ring.

Pelves in this series were mounted in cement up to and including the distal third of the femurs and has heretofore been described. The viscera in the pelvis were removed; the muscles and ligaments were, however, left completely intact. Forces of gradual intensity up to the limit of tolerance were delivered by means of the pile driver directly and immediately to the sacro-iliac joint in order to interrupt the strength of the posterior pelvic wall. Inspection of the data given below shows that in this case, a force of 775-lbs. was of sufficient intensity to cause a fracture disjunction of this point.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Sacro-iliac joint	775-lbs.

This figure compares favorably well with the strength of this joint as presented in the preceeding section in which, in that particular sample,

a force of 830 caused a fracture disjunction of this same joint.

With the destruction of the posterior pelvic wall, and hence, an interruption of the weight bearing arches, a force was then delivered directly and suddenly to the symphysis pubis, which it must be recalled, is the union of the conjoined rami, i.e., the union of the superior and inferior rami anteriorly. A force of 350-lbs. is of sufficient intensity to cause a fracture in this area.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Symphysis pubis with fractured sacro-iliac joint	350-lbs.

Fractures in this case were identical in location to those found in all other cases, i.e., they involved a bilateral fracture of both the superior and inferior ramus.

Having thus visualized the problem from the point of view of the support that the anterior wall gives the posterior wall, the reverse question also presented itself: - "What support does the posterior wall give the anterior wall?"

Data has already been given relative to the strength of the joint, but will be repeated here for purpose of clarity. Force was delivered by means of the pile driver to the anterior surface of the symphysis pubis in order to disrupt the union of the weight bearing arches in front. Inspection of these data below shows a force of 595-lbs. was of sufficient intensity to cause a bilateral fracture involving both the superior and inferior rami.

STRUCTURE	ULTIMATE BREAKING STRENGTH (DYNAMIC)
Symphysis pubis	595-lbs.
Sacro-iliac joint	480-lbs.

After disruption of this joint, the sample was mounted in cement cast as was the case with preceeding samples. Force was again delivered directly and suddenly by means of a pile driver to the sacro-iliac joint. Inspection of the above data shows a force of 480-lbs. was of sufficient intensity to cause a fracture of this joint. Fractures were again identical in nature to those herein described (Figure #10) which involved this joint.

DISCUSSION

II. ANATOMICAL

A history of the development of studies relative to the strength of bones and the methods for testing has already been reviewed. Our approach to the problem of strength of the pelvic girdle, inclusive of the acetabulae and femurs, was to determine the ultimate breaking strength of the isolated and intact series of structures that comprise the hip joint. If knowledge of both the static and dynamic loads required to produce and the location of fractures are known, we should be able to provide some reasonable estimate of the force which could be applied to this structural unit with minimum damage to the individual. The same information should be particularly useful in the construction of an anthropomorphic dummy to be used in experimentation where the approach to the problem by using live human individuals might subject them to unforeseen hazard. To this end, we hope we have been successful.

We have selected the approach by studying ultimate breaking strength of bones on the basis that it provided more useful information than the study of strength by "stress coat" or by milling bones to desired size and studying strength per unit volume. Though our approach has involved many difficulties, principally equipment, we believe the methods to be fundamentally sound and the results to be accurate to $\pm 15\%$.

The difficulties in obtaining cadaver materials for this type of experimentation should be obvious, especially since we have endeavored to use only recent state materials rather than ordinary Medical Dissecting Room materials.

The importance of the adductor group of muscles was indicated in the early stages of this investigation for the reason that the area of the femur subjected to violence from a free fall, such as jolt received during opening of parachute, will depend upon the nature of the adductor group of muscles. From the data indicated in the series of experiments in which violence was delivered to the inferior surface of the neck of the femur and in the experiments in which this medial mass of muscles was removed, no fractures were obtained which involved either the neck or the trochanters of the femur, such as were obtained on isolated tests on the femur, irrespective of the nature of the applied load.

Attention was, therefore, focused from the importance of this medial mass of muscles to a survey of the weight bearing arches, especially since fracture obtained in the completely intact specimen occurred: -

1. as a unilateral fracture through the superior ramus of the pubis, thus breaking the tie or corenter arch of the femoro-sacral arch of the pelvis
2. as a bilateral fracture disjunction of the sacro-iliac joint.

It is, therefore, important at this time to emphasize certain structural areas of the pelvis to which reference has already been made; namely, the weight bearing arches, two in number and bilateral in position.

One pair extends from the superior pubic rami backward and above the acetabula to the sacrum through the ilio-sacral joints. See Figure #11. This is in fact a bony buttress and may well be designated the femoro-sacral arch and receives the weight of the body in standing. The other pair of arches passes from the ischial tuberosities upward and behind the acetabula to the sacrum through the sacro-iliac joint. See Figure #12. This constitutes another bony buttress of the ischio-sacral arch and functions in

weight bearing in the sitting position. These arches are further strengthened by counter-ties; the femoro-sacral is tied in front at the symphysis by the superior pubic rami and the ischio-sacral at the pubic symphysis by the conjoint rami of the ischium and pubis. In determining the strength of the pelvis these arches are important and must be carefully considered in the conduction of tests on this region. On the basis of this information, a series of tests was designed to determine the strength of the sacrum, since through this joint both pairs of pelvic arches become confluent with the sacrum and for this reason alone, it constitutes one of the most significant articulations. The strength of this joint and type of fracture has already been described.

The strength of the lateral wall of acetabulum was also determined because it is directly related to the femoro-sacral arch. In spite of this relationship, however, no tests produced fractures destroying the integrity of the femoro-sacral arch though the force was delivered directly below its anterior extremity; it follows, therefore, that the sacro-iliac joint was not involved in the initial injury.

The remaining wall, the anterior wall, is important because this part of the pelvic ring is formed by the union of the bodies of the pubic bones from which rami, the superior and inferior, unite the ilium and ischium of the lateral pelvic walls. It unites the weight bearing arches in front. From the description of fracture obtained when this anterior wall is subjected to stress to the limit of tolerance, it is at once apparent that a definite and well defined relationship exists. The secondary involvement of the sacro-iliac joint, fracture disjunction, by fractures of the symphysis or anterior wall carries with it the

inference that damage to the rami, superior or inferior, damages the principal arches and spread open the joint.

A remaining series of experiments was designed to correlate the strength that the anterior and posterior wall give to the inherent strength of the entire pelvic ring. The posterior wall was first disrupted before tests were conducted on the anterior wall and conversely on another sample, the anterior wall was disrupted before tests were conducted on posterior wall. From the data presented herein, one may say generally that the posterior and anterior wall play equal part in the inherent strength of the entire pelvic ring.

CONCLUSIONS

Methods, strength, and type and location of fractures have been described for the various structures of the pelvis, inclusive of the acetabulum and femur. In the intact condition, fractures of the femurs do not occur when this force is applied by cables to the inferior surface of the neck of the femur, or when a force is applied to the base of the sacrum. Fractures of the lateral wall of the pelvis and acetabulum do not produce fractures or disjunction of the sacro-iliac joint. The strength of the pelvic ring is directly related to the strength of the anterior and posterior wall and as such, the strength of these walls must be known to correctly ascertain the inherent strength of the entire pelvic ring. Primary fractures of the pubic ramus-unilateral or bilateral, produce secondary fractures or disjunction of the sacro-iliac joint by disrupting the integrity of the counter-arch of the pelvis. The counter arch is, therefore, the important factor in maintaining the inherent strength of the pelvis for the reason that it ties anteriorly the weight bearing arches that are confluent with the sacrum.

ANTERIOR VIEW

SOLID LINE - FEMORO SACRAL ARCH
BROKEN LINE - COUNTER ARCH OR TIE

FIGURE 11

POSTERIOR VIEW

SOLID LINE - ISCHIO SACRAL ARCH

BROKEN LINE - COUNTER ARCH OR TIE

FIGURE 12

HIGH SPEED X-RAY STUDIES

METHODS & RESULTS

Previous data from this laboratory - Joffe (110) - shows that congestion of the lungs interpreted as congestive heart failure is the primary result of deceleration into abdominal safety belts, a symptom characteristic of non-penetrating chest injury. Since literature on the effects of abdominal safety belts is nil, a survey was made of both the clinical and experimental literature on non-penetrating chest injury in order to determine the evidence for production of cardiac failure. In line with our second objective, high speed X-ray studies were carried out with the assistance of the Allegheny Ballistic Laboratory, Cumberland, Maryland.

Since none of the theories gleaned from the available literature on non-penetrating chest injury explained completely the mechanism which we surmised was responsible for cardiac failure, it seemed likely that information obtained by X-ray at the instant of deceleration might supply in part the answer to this question.

Dogs were harnessed to an aluminum frame in such a manner as to permit animals to fall freely a distance of 5-1/2 feet in superior-inferior position. Two vertical "I" beams about 24" apart (the width of the frame) were used as guides for this frame. A 3/4" hemp rope was used as a tail line and was securely fastened around the dogs abdomen. At the instant of deceleration, a force of 500 - 600-lbs. was delivered to the abdomen and the thorax by the action of the belt.

Figure #12 shows the manner in which the dogs were fastened to the aluminum frame and the manner in which the belt cuts into the abdomen at the end of the fall.

A Westinghouse high speed X-ray apparatus (shown in the same figure) was synchronized in such a manner that serial X-ray photograph at the rate of 50 frames per second were taken at the instant of deceleration for approximately 1-1/2 seconds. The actual size of the individual frames was 2-1/2" x 8". Several difficulties are obvious in this type of experiment: -

1. The size of the X-ray plate was not large enough to show a clear cut outline of the entire heart. It was possible, however, to observe changes in maximum transverse diameter, maximum right (T_R) and maximum left (T_L) projections, as well as changes in surface area of cardiac silhouette.
2. It was not always possible to direct the fall of the dogs to the set position of the X-ray machine and to the degree that the heart itself was always visualized.
3. Because of the extremely fast speed of the machine and the thickness of the thoracic cage of the dog, many of the individual frames in the roll were under-exposed and, consequently, no cardiac silhouette could be observed.

Control and experimental runs were made in both the anterior-posterior and lateral positions. Protocols for each of the seven dogs, accompany this dissertation, together with statistical summary of results.

Results were sufficiently striking in Roll #1 so that separate measurements were made on a total of 63 frames.

Figure #13 and #14 shows the type of X-ray shadow taken at the instant of deceleration. Figure #12 shows dogs in anterior-posterior position and lateral position for control and experimental runs. Figure #15 shows the type of measurements taken from the individual frames of the entire roll (contains 63 frames).

Maximum transverse = x

Maximum right and left projections = T_R and T_L respectively

Area of cardiac silhouette given by equation: -

$$A = \frac{1}{4} L B$$

Where A = area

L = long diameter

B = broad diameter

These same measurements are used in the clinic as valuable diagnostic aid in determining size of the cardiac shadow.

Individual measurements are recorded in Table I. The change in values, indicated in the same table are plotted as ordinates with time as abscissae.

HEART SIZE MEASUREMENTS

Legend:

Transverse Diameter = $T_R + T_L$ (sum of maximum projections to right and left heart borders from midline)

Transverse Diameter = X (maximum projection at the level indicated)

Long Diameter = L (extends from junction of cardiac silhouette and vascular pedicle on right to apex on left)

Broad Diameter = B (greatest diameter of cardiac shadow perpendicular to long diameter)

Calculated area from Long and Broad Diameters:

$$A = \pi / 4 \quad L \cdot B$$

FIGURE 13

FIGURE 14

Film No. 22

Film No. 39

Film No. 44

Film No. 48

Film No. 59

FIGURE 15

Film No. 65

Film No. 69

Film No. 75

Film No. 78

Film No. 84

FIGURE 16

DISCUSSION & CONCLUSIONS

An inspection of the protocols shows, and it has already been mentioned, that complete data could be obtained from only one roll of the total of 14 rolls. It must at the same time be clearly pointed out that this was due in the majority of cases to underexposed film caused by the rapid speed at which the X-ray machine was operated. It must also be pointed out that Figures #13 and #14 are reduced in size from the originals and the heart shadows, therefore, are not as clearly defined.

Four of the rolls showed evidence of transverse enlargement, but unfortunately, these changes could not be analyzed in the same manner and to the same degree as in roll #1 from which the data in Table 1 was taken. It is, therefore, desirable to fortify our argument concerning the production of cardiac damage with many measurements on roll #1. A total of 189 separate measurements was made on this roll and the results plotted on separate graphs. Any one graph by itself might be considered a matter of chance; however, the element of chance is reduced if separate and distinct measurements in graphs follow the same type of curves as graph

Inspection and superimposing these three graphs show that peaks and troughs occur in most instances at precisely the same interval of time. We must also make clear that plotting of data from Table 1 does not give the smooth curve indicated in the three graphs. It showed instead an irregular curve with many small vibrations. This question immediately presented itself: - "How should this data be treated to indicate the phenomenon most clearly?" Several factors were considered before these data were plotted: -

1. Precise measurements could only be made with an accuracy of ± 2 mm, therefore, differences of 2 mm were not considered to be significant.
2. Examination of subsequent accelerometer readings under the same conditions as these experiments show damping effects of biological tissue consisting of several peaks rather than one bell-shaped curve. It is, therefore, justifiable to consider changes in transverse diameter and area of the cardiac silhouette in terms of damping with several peaks.
3. These data could be statistically treated as a regression line which would give a straight line phenomenon. This treatment is not justified on the basis of accelerometer readings showing several oscillations.
4. These data could be treated as moving averages which would give a smooth drive to some extent. However, since these data are presented as qualitative rather than quantitative measurements, our treatment of smoothing the curves without recourse to moving averages is justified and the theory for production of cardiac damage as a consequence of these data is believed valid.

DISCUSSION & CONCLUSIONS

A brief description of the mechanisms postulated by investigators in the field of non-penetrating chest injury will first be given because it is entirely possible that to some extent these mechanisms also play a part in the production of injury. Five mechanisms have been suggested: -

1. Work at Randolph Field (103) suggests that the vagus is important in the mediation of conduction disturbances and ectopic contractions. In their group of three dogs, conduction disturbances were found less frequently in vagotomized animals and more frequently than in the normal animal in the group of animals that had been given physostigmine.
2. The forcing of the blood into the ventricle causing an increase in intracardial pressure has been suggested, and in my opinion, appears to be a likely cause of damage. In support of this, the work of Beck and Bright (10) is cited. By applying pressure to the legs and abdomen and forcing the blood back into the ventricle very rapidly caused rupture of the valves and of the myocardium and overdistension of the heart. The degree of damage was directly related to the ability of the heart to accommodate to the increased blood supply.
3. The phase of the cardiac cycle has been mentioned as a means of inciting damage since the relaxed heart showed less damage than the distended heart. A Randolph Field report (104), however, showed that there was no relationship between the degree of electrocardiographic change and the phase of the cardiac cycle at which impact occurred.
4. Sigler (24) (25) has stated that trauma of the heart is frequently overlooked because of the feeling that the chest wall and the cushion effect of the lungs prevents trauma. However, the fact that the heart has a rather loose attachment makes it vulnerable to practically any force. Joffe (110) has shown that a force delivered, via the chondrocostal arch, shows no damping effect, and the force as such, delivered to the arch is transmitted as such to the heart.
5. Several investigators support the idea that a positive pressure wave is set up in the great vessels and is transmitted to the heart and responsible for damage. Potain in 1894 proposed such an idea which he later supported with experimental evidence showing heart rupture with pressure differentials of 896 mm Hg.

These experiments suggest that the mechanism by which cardiac damage is produced in rapid deceleration involves the action of the belt in suddenly blocking blood flow in the abdomen, both in the vena cava and the abdominal aorta. Since the flow of blood from the upper region of the body is toward the heart, the effect produced is similar to that of a closed liquid system subjected to a force from below and above. Therefore, the heart is squeezed between these two forces and is stretched in the transverse direction. This phenomena is analogous to the deformation of a rubber balloon filled with water which is suddenly and forcibly deformed by forces acting from below and above. In these experiments, the changes noted either diminished or completely disappeared within a fraction of a second after the force was applied. Even so, it is possible that this force might produce cardiac pathology by momentarily stretching the muscle beyond its limit of extensibility. Furthermore, it is likely that higher forces of deceleration might result in permanent deformation of the myocardium.

SUMMARY OF HIGH SPEED X-RAY STUDIES OF DOG THORAX AFTER RAPID DECELERATION

Dogs were decelerated with 3/4" hemp rope from a free fall of 5-1/2-ft. with a force between 500 - 600-lbs. All dogs lived and showed no gross pathology at autopsy.

At no time could any evidence of eventration or herniation of the hemidiaphragms be identified.

No evidence of fracture of the thoracic cage was noted.

Only four rolls demonstrated possible diffuse cardiac enlargement. Of the four that demonstrated questionable enlargement of the pulmonary artery segment or outflow tract, only two showed cardiac enlargement as well (#3 and #1).

Of the three that demonstrated coudiness in the lung fields, only one was of more than the costo-phrenic angles.

The most striking changes of all occurred in #1 where there was diffuse infiltration in the lung fields bilaterally, associated with cardiac enlargement and prominence of the pulmonary artery segment. All of the changes disappeared before the roll was completed.

The findings that of the 23 visualized hemidiaphragms, 13 changed in location suggests that the animals "bounced" one or more times at the completion of their drop.

CUMBERLAND PROJECT - DEPT. OF PHYSIOLOGY

STATISTICAL SUMMARY OF FILMS

Number of rolls	28			
AP	7	Light films	1	8
Laterals	8	Light films	5	13
Obliques	7			<u>7</u>
				28

Range of exposures/roll - 49 to 88

CARDIAC CONTOUR

Unchanged	11	
Inadequately seen	10	
Incr. diameter	4	
? inch pulmonary artery segment	4	(of which only two were the same as (increase in total diameter

LUNGS

Clear	15
Clouded, but cleared	1
Clouded, but did not clear	3
Not clearly seen	9

DOG #1

Sex . . . Female
Weight . 24-lbs.

	HEART CHANGES	LUNG
Roll #1 Drop - 5-ft. 6" Position - anterior posterior	Results of data from this experiment is graphed in figures Increase in the prominence of the artery segment noted	#31 obliteration of costo-phrenic angle #33 two-thirds of lung field oblit- erated #34 left inferior half of lung oblit- erated
Roll #2 Drop - 5-ft. 6" Position - lateral	Maximum change noted from 7.6 cm to 8.5 cm	Clear throughout Light exposure

DOG #2

Sex . . . Male
 Weight . 15-lbs.

	HEART CHANGES	LUNG	REMARKS
Roll #3 Control Position . anterior posterior	Maximum change noted 0.5 cm	Clear throughout	
Roll #4 Control Position . anterior posterior	No evidence of change	Clear throughout	
Roll #5 Drop - 5-ft. 6" Position . anterior posterior	Maximum change noted This is maximum change noted, but not enough data to plot as in dog #1	#4 clear #5 clouding along cardiac border #12 border clears	Light exposure
Roll #6 Drop - 5-ft. 6" Position - lateral	#3 - 8 cm #4 - 7 cm #85 - 6.5 cm	#3 lung field clear posteriorly but the inferior region is cloudy throughout	Changes appear in both anterior cardiac space and retro-card space

DOG #3

Sex . . . Male
 Weight . . 22.5-lbs.

	HEART CHANGES	LUNG	REMARKS
Roll #7 Control Position - anterior posterior	No changes noted	Clear throughout	
Roll #8 Control Position - anterior posterior	The heart could not be adequately seen because of light exposure		
Roll #9 Drop - 5-ft. 6" Position - lateral	Heart was obscured by the dog's elbows		
Roll #10 Drop - 5-ft. 6" Position - anterior posterior	#7 Transverse dia. 8 cm #25 Transverse dia. 8.5cm #30 Transverse dia. 9.5cm	No evidence of change	

DOG #4

Sex . . . Female
 Weight . .16.5-lbs.

	HEART CHANGES	LUNG	REMARKS
Roll #11 Control Position - anterior posterior	No evidence of change in trans- verse diameter	Clear throughout	
Roll #12 Control Position - lateral	No evidence of change	Clear throughout	
Roll #13 Drop - 5-ft. 6" Position - lateral			Exposure of thi film too light to permit measurements
Roll #14 Drop - 5-ft. 6" Position - anterior posterior	Minimal suggestion in this roll of cardiac enlargement in the area of the out- flow tract on the left.	Clear	

DOG #5

Sex . . . Female
 Weight . .13-1/2-lbs.

	HEART CHANGES	LUNG	REMARKS
Roll #15 Control Position - anterior posterior	No evidence of change	Clear throughout	
Roll #16 Control Position - lateral	No evidence of change	Clear throughout	
Roll #17 Drop - 5-ft. 6" Position - lateral	No definite evidence of change in transverse dia- meter, but a prom- inence of the pul- monary artery segment is noted	#9 right central lung field cloudy	
Roll #18 Drop - 5-ft. 6" Position -	Roll too light to permit measurements		

DOG #6

Sex . . . Male

Weight . 21.5-lbs.

	HEART CHANGES	LUNG	REMARKS
Roll #19 Control Position - anterior posterior	No evidence of change	Clear throughout	
Roll #20 Control Position - lateral	No evidence of change	Clear throughout	
Roll #21			Belt broke; therefore no measurements were taken on this roll
Roll #22			Ditto
Roll #23 Drop - 5-ft. 6" Position - lateral	Questionable change appearing in this experiment amounting to approximately 1.5 cm	Clear throughout	
Roll #24 Drop - 5-ft. 6" Position - anterior posterior	Unable to evaluate heart changes be- cause of light exposure	Lung bases clear	

DOG #7

Sex . . . Female
 Weight . 11.5-lbs.

	HEART CHANGES	LUNG	REMARKS
Roll #25 Control Position - anterior posterior	No absolute evidence of change	Clear throughout	
Roll #26 Control Position - lateral	No evidence of change	Clear throughout	
Roll #27 Drop - 5-ft. 6" Position - lateral	Possible 1 cm change between film #10 and #30	Lungs appear first cloudy posteriorly; the anterior cardiac phrenic angle re- mains clear	
Roll #28 Drop - 5-ft. 6" Position - anterior posterior	Poor positioning of animal made it impossible to make cardiac measurements	Right lower lobe gradually becomes cloudy and remains that way	

FILM NO.	MAXIMUM TRANSVERSE DIAMETER	CHANGE	'L' INTERPOLATED	'B' INTERPOLATED	/4 L B	CHANGE IN /4 L B	T _R	T _L	T _R + T _L	CHANGE IN T _R + T _L
Film #1 to 21 show the animal in the process of falling; therefore, no measurements can be made during this period.										
22	64	control film	81	72	45.0	Control	43	27	70	
23	-	-	-	-	-	-	-	-	-	
24	-	-	-	-	-	-	-	-	-	
25,26	-	-	-	-	-	-	-	-	-	
27	68	4	85	76	50.0	5	42	30	72	2
28	71	7	83	74	48.3	3.3	58	12	70	0
29	71	86	86	76	51.4	6.4	52	21	71	1
30	71	7	81	81	51.6	6.5	53	21	74	4
31	71	7	89	82	57.4	12.4	54	21	75	5
32	71	7	89	74	51.8	6.8	55	21	76	6
33	72	8	90	75	52.9	7.9	53	23	76	6
34	-	-	-	-	-	-	-	-	-	
35	82	18	97	76	57.7	12.7	58	31	89	19
36	71	7	93	67	48.9	3.9	57	19	76	6
37	74	10	89	72	50.0	5.0	61	16	77	7
38	77	13	90	77	54.4	9.4	64	17	81	11
39	80	16	94	80	58.9	13.9	65	20	85	15
40	79	15	95	79	58.9	13.9	63	21	84	14
41	79	15	92	80	57.7	12.7	61	19	80	10
42	80	16	95	81	60.4	15.4	62	21	83	13
43	76	12	92	80	58.9	13.9	58	22	80	10
44	74	10	92	79	57.0	12	54	24	78	8
45	79	15	93	81	59.1	14.1	53	27	80	10
46	79	15	94	81	59.7	14.7	53	25	78	8
47	82	18	95	83	62.0	17.0	52	28	80	10
48	82	18	98	81	62.5	17.5	51	30	81	11
49	80	16	97	81	61.7	16.7	50	30	80	10
50	83	19	101	84	67.0	22.0	50	33	83	13
51	82 79	15	97	84	64	19.0	48	32	80	10
52	79	15	98	83	63.8	18.8	50	32	82	12
53	75	11	97	80	60.99	15.9	50	30	80	10
54	79	15	98	82	63.0	18.0	48	31	79	9
55	80	16	98	82	63.0	18.0	48	36	84	14
56	77	13	101	82	65.0	20.0	45	34	79	9
57	79	15	100	81	63.5	18.5	48	33	81	11
58	80	16	95	87	65.1	20.1	48	37	85	15
59	80	16	103	84	67.9	22.9	47	36	83	13
60	78	14	99	83	64.6	19.6	47	37	84	14
61	77	13	102	79	63.2	18.2	44	37	81	11
62	76	12	100	77	60.0	15.0	43	37	80	10
63	75	11	104	77	62.6	17.6	43	39	82	12
64	74	12	101	75	59.0	14.0	40	38	78	8
65	75	13	98	74	56.8	11.8	39	37	76	6
66	73	9	92	72	51.9	6.9	41	36	77	7
67	75	11	97	73	55.5	10.5	41	38	79	9
68	76	12	98	77	59.3	14.3	40	40	80	10
69	76	12	103	78	63.0	18.0	39	44	83	13
70	77	13	104	77	62.6	17.6	38	47	85	15
71	75	11	103	76	61.5	16.5	35	48	83	13
72	74	10	102	76	60.0	15.0	34	49	83	13
73	73	9	92	76	54.9	9.9	31	47	78	8
74	74	10	91	76	54.4	9.4	31 32	47 45	77	7
75	71	7	82	76	49.0	4.0	30	45	75	5
76	72	8	90	75	53.1	8.1	29	49	78	8
77	71	7	100	76	59.6	14.6	28	51	79	9
78	72	8	94	78	57.4	12.4	27	50	77	7
79	72	8	100	78	61.3	16.3	26	51	77	7
80	71	7	97	75	57.2	12.2	26	50	76	6
81	71	7 7	95	75	55.9	13.9	26	50	76	6
82	72	8	96	76	57.6	12.6	25	50	75	5
83	70	6	91	77	55.1	10.1	26	49	75	5
84	70	6	89	73	51.0	6.0	26	49	75	5
85	70	6	92	73	52.9	7.9	25	48	73	3

FIGURE 17

FIGURE 18

FIGURE 79

METHODS & RESULTS

This phase of the investigation was undertaken to fulfill the third objective: - "To measure the tolerance of dogs to rapid deceleration and to provide information which would contribute to the solution of the controversy concerning the possible danger resulting from the use of abdominal safety belts in rapid deceleration". Considerable data was accumulated in this laboratory from the period 1946 to 1948 by Joffe (110). Several difficulties were encountered during that phase of the investigation concerning accurate measurements of the time and peak periods of deceleration. In the words of the investigator: - "As will be brought out later, our results on living animals indicate beyond doubt that decelerative forces when applied by means of the safety belt or harness at the lower margin of the ribs produces cardiac injury so characteristic of heart trauma due to non-penetrating chest wounds or any origin, and that a knowledge of the force level at which this injury might be manifest would be of great value".

We have attempted then, to provide the additional piece of information lacking in that investigation, i.e., to provide accelerometer measurements of the lethal dose of deceleration as determined by an accelerometer mounted at the region of the fifth rib.

In the preceeding section concerning the effects of abdominal deceleration as determined by high speed X-rays, we described the method and have shown several photographs of the manner in which the force is delivered to the lower region of the ribs by these safety belts when the dog is oriented in the superior-inferior position. This same method was used in this phase of investigation.

By suturing the accelerometer to the fifth rib, a rigid mounting was obtained, and under such conditions deceleration readings had no distortion which might otherwise have been caused by the acceleration of the mass of the transducer itself.

To date four dogs have been subjected to decelerative forces of short duration. Data on the fourth dog is not complete, but the available data will, nevertheless, be given and final, unequivocal conclusions withheld until additional data is forthcoming.

Based upon gross autopsy findings, Jöffe (110) reported seven out of seven dogs subjected to horizontal deceleration of unknown magnitude died of cardiac dilatation. We have attempted in this phase of the investigation to replace the subjective assessment of cardiac dilatation with objective measurements of the area of the cardiac silhouette by planimeter on X-ray shadows taken before and after deceleration and to further substantiate these findings with histological examination of section of heart tissue. Since evidence exists, clinical and experimental, that some damage is sustained by the liver and kidneys, histological examinations were made also of these two organs.

Electrocardiographic changes for each of the first three dogs have been summarized as to: -

1. Rhythm
2. P-R, QRS, QRST intervals
3. Heart rate
4. Individual measurements in amplitude of P,Q,R,S,T waves and the level of the ST segment in leads I, II, III.

It has been mentioned previously that the literature shows that cardiac trauma is associated in humans with non-penetrating injury to the chest. Joffe in this laboratory showed that cardiac trauma produced experimentally in animals with abdominal safety belts shows results similar to those of non-penetrating chest injury. Both conditions produce electrocardiographic changes involving the ST segment and the T wave.

On the basis of this information, our evidence for the production of cardiac trauma is based on the inversion of the T wave with simultaneous elevation of the ST segment. Many other bizzare changes occur such as enlargement of the Q wave and changes in contour of the QRS complex, but unfortunately, these changes cannot be accurately described and cannot be correlated with any specific heart damage.

Dog #1 (Scottie) was subjected to three separate falls from a height of 5-1/2 ft. with a force of approximately 20 g's acting for .1 seconds. This was done to determine whether or not there were any accumulative effects from repeated exposure to rapid decelerations. Separate electrocardiograms were taken before and after each run and are mounted in Figures #19 and #20. Protocols summarizing electrocardiographic changes are also presented. Examination will show that no significant changes occurred except 10-minutes after the deceleration of the first run. Slight inversion of the T wave was noted with simultaneous elevated takeoff of the ST segment. It is, however, doubtful that these slight changes can be interpreted as definite evidence of cardiac damage. No X-rays are available on this dog.

Second and third drop were made from the same height about a week apart. Serial electrocardiograms following these two drops show no evidence

of damage and the inference is that animals tolerate this magnitude and duration especially well and that little accumulative effects are produced from repeated sublethal doses of rapid deceleration.

Dog #2 (Hound) was dropped in the same manner as indicated in the preceeding experiment, sustaining a force of 56.7 g's for a period of .06 seconds at the level of the fifth rib.

The most significant changes in the electrocardiogram occurred 5 minutes after the drop. In this series, the T wave appears in lead I, whereas the control showed no wave. The T wave is inverted and is accompanied by a slightly higher takeoff of the ST segment. These changes, according to the literature (1) (24) (30)(34) (35), indicates that some cardiac damage has been produced with a free fall from a height of 12-ft. with the magnitude and duration of force indicated. The following series of electrocardiograms in Figures #21, #22, #23, and #24, and the accompanying summaries of these changes shows these changes to become less prominent as time goes on, so it is doubtful if any permanent damage was produced.

Histological examination of heart sections showed only isolated small hemorrhages in the myocardium, no degeneration of the parenchymatous myocardium was noted. Small subcapsular hemorrhages of the liver were noted. No changes in renal tissue was noted. None of these changes is believed to be severe enough to cause discomfort or death to the animal.

Serial X-rays of this animal showed changes in the area of the cardiac silhouette amounting to approximately 5 sq. c m (.09%). This dilatation practically disappears in about three weeks.

Dog #3 (Brownie) was dropped from a height of 12-1/2 ft. Accelerometer record is not available, but on the basis of subsequent experiments

using the same apparatus, the estimated force is 50 g's acting for .05 seconds.

Serial electrocardiograms (Figures #25, #26, #27, and #28) were taken for a period of three weeks following the deceleration at which time the animal was sacrificed and histological sections made again of heart, liver, and kidney.

The most significant electrocardiographic changes were noted in which a definite sinus arrhythmia with simultaneous changes involving the ST segment persisted until the time the dog was sacrificed.

Histological examination showed no damage to the kidney or any degeneration of the myocardium. Small areas of hemorrhage were noted in the myocardium and in the subcapsular area of the liver. None of these changes are believed of sufficient intensity to cause distress or discomfort to the animal. Measurement of the cardiac silhouette revealed no significant changes.

A force of 55 g's was supplied to the thorax of Dog #4 (Lady). As has been pointed out, complete data is not available on this dog. Control electrocardiogram showed inversion of the T wave in all leads, but it must also be emphasized that the inversion became deeper and the ST segment elevated following the drop. This dog died 10 days later, but it cannot be determined whether death was caused by or merely hastened by the effects of the deceleration. Parasites were found at autopsy to have invaded the intestinal tract and undoubtedly was responsible for the general emaciation of the dog prior to death.

Changes in the cardiac silhouette were minimal. Significant changes were, however, noted in the histological examination of the heart, liver, and kidney. Sections of the heart showed the coronary tree to be engorged with blood with small hemorrhages appearing throughout the myocardium. No evidence of degeneration of the myocardium was noted. We do not believe these areas of hemorrhage in the myocardium to be caused by any of the three parasites which usually invade heart tissue: - *Dirophalaria*, *Sarcosporidia*, and *Toxoplasma*. None of these parasites, according to veterinary pathologists are known to cause hemorrhages as was noted in these sections. Larger vessels of the heart appeared normal. The hemorrhage areas were noted in the arterioles and venules of the myocardium.

Some hemorrhage was noted in the renal tissue and there was general congestion of the vessels of the cortex involving the interlobar vessels.

Large hemorrhage areas were noted in the liver at the periphery of the inferior border and extending into the septa of the larger vessels. Hepatic tissue appeared normal, but liver sinuses were engorged in some sections and ruptured in others. Small hemorrhage areas were also noted along the chief portal vessels.

CONCLUSIONS

As has already been mentioned, final conclusions must be deferred on this phase of the investigation until additional data is forthcoming. It has not been possible to date to deliver enough deceleration from free fall drops to produce anything comparable to the cardiac damage under the conditions of Joffee's experiments (110).

At this point, nevertheless, one may hazard a guess as to the limit of tolerance of dogs to decelerative forces applied at the lower region of the ribs. Since we have produced some minor damage to the heart at the level of g's indicated (56 g's) in these experiments, the lethal dose of deceleration might possibly be reached at approximately 100 g's acting for .1 seconds.

Enough evidence has been reviewed to suggest some of the possible dangers resulting from use of the abdominal type safety belt. Though the heart by virtue of its position seems particularly vulnerable to violence, the liver and kidney also may be included as areas in which damage to viscera might be produced.

Dog Scottie Deceleration None Weight 25 lbs. EKG Control

Heart Rate 115/min

Rhythm Regular

P-R Interval .12 sec.

QRS " " .04 sec.

QRST " " .28 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .3 mv	+ .15	+ .15
Q.....	- .15	Slightly elevated	Slightly elevated
R.....	.3	1.5	1.3
S.....	0	.5	.5
ST.....	Isoelectric	Low takeoff then blends with T wave	Low takeoff then blends with T wave
T.....	Inverted .05 mv.	Inverted to diphasic	Inverted to diphasic

Dog Scottie Deceleration 18.5 g's .10 sec. Weight 20 lbs.

EKG 10 min. after drop

Heart Rate 88/ min.

Rhythm Regular

P-R Interval .10 sec

QRS " " .05 sec

QRST " " .28 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .25 mv	+ .20 mv	+ .10 mv
Q.....	0	0	0
R.....	.6 mv	1.9 mv	1.5 mv
S.....	.05 mv	.4 mv	.45 mv
ST.....	Slightly higher takeoff than control	Isoelectric blends with T wave	Isoelectric, blends with T wave
T.....	Inverted to diphasic	Inverted to diphasic	Inverted to diphasic

Some T wave changes appear, but cannot definitely be interpreted as cardiac damage.

Dog Scottie Deceleration None Weight 25 lbs. EKG Control for 2nd drop

Heart Rate 94/ min.

Rhythm Regular

P-R Interval .11 sec

QRS " " .05 sec

QRST " " .28 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .15 mv	+ .2 mv	+ .1 (several diphasic waves)
Q.....	.1 mv	0	0
R.....	.5 mv	1.5 mv	1.6 mv
S.....	0	.4 mv	.6 mv
ST.....	Isoelectric	Low takeoff blends with T wave	Low takeoff blends with T wave
T.....	Inverted	Inverted to diphasic	Inverted

No appreciable change from the Original

Dog Scottie Deceleration 21.4 g's .13 sec Weight 25 lbs.

EKG 10 min after 2nd drop

Heart Rate 125/ min

Rhythm Regular

P-R Interval .10 sec

QRS " .05 sec

QRST " .24 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .10 mv	+ .25 mv (notched)	+ .20 mv
Q.....	.05 mv	0	0
R.....	.4 mv	1.5 mv	1.5 mv
S.....	0	.3 mv	.5 mv
ST.....	Isoelectric	Depressed takeoff blends blends with T wave	Slightly depressed takeoff blends with T wave
T.....	Inverted	Inverted to diphasic	Inverted
	No appreciable change		

Dog <u>Scottie</u>	<u>Deceleration</u> <u>None</u>	<u>Weight</u> <u>25 lbs.</u>	<u>EKG Control for 3rd. drop</u>
Heart Rate	115/ min		
Rhythm	Regular		
P-R Interval	.12 sec		
QRS " "	.05 sec		
QRST " "	.28 sec		

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .15 mv	+ .25 (some notching) mv	+ .15 mv
Q.....	0	0	0
R.....	.4 mv	1.7 mv	1.3 mv
S.....	.05 mv	.5 mv	.5 mv
ST.....	Isoelectric	Slightly higher takeoff than original	Depressed takeoff blends blends with T wave
T.....	Inverted (diphasic)	Inverted (diphasic)	Inverted (diphasic)
	No appreciable change from the original.		

Dog <u>Scottie</u>	Deceleration <u>Approx 15 G's</u>	Weight <u>25 lbs.</u>	EKG <u>4 min after 3rd drop</u>
Heart Rate	136/ min		
Rhythm	Regular		
P-R Interval	.09 sec		
QRS " "	.05 sec (some splintering of this complex)		
QRST " "	.28 sec		

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .15 mv	+ .25 mv	+ .15 mv
Q.....	0	0	Ø
R.....	.6 mv	1.6 mv	1.4 mv
S.....	.1 mv	.4 mv	.5 mv
ST.....	Isoelectric	Slightly higher takeoff than than original	Slightly higher takeoff than original
T.....	Inverted to diphasic	Inverted to diphasic	Inverted to diphasic
	No appreciable change		

FIGURE 20

Dog #1 Scottie

FIGURE 21

Dog Hound Deceleration None Weight 22lbs. EKG Control

Heart Rate 150/ min

Rhythm Regular

P-R Interval .10 sec.

QRS " " .03 sec.

QRST " " .28 sec.

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .05 mv	+ .3 mv	+ .2 mv
Q.....	.2 mv	.15 mv	.15 mv
R.....	.25 mv	.7 mv	1.0 mv
S.....	0	.5 mv	.6 mv
ST.....	Isoelectric	Low takeoff blends with T wave	Low takeoff blends with T wave
T.....	No T wave present	Elevated T wave	Elevated T wave

Dog Hound Deceleration 56.7 g's .05 sec Weight 22 lbs. EKG 5 min after drop

Heart Rate 158/ min

Rhythm Regular

P-R Interval .09 sec

QRS " .03 sec

QRST " .20 sec

	Lead I	Lead II	Lead III
P.....	+ .05 mv	+ .2 mv	+ .15 mv
Q.....	0	.1 mv	.1 mv
R.....	.4 mv	.8 mv	.8 mv
S.....	.1 mv	.4 mv	.45 mv
ST.....	Isoelectric	Low takeoff blends with T wave	Low takeoff blends with T wave
T.....	Inverted	Slightly higher takeoff	Elevated

The most significant changes take place in lead I with inverted T waves.
None were present in Lead I of the control.

Dog Hound Deceleration same Weight 22 lbs. EKG 25 min after drop

Heart Rate 175/ min
 Rhythm Regular
 P-R Interval .09 sec
 QRS " " .04 to .05 sec slight increase over control
 QRST " " .22 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .1 mv	+ .3 mv	+ .3 mv
Q.....	.25 mv	.15 mv	.1 mv
R.....	.4 mv	.4 mv	.5 mv
S.....	0	.3 mv	.5 mv
ST.....	Isoelectric	Tends to become isoelectric	same
T.....	Inverted	Tends to become inverted	Tends to become inverted

T waves remain inverted but are less prominent than in control
 QRS interval becomes splintered.

Dog Hound Deceleration same Weight 22 lbs. EKG 70 min after drop

Heart Rate 180/ min

Rhythm Regular

P-R Interval .10 sec

QRS " .04 sec

QRST " .20 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .03 mv	+.25 mv	+ .25 mv
Q.....	.4 mv	.15 mv	.10 mv
R.....	.5 mv	.6 mv	.6 mv
S.....	0	.2 mv	.4 mv
ST.....	Slightly slurred	Isoelectric takeoff blends with T wave	Isoelectric takeoff blends with T wave
T.....	Inverted when it appears	Tends to become inverted	Tends to become inverted

Changes less prominent than in the EKG 5 minutes after drop.

Dog Hound Deceleration same Weight 22 lbs. EKG 1 day

Heart Rate 100/ min

Rhythm Regular

P-R Interval .20 sec

QRS " .04 sec

QRST " .20 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .05 mv	+ .25 mv	+ .05 mv
Q.....	.25 mv	.20 mv	.15 mv
R.....	.2 mv	.4 mv	.9 mv
S.....	.25 mv	.15 mv	.15 mv
ST.....	Slightly elevated then isoelectric	Depressed takeoff blends with T wave	Depressed takeoff blends with T wave
T.....	Inverted	Inverted and notched	Inverted and notched

P waves appear notched
T waves appear inverted and notched

Dog Hound Deceleration same Weight 22 lbs. EKG 9 days

Heart Rate 97/ min

Rhythm Regular

P-R Interval .10 sec

QRS " " .04 sec

QRST " " .2+ sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .05 mv	+ .2 mv	+ .15 mv
Q.....	.4 mv	.15 mv	.15 mv
R.....	.4 mv	.7 mv	1.0 mv
S.....	0	.5 mv	.6 mv
ST.....	Slightly elevated takeoff	Low takeoff blends with with T wave	Low takeoff blends with T wave
T.....	Slightly inverted	Elevated T wave	Elevated T wave

Rhythm slower associated with a slight inversion of T wave in lead I.

Dog	<u>Hound</u>	Deceleration	<u>same</u>	Weight	<u>22 lbs.</u>	EKG	<u>3 weeks</u>
Heart Rate			107/ min				
Rhythm			Regular				
P-R Interval			.10 sec				
QRS	" "		.05 sec				
QRST	" "		.20 sec				

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .05 mv	+ .2 mv	+ .15 mv
Q.....	.1 mv	.15 mv	.1 mv
R.....	.3 mv	.7 mv	.5 mv
S.....	0	.35 mv	.5 mv
ST.....	Slightly elevated	Low takeoff blends with T wave	Low takeoff blends with T wave
T.....	Inverted	Diphasic	Diphasic

Except for the slightly elevated takeoff of the ST segment in lead I and the T wave of the Lead II and III, this EKG looks similar to the control.

FIGURE 22

FIGURE 23

FIGURE 24

FIGURE 25

Dog Brownie Deceleration None Weight 25 lbs. EKG Control

Heart Rate 100/ min

Rhythm Regular

P-R Interval .12 sec

QRS " .03 sec

QRST " .24 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .1 mv	+ .2 mv	+ .25 mv
Q.....	.3 mv	.2 mv	.2 mv
R.....	.5 mv	1.3 mv	1.9 mv
S.....	0	0 to Slightly depresses	0
ST.....	Slightly elevated (.05)	Low takeoff, blends with T wave	Isoelectric
T.....	Inverted slightly	Diphasic	Diphasic

Dog Brownie Deceleration Approx 50 g's Weight 25 lbs. EKG 5 min after drop

Heart Rate 150/ min

Rhythm Regular

P-R Interval .11 sec

QRS " " .04 sec

QRST " " .20 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .3 mv	+ .25 mv	+ .2 mv
Q.....	.2	0	Inverted
R.....	1.9 mv	.9 mv	1.6 mv (Inverted)
S.....	.2 mv	.15 mv	.3 mv (Inverted)
ST.....	Slightly elevated takeoff above control	Slightly elevated takeoff above control	Slightly elevated takeoff above control
T.....	Diphasic	Diphasic	Diphasic

Dog Brownie Deceleration same Weight 25 lbs. EKG 55 min after drop

Heart Rate 79/ min

Rhythm Irregular

P-R Interval .12 sec

QRS " " .04 sec

QRST " " .28 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .3 mv	+ .2 mv	.15 mv (Inverted)
Q.....	.3 mv	0	.3 mv (Inverted)
R.....	2.2 mv	.9 mv	2.0 mv (Inverted)
S.....	.2 mv	.15 mv	.1 mv (Inverted)
ST.....	Isoelectric	Elevated takeoff, blends with T wave	Elevated takeoff, blends with T wave
T.....	Diphasic	Diphasic	Diphasic

A definite sinus arrhythmia is present in all leads. In leads II and III this arrhythmia is present with slight elevation of the ST segment.

<u>Dog Brownie</u>	<u>Deceleration</u> <u>same</u>	<u>Weight</u> <u>25 lbs.</u>	<u>EKG</u> <u>1 hr. 30 min after</u>
Heart Rate	115/ min		
Rhythm	Irregular		
P-R Interval	.10 sec		
QRS " "	.04 sec		
QRST " "	.20 sec		

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .3 mv	+ .2 mv	+ .15 mv
Q.....	.25 mv	+ 0	0
R.....	2.0 mv	.7 mv	.9 mv
S.....	.2 mv	.2 mv	.1 mv
ST.....	Isoelectric	Slightly above control	Slightly above control
T.....	Diphasic	Diphasic	Diphasic

Sinus arrhythmia still persists with T waves remaining the same as the EKG taken after 55 minutes.

Dog Brownie Deceleration same Weight 25 lbs. EKG 11 days

Heart Rate 79/ min
 Rhythm Irregular
 P-R Interval .10 sec
 QRS " " .05 sec
 QRST " " .28 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .05 mv	+ .20 mv	+ .05 mv
Q.....	.20 mv	.40 mv	.30 mv
R.....	.35 mv	1.7 mv	1.5 mv
S.....	.05 mv	.3 mv	.40 mv
ST.....	Isoelectric	Isoelectric (control lead was slightly depressed)	Slightly elevated above control
T.....	Elevated above control	Upright .4 mv	Upright .3 mv

Sinus arrhythmia still present with same changes in ST segment and some slight changes in the contour of the T wave.

Dog Brownie Deceleration same Weight 25 lbs. EKG 3 weeks

Heart Rate 83/ min
Rhythm Irregular
P-R Interval .12 sec
QRS " " .04 sec
QRST " " .25 sec

	<u>Lead I</u>	<u>Lead II</u>	<u>Lead III</u>
P.....	+ .1 mv	+ .25 mv	+ .20 mv
Q.....	.25 mv	.20 mv	.20 mv
R.....	.45 mv	1.5 mv	1.1 mv
S.....	.1 mv	.35 mv	.3 mv
ST.....	Isoelectric	Isoelectric	Isoelectric
T.....	Upright .15 mv	Upright .3 mv	Upright .25 mv

Sinus arrhythmia still persists

FIGURE 26

Read II
Control

Read I

Dog #3 Brownie
no recording available
approximate acceleration = 50 60 g's

FIGURE 27

FIGURE 28

FIGURE 29

BIBLIOGRAPHY

⁶
-127-

I. Non-penetrating Chest Injury A. Clinical

1. Ahrenbert, H., Traumatic Heart Disease: A Clinical Study of 250 Cases of Non-penetrating Chest Injuries and their Relation to Cardiac Disability. *Annals of Internal Medicine* 19; 326, 1943
2. Anderson, R.G., Non-penetrating Injuries of the Heart
British Medical Journal 2: 307, 1940
3. Barber, H., Trauma of the Heart
British Medical Journal 1: 433, 1938
4. Barber, H., Electrocardiographic Changes Due to Trauma
British Medical Journal, 4: 83, 1942
5. Barber, H., The Effect of Trauma, Direct and Indirect on the Heart
Quarterly Journal of Medicine, 13: 137, 1944
6. Barber, H., *British Medical Journal*, 2: 854, 1951
7. Beck, C. S. and Bright, H. F., Changes in the Heart and Pericardium Brought About by Compression of the Legs and Abdomen
Journal of Thoracic Surgery, 2: 616, 1933
8. Beck, C. S., Contusions of the Heart
Journal of the American Medical Journal, 109: 1935
9. Boas, E. P., Angina Pectoris and Cardiac Infarction from Trauma or Unusual Effort
Journal of Medical Association 62: 1887, 1939
10. Bright, E. F. and Beck, C. S., Non-penetrating Wounds of the Heart
American Heart Journal, 10: 293-321, 1935
11. Foster, R. F., The Relation of Trauma to Heart Disease
Industrial Medicine 8: 258, 1938
12. Joachim, H., and Mays, A. T., A Case of Cardiac Aneurysm Probably of Traumatic Origin
American Heart Journal, 2: 682, 1926-27
13. Kahn, M. H., and Kahn, B. S., Cardiovascular Lesions Following Injury to the Chest
Annals of Internal Medicine, 2: 1013, 1929

14. Kellert, E., Traumatic Rupture of the Heart: A Report of Cases With Uninjured Chest Wall
Journal of Laboratory and Clinical Medicine, 2: 726, July 1916-17
15. Kessler, H.H., Accidental Injuries
Philadelphia, Lea and Febiger., 2nd Edition
16. Krumbhaar, E.B., and Crowell, C., Spontaneous Rupture of the Heart
American Journal of Medical Science, 170: 828, 1925
17. Langendorf, R., and Goldberg, S., The Electrocardiogram in Traumatic Pericarditis
American Heart Journal 24: 412, 1942
18. Leinoff, H. D., Direct Non-penetrating Injuries of the Heart
Annals of Internal Medicine, 14: 653, 1940
19. Leinoff, H.D., Acute Coronary Thrombosis in Industry Non-penetrating Injuries, with Report of Cases
Archives of Internal Medicine, 70: 33, 1942
20. Masini, V., Alterazioni Miocardiche Nei Traumi Chiusi Del Torace
Rivista Di Medicina Aeronautica, Vol. 11, N., 1, 1948
21. Moritz, A.R., and Atkins, J.P., Cardiac Contusions, An Experimental and Pathologic Study
Archives of Pathology, 24: 445, 1938
22. Saphir, Otto, Rupture of the Heart by Indirect Trauma
American Journal of Medical Science, 173: 353, 1927
23. Schlomka, G., Commotio Cordis und Ihre Folgen,
Ergebn.d.inn. Med. u. Kenderh, 27: 1, 1934
24. Sigler, L.H., Trauma of the Heart Due to Non-penetrating Chest Injuries, 119: 855, 1942
25. Sigler, L.H., Traumatic Injury of the Heart
American Heart Journal, 30: 459, 1945
26. Smith, L.B. and McKeown, Contusions of the Heart: Report of a Case with Serial Electrocardiogram
American Heart Journal 17: 561, 1939
27. Stephens, G.H., Three Thoracic Emergencies
Lancet 2: 1383, December 1922
28. Stromer, A., Traumatic Disease of the Heart
Deutsche Med. Wchnschr, 64: 235, 1938

29. Viko, L.E., Communication of 38-year old man with Symptoms of Recent Coronary Occlusion After Being Hit by a Golf Ball Over the Lower Part of the Sternum, 1933
30. Warburg, E., Subacute and Chronic Pericardial and Myocardial Lesions Due to Non-penetrating Traumatic Injury
Oxford University Press, London, 1938
31. Warburg, E., Myocardial and Pericardial Lesions Due to Non-penetrating Injury
British Heart Journal, 2: 271, 1940
32. Wearn, J. T., In Discussion to Beck, C.S., Contusion of the Heart
Journal of American Medical Association, c.v., 114: 1935
33. Wilson, J.V., The Pathology of Closed Injuries of the Chest
British Medical Journal 1: 470, 1943

B. Experimental

34. Kissane, R.W., Fidler, R.A., and Koons, R.A.,
Electrocardiographic Changes Following External Chest Injury to Dogs
Annals of Internal Medicine, 11: 907-935, 1937
35. Kissane, R.W., Fidler, R.S., and Koons, R.A.,
Traumatic Lesions of the Heart
American Association for the Advancement of Science, 13: 170-175
1940
36. Randles, F.S., Gorham, L.W., and Dreshbach, M.
Changes in the RS-T Component of the Electrocardiogram Produced by Experimental Rupture of the Auricle of Dogs' Heart and by Pericardial Injection
American Heart Journal 9: 333, 1934

II. Bones

37. Calabrisi, P., and Smith, F.C., The Effects of Embalming in the Compressive Strength of a Few Specimens of Compact Human Bone
Naval Medical Research Institute Memorandum Report 51-2 NM 000 018.07 .02 Naval Medical Center, Bethesda, Maryland
38. Carothers, C.O., Smith, F.C., Calabrisi, P., The Elasticity and Strength of Some Long Bones of the Human Body
Naval Medical Institute, Project NM 001 056 13: 1, October 6, 1949
39. Duret, M., Note Sur la Disposition Architecturale du Tissue Spongieux des Os: Role de cette disposition dans la production des fractures,
Comp Rend et Memoir de Soc. Ciol, 28: 384-387 1876

40. DeForest, A.V., Ellis, Greer, Brittle Lacquer as an Aid to Stress Analysis
Journal of Aeronautical Sciences 7: 205-208, 1940
41. Evans, F.G., and Lissner, H.R., "Stresscoat" Deformation Studies of the Femur Under Static Vertical Loading
Anat. Rec. 100: 159-190, 1948
42. Evans, F.G., Studies of Femoral Deformation
Stanford University Bull, 6: 374-381, 1948
43. Evans, F.G., Deformation Studies of the Femur Under Static and Dynamic Loading
Sorbretiro de Los Anales del Instituto de Biologia Tomo 20: #1y2 Mexico, 1949
44. Evans, F.G., and Lebow, M., Regional Differences in Some of the Physical Properties of the Human Femur
Journal of Applied Physiology, Vol. 3 #9, March 1951
45. Evans, F.G., Pedersen, H. E., and Lissner, H.R.,
Role of Tensile Stress in the Mechanism of Femoral Fractures
Journal of Bone and Surgery, Vol. 33-A #2, 485-501, April, 1951
46. Evans, G., and Lebow, Milton
Strength of Human Compact Bone as Revealed by Engineering Techniques
American Journal of Surgery, Vol. 83: #3 326-331, 1952
47. Evans, G., and Lessner, H.R., Deformation Studies of the Adult Human Pelvis Under Dynamic Loading
Dept. of Engineering Mechanics, Wayne University, 1953
(Meeting of American Association of Anatomists)
48. Fasola, Alfred; Anatomical and Physiological Effects of Rapid Deceleration
Master's Thesis - Ohio State University, 1950
49. Fick, R., Handbuch der Anatomie und der Gelenke Dritter Teil Spezielle Gelenk-und Muskelmechnik, Gustav Fishher, Jena
50. Gurdjian, E.S., and Lissner, H.R., Deformation of the Skull in Head Injury, A Study with the "Stresscoat" Technique
Surgery, Gynecology, and Obstetrics, 81: 679-687, 1945
51. Gurdjian, E.S., and Lissner, H.R.,; Deformation of the Skull in Head Injury Studied by the "Stresscoat" Technique, Quantative Determinations,
Surgery, Gynecology, and Obstetrics, 83: 219-233, 1946
52. Gurdjian, E.S., Lissner, H.R., and Webster, J.E.; The Mechanism of Production of Linnear Skull Fracture. Further Studies on Deformation of the Skull by the "Stresscoat" Technique
Surgery, Bynecology, and Obstetrics 85: 195-210, 1947

53. Gurdjian, E.S., and Lissner, H.R.,; Deformation of the Skull in Head Injury as Studied by "Stresscoat" Technique
American Journal of Surgery 73: 269, 1947
54. Evans, F.G., Lissner, H.R., and Pedersen, H.E.; Deformation Studies of the Femur under Dynamic Vertical Loading
Anat. Rec. 101: 225-241, 1948
55. Gurdjian, E.S., and Lissner, H.R., Anatomy and Some Principles of Mechanics
(College of Engineering) Wayne University, Anat. Rec. Vol. #3 March, 1949
56. Gurdjian, E.S., Webster, J.E., and Lissner, H.R.; Studies on Skull Fractures with Particular Reference to Engineering Factors
American Journal of Surgery 78: 736-742, 1949
57. Gurdjian, E.S., Webster, J.E., and Lissner, H.R.
Mechanism of Skull Fracture
Journal of Neurosurgery, 7: 106-114 - March, 1950
Radiology 54: 313, March, 1950
58. Jones, E.S.; Joint Lubrication
Lancet 1: 1043-1044, 1936
59. Koch, J.C.,; Laws of Bone Architecture
American Journal of Anatomy 21: 177-298, 1917
60. Maj, G., and Toajari, E., Chir.d. org di Movimento 22: 541, 1937
61. Maj, G., Monit Zoll Ital 49: 139, 1938
62. Maj, G. Resistenza Mecchanica del Tessuto Osseo e Diversi Livelli di Uno Stesso Osso
Boll. Soc. Ital, Sper. 13: 413-415, 1938
63. Maj, G., Variazioni Individuali e Topographicle dell resistenza Mecchanica del Tessuto Osseo Umano
Boll. Soc., Ital, Ciol. Sper 15: 1151, 1940
64. Maj, G., Studio Sulle Variazioni Individuali e Topographiche delle Resistenza Mecchanica del Tessuto Osse Diafisario Umano in Diversi eta
Arch. Ital, Annat e Embriol 47: 612, 1942
65. Marique, P., Etudes sur le Femur
Bruxcelles, Belgium: Librairel des Sci.
66. Messerer, O., Eber Elasticitat und Festigkeit der Menschl Chen Knochen
Stuttgart, Germany Cotta 1880

67. Milch, H., Photoelastic Studies of Bone Form
Journal of Bone and Joint Surgery, (N.S.)22: 621-626, 1940
68. National Bureau of Standards; Compressive Tests of Tubular Specimens of Human Bone - Report #2, U.S. Dept. of Commerce, Naval Medical Institute, Bethesda, Maryland, August 13, 1948
69. National Bureau of Standards; The Mechanical Properties of Bones; U.S. Dept. of Commerce, Progress Report #1, NBS, Lab. 64219 Washington, D.C., January 31, 1948
70. National Bureau of Standards; Tensile Tests of Specimens Removed from Human Femurs
Naval Medical Research Institute, Bethesda, Maryland, January 27, 1949
71. Pedersen, H.E., Evans, F.G., Lissner, H.R.; Deformation Studies of the Femur Under Various Loadings and Orientations
Anat Rec 103: 159-185 1949
72. Rauber, A.A., Elasticitat und Festigkeit der Knochen
Leipzig, Englemann, 1876
73. Spears, G.M., Owen, J. T. The Tiology of Trochanteric Fractures of the Femur
Journal of Bone and Joint Surgery, 31-A: 548-552, July, 1949
74. Toajari, E., Resistenza Meccanica e Elasticita del Tessuto Osseo Studiata in Rapporto all Minuta Struttura Monit. Zool. Ital 47: 148-154, 1938
75. Toajari, E., Monit, Zool. Ital, 48: 148, 1938
76. Walmsley, T., The Vertical of the Femur and their Relations. A Contribution to the Study of Erect Posture
Journal of Anatomy 67: 284-300, 1932

III. General Aspects of Deceleration

A. Exposure to long "g" deceleration

77. Beckman, E.L.; Protection Afforded Cerebrospinal System by Cerebrospinal Fluid Under Stress of Negative G
Journal of Aviation Medicine, 20: 430, December, 1949
78. Christy, R.L., New Human Centrifuge
Journal of Aviation Medicine, 20: 454-458, December, 1949
79. Denzin, E.C; Decelerator for Human Experimentation
A.F. Tech. Rep., U.S. Air Force (5973) pp 1-70, February, 1950

80. Gamble, J.L., Jr., and Shaw, R.S.; Pathology in Dogs Exposed to Negative Acceleration
Air Materiel Command Memorandum Report #TSEAA-695-74B, August, 1947
81. Gamble, J.L., Jr., Shaw, R.S., Gauer, O.H., and Henry, J.P.
On Cerebral Dysfunction During Negative Acceleration
Journal of Applied Physiology, 2: 133, 1949
82. Henry, J.P., Gamble, J.L., Shaw, R.S., Gauer, O.H. Martin, E.E. Maher, P., Jr. and Simmons, D.G.
Studies of the Physiology of Negative Acceleration
USAF Technical Report #5953, October, 1950
83. Lombard, C.F., Beckman, E.L., Rushmer, R.F., Drury, D.R. Goodman, H., Edmonson, H.,
Effects of Radial Acceleration on Large Experimental Animals (goats)
I Pathology, Office of Naval Research Contract, No. 60 re 77, Project NR 161014, November, 1948
84. Lambert, C.H., Comparison of the Protective Value of Anti-Blackout Suit on Subjects in Airplane and Mayo Centrifuge
Journal of Aviation Medicine, 21: 28-37, February, 1950
85. Memorandum Report, Pathology of Dogs Exposed to Negative Acceleration
Wright-Patterson Air Force Base, Dayton, Ohio, August 18, 1947
86. Memorandum Report, Use of the Anti-G Suit to Aid in the Relief of Fighter Pilot Discomfort
Wright-Patterson Air Force Base, September 22, 1947
87. Memorandum Report, Venous Pressure in the Head Under Negative Acceleration
MCREXD-695-74-D, Wright-Patterson Air Force Base, Dayton, Ohio June 16, 1948
88. Memorandum Report, The Significance of the Volume of Blood Contained in the Legs in Negative Acceleration
MCREXD-695-74 J, Wright-Patterson Air Force Base, Dayton, Ohio May 11, 1948
89. Memorandum Report, Service Test Report on UASF Type G-4A Pilots Pneumatic Suit, Anti-G MCREXD-689-2E, U.S. Air Force Base, Dayton, Ohio, May 20, 1949
90. Martin, E. E. and Whitney, R.W., A Description of the U. S. Air Force Type M-7 No-Leak Negative 'g' Valve
WADC Technical Note #52-11

91. Memorandum Report; Pathology in Dogs Exposed to Negative Acceleration
TSEAA-695-74 b Wright-Patterson Air Force Base, Dayton, Ohio
92. Rushmer, R.F., Beckman, E.L., and Lee, D.; Protection of the Cerebral Circulation by the Cerebrospinal Fluid under the Influence of Negative 'g'
American Journal of Physiology, 151: 355, 1948
93. Ryan, E.A., Kerr, W. K., and Franks, W.R.; Some Physiological Findings on Normal Man Submitted to Negative Acceleration Report RCAF, Institute of Aviation Medicine, Toronto, Canada 1948
94. Shaw, R.S., and Henry, J.P.; The Pressurized Helmet as a Negative 'g' Protective Device
Air Materiel Command Memorandum Report TSEAA-660-100, App. May 4, 1946
95. Sieker, H.O., Capt., USAF (MC) Devices for Protection Against Negative Acceleration, WADC Technical Report 52-87, Part I Wright-Patterson Air Force Base, Dayton, Ohio
96. Simons, D.G. (MC), Henry, J.P., MD; Electronencephalographic Changes Occurring During Negative Acceleration (Headward Centrifugal Force), AF Technical Report #5966
Wright-Patterson Air Force Base, Dayton, Ohio, May, 1950
97. Wood, J. Cain, C.C., and Mahoney, D.,; Physiological Evaluation of the Partial Pressure Suit,
Air Materiel Command Memorandum Report MCREXD-696-104P (unpublished)

B. Exposure to Impact 'g'

98. All American Aviation, Research Progress of Unolyn (Impact Absorption Material to May 15, 1946)
Wilmington, Delaware, May 24, 1946
99. Army Air Force; To Describe the Differences Obtained Between Silk and Nylon Parachutes Employed with Dummies and Opened with Static Lines at Various Altitudes, May 5, 1945
100. Army Air Force; To Compare the Opening Shock Forces and Descent Times of 24' and 28' nylon Parachute at Various Altitudes
May 22, 1945
101. Army Air Force; To Describe Descent of 24' and 28' Nylon and 28' Silk Parachute Opened at Various Altitudes, May 30, 1945

102. Air Technical Service Command; To Describe the Differences Obtained Between 1.7 Oz. Ripstop Nylon, 1.4 OZ. Standard Nylon, and 1.1 OZ. Ripstop Canopies of 24' diameter, July 20, 1945
103. Army Air Force; Internal Injuries Produced by Abrupt Deceleration of Experimental Animals
Report #1 3 AM Project 401 - January 15, 1946
104. Army Air Force; Effects of Abrupt Deceleration on the Electrocardiogram (Lead II) in the Cat. in the Supine Position
Report #1 SAM Project #459 - January 21, 1946
105. Aero Medical Research News Letter; Investigation of Human Tolerance to Parachute Opening
Aeronautical Medical Equipment Laboratory, BU Med Project NMool 062.03 Progress Report, March, 1951
106. Bierman, H.R., and Larsen, V.R., Reactions of Humans to Impact Forces Revealed by High Speed Motion Picture Technique
Journal of Aviation Medicine, 17: 407, 1946
107. Cornell Aeronautical Laboratory, Inc.; Kinematic Behavior of the Human During Crash Deceleration (Thin Man Project)
Internal Research Project, Report #)M-596-J-1
108. Crash Injury Research, Crash Deceleration, Crash Energy, and Their Relationship to Crash Injury
Technical Report AFTR-6242, 1950
109. Hallenback, G.A., Capt., Army Air Force
The Magnitude and Duration of Parachute Opening Shocks at Various Altitudes and Air Speeds - July 8, 1944
110. Joffee, M., Anatomical and Physiological Effects of Abrupt Deceleration
Ph.D. Dissertation, Ohio State University, 1949
111. Leavell, B.S.; Acute Heart Failure Following Blast Injury
War Medicine 7: 162, 1945
112. Memorandum Report; Human Tolerance to Negative G Short Duration
TSEAA-695-74 May 19, 1947
113. Memorandum Report; Animal Studies in Impact Deceleration (negative) MCREXD-695-74-G
Wright-Patterson Air Force Base, Dayton, Ohio, March 10, 1948
114. Ruff, S., Concerning Human Tolerance of Acceleration as it Applies to Certain Jerking Types of Acceleration Which Occur in Flying (presented at the German Academy of Aviation Development on October 31, 1941. Translated in Crash Injury Research Report on September 27, 1947) 1941

- 115. Ruff, S.; Brief Acceleration; Less than One Second
German Aviation Medicine, World War II, Vol. 1 Chapt. VI-C
p. 584-586
- 116. Shaw, R., Capt., (MC) Acceleration Time Diagrams for Catapult
Ejection Seats
AMC Memorandum Report No. TSEAA-695-66D, February, 1947
- 117. Shaw, R., Capt., (MC); Test Firing of T-D Catapult for Downward
Ejection
AMC Memorandum Report #MCREXD-695-74-I, May, 1948
- 118. Stapp, J.P., Human Exposure to Linear Deceleration: Preliminary
Survey of Aft-Facing Seated Position
A.F. Tech. Report #5915 1-36 U.S. Air Force, June, 1949
- 119. Webster, A.P. National Advisory Committee for Aeronautics;
Free Falls and Parachute Descent in Standard Atmosphere,
Bureau of Medical and Surgery, Naval Department

C. Miscellaneous

- 120. Armstrong, H., and Heim, J.W.; Effect of Acceleration on the
Living Organism
USAF Technical Report #4362, December, 1937
- 121. Aviation Week; Crash Safety Can Be Engineered
McGraw-Hill Publishing Co., New York 18, N.Y., March 13, 1950
- 122. Bieman, H.R., Wilder, R., Jr. Hellems, H.; The Principles of
Protection of the Human Body as Applied in a Restraining Harness
for Aircraft Pilots
Naval Medical Research Institute, Bethesda, Maryland
Project X-630, Report #6 - May, 1948
- 123. Crash Injury Research; Handbook for Aircraft Accident Investigat-
ors - Cornell University Medical College
- 124. Crash Injury Research; Dept. of Commerce, Civil Aeronautics
Authority, 612.1 (03.38) Washington, D.C., July 1, 1948
- 125. Crash Injury Research; Hazard of Seat Back in Aircraft Accidents
National Research Council - October 18, 1946
- 126. Crash Injury Research; Informative Accident Release, Jan. 1, 1947
- 127. Crash Injury Research; The Rare Occurrence of Internal Abdominal
Injury from Safety Belts or Other Causes in Serious Aircraft
Accidents - October, 1947

128. Crash Injury Research Release; The Function of Safety Belts in Crash Protection - February 20, 1948
129. Crash Injury Research; Informative Accident #7
National Research Council - May 7, 1948
130. Crash Injury Research; Informative Accident #8
Cornell Committee for Air Safety Research
Cornell Medical College - September 15, 1949
131. Crash Injury Research; Human Tolerance to Deceleration,
Committee for Air Safety Research
Cornell Medical College, January 31, 1950
132. Crash Injury Research; Informative Accident #9
National Research Council - Cornell Medical College, May 18, 1950
133. Crash Injury Research; Informative Accident Release #11
National Research Council, Cornell Medical College, April 25, 1951
134. Crash Injury Research; Informative Release #13
Cornell Medical College, August 30, 1951
135. Crash Injury Research; The Site, Frequency, and Dangerousness of Injury Sustained by 800 Survivors of Light-Plane Accidents
Dept. of Public Health and Preventive Medicine
Cornell University Medical College, July, 1952
136. Crash Injury Research; Crash Injury Study of the Northeast Airlines Convair 240 Accidents at Laguardia Airport on January 14, Informative Accident Release #14, August, 1952
137. Crash Injury Research; Shoulder Harness; Its Use and Effectiveness,
Dept. of Public Health and Preventive Medicine
Cornell University Medical College - November 1, 1952
138. DeHaven, H., Mechanical Analysis of Survivable Accidents in Falls from Heights of 50 to 150 Feet
War Medicine, Vol. 2, p 586, 1942
139. DeHaven, H., Injuries in Thirty Light-Aircraft Accidents
Report #230, Committee on Aviation Medicine, National Research Council, November 17, 1943
140. DeHaven, H., Causes of Injury in Light-Plane Accidents
Aero Digest, Vol. 44, 51, 1944
141. DeHaven, H., Crash Research from the Point of View of Cabin Design, Aeronautical Engineering Review, Vol. 4 #6, June, 1946

142. DeHaven, H., Crash Injury Research; semi-annual Progress Report - Cornell Medical College - January 31, 1952
153. DeHaven, H., Crash Injury Research; Current Safety Considerations in the Design of Passengers Seats for Transport Aircraft Cornell University, Medical College - June, 1952
154. DuBois, E., Limits of Factors of Safety in the Human Body Mechanical Engineering, July, 1946
155. German Aviation Research Report #1549 P395 T7; Seat Installation with Steering for High Flying Acceleration - written by German Research Institute for Aviation, E.V. Berlin
156. Hertzberg, H.T.E., and Colgan, J.W., A Prone Position Bed for Pilots - Air Material Command, Memorandum Report MCREXD-695-71D June, 1948
157. Limits and Special Problems in the Use of Seat Catapult approximately 1946 (author unknown)
158. Memorandum Report; Evaluation of the Anti-G Suit, Report #8 MCREXD-689-2C, Wright-Patterson Air Force Base, Dayton, Ohio July 24, 1948
159. National Research Council; Committee on Aviation Medicine; The Relationship of Injuries in Survivable Aircraft Accidents Report #440 - July 9, 1945
160. Research on Crash Injury; Journal of American Medical Association June, 8, 1946
161. Schneider, J., Protective Measures for Prevention of Injuries; Especially Spinal Fractures in Aircraft on Skids German Aviation Medicine, World War II, Vol. 1, p 612
162. Stapp, J. P., Major USAF (MC) Human Exposure to Linear Deceleration of a Crash Harness, AF Technical Report #5915, U.S. Air Force, Wright-Patterson Development Center Wright-Patterson Air Force Base, Dayton, Ohio
163. Teare, D.; Analysis of the Viking Aircraft Accident British Medical Journal 2; 1337, 1951
164. Wurzel, M. E., Plansky, J. L., Metcalf, E.E. Measurements of the Loads Required to Break Commercial Aviation Safety Belts as an Indication of the Ability of the Human Body to Withstand High impact Forces Report #12, Project NM 001 006 X-630 - Naval Medical Research Institute - National Medical Center - Bethesda, Maryland
- 11a. Hecht, H. H. - Myocardial Involvement (contusion) Following Non-penetrating Injury to the Chest Annals of Internal Medicine 27: 126 1947

ACKNOWLEDGEMENTS

To Dr. Rollo C. Baker, Department of Anatomy and Secretary, College of Medicine, The Ohio State University, I am especially indebted for expert advice and extreme interest in all phases of this research. Without his keen analysis of the problems involved, this investigation could not have been completed successfully. I have gained not only from his tremendous wealth of technical knowledge but also from his knowledge and attitudes in the conduct of life itself. It has been a real pleasure to be associated with Dr. Baker.

To Dr. F. A. Hitchcock, Department of Physiology, The Ohio State University, I am indebted for the opportunity to conduct this investigation. Without the financial assistance from his projects I would have been unable to continue my education. Dr. Hitchcock's advice was especially valuable in the Physiological phases of this work.

I am also indebted to the following:

Dr. S. M. Marco - for technical advice in testing bone samples.
C. J. Carter - for technical advice concerning recording apparatus.

To Colonel H. M. Sweeney and Dr. Savely, and to the Wright-Patterson Air Force Base I am indebted for making available the funds essential to this research.

To Dr. Hugh Hull, Assistant Professor, Department of Physiology, I am indebted for valuable assistance in reading the electrocardiograms.

AUTOBIOGRAPHY

I, Alfred Francis Fasola, was born in Connellsville, Pennsylvania, March 29, 1919. I received my secondary school education in the public schools of the city of Connellsville, Pennsylvania. My undergraduate training was received at Oberlin College, from which I received the degree Bachelor of Arts in 1948. From The Ohio State University I received the degree Master of Science in 1950. While in residence at The Ohio State University I held the title of Research Fellow from 1949 to 1953. I held this position while completing the requirements for the degree Doctor of Philosophy.