THE THERMODYNAMIC PROPERTIES OF
PERFLUORO-2-BUTYL-TETRAHYDROFURAN

DISSERTATION

Presented in Partial Fulfillment of the Requirements
for the Degree Doctor of Philosophy in the
Graduate School of The Ohio State
University

By

ROBERT M. YARRINGTON, B.S., M.S.

The Ohio State University
1958

Approved by:

Adviser
Department of Chemical
Engineering

ACKNOWLEDGMENT

The author wishes to express his appreciation for the advice and guidance given by Dr. Webster B. Kay.

Grateful thanks are due the American Gas Association for funds provided to complete the graphical calculations and to the American Cyanamid Company for granting financial aid in the form of a fellowship to the author.

The assistance of Phasook Kullavanijaya and Robert Savageau in preparing the tables and graphs was appreciated. The help of the author's fellow students is also acknowledged.

TABLE OF CONTENTS

	Page
I. SUMMARY	1
II. INTRODUCTION	6
III. HEAT CAPACITY OF THE VAPOR	12
A. Introduction	
B. The Apparatus	
C. Procedure	
D. Results	
E. Discussion of Results	
F. Conclusions	
IV. PHYSICAL PROPERTIES OF PERFLUORO-2OBUTYL- TETRAHYDROFURAN	37
V. CALCULATION OF THERMODYNAMIC PROPERTIES	42
VI. RESULTS	56
VII. DISCUSSION OF RESULTS	84
VIII. CONCLUSIONS	93
IX. RECOMMENDATIONS	97
APPENDIX A. DETAILS ON THE CONSTRUCTION OF THE FLOW CALORIMETER	99
B. CALIBRATION OF THE DIFFERENTIAL THERMEL .	107
C. EXPERIMENTAL PROCEDURE	116
D. SAMPLE CALCULATION	120
E. EXPERIMENTAL DATA AND CALCULATED RESULTS.	126
F. RESULTS OF GRAPHICAL INTEGRATION FOR THE EFFECT OF PRESSURE ON THE ENTHALPY AND ENTROPY	145
BIBLIOGRAPHY	156

LIST OF TABLES

	Page
I. EXPERIMENTAL HEAT CAPACITY OF BENZENE AND PERFLUORO-2-BUTYL-TETRAHYDROFURAN	29
II. EXPERIMENTAL SATURATED LIQUID AND VAPOR VOLUMES AND VAPOR PRESSURE OF PERFLUORO-2- BUTYL-TETRAHYDROFURAN	41
III. SATURATED PROPERTIES OF PERFLUORO-2-BUTYL- TETRAHYDROFURAN WITH TEMPERATURE AS INDEPENDENT VARIABLE	58
IV. SATURATED PROPERTIES OF PERFLUORO-2-BUTYL- TETRAHYDROFURAN WITH PRESSURE AS INDEPENDENT VARIABLE	60
V. SUPERHEATED PROPERTIES OF PERFLUORO-2-BUTYL- TETRAHYDROFURAN	63
VI. ACTIVITY COEFFICIENTS FOR PERFLUORO-2-BUTYL- TETRAHYDROFURAN	74
VII. COMPARISON OF LATENT HEATS CALCULATED BY TWO METHODS	88
VIII. SATURATED LIQUID ENTHALPIES CALCULATED BY TWO METHODS	89
IX. COMPARISON OF PHYSICAL PROPERTIES OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN WITH OTHER FLUOROCARBONS OF SIMILAR MOLECULAR WEIGHT	92

LIST OF APPENDIX TABLES

I. LIST OF ELECTRICAL EQUIPMENT	104
II. THE FUNCTION, $\mathcal{U}$, MEASURED BY THE DIFFER- ENTIAL METHOD	112
III. EXPERIMENTAL AND CALCULATED THERMEL EMF'S	113
IV. EXPERIMENTAL HEAT CAPACITY DATA FOR BENZENE VAPOR	128
V. EXPERIMENTAL HEAT CAPACITY DATA FOR PERFLUORO-2-BUTYL-TETRAHYDROFURAN VAPOR	130

LIST OF TABLES (CONT'D)

	Page
VI. CALCULATED DATA FOR THE HEAT CAPACITY OF BENZENE VAPOR	135
VII. CALCULATED DATA FOR THE HEAT CAPACITY OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN VAPOR . . .	138
VIII. PRESSURE EFFECT ON THE ENTHALPY OF PERFLUORO-2- BUTYL-TETRAHYDROFURAN IN CALORIES/MOLE . . .	146
IX. PRESSURE EFFECT ON THE ENTROPY OF PERFLUORO-2- BUTYL-TETRAHYDROFURAN IN CALORIES/MOLE, °K .	151

LIST OF ILLUSTRATIONS

Figure		Page
1.	EXPERIMENTAL APPARATUS	19
2.	HEAT CAPACITY OF BENZENE VAPOR	28
3.	HEAT CAPACITY OF PERFLUORO-2-BUTYL- TETRAHYDROFURAN	31
4.	RESIDUAL VOLUMES	51
5.	ACTIVITY COEFFICIENTS	81
6.	PRESSURE-ENTHALPY CHART FOR PERFLUORO-2- BUTYL-TETRAHYDROFURAN	83
7.	DEVIATION PLOT, P_c - P	86

LIST OF APPENDIX ILLUSTRATIONS

1.	CALORIMETER AND REBOILER	103
2.	ELECTRICAL CIRCUIT	106
3.	THERMEL CALIBRATION	115
4.	THERMEL EMF WHEN NO HEAT WAS ADDED TO VAPOR	122
5.	$C_{p_{obs}}$ EXTRAPOLATED TO INFINITE FLOW RATE	122

NOMENCLATURE

C_p	heat capacity at constant pressure, cal/gr, °C or cal/mole, °K
C_{pl}^{sat}	heat capacity of the saturated liquid
C_v	heat capacity at constant volume, cal/mole, °K
f	fugacity, atmospheres
F	vapor flow rate, gr/sec
H	enthalpy of superheated vapor, cal/mole
H_0	enthalpy of compound in reference state, saturated liquid at 0°C. $H_0 = 0$.
H_l^1	enthalpy of saturated liquid at 1 atmosphere (superscript refers to pressure), cal/mole
H_v^1	enthalpy of saturated vapor at one atmosphere, cal/mole
H_v	latent heat of vaporization, cal/mole
P	pressure, atmospheres
P_c	pressure calculated by a vapor pressure equation
P_{cr}	critical pressure, atmospheres
Q	heat input, cal/sec
q	heat losses other than by radiation, cal/sec
r	deviation between calculated and experimental vapor pressures, atmospheres
S	entropy, cal/mole, °K
S_0	entropy of compound in reference state, saturated liquid at 0°C, cal/mole, °K. $S_0 = 0$.
S_v	entropy of vaporization, cal/mole, °K
T	temperature, °C or °K
T_{cr}	critical temperature, °C or °K

v	superheated vapor volume, liters/mole
v_v	volume of saturated vapor, liters/mole
v_l	volume of saturated liquid, liters/mole
W	heat losses due to radiation, calories
α	residual volume, liters/mole

I. SUMMARY

The fluorinated cyclic ether studied in this work had an empirical formula, $C_8F_{16}O$, and, according to the suppliers, Minnesota Mining and Manufacturing Company, was composed of two isomers; perfluoro-2-butyl-tetrahydrofuran and perfluoro-2-propyl-tetrahydropyran. The material was purified by repeated distillation and a center cut with a one degree boiling range was used in determining the physical properties.

The calculation of the thermodynamic properties was based on the following experimentally determined physical properties: the specific volumes of the saturated liquid and vapor, the vapor pressure, the heat capacity of liquid at one atmosphere, the specific volume of the superheated vapor and the heat capacity of the vapor at one atmosphere. All the properties except the latter were available from previous work.

The heat capacity of the vapor was determined with a flow calorimeter consisting of a 250 cc., silvered, vacuum jacketed reboiler to provide constant vapor flow rates and a calorimeter in which heat was transferred to the vapor from an electrical resistance heater and resulting temperature rise was measured by a five-junction copper-constantan thermel. Steady heater current was

supplied by 2 six volt storage batteries, which were continuously charged by 2 twelve volt batteries. The compound was kept in a closed system in which the vapor was continuously condensed and returned to the reboiler. The heat input was determined by measuring the current drawn by the heater and the voltage drop across it. Flow rates were determined by weighing a sample collected over a timed interval. Heat losses were accounted for by measuring the temperature drop under conditions when no heat was being supplied to the vapor, which corrected for Joule-Thomson cooling, and by extrapolating the observed heat capacities to infinite flow rate.

The reliability of the calorimeter was established by determining the heat capacity of benzene vapor. The results agreed with accepted values within $\pm 1.3\%$. The heat capacity of $\text{C}_8\text{F}_{16}\text{O}$ was determined for temperatures from 110°C to 240°C and was found to vary linearly with temperature and could be represented by the equation,

$$C_p = 72.73 + 0.06745T,$$

where C_p is in cal/mole, $^\circ\text{K}$ and T is in $^\circ\text{K}$. This equation fit the experimental data with an average deviation of $\pm 1.3\%$.

Although the data on the physical properties were incomplete in spots, they were extended by analytical and by graphical means, when necessary, to cover the temperature range under consideration.

The enthalpy and entropy of the saturated liquid up to the atmospheric boiling point of 102.6 °C were calculated by integration of the appropriate equations using the heat capacity of the liquid. The latent heat of vaporization was calculated by the Clausius-Clapeyron equation used in conjunction with the vapor pressure equation, $\log P = A + B/T$. The change of the enthalpy and entropy with pressure in the vapor phase was determined graphically because the P-V-T data could not be fitted to an equation of state. The residual volumes, $\alpha = RT/P - v$, were used to make these calculations. After the superheated enthalpies and entropies were determined, they were extrapolated at constant temperature to the saturation pressure to find the enthalpy and entropy of the saturated vapor. The latent heat of vaporization was subtracted from the saturated vapor enthalpy to determine the enthalpy of the saturated liquid above 102.6°C. The activity coefficients, f/P , were determined by graphical integration of the α versus pressure plots.

The consistency of the calculated results were checked when possible. The latent heats were compared with those calculated using the Clausius-Clapeyron equation in conjunction with the vapor pressure equation, $\log P = A + B/T + C \log T$, for temperatures above 160°C. The two methods agreed to within $\pm 0.8\%$.

The saturated liquid enthalpy above 102.6°C was also calculated by integration of the appropriate equations

using the liquid heat capacity extended to the critical. The enthalpy calculated by this method showed an average deviation of $\pm 1.1\%$, excluding the deviation at the critical temperature, from the enthalpy calculated by subtracting the latent heat from the enthalpy of the saturated vapor. The comparison of the saturated liquid enthalpy calculated by these two procedures gives an indication of the consistency of the experimental results used in making these calculations.

The superheated vapor volumes were calculated from the smoothed residual volume plot. The consistency of the superheated properties was verified by the regularity in the results when plotted on a large scale.

Because of the similarity of the isomers, their physical properties are very nearly the same. The fact that both isomers were present in the sample would not affect to any great extent the values of the properties reported.

The physical properties of $C_8F_{16}O$ show no outstanding irregularities from the physical properties of fluorocarbons of similar molecular weight, such as C_6F_{14} and C_7F_{16} . It exhibits a low latent heat per unit weight (19.52 cal/gr at 102.6°C) and a low specific heat. The specific heat of the liquid (0.248 cal/gr, $^\circ\text{C}$ at 25°C) is similar to that of the vapor (0.236 cal/gr, $^\circ\text{C}$ at 110°C).

The critical pressure of C_8F_{16} (15.86 atmospheres) is below that reported for C_7F_{16} (16.0 atmospheres). Otherwise, the physical properties of these fluorocarbons vary with molecular weight as do all compounds.

Thermodynamic data of sufficient accuracy for engineering calculations are presented in both tabular and graphical form for temperatures from 60°C to 300°C for pressures up to 44 atmospheres.

II. INTRODUCTION

Compilations of thermodynamic data on various compounds are useful in engineering calculations. The thermodynamic networks for some fluoro-chloro-hydrocarbons have been determined and these have been of value for the calculations involved in refrigeration cycles. The high molecular weight fluorocarbons similar to the compound studied in this project are being considered as vapor phase coolants in electrical equipment. For these studies the heat content and volumetric data are of great importance.

Fluorocarbon compounds have been used in the laboratory for studies on solubilities and other experiments involving the liquid state. Here they are used as chemically inert, non-polar reference compounds. The comparison of the properties of fluorocarbons with those of the corresponding hydrocarbons have provided information concerning intermolecular forces.

The relationship between the physical properties and molecular structure of fluorocarbons has been studied by Bondi,¹ who states that the polarizability and diamagnetic

¹Bondi, A., J. Phys. and Colloid Chem., 55, 1355-68(1951).

susceptibility of fluorocarbons are small due to the presence of a relatively greater proportion of ionic bonds than in

other organic molecules. Correlations based on polarizability are shown to be better than those based on molecular weight. The packing of the molecules is much the same as for other liquids but the molecules are extremely stiff, which accounts for the surprising lack of external rotation in the liquid state. This lack of complete freedom of rotation is demonstrated by the fact that the entropy of vaporization, ΔS_v , is greater than the value of 20.2 e.u. which is the accepted value for freely rotating molecules.

Among the data available on fluorocarbons of high molecular weight are those of Oliver and Grisard² on

²Oliver, G. D., and Grisard, J. W., J. Am. Chem. Soc., 73, 1688 (1951).

hexadecafluoroheptane. They have determined that the heat capacity from 18 °K up to 310 °K and presented vapor pressure data for this compound. The boiling point of C₇F₁₆ is 82.50 °C and its latent heat is 7543 cal/mole. The properties of the superheated vapor were not determined.

The work of Stiles and Cady³ showed that the

³Stiles, V. E., and Cady, G. H., J. Am. Chem. Soc., 74, 3771-3 (1952).

properties of fluorocarbon isomers are much alike. The boiling point of perfluorohexane is 57.23 °C whereas the boiling point of its isomer, perfluoro-2-methyl-pentane, is 57.74°C. The latent heat of the former compound is 7307

cal/mole while that of the latter is 7273 cal/mole. The effect of branching on fluorocarbons is to increase the boiling point, whereas the reverse is noted for hydrocarbons.

The fluorocarbon compound studied was a fluorinated cyclic ether with an empirical formula, $C_8F_{16}O$. The raw material was supplied by Minnesota Mining and Manufacturing Company. It was believed to be composed of two isomers; (I) perfluoro-2-butyl-tetrahydrofuran and (II) perfluoro-2-propyl-tetrahydropyran. The formulae of these isomers are shown below.

The unpurified material was distilled in a 20 mm. diameter, silvered and vacuum jacketed distilling column, packed with small glass helices and operated at a reflux ratio of 20 to 1. The sample collected for the P-V-T studies was taken from the center cut of the final distillation. For the determination of the liquid and vapor specific heats, a sample with a boiling range of about one degree was used. The boiling point at 760.0 mm. Hg., as determined by an ebulliometer, was 102.6°C . The percentage of each isomer in the sample was not determined and it was assumed

that the sample contained equal amounts of the isomers. For convenience the material is referred to as perfluoro-2-butyl-tetrahydrofuran in all table and graph headings and the empirical formula, $C_8F_{16}O$, is used in the text for the sake of brevity.

Methods of calculating thermodynamic properties have been discussed adequately in thermodynamic textbooks. Dodge⁴ has reviewed some of the methods which have been used

⁴Dodge, B. F., Chemical Engineering Thermodynamics (New York: McGraw-Hill Book Company, 1940), pp. 257-260.

and concludes that the method to be chosen depends on the data available. Quite often the data are incomplete and from different sources. The greatest difficulty then, lies in extending the data to cover the range under consideration.

The compilation of the thermodynamic properties of the fluoro-chloro-hydrocarbons by Benning and McHarness⁵

⁵Benning, A. F., and McHarness, R. C., Ind. Eng. Chem., 31, 912 (1939).

serves as an illustration of the procedure to be followed. The experimental data required were vapor pressures, liquid and vapor densities, liquid and vapor specific heats and the ratio, C_p/C_v , for the vapor. In this work vapor densities were correlated by an equation of state of the Beattie-Bridgeman type and the effect of pressure on the

enthalpy and entropy was calculated using this equation. The latent heats of vaporization were calculated by the Clausius-Clapeyron equation using a vapor pressure equation in conjunction with the liquid and vapor volumes. These values were checked by calculating the heat content of the saturated vapor from the vapor heat capacity and the equation of state and subtracting from this the enthalpy of the saturated liquid which was calculated from the liquid heat capacity. Another check was made by calculating the ratio, C_p/C_v , from the vapor heat capacity and the equation of state, and by comparing the calculated value with that determined experimentally by the velocity of sound method. The work of Benning and McHarness stresses the importance and the method of proving the consistency of the calculated values.

The problem presented in this study was to determine the thermodynamic properties of $C_8F_{16}O$ from $60^{\circ}C$ to $300^{\circ}C$ for pressures from one to 40 atmospheres using the experimental data, either available or to be determined, on the heat capacity of the liquid for temperatures from $0^{\circ}C$ to the atmospheric boiling point, the vapor pressure, the liquid and vapor volumes, and the heat capacity of the vapor at one atmosphere. The calculated results were to be presented in both graphical and tabular form.

All the data needed except the heat capacity of the vapor was available and the experimental determination of this property is presented in the next section before proceeding with the calculation of the thermodynamic functions.

III. HEAT CAPACITY OF THE VAPOR

A. Introduction

As part of the study of the thermal properties of $C_8F_{16}O$, it was necessary to determine the heat capacity of the vapor from the atmospheric boiling point to $300^{\circ}C$. Similar determinations have been made using the velocity of sound method, the isentropic expansion method and the constant flow method. These methods have been thoroughly reviewed by Masi.⁶ The latter method has the advantage of

⁶Masi, J. F., Trans. Am. Soc. Mech. Engrs., 76, 1067 (1954).

being simple and direct. Since it has been widely used there are available sufficient data with which the results can be compared. It has been used for compounds with boiling points above room temperature; compounds similar to $C_8F_{16}O$.

In recent years both Pitzer and DeVries have thoroughly discussed the use of the flow calorimeter for measuring the heat capacity of vapors and they have given particular emphasis to the details of design. Pitzer⁷ lists

⁷Pitzer, K. S., J. Am. Chem. Soc., 63, 2413 (1941).

the essentials of a good flow calorimeter as,

"a. a constant, accurately measured flow rate,

b. a heater to introduce an accurately measured amount of heat into the gas,

c. a thermometer that measures the temperature of the gas itself and

d. a design which prevents excessive heat loss between heater and thermometer and which permits accurate correction for the loss occurring."

The use of a closed system was essential to prevent the accumulation of water vapor which might be picked up by the liquid if it made contact with the air. Since the heat capacity of fluorocarbons is about half that of water vapor, a small amount of water would have a pronounced effect on the heat capacity of the $\text{C}_8\text{F}_{16}\text{O}$ vapor.

Montgomery and DeVries⁸ studied the effect of

⁸Montgomery, J. B., and DeVries, T., J. Am. Chem. Soc., 64, 2372 (1942).

calorimeter design on the experimental heat capacity and made the following conclusions:

It is possible to design flow calorimeters in which the results are precise to within $\pm 0.3\%$. The elimination of constant errors from the design and construction of flow calorimeters which will give an accuracy better than a few percent is difficult. They warn that a high degree of precision is sometimes mistakenly considered to indicate high accuracy. They state,

Some essentials of a properly designed flow calorimeter include:

(a) a minimum rate of heat loss, obtained by reducing the radiating surface to a minimum, by evacuating the jacket space around the calorimeter, and by using properly spaced radiation shields to prevent radiated heat from being used twice; (b) a proper arrangement of the vapor heater and thermometers to eliminate constant errors due to the effect of direct radiation and conduction from the heater; and (c) a construction which uses a minimum volume of material of low heat capacity to reduce the time-lag to temperature changes.

These principles were used as a guide in constructing the calorimeter used in this work.

An analysis of the heat transfer problem associated with the experimental flow calorimeter chosen for this work was presented by Sinke and DeVries.⁹ Losses due to

⁹Sinke, G. C., and DeVries, T., J. Am. Chem. Soc., 75, 1815 (1953).

radiation, W , are given by the equation

$$W = k_1(T_1^m - T_0^m),$$

where m will vary between 4 and 5.5, depending on the radiating surface. The temperature difference between the inner (T_1) and outer (T_0) walls of the calorimeter, $\Delta T' = T_1 - T_0$, will be slightly larger than the measured temperature rise, ΔT , of the heated vapor. Considering the first term of a Taylor expansion, W can be approximated (within 3%) by the equation,

$$W \cong mk_1 T_0^{(m-1)} \Delta T'.$$

Now defining $\alpha = 1/2dC_p/dt$, it is apparent that $C_p'' + \alpha \Delta T$ will be the average heat capacity of the vapor over the temperature interval ΔT near the temperature of the calorimeter bath, T_0 . By a heat balance,

$$Q = (C_p'' + \alpha \Delta T)F \Delta T + mk_1 T_0^{(m-1)} \Delta T' + \Delta q$$

where Q is the heat input in calories per second, C_p is the vapor heat capacity at T_0 , F is the flow rate of the vapor and Δq is any heat loss other than by radiation. Rearranging the equation,

$$\begin{aligned} C_{pobs} = Q/F\Delta T &= (C_p'' + \alpha \Delta T) + mk_1 T_0^{(m-1)} \Delta T'/F\Delta T + \Delta q/F\Delta T \\ &= (C_p'' + \alpha \Delta T) + (1/F) (mk_1 T_0^{(m-1)} \Delta T'/\Delta T + \Delta q/\Delta T). \end{aligned}$$

It has been shown that $(mk_1 T_0^{(m-1)} \Delta T'/\Delta T + \Delta q/\Delta T)$ is a constant independent of flow rate, heat input and temperature rise. By letting,

$$k_2 = (mk_1 T_0^{(m-1)} \Delta T'/\Delta T + \Delta q/\Delta T)$$

and by letting,

$$C_p = C_p'' + \alpha \Delta T$$

it can be shown that,

$$C_{pobs} = C_p + k_2/F.$$

Thus by plotting C_{pobs} versus the reciprocal flow rate and extrapolating to infinite flow rate the average heat capacity at the mean temperature of the vapor (C_p) is obtained as the intercept at $(1/F) = 0$. To correct for heat losses the observed heat capacity must be obtained for a series of runs at different flow rates. This procedure was used in this work.

It is obvious from the preceding discussion that it is impossible to determine whether all the heat losses have been accounted for by the method described. Therefore, the accuracy of determining vapor heat capacities cannot be ascertained. However, it is equally apparent that the smaller the heat losses the more accurate the calorimeter. For this reason it is best to compare the experimental results with those determined by a calorimeter with good precision such as that of Scott, et al.¹⁰ Extrapolation to

¹⁰Scott, D. W., Waddington, G., Smith, J. C., and Huffman, H. M., J. Chem. Phys., 15, 565 (1947).

the zero value of the reciprocal flow, corrected for heat losses which amounted to no more than 2% at the highest temperature and lowest flow rate with their apparatus. For this reason Scott's data provide a good basis for determining the reliability of data from a flow calorimeter.

This brief discussion of flow calorimeters should make clear the reasons for the choice of the experimental apparatus, the procedure used and the method of calculating the results.

B. The Apparatus

The experimental apparatus, shown diagrammatically in Figure 1, consisted of two constant temperature baths, one for the reboiler and one for the calorimeter. Both baths were stainless steel cooking pots, 13 7/8 inches in diameter and 15 inches deep, placed in a box constructed of angle iron and transite board. The baths were insulated on all sides by a four inch layer of vermiculite, an exploded mica. Further discussion of the baths and the temperature control are presented in Appendix A.

A steady flow of vapor was provided by the reboiler shown in Figure 1 and in more detail in Appendix A, Figure A-1. The space between the double wall was evacuated through the 10 mm. vacuum line, located on the side, to a pressure of about 1 micron. This space was silvered except for a narrow slit through which the interior of the flask could be observed. The liquid returned from the condensing system via the 6 mm. tubing coiled around the flask and was heated to the bath temperature before entering the flask at the bottom. The heater was a 16 B&S gage Chromel A wire covered with fiber glass insulation to provide nucleation sites for smooth, even boiling. The rate of vaporization was controlled by two "Variac" transformers connected in series to the 0.8 ohm heater. Vapor rates up to 0.1 gr/sec could be obtained.

FIGURE 1
EXPERIMENTAL APPARATUS

SAMPLING
FLASK

FIGURE 1
EXPERIMENTAL APPARATUS

The vapor left the reboiler through a 10 mm. tube lagged with asbestos tape and heated by an asbestos heating tape which was controlled by a "Variac" transformer. The temperature of the tube was indicated by a thermocouple imbedded in the lagging. This temperature was set a few degrees above the boiling point of the fluid being studied to prevent condensation.

The vapor from the reboiler passed through 2 meters of 10 mm. glass tubing coiled in the calorimeter bath. The calorimeter was similar to that described by Coleman and DeVries¹¹ and was made of 6 mm. glass tubing. It was

¹¹Coleman, C. F., and DeVries, T., J. Am. Chem. Soc., 71, 2839 (1949).

essentially an insulated U tube with a heater and a differential thermel. The vapors entered past the cold junction of the thermel, were heated by the electrical resistance heater, flowed through a constriction in the bottom of the U tube to assure complete mixing and then flowed out past the hot junction of the five-junction thermel. The jacketed space was completely silvered and was evacuated to about 1 micron Hg during operation.

The five-junction thermel was made of #24 B&S gage copper and constantan wire which had a ceramic insulation and was covered by cotton cloth. The junctions of the thermel were silver soldered and dipped in porcelain

cement (Sauereisen) to keep the tips from short circuiting. The calibration of the thermel is discussed in Appendix B.

The wires were sealed into the 6 mm. glass tubing of the calorimeter after they had been placed in a 6 inch, single hole, 2 mm. diameter ceramic tubing. Sauereisen cement sealed the wires in the ceramic tubing and was used to hold the ceramic tubing in the glass tubing.

The heater was made of 30 B&S gage Chromel A wire coiled at the end of a 2 mm., 2 hole ceramic tube. The two 20 B&S gage copper current lead wires extended through the two holes of the ceramic tubing where they were silver soldered to the Chromel A heater. The potential wires were soldered to the current wires at the top of the tubing. The current lead wires and the potential wires were insulated by glass fiber insulation. The calorimeter and its parts are shown in Appendix A, Figure A-1, in more detail.

The vapor line from the calorimeter to the condenser was lagged and was heated by an asbestos heating tape. The condenser was designed such that the condensed fluids were not subcooled. A two-way, Teflon stopcock was used to divert the liquid stream to the sampling flask when the flow rates were being determined. The Teflon stopcock did not stick and required no grease which could have been dissolved by the fluids. A short condenser sub-cooled the liquid before it went to the sampling flask to prevent the liquid from flashing. A drying tube was attached to the sampling

flask when the sample was being collected to keep moisture-laden air from the liquid. Flow rates were timed by a Cenco precision stopwatch. The sampling flask was weighed on a balance accurate to 0.2 milligrams using a similar flask as a tare to eliminate buoyance effects. The sample was returned to the reboiler by attaching the sampling flask to the top of the condenser.

The electrical circuit used to supply current to the calorimeter heater, to measure the emf of the thermel, the voltage drop across the heater, and the current drawn by the calorimeter heater are shown in Appendix A, Figure A-2.

Constant current was supplied by two six volt storage batteries connected in parallel that were continuously charged by two parallel connected 12 volt lead storage batteries. The two 12 volt batteries were intermittently charged by a selenium rectifier type battery charger. This combination provided steady current which varied about 0.002 amperes per hour. The current to the heater was regulated by a 100 ohm variable resistor made by the Ohmite Manufacturing Company. A similar resistor was used to adjust the current flow from the 12 volt batteries to the 6 volt batteries.

Both the current drawn by the heater and voltage drop across it were measured by a type K-2 Leeds and Northrup potentiometer. An Eppley standard cell was used and the null point was indicated by a Leeds and Northrup

galvanometer. The current was determined by measuring the voltage drop across a 0.1000 ohm Leeds and Northrup standard resistor. The voltage drop across the heater was measured using a Leeds and Northrup volt box, which was set to divide the potential in the ratio 100:1, and the K-2 potentiometer.

C. Procedure

After assembling the apparatus and calibrating the thermel, the heat capacity of benzene was determined as a check on the apparatus. The thiophene-free benzene was washed with a 10% H_2SO_4 solution, with a 5% caustic solution, and with distilled water before being distilled. The sample of $\text{C}_8\text{F}_{16}\text{O}$ used was purified by repeated distillation.

To calculate the heat capacities, the average observed temperature rise, the current drawn by the heater, the voltage drop across the heater, the flow rate, the temperature drop under conditions when no heat was being added to the vapor, and the temperature of the calorimeter bath were determined. The procedure is discussed in more detail in Appendix C.

The observed heat capacity, $C_{p\text{obs}}$, was calculated from this data by the equation,

$$C_{p\text{obs}} = \frac{EI}{4.185 F \Delta T},$$

where $C_{p\text{obs}}$ is in cal/gr, $^{\circ}\text{C}$, E is the voltage drop in volts, I is the current in amperes, F is the flow rate in grams per second, 4.185 is the factor to convert joules to calories, and ΔT is the temperature rise in $^{\circ}\text{C}$. ΔT was calculated from the equation,

$$\Delta T = \Delta T_{\text{obs}} - \Delta T_{\text{c}},$$

where ΔT_{obs} is the observed temperature rise and ΔT_{c} is

the temperature drop under conditions when no heat was added to the vapor.

The heat capacity, C_p , at the average temperature was calculated using the equation,

$$C_{pobs} = C_p + b/F,$$

by fitting the data to the equation by the method of least squares and calculating C_p as the intercept at $1/F = 0$. A step by step sample calculation is presented in Appendix D.

D. Results

Experimental heat capacities for benzene vapor and $\text{C}_8\text{F}_{16}\text{O}$ vapor are presented in Table I. With the experimental results for benzene, the data of Scott, et al., extrapolated to the same temperature, are presented and the deviation of the experimental data from Scott's data is also listed. In Figure 2 the experimental data are plotted along with the data presented by Scott, et al.,¹⁰ Bennewitz and Rossner,¹² Montgomery and DeVries,¹³ and

¹²Bennewitz, K., and Rossner, W., Z. Physik. Chem., B 39, 126 (1938).

¹³Montgomery, J. B., and DeVries, T., J. Am. Chem. Soc., 64, 2375 (1942).

Pitzer and Scott.¹⁴

¹⁴Pitzer, K. S., and Scott, D. W., J. Am. Chem. Soc., 65, 803 (1943).

The vapor heat capacity of $\text{C}_8\text{F}_{16}\text{O}$ is presented with the percent deviations of the experimental points from the least mean square fit of the data to the equation,

$$C_p = a + bT.$$

The average percent deviation from the linear equation is $\pm 1.31\%$. In calculating the linear equation the data at 239.3°C were not included. This line is drawn through the data in Figure 3 along with the heat capacity of the liquid that was previously determined.

FIGURE 2
HEAT CAPACITY OF BENZENE VAPOR

TABLE I

EXPERIMENTAL HEAT CAPACITY OF BENZENE AND PERFLUORO-2-BUTYL-TETRAHYDROFURAN VAPOR

A. Benzene			
Temp °C	C _p (expt'l) Cal/mole, °K	C _p (Scott, <u>et al.</u>) Cal/mole, °K	Per Cent Devia- tion
103.3	26.2	25.97	0.77
123.0	27.6	27.27	1.10
141.8	29.1	28.46	2.11
141.9	28.7	28.46	0.70
161.2	30.4	29.62	2.70
181.3	30.6	30.71	-0.30
B. Perfluoro-2-butyl-tetrahydrofuran			
Temp °C	C _p Cal/mole, °K	Per Cent Deviation from Calc. Value	
112.5	96.7	-1.73	
122.6	97.8	-1.31	
132.1	100.3	0.60	
142.0	102.2	1.79	
151.9	100.7	-0.30	
152.0	104.0	2.87	
163.2	103.4	1.57	
171.1	101.4	-0.88	
171.4	101.1	-1.27	
191.1	102.7	-0.96	
192.9	102.7	-1.06	
212.4	104.6	-0.48	
239.3	104.5	-2.24	

FIGURE 3
HEAT CAPACITY
PERFLUORO-2-BUTYL-TETRAHYDROFURAN

E. Discussion of Results

The heat losses associated with flow calorimeters cannot be completely eliminated, as was pointed out in the introduction to this section, and, therefore, it is necessary to find out how well the heat losses have been accounted for by the method used to calculate the heat capacity. For this reason, the heat capacity of benzene vapor was determined and results were compared with published data. From Figure 2 it can be seen that the experimental data are higher than any of the other data, but the least mean square fit of the data does not deviate from the data of Scott, et al.,¹⁰ which is generally considered to be quite reliable, as much as some of the other published results. The average deviation of the experimental points from Scott's data was $\pm 1.29\%$. The deviation of the experimental data from the value calculated from the linear equation fitted to the data by the method of least squares was $\pm 0.96\%$, which is an indication of the precision of the data.

The experimental data for $\text{C}_8\text{F}_{16}\text{O}$ showed a deviation of $\pm 1.31\%$ from the least mean square fit of the data. This deviation is greater than that for benzene and probably represents a better indication of the precision of the calorimeter since more runs were made on $\text{C}_8\text{F}_{16}\text{O}$.

Two corrections were made for heat losses. One correction was applied to the temperature rise to account

for the heat losses when the vapor heater was off. This loss can be attributed largely to Joule-Thomson cooling. In Figure A-4 in Appendix D, this correction was plotted against the reciprocal flow rate. The correction decreases with increasing flow rate indicating that part of the loss was due to radiation losses. This correction was independent of the temperature rise and, for the ΔT 's used in these determinations, about 5 °C, accounted for about 5.5% of the total temperature rise.

The other correction was applied by extrapolating the observed heat capacities to infinite flow rate to account for radiation losses. These losses were quite large, as can be seen in Figure A-5, and showed that as much as 40% of the heat from the calorimeter heater was dissipated by radiation losses at the lower flow rates. At high flow rates about 20% of the heat was being lost due to radiation.

A summation of the deviations of the individual measurements employed to calculate the heat capacities indicated that deviations in temperature-rise measurements and flow rates account for almost all of the variance. The experimental deviation in measuring the heat input was about $\pm 0.06\%$ (electrical measurements are quite precise), the deviations in measuring the temperature rise after steady state had been attained were about

$\pm 0.5\%$, and a deviation of about $\pm 1.0\%$ in the flow rate for a total deviation of about $\pm 1.56\%$. The deviation of the experimental points from the least mean square fit of the data was about $\pm 1.3\%$ indicating that some of the scatter in the observed heat capacities was resolved by drawing the least mean square line through the data in the C_{pobs} versus $1/F$ plots.

F. Conclusions

The maximum deviation of the experimental heat capacity data for $\text{C}_8\text{F}_{16}\text{O}$ vapor from the least mean square fit of the data to a linear equation was + 2.87% and the average deviation was $\pm 1.31\%$. The linear equation was extended to 300°C although the highest experimental temperature was 239.3°C at which temperature the data fell 2.2% below the straight line fit of the data. This point was not included in the calculation of the linear equation as the reliability of the data at this high temperature was questionable. This served to place greater weight on the more reliable lower temperatures. The linear fit of the data up to 250°C can be justified, but the linear equation becomes more uncertain for temperatures above 250°C .

An analysis of the data indicated that as much as 40% of the heat supplied by the electrical resistance heater was lost by radiation at the low flow rates. However, the data for benzene vapor were found to agree with accepted values within $\pm 1.3\%$. Therefore, about 98.7% of the losses were accounted for by the methods used to correct for these heat losses.

Although the heat losses were large, the method used to calculate the heat capacities were considered to be reliable, as was indicated by the close agreement of the experimentally determined heat capacities of benzene

vapor with accepted values. Therefore, the linear equation for $\text{C}_8\text{F}_{16}\text{O}$ vapor,

$$C_p = 72.37 + 0.06745T,$$

where C_p is in calories per mole per degree Kelvin and T is in degrees Kelvin, adequately represents the experimentally determined heat capacities to justify the use of this equation in the subsequent calculations of the thermodynamic functions.

IV. PHYSICAL PROPERTIES OF PERFLUORO-2-BUTYL-TETRA-HYDROFURAN

Several investigators have collected the data on $C_8F_{16}O$ used in subsequent calculations. These data are presented here along with a brief description of the apparatus used for the determination.

Saturated liquid molar volumes from $25^{\circ}C$ to $100^{\circ}C$ were determined by Green.¹⁵ The apparatus used resembled

¹⁵Green, Robert C., "Measurement of Liquid Heat Capacities by the Adiabatic Expansion Technique," Master's thesis, Ohio State University, 1957.

a thermometer with a 3 c.c. bulb and 20 cm. stem of 1 mm. capillary tubing attached to the bulb. Constant temperature was provided by condensing vapor in a specially designed jacket surrounding the sample tube. The rise of the liquid in the stem was measured with a cathetometer. A correction was applied to account for the amount of $C_8F_{16}O$ in the vapor space above the liquid. This correction was appreciable due to the large molecular weight of this compound (416.08). The molar volumes were determined with a precision of 1 part in 20,000. The data are listed in Table II at selected temperatures.

Saturated liquid and vapor volumes from $160^{\circ}C$ to temperatures near the critical were determined by

Throckmorton¹⁶ in an apparatus also used to determine the

¹⁶Throckmorton, Robert D., "Pressure, Volume, and Temperature Relationships for Perfluoro-3-Butyl-Tetrahydrofuran," Master's thesis, Ohio State University, 1957.

superheated vapor volumes. The experimental procedure involved confining the sample over mercury in a capillary tube mounted in a steel compressor block. Pressure was applied to the compressor block and thereby to the sample by use of compressed nitrogen. Pressures were measured to ± 0.1 psi by a dead weight piston gage. Condensing vapor maintained a constant temperature around the sample tube. The accuracy in measuring volumes was about ± 0.001 cc./gr. Experimental vapor pressures differed by as much as 3.3 psi between the bubble and dew points at the same temperature. The P-V isotherm in the two-phase region was linear as would be expected for a mixture of isomers with such close boiling points. The vapor pressures presented are the average pressures between the dew and bubble points. Saturated liquid and vapor volumes are presented in Table II and the superheated vapor volumes are listed in Table V along with the enthalpy and entropy.

Saturated vapor volumes at 100 and 110°C and superheated vapor volumes for pressures near one atmosphere

were determined by Leverett¹⁷ in an apparatus similar to

¹⁷Leverett, Glen F., "Low Pressure Compressibilities of Vapors," Master's thesis, Ohio State University, 1958.

that used by Throckmorton. The sample tube was much larger (25 mm. I.D.) than that used for the high pressure work. This large tube was necessary to accommodate the very large volumes encountered at these low pressures. Pressures were determined by measuring the mercury level in a connected barometric leg. Saturated vapor volumes were determined with a precision estimated to be $\pm 0.57\%$. The superheated vapor volumes are not listed here but they could be satisfactorily represented by an equation of state of the form:

$$Pv/RT = 1 + B(T)/v.$$

The vapor pressure data between 60°C and 100°C were presented in the technical literature on C₈F₁₆O distributed by Minnesota Mining and Manufacturing Company.¹⁸

¹⁸Minnesota Mining and Manufacturing Company, New Products Division, Circular, "Fluorochemical O-75," St. Paul, Minnesota.

The static method was used to measure the liquid heat capacities.¹⁹ The sample was contained in a 250 ml.

¹⁹Yarrington, Robert M., "Heat Capacity of Fluorocarbons," Master's thesis, Ohio State University, 1956.

silvered and vacuum jacketed calorimeter. The liquid was

stirred by a glass-covered iron rod rotated by turning a U-shaped magnet placed below the calorimeter. Heat was supplied by an electric resistance coil. The temperature rise was measured by a 3-junction copper-constantan thermel. The accuracy of this heat capacity determination was estimated to be 1.1% and the data could be represented by the linear equation

$$C_p = 50.75 + 0.1752T$$

in calories per mole per degree Kelvin.

Vapor heat capacities, as previously described in this paper, could be represented by the linear equation

$$C_p = 72.37 + 0.06745T$$

in calories per mole per degree Kelvin.

TABLE II

EXPERIMENTAL SATURATED LIQUID AND VAPOR VOLUMES AND VAPOR PRESSURES OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN

Temp °C	Liquid Volumes liters/mole	Vapor Volumes liters/mole	Vapor Pressure atmospheres
25.0	0.235626		
34.995	0.239089		
44.706	0.242691		
50.149	0.244757		
60			0.2307
60.841	0.248844		
70			0.3428
70.629	0.252701		
80			0.4910
80.033	0.256925		
90			0.6824
90.612	0.261944		
99.809	0.266568		
100		30.413	0.9269
102.6			1.000
110		22.77	
160.02	0.31570	6.5659	4.528
170.02	0.32904	5.2218	5.579
179.99	0.34411	4.0958	6.799
190.00	0.35911	3.2390	8.225
200.02	0.37996	2.5065	9.887
205.01	0.39453	2.2358	10.815
210.05	0.41125	1.9213	11.803
215.65			12.990
220.01		1.4090	14.053
223.00	0.49351		14.795
224.98	0.52251		15.318
227.06			15.861

V. CALCULATION OF THERMODYNAMIC PROPERTIES

The data available to calculate the thermodynamic properties were presented in the preceding section; these include:

- (1) the heat capacity of the liquid at one atmosphere,
- (2) the heat capacity of the vapor at one atmosphere,
- (3) the vapor pressure at high temperatures and below the atmospheric boiling point but none in the intermediate region,
- (4) some saturated vapor volumes at high temperatures and at 100 and 110°C but none in the other regions, and,
- (5) saturated liquid volumes complete up to the atmospheric boiling point and from 160°C to the critical but none in the intermediate temperature range.

To complete the calculations, it was necessary to extend these data by analytical methods and by graphical interpolation.

The saturated vapor and liquid volumes in the high temperature region were completed using the Law of Cailletet and Mathais—the law of rectilinear diameters. The experimental saturated volume data were fitted by the

method of least squares to the equation,

$$\frac{v_v + v_l}{2 v_v v_l} = A + B(t_c - t),$$

where v_v and v_l are the saturated vapor and liquid volumes, respectively, in cc./gr. and t is in $^{\circ}\text{C}$. From this equation the critical volume was calculated as follows:

$$\text{at } t = t_c, \quad v_v = v_l = v_c$$

$$\text{and thus, } 1/v_c = A = 0.588228.$$

The missing saturated liquid volumes were read from a large plot and the saturated vapor volume at the same temperature was calculated by the equation above.

The vapor pressure data were complete except for the region from 102.6 to 160 $^{\circ}\text{C}$. The data in this intermediate range were obtained as follows. The constants in the common vapor pressure equation were obtained from the critical temperature and pressure and the atmospheric boiling point to give,

$$\log P_c = -1812.96/T + 4.82465.$$

From this equation and the experimental data, the deviations ($r = P_c - P$) were calculated and plotted as a function of temperature. Since r must equal zero at the atmospheric boiling point, the deviation curve was extended from 160 $^{\circ}\text{C}$ to 102.6 $^{\circ}\text{C}$ as is shown in Figure 7. Using this plot to obtain values of r , the vapor pressure, P , was calculated for the temperatures from 110 to 150 $^{\circ}\text{C}$.

Saturated liquid volumes were read from a large plot of the experimental data. Values between 110 and 160°C were read from a large plot connecting the low and high temperature data.

Latent heats of vaporization were calculated using the Clausius-Clapeyron equation, the vapor pressure equation and the deviation plot shown in Figure 7. From the Clausius-Clapeyron equation,

$$\Delta H_v = T(dP/dT) \Delta v.$$

The slope of the vapor pressure curve, dP/dT , can be obtained by graphical differentiation. However, this method does not give very precise results due to uncertainties in determining slopes. To get around this difficulty, dP/dT was determined as follows. From the deviation equation,

$$P = P_c - r$$

and, differentiating with respect to temperature,

$$dP/dT = dP_c/dT - dr/dT.$$

The first term, dP_c/dT , was calculated from the vapor pressure equation as follows:

$$2.303 \log P_c = \ln P_c = 2.303 \times 1812.96/T + 2.303 \times 4.82465$$

$$d \ln P_c / dt = 2.303 \times 1812.96 / T^2$$

$$dP_c / dT = 2.303 \times 1812.96 P_c / T^2$$

The second term, dr/dT , was determined graphically from the deviation plot. Although this method still involves

graphical differentiation, the error in dr/dT will not affect dP/dT in direct proportion. After values of dP/dT were obtained, ΔH_v was calculated from the Clausius-Clapeyron equation using the volume change due to vaporization, Δv , obtained from the experimental data. A large plot of the latent heats as a function of temperature was made in order to extend the data to 60°C . From this plot the latent heats for temperatures from 60°C to the critical temperature were read off for 10 degree intervals.

The remaining, unknown vapor volumes were calculated from the Clausius-Clapeyron equation,

$$\Delta v = \Delta H_v / T(dP/dT)$$

and

$$v_v = v_l + \Delta v.$$

This completed the P-V-T saturation properties for C_8F_{16} that were needed for subsequent calculations.

Before proceeding with the calculation of the enthalpy and entropy, it was necessary to define the reference state for these two properties. Both the enthalpy and entropy were set equal to zero for the saturated liquid at 0°C .

To calculate the enthalpy and entropy of the saturated liquid from 60 to 102.6°C , it was assumed that the heat capacity of the saturated liquid, C_{pl}^{sat} , was equal to the heat capacity of the liquid at one atmosphere. The

equations used to calculate these properties were derived as follows:

$$C_{p1} = 50.75 + 0.1752T$$

$$\int_{H_0}^{H_1} dH = \int_{T_0}^T C_{p1} dT$$

integration gives,

$$H_1 - H_0 = H_1 = 50.75(T - 273.16) + 0.0876(T^2 - 273.16^2)$$

and for the entropy,

$$\int_{S_0}^{S_1} dS = \int_{T_0}^T (C_{p1}/T) dT$$

$$S_1 - S_0 = S_1 = 50.75 \ln(T/273.16) + 0.1752(T - 273.16).$$

The enthalpy and entropy of the superheated vapor between 60 and 102.6°C were calculated by adding ΔH_v and ΔS_v to the liquid enthalpies and entropies,

$$H_v = H_l + \Delta H_v$$

$$S_v = S_l + \Delta S_v.$$

In the superheated region, the enthalpy and entropy were calculated from the heat capacity data for the vapor at one atmosphere and the effect of pressure was accounted for from the P-V-T data available. The total change in enthalpy is given by the equation,

$$dH = (\partial H / \partial T)_P dT + (\partial H / \partial P)_T dP,$$

$$dH = C_p dT + (\partial H / \partial P)_T dP.$$

The first term, which gives the effect of temperature on the enthalpy at constant pressure, was expanded to give,

$$H^1 - H_V^1 = \int_{375.76}^T C_p dT$$

where H^1 is the enthalpy of the superheated vapor at 1 atmosphere at the temperature T and H_V^1 is the saturated enthalpy at 1 atmosphere. Since

$C_p = 72.37 + 0.06745T$, and $H_V^1 = 19,162$ cal/mole, this equation expands to,

$$H^1 = 19,162 + 72.73(T-375.76) + 0.033725(T^2-375.76^2).$$

Similar derivations for the entropy show that,

$$dS = (C_p/T)dT + (\partial S / \partial P)_T dP$$

and

$$S^1 = 55.78 + 72.37 \ln(T/375.76) + 0.06745(T-375.76).$$

The pressure effect on the enthalpy, $(\partial H / \partial P)_T$, can be rearranged to give the relation,

$$(\partial H / \partial P)_T = -T(\partial v / \partial T)_P + v$$

and the pressure effect on the entropy gives,

$$(\partial S / \partial P)_T = -(\partial v / \partial T)_P.$$

Generally, it is desirable to find an equation of state which fits the P-V-T data throughout the region in which the calculations are to be made such that the term $(\partial v/\partial T)_p$, can be determined analytically. However, for $C_8F_{16}O$, attempts at fitting the data to existing equations proved fruitless. The Benedict-Webb-Rubin equation was tried but the curvature of the isometrics was too pronounced and the constants for this elaborate equation could not be calculated. A review of various equations of state soon showed that they are useful for light hydrocarbons but not for high molecular weight compounds. The constants for the van der Waal's equation were determined using the extreme temperatures and pressures for several isometrics. These constants could be correlated with the specific volume, but the usefulness of such an equation was doubtful. For these reasons, graphical methods were employed.

Previously, Deming and Shupe²⁰ have shown the use-

²⁰Deming, W. E., and Shupe, L. E., Phys. Rev., 37, 638-654 (1931).

fulness and simplicity of using residual volumes to calculate thermodynamic properties graphically. The residual volume was defined as,

$$\alpha = RT/P - v.$$

Using this term, the effect of pressure on the enthalpy and entropy could be determined as follows:

$$(\partial H/\partial P)_T = -T(\partial v/\partial T)_P + v$$

but

$$v = RT/P - \alpha$$

$$(\partial v/\partial T)_P = R/P - (\partial \alpha/\partial T)_P$$

Therefore,

$$\begin{aligned} (\partial H/\partial P)_T &= -RT/P + T(\partial \alpha/\partial T)_P + RT/P - \alpha \\ &= T(\partial \alpha/\partial T)_P - \alpha \end{aligned}$$

For the entropy,

$$(\partial S/\partial P)_T = -(\partial v/\partial T)_P = -R/P + (\partial \alpha/\partial T)_P.$$

The advantages of using residuals are:

(1) the slope of α versus T at constant P is much greater than the slope of v versus T at constant P . Therefore, the slopes can be determined with great precision by graphical means, and

(2) small errors in determining vapor volumes are made apparent. Plotting the data is a useful method of smoothing the superheated volume data.

The residual volumes, α , were calculated from Throckmorton's data for pressures above 3 atmospheres for temperatures above 160°C. The isotherms, shown in Figure 4, were extended to zero pressure, the data of Leverett being used as a guide in drawing the curves. Each isotherm was drawn so as to be consistent with surrounding isotherms. Leverett's data were used to establish the α isotherms from 110 to 160°C. A cross plot of α values at constant

FIGURE 4
RESIDUAL VOLUMES

pressure as a function of temperature was used to further smooth the data. The regularity of the constant pressure curves indicated that the α values had been satisfactorily extended to zero pressure.

From the plots of α versus T at constant P , the slopes were determined for each 10 degree interval between 160 and 300°C for pressure intervals of one atmospheres from 1 to 44 atmospheres. This slope, $(\partial\alpha/\partial T)_P$, was determined with use of a straightedge. The consistency with which the slopes were determined was verified in subsequent plots of the term $[T(\partial\alpha/\partial T)_P - \alpha]$ against pressure which showed considerable regularity.

The effect of pressure on enthalpy was determined by calculating the term, $T(\partial\alpha/\partial T)_P - \alpha$; by plotting this as a function of pressure the equation,

$$H - H^1 = 24.206 \int_{P=1}^P [T(\partial\alpha/\partial T)_P - \alpha] dP,$$

was graphically integrated. The only difficulty encountered in this integration was for temperatures immediately above the critical, where the slope, $(\partial\alpha/\partial T)_P$, changes rapidly. Values of $T(\partial\alpha/\partial T)_P - \alpha$ for each 0.2 atmosphere were determined in this region to facilitate the drawing of the curves.

The effect of pressure on entropy was determined similarly by graphical integration of the equation,

$$S-S^1 = 24.206 \int_{P=1}^P [R/P - (\partial \alpha / \partial T)_P] dP.$$

The values for both enthalpy and entropy variation with pressure are presented in Appendix Tables VIII and IX in Appendix F.

The pressure corrections were subtracted from the values of H and S at one atmosphere to give the superheated enthalpies and entropies up to 44 atmospheres. The two properties were plotted against pressure with temperature as a parameter. The results were consistent except for temperatures of 230, 240 and 250°C for pressures above the critical. To smooth the data in this region, cross plots of H and S against temperature, with curves of constant pressure were constructed. These smoothed data were plotted again on the charts of H and S against temperature which then showed greater consistency.

From the H versus P and S versus P plots for constant temperatures, the saturated enthalpies and entropies of the vapor were obtained by extending the isotherms to the saturation pressure. The latent heat of vaporization and entropy of vaporization were subtracted from these saturated vapor properties to give the saturated liquid enthalpies and entropies for temperatures from 160°C to the critical. The values for temperatures between 102.6 and 160°C were obtained from a plot of the data on a large

scale. This completed the calculation of the saturated properties.

The superheated vapor volumes were calculated from the values of α taken from the large plots, in order to present vapor volumes from 1 atmosphere to 44 atmospheres. These calculated vapor volumes do not vary appreciably from the experimental data.

Since the α versus P plots were available, the activity coefficient, f/P , was determined by graphical integration. The fugacity was defined such that $f = P$ as $P \rightarrow 0$. Since $dF = RT d \ln f$, and $dF = v dP$ at constant T , then $RT d \ln f = v dP$, such that,

$$\int_{f_0}^f d \ln f = (1/RT) \int_{P_0}^P v dP.$$

but $v = RT/P - \alpha$

substitution gives,

$$\int_{f_0}^f d \ln f = \int_{P_0}^P dP/P - (1/RT) \int_{P_0}^P \alpha dP.$$

Integration gives

$$\ln(f/f_0) = \ln(P/P_0) - (1/RT) \int_{P_0}^P \alpha dP$$

or

$$\ln(f_{P_0}/f_0P) = -(1/RT) \int_{P_0}^P \alpha \, dP.$$

Since $f_0 = P_0$, the last equation becomes,

$$\log (f/P) = -(1/2.303RT) \int_{P_0}^P \alpha \, dP.$$

This last equation was used to calculate the activity coefficient, f/P .

VI. RESULTS

The original data and the calculated results are presented here in graphical and tabular form.

Table III lists the saturated properties as a function of temperature in increments of 10°C up to 220°C . In this table v_v is the saturated vapor volume in liters/mole, v_l is the saturated liquid volume in liters/mole, Δv is the change in volume due to vaporization, H_l is the enthalpy of saturated vapor in calories/mole, H_v is the enthalpy of the saturated vapor in calories/mole, ΔH_v is the heat of vaporization, S_l and S_v are the entropy of the saturated liquid and vapor, respectively, in calories/mole, $^{\circ}\text{K}$ and ΔS_v is the entropy of vaporization in the same units.

Table IV lists these same properties, using the same nomenclature, but with pressure as the independent variable for every 0.5 atmosphere. This table was assembled from Table III by plotting the results of the table on a large graph and reading the values from the graph.

Table V gives the superheated enthalpy, H , entropy, S , and volume, v , for pressures from 1 to 44 atmospheres with 0.5 atmosphere increments up to 20 atmospheres and in 1 atmosphere increments above 20 atmospheres. For pressures below the critical pressure (15.861 atmospheres) the

saturation temperature in $^{\circ}\text{C}$ is listed in parenthesis below the pressure heading.

Table VI lists the activity coefficients, f/P , for temperatures from 110 to 300°C for pressure increments of 1 atmosphere. Figure 5 is a plot of this data.

Figure 6 is a $\log P$ versus enthalpy diagram with curves of constant temperature, constant entropy, and constant volume which was plotted from the data in Tables IV and V. The lines of constant entropy were obtained from the plot of S versus P at constant T . The constant volume lines were taken from the original data presented by Throckmorton. The volumes at 30, 40, and 50 cc/gr were calculated from the perfect gas law and were put in as an aid in calculating volume changes at these low pressures where the vapor may be considered ideal.

TABLE III

SATURATED PROPERTIES OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN WITH TEMPERATURE AS
INDEPENDENT VARIABLE

Temp °C	Press Atm	v_l liter/ mole	Δv liter/ mole	v_v liter/ mole	H_l cal/ mole	ΔH_v cal/ mole	H_v cal/ mole	S_l cal/ mole, °K	ΔS_v cal/ mole, °K	S_v cal/ mole, °K
60	0.2307	0.24851	123.30	123.55	6232	9029	15261	20.59	27.35	47.94
70	0.3428	0.25245	86.09	86.34	7332	8824	16156	23.85	25.94	49.79
80	0.4910	0.25691	61.28	61.54	8449	8612	17061	27.06	24.59	51.65
90	0.6824	0.26164	44.40	44.66	9585	8400	17985	30.23	23.32	53.55
100	0.9269	0.26653	32.64	32.91	10740	8179	18920	33.36	21.92	55.28
102.6	1.000	0.26779	27.99	28.26	11040	8123	19160	34.16	21.62	55.78
110	1.257	0.2722	22.72	22.99	11860	7941	19800	36.28	20.73	57.01
120	1.679	0.2794	17.16	17.44	12970	7696	20670	39.16	19.57	58.73
130	2.207	0.2875	12.95	13.24	14090	7433	21520	42.00	18.44	60.44
140	2.853	0.2964	10.12	10.42	15240	7138	22380	44.88	17.28	62.16
150	3.623	0.3051	7.933	8.238	16440	6796	23240	47.81	16.06	63.87
160	4.528	0.31570	6.2502	6.5659	17810	6405	24210	50.95	14.79	65.74

(cont'd)

TABLE III (CONT'D)

Temp °C	Press Atm	v_l liter/ mole	Δv liter/ mole	v_v liter/ mole	H_l cal/ mole	ΔH_v cal/ mole	H_v cal/ mole	S_l cal/ mole, °K	ΔS_v cal/ mole, °K	S_v cal/ mole, °K
170	5.579	0.32904	4.8928	5.2218	19010	5924	24930	53.90	13.37	67.27
180	6.799	0.34411	3.7517	4.0958	20390	5428	25820	56.93	11.98	68.91
190	8.225	0.35911	2.8799	3.2390	21790	4917	26710	59.75	10.62	70.37
200	9.887	0.37996	2.1265	2.5065	23150	4351	27500	62.59	9.196	71.79
210	11.803	0.41125	1.5100	1.9213	24640	3654	28290	65.58	7.563	73.14
220	14.053	0.46064	0.9484	1.4090	26280	2753	29030	68.79	5.582	74.37
223	14.795	0.49351	0.7059	1.1994	26800	2321	29120	69.76	4.678	74.44
225	15.318	0.52251	0.5507	1.0732	27350	1736	29090	70.79	3.485	74.28
227.06	15.861	0.70738	0	0.70738	28490	0	28490	73.09	0	73.09

TABLE IV

SATURATED PROPERTIES OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN WITH PRESSURE AS INDEPENDENT VARIABLE

Press Atm	Temp °C	v _l liter/ mole	Δv liter/ mole	v _v liter/ mole	H _l cal/ mole	ΔH _v cal/ mole	H _v cal/ mole	S _l cal/ mole, °K	ΔS _v cal/ mole, °K	S _v cal/ mole, °K
0.5	80.4	0.25712	61.56	61.82	8490	8610	17100	27.26	24.49	51.75
1.0	102.6	0.26779	27.99	28.26	11040	8120	19160	34.16	21.62	55.78
1.5	116.3	0.2761	18.94	19.22	12500	7840	20340	38.06	20.17	58.23
2.0	126.4	0.2837	14.25	14.53	13650	7560	21210	40.98	18.98	59.96
2.5	134.7	0.2907	11.46	11.75	14630	7300	21930	43.38	18.02	61.40
3.0	142.1	0.2969	9.680	9.977	15520	7060	22580	45.53	17.13	62.69
3.5	148.5	0.3032	8.053	8.356	16200	6830	23130	47.47	16.31	63.78
4.0	154.3	0.3094	7.047	7.356	17020	6630	23650	49.20	15.54	64.74
4.5	159.7	0.3156	6.372	6.688	17700	6410	24110	50.83	14.81	65.64
5.0	164.9	0.3218	5.536	5.858	18370	6190	24560	52.38	14.11	66.49
5.5	169.2	0.3281	4.986	5.314	18930	6000	24930	53.67	13.51	67.18
6.0	173.6	0.3338	4.467	4.801	19510	5800	25310	54.97	12.91	67.88
6.5	177.7	0.3395	4.001	4.341	20060	5610	25670	56.18	12.35	68.53

(cont'd)

TABLE IV (CONT'D)

Press Atm	Temp °C	v_l liter/ mole	Δv liter/ mole	v_v liter/ mole	H_l cal/ mole	ΔH_v cal/ mole	H_v cal/ mole	S_l cal/ mole, °K	ΔS_v cal/ mole, °K	S_v cal/ mole, °K
7.0	181.5	0.3452	3.601	3.946	20560	5440	26000	57.29	11.82	69.11
7.5	185.2	0.3509	3.276	3.627	21070	5230	26300	58.35	11.33	69.68
8.0	188.7	0.3565	3.007	3.364	21540	5050	26590	59.36	10.84	70.20
8.5	192.0	0.3625	2.758	3.121	22000	4860	26860	60.28	10.41	70.69
9.0	195.1	0.3686	2.520	2.889	22440	4680	27120	61.17	9.97	71.14
9.5	198.0	0.3750	2.292	2.667	22850	4500	27350	61.98	9.56	71.54
10.0	200.7	0.3815	2.049	2.431	23250	4320	27570	62.78	9.15	71.93
10.5	203.4	0.3931	1.909	2.302	23650	4140	27790	63.59	8.69	72.28
11.0	206.0	0.3999	1.773	2.173	24040	3950	27990	64.37	8.26	72.63
11.5	208.5	0.4070	1.638	2.045	24420	3760	28180	65.15	7.81	72.96
12.0	210.9	0.4149	1.503	1.918	24790	3570	28360	65.88	7.39	73.27
12.5	213.3	0.4247	1.366	1.791	25160	3380	28540	66.63	6.94	73.57
13.0	215.6	0.4350	1.229	1.664	25520	3190	28710	67.37	6.47	73.84

(Cont'd)

TABLE IV (CONT'D)

Press Atm	Temp °C	v_l liter/ mole	Δv liter/ mole	v_v liter/ mole	H_l cal/ mole	ΔH_v cal/ mole	H_v cal/ mole	S_l cal/ mole, °K	ΔS_v cal/ mole, °K	S_v cal/ mole, °K
13.5	217.8	0.4463	1.091	1.537	25890	2980	28870	68.08	6.03	74.11
14.0	219.8	0.4593	0.955	1.414	26240	2770	29010	68.73	5.58	74.31
14.5	221.9	0.4769	0.808	1.285	26630	2510	29140	69.44	5.00	74.44
15.0	223.9	0.5022	0.654	1.156	27040	2110	29150	70.19	4.22	74.41
15.5	225.7	0.5412	0.457	0.9981	27460	1530	28990	71.22	2.86	74.08
15.861	227.06	0.7074	0	0.7074	28490	0	28490	73.09	0	73.09

TABLE V

SUPERHEATED PROPERTIES OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN

H - Kcal/mole			S- cal/mole, °K	v- liters/mole			
1.0 Atmospheres (102.6)				1.5 Atmospheres (116.3)			
Temp	H	S	v	Temp	H	S	v
110	19.89	57.70	29.84				
120	20.87	60.23	30.80	120	20.74	59.17	19.90
130	21.87	62.73	31.76	130	21.72	61.81	20.60
140	22.86	65.17	32.71	140	22.74	64.38	21.30
150	23.87	67.58	33.66	150	23.74	66.90	21.99
160	24.88	69.95	34.64	160	24.80	69.09	22.71
170	25.90	72.27	35.60	170	25.84	71.48	23.40
180	26.93	74.56	36.50	180	26.86	73.80	24.04
190	27.96	76.82	37.42	190	27.91	75.98	24.69
200	29.00	79.04	38.33	200	28.94	78.21	25.33
210	30.05	81.22	39.25	210	29.98	80.37	25.97
220	31.10	83.38	40.13	220	31.06	82.54	26.59
230	32.16	85.51	41.01	230	32.10	84.68	27.18
240	33.23	87.61	41.90	240	33.18	86.86	27.80
250	34.30	89.68	42.76	250	34.26	88.65	28.39
260	35.38	91.73	43.64	260	35.34	90.94	29.00
270	36.47	93.74	44.50	270	36.45	92.96	29.59
280	37.56	95.74	45.34	280	37.54	95.01	30.18
290	38.66	97.71	46.18	290	38.64	96.99	30.74
300	39.77	99.66	47.03	300	39.74	98.89	31.32
2.0 Atmospheres (126.4)				2.5 Atmospheres (134.7)			
Temp	H	S	v	Temp	H	S	v
130	21.59	60.89	14.96				
140	22.61	63.58	15.54	140	22.48	62.78	12.04
150	23.63	66.20	16.10	150	23.50	65.49	12.53
160	24.73	68.33	16.65	160	24.63	67.70	13.07
170	25.76	70.72	17.26	170	25.70	70.14	13.55
180	26.80	73.01	17.77	180	26.74	72.49	13.98
190	27.84	75.27	18.29	190	27.78	74.69	14.43
200	28.89	77.49	18.79	200	28.83	76.91	14.73
210	29.94	79.68	19.30	210	29.88	79.09	15.28
220	31.00	81.87	19.80	220	30.96	81.30	15.69
230	32.07	84.03	20.25	230	32.00	83.48	16.06
240	33.15	86.14	20.72	240	33.10	85.65	16.45
250	34.23	88.25	21.18	250	34.17	87.70	16.83
260	35.32	90.33	21.66	260	35.28	89.85	17.23
270	36.42	92.36	22.12	270	36.38	91.87	17.62
280	37.52	94.36	22.57	280	37.49	93.89	17.99
290	38.62	96.33	23.01	290	38.59	95.89	18.35
300	39.73	98.28	23.45	300	39.68	97.79	18.72

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K				v - liters/mole			
3.0 Atmospheres (142.1)				3.5 Atmospheres (148.5)							
Temp	H	S	v	Temp	H	S	v				
150	23.38	64.79	10.12	150	23.27	64.09	8.376				
160	24.55	67.17	10.62	160	24.42	66.61	8.846				
170	25.60	69.62	11.05	170	25.50	69.10	9.243				
180	26.66	71.94	11.44	180	26.59	71.49	9.602				
190	27.71	74.22	11.83	190	27.65	73.77	9.960				
200	28.77	76.45	12.21	200	28.71	76.00	10.30				
210	29.83	78.65	12.58	210	29.76	78.20	10.63				
220	30.90	80.87	12.94	220	30.84	80.40	10.96				
230	31.98	83.06	13.25	230	31.91	82.62	11.23				
240	33.06	85.19	13.59	240	33.01	84.78	11.49				
250	34.15	87.32	13.91	250	34.09	86.90	11.82				
260	35.25	89.42	14.26	260	35.22	89.01	12.13				
270	36.36	91.46	14.60	270	36.32	91.05	12.43				
280	37.46	93.46	14.92	280	37.43	93.08	12.71				
290	38.57	95.44	15.23	290	38.53	95.10	12.99				
300	39.68	97.39	15.54	300	39.64	97.00	13.26				
4.0 Atmospheres (154.3)				4.5 Atmospheres (159.7)							
Temp	H	S	v	Temp	H	S	v				
160	24.33	66.17	7.501	170	25.26	68.19	6.793				
170	25.40	68.70	7.873	180	26.42	70.64	7.116				
180	26.60	71.07	8.211	190	27.50	73.01	7.429				
190	27.57	73.39	8.543	200	28.57	75.29	7.648				
200	28.63	75.64	8.854	210	29.63	77.50	8.002				
210	29.71	77.86	9.156	220	30.73	79.73	8.292				
220	30.79	80.10	9.517	230	31.81	81.95	8.519				
230	31.88	82.32	9.710	240	32.92	84.11	8.759				
240	32.97	84.47	9.974	250	34.00	86.30	9.002				
250	34.06	86.62	10.24	260	35.14	88.39	9.367				
260	35.17	88.73	10.53	270	36.24	90.46	9.508				
270	36.28	90.77	10.79	280	37.36	92.47	9.743				
280	37.40	92.78	11.05	290	38.47	94.47	9.974				
290	38.51	94.77	11.30	300	39.57	96.44	10.19				
300	39.62	96.72	11.54								

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K		v - liters/mole	
5.0 Atmospheres (164.9)				5.5 Atmospheres (169.2)			
Temp	H	S	v	Temp	H	S	v
170	25.17	67.83	5.917	170	24.96	67.30	5.189
180	26.31	70.30	6.228	180	26.21	69.89	5.493
190	27.41	72.67	6.527	190	27.32	72.35	5.780
200	28.49	74.99	6.804	200	28.42	74.67	6.046
210	29.58	77.21	7.068	210	29.50	76.90	6.299
220	30.67	79.46	7.350	220	30.61	79.12	6.574
230	31.77	81.70	7.561	230	31.70	81.40	6.871
240	32.87	83.87	7.784	240	32.82	83.60	6.984
250	33.97	86.03	8.010	250	33.91	85.78	7.196
260	35.08	88.15	8.257	260	35.06	87.85	7.427
270	36.20	90.21	8.475	270	36.16	89.95	7.629
280	37.32	92.23	8.692	280	37.28	91.98	7.853
290	38.44	94.22	8.910	290	38.40	93.97	8.034
300	39.56	96.18	9.110	300	39.51	95.96	8.222
6.0 Atmospheres (173.6)				6.5 Atmospheres (177.7)			
Temp	H	S	v	Temp	H	S	v
180	26.09	69.53	4.873	180	25.96	69.13	4.340
190	27.23	71.99	5.151	190	27.12	71.68	4.613
200	28.33	74.36	5.408	200	28.25	74.06	4.864
210	29.44	76.62	5.654	210	29.36	76.31	5.104
220	30.55	78.89	5.923	220	30.48	78.60	5.366
230	31.66	81.16	6.112	230	31.58	80.91	5.550
240	32.77	83.34	6.316	240	32.72	83.13	5.749
250	33.87	85.51	6.519	250	33.81	85.29	5.945
260	34.99	87.66	6.732	260	34.97	87.40	6.143
270	36.12	89.72	6.923	270	36.08	89.48	6.323
280	37.25	91.75	7.116	280	37.21	91.55	6.508
290	38.36	93.75	7.302	290	38.33	93.53	6.682
300	39.49	95.72	7.482	300	39.44	95.54	6.855

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K		v - liters/mole	
7.0 Atmospheres (181.5)				7.5 Atmospheres (185.2)			
Temp	H	S	v	Temp	H	S	v
190	27.02	71.30	4.145	190	26.90	70.93	3.734
200	28.16	73.74	4.393	200	28.06	73.45	3.981
210	29.29	76.05	4.628	210	29.20	75.76	4.212
220	30.43	78.36	4.884	220	30.35	78.10	4.463
230	31.55	80.67	5.066	230	31.49	80.45	4.647
240	32.67	82.87	5.262	240	32.61	82.68	4.839
250	33.77	85.05	5.451	250	33.71	84.81	5.020
260	34.90	87.31	5.638	260	34.88	87.02	5.200
270	36.03	89.29	5.811	270	36.00	89.05	5.369
280	37.17	91.33	5.947	280	37.13	91.16	5.535
290	38.28	93.34	6.149	290	38.25	93.16	5.690
300	39.41	95.31	6.317	300	39.37	95.15	5.851
8.0 Atmospheres (188.7)				8.5 Atmospheres (192.0)			
Temp	H	S	v	Temp	H	S	v
190	26.77	70.56	3.367	200	27.85	72.81	3.288
200	27.96	73.13	3.615	210	29.02	75.20	3.514
210	29.13	75.50	3.844	220	30.21	77.60	3.758
220	30.29	77.85	4.090	230	31.34	80.00	3.956
230	31.42	80.20	4.279	240	32.50	82.21	4.135
240	32.55	82.43	4.466	250	33.61	84.40	4.309
250	33.67	84.62	4.642	260	34.77	86.63	4.477
260	34.81	86.80	4.817	270	35.90	88.67	4.636
270	35.94	88.89	4.979	280	37.05	90.77	4.788
280	37.08	90.94	5.139	290	38.16	92.79	4.929
290	38.20	92.96	5.287	300	39.30	94.78	5.083
300	39.34	94.94	5.443				

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K		v - liters/mole	
9.0 Atmospheres (195.1)				9.5 Atmospheres (198.)			
Temp	H	S	v	Temp	H	S	v
200	27.73	72.47	2.994	200	27.61	72.11	2.727
210	28.94	74.93	3.219	210	28.83	74.61	2.952
220	30.14	77.37	3.460	220	30.06	77.10	3.190
230	31.29	79.75	3.665	230	31.22	79.57	3.402
240	32.43	82.00	3.840	240	32.37	81.79	3.575
250	33.56	84.21	4.010	250	33.50	84.00	3.742
260	34.71	86.42	4.173	260	34.66	86.27	3.904
270	35.85	88.52	4.329	270	35.80	88.30	4.053
280	37.00	90.58	4.475	280	36.97	90.39	4.194
290	38.12	92.61	4.618	290	38.09	92.43	4.336
300	39.26	94.60	4.761	300	39.23	94.43	4.472
10.0 Atmospheres (200.7)				10.5 Atmospheres (203.4)			
Temp	H	S	v	Temp	H	S	v
210	28.73	74.33	2.709	210	28.61	74.01	2.486
220	29.97	76.87	2.944	220	29.89	76.60	2.717
230	31.15	79.31	3.163	230	31.08	79.10	2.944
240	32.30	81.59	3.333	240	32.24	81.36	3.112
250	33.45	83.82	3.500	250	33.38	83.59	3.280
260	34.60	86.05	3.655	260	34.55	85.89	3.433
270	35.76	88.16	3.804	270	35.71	87.94	3.579
280	36.91	90.23	3.943	280	36.88	90.04	3.717
290	38.04	92.28	4.082	290	38.00	92.10	3.853
300	39.18	94.28	4.213	300	39.15	94.10	3.980
11.0 Atmospheres (206.0)				11.5 Atmospheres (208.5)			
Temp	H	S	v	Temp	H	S	v
210	28.49	73.70	2.280	210	28.37	73.35	2.091
220	29.78	76.35	2.513	220	29.69	76.09	2.321
230	30.99	78.85	2.742	230	30.92	78.65	2.553
240	32.17	81.17	2.911	240	32.10	80.95	2.726
250	33.32	83.43	3.080	250	33.25	83.20	2.895
260	34.50	85.69	3.229	260	34.44	85.53	3.044
270	35.66	87.82	3.373	270	35.61	87.60	3.186
280	36.82	89.90	3.511	280	36.79	89.73	3.323
290	37.95	91.96	3.645	290	37.92	91.79	3.454
300	39.10	93.98	3.768	300	39.08	93.80	3.574

(cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K		v - liters/mole	
12.0 Atmospheres (210.9)				12.5 Atmospheres (213.3)			
Temp	H	S	v	Temp	H	S	v
210	28.22	73.01	1.915				
220	29.57	75.79	2.142	220	29.46	75.50	1.977
230	30.82	78.37	2.377	230	30.73	78.19	2.211
240	32.02	80.76	2.554	240	31.95	80.51	2.397
250	33.20	83.06	2.726	250	33.11	82.81	2.569
260	34.38	85.34	2.874	260	34.32	85.19	2.717
270	35.56	87.49	3.014	270	35.51	87.25	2.856
280	36.72	89.58	3.151	280	36.69	89.41	2.991
290	37.86	91.65	3.278	290	37.83	91.49	3.116
300	39.01	93.69	3.396	300	38.99	93.52	3.233
13.0 Atmospheres (215.6)				13.5 Atmospheres (217.8)			
Temp	H	S	v	Temp	H	S	v
220	29.33	75.19	1.823				
230	30.63	77.99	2.052	230	30.51	77.63	1.896
240	31.86	80.33	2.250	240	31.77	80.10	2.113
250	33.06	82.68	2.424	250	32.99	82.48	2.289
260	34.27	85.00	2.572	260	34.20	84.83	2.438
270	35.45	87.16	2.709	270	35.39	86.91	2.574
280	36.63	89.27	2.846	280	36.59	89.10	2.708
290	37.77	91.36	2.967	290	37.74	91.21	2.828
300	38.93	93.41	3.082	300	38.90	93.26	2.942
14.0 Atmospheres (219.8)				14.5 Atmospheres (221.9)			
Temp	H	S	v	Temp	H	S	v
230	30.40	77.34	1.745	230	30.25	77.00	1.596
240	31.68	79.88	1.986	240	31.58	79.61	1.866
250	32.91	82.29	2.162	250	32.83	82.10	2.045
260	34.14	84.65	2.312	260	34.06	84.49	2.195
270	35.34	86.83	2.448	270	35.28	86.61	2.330
280	36.53	88.97	2.581	280	36.48	88.80	2.463
290	37.68	91.07	2.700	290	37.64	91.93	2.581
300	38.84	93.13	2.812	300	38.81	92.99	2.690

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K				v - liters/mole			
15.0 Atmospheres (223.9)				15.5 Atmospheres (225.7)							
Temp	H	S	v	Temp	H	S	v				
230	30.08	76.63	1.450	230	29.80	76.07	1.288				
240	31.46	79.37	1.724	240	31.33	79.08	1.596				
250	32.76	81.89	1.936	250	32.67	81.70	1.829				
260	34.01	84.31	2.081	260	33.93	84.13	1.980				
270	35.23	86.51	2.222	270	35.16	86.32	2.115				
280	36.42	88.68	2.354	280	36.38	88.51	2.250				
290	37.58	90.79	2.470	290	37.54	90.65	2.361				
300	38.75	92.87	2.576	300	38.72	92.71	2.476				
16.0 Atmospheres				16.5 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	29.61	76.16	1.106	230	29.43	75.95	0.866				
240	31.18	78.86	1.470	240	31.02	78.62	1.344				
250	32.58	81.47	1.727	250	32.47	81.28	1.630				
260	33.87	83.96	1.883	260	33.80	83.78	1.793				
270	35.11	86.20	2.017	270	35.04	86.02	1.921				
280	36.32	88.39	2.152	280	36.27	88.22	2.055				
290	37.48	90.52	2.262	290	37.43	90.38	2.167				
300	38.66	92.61	2.371	300	38.60	92.45	2.285				
17.0 Atmospheres				17.5 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	29.27	75.76	0.582	230	29.12	75.58	0.526				
240	30.87	78.41	1.224	240	30.73	78.20	1.110				
250	32.37	81.10	1.536	250	32.27	80.92	1.447				
260	33.73	83.60	1.706	260	33.66	83.42	1.623				
270	34.99	85.89	1.829	270	34.92	85.72	1.749				
280	36.21	88.10	1.965	280	36.16	87.94	1.880				
290	37.38	90.24	2.076	290	37.32	90.09	1.993				
300	38.56	92.34	2.188	300	38.51	92.19	2.111				
18.0 Atmospheres				18.5 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	28.99	75.41	0.502	230	28.90	75.18	0.483				
240	30.61	78.00	1.004	240	30.49	77.79	0.902				
250	32.16	80.77	1.361	250	32.05	80.60	1.277				
260	33.59	83.24	1.545	260	33.52	83.09	1.469				
270	34.87	85.58	1.670	270	34.79	85.44	1.593				
280	36.10	87.81	1.799	280	36.04	87.64	1.723				
290	37.28	89.97	1.912	290	37.21	89.80	1.838				
300	38.46	92.08	2.027	300	38.40	91.91	1.952				

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K				v - liters/mole			
19.0 Atmospheres				19.5 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	28.81	74.93	0.470	230	28.73	74.71	0.464				
240	30.39	77.58	0.805	240	30.30	77.37	0.715				
250	31.95	80.44	1.192	250	31.86	80.28	1.106				
260	33.45	82.92	1.396	260	33.38	82.78	1.324				
270	34.74	85.28	1.530	270	34.66	85.12	1.455				
280	35.98	87.53	1.650	280	35.92	87.37	1.583				
290	37.17	89.70	1.766	290	37.11	89.53	1.699				
300	38.36	91.82	1.876	300	38.30	91.65	1.811				
20 Atmospheres				21 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	28.65	74.50	0.459	230	28.49	74.09	0.446				
240	30.21	77.14	0.644	240	30.04	76.75	0.559				
250	31.76	80.11	1.022	250	31.58	79.75	0.869				
260	33.31	82.60	1.256	260	33.15	82.28	1.123				
270	34.61	84.98	1.392	270	34.47	84.66	1.274				
280	35.86	87.24	1.517	280	35.73	86.95	1.397				
290	37.05	89.43	1.636	290	36.94	89.16	1.520				
300	38.25	91.56	1.745	300	38.14	91.30	1.626				
22 Atmospheres				23 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	28.35	73.70	0.440	230	28.22	73.33	0.434				
240	29.88	76.38	0.531	240	29.73	76.03	0.512				
250	31.41	79.33	0.746	250	31.26	78.95	0.663				
260	32.98	81.92	0.996	260	32.81	81.54	0.889				
270	34.32	84.32	1.163	270	34.16	83.97	1.059				
280	35.60	86.46	1.288	280	35.47	86.17	1.194				
290	36.82	88.88	1.409	290	36.70	88.60	1.306				
300	38.02	91.03	1.518	300	37.91	90.76	1.421				
24 Atmospheres				25 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	28.09	72.99	0.430	230	27.98	72.68	0.425				
240	29.59	75.71	0.496	240	29.47	75.40	0.481				
250	31.10	78.59	0.605	250	30.96	78.27	0.564				
260	32.62	81.17	0.799	260	32.43	80.82	0.726				
270	34.00	83.63	0.964	270	33.84	83.28	0.890				
280	35.33	85.88	1.095	280	35.20	85.58	1.020				
290	36.57	88.32	1.214	290	36.44	88.04	1.133				
300	37.79	90.49	1.329	300	37.66	90.22	1.250				

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K		v - liters/mole	
26 Atmospheres				27 Atmospheres			
Temp	H	S	v	Temp	H	S	v
230	27.88	72.36	0.421	230	27.79	72.08	0.417
240	29.33	75.12	0.468	240	29.22	74.86	0.458
250	30.83	77.93	0.535	250	30.71	77.63	0.520
260	32.27	80.50	0.671	260	32.12	80.21	0.628
270	33.67	82.94	0.823	270	33.52	82.60	0.767
280	35.06	85.29	0.948	280	34.92	85.00	0.891
290	36.31	87.76	1.061	290	36.18	87.49	0.999
300	37.54	89.95	1.176	300	37.41	89.68	1.113
28 Atmospheres				29 Atmospheres			
Temp	H	S	v	Temp	H	S	v
230	27.70	71.82	0.414	230	27.61	71.59	0.410
240	29.10	74.61	0.448	240	29.00	74.38	0.440
250	30.59	77.37	0.508	250	30.47	77.09	0.495
260	31.99	79.93	0.595	260	31.86	79.66	0.568
270	33.36	82.28	0.718	270	33.21	81.98	0.677
280	34.79	84.72	0.842	280	34.66	84.44	0.793
290	36.05	87.22	0.950	290	35.93	86.95	0.903
300	37.29	89.42	1.061	300	37.16	89.16	1.010
30 Atmospheres				31 Atmospheres			
Temp	H	S	v	Temp	H	S	v
230	27.54	71.39	0.408	230	27.48	71.21	0.405
240	28.90	74.15	0.438	240	28.82	73.93	0.432
250	30.37	76.81	0.484	250	30.24	76.57	0.482
260	31.74	79.39	0.550	260	31.64	79.14	0.536
270	33.08	81.71	0.644	270	32.97	81.48	0.615
280	34.53	84.18	0.750	280	34.40	83.94	0.711
290	35.80	86.69	0.858	290	35.68	86.44	0.817
300	37.04	88.90	0.963	300	36.92	88.64	0.918
32 Atmospheres				33 Atmospheres			
Temp	H	S	v	Temp	H	S	v
230	27.42	71.05	0.402	230	27.37	70.92	0.404
240	28.75	73.74	0.428	240	28.69	73.54	0.429
250	30.20	76.34	0.473	250	30.12	76.18	0.465
260	31.55	78.90	0.520	260	31.47	78.71	0.505
270	32.88	81.28	0.591	270	32.79	81.10	0.572
280	34.29	83.71	0.680	280	34.19	83.50	0.653
290	35.56	86.19	0.774	290	35.45	85.96	0.736
300	36.81	88.39	0.874	300	36.70	88.15	0.831

(Cont'd)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K				v - liters/mole			
34 Atmospheres				35 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	27.33	70.81	0.405	230	27.30	70.69	0.405				
240	28.64	73.40	0.430	240	28.60	73.28	0.428				
250	30.06	76.01	0.458	250	30.00	75.99	0.455				
260	31.39	78.54	0.492	260	31.33	78.39	0.481				
270	32.71	80.93	0.556	270	32.64	80.77	0.541				
280	34.10	83.31	0.629	280	34.01	83.13	0.611				
290	35.35	85.75	0.709	290	35.26	85.56	0.685				
300	36.60	87.92	0.792	300	36.51	87.71	0.759				
36 Atmospheres				37 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	27.26	70.58	0.403	230	27.24	70.49	0.400				
240	28.56	73.15	0.426	240	28.53	73.06	0.422				
250	29.95	75.76	0.449	250	29.90	75.62	0.444				
260	31.26	78.23	0.471	260	31.20	78.10	0.466				
270	32.57	80.63	0.526	270	32.52	80.51	0.514				
280	33.93	82.96	0.593	280	33.86	82.81	0.576				
290	35.17	85.37	0.663	290	35.09	85.21	0.643				
300	36.42	87.52	0.733	300	36.34	87.35	0.708				
38 Atmospheres				39 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	27.22	70.40	0.397	230	27.20	70.31	0.394				
240	28.50	72.97	0.418	240	28.48	72.90	0.415				
250	29.85	75.51	0.440	250	29.81	75.42	0.436				
260	31.15	77.99	0.461	260	31.10	77.88	0.458				
270	32.46	80.38	0.504	270	32.41	80.27	0.515				
280	33.80	82.66	0.563	280	33.73	82.53	0.549				
290	35.02	85.05	0.624	290	34.95	84.91	0.607				
300	36.26	87.18	0.687	300	36.19	87.03	0.666				
40 Atmospheres				41 Atmospheres							
Temp	H	S	v	Temp	H	S	v				
230	27.18	70.26	0.329	230	27.16	70.21	0.391				
240	28.46	72.82	0.413	240	28.44	72.78	0.411				
250	29.77	75.37	0.433	250	29.73	75.29	0.431				
260	31.05	77.78	0.454	260	31.01	77.68	0.451				
270	32.37	80.17	0.487	270	32.33	80.77	0.481				
280	33.68	82.40	0.537	280	33.63	82.29	0.527				
290	34.89	84.77	0.591	290	34.83	84.64	0.577				
300	36.12	86.88	0.649	300	36.06	86.74	0.632				

(Continued)

TABLE V (CONT'D)

H - Kcal/mole				S - cal/mole, °K		v - liters/mole	
42 Atmospheres				43 Atmospheres			
Temp	H	S	v	Temp	H	S	v
230	27.15	70.18	0.388	230	27.14	70.12	0.384
240	28.43	72.70	0.408	240	28.42	72.66	0.403
250	29.69	75.21	0.427	250	29.66	75.18	0.422
260	30.97	77.59	0.447	260	30.93	77.51	0.441
270	32.29	79.98	0.477	270	32.25	79.90	0.474
280	33.58	82.18	0.519	280	33.54	82.08	0.512
290	34.78	84.52	0.564	290	34.73	84.40	0.554
300	36.00	86.61	0.617	300	35.94	86.48	0.603
44 Atmospheres							
Temp	H	S	v				
230	27.14	70.10	0.380				
240	28.41	72.61	0.398				
250	29.64	75.13	0.417				
260	30.90	77.47	0.435				
270	32.22	79.81	0.471				
280	33.50	81.99	0.505				
290	34.68	84.30	0.543				
300	35.89	86.37	0.590				

TABLE VI

ACTIVITY COEFFICIENTS FOR PERFLUORO-2-BUTYL-TETRAHYDROFURAN

Press Atm	110 °C	120 °C	130 °C	140 °C	150 °C
0	1.0000	1.0000	1.0000	1.0000	1.0000
1	0.9560	0.9600	0.9650	0.9689	0.9729
2	0.9033	0.9134	0.9235	0.9324	0.9408
3			0.8771	0.8915	0.9055
4					0.8653

(Cont'd)

TABLE VI (CONT'D)

Press Atm	160 °C	170 °C	180 °C	190 °C	200 °C
0	1.0000	1.0000	1.0000	1.0000	1.0000
1	0.9771	0.9813	0.9836	0.9863	0.9889
2	0.9503	0.9588	0.9638	0.9696	0.9747
3	0.9199	0.9328	0.9409	0.9500	0.9578
4	0.8866	0.9039	0.9154	0.9278	0.9384
5	0.8510	0.8724	0.8876	0.9033	0.9167
6		0.8390	0.8579	0.8768	0.8931
7			0.8266	0.8488	0.8679
8				0.8195	0.8416
9					0.8143
10					0.7862

(Cont'd)

TABLE VI (CONT'D)

Press Atm	210 °C	220 °C	230 °C	240 °C	250 °C
0	1.0000	1.0000	1.0000	1.0000	1.0000
1	0.9916	0.9931	0.9946	0.9964	0.9976
2	0.9801	0.9836	0.9864	0.9899	0.9922
3	0.9658	0.9715	0.9755	0.9807	0.9843
4	0.9489	0.9571	0.9623	0.9691	0.9740
5	0.9298	0.9407	0.9472	0.9554	0.9619
6	0.9087	0.9227	0.9304	0.9403	0.9484
7	0.8862	0.9033	0.9126	0.9242	0.9339
8	0.8625	0.8835	0.8938	0.9069	0.9187
9	0.8378	0.8611	0.8745	0.8894	0.9030
10	0.8124	0.8386	0.8547	0.8715	0.8868
11	0.7864	0.8154	0.8345	0.8531	0.8703
12	0.7600	0.7916	0.8138	0.8343	0.8534
13		0.7673	0.7925	0.8153	0.8364
14			0.7705	0.7961	0.8192
15			0.7475	0.7767	0.8020
16			0.7229	0.7570	0.7847
17			0.6944	0.7356	0.7671
18			0.6643	0.7134	0.7493
19			0.6368	0.6905	0.7313
20			0.6118	0.6673	0.7129
21			0.5891	0.6445	0.6940
22			0.5684	0.6232	0.6750

(cont'd)

TABLE VI (CONT'D)

Press Atm	210 °C cont'd	220 °C cont'd	230 °C cont'd	240 °C cont'd	250 °C cont'd
23			0.5494	0.6036	0.6563
24			0.5321	0.5854	0.6383
25			0.5161	0.5685	0.6211
26			0.5014	0.5529	0.6049
27			0.4877	0.5383	0.5897
28			0.4751	0.5247	0.5755
29			0.4633	0.5119	0.5622
30			0.4523	0.5001	0.5497
31			0.4419	0.4889	0.5381
32			0.4323	0.4785	0.5271
33			0.4230	0.4688	0.5167
34			0.4149	0.4596	0.5069
35			0.4070	0.4511	0.4977
36			0.3996	0.4430	0.4890
37			0.3926	0.4354	0.4807
38			0.3860	0.4282	0.4729
39			0.3797	0.4214	0.4655
40			0.3737	0.4149	0.4585
41			0.3681	0.4087	0.4518
42			0.3627	0.4029	0.4455
43			0.3576	0.3973	0.4395
44			0.3527	0.3920	0.4337

(Cont'd)

TABLE VI (CONT'D)

Press Atm	260 °C	270 °C	280 °C	290 °C	300 °C
0	1.0000	1.0000	1.0000	1.0000	1.0000
1	0.9986	0.9991	0.9993	0.9996	0.9999
2	0.9947	0.9964	0.9973	0.9982	0.9993
3	0.9886	0.9917	0.9938	0.9953	0.9972
4	0.9803	0.9849	0.9882	0.9907	0.9934
5	0.9702	0.9761	0.9808	0.9844	0.9880
6	0.9586	0.9658	0.9718	0.9766	0.9811
7	0.9458	0.9543	0.9617	0.9676	0.9732
8	0.9322	0.9417	0.9508	0.9578	0.9646
9	0.9180	0.9289	0.9393	0.9474	0.9554
10	0.9034	0.9157	0.9272	0.9366	0.9457
11	0.8884	0.9022	0.9150	0.9256	0.9357
12	0.8731	0.8883	0.9025	0.9143	0.9255
13	0.8576	0.8743	0.8899	0.9029	0.9152
14	0.8420	0.8602	0.8771	0.8914	0.9047
15	0.8262	0.8459	0.8643	0.8798	0.8941
16	0.8104	0.8316	0.8515	0.8681	0.8835
17	0.7947	0.8172	0.8385	0.8563	0.8729
18	0.7789	0.8027	0.8255	0.8444	0.8623
19	0.7631	0.7881	0.8123	0.8324	0.8515
20	0.7472	0.7736	0.7990	0.8204	0.8407
21	0.7313	0.7591	0.7858	0.8079	0.8299
22	0.7151	0.7446	0.7726	0.7965	0.8190

(Cont'd)

TABLE VI (CONT'D)

Press Atm	260 °C cont'd	270 °C cont'd	280 °C cont'd	290 °C cont'd	300 °C cont'd
23	0.6989	0.7302	0.7594	0.7845	0.8082
24	0.6828	0.7159	0.7465	0.7726	0.7975
25	0.6670	0.7017	0.7337	0.7608	0.7868
26	0.6516	0.6877	0.7211	0.7491	0.7763
27	0.6369	0.6742	0.7088	0.7375	0.7659
28	0.6227	0.6610	0.6967	0.7263	0.7558
29	0.6093	0.6483	0.6849	0.7153	0.7459
30	0.5966	0.6360	0.6734	0.7046	0.7363
31	0.5846	0.6242	0.6623	0.6942	0.7269
32	0.5732	0.6130	0.6515	0.6840	0.7176
33	0.5624	0.6022	0.6411	0.6742	0.7085
34	0.5521	0.5919	0.6311	0.6647	0.6995
35	0.5423	0.5821	0.6215	0.6555	0.6908
36	0.5330	0.5728	0.6123	0.6467	0.6823
37	0.5242	0.5638	0.6034	0.6381	0.6742
38	0.5158	0.5553	0.5950	0.6299	0.6662
39	0.5079	0.5472	0.5869	0.6220	0.6585
40	0.5004	0.5394	0.5791	0.6143	0.6511
41	0.4932	0.5320	0.5716	0.6070	0.6439
42	0.4865	0.5249	0.5645	0.5999	0.6370
43	0.4800	0.5182	0.5576	0.5931	0.6303
44	0.4738	0.5118	0.5511	0.5865	0.6239

FIGURE 5
ACTIVITY COEFFICIENTS

FIGURE 6
PRESSURE-ENTHALPY CHART
for
PERFLUORO-2-BUTYL-TETRAHYDROFURAN

FIGURE 6

PRESSURE - ENTHALPY CHART
 FOR
 PERFLUORO-2-BUTYL-TETRAHYDROFURAN

PRESSURE - ATMOSPHERES
 ENTHALPY - KCAL / MOLE
 TEMPERATURE - °C
 ENTROPY - CAL / MOLE, °K
 VOLUME - CC / GR

VII. DISCUSSION OF RESULTS

The calculated results appear satisfactory, at least as far as can be judged by applying the usual criteria of thermodynamic consistency.

The vapor pressure data were checked against values calculated by the vapor pressure equation, $\log P_c = A + B/T$. The deviations of the experimental pressures, P , from those calculated from the vapor pressure equation, P_c , are graphically illustrated in Figure 7. The data below 102.6°C do not agree particularly well with the data above 102.6°C , but these data were reported on a different sample. Fortunately, these vapor pressures were not used in any of the calculations. The rest of the data fall on a smooth curve and this is considered to be an adequate indication of consistency.

The latent heats listed in Table III were calculated using the vapor pressure equation, $\log P_c = A + B/T$, along with the graphically determined slopes of the deviation curve in Figure 7.

To check the reliability of the values it was considered desirable to calculate the latent heats analytically. This was done using the vapor pressure equation, $\log P_c = A + B/T + C \log T$, above 160°C . The equation fit

FIGURE 7
DEVIATION PLOT, $P_c - P$

FIGURE 7
DEVIATION PLOT
 $P_c - P$

the data in this region with an average deviation of $\pm 0.13\%$ when the following constants were used:

$$A = -7.64326$$

$$B = -955.03$$

$$C = 3.9838.$$

The latent heats were calculated from the Clausius-Clapeyron equation in conjunction with the vapor pressure equation, $\log P_c = A + B/T + C \log T$, which gave the following equation:

$$\Delta H_v = 24.206 [-2.303BP/T + CP] \Delta v.$$

Experimental vapor volumes were used in the calculation; the results are listed in Table VII along with the latent heats previously calculated. The two methods check within $\pm 0.8\%$ and serve to justify the use of the deviation curve for this calculation. A further indication of the reliability of the latent heats was demonstrated when results were plotted against temperature on a large plot, which showed that the points fell on a smooth curve.

The method used to calculate the enthalpy of the saturated liquid above 102.6°C has been described. These values could have been calculated by assuming that the heat capacity of the liquid at one atmosphere was equal to the saturated heat capacity for temperatures up to the critical. This would be assuming that the effect of pressure on the liquid heat capacity was small and that the term, $-T(\partial v/\partial T)_p dP/dT$, was small for all temperatures.

TABLE VII

COMPARISON OF LATENT HEATS CALCULATED BY TWO METHODS

Temp °C	ΔH_Y^* cal/mole	ΔH_Y^{**} cal/mole	Per Cent Difference
170	5912	5924	0.20
180	5457	5428	-0.53
190	5007	4917	-1.18
200	4393	4351	-0.97
210	3683	3654	-0.80
220	2724	2753	1.05

*Determined using the equation, $\log P_c = A + B/T + C \log T$.

**Determined using the equation, $\log P_c = A + B/T$ plus the slope of the deviation curve.

This last term arises from the difference between the saturated heat capacity, C_p^{sat} , and the heat capacity at constant pressure, C_p . This last term is insignificant at low temperatures but becomes very large near the critical. A comparison is made in Table VIII of the liquid enthalpies calculated by the two methods; the one previously demonstrated, the other from the equation,

$$H_1 = \int_{T=273.16}^T C_{p1}^1 dT = 50.75(T-273.16) + 0.0876(T^2-273.16^2).$$

As was expected, the results at the critical temperature showed the poorest agreement; amounting to 5.6%. The average deviation of the other results, excluding the value

TABLE VIII

SATURATED LIQUID ENTHALPIES CALCULATED BY TWO METHODS

Temp °C	H _l * cal/mole	H _l ** cal/mole	Per Cent Difference
110	11910	11860	-0.42
120	13090	12970	-0.93
130	14300	14090	-1.49
140	15520	15240	-1.84
150	16760	16440	-1.95
160	18020	17810	-1.18
170	19300	19010	-1.52
180	20590	20390	-1.47
190	21900	21790	-0.50
200	23230	23150	-0.35
210	24570	24640	0.28
220	25930	26280	1.33
227.06	26910	28490	5.55

*Calculated from the heat capacity of the liquid at one atmosphere.

**Calculated by subtracting the latent heats from the enthalpy of the saturated vapor.

the value at the critical, was $\pm 1.1\%$. The percentage deviation between the methods shows a definite regularity for all values except those at 160°C. A discrepancy occurs at this temperature because the extrapolation of the saturated vapor enthalpies from the higher temperatures to 102.6°C did not pass through the data at 160°C, the lowest temperature for which experimental P-V-T data were available. Considering that this comparison is influenced by errors, (1) in determining the heat capacity of the liquid, (2) in determining the heat capacity of the vapor, (3) in

calculating the effect of pressure on the enthalpy, which in itself involves errors in determining the P-V-T data for the superheated vapor plus errors in determining the slopes, $(\partial \alpha / \partial T)_P$, and (4) in calculating the latent heats, the results agree better than would be expected. The consistency of the data in the superheated region depend almost entirely on the precision with which the slopes, $(\partial \alpha / \partial T)_P$, are determined. Since $(\partial v / \partial T)_P = R/P - (\partial \alpha / \partial T)_P$, the precision of $(\partial v / \partial T)_P$ varies depending on the magnitude of R/P and $(\partial \alpha / \partial T)_P$. In the low pressure and high temperature region, the gas is more ideal and thus $(\partial \alpha / \partial T)_P$ is only a small part of $(\partial v / \partial T)_P$ so that the error in determining the former does not seriously affect the latter. However, near the critical region, errors in $(\partial \alpha / \partial T)_P$ greatly affect $(\partial v / \partial T)_P$ so that a one percent error in the former would cause about a one percent error in the latter. For this reason, the method of cross plotting the enthalpy and entropy to determine these values at 230, 240 and 250°C for pressures above 15 atmospheres, was justified for the reason that the values at these temperatures were forced to conform to the values determined at higher temperatures which were more precise.

The over-all consistency of the calculated results is demonstrated by the pressure-enthalpy chart in Figure 6. The regularity of the properties with changing temperature and pressure is apparent.

The data available on the physical properties of other fluorocarbons of similar molecular weight are listed in Table IX along with the same properties of $C_8F_{16}O$. The entropy of vaporization at one atmosphere, ΔS_v^1 , for C_6F_{14} was calculated by Stiles and Cady assuming the vapor to be ideal. For $C_8F_{16}O$, the compressibility factor for the saturated vapor volume at one atmosphere is 0.91. Applying a similar compressibility factor to C_6F_{14} would lower the value of ΔS_v^1 to below 21 and would bring these data more in line with the other values. The critical pressure of C_7F_{16} is higher than that of $C_8F_{16}O$, which is surprising considering the higher molecular weight of the latter. Except for these discrepancies, the properties are in general agreement.

TABLE IX
COMPARISON OF PHYSICAL PROPERTIES OF PERFLUORO-2-BUTYL-
TETRAHYDROFURAN WITH OTHER FLUOROCARBONS OF SIMILAR
MOLECULAR WEIGHT

Compound	MW	BP °C	ΔH_V^l cal/mole	ΔS_V^l cal/mole°K	$C_{pl}@25^\circ C$ cal/gr, °C	T_c °C	P_c atm
$C_8F_{16}^O$	416.1	102.6	8123	21.62	0.248	227.06	15.861
$C_7F_{16}^*$	388.1	82.50	7543	21.21	0.253	201.7	16.0
$C_6F_{14}^{**}$	338.1	57.23	7307***	22.12			
$C_5F_{11}-CF_3^{**}$	338.1	57.74	7273***	21.98			

*Data by Oliver and Grisard, J. Am. Chem. Soc., 73, 1688 (1951).

**Data by Stiles and Cady, J. Am. Chem. Soc., 74, 3771 (1952).

***Calculated assuming vapor volume to be ideal.

VIII. CONCLUSIONS

The internal consistency of the results, as demonstrated by comparing the liquid enthalpies calculated by two different procedures, is about $\pm 1.1\%$. This value is of the same magnitude as the precision in determining the physical properties, especially the heat capacities. Therefore, the methods used to calculate these properties, which required graphical procedures in some instances, have utilized the data to advantage. Although the absolute accuracy of the results has not been established, this should not impose serious limitations on the use of the data for engineering calculations where differences in the thermodynamic functions are involved rather than absolute values. Thus, the data can be used for calculations involving cyclic processes operating within the range of the pressure and temperature for which the data are presented, but cannot be used for thermochemical calculations where absolute values are needed. Since fluorocarbons are chemically inert, this latter restriction is of little consequence.

The use of the deviation plot to calculate the latent heats gave results which compared favorably (average deviation, $\pm 0.8\%$) with those calculated using the vapor equation, $\log P = A + B/T + C \log T$, at the higher

temperatures. This close agreement establishes the reliability of the procedure used to calculate the latent heats.

The comparison of the enthalpies of the saturated liquid calculated by subtracting the latent heat from the saturated vapor enthalpy with those values calculated by integration, using the liquid heat capacities at one atmosphere extended to the critical, shows an average deviation of $\pm 1.1\%$. Considering that this comparison reflects on the precision of most of the physical properties involved in the calculations, this deviation is surprisingly small.

The reliability of the results in the superheated region was demonstrated by the regularity of the data when plotted on a large scale in the pressure-enthalpy chart. The precision of the results in this region depends largely upon the precision with which the slopes, $(\partial\alpha/\partial T)_P$, were determined from the α versus T plots. The consistency of these slopes was established by the regularity shown in the subsequent plots of the terms $[T(\partial\alpha/\partial T)_P - \alpha]_T$ and $[R/P - (\partial\alpha/\partial T)_P]_T$ versus pressure. Any error in the heat capacity of the vapor would cause the same error in the enthalpy and entropy. Therefore, the conclusions regarding the vapor heat capacity apply equally to the superheated enthalpy and entropy. Since the vapor heat capacity was determined with a precision of $\pm 1.3\%$, these functions in

the superheated region can be no more precise than this and, like the heat capacity, become more uncertain above 250°C.

Although it was regrettable that $C_8F_{16}^O$ was not a single compound, the differences in the isomers, the pyran and the furan form, are small as was indicated by the small differences in the dew and bubble points (maximum difference, 3.3 psi). It can be assumed that the properties reported apply with equal precision to either isomer.

No definite conclusions can be drawn about fluorocarbons similar to $C_8F_{16}^O$ from the small amount of data available. The physical properties tend to change with molecular weight as do all other compounds. The discrepancy in the entropy of vaporization of C_6F_{14} as reported by Stiles and Cady³ was pointed out and the correction to be applied would bring this property into line with the others. The critical pressure of C_7F_{16} was slightly higher than that of $C_8F_{16}^O$. Otherwise, the comparison shows no striking anomalies in the properties of $C_8F_{16}^O$.

This cyclic ether exhibits some of the criteria of a good refrigerant in that it is stable, non-corrosive, and that the entropy of the saturated vapor changes with temperature in such a manner that the vapor is easily compressed into the two phase region. The operating temperatures of any refrigeration cycle employing $C_8F_{16}^O$

should be below 227°C , its critical temperature. The low vapor pressure of $\text{C}_8\text{F}_{16}\text{O}$ would be detrimental to its use as a low temperature refrigerant as pressures below atmospheric would have to be maintained on the low temperature side of the cycle. The latent heat of $\text{C}_8\text{F}_{16}\text{O}$ is approximately half that of the fluoro-chloro-hydrocarbons which would necessitate the use of large amounts of refrigerant. Any further comparison must be made by calculations where $\text{C}_8\text{F}_{16}\text{O}$ is used in the same cycle as the other refrigerant under consideration.

For such calculations where $\text{C}_8\text{F}_{16}\text{O}$ may be used either as a refrigerant or a coolant for electrical equipment, the data presented here are of sufficient precision to serve as a basis for sound engineering decisions.

IX. RECOMMENDATIONS

One of the difficulties encountered in this work was that the data for the vapor volumes could not be fitted to an equation of state. An equation of state for compounds similar to $\text{C}_8\text{F}_{16}\text{O}$ would necessarily be complex due to the large curvature of the isometrics that would have to be accounted for by the equation. However, it is not really necessary to find an equation of state that will fit all the data. It is essential to find an equation, especially one explicit in volume, such as the Linde equation, which will at least fit the data in a narrow region accurately. With the high speed digital computer, the constants can be solved as many times as necessary to cover the entire range. Such a program would necessitate punching the P-V-T data into cards and arranging the program to give the integrals $\int (\partial H / \partial P)_T dP$ and $\int (\partial S / \partial P)_T dP$ for the narrow regions. Since these integrals are now complete for $\text{C}_8\text{F}_{16}\text{O}$ (determined graphically in this paper), a check on the method would be available. Such a program could be made general enough to be used for any compound and would eliminate the need to use more complex equations of state.

One weakness of this work lies in the poor precision with which the heat capacities were determined, especially the vapor heat capacities. Two ways in which the flow

calorimeter could be improved are to use a different type of vaporizer to assure more even flow rates. Such a vaporizer might be made by allowing the liquid to evaporate from a wick made of asbestos heating tape. The other possible improvement would be the use of platinum or nickel resistance thermometers to measure the temperature rise.

Although the velocity of sound method involves some uncertainties as to the effect of frequency on the determination, it does have the advantage that only a small sample is required. For example, for $\text{C}_8\text{F}_{16}\text{O}$, 10 grams would fill a 1 liter Kundt's tube. This method for vapors and the isentropic expansion method for liquids might solve the problems arising from the need to use small samples of fluorocarbons.

APPENDIX A

DETAILS ON THE CONSTRUCTION OF THE FLOW CALORIMETER

The information in this section is a supplement to that presented in the main body of the thesis. Details concerning the baths, the temperature controllers, the reboiler, the calorimeter, and the electrical set-up are discussed.

The liquid medium used in the baths was "Aroclor 1248," a tetrachloro-biphenyl heat transfer media manufactured by the Monsanto Chemical Company. This liquid was stable and non-volatile to temperatures above 300°C. However, it was irritating to the skin and therefore, the box surrounding the baths was vented to the hood.

The two baths were heated and stirred in a similar manner. Stirring was provided by a Cenco variable speed, cone drive stirring motor mounted on top of the box. The stirring blades could be set at any desired depth and were pitched to give an upward circulation to the bath liquid. The stirrers provided adequate agitation even at room temperature where the "Aroclor" was rather viscous.

Each bath contained one control and one continuous heater. These were made by stretching 26 gage Nichrome wire between transite disks spaced on a 5/16 inch, threaded steel rod. The heaters had a resistance of about 25 ohms and were connected to the line or controller through a

"Variac" transformer. Having the bare Nichrome wire exposed to the liquid reduced the time-lag characteristic of commercial immersion heaters.

The temperature of the reboiler bath was maintained throughout the experiment at the boiling temperature of the fluid being studied. Temperature control was provided by a mercury regulator. The sensing element was essentially a thermometer with a capacity of 100 cc. of Hg. Extra surface was provided by having the mercury in three legs. The stem was a fine capillary tube with a 0.7 mm. bore. The control element was a "Thermocap Relay" made by the Niagara Electron Laboratories. This instrument is sensitive to minute changes in electrical capacities such as when a column of mercury rises in the stem of a thermometer. A copper clip was placed on the stem of the capillary tube at the control point and was connected to the relay. This provided control to within $\pm 0.03^{\circ}\text{C}$ of the control point.

The temperature of the calorimeter bath was controlled to about $\pm 0.005^{\circ}\text{C}$ up to 220°C by an electronic control. The "Thermotrol" controller manufactured by Hallikainen Instruments was used as an on-off controller although it has proportional and proportional plus reset controls available. This controller uses an AC Wheatstone bridge with a resistance thermometer detector as the variable arm of the bridge. The bridge is operated at

balance using an adjustable ratio arm to select the temperature setting. A change in resistance produces an AC voltage which is amplified by a resistance coupled amplifier. This amplified AC voltage is then applied as a bias voltage to a thyratron tube which controls an enclosed mercury switch, turning the heater on and off. The resistance thermometer Model 1080A was used as the sensing element. Above 220°C a mercury controller similar to that previously described was used. Bath temperatures were determined by a Leeds and Northrup platinum resistance thermometer in conjunction with a Mueller bridge.

The reboiler and calorimeter are shown in detail in Figure A-1. The reboiler had the following dimensions: 6.0 cm. I.D., 7.0 cm. O.D., and 15 cm. deep. The liquid return line was made from 6 mm. I.D. glass tubing and the vapor exit line from 10 mm. I.D. tubing. The vacuum line was made from 10 mm. heavy walled tubing. The heater was made of 16 gage Chromel A wire covered with fiber glass insulation.

The calorimeter was made from glass tubing with the following dimensions: entering vapor line and coiled tubing, 10 mm. I.D.; vapor tubing in the U tube, 6 mm. I.D.; U tube, 18 mm. I.D.; and vacuum line, 10 mm. heavy walled. The thermel was a five-junction type made from 30 gage copper and constantan thermocouple wire. The heater was

FIGURE A-1
CALORIMETER AND REBOILER

FIGURE A-1
CALORIMETER
AND
REBOILER

made from 30 gage Chromel A wire and was suspended in the calorimeter through a two-hole ceramic tube.

The electrical circuit used is shown in Figure A-2. This drawing shows the arrangement used to measure the voltage drop across the calorimeter heater with the use of the volt box and to measure the current drawn by the calorimeter heater. The same potentiometer was employed to measure the emf developed by the thermel. The lead storage batteries shown were two batteries connected in parallel in both cases. The serial numbers of the various electrical instruments are listed in Appendix Table I.

APPENDIX TABLE I
LIST OF ELECTRICAL EQUIPMENT

Item	Manufacturer	Serial No.
"Thermotrol" Controller	Hallikainen Instruments	1298
Platinum Resistance Thermometer	Leeds and Northrup	714136
Potentiometer, Type K-2	" " "	734287
Galvanometer	" " "	728863
Standard Resistor	" " "	719996
Volt Box	" " "	734208
Standard Cell	The Eppley Laboratory	656633
Stopwatch	Central Scientific Co.	73535
Ammeter	" " "	4393

FIGURE A-2
ELECTRICAL CIRCUIT

APPENDIX B

CALIBRATION OF THE DIFFERENTIAL THERMEL

The five-junction copper-constantan thermel previously described was calibrated by the integral method discussed by Burlew and Smith²¹ and was checked by the

²¹Burlew, J. S., and Smith, R. P., J. Am. Chem. Soc., 62, 701-4 (1940).

differential method and by estimations based on data for copper-constantan thermocouples presented in the International Critical Tables.

In the direct differential method, the two junctions of the thermel were maintained at different temperatures while the emf produced was measured. Since the reboiler bath temperature could not be maintained constant at temperatures above 140°C, it was necessary to use a less direct method of calibration, namely, the integral method. Here one junction was placed in an ice bath and the other junction was maintained at a higher temperature in the calorimeter bath while the emf produced was measured. The conversion of this data to a form which can be used to measure temperature differences will be discussed later.

The errors arising from the use of the integral method have been discussed by Burlew and Smith²¹ as follows:

A thermel that is to be used for the measurement of temperature differences also may be

the integral method; but the error from inhomogeneity will be considerably greater than if the same thermel were used for single temperature measurements. The error is magnified because, first, the emf that corresponds to the difference in temperature is the difference between two large emf's with each of which is associated an error due to inhomogeneity; and, second, the temperature gradients during calibration are much steeper and occur along different portions of the wires than those during subsequent use.

The accuracy of the integral method depends considerably on the purity of the thermocouple wire used. The thermel used in this experiment was made of 30 gage wire which should be more homogeneous than the finer wire used by Burlew and Smith.

For the differential method a function, μ , is defined as

$$\mu = \Delta E / (t_2 - t_1).$$

This function is determined experimentally and is related to the mean temperature of the junctions by the quadratic equation,

$$\mu = \alpha + \beta t_m + \gamma t_m^2,$$

where,

$$t_m = (t_1 + t_2)/2.$$

Now μ is the slope of a secant that cuts the curve representing the function $E(t)$. The thermoelectric power, dE/dt , is the tangent to this same curve. It so happens that the shape of the curve for a copper-constant thermel is such that the tangent at a particular temperature, t_m , is not

quite parallel to the secant whose mid-abscissa is t_m .

For copper-constantan the emf is a cubic function of the temperature of the form,

$$E = at + bt^2 + ct^3.$$

If $\Delta E = E_2 - E_1$, then,

$$\Delta E = at_2 + bt_2^2 + ct_2^3 - at_1 - bt_1^2 - ct_1^3,$$

and,

$$\nu = \Delta E / \Delta t = \frac{a(t_2 - t_1) + b(t_2^2 - t_1^2) + c(t_2^3 - t_1^3)}{(t_2 - t_1)}$$

Dividing through by $(t_2 - t_1)$, remembering that,

$$(t_2^2 - t_1^2) = (t_2 + t_1)(t_2 - t_1)$$

and that

$$(t_2^3 - t_1^3) = (t_2 - t_1)(t_2^2 + t_2 t_1 + t_1^2),$$

gives the equation,

$$\nu = a + b(t_2 + t_1) + c(t_2^2 + t_2 t_1 + t_1^2)$$

Since $t_m = (t_2 + t_1)/2$, then $t_2 + t_1 = 2t_m = 2t$.

Therefore,

$$\nu = a + 2bt + c(t_2^2 + t_2 t_1 + t_1^2).$$

Now,

$$t_m^2 = t^2 = (t_2^2 + 2t_2 t_1 + t_1^2)/4$$

and

$$dE/dt = a + 2bt + 3ct^2.$$

Therefore,

$$\begin{aligned}
 \mu - dE/dt &= c(t_2^2 + t_2 t_1 + t_1^2) - 3ct^2 \\
 &= c(t_2^2 + t_2 t_1 + t_1^2) - 3c(t_2 + 2t_2 t_1 + t_1^2)/4 \\
 &= c(t_2^2 - 2t_2 t_1 + t_1^2)/4 \\
 &= c(t_2 - t_1)^2/4 = c(\Delta t)^2/4
 \end{aligned}$$

Comparing μ and dE/dt term by term shows that by inspection,

$$\beta = 2b$$

$$\gamma = 3c$$

Since $\mu - dE/dt = c(4t/2)^2$, then

$$\alpha + \beta t_m + \gamma t_m^2 - a - 2bt_m - 3ct_m^2 = c(\Delta t/2)^2$$

and therefore,

$$\alpha = a + c(\Delta t/2)^2.$$

The relation between the integral and differential methods is given by the equalities:

$$\alpha = a + c(\Delta t/2)^2$$

$$\beta = 2b$$

$$\gamma = 3c$$

Burlew and Smith²¹ show that a value of μ that applies to one temperature difference, Δ_1 , can be transformed to one that applies to any other temperature difference, Δ_x , by the equation,

$$\mu_{\Delta_x} - \mu_{\Delta_1} = (c/4)(\Delta_x^2 - \Delta_1^2) = (\gamma/12)(\Delta_x^2 - \Delta_1^2).$$

For the thermel used in this experiment γ was small ($\gamma = -2.799 \times 10^{-7}$) such that ^{for} Δt 's less than 10 degrees the correction to be applied would be insignificant.

In the differential method one bath was maintained about 10°C higher than the other. The calorimeter bath was controlled at the higher temperature within $\pm 0.005^\circ\text{C}$. The reboiler bath was controlled by the mercury regulator which maintained the bath temperature to about $\pm 0.03^\circ\text{C}$ for temperatures below 140°C. Above 140°C this regulator was inoperative due to its slow response. The thermel emf was determined by a type K-2 Leeds and Northrup potentiometer. Readings were taken at frequent intervals to minimize the effect of cycling and an average emf was recorded. The bath temperatures were measured by a platinum resistance thermometer. The experimental data and calculated results are listed in Appendix Table II.

In the integral method one junction was placed in the calorimeter bath which was controlled to about $\pm 0.005^\circ\text{C}$. At 250°C there was some cycling but the period was long enough to permit the emf and temperature to be measured. The other junction was placed in a Dewar flask filled with crushed ice and wetted with distilled water. The emf was again measured with the K-2 potentiometer and the temperature was determined with the platinum resistance thermometer. The data was fitted by the method of least squares to the equation, $E = at + bt^2 + ct^3$, which was rewritten in the

quadratic form, $E/t = a + bt + ct^2$. The constants were found to be:

$$a = 0.19303$$

$$b = 2.1337 \times 10^{-4}$$

$$c = 9.3269 \times 10^{-8}$$

Appendix Table III lists the experimental emf's along with those calculated by the cubic equation.

APPENDIX TABLE II

THE FUNCTION, μ , MEASURED BY THE DIFFERENTIAL METHOD

E mv	t_2 °C	t_1 °C	Δt °C	t_m °C	μ mv/°C
2.0645	79.680	70.548	9.132	75.114	0.22607
2.4508	99.631	89.125	10.506	94.378	0.23328
2.2826	118.697	109.159	9.538	113.928	0.23932
2.0110	138.895	130.719	8.176	134.807	0.24596

The constants for the differential equation were calculated from these values as follows:

$$\alpha = a + c(\Delta t/2)^2 = 0.19303 - 9.327 \times 10^{-8}(\Delta t/2)^2$$

$$\beta = 2b = 2 \times 2.134 \times 10^{-4} = 4.268 \times 10^{-4}$$

$$\gamma = 3c = 3 \times (-9.327 \times 10^{-8}) = -2.799 \times 10^{-7}$$

for the calculations in this experiment α was assumed equal to a since the second term effects calculated values of Δt only in the sixth decimal place for Δt 's less than 10°C .

APPENDIX TABLE III

EXPERIMENTAL AND CALCULATED THERMEL EMF'S

Temp °C	Thermel Emf mv (expt'l)	Thermel Emf mv (calc)	Deviation (E - E _{calc})mv
69.291	14.3599	14.368	-0.008
89.513	18.916	18.921	-0.005
109.663	23.622	23.612	0.010
121.964	26.562	26.547	0.015
129.015	28.267	28.256	0.011
148.730	33.126	33.122	0.004
168.465	38.119	38.129	-0.010
188.869	43.417	43.440	-0.023
208.306	48.543	48.625	-0.082
230.308	54.737	54.634	0.103
250.337	60.197	60.229	0.032

avg = ± 0.028

As another check on the thermel calibration, values of μ were estimated using the International Critical Table's²² copper-constantan thermocouple calibration table.

²²International Critical Tables, Vol. I, p. 58.

In this table temperatures are listed for each 0.1 mv and the change in temperature for this 0.1 mv is given. Since $\mu = \Delta E / \Delta t$, this function can be calculated at the average temperature for a five junction thermel. In Figure A-3 values of μ obtained by the three methods are presented in graphical form.

These methods compared favorably, but the integral method was considered more reliable. Therefore, in this experiment ΔT 's were calculated using the following equation:

$$\mu = 0.19303 + 4.268 \times 10^{-4} t_m - 2.799 \times 10^{-7} t_m^2.$$

FIGURE A-3
THERMEL CALIBRATION

FIGURE A-3
THERMEL CALIBRATION

- △ ESTIMATED FROM ICT TABLE
- DIFFERENTIAL METHOD
- INTEGRAL METHOD

APPENDIX C

EXPERIMENTAL PROCEDURE

In determining the heat capacity of both benzene and $C_8F_{16}O$ vapor, the following procedure was used:

1. Two-hundred and fifty milliliters of liquid were transferred to the reboiler by attaching the sampling flask to the top of the condenser. Whenever liquid was added to the sampling flask, the drying tube was attached to prevent water vapor from entering the system.

2. The stirrers in both baths were turned on and full heat was supplied to the heaters to bring the baths quickly up to operating temperatures. The reboiler bath was always set to control about 2 degrees below the boiling point of the compound and the calorimeter bath was set at some value between the boiling point and $250^{\circ}C$. The amount of heat supplied by the continuous heaters and the control heaters was adjusted until the on-time of the controller was the same as the off-time.

3. After the baths had been adjusted, the vapor lines outside the baths were heated to at least $10^{\circ}C$ above the boiling point by adjusting the voltage drop across the asbestos heating tape wrapped around the lines. The temperature of the lines were determined by thermocouples imbedded in the lagging.

4. The pressure in the reboiler and calorimeter jacketets was lowered to about 1 micron of Hg. The pressure was lowered to about 400 microns by the fore pump before the mercury diffusion pump was started. Liquid nitrogen was used at the cold trap. The pressure reached its equilibrium value after 30 minutes.

5. The reboiler heater was adjusted to give some preselected flow rate. Cooling water for the condensers was turned on.

6. The sampling flask was weighed empty and this value was used for the entire run.

7. The current to the calorimeter heater was adjusted until the temperature rise as indicated by the differential thermel was between 4 and 5°C. After the temperature rise was shown to be constant, the current drawn by the heater was determined. Then the resistor between the 12 volt and 6 volt lead storage batteries was set such that the current supplied to the 6 volt batteries was about the same as the current drawn by the calorimeter heater.

8. The temperature rise of the vapor was measured periodically to see whether steady state conditions had been established. After steady state was attained, which took about 30 minutes, the thermel emf was measured five times and an average value was recorded for the observed temperature rise in millivolts.

9. The voltage drop across the calorimeter heater was measured by the potentiometer using a volt box to divide the potential in the ratio of 100:1, and was recorded in volts.

10. The current drawn by the calorimeter was measured using the voltage drop across the 0.1 ohm standard resistor and this was recorded in volts.

11. The condensed fluid was diverted to the sampling flask by turning the two-way Teflon stopcock and, simultaneously, the stopwatch was started to determine the vapor flow rate. After about 30 grams of sample had been collected, the stopcock was turned to divert the condensed fluid back to the reboiler and the stopwatch was stopped at the same time. The sampling flask was weighed after the receiving line was allowed to drain for about 5 minutes.

12. While the sample was being collected, the temperature of the calorimeter bath was determined by measuring the resistance of the platinum resistance thermometer on the Mueller bridge. The resistance was recorded in ohms.

13. After the weight of the sample had been recorded, the sampling flask was attached to the top of the condenser with the drying tube intact and the sample was returned to the reboiler. The sampling flask was flushed with air after the liquid was transferred to the reboiler and before it was attached to the receiving line.

14. The current to the calorimeter heater was turned off the system approached steady state conditions. After about 30 minutes the thermel emf was measured under conditions in which no heat was supplied to the vapor. This emf was less than zero and the lead wires to the potentiometer were reversed to make this measurement. The average emf was recorded in millivolts.

15. The calorimeter heater current was turned on again and steps 7 through 13 were repeated.

16. After the measurements were made at this one flow rate, the flow rate was changed by adjusting the voltage drop across the reboiler heater and steps 7 through 15 were repeated. The procedure was repeated again for another flow rate. This gave two values of observed heat capacity at about the same flow rate and six data points at three different flow rates to enable one to extrapolate to infinite flow rate.

17. The calorimeter bath was set at a different temperature and steps 2 through 16 were repeated.

18. To remove the liquid from the reboiler the reboiler bath was raised to a temperature above the boiling point and a vacuum was drawn on the system until all the compound had evaporated. The system was flushed with dry air before the next compound was added.

. . . APPENDIX D
SAMPLE CALCULATION

The example that follows indicates the method used to calculate the heat capacity of benzene vapor in Run #14. The method was the same for all the other runs. The data collected for Run #14 are listed in Appendix E. A step by step procedure used for the calculation follows.

(1) The temperature of calorimeter bath was calculated from the resistance of the platinum resistance thermometer using the following equation:

$$t_o = \frac{R_t - R_o}{\alpha R_o} + \delta [(t_o/100) - 1] t_o/100$$

where ,

R_t = resistance of thermometer at temperature, t

R_o = 25.5673

α = 0.0039247

δ = 1.492

A trial and error solution was used to calculate t_o ; the first trial used the value of the first term of the equation. Three trials were sufficient in most cases.

(2) The flow rate (F) was calculated in grams per second.

(3) The thermel emf produced under conditions when no heat was supplied to the vapor (ΔE_c) was plotted against the reciprocal flow rate ($1/F$) as shown in Figure A-4 and the

FIGURE A-4
THERMEL EMF WHEN NO HEAT
WAS ADDED TO THE VAPOR
and

FIGURE A-5
 C_{pobs} EXTRAPOLATED TO INFINITE
FLOW RATE

best straight line was drawn through the points. From this plot ΔE_c was read off for the measured values of $1/F$.

(4) The temperature drop (ΔT_c) associated with this thermel emf was calculated from the equation,

$$\mu_c = \Delta E_c / \Delta T_c = 1.9303 + 4.268 \times 10^{-4} t_m - 2.799 \times 10^{-7} t_m^2.$$

In this case,

$$t_m = t_o - 1/2 \Delta T_c,$$

where t_o is the calorimeter bath temperature. Since ΔT_c was small, t_m was assumed equal to t_o . For Run #14a,

$$\Delta E_c = 0.0884 \text{ mv and } t_o = 178.934^\circ\text{C}.$$

Therefore,

$$\begin{aligned} \mu_c &= 1.9303 + 4.268 \times 10^{-4} \times 178.934 \\ &\quad - 2.799 \times 10^{-7} (178.934)^2 = 0.26044 \text{ mv}/^\circ\text{C}. \end{aligned}$$

$$\therefore \Delta T_c = \Delta E_c / \mu_c = -0.339^\circ\text{C}.$$

(5) The observed temperature rise (ΔT_{obs}) was calculated by a similar procedure. First a value of μ was calculated by the equation in step (4). In this case $t_m = t_o + 1/2 \Delta T_{obs}$ and therefore a trial and error procedure was used. A value of ΔT_{obs} was assumed and from this a value of μ was calculated. From the equation $\Delta T_{obs} = \Delta E / \mu$, a value of ΔT_{obs} was calculated and compared with the assumed value. This was repeated until the two matched. For example, Run #14a,

$$\Delta E = 1.3098 \text{ mv and } t_o = 178.934^\circ\text{C}$$

now assume $\Delta T_{\text{obs}} = 5.013^{\circ}\text{C}$,

then,

$$t_m = 178.934 + 1/2(5.013) = 181.451^{\circ}\text{C}.$$

Calculating μ for this value of t_m gives,

$$\begin{aligned}\mu &= 1.9303 + 4.268 \times 10^{-4}(181.451) - 2.799 \times 10^{-7}(181.451)^2 \\ &= 0.26126 \text{ mv}/^{\circ}\text{C}.\end{aligned}$$

Calculating ΔT_{obs} shows that,

$$\Delta T_{\text{obs}} = \Delta E/\mu = 1.3098/0.26126 = 5.013^{\circ}\text{C}$$

which was the same as the value assumed.

(6) C_{pobs} was calculated from the equation,

$$C_{\text{pobs}} = EI/4.185F\Delta T.$$

For Run #14a, $E = 1.6413$ volts, $I = 0.15374$ amps,

$F = 0.023601$ grs/sec and $\Delta T = \Delta T_{\text{obs}} - \Delta T_c = 5.013 + 0.339$
 $= 5.352^{\circ}\text{C}.$

$$\begin{aligned}C_{\text{pobs}} &= 1.6413 \times 0.15374 / 4.185 \times 0.023601 \times 5.352 \\ &= 0.4773 \text{ cal/gr, } ^{\circ}\text{C}.\end{aligned}$$

(7) After values of the observed heat capacity were obtained it was necessary to extrapolate the data to infinite flow rate to obtain the true heat capacity as given by the equation, $C_{\text{pobs}} = C_p + b(1/F)$. The least mean square fit of the data was made and C_p was calculated as follows:

$$C_p = \overline{C_{\text{pobs}}} - b\overline{(1/F)} = \sum(C_{\text{pobs}})/n - b\sum(1/F)/n$$

where

$$b = \frac{\sum(1/F)(C_{pobs}) - [\sum(1/F)(\sum C_{pobs})]/n}{\sum(1/F)^2 - [\sum(1/F)]^2/n}$$

n = number of data sets.

For example in Run #14 the values of C_{pobs} and $1/F$ are:

C_{pobs} cal/gr, °C	$1/F$ sec/gr
0.4773	42.371
0.4786	41.890
0.4545	31.898
0.4546	31.723
0.4373	21.876
0.4355	21.382

The values of the summations are:

$$\sum C_{pobs} = 2.7378$$

$$\sum 1/F = 191.140$$

$$\sum (1/F)^2 = 6509.65$$

$$\sum (1/F)(C_{pobs}) = 88.070$$

From these values

$$b = \frac{88.070 - (191.140)(2.7378)/6}{6509.65 - (191.140)^2/6} = 0.002028$$

$$C_p = 2.7378/6 - 0.002028(191.140/6) = 0.3917 \text{ cal/gr, } ^\circ\text{C}.$$

The temperature was taken as the average value of the mean temperatures. Thus for Run #14, the heat capacity of benzene vapor is 0.3917 cal/gr, °C at 181.3 °C. This procedure is demonstrated graphically in Figure A-5.

APPENDIX E
EXPERIMENTAL DATA AND CALCULATED RESULTS

The experimental data for benzene vapor is presented in Appendix Table IV with the data for each run grouped together. The units are listed with item measured. The term ΔE is the thermel emf. The voltage drop is that across the calorimeter heater and was measured with the aid of the volt box which was set to divide the potential in the ratio 100:1. The resistor voltage drop is that across the 0.1 ohm standard resistor used to measure the current. The empty flask was weighed only once during each run. The resistance of the platinum resistance thermometer is a measure of the temperature of the calorimeter bath.

Appendix Table V uses the same nomenclature for the experimental data for perfluoro-2-butyl-tetrahydrofuran.

In Appendix Table VI the data used for calculating the heat capacity of benzene vapor is grouped together for each run. The units are listed after each item. The terms ρ_c , ΔE_c and ΔT_c applied to the temperature drop under conditions when no heat was supplied to the vapor. This has been thoroughly explained in Appendix D. The term ΔT in this table is ΔT_{Obs} and was shortened for convenience. Other terms have been previously explained. At the bottom

of group is the heat capacity in cal/gr, °C at the average temperature of the run.

Appendix Table VII lists the calculated data for perfluoro-2-butyl-tetrahydrofuran with the same nomenclature as above.

APPENDIX TABLE IV

EXPERIMENTAL HEAT CAPACITY DATA FOR BENZENE VAPOR

Run No.	4a	4b	4c	4d	4e	4f
ΔE , mv	1.2395	1.2706	1.1751	1.1621	1.2604	1.2710
Voltage Drop, volts	0.021650	0.021812	0.018425	0.018431	0.016346	0.016342
Resistor volt drop, volt	0.020437	0.020570	0.017380	0.017390	0.015420	0.015419
Wt. of flask + sample, gr	32.8469	18.9752	21.3688	21.5490	22.8498	17.9900
Wt. of flask, gr	5.5342					
Time of sampling, sec.	600.0	300.4	480.0	480.2	840.0	600.0
Resistance Therm., ohms	39.4718	39.4742	39.4758	39.4745	39.4742	38.4731

Run No.	5a	5b	5c
ΔE , mv	1.1508	1.2214	1.2138
voltage drop, volts	0.016335	0.019781	0.022681
Resistor volt drop, volts	0.015417	0.018667	0.021398
Wt of flask + sample, grs	19.0942	26.6045	31.0672
Wt of flask, grs	5.5348		
Time of sampling, sec	540.2	540.0	480.0
Resistance therm., ohms	39.4726	39.4720	39.4711

Run No.	8a	8b	8c	8d	8e	8f
ΔE , mv	1.1735	1.1920	1.2695	1.2970	1.1830	1.1546
Voltage drop, volts	0.019868	0.019880	0.018058	0.018067	0.015057	0.015056
Resistor volt drop, volts	0.018849	0.018852	0.017125	0.017135	0.014284	0.014283
Wt of flask + sample, grs	26.2064	25.5219	25.3842	26.9270	20.0461	20.1689
Wt of flask, grs	5.5370					
Time of sampling, sec	480.4	482.2	660.0	720.6	720.6	720.8
Resistance therm., ohms	35.6684	35.6736	35.6798	35.6793	35.6603	35.6618

(Cont'd)

APPENDIX TABLE IV (CONT'D)

Run No.	12a	12b	12c	12d	12e	12f
ΔE , mv	1.0700	1.0806	1.1275	1.0750	1.1481	1.1261
Voltage drop, volts	0.013522	0.013532	0.016670	0.016682	0.019921	0.019923
Resistor volt drop, volts	0.012799	0.012808	0.015778	0.015782	0.018841	0.018846
Wt of flask + sample, grs	17.5060	17.7671	24.8452	24.1382	30.5331	18.3700
Wt of flask, grs	5.5270					
Time of sampling, sec	605.4	602.4	602.2	540.6	540.7	270.9
Resistance therm., ohms	37.6436	37.6438	37.6447	37.6444	37.6460	37.6468
Run No.	13a	13b	13c	13d	13e	13f
ΔE , mv	1.1282	1.0872	1.1317	1.1367	1.1681	1.1831
Voltage drop, volts	0.019959	0.019952	0.017356	0.017358	0.015991	0.016004
Resistor volt drop, volts	0.018757	0.018758	0.016315	0.016319	0.015033	0.015047
Wt of flask + sample, grs	21.8902	25.6362	25.3404	25.3323	24.9972	21.1022
Wt of flask, grs	5.5253					
Time of sampling, sec	362.5	420.4	600.3	600.9	736.5	600.9
Resistance therm., ohms	41.3784	41.3781	41.3754	41.3756	41.3782	41.3758
Run No.	14a	14b	14c	14d	14e	14f
ΔE , mv	1.3098	1.2883	1.2987	1.2920	1.1492	1.1282
ΔE_c , mv	-0.0885		-0.0729		-0.0583	
Voltage drop, volts	0.016413	0.016405	0.018279	0.018294	0.020322	0.020332
Resistor volt drop, volts	0.015374	0.015360	0.017129	0.017134	0.019039	0.019040
Wt of flask + sample, grs	19.7142	19.9322	22.4949	22.5510	24.7381	25.1911
Wt of flask, grs	5.5253					
Time of sampling, sec.	601.2	603.5	541.3	540.1	420.3	420.5
Resistance therm., ohms	43.3108	43.3084	43.3084	43.3073	43.3073	43.3064

APPENDIX TABLE V
EXPERIMENTAL HEAT CAPACITY DATA FOR PERFLUORO-2-BUTYL-TETRAHYDROFURAN VAPOR

Run No.	15a	15b	15c	15d	16e	15f
ΔE , mv	1.244	1.1872	1.2144	1.2185	1.2174	1.2301
ΔE_c , mv	-0.1206	-0.0966	-0.0715		-0.0749	
Voltage drop, volts	0.017934	0.017946	0.023201	0.023156	0.020696	0.020690
Resistor volt drop, volts	0.016984	0.016991	0.021972	0.021930	0.019606	0.019584
Wt of flask + sample, grs	31.8410	33.7906	48.4546	38.0280	43.3988	43.9138
Wt of flask, grs	5.5380			5.5374	5.5652	
Time of sampling, sec	541.4	541.2	480.8	360.5	542.7	540.4
Resistance therm., ohms	36.5836	36.5845	36.5857	36.5851	36.5862	36.5855
Run No.	16a	16b	16c	16d	16e	16f
ΔE , mv	1.3007	1.2709	1.2470	1.2425	1.1777	1.1894
ΔE_c , mv	-0.1122	-0.0892		-0.0698		-0.0639
Voltage drop, volts	0.016195	0.016212	0.021247	0.021248	0.023575	0.023575
Resistor volt drop, volts	0.015284	0.015308	0.020044	0.020057	0.022252	0.022254
Wt of flask + sample, grs	26.9748	27.9428	43.9534	44.5296	36.4450	44.9820
Wt of flask, grs	5.5380					
Time of sampling, sec	600.4	601.8	540.5	541.2	360.8	420.2
Resistance therm., ohms	38.5155	38.5146	38.5150	38.5153	38.5157	38.5161
Run No.	18a	18b	18c	18d	18e	18f
ΔE , mv	1.4742	1.4009	1.0967	1.0866	1.4227	1.3955
ΔE_c , mv		-0.0941		-0.0720		-0.0615
Voltage drop, volts	0.016839	0.016836	0.018177	0.018161	0.023541	0.023540
Resistor volt drop, volts	0.015795	0.015795	0.017051	0.017037	0.022073	0.022077
Wt of flask + sample, grs	33.4847	35.8100	40.4350	40.4580	43.0756	44.8884
Wt of flask, grs	5.5370					
Time of sampling, sec	840.3	840.5	600.8	604.3	480.0	480.6
Resistance therm., ohms	42.3088	42.3085	42.3085	42.3086	42.3075	42.3064

130

(cont'd)

APPENDIX TABLE V (CONT'D)

Run No.	19a	19b	19c	19d	19e	19f
ΔE , mv	1.1641	1.1056	1.4329	1.4490	1.4111	1.4081
ΔE_c , mv		-0.1028	-0.0991			-0.1050
Voltage drop, volts	0.019700	0.019668	0.019653	0.019637	0.016118	0.016127
Resistor volt drop, volts	0.018622	0.018594	0.018570	0.018560	0.015234	0.015240
Wt of flask + sample, grs	36.1382	37.7573	36.4620	36.2266	34.8034	35.1666
Wt of flask, grs	5.5358					
Time of sampling, sec	481.0	480.6	601.0	600.7	900.7	900.1
Resistance therm., ohms	37.5548	37.5564	37.5567	37.5577	37.5565	37.5573
Run No.	20a	20b	20c	20d	20e	
ΔE , mv	1.5384	1.5186	1.3555	1.3679	1.2667	
ΔE_c , mv	-0.1144			-0.1035	-0.0924	
Voltage drop, volts	0.014945	0.014951	0.016634	0.016656	0.018130	
Resistor volt drop, volts	0.014063	0.014062	0.015647	0.015667	0.017058	
Wt of flask + sample, grs	26.8110	27.3241	27.2200	27.0278	31.3582	
Wt of flask, grs	5.5368					
Time of sampling, sec	900.4	900.6	600.3	601.7	540.0	
Resistance therm., ohms	40.4309	40.4305	40.4302	40.4298	40.4306	
Run No.	21a	21b	21c	21d	21e	21f
ΔE , mv	1.4815	1.4668	1.4577	1.5117	1.4154	1.4134
ΔE_c , mv		-0.0890		0.0911		-0.0951
Voltage drop, volts	0.020011	0.020017	0.018072	0.018061	0.015195	0.015306
Resistor volt drop, volts	0.018763	0.018770	0.016943	0.016932	0.014250	0.014352
Wt of flask + sample, grs	36.1804	37.2140	30.5326	30.0882	30.5616	30.8958
Wt of flask, grs	5.5354					
Time of sampling, sec	600.4	600.4	601.4	600.3	900.5	901.8
Resistance therm., ohms	42.3159	42.3149	42.3139	42.3140	42.3133	42.3139

(Cont'd)

APPENDIX TABLE V (CONT'D)

Run No.	23a	23b	23c	23d	23e	23f
ΔE , mv	1,3046	1.2836	1.2837	1.2208	1.2242	1.2480
ΔE_c , mv		-0.0934		-0.0880		-0.0684
Voltage drop, volts	0.016327	0.016328	0.018202	0.018218	0.020063	0.020074
Resistor volt drop, volts	0.015196	0.015198	0.016941	0.016945	0.018661	0.018664
Wt of flask + sample, grs	37.2270	37.6562	34.9164	36.2140	43.2676	42.9016
Wt of flask, grs	5.5356					
Time of sampling, sec	900.4	900.1	600.4	600.4	600.8	600.5
Resistance therm., ohms	46.2994	46.2995	46.2995	46.3003	46.2981	46.2985
Run No.	24a	24b	24c	24d		
ΔE , mv	1.1629	1.1575	1.4948	1.4570		
ΔE_c , mv		-0.0693		-0.0767		
Voltage drop, volts	0.021074	0.021177	0.020276	0.020287		
Resistor volt drop, volts	0.019656	0.019752	0.018912	0.018921		
Wt of flask + sample, grs	49.6816	38.5128	36.8656	37.6870		
Wt of flask, grs	5.5364					
Time of sampling, secs	600.0	420.0	599.8	600.9		
Resistance therm., ohms	44.2403	44.2393	44.2398	44.2396		
Run No.	25a	25b	25c	25d	25e	25f
ΔE , mv	1.5811	1.5129	1.2323	1.2400	1.3093	1.3350
ΔE_c , mv		-0.0962		-0.0732		-0.0687
Voltage drop, volts	0.020282	0.020277	0.020269	0.020272	0.022951	0.022952
Resistor volt drop, volts	0.018912	0.018905	0.018901	0.018906	0.021403	0.021402
Wt of flask + sample, grs	34.6718	37.3750	37.3680	37.1030	35.0170	43.8466
Wt of flask, grs	5.5358					
Time of sampling, sec	600.8	600.2	480.3	480.3	360.3	480.5
Resistance therm., ohms	44.4073	44.4147	44.4091	44.4109	44.4114	44.4110

(Cont'd)

APPENDIX TABLE V (CONT'D)

Run No.	26a	26b	26c	26d		
ΔE , mv	1.3223	1.3874	1.3573	1.4286		
ΔE_c , mv		-0.0615		-0.0648		
Voltage drop, volts	0.022886	0.022884	0.020012	0.020008		
Resistor volt drop, volts	0.021154	0.021151	0.018488	0.018496		
Wt. of flask + sample, grs	44.5244	45.3246	43.4750	37.0086		
Wt of flask, grs	5.5350					
Time of sampling, sec	480.5	491.5	660.4	541.3		
Resistance therm., ohms	48.8401	48.8498	48.8565	48.8538		
Run No.	27a	27b	27c	27d	27e	27f
ΔE , mv	1.4873	1.5354	1.2359	1.2298	1.2908	1.2800
ΔE_c , mv		-0.0790		-0.0662		-0.0547
Voltage drop, volts	0.020000	0.020009	0.020000	0.019997	0.022503	0.022486
Resistor volt drop, volts	0.018474	0.018482	0.018478	0.018470	0.020786	0.020769
Wt of flask + sample, grs	39.7482	38.2266	40.9690	42.5070	47.8550	48.1670
Wt of flask, grs	5.5326					
Time of sampling, sec	720.9	720.7	600.8	600.5	540.8	547.8
Resistance therm., ohms	48.8576	48.8585	48.8550	48.8543	48.8545	48.8588
Run No.	29a	28b	28c	28d	28e	28f
ΔE , mv	1.4481	1.4363	1.4883	1.4812	1.3134	1.3334
ΔE_c , mv		-0.1463		-0.1136		-0.1259
Voltage drop, volts	0.020862	0.020884	0.023984	0.023990	0.018587	0.018733
Resistor volt drop, volts	0.019555	0.019579	0.022492	0.022498	0.017433	0.017573
Wt of flask + sample, grs	36.1532	38.1184	40.7642	41.1750	39.7850	39.8130
Wt of flask, grs	5.5400					
Time of sampling, sec	601.7	601.0	480.2	480.4	720.4	721.0
Resistance therm., ohms	39.4652	39.4571	39.4518	39.4485	39.4485	39.4449

(Cont'd)

APPENDIX TABLE V (CONT'D)

Run No.	29a	29b	29c	29d	29e	29f
ΔE , mv	1.1917	1.1911	1.2183	1.2032	1.3572	1.3683
ΔE_c , mv		-0.1522		-0.1133		-0.1052
Voltage drop, volts	0.019378	0.019394	0.022660	0.022678	0.026066	0.026066
Resistor volt drop, volts	0.018146	0.018156	0.021235	0.021243	0.024402	0.024407
Wt of Flask + sample, grs	45.5504	45.4636	44.6570	44.5370	52.3888	52.5438
Wt of Flask, grs	5.5342					
Time of sampling, sec	720.1	720.8	480.8	481.0	480.4	480.5
Resistance therm., ohms	40.4563	40.4515	40.4509	40.4524	40.4503	40.4502
Run No.	30a	30b	30c	30d	30e	30f
ΔE , mv	1.4244	1.4195	1.2656	1.2044	1.1779	1.1692
ΔE_c , mv		-0.1125		-0.1086		-0.1118
Voltage drop, volts	0.026048	0.026074	0.022340	0.022332	0.019990	0.019990
Resistor volt drop, volts	0.024344	0.024370	0.020890	0.020880	0.018688	0.018688
Wt of flask + sample, grs	49.6868	50.1844	41.3890	43.5500	38.9000	39.1964
Wt of flask, grs	5.5350					
Time of sampling, sec	481.3	480.5	482.1	481.8	540.5	541.3
Resistance therm., ohms	41.5463	41.5445	41.5471	41.5436	41.5440	41.5423

APPENDIX TABLE VI

CALCULATED DATA FOR THE HEAT CAPACITY OF BENZENE VAPOR

Run No.	4a	4b	4c	4d	4e	4f
Current, amps	0.20437	0.20570	0.17380	0.17390	0.15420	0.15419
Voltage drop, volts	2.1650	2.1812	1.8425	1.8431	1.6346	1.6342
Temp of bath, °C	139.387	139.412	139.428	139.415	139.412	139.400
μ_c , mv/°C	0.24708	0.24709	0.24710	0.24709	0.24709	0.24709
ΔE_c , mv	-0.0584	-0.0589	-0.0707	-0.0702	-0.0975	-0.0970
ΔT_c , °C	-0.236	-0.238	-0.286	-0.284	-0.395	-0.393
μ , mv/°C	0.24795	0.24798	0.24791	0.24791	0.24798	0.24798
ΔE , mv	1.2395	1.2706	1.1751	1.1621	1.2604	1.2710
ΔT , °C	4.999	5.124	4.740	4.688	5.083	5.125
T_m , °C	141.887	141.974	141.798	141.759	141.954	141.963
F, grs/sec	0.045521	0.044744	0.032989	0.033350	0.020614	0.020760
C_{pobs} , cal/gr, °C	0.4437	0.4469	0.4615	0.4619	0.5334	0.5256

$$C_p = 0.2679 \text{ at } 141.889^\circ\text{C}$$

Run No.	5a	5b	5c
Current, amps	0.15417	0.18667	0.21398
Voltage drop, volts	1.6335	1.9781	2.2681
Temp of bath, °C	139.395	139.389	139.380
μ_c , mv/°C	0.24708	0.24708	0.24708
ΔE_c , mv	-0.0847	-0.0638	-0.0537
ΔT_c , °C	-0.343	-0.258	-0.217
μ , mv	0.24789	0.24794	0.24793
ΔE , mv	1.1508	1.2214	1.2138
ΔT , °C	4.642	4.926	4.896
T_m , °C	141.716	141.852	141.828
F, grs/sec	0.025101	0.039018	0.053193
C_{pobs} , cal/gr, °C	0.4809	0.4362	0.4264

$$C_p = 0.3727 \text{ at } 141.799^\circ\text{C}$$

(Cont'd)

APPENDIX TABLE VI (CONT'D)

Run No.	8a	8b	8c	8d	8e	8f
Current, amps	0.18849	0.18852	0.17125	0.17135	0.14284	0.14283
Voltage drop, volts	1.9868	1.9880	1.8058	1.8067	1.5057	1.5056
Temp of bath, °C	100.675	100.728	100.790	100.785	100.593	100.670
μ_c , mv/°C	0.23316	0.23318	0.23321	0.23321	0.23313	0.23314
ΔE_c , mv	-0.0602	-0.0616	-0.0750	-0.0756	-0.0992	-0.0986
ΔT_c , °C	-0.258	-0.264	-0.322	-0.324	-0.426	-0.423
μ , mv/°C	0.23409	0.24313	0.23420	0.23423	0.23406	0.23404
ΔE , mv	1.1735	1.1920	1.2695	1.2970	1.1830	1.1546
ΔT , °C	5.013	5.091	5.421	5.537	5.054	4.933
T_m , °C	103.182	103.274	103.501	103.554	103.120	103.074
F, grs/sec	0.043025	0.041445	0.030072	0.029684	0.020135	0.020300
Cpobs, cal/gr, °C	0.3946	0.4035	0.4279	0.4252	0.4658	0.4726
$C_p = 0.3350$ at 103.284°C						

Run No.	12a	12b	12c	12d	12e	12f
Current, amps	0.12799	0.12808	0.15778	0.15782	0.18841	0.18846
Voltage drop, volts	1.3522	1.3532	1.6670	1.6682	1.9921	1.9923
Temp of bath, °C	120.722	120.724	120.733	120.730	120.747	120.755
μ_c , mv/°C	0.24047	0.24047	0.24048	0.24048	0.24048	0.24049
ΔE_c , mv	-0.1005	-0.0985	-0.0719	-0.0688	-0.0579	-0.0571
ΔT_c , °C	-0.418	-0.410	-0.299	-0.286	-0.241	-0.237
μ , mv/°C	0.24127	0.24128	0.24132	0.24128	0.24134	0.24132
ΔE , mv	1.0700	1.0806	1.1275	1.0750	1.1481	1.1261
ΔT , °C	4.435	4.479	4.673	4.456	4.757	4.666
T_m , °C	122.940	122.964	123.070	122.958	123.126	123.088
F, grs/sec	0.019787	0.020319	0.032079	0.034427	0.046248	0.047409
Cpobs, cal/gr, °C	0.4307	0.4169	0.3940	0.3853	0.3880	0.3860
$C_p = 0.3535$ at 123.024°C						

(Cont'd)

APPENDIX TABLE VI (CONT'D)

Run No.	13a	13b	13c	13d	13e	13f
Current, amps	0.18757	0.18757	0.16315	0.16319	0.15033	0.15047
Voltage drop, volts	1.9959	1.9952	1.7356	1.7358	1.5991	1.6004
Temp of bath, °C	158.968	158.965	158.937	158.939	158.966	158.941
μ_c , mv/°C	0.25381	0.25381	0.25379	0.25379	0.25381	0.25379
ΔE_c , mv	-0.0586	-0.0568	-0.0706	-0.0707	-0.0817	-0.0828
ΔT_c , °C	-0.231	-0.224	-0.278	-0.279	-0.322	-0.326
μ , mv/°C	0.25455	0.25453	0.25454	0.25455	0.25458	0.25458
ΔE , mv	1.1282	1.0872	1.1317	1.1367	1.1681	1.1831
ΔT , °C	4.432	4.272	4.446	4.466	4.588	4.647
T_m , °C	161.184	161.101	161.160	161.169	161.260	161.265
F, grs/sec	0.045144	0.047838	0.033009	0.032962	0.026438	0.025923
Cpobs, cal/gr, °C	0.4250	0.4158	0.4339	0.4328	0.4425	0.4464

$C_p = 0.3888$ at 161.190°C

Run No.	14a	14b	14c	14d	14e	14f
Current, amps	0.15374	0.15360	0.17129	0.17134	0.19039	0.19040
Voltage drop, volts	1.6413	0.6405	1.8279	1.8294	2.0322	2.0332
Temp of bath, °C	178.934	178.909	178.909	178.898	178.898	178.889
μ_c , mv/°C	0.26044	0.26043	0.26043	0.26042	0.26042	0.26042
ΔE_c , mv	-0.0884	-0.0877	-0.0730	-0.0727	-0.0582	-0.0575
μ , mv/°C	0.26126	0.26123	0.26124	0.26123	0.26114	0.26113
ΔE , mv	1.3098	1.2883	1.2987	1.2920	1.1492	1.1282
ΔT , °C	5.013	4.932	4.971	4.946	4.401	4.320
T_m , °C	181.441	181.375	181.395	181.371	181.098	181.049
F, grs/sec	0.023601	0.023872	0.031350	0.031523	0.045712	0.046768
Cpobs, cal/gr, °C	0.4773	0.4786	0.4545	0.4546	0.4370	0.4355

$C_p = 0.3917$ at 181.288

APPENDIX TABLE VII

CALCULATED DATA FOR THE HEAT CAPACITY OF PERFLUORO-2-BUTYL-TETRAHYDROFURAN VAPOR

Run No.	15a	15b	15c	15d	15e	15f*
Current, amps	0.16984	0.16991	0.21972	0.21930	0.19606	0.19584
Voltage drop, volts	1.7934	1.7946	2.3201	2.3156	2.0696	2.0690
Temp of bath, °C	109.948	109.957	109.970	109.963	109.975	109.968
μ_c , mv/°C	0.23658	0.23658	0.23659	0.23658	0.23659	0.23658
ΔE_c , mv	-0.0989	-0.0946	-0.0691	-0.0686	-0.0788	-0.0783
ΔT_c , °C	-0.418	-0.400	-0.292	-0.290	-0.333	-0.331
μ , mv/°C	0.23751	0.23749	0.23752	0.23752	0.23752	0.23752
ΔE , mv	1.2244	1.1872	1.2144	1.2185	1.2174	1.2301
ΔT , °C	5.155	4.999	5.113	5.130	5.125	5.179
T_m , °C	112.526	112.457	112.527	112.528	112.538	112.558
F, grs/sec	0.048583	0.052204	0.089261	0.090126	0.069765	0.071015
C_{pobs} , cal/gr, °C	0.2688	0.2585	0.2527	0.2484	0.2546	0.2474

$C_p = 0.2324$ at 112.522°C

Run No.	16a	16b	16c	16d	16e*	16f
Current, amps	0.15284	0.15308	0.20044	0.20057	0.22252	0.22254
Voltage drop, volts	1.6195	1.6212	2.1247	2.1248	2.3575	2.3575
Temp of the bath, °C	129.611	129.602	129.606	129.609	129.613	129.617
μ_c , mv/°C	0.24365	0.24364	0.24365	0.24365	0.24365	0.24365
ΔE_c , mv	-0.0914	-0.0897	-0.0697	-0.0692	-0.0658	-0.0641
ΔT_c , °C	-0.375	-0.368	-0.286	-0.284	-0.270	-0.263
μ , mv/°C	0.24458	0.24455	0.24454	0.24454	0.24450	0.24451
ΔE , mv	1.3007	1.2709	1.2470	1.2425	1.1777	1.1894
ΔT , °C	5.318	5.197	5.099	5.081	4.816	4.864
T_m , °C	132.270	132.201	132.156	132.150	132.021	132.049
F, grs/sec	0.035704	0.037230	0.071074	0.072047	0.085662	0.093870
C_{pobs} , cal/gr, °C	0.2910	0.2862	0.2659	0.2635	0.2877	0.2605

$C_p = 0.2411$ at 132.141°C

* not included in calc of C_p

(Cont'd)

APPENDIX TABLE VII (CONT'D)

Run No.	18a	18b	18c	18d	18e	18f
Current, amps	0.15795	0.15795	0.17051	0.17037	0.22073	0.22077
Voltage drop, volts	1.6939	1.6836	1.8177	1.8161	2.3541	2.3540
Temp of bath, °C	168.565	168.562	168.562	168.563	168.552	168.538
μ_c , mv/°C	0.25702	0.25702	0.25702	0.25702	0.25702	0.25701
ΔE_c , mv	-0.0991	-0.0941	-0.0720	-0.0720	-0.0628	-0.0615
ΔT_c , °C	-0.386	-0.366	-0.280	-0.280	-0.244	-0.239
μ , mv/°C	0.25796	0.25792	0.25773	0.25772	0.25794	0.25791
ΔE , mv	1.4742	1.4009	1.0967	1.0866	1.4227	1.3955
ΔT , °C	5.715	5.432	4.255	4.216	5.516	5.411
T_m , °C	171.423	171.278	170.690	170.671	171.310	171.244
F, grs/sec	0.033259	0.036018	0.058086	0.057788	0.078205	0.081880
C_{pobs} , cal/gr, °C	0.3132	0.3043	0.2811	0.2846	0.2756	0.2684

 $C_p = 0.2437 \text{ at } 171.103^\circ\text{C}$

Run No.	19a	19b	19c	19d	19e	19f
Current, amps	0.18622	0.18594	0.18570	0.18560	0.15234	0.15240
Voltage drop, volts	1.9700	1.9668	1.9653	1.9637	1.6118	1.6127
Temp of bath, °C	119.818	119.835	119.838	119.848	119.836	119.844
μ_c , mv/°C	0.24015	0.24016	0.24016	0.24016	0.24016	0.24016
ΔE_c , mv	-0.1010	-0.1008	-0.1018	-0.1019	-0.1044	-0.1043
ΔT_c , °C	-0.421	-0.420	-0.424	-0.424	-0.435	-0.434
μ , mv/°C	0.24102	0.24098	0.24122	0.24123	0.24120	0.24121
ΔE , mv	1.1641	1.1056	1.4329	1.4490	1.4111	1.4081
ΔT , °C	4.830	4.588	5.940	6.007	5.850	5.838
T_m , °C	122.233	122.129	122.308	122.852	122.761	122.763
F, grs/sec	0.063622	0.067044	0.051457	0.051092	0.032494	0.032919
C_{pobs} , cal/gr, °C	0.2624	0.2603	0.2663	0.2650	0.2873	0.2844

 $C_p = 0.2350 \text{ at } 122.591^\circ\text{C}$

(Cont'd)

APPENDIX TABLE VII (CONT'D)

Run No.	20a	20b	20c	20d	20e
Current, amps	0.14063	0.14062	0.15647	0.15667	0.17058
Voltage drop, volts	1.4945	1.4951	1.6634	1.6656	1.8130
Temp of bath, °C	149.222	149.218	149.216	149.212	149.219
μ_c , mv/°C	0.25049	0.25049	0.25049	0.25049	0.25049
ΔE_c , mv	-0.1163	-0.1153	-0.1012	-0.1015	-0.0941
ΔT_c , °C	-0.464	-0.461	-0.404	-0.405	-0.376
μ , mv/°C	0.25153	0.25151	0.25141	0.25142	0.25135
ΔE , mv	1.5384	1.5186	1.3555	1.3679	1.2667
ΔT , °C	6.116	6.038	5.392	5.441	5.040
T_m , °C	152.280	152.237	151.912	151.933	151.739
F, grs/sec	0.023627	0.024192	0.036121	0.035717	0.047817
C_{pobs} , cal/gr, °C	0.3230	0.3195	0.2971	0.2986	0.2853

 $C_p = 0.2500$ at 152.019°C

Run No.	21a	21b	21c	21d	21e	21f
Current, amps	0.18763	0.18770	0.16943	0.16932	0.14250	0.14352
Voltage drop, volts	2.0011	2.0017	1.8072	1.8061	1.5195	1.5306
Temp of bath, °C	168.639	168.629	168.618	168.619	168.612	168.619
μ_c , mv/°C	0.25705	0.25704	0.25704	0.25704	0.25704	0.25704
ΔE_c , mv	-0.0892	-0.0890	-0.0910	-0.0911	-0.0954	-0.0951
ΔT_c , °C	-0.347	-0.346	-0.354	-0.354	-0.371	-0.370
μ , mv/°C	0.25800	0.25798	0.25797	0.25801	0.25798	0.25797
ΔE , mv	1.4815	1.4668	1.4577	1.5117	1.4154	1.4134
ΔT , °C	5.742	5.686	5.651	5.859	5.486	5.479
T_m , °C	171.510	171.472	171.444	171.549	171.355	171.359
F, grs/sec	0.051041	0.052762	0.041563	0.040901	0.027791	0.028122
C_{pobs} , cal/gr, °C	0.2887	0.2821	0.2931	0.2876	0.3179	0.3191

 $C_p = 0.2430$ at 171.448°C

(Cont'd)

APPENDIX TABLE VII (CONT'D)

Run No.	23a	23b	23c	23d	23e	23f
Current, amps	0.15196	0.15198	0.16941	0.16945	0.18661	0.18664
Voltage drop, volts	1.6327	1.6328	1.8202	1.8218	2.0063	2.0074
Temp of bath, °C	210.059	210.060	210.060	210.069	210.046	210.050
μ_c , mv/°C	0.27033	0.27033	0.27033	0.27034	0.27033	0.27033
ΔE_c , mv	-0.0970	-0.0964	-0.0840	-0.0827	-0.0765	-0.0769
ΔT_c , °C	-0.359	-0.357	-0.311	-0.306	-0.283	-0.284
μ , mv/°C	0.27108	0.27106	0.27106	0.27103	0.27102	0.27104
ΔE , mv	1.3046	1.2836	1.2837	1.2208	1.2242	1.2480
ΔT , °C	4.813	4.735	4.736	4.504	4.517	4.604
T_m , °C	212.466	212.428	212.428	212.321	212.305	212.352
F, grs/sec	0.035197	0.035686	0.048935	0.051097	0.062803	0.062225
C_{pobs} , cal/gr, °C	0.3257	0.3263	0.2983	0.3001	0.2968	0.2943

 $C_p = 0.2514$ at 212.383°C

Run No.	24a	24b	24c	24d
Current, amps	0.19656	0.19752	0.18912	0.18921
Voltage drop, volts	2.1074	2.1177	2.0276	2.0287
Temp of bath, °C	188.582	188.572	188.577	188.575
μ_c , mv/°C	0.26357	0.26356	0.26356	0.26357
ΔE_c , mv	-0.0704	-0.0693	-0.0772	-0.0767
ΔT_c , °C	-0.267	-0.263	-0.293	-0.291
μ , mv/°C	0.26427	0.26426	0.26447	0.26444
ΔE , mv	1.1629	1.1575	1.4948	1.4570
ΔT , °C	4.400	4.380	5.652	5.510
T_m , °C	190.782	190.762	191.403	191.330
F, grs/sec	0.073575	0.078515	0.052233	0.053504
C_{pobs} , cal/gr, °C	0.2883	0.2742	0.2951	0.2955

 $C_p = 0.2468$ at 191.069°C

(Cont'd)

APPENDIX TABLE VII (CONT'D)

Run No.	25a	25b	25c	25d	25e*	25f
Current, amps	0.18912	0.18905	0.18901	0.18906	0.21403	0.21402
Voltage drop, volts	2.0282	2.0277	2.0269	2.0272	2.2951	0.2952
Temp of bath, °C	190.319	190.396	190.337	190.356	190.361	190.357
μ_c , mv/°C	0.26412	0.26414	0.26413	0.26413	0.26413	0.26413
ΔE_c , mv	-0.0986	-0.0917	-0.0764	-0.0768	-0.0733	-0.0663
ΔT_c , °C	-0.373	-0.347	-0.289	-0.291	-0.278	-0.251
μ , mv/°C	0.26507	0.26506	0.26487	0.26488	0.26492	0.26494
ΔE , mv	1.5811	1.5129	1.2323	1.2400	1.3093	1.3350
ΔT , °C	5.965	5.708	4.653	4.681	4.942	5.039
T_m , °C	193.302	193.250	192.664	192.597	192.832	192.877
F, grs/sec	0.048495	0.053048	0.066276	0.065724	0.070143	0.079731
C_{pobs} , cal/gr, °C	0.2982	0.2852	0.2795	0.2803	0.3206	0.2783

$C_p = 0.2469$ at 192.937°C *not included in calc of C_p

142

Run No.	26a	26b	26c	26d
Current, amps	0.21154	0.21151	0.18488	0.18496
Voltage drop, volts	2.2886	2.2884	2.0012	2.0008
Temp of bath, °C	236.761	236.864	236.935	236.906
μ_c , mv/°C	0.27839	0.27842	0.27844	0.27843
ΔE_c , mv	-0.0615	-0.0615	-0.0650	-0.0648
ΔT_c , °C	-0.221	-0.221	-0.233	-0.233
μ , mv/°C	0.27908	0.27914	0.27915	0.27919
ΔE , mv	1.3223	1.3874	1.3573	1.4286
ΔT , °C	4.738	4.970	4.862	5.117
T_m , °C	239.130	239.349	239.366	239.465
F, grs/sec	0.081143	0.080955	0.057450	0.058144
C_{pobs} , cal/gr, °C	0.2875	0.2752	0.3020	0.2843

$C_p = 0.2511$ at 239.328°C

(Cont'd)

APPENDIX TABLE VII (CONT'D)

Run No.	27a	27b	27c	27d	27e	27f
Current, amps	0.18474	0.18482	0.18478	0.18470	0.20786	0.20769
Voltage drop, volts	2.0000	2.0009	2.0000	1.9997	2.2503	2.2486
Temp of bath, °C	236.946	236.955	236.919	236.912	236.914	236.958
μ_c , mv/°C	0.27845	0.27845	0.27844	0.27844	0.27844	0.27843
ΔE_c , mv	-0.0776	-0.0802	-0.0669	-0.0650	-0.0560	-0.0560
ΔT_c , °C	-0.279	-0.288	-0.240	-0.233	-0.201	-0.201
μ , mv/°C	0.27923	0.27926	0.27908	0.27908	0.27911	0.27912
ΔE , mv	1.4873	1.5354	1.2359	1.2298	1.2908	1.2800
ΔT , °C	5.326	5.498	4.428	4.407	4.625	4.586
T_m , °C	239.609	239.704	239.133	239.116	239.227	239.251
F, grs/sec	0.047462	0.045364	0.058982	0.061573	0.078259	0.077828
C_{pobs} , cal/gr, °C	0.3319	0.3368	0.3207	0.3089	0.2959	0.2995

$$C_p = 0.2439 \text{ at } 239.340^\circ\text{C}$$

143

Run No.	28a	28b	28c	28d	28e	28f
Current, amps	0.19555	0.19579	0.22492	0.22498	0.17433	0.17573
Voltage drop, volts	2.0862	2.0884	2.3984	2.3990	1.8587	1.8733
Temp of bath, °C	139.320	139.237	139.182	139.149	139.149	139.112
μ_c , mv/°C	0.24706	0.24703	0.24701	0.24700	0.24700	0.24698
ΔE_c , mv	-0.1368	-0.1341	-0.1237	-0.1232	-0.1400	-0.1400
ΔT_c , °C	-0.554	-0.543	-0.501	-0.499	-0.567	-0.567
μ , mv/°C	0.24808	0.24804	0.24805	0.24804	0.24792	0.24792
ΔE , mv	1.4481	1.4363	1.4883	1.4812	1.3134	1.3334
ΔT , °C	5.837	5.791	6.000	5.972	5.298	5.378
T_m , °C	142.239	142.133	142.182	142.135	141.798	141.801
F, grs/sec	0.050878	0.054207	0.073353	0.074178	0.047536	0.047535
C_{pobs} , cal/gr, °C	0.2998	0.2846	0.2703	0.2687	0.2777	0.2784

$$C_p = 0.2457 \text{ at } 142.048^\circ\text{C}$$

(Cont'd)

APPENDIX TABLE VII (CONT'D)

Run No.	29a	29b	29c	29d	29e	29f
Current, amps	0.18146	0.18156	0.21235	0.21243	0.24402	0.24407
Voltage drop, volts	1.9378	1.9394	2.2660	2.2678	2.6066	2.6066
Temp of bath, °C	149.484	149.434	149.428	149.443	149.422	149.421
μ_c , mv/°C	0.25058	0.25056	0.25056	0.25056	0.25055	0.25055
ΔE_c , mv	-0.1501	-0.1504	-0.1157	-0.1160	-0.1036	-0.1034
ΔT_c , °C	-0.599	-0.600	-0.462	-0.463	-0.413	-0.413
μ , mv/°C	0.25139	0.25137	0.25139	0.25138	0.25150	0.25148
ΔE , mv	1.1917	1.1911	1.2183	1.2032	1.3572	1.3683
ΔT , °C	4.740	4.738	4.846	4.786	5.396	5.441
T_m , °C	151.854	151.803	151.851	151.836	152.120	152.142
F, grs/sec	0.055570	0.055396	0.081370	0.081087	0.097532	0.097835
C_{pobs} , cal/gr, °C	0.2832	0.2845	0.2662	0.2705	0.2683	0.2654

 $C_p = 0.2419$ at 151.934°C

Run No.	30a	30b	30c	30d	30e	30f
Current, amps	0.24344	0.24370	0.20890	0.20880	0.18688	0.18688
Voltage drop, volts	2.6048	2.6074	2.2340	2.2332	1.9990	1.9990
Temp of bath, °C	160.697	160.679	160.715	160.670	160.674	160.657
μ_c , mv/°C	0.25439	0.25438	0.25439	0.25437	0.25438	0.25437
ΔE_c , mv	-0.1068	-0.1067	-0.1092	-0.1086	-0.1119	-0.1118
ΔT_c , °C	-0.420	-0.419	-0.429	-0.427	-0.440	-0.440
μ , mv/°C	0.25533	0.25531	0.25523	0.25517	0.25515	0.25514
ΔE , mv	1.4244	1.4195	1.2656	1.2044	1.1779	1.1692
ΔT , °C	5.579	5.560	4.959	4.720	4.617	4.583
T_m , °C	163.487	163.459	163.195	163.030	162.983	162.949
F, grs/sec	0.091734	0.092923	0.074370	0.078902	0.061730	0.062186
C_{pobs} , cal/gr, °C	0.2753	0.2733	0.2783	0.2744	0.2860	0.2858

 $C_p = 0.2486$ at 163.184°C

APPENDIX F

RESULTS OF GRAPHICAL INTEGRATION FOR THE EFFECT OF PRESSURE ON THE ENTHALPY AND ENTROPY

The change of enthalpy with pressure at constant temperature, $(dH/dP)_T$, was determined by graphical integration of the equation,

$$(dH/dP)_T = 24.206 \int_{P=1}^P [T(\partial \alpha / \partial T)_P - \alpha] dP.$$

The results of this integration are presented in Appendix Table VIII with the enthalpy change in calories per mole listed for increments of one atmosphere up to 44 atmospheres over the temperature range from 160 to 300°C.

Appendix Table IX presents the effect of pressure on the entropy at constant temperature, $(dS/dP)_T$, as was determined by the graphical integration of the equation,

$$(dS/dP)_T = 24.206 \int_{P=1}^P [R/P - (\partial \alpha / \partial T)_P] dP.$$

The pressure effect on the entropy is given in calories per mole per degrees Kelvin for pressure increments of one atmosphere up to 44 atmospheres for temperatures from 160 to 300°C.

APPENDIX TABLE VIII

PRESSURE EFFECT ON THE ENTHALPY OF PERFLUORO-2-BUTYL-
TETRAHYDROFURAN IN CALORIES/MOLE

Press Atm	160 °C	170 °C	180 °C	190 °C	200 °C
1	0	0	0	0	0
2	154	140	128	119	113
3	337	305	271	249	235
4	552	500	432	392	367
5		730	617	549	511
6			837	729	669
7			1098	941	843
8				1195	1041
9					1267
10					1528

(Cont'd)

APPENDIX TABLE VIII (CONT'D)

Press Atm	210 °C	220 °C	230 °C	240 °C	250 °C
1	0	0	0	0	0
2	106	99	88	79	72
3	218	203	182	165	153
4	338	312	282	257	239
5	466	425	386	354	331
6	603	545	495	455	426
7	754	672	611	562	526
8	920	809	735	676	629
9	1106	960	867	796	738
10	1315	1127	1009	924	852
11	1553	1315	1164	1059	974
12	1828	1527	1336	1205	1103
13		1771	1530	1364	1239
14			1762	1545	1384
15			2078	1762	1541
16			2652	2030	1719
17			3595	2374	1936
18			3923	2811	2204
19			4086	3356	2547
20			4189	3878	3009
21			4268	4133	3488
22			4331	4294	3870

(Cont'd)

APPENDIX TABLE VIII (CONT'D)

Press Atm	210 °C cont'd	220 °C cont'd	230 °C cont'd	240 °C cont'd	250 °C cont'd
23			4381	4422	4143
24			4423	4526	4332
25			4459	4609	4473
26			4491	4677	4585
27			4520	4733	4680
28			4547	4782	4762
29			4572	4825	4831
30			4595	4864	4893
31			4617	4898	4947
32			4638	4929	4993
33			4659	4957	5032
34			4679	4983	5065
35			4698	5002	5093
36			4717	5021	5116
37			4735	5039	5136
38			4753	5057	5154
39			4770	5075	5172
40			4787	5091	5188
41			4803	5107	5204
42			4818	5122	5219
43			4832	5137	5234
44			4846	5150	5247

(Cont'd)

APPENDIX TABLE VIII (CONT'D)

Press Atm	260 °C	270 °C	280 °C	290 °C	300 °C
1	0	0	0	0	0
2	59	48	40	36	34
3	129	109	95	87	82
4	208	181	161	150	141
5	295	261	235	220	208
6	385	345	313	296	280
7	477	433	393	374	354
8	573	522	476	454	430
9	672	614	562	536	507
10	775	708	650	620	586
11	882	806	741	707	668
12	995	908	835	795	751
13	1113	1014	932	886	836
14	1237	1125	1032	979	924
15	1366	1239	1135	1075	1014
16	1501	1356	1241	1174	1107
17	1642	1477	1348	1276	1203
18	1786	1599	1462	1382	1303
19	1936	1723	1581	1492	1407
20	2100	1854	1703	1604	1514
21	2287	1994	1828	1720	1626
22	2513	2145	1957	1839	1741

(Cont'd)

APPENDIX TABLE VIII (CONT'D)

Press Atm	260 °C cont'd	270 °C cont'd	280 °C cont'd	290 °C cont'd	300 °C cont'd
23	2767	2303	2089	1962	1858
24	3023	2465	2225	2088	1979
25	3265	2629	2362	2217	2103
26	3481	2791	2500	2346	2228
27	3661	2950	2636	2476	2354
28	3803	3105	2771	2604	2479
29	3913	3251	2903	2732	2603
30	4002	3382	3031	2857	2724
31	4078	3492	3154	2979	2841
32	4146	3588	3267	3097	2954
33	4207	3674	3369	3208	3062
34	4261	3753	3460	3311	3164
35	4309	3825	3545	3403	3259
36	4351	3891	3624	3487	3348
37	4387	3950	3696	3565	3430
38	4419	4003	3763	3638	3507
39	4448	4052	3824	3706	3580
40	4473	4096	3880	3769	3647
41	4497	4138	3932	3828	3710
42	4519	4176	3980	3882	3769
43	4540	4212	4023	3932	3824
44	4559	4246	4063	3977	3875

APPENDIX TABLE IX
PRESSURE EFFECT ON THE ENTROPY OF PERFLUORO-2-BUTYL-
TETRAHYDROFURAN IN CALORIES/MOLE, °K

Press Atm	160 °C	170 °C	180 °C	190 °C	200 °C
1	0	0	0	0	0
2	1.614	1.558	1.551	1.544	1.543
3	2.782	2.658	2.628	2.600	2.585
4	3.781	3.573	3.491	3.430	3.393
5		4.442	4.268	4.148	4.050
6		5.370	5.039	4.831	4.679
7			5.846	5.519	5.290
8				6.258	5.912
9					6.568
10					7.257

(Cont'd)

APPENDIX TABLE IX (CONT'D)

Press Atm	210 °C	220 °C	230 °C	240 °C	250 °C
1	0	0	0	0	0
2	1.542	1.508	1.479	1.467	1.430
3	2.574	2.509	2.448	2.417	2.358
4	3.366	3.279	3.190	3.140	3.065
5	4.015	3.917	3.804	3.741	3.655
6	4.608	4.492	4.346	4.269	4.167
7	5.171	5.024	4.839	4.744	4.629
8	5.724	5.526	5.303	5.186	5.061
9	6.291	6.015	5.754	5.609	5.470
10	6.890	6.512	6.202	6.024	5.864
11	7.529	7.033	6.654	6.437	6.248
12	8.210	7.591	7.121	6.853	6.626
13		8.189	7.615	7.281	7.005
14			8.170	7.736	7.392
15			8.875	8.243	7.792
16			10.031	8.846	8.213
17			11.833	9.593	8.698
18			12.479	10.520	9.309
19			12.837	11.752	10.115
20			13.071	12.932	11.153
21			13.251	13.538	12.223
22			13.401	13.913	13.101

(Cont'd)

APPENDIX TABLE IX (CONT'D)

Press Atm	210 °C cont'd	220 °C cont'd	230 °C cont'd	240 °C cont'd	250 °C cont'd
23			13.529	14.191	13.695
24			13.640	14.417	14.080
25			13.740	14.599	14.367
26			13.828	14.752	14.601
27			13.910	14.885	14.800
28			13.986	15.001	14.974
29			14.059	15.105	15.131
30			14.129	15.200	15.269
31			14.197	15.290	15.396
32			14.262	15.372	15.509
33			14.325	15.447	15.608
34			14.385	15.517	15.695
35			14.443	15.580	15.770
36			14.499	15.639	15.838
37			14.554	15.695	15.898
38			14.608	15.749	15.954
39			14.661	15.801	16.007
40			14.712	15.852	16.058
41			14.762	15.902	16.107
42			14.810	15.951	16.156
43			14.856	15.997	16.202
44			14.902	16.043	16.248

(Cont'd)

APPENDIX TABLE IX (CONT'D)

Press Atm	260 °C	270 °C	280 °C	290 °C	300 °C
1	0	0	0	0	0
2	1.394	1.386	1.383	1.383	1.383
3	2.304	2.288	2.276	2.271	2.271
4	2.999	2.972	2.956	2.942	2.940
5	3.574	3.536	3.510	3.488	3.482
6	4.071	4.025	3.986	3.955	3.941
7	4.516	4.458	4.411	4.368	4.346
8	4.925	4.855	4.801	4.749	4.715
9	5.309	5.228	5.163	5.103	5.056
10	5.678	5.581	5.506	5.434	5.378
11	6.034	5.924	5.838	5.752	5.683
12	6.383	6.259	6.157	6.057	5.973
13	6.731	6.588	6.467	6.351	6.253
14	7.077	6.912	6.767	6.637	6.524
15	7.421	7.231	7.062	6.917	6.789
16	7.765	7.544	7.353	7.193	7.052
17	8.111	7.854	7.638	7.465	7.314
18	8.459	8.161	7.926	7.736	7.575
19	8.815	8.465	8.215	8.007	7.837
20	9.182	8.769	8.503	8.279	8.098
21	9.591	9.087	8.792	8.554	8.360
22	10.066	9.423	9.277	8.830	8.626

(Cont'd)

APPENDIX TABLE IX (CONT'D)

Press Atm	260 °C cont'd	270 °C cont'd	280 °C cont'd	290 °C cont'd	300 °C cont'd
23	10.586	9.771	9.570	9.108	8.894
24	11.105	10.120	9.865	9.389	9.166
25	11.595	10.467	10.161	9.670	9.438
26	12.033	10.810	10.451	9.948	9.707
27	12.382	11.144	10.738	10.223	9.976
28	12.664	11.465	11.021	10.493	10.242
29	12.896	11.764	11.296	10.762	10.502
30	13.094	12.032	11.562	11.022	10.758
31	13.269	12.262	11.804	11.273	11.013
32	13.423	12.465	12.029	11.517	11.265
33	13.561	12.648	12.237	11.749	11.509
34	13.684	12.816	12.431	11.960	11.737
35	13.795	12.971	12.612	12.153	11.944
36	13.894	13.115	12.779	12.332	12.134
37	13.982	13.237	12.934	12.499	12.311
38	14.061	13.361	13.079	12.656	12.476
39	14.133	13.475	13.214	12.803	12.630
40	14.201	13.579	13.337	12.942	12.777
41	14.264	13.675	13.452	13.073	12.917
42	14.324	13.764	13.558	13.194	13.049
43	14.383	13.849	13.657	13.308	13.175
44	14.441	13.931	13.750	13.412	13.293

BIBLIOGRAPHY

CALORIMETERY

- Bennewitz, K., and Rossner, W., Z. Physik. Chem., B39, 126 (1938).
- Burlew, J. S., and Smith, R. P., J. Am. Chem. Soc., 65, 803 (1943).
- Coleman, C. F., and DeVries, T., J. Am. Chem. Soc., 71, 2839 (1949).
- Masi, J. F., Trans. Am. Soc. Mech. Engrs., 76, 1067 (1954).
- Montgomery, J. B., and Devries, T., J. Am. Chem. Soc., 64, 2372 (1942).
- Montgomery, J. B., and DeVries, T., J. Am. Chem. Soc., 64, 2375 (1942).
- Pitzer, K. S., J. Am. Chem. Soc., 63, 2413 (1941).
- Pitzer, K. S., J. Am. Chem. Soc., 65, 803 (1943).
- Scott, D. W., Waddington, G., Smith, J. C., and Huffman, H. M., J. Chem. Phys., 15, 565 (1947).
- Sinke, G. C., and DeVries, T., J. Am. Chem. Soc., 75, 1815 (1953).

FLUOROCARBONS

- Bondi, A., J. Phys. and Colloid Chem., 55, 1355-68 (1951).
- Oliver, G. D., and Grisard, J. W., J. Am. Chem. Soc., 75, 1688 (1951).
- Stiles, V. E., and Cady, G. H., J. Am. Chem. Soc., 74, 37771-3 (1952).

PHYSICAL PROPERTIES OF $C_8F_{16}O$

- Green, Robert C., "Measurement of Liquid Heat Capacities by the Adiabatic Expansion Technique," Master's Thesis, Ohio State University, 1957.

Leverett, Glen F., "Low Pressure Compressibilities of Vapors," Master's thesis, Ohio State University, 1958.

Minnesota Mining and Manufacturing Company, New Products Division, Circular, "Fluorochemical O-75," St. Paul, Minnesota.

Throckmorton, Robert D., "Pressure, Volume, and Temperature Relationships for Perfluoro-3-butyl-tetrahydrofuran," Master's thesis, Ohio State University, 1957.

Yarrington, Robert M., "The Heat Capacities of Fluorocarbons," Master's thesis, Ohio State University, 1956.

THERMODYNAMIC CALCULATIONS

Benning, A. F., and McHarness, R. C., Ind. Eng. Chem., 31, 912 (1939).

Deming, W. E., and Shupe, L. E., Phys. Rev., 37, 638-654 (1931).

Dodge, B. F., Chemical Engineering Thermodynamics. New York: McGraw-Hill Book Company, 1940, pp. 257-260.

AUTOBIOGRAPHY

I, Robert M. Yarrington, was born in York Center, Ohio, September 26, 1928. I received my secondary school education at York Local School, and my undergraduate training at Ohio State University, which granted me the Bachelor of Science degree in 1951. I received the degree Master of Science from Ohio State University in 1956. While working toward this degree, I was the Ethyl Corporation Fellow in the Department of Chemical Engineering. In October, 1955, I was appointed American Cyanamid Fellow in the Department of Chemical Engineering, and I held this position for two years while completing the requirements for the degree Doctor of Philosophy.