71-27,524

MILLER, Roy William, 1940-
ANALYSIS OF UNSTEADY LAMINAR BOUNDARY LAYER
FLOW BY AN INTEGRAL METHOD.

The Ohio State University, Ph.D., 1971
Engineering, mechanical

University Microfilms, A XEROX Company, Ann Arbor, Michigan

ANALYSIS OF UNSTEADY LAMINAR BOUNDARY
LAYER FLOW BY AN INTEGRAL METHOD

DISSERTATION

Presented in Partial Fulfillment of the Requirements for
the Degree of Doctor of Philosophy in the Graduate
School of The Ohio State University

By

Roy W. Miller, B.S.M.E., M.S.M.E.

* * * * *

The Ohio State University
1971

Approved by

A handwritten signature in black ink, appearing to read "L. A. Han", is written over a horizontal line.

Advisor
Department of Mechanical Engineering

ACKNOWLEDGMENTS

I wish to express my appreciation to my advisor, Professor L. S. Han for his assistance during the course of this research and for his continuing guidance and instruction throughout the past years.

I also wish to thank the Lewis Research Center of the National Aeronautics and Space Administration who generously supported this work. Particular thanks to Dr. Robert Siegel for his interest and encouragement.

Finally, I wish to express my deepest thanks to my wife Diane for her help during my doctoral studies.

VITA

June 7, 1940 . . . Born - Boston, Massachusetts

1962 B.S.M.E., Northeastern University, Boston,
Massachusetts

1962-1968 Design Engineer, NASA Lewis Research Center,
Cleveland, Ohio

1966 M.S.M.E., Case Institute of Technology,
Cleveland, Ohio

1968-1971 Graduate Student, Mechanical Engineering
Department, The Ohio State University,
Columbus, Ohio

1969-1971 Research Engineer, NASA Lewis Research Center,
Cleveland, Ohio

PUBLICATIONS

- P. C. Lu, and R. W. Miller, "An Equitriangular Transform and Its Application", Journal of Applied Mechanics, Vol. 34, No. 2, June 1967.
- "Transient Heat Conduction in Finite Slabs with Position-Dependent Heat Generation", NASA Technical Memorandum, TM-X-1442, October 1967.
- R. W. Miller, and L. S. Han, "Pressure Losses For Laminar Flow in the Entrance Region of Ducts of Rectangular and Equilateral Triangular Cross Section", Journal of Applied Mechanics, BN 69-510, in print.

FIELDS OF STUDY

Major Field: Mechanical Engineering

Studies in Fluid Mechanics, Professor L. S. Han

Studies in Aerodynamics, Professors T. Y. Li and R. Edse

Studies in Applied Mathematics. Professor H. Colson

TABLE OF CONTENTS

	Page
ACKNOWLEDGMENTS.....	ii
VITA.....	iii
LIST OF ILLUSTRATIONS.....	vii
LIST OF TABLES.....	ix
SYMBOLS.....	x
Chapter	
I. INTRODUCTION.....	1
II. INTEGRAL ANALYSIS OF THE UNSTEADY BOUNDARY LAYER.....	5
2.1 Governing equations.....	5
2.2 Asymptotic solutions.....	10
2.2.1 Low-frequency (quasi-steady) solution.....	10
2.2.2 High-frequency (Stokes) solution.....	11
2.3 The integral method.....	12
2.3.1 Integral relations.....	15
2.3.2 Compatibility conditions.....	18
2.4 Profile forms.....	20
2.5 Approximation of the Blasius profile.....	21
III. UNSTEADY FLOW OVER A FLAT PLATE WITH OSCILLATING FREE-STREAM.....	33
3.1 Quasi-steady limit.....	33
3.2 Form parameters.....	40
3.2.1 Governing equations.....	40
3.2.2 Solution.....	46
3.3 Velocity profiles.....	53
3.2.1 Profile results.....	53
3.2.2 Wall shear stress.....	61

IV.	EFFECT OF OSCILLATIONS ON TIME-AVERAGE BOUNDARY LAYER FLOW.....	65
4.1	Governing equations.....	65
4.2	Quasi-steady limit.....	70
4.2.1	Four parameter profiles.....	73
4.2.2	Five parameter profiles.....	74
4.3	Form parameters.....	79
4.3.1	Governing equations.....	79
4.3.2	Solution.....	87
4.3.3	Velocity profiles.....	88
V.	SUMMARY AND CONCLUSIONS.....	91
APPENDICES		
A	DERIVATION OF THE GENERAL INTEGRAL RELATIONS.....	93
B	CURVE FIT BY METHOD OF LEAST SQUARES.....	95
C	METHOD OF SOLUTION FOR SYSTEMS OF NONLINEAR ALGEBRAIC EQUATIONS.....	97
D	FOURTH-ORDER RUNGE-KUTTA INTEGRATION FORMULAS.....	100
BIBLIOGRAPHY.....		102

LIST OF ILLUSTRATIONS

Figure	Page
1. Flat plate boundary layer configuration and nomenclature.....	6
2. First-order quasi-steady velocity profile.....	13
3. Stokes velocity profile.....	14
4. Quasi-steady profile approximations by least square fit for flat plate boundary layer with oscillating free-stream.....	22
5. Three parameter profile approximations for the Blasius profile.....	30
6. Four parameter profile approximations for the Blasius profile.....	31
7. Quasi-steady profile approximations for flat plate boundary layer with oscillating free-stream.....	38
8. First-order velocity profile form parameter real parts for flat plate boundary layer with oscillating free-stream.....	51
9. First-order velocity profile form parameter imaginary parts for flat plate boundary layer with oscillating free-stream.....	52
10. Development of in-phase velocity component along flat plate with oscillating free-stream.....	55
11. Development of phase angle between in-phase and out-of-phase velocity components along flat plate with oscillating free-stream.....	56
12. Development of in-phase velocity component along flat plate with oscillating free-stream.....	57

Figure		Page
13.	Development of phase angle between in-phase and out-of-phase velocity components along flat plate with oscillating free-stream.....	58
14.-19.	Development of in-phase velocity component along flat plate with oscillating free stream.....	59
20.-24.	Development of phase angle between in-phase and out-of-phase velocity components along flat plate with oscillating free-stream.....	60
25.	Real part of first-order wall shear stress coefficient for flat plate boundary layer with oscillating free-stream.....	63
26.	Imaginary part of first-order wall shear stress coefficient for flat plate boundary layer with oscillating free-stream.....	63
27.	Phase advance of first-order wall shear stress relative to free-stream oscillations for flat plate boundary layer.....	64
28.	Development of first-order "driving" terms in second-order momentum equation.....	69
29.	Second-order quasi-steady velocity profile approximations for flat plate boundary layer with oscillating free-stream.....	72
30.	Second-order velocity profile form parameters for flat plate boundary layer with oscillating free-stream.....	89
31.	Steady second-order velocity parallel to flat plate with oscillating free-stream.....	90
32.	Linear approximation for a nonlinear function of one variable.....	99
33.	Linear approximation for a nonlinear function of two variables.....	99

LIST OF TABLES

Table		Page
1.	Form parameters for Blasius profile approximation based on combinations of integral relations and compatibility conditions.....	29
2.	Comparison of four parameter profile approximation, based on three integral relations and one compatibility condition, with the Blasius profile.....	32
3.	Form parameters for quasi-steady profile approximation based on combinations of integral relations and compatibility conditions.....	37
4.	Comparison of four parameter profile approximation, based on three integral relations and one compatibility condition, with the quasi-steady expansion profile.....	39
5.	Summary of integration procedure for first-order velocity profile form parameters for flat plate boundary layer with oscillating free-stream.....	50
6.	Comparison of five parameter profile approximation, based on three integral relations and two compatibility conditions, with the Blasius profile.....	78

SYMBOLS

a	first-order quasi-steady profile factor
$\tilde{a}$	complex attenuation factor, equation (2.58)
$\bar{a}$	imaginary coefficient in α expansion, equation (3.60)
A	Blasius profile approximation form factor
$\bar{A}$	constant, Appendix B
b	first-order quasi-steady profile factor
$\bar{b}$	imaginary coefficient in β expansion, equation (3.61)
B	Blasius profile approximation form factor
B_1	constant, Appendix B
c	first-order quasi-steady profile factor
C	Blasius profile approximation form factor
C_1	constants, Appendix B
C_0	constant, equation (2.83)
C_τ	first-order wall shear stress coefficient, equation (3.69)
d	first-order quasi-steady profile factor
$\bar{d}$	imaginary coefficient in δ expansion, equation (3.62)
D	Blasius profile approximation form factor
D_1	difference, Appendix B
E	Blasius profile approximation form factor
E_0	error, Appendix B
f	velocity profile summation function, equation (2.78)
F	velocity profile summation function, equation (4.55)
F_B	Blasius flow dimensionless stream function

$\overline{F}$	constant defined by equation (4.73)
g	general function of F_2 , equation (3.26)
g_1	functions, Appendix C
h	velocity profile approximation matrix, equation (2.80)
H	velocity profile approximation matrix, equation (3.27)
I_1	integrals, Appendix A
k_1	Runge-Kutta functions, Appendix D
l_1	Runge-Kutta functions, Appendix D
m_1	Runge-Kutta functions, Appendix D
M	functions in example expansion, equation (4.34)
p	second-order quasi-steady profile factor, equation (4.22)
P	pressure
P_{1j}	coefficients in differential equations (3.38) through (3.40)
$\overline{P}_{1j}$	coefficients in differential equations (4.58) through (4.60)
q_1	second-order quasi-steady profile factors, equation (4.22)
R_1	terms in differential equations (3.38) through (3.40)
$\overline{R}_1$	terms in differential equations (4.58) through (4.60)
s	attenuation matrix, equation (2.79)
S	attenuation matrix, equation (3.36)
t	dimensionless time, ωT
T	time
u	dimensionless velocity component parallel to the body, U/U_0

$\bar{u}_2$	time-independent part of second-order velocity, equation (4.9)
$\tilde{u}_2$	time-dependent part of second-order velocity, equation (4.9)
U	velocity component parallel to the body
U_0	mean value of free-stream velocity
v	dimensionless velocity component normal to the body, $v / \sqrt{\omega v}$
$\bar{v}_2$	time-independent part of second-order velocity, equation (2.10)
$\tilde{v}_2$	time-dependent part of second-order velocity, equation (2.10)
V	velocity component normal to the body
w	complex function
w^*	complex conjugate of w
x	dimensionless coordinate along the body, $\omega X / U_0$
X	coordinate along the body
y	dimensionless coordinate normal to the body, $\sqrt{\frac{\omega}{v}} Y$
Y	coordinate normal to the body
z_1	coordinates, Appendix B
Z	dummy variable, equation (2.83)

Greek letters

α	first-order velocity profile form function
β	first-order velocity profile form function
γ	first-order velocity profile form function

δ	first-order velocity profile form function
Δ	increment in Runge-Kutta integration formulas, Appendix D
ϵ	amplitude of harmonic free-stream velocity fluctuation
ζ	stretched coordinate, $\sqrt{x}$
η	similarity variable, y/ζ
θ_1	differential functions, equations (3.53) through (3.55)
$\bar{\theta}_1$	differential functions, equations (4.74) through (4.76)
ν	kinematic viscosity
ρ	density
ϕ	second-order velocity profile form function
ϕ_τ	phase angle of first-order wall shear stress coefficient, equation (3.70)
ψ_1	second-order velocity profile form functions
ω	frequency of harmonic free-stream fluctuations

Subscripts

B	Blasius flow value
i	imaginary part
q	quasi-steady approximation value
Q	quasi-steady expansion value
r	real part
S	Stokes flow value
0	zeroth-order (ϵ^0) value
1	first-order (ϵ^1) value
2	second-order (ϵ^2) value
∞	free stream value

Special symbols

$F(I,J,K,L)$ integration summation function, equation (2.89)

$G(I,J,K,L)$ integration summation function, equation (3.35)

$\text{Re}\{\}$ real part

$\text{Im}\{\}$ imaginary part

CHAPTER I

INTRODUCTION

Unsteady fluid motions have attracted the attention of researchers for many years. Several excellent summaries of the state of the theory have been prepared. These include the summaries by Schlichting (1)¹, Rott (2), Stuart (3), and Stewartson (4). There is also a large body of work dealing with specific cases of unsteady flows.

The problem area which has generated the most interest is the unsteady laminar boundary layer flow. The work of Moore in 1951 (5) first pointed out the relevant parameters and the conditions under which the flow may be considered quasi-steady.

Another important early contribution was made by Lighthill - 1954 (6). That analysis deals with the incompressible flow boundary layer when the external flow magnitude makes a small harmonic fluctuation about a steady mean value. Lighthill assumed that all flow quantities perform small oscillations about a steady mean. The equations governing the first-order fluctuations were then solved for the limiting cases of high-frequency and low-frequency free-stream fluctuations. For the low-frequency case the correction to the quasi-steady flow was obtained by a Kármán-Pohlhausen method. High-frequency fluctuations

¹Numbers in parenthesis refer to references in the Bibliography.

were found to produce "shear-waves" identical to the boundary layer with external flow fluctuations about a zero mean (so called Stokes flow).

The effect of compressibility was considered by Ostrach (7), for nearly quasi-steady flow, and the time-average correction to the quasi-steady flow was computed by Moore and Ostrach (8). Limiting cases for the compressible boundary layer on a flat plate with free stream fluctuations were also analyzed by Illingworth (9). Other early analysis include: The flow normal to a fluctuating plate by Glauert (10), and the boundary layer on a flat plate with suction and free stream oscillations by Stuart (11).

The method of Lighthill was later extended by Rott and Rosenzweig (12). In that work, the velocity is formally expanded in powers of the frequency parameter for near quasi-steady flow, and in inverse powers of the frequency for high frequency oscillations. Questions of validity and convergence of such a series expansion are raised but not answered. Other asymptotic analyses of boundary layers with free stream oscillations were performed by Lin (13), Nickerson (14), Kestin, Maeder, and Wang (15), and Gersten (16).

A most significant experimental study of the laminar boundary layer in oscillatory flow was conducted by Hill and Stenning (17). Velocity measurements were made for the flow of air over flat plates and wedges. Results for the unsteady velocity magnitude and phase shift are presented for a wide range of the frequency parameter.

Recent research in unsteady boundary layer flow has been motivated by several important physical problems. Helicopter rotor blades in forward flight experience a main flow, due to the blade rotation, plus

a small velocity fluctuation caused by the change in blade orientation with respect to the flight direction. This flow situation has prompted the analyses of McCrosky and Yaggy (18), Illingworth (19), and Young and Williams (20).

The mass transport due to progressing water waves was studied in detail by Longuet-Higgins in 1953 (21). The surface wave phenomena results in a second-order drift velocity in the fluid interior. Recent interest in this unsteady flow situation has been expressed by the analyses of Johns (22), and Moore (23).

The integral method of analysis has had widespread application in analytical fluid mechanics (c.f. Schlichting (v) and Walz (24)). The method has been used for computing internal flows by Han (25), and Han and Cooper (26), by using exponential type velocity profiles. The use of the exponential expression obviates the definition of a discrete boundary layer thickness. Important contributions to the integral analysis of boundary layer flows were made by Tani (27) and Head (28).

The integral method was first applied to an unsteady flow by Siegel (29), who studied the transient free convection from a vertical flat plate. The non-stationary laminar boundary layer flow was given general consideration by Rozin (30). Recently, Akamatsu (31), performed an integral analysis of the boundary layer on a flat plate which is set impulsively in motion.

In this work, we investigate the general integral method of analysis for unsteady laminar boundary layer flows. The case of incompressible laminar flow over a flat plate in an oscillating stream is treated in detail and exponential forms for the velocity profiles are

utilized. The velocity fluctuations are computed and compared with the experimental results of Hill and Stenning. The steady contribution to the mean flow is also computed for this case. Based on this example, some general observations can be made about integral analysis of unsteady boundary layer flows.

CHAPTER II

INTEGRAL ANALYSIS OF THE UNSTEADY LAMINAR BOUNDARY LAYER

The integral analysis of unsteady laminar boundary layer flow is formulated for the case of incompressible flow over a flat plate. The free-stream time dependence considered is that of small harmonic fluctuations superimposed on a uniform stream parallel to the plate surface. The essential features of the integral method of analysis are clearly exhibited by considering the special case. Compressibility effects, spacially varying pressure gradient, and other free-stream temporal variations can later be included in the development.

2.1. Governing equations

Referring to Figure 1, consider the two-dimensional incompressible flow over a flat plate. The free-stream flow is parallel to the plate and the free stream velocity depends only on time. Then, the boundary layer equations are:

$$\frac{\partial U}{\partial X} + \frac{\partial V}{\partial Y} = 0 \quad (2.1)$$

$$\frac{\partial U}{\partial T} + U \frac{\partial U}{\partial X} + V \frac{\partial U}{\partial Y} = \nu \frac{\partial^2 U}{\partial Y^2} - \frac{1}{\rho} \frac{\partial P}{\partial X} \quad (2.2)$$

$$\frac{\partial P}{\partial Y} = 0 \quad (2.3)$$

The boundary conditions of no-slip and impermeability at the plate surface are

Figure 1. - Flat plate boundary layer configuration and nomenclature.

$$U(X,0,T) = 0 \quad (2.4)$$

$$V(X,0,T) = 0 \quad (2.5)$$

The imposed pressure gradient is determined by evaluating the momentum equation (2.2) at the free-stream. Since,

$$U(X,Y,T) \rightarrow U_{\infty}(T) \quad \text{as} \quad Y \rightarrow \infty \quad (2.6)$$

it follows from equations (2.2) and (2.3) that throughout the entire flow field we have

$$-\frac{1}{\rho} \frac{\partial P}{\partial X} = \frac{\partial U_{\infty}}{\partial T} \quad (2.7)$$

We consider the case of a free-stream velocity which makes a small harmonic fluctuation about a steady mean value U_0 . For oscillations of frequency ω and amplitude ϵU_0 , we can express the free-stream velocity in the following complex form:

$$U_{\infty}(T) = U_0(1 + \epsilon e^{i\omega T}) \quad (2.8)$$

It was pointed out by Lighthill (5), that this analysis also applies to cases for which: (a) the body oscillates parallel to a steady oncoming stream; and (b) the body moves through a medium at rest with velocity U_0 plus a small harmonic fluctuation.

It is convenient to non-dimensionalize the above equations by introducing the following variables:

$$\left. \begin{aligned} u &= \frac{U}{U_0} & t &= \omega T & x &= \frac{\omega X}{U_0} \\ v &= \frac{V}{\sqrt{\omega \nu}} & y &= \sqrt{\frac{\omega}{\nu}} Y \end{aligned} \right\} \quad (2.9)$$

Then, the governing equations and boundary conditions become:

$$\left\{ \begin{array}{l} \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \end{array} \right. \quad (2.10)$$

$$\left\{ \begin{array}{l} \frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = \frac{\partial^2 u}{\partial y^2} + i\epsilon e^{it} \end{array} \right. \quad (2.11)$$

$$\left\{ \begin{array}{l} u(x, 0, t) = 0 \end{array} \right. \quad (2.12)$$

$$\left\{ \begin{array}{l} v(x, 0, t) = 0 \end{array} \right. \quad (2.13)$$

$$\left\{ \begin{array}{l} u(x, y, t) \rightarrow (1 + \epsilon e^{it}) \quad \text{as } y \rightarrow \infty \end{array} \right. \quad (2.14)$$

The mathematical form of the free-stream velocity (2.14) suggests that the flow quantities u and v be expanded in powers of ϵ . Thus, the following expansions are assumed for free-stream fluctuations of small amplitude ϵ :

$$u = u_0(x, y) + \epsilon u_1(x, y)e^{it} + \mathcal{O}(\epsilon^2) \quad (2.15)$$

$$v = v_0(x, y) + \epsilon v_1(x, y)e^{it} + \mathcal{O}(\epsilon^2) \quad (2.16)$$

where, u_1 and v_1 are complex components of velocity for fluctuations about local mean values u_0 and v_0 . Substituting these expressions into the boundary layer equations (2.10) and (2.11) and grouping like powers of ϵ yields

$$\left[\frac{\partial u_0}{\partial x} + \frac{\partial v_0}{\partial y} \right] + \epsilon e^{it} \left[\frac{\partial u_1}{\partial x} + \frac{\partial v_1}{\partial y} \right] + \mathcal{O}(\epsilon^2) = 0 \quad (2.17)$$

$$\begin{aligned} & \left[u_0 \frac{\partial u_0}{\partial x} + v_0 \frac{\partial u_0}{\partial y} - \frac{\partial^2 u_0}{\partial y^2} \right] + \epsilon e^{it} \left[i(u_1 - 1) + u_0 \frac{\partial u_1}{\partial x} \right. \\ & \quad \left. + u_1 \frac{\partial u_0}{\partial x} + v_0 \frac{\partial u_1}{\partial y} + v_1 \frac{\partial u_0}{\partial y} - \frac{\partial^2 u_1}{\partial y^2} \right] + \mathcal{O}(\epsilon^2) = 0 \end{aligned} \quad (2.18)$$

In order that the solution apply for all small but arbitrary ϵ , we require that the coefficients of ϵ^n vanish independently. We expand the boundary conditions in a similar manner and obtain the following systems of governing equations:

order ϵ^0 equations;

$$\left\{ \begin{array}{l} \frac{\partial u_0}{\partial x} + \frac{\partial v_0}{\partial y} = 0 \end{array} \right. \quad (2.19)$$

$$\left\{ \begin{array}{l} u_0 \frac{\partial u_0}{\partial x} + v_0 \frac{\partial v_0}{\partial y} = \frac{\partial^2 u_0}{\partial y^2} \end{array} \right. \quad (2.20)$$

$$\left\{ \begin{array}{l} u_0(x, 0) = 0 \end{array} \right. \quad (2.21)$$

$$\left\{ \begin{array}{l} v_0(x, 0) = 0 \end{array} \right. \quad (2.22)$$

$$\left\{ \begin{array}{l} u_0 \rightarrow 1 \quad \text{as} \quad y \rightarrow \infty \end{array} \right. \quad (2.23)$$

order ϵ^1 equations;

$$\left\{ \begin{array}{l} \frac{\partial u_1}{\partial x} + \frac{\partial v_1}{\partial y} = 0 \end{array} \right. \quad (2.24)$$

$$\left\{ \begin{array}{l} i(u_1 - 1) + u_0 \frac{\partial u_1}{\partial x} + u_1 \frac{\partial u_0}{\partial x} + v_0 \frac{\partial u_1}{\partial y} + v_1 \frac{\partial u_0}{\partial y} = \frac{\partial^2 u_1}{\partial y^2} \end{array} \right. \quad (2.25)$$

$$\left\{ \begin{array}{l} u_1(x, 0) = 0 \end{array} \right. \quad (2.26)$$

$$\left\{ \begin{array}{l} v_1(x, 0) = 0 \end{array} \right. \quad (2.27)$$

$$\left\{ \begin{array}{l} u_1 \rightarrow 1 \quad \text{as} \quad y \rightarrow \infty \end{array} \right. \quad (2.28)$$

The zeroth-order system given by equations (2.19) through (2.23) governs the boundary layer flow over a flat plate in a uniform stream.

Thus, the leading terms in the velocity expansions (2.15) and (2.16) are the well known Blasius flow velocities (u_B, v_B) for uniform free-stream velocity U_0 . This is of course a similarity solution in terms of the variable

$$\eta = \frac{y}{\sqrt{\frac{\nu X}{U_0}}} = \frac{y}{\sqrt{x}} \quad (2.29)$$

Thus, the velocity component along the plate is

$$u_B = \frac{U_B}{U_0} = F'_B(\eta) \quad (2.30)$$

where F_B is the well known Blasius stream function.

The first-order system, equations (2.24) through (2.28) will be solved by an approximate integral technique. First, however, it is beneficial to examine some asymptotic solutions to these equations. The asymptotic solutions will later provide valuable guidelines for assuming profile forms to be used in the integral analysis.

2.2 Asymptotic solutions

It will prove useful to obtain asymptotic solutions to the first-order equations (2.24) through (2.28) by considering the limiting cases of very low and very high frequency fluctuations. These high- and low-frequency asymptotic solutions have provided the leading terms in power series solutions of other investigators. Here they will indicate the limiting behaviour of solutions for the integral analysis.

2.2.1. Low-frequency (quasi-steady) solution

For the limiting case of very low frequency fluctuations, the time derivatives in the momentum equation will be negligible compared to the other terms. Thus, the problem reduces to a "quasi-steady"

flow. That is, the steady flow with free-stream velocity at any instant given by equation (2.8). In this event, the solution follows the Blasius form with the velocity component defined as follows:

$$U_Q = U_0(1 + \epsilon e^{i\omega T}) F'_B(\eta_Q) \quad (2.31)$$

where

$$\eta_Q = \frac{y}{\sqrt{\nu x}} \sqrt{U_0(1 + \epsilon e^{i\omega T})} \quad (2.32)$$

We now expand the velocity, equation (2.31), for small free-stream perturbations in a Taylor series as follows

$$U_Q = \left(U_Q \right)_{\epsilon U_0 e^{i\omega T}=0} + \epsilon U_0 e^{i\omega T} \left(\frac{dU_Q}{dU_0} \right)_{\epsilon U_0 e^{i\omega T}=0} + \dots \quad (2.33)$$

Upon carrying out the operations indicated above, we obtain

$$U_Q = U_0 F'_B(\eta) + \epsilon U_0 e^{i\omega T} \left[F'_B(\eta) + \frac{1}{2} \eta F''_B(\eta) \right] + \dots \quad (2.34)$$

Thus, the first-order quasi-steady velocity is

$$u_{1Q} = F'_B + \frac{1}{2} \eta F''_B \quad (2.35)$$

The quasi-steady velocity is a similarity solution for very low frequency fluctuations. This profile is shown on Figure 2.

2.2.2. High-frequency (Stokes) solution

For the limiting case of high-frequency fluctuations, the dominant terms in the first-order momentum equation are the time derivatives of the fluctuating velocities. As usual, we also retain the

highest order derivatives and obtain the following form of the first-order system (2.24) through (2.28) which is valid for the limiting case of very high frequency fluctuations.

$$\left\{ \begin{array}{l} \frac{\partial^2 u_1}{\partial y^2} = i(u_1 - 1) \end{array} \right. \quad (2.36)$$

$$u_1(x, 0) = 0 \quad (2.37)$$

$$u_1(x, y) \rightarrow 1 \quad \text{as} \quad y \rightarrow \infty \quad (2.38)$$

These equations also describe the so called Stokes flow for a flat plate oscillating in a fluid at rest. The solution to this system of equations, which we denote u_{1S} , is as follows:

$$u_{1S} = 1 - e^{-\sqrt{i}y} \quad (2.39)$$

The profile described by the real part of equation (2.39), denoted u_{1Sr} , is plotted on Figure 3. Note that the Stokes profile is plotted versus y ; whereas, the quasi-steady profile was given as a function of $y/\sqrt{x}$ on Figure 2.

2.3. The integral method

The objective of the integral analysis is to determine approximate velocity profiles for any frequency value between the quasi-steady and Stokes flow limits. That is, to generate the velocity profile as a continuous function of the frequency parameter.

The essence of the method is to first assume velocity profile forms (involving unknown form parameters) with sufficient generality to include the high- and low-frequency solutions. Then, a combination

Figure 2. - First-order "quasi-steady" velocity profile.
Asymptotic first-order solution for boundary layer on a
flat plate with low-frequency free-stream fluctuations.

Figure 3. - "Stokes" velocity profile. Asymptotic first-order solution for boundary layer on a flat plate with high-frequency free-stream fluctuations.

of "integral relations" and "compatibility conditions" are applied to determine the form parameters. We now obtain general expressions for the integral relations and compatibility conditions and specialize the results for the flat plate in an oscillating stream.

2.3.1. Integral relations

The momentum-integral method has been widely used to obtain approximate solutions to steady flow problems. The momentum integral equation is obtained by averaging the boundary layer equations across some suitably chosen layer. Thus, profiles are determined which satisfy the momentum equation on the average.

A generalization of the momentum-integral equation is developed here by multiplying the momentum equation by certain weighing functions and integrating in the direction normal to the body from the surface to the free-stream. By choosing the weighing functions as powers of the local U-velocity component, the V-velocity component can be eliminated by applying the continuity requirement.

The momentum equation (2.2) is multiplied by U^k and integrated in the Y-direction from the plate surface to the free-stream. This gives

$$\int_0^{\infty} U^k \frac{\partial U}{\partial T} dY + \int_0^{\infty} \left(U^{k+1} \frac{\partial U}{\partial X} + V U^k \frac{\partial U}{\partial Y} \right) dY = \int_0^{\infty} U^k \frac{\partial U_{\infty}}{\partial T} dY + \nu \int_0^{\infty} U^k \frac{\partial^2 U}{\partial Y^2} dY \quad (2.40)$$

The pressure gradient has been expressed in terms of the main stream

acceleration by equation (2.7) which applies for free-stream variation with time only. Upon imposing the continuity requirement (2.1), and integrating by parts, we obtain (see Appendix A)

$$\begin{aligned} \frac{d}{dX} \int_0^\infty \frac{U}{k+1} (U^{k+1} - U_\infty^{k+1}) dY \\ = \begin{cases} \int_0^\infty U^k \frac{\partial}{\partial T} (U_\infty - U) dY - \nu \left(\frac{\partial U}{\partial Y} \right)_{Y=0} & k = 0 \\ \int_0^\infty U^k \frac{\partial}{\partial T} (U_\infty - U) dY - \nu \int_0^\infty k U^{k-1} \left(\frac{\partial U}{\partial Y} \right)^2 dY & k > 0 \end{cases} \end{aligned} \quad (2.41)$$

The three equations of this system for $k = 0, 1$, and 2 are as follows

$$\frac{d}{dX} \int_0^\infty U(U - U_\infty) dY = \int_0^\infty \frac{\partial}{\partial T} (U_\infty - U) dY - \nu \left(\frac{\partial U}{\partial Y} \right)_{Y=0} \quad (2.42)$$

$$\frac{d}{dX} \int_0^\infty \frac{U}{2} (U^2 - U_\infty^2) dY = \int_0^\infty U \frac{\partial}{\partial T} (U_\infty - U) dY - \nu \int_0^\infty \left(\frac{\partial U}{\partial Y} \right)^2 dY \quad (2.43)$$

$$\frac{d}{dX} \int_0^\infty \frac{U}{3} (U^3 - U_\infty^3) dY = \int_0^\infty U^2 \frac{\partial}{\partial T} (U_\infty - U) dY - 2\nu \int_0^\infty U \left(\frac{\partial U}{\partial Y} \right)^2 dY \quad (2.44)$$

For $k = 0$, the resulting equation (2.42) is the familiar momentum-integral equation. The second equation (2.43) is a mechanical energy

balance for the boundary layer. The final equation has no known physical significance. Of course, higher moment equations could easily be written.

We now introduce the small- ϵ expansions (2.15) and (2.16) into the integral relations (2.42) through (2.44). The dimensionless variables, equations (2.9), are also introduced and the following systems of integral equations are obtained:

order ϵ^0 equations;

$$\left\{ \begin{array}{l} \frac{d}{dx} \int_0^\infty u_0(u_0 - 1)dy = -\left(\frac{\partial u_0}{\partial y}\right)_{y=0} \end{array} \right. \quad (2.45)$$

$$\left\{ \begin{array}{l} \frac{d}{dx} \int_0^\infty \frac{u_0}{2} (u_0^2 - 1)dy = - \int_0^\infty \left(\frac{\partial u_0}{\partial y}\right)^2 dy \end{array} \right. \quad (2.46)$$

$$\left\{ \begin{array}{l} \frac{d}{dx} \int_0^\infty \frac{u_0}{3} (u_0^3 - 1)dy = - 2 \int_0^\infty u_0 \left(\frac{\partial u_0}{\partial y}\right)^2 dy \end{array} \right. \quad (2.47)$$

order ϵ^1 equations;

$$\left\{ \begin{aligned} \frac{d}{dx} \int_0^\infty (2u_0 u_1 - u_0 - u_1) dy = 1 \int_0^\infty (1 - u_1) dy - \left(\frac{\partial u_1}{\partial y} \right)_{y=0} \end{aligned} \right. \quad (2.48)$$

$$\left\{ \begin{aligned} \frac{d}{dx} \int_0^\infty \left(\frac{3}{2} u_1 u_0^2 - u_0 - \frac{1}{2} u_1 \right) dy = 1 \int_0^\infty u_0 (1 - u_1) dy - 2 \int_0^\infty \left(\frac{\partial u_1}{\partial y} \right) \left(\frac{\partial u_0}{\partial y} \right) dy \end{aligned} \right. \quad (2.49)$$

$$\left\{ \begin{aligned} \frac{d}{dx} \int_0^\infty \left(\frac{4}{3} u_1 u_0^3 - u_0 - \frac{1}{3} u_1 \right) dy = 1 \int_0^\infty u_0^2 (1 - u_1) dy - 2 \int_0^\infty \left[u_1 \left(\frac{\partial u_0}{\partial y} \right)^2 \right. \\ \left. + 2u_0 \left(\frac{\partial u_1}{\partial y} \right) \left(\frac{\partial u_0}{\partial y} \right) \right] dy \end{aligned} \right. \quad (2.50)$$

Equations (2.45) through (2.50) are typical of the infinite numbers of integral equations that can be generated by averaging certain moments of the momentum equation. These equations provide relations for the unknown form parameters of the assumed velocity profiles. The relations are algebraic if the x -dependence of the profile parameters is known. Otherwise the equations provide first-order ordinary differential equations for the form factors.

2.3.2. Compatibility conditions

In applying the classical momentum integral method a second form parameter is often introduced. A second relation is then required to

determine this additional parameter. The momentum equation, evaluated on the boundary, is generally used as this second relation. This is called the "compatibility condition".

We now develop a general system of compatibility conditions by taking derivatives of the momentum equation with respect to the coordinate normal to the body, and then evaluating the result at the surface. These compatibility conditions are later used in conjunction with the integral relations of the previous section to determine the unknown velocity profile parameters.

Consider the j^{th} normal derivative of the momentum equation (2.11) and evaluate the result at the plate surface, that is

$$\left[\frac{\partial^j}{\partial y^j} \left(u_t + uu_x + vu_y - u_{yy} - i\epsilon e^{it} \right) \right]_{y=0} = 0 \quad (2.51)$$

where variable subscripts denote differentiation. We make use of the continuity equation (2.10) to eliminate the normal velocity component and also recognize the boundary conditions on the body (2.12) and (2.13). Then, upon expanding the velocity in powers of ϵ we obtain the following systems of compatibility conditions for $j=0, 1$, and 2 : order ϵ^0 equations;

$$\begin{cases} [u_{0yy}]_{y=0} = 0 \end{cases} \quad (2.52)$$

$$\begin{cases} [u_{0yyy}]_{y=0} = 0 \end{cases} \quad (2.53)$$

$$\begin{cases} [u_{0yyyy}]_{y=0} = [u_{0y}u_{0xy}]_{y=0} \end{cases} \quad (2.54)$$

order ϵ^1 equations;

$$\left\{ \begin{array}{l} [u_{1yy}]_{y=0} = -1 \end{array} \right. \quad (2.55)$$

$$\left\{ \begin{array}{l} [u_{1yyy}]_{y=0} = [1u_{1y}]_{y=0} \end{array} \right. \quad (2.56)$$

$$\left\{ \begin{array}{l} [u_{1yyyy}]_{y=0} = [1 + u_{1y}u_{0xy} + u_{0y}u_{1xy} + 1u_{0x}]_{y=0} \end{array} \right. \quad (2.57)$$

Additional conditions could easily be obtained in a similar manner.

2.4. Profile forms

It was pointed out earlier that the form of the velocity profiles must be chosen with sufficient generality to include the quasi-steady and Stokes flow limits. The assumed profiles must also satisfy the no-slip condition at the plate and approach the free stream velocity far from the wall. It is also obvious that complicated profile forms increase the labor of computation by increasing the number of, and introducing added complexity to, the integral relations and compatibility conditions.

We first note that the Stokes flow limit, equation (2.39), is a profile of the following form:

$$u_1 = 1 - e^{-\tilde{a}y} \quad (2.58)$$

In fact, for the particular choice $\tilde{a} = \sqrt{1}$, the Stokes flow limit is given exactly by equation (2.58).

Next, note that if $\tilde{a}$ is chosen as $a/\sqrt{x}$, then the Blasius similarity variable appears. That is,

$$\tilde{a}y = \frac{a}{\sqrt{x}} y = \eta \quad (2.59)$$

Thus, to approximate the quasi-steady limit, assume profiles of the following form:

$$u_{1q} = 1 - e^{-an}(1 + bn + cn^2 + dn^3 + \dots) \quad (2.60)$$

A preliminary determination of the number of terms to be retained in the polynomial is determined by curve fitting equation (2.60) to the quasi-steady profile. This is done to examine the form required to match the limiting case profile. The coefficient sets (a,b,c) and (a,b,c,d) were determined by Method of Least Squares as described in Appendix B. The results are shown on Figure 4.

Once the number of polynomial terms in equation (2.60) has been established, the profile form for the integral analysis is obtained by treating the constants in (2.60) as functions of x . Thus, the following profile form results:

$$u_1 = 1 - e^{-\alpha y}(1 + \beta y + \gamma y^2 + \delta y^3 + \dots) \quad (2.61)$$

2.5. Approximation of the Blasius profile

It was noted earlier that the ϵ^0 solution for the flat plate boundary layer is, in fact, the Blasius solution. Also, the profiles of u_0 appear in the calculation of higher order solutions. The use of tabulated values is inconvenient due to the algebraic nature of the integral method. In this section we consider approximations for the Blasius profile which will be used in the subsequent analysis.

It was shown in section 2.2.1., equation (2.35), that the quasi-steady velocity is functionally related to the Blasius profile. Thus, it is reasonable to assume an approximate form for the Blasius profile

Figure 4. - Quasi-steady profile approximations by least square fit for flat plate boundary layer with oscillating free stream.

which is similar to equation (2.60) for the quasi-steady approximation, namely

$$u_0 = 1 - e^{-A\eta}(1 + B\eta + C\eta^2 + D\eta^3 + \dots) \quad (2.62)$$

The number of terms to be retained, in the approximation (2.62), is partially determined by the desired accuracy. If this was the only restriction, the coefficients could easily be obtained by the Method of Least Squares (Appendix B). However, the number of coefficients in equation (2.62) must equal or exceed the total number of integral relations and compatibility conditions to be applied in determining the higher order solutions. Specifically, the profiles of u_0 must satisfy the same integral and compatibility conditions to order ϵ^0 . This requirement results from the fact that the derivation of equations (2.45) through (2.50), and (2.52) through (2.57), supposed the coefficients of ϵ^n to vanish individually. The basic difficulty is that we are not satisfying the momentum equation at all points in the flow field. Instead, we are satisfying the momentum equation on the average and (together with derivatives of the momentum equation) on the boundary.

We now compute the Blasius profile approximation, by the integral method, for three and four parameter profiles. Several combinations of integral and compatibility conditions will be applied.

Consider first the compatibility conditions. Direct substitution of the four parameter profile form, equation (2.62), into equations (2.52) through (2.54) gives

$$\left\{ \begin{array}{l} A^2 - 2AB + 2C = 0 \\ A^3 - 3A^2B + 6AC - 6D = 0 \\ 2A^4 - 8A^3B + 24A^2C - 48AD - A^2 + 2AB - B^2 = 0 \end{array} \right. \quad \begin{array}{l} (2.63) \\ (2.64) \\ (2.65) \end{array}$$

Since these conditions are applied in succession from (2.63) through (2.65), we can combine them to obtain the more convenient forms:

$D \neq 0$, four parameter profiles;

$$\left\{ \begin{array}{l} C = \frac{A}{2} (2B-A) \end{array} \right. \quad (2.66)$$

$$\left\{ \begin{array}{l} D = \frac{A^2}{6} (3B-2A) \end{array} \right. \quad (2.67)$$

$$\left\{ \begin{array}{l} B = A(1 - 4A^2) + A^2 \sqrt{2(8A^2 - 1)} \end{array} \right. \quad (2.68)$$

$D = 0$, three parameter profiles;

$$\left\{ \begin{array}{l} C = \frac{1}{6} A^2 \end{array} \right. \quad (2.69)$$

$$\left\{ \begin{array}{l} B = \frac{2}{3} A \end{array} \right. \quad (2.70)$$

In equation (2.68), the positive value of the radical was chosen to prevent velocity overshoot as the free stream is approached.

The assumed u_0 profile, equation (2.62), could be substituted directly into the integral relations (2.45) through (2.47). Then, upon carrying out the indicated operations, a set of three algebraic relations would result. The algebraic detail can be simplified considerably, however, by first introducing matrix notation. The labor saving value of this notation will become apparent in subsequent work involving more cumbersome expressions.

First, consider the momentum - integral equation which is re-written below:

$$\frac{d}{dx} \int_0^{\infty} u_0(u_0 - 1)dy = - \left(\frac{\partial u_0}{\partial y} \right)_{y=0} \quad (2.45)$$

Since u_0 is a function of the similarity variable, $\eta = y/\sqrt{x}$, we make a change in variable by letting

$$\zeta = \sqrt{x} \quad (2.71)$$

Then,

$$\frac{d}{dx} = \frac{1}{2\zeta} \frac{d}{d\zeta} \quad (2.72)$$

Thus, the momentum - integral can be rewritten as follows:

$$\frac{d}{d\zeta} \int_0^{\infty} u_0(u_0 - 1)dy = - 2\zeta \left(\frac{\partial u_0}{\partial y} \right)_{y=0} \quad (2.73)$$

Now, the integration over y can be computed by integrating over η with ζ held constant; thus

$$\frac{d}{d\zeta} \left[\zeta \int_0^{\infty} u_0(u_0 - 1)d\eta \right] = - 2 \left(\frac{\partial u_0}{\partial \eta} \right)_{\eta=0} \quad (2.74)$$

Since u_0 depends on η alone, the result of the integration is independent of ζ and we differentiate, in equation (2.74), to obtain the following:

$$\int_0^{\infty} u_0(u_0 - 1)d\eta = - 2 \left(\frac{\partial u_0}{\partial \eta} \right)_{\eta=0} \quad (2.75)$$

It is convenient to express the velocity profile, and its derivative, in the following forms:

$$\begin{cases} u_0 = f_1 - f_2 \\ \frac{\partial u_0}{\partial \eta} = f_3 \end{cases} \quad (2.76)$$

$$(2.77)$$

where

$$f_1 = e^{-s_1 \eta} \sum_{m=0}^3 h_{1m} \eta^m \quad (2.78)$$

In the above expressions, we have introduced the following array:

$$[s_1] = \begin{bmatrix} 0 \\ A \\ A \end{bmatrix} \quad (2.79)$$

and h_{1m} are elements of the matrix below;

$$[h_{1m}] = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 1 & B & C & D \\ A - B & AB - 2C & AC - 3D & AD \end{bmatrix} \quad (2.80)$$

Introducing this notation in equation (2.75), and noting that $f_1 \equiv 1$, the momentum-integral equation becomes:

$$\int_0^\infty (f_1 - f_2) f_2 d\eta = 2[f_3]_{\eta=0} \quad (2.81)$$

A function notation can be introduced for integrals of the type which appear in the momentum-integral equation. That is,

$$F(I, J) = \int_0^\infty \sum_{i=0}^3 \sum_{j=0}^3 e^{-(s_I + s_J) \eta} \eta^{i+j-2} h_{1i} h_{1j} d\eta \quad (2.82)$$

Next, we recall the following integration formula:

$$\int_0^{\infty} e^{-C_0 Z} Z^n dZ = \frac{n!}{C_0^{n+1}} \quad (2.83)$$

Upon applying this integration formula in equation (2.82), we obtain:

$$F(I, J) = \frac{h_{Ii} h_{Jj} [(i+j)!]}{[s_I + s_J]^{(i+j+1)}} \quad \begin{array}{l} \text{sum on} \\ i \text{ and } j \\ \text{from 0 to 3} \end{array} \quad (2.84)$$

Now, the momentum-integral, equation (2.81), can be written in the following very simple form:

$$[F(2,2) - F(2,1)] + 2(A - B) = 0 \quad (2.85)$$

The same procedure is applied with the other integral relations, and the system of equations (2.45) through (2.47) is reduced to the following:

$$\left\{ \begin{array}{l} [F(2,2) - F(2,1)] + 2(A - B) = 0 \quad (2.86) \\ [3F(2,2,1) - F(2,2,2) - 2F(2,1,1)] + 4F(3,3,1) = 0 \quad (2.87) \\ [F(2,2,2,2) - 4F(2,2,2,1) + 6F(2,2,1,1) - 3F(2,1,1,1)] \\ + 12[F(3,3,1,1) - F(3,3,2,1)] = 0 \quad (2.88) \end{array} \right.$$

The extension of the F notation to three and four subscripts utilizes the definition below (summation on lower case index 0 to 3):

$$F(I, J, K, L) = \frac{h_{Ii} h_{Jj} h_{Kk} h_{Ll} [(i+j+k+l)!]}{[s_I + s_J + s_K + s_L]^{(i+j+k+l+1)}} \quad (2.89)$$

The values of A , B , C , and D were computed for various combinations of compatibility conditions and integral relations, by applying the computational scheme outlined in Appendix C. The results are summarized in Table I. The resulting profile approximations are shown on Figures 5 and 6 for three and four parameters respectively. Values of the four parameter profile, using three integral relations and one compatibility condition, are compared with the Blasius values in Table II.

	Number of integral relations	Number of compatibility conditions	A	B	C	D
Three parameter profiles	1	2	1.1411	0.7607	0.2170	-----
	2	1	1.3477	1.0071	.4491	-----
Four parameter profiles	1	3	1.4299	1.0668	0.5031	0.1160
	2	2	1.6387	1.3013	.7898	.2084
	3	1	1.7780	1.4444	.9876	.5968

Table 1. Form parameters for Blasius profile approximation based on combinations of integral relations and compatibility conditions.

Figure 5. - Three parameter profile approximations for the Blasius profile.

Figure 6. - Four parameter profile approximations for the blasius profile.

$\eta = \frac{y}{\delta}$	Blasius value	Approximate value	Percent error
0.20	0.06641	0.06579	-0.94
0.40	0.13277	0.12888	-2.93
0.60	0.19894	0.19097	-4.00
0.80	0.26471	0.25414	-3.99
1.00	0.32979	0.31923	-3.20
1.20	0.39378	0.38584	-2.02
1.40	0.45627	0.45273	-0.78
1.60	0.51676	0.51833	0.30
1.80	0.57477	0.58112	1.10
2.00	0.62977	0.63985	1.60
2.20	0.68132	0.69362	1.81
2.40	0.72899	0.74194	1.78
2.60	0.77246	0.78462	1.57
2.80	0.81152	0.82176	1.26
3.00	0.84605	0.85364	0.90
3.20	0.87609	0.88068	0.52
3.40	0.90177	0.90337	0.18
3.60	0.92333	0.92223	-0.12
3.80	0.94112	0.93776	-0.36
4.00	0.95552	0.95045	-0.53
4.20	0.96696	0.96075	-0.64
4.40	0.97587	0.96905	-0.70
4.60	0.98269	0.97570	-0.71
4.80	0.98779	0.98099	-0.69
5.00	0.99155	0.98519	-0.64
5.20	0.99425	0.98850	-0.58
5.40	0.99616	0.99110	-0.51
5.60	0.99748	0.99313	-0.44
5.80	0.99838	0.99472	-0.37
6.00	0.99898	0.99595	-0.30
6.20	0.99937	0.99690	-0.25
6.40	0.99961	0.99763	-0.20
6.60	0.99977	0.99820	-0.16
6.80	0.99987	0.99863	-0.12
7.00	0.99992	0.99896	-0.10

Table 2. Comparison of four parameter profile approximation, based on three integral relations and one compatibility condition, with the Blasius profile (last combination listed in Table 1).

CHAPTER III
UNSTEADY FLOW OVER A FLAT PLATE WITH
OSCILLATING FREE-STREAM

In Chapter II, we developed the general integral method for calculating the unsteady laminar boundary layer flow. We saw that the method basically consists of: (a) Choosing the profiles with sufficient generality to include the asymptotic solutions; and (b) Applying integral relations and compatibility conditions, as required, to determine the unknown form parameters.

We now apply this method to calculate a specific case; namely, the unsteady flow over a flat plate with oscillating free-stream. That is, the first-order unsteady effect on the flat plate boundary layer due to small harmonic fluctuations in the main stream velocity.

As indicated by the general method, we utilize the quasi-steady asymptotic solution in selecting the profile form and determining the best combination of integral relations and compatibility conditions to be applied.

3.1. Quasi-steady limit.

In Section 2.2.1., a quasi-steady solution was obtained for the effect of low-frequency oscillations on the flat plate boundary layer. This solution was found to depend on the familiar Blasius similarity variable.

Later, in Section 2.4., approximations for the quasi-steady solution were examined. Specifically, three and four parameter profiles were found to yield reasonable curve fits to the quasi-steady profile by the Method of Least Squares.

Thus, we are led to examine quasi-steady profile approximations of the form (2.60), specialized below for three or four parameters:

$$u_{1q} = 1 - e^{-a\eta}(1 + b\eta + c\eta^2 + d\eta^3) \quad (3.1)$$

We now determine the coefficient sets (a,b,c,d) to satisfy certain combinations of integral relations and compatibility conditions. The combination which admits the best quasi-steady profile representation will later be used to calculate the velocity at other frequencies.

First, consider the compatibility conditions. Direct substitution of equation (3.1) into the ϵ^1 compatibility conditions, equations (2.55) through (2.57), gives the following (real parts):

$$\begin{cases} c = \frac{a}{2} (2b - a) & (3.2) \\ d = \frac{a^2}{6} (3b - 2a) & (3.3) \\ b = a \frac{(3a^3 - A + B)}{(4a^3 - A + B)} & (3.4) \end{cases}$$

The first two of these conditions have been applied in obtaining the third. Note also, for the three parameter case, $d = 0$;

$$\begin{cases} b = \frac{2}{3} a & (3.5) \\ c = \frac{1}{6} a^2 & (3.6) \end{cases}$$

Since the coefficient appearing in the exponential (that is 'a') is always positive, the other coefficients according to equations (3.5) and (3.6) are always positive. Thus, in order that the quasi-steady profiles exhibit values greater than unity, we apply only one compatibility condition for three parameter profiles.

We next evaluate the integral relations by substituting equation (3.1) into the ϵ^1 integral equations (2.48) through (2.50). First, however, we extend the matrix definitions introduced in Section 2.5., to include the u_{1q} profile and its derivatives. Thus, we define

$$\begin{cases} u_{1q} = 1 - f_4 \\ \frac{\partial u_{1q}}{\partial \eta} = f_5 \end{cases} \quad (3.7)$$

$$(3.8)$$

where, as before

$$f_1 = e^{-s_1 \eta} \sum_{m=0}^3 h_{1m} \eta^m \quad (3.9)$$

The arrays are defined as follows:

$$[s_1] = \begin{bmatrix} 0 \\ A \\ A \\ a \\ a \end{bmatrix} \quad (3.10)$$

$$[h_{im}] = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 1 & B & C & D \\ A - B & AB - 2C & AC - 3D & AD \\ 1 & b & c & d \\ a - b & ab - 2c & ac - 3d & ad \end{bmatrix} \quad (3.11)$$

Now, introducing the F notation, equation (2.89), the three integral equations (2.48) through (2.50) can be written as the following (real parts):

$$\left\{ \begin{array}{l} 2F(3,2,1,1) - F(3,1,1,1) - F(2,1,1,1) + 2(a - b) = 0 \end{array} \right. \quad (3.12)$$

$$\left\{ \begin{array}{l} 3F(2,2,1,1) - 3F(3,2,2,1) + 6F(3,2,1,1) \\ - 4F(2,1,1,1) - 2F(3,1,1,1) + 8F(5,4,1,1) = 0 \end{array} \right. \quad (3.13)$$

$$\left\{ \begin{array}{l} 12F(2,2,1,1) - 9F(2,1,1,1) - 4F(2,2,2,1) - 3F(3,1,1,1) \\ + 12F(3,2,1,1) - 12F(3,2,2,1) + 4F(3,2,2,2) + 12F(4,4,1,1) \\ - 12F(4,4,3,1) + 24F(5,4,1,1) - 24F(5,4,2,1) = 0 \end{array} \right. \quad (3.14)$$

The coefficient sets (a, b, c, d) were computed for various combinations of integral and compatibility conditions using the corresponding sets (A, B, C, D) . The method outlined in Appendix C was employed and results are summarized in Table 3. The velocity profiles based on these coefficient sets are shown on Figure 7. Clearly, the four parameter profile, based on three integrals plus one compatibility condition, gives the best approximation of the quasi-steady profile. These values are also compared in Table 4.

	Number of integral relations	Number of compatibility conditions	a	b	c	d
Three parameter profile	2	1	0.5316	0.09838	-0.08900	-----
Four parameter profiles	1	3	0.5437	0.2313	-0.02204	-0.01938
	2	2	.8979	.4297	-.01729	-.06809
	3	1	1.1813	.6913	.1189	-.2084

Table 3. Form parameters for quasi-steady profile approximation based on combinations of integral relations and compatibility conditions.

Figure 7. - Quasi-steady profile approximations for flat plate boundary layer with oscillating free-stream.

$\eta = \frac{y}{\zeta}$	Quasi-steady expansion	Approximate value	Percent error
0.20	0.09961	0.09882	-0.79
0.40	0.19906	0.20064	0.79
0.60	0.29796	0.30467	2.25
0.80	0.39567	0.40828	3.19
1.00	0.49129	0.50844	3.49
1.20	0.58373	0.60246	3.21
1.40	0.67178	0.68834	2.47
1.60	0.75410	0.76482	1.42
1.80	0.82941	0.83133	0.23
2.00	0.89652	0.88784	-0.97
2.20	0.95450	0.93477	-2.07
2.40	1.00270	0.97281	-2.98
2.60	1.04086	1.00286	-3.65
2.80	1.06913	1.02588	-4.05
3.00	1.08809	1.04285	-4.16
3.20	1.09870	1.05475	-4.00
3.40	1.10217	1.06245	-3.60
3.60	1.09989	1.06677	-3.01
3.80	1.09337	1.06842	-2.28
4.00	1.08400	1.06802	-1.47
4.20	1.07305	1.06610	-0.65
4.40	1.06160	1.06308	0.14
4.60	1.05049	1.05932	0.84
4.80	1.04028	1.05512	1.43
5.00	1.03132	1.05068	1.88
5.20	1.02373	1.04619	2.19
5.40	1.01757	1.04177	2.38
5.60	1.01243	1.03751	2.48
5.80	1.00896	1.03348	2.43
6.00	1.00618	1.02972	2.34
6.20	1.00417	1.02625	2.20
6.40	1.00275	1.02309	2.03
6.60	1.00178	1.02022	1.84
6.80	1.00113	1.01764	1.65
7.00	1.00069	1.01533	1.46
7.20	1.00043	1.01329	1.29
7.40	1.00024	1.01148	1.12
7.60	1.00014	1.00989	0.97
7.80	1.00008	1.00849	0.84
8.00	1.00000	1.00728	0.73
8.20	1.00000	1.00623	0.62
8.40	1.00000	1.00531	0.53
8.60	1.00000	1.00452	0.45
8.80	1.00000	1.00384	0.38
9.00	1.00000	1.00326	0.33

Table 4. Comparison of four parameter profile approximation, based on three integral relations and one compatibility condition, with the quasi-steady expansion profile (last combination listed in Table 3).

3.2. Form parameters

It has been ascertained that the four parameter profile gives a good approximation for the quasi-steady profile if the parameters are determined to satisfy one compatability condition plus three integral relations. We therefore assume general first-order velocity profiles of the following form:

$$u_1 = 1 - e^{-\alpha y}(1 + \beta y + \gamma y^2 + \delta y^3) \quad (3.15)$$

The complex form functions $(\alpha, \beta, \gamma, \delta)$ are functions of the variable $\zeta = \sqrt{\omega X/U_0}$. Thus, equation (3.15) describes the velocity as a function of the distance along the plate (X) and applies for all frequencies. Of course, for small frequency values we expect the independent variables to combine as the similarity variable and equation (3.15) to yield the quasi-steady profile approximation.

In this section, the complex form functions in equation (3.15) are determined to satisfy three integral relations plus one compatability condition. The integral relations lead to a system of first-order ordinary differential equations which are then solved numerically for the form parameters.

3.2.1. Governing equations

The governing equations for determining the form parameters in equation (3.15) are the ϵ^1 equations for the compatability conditions (one equation) and integral relations (three equations).

Substitution of equation (3.15) into the first compatability condition, equation (2.55), gives the following result:

$$\gamma = -\frac{1}{2}(\alpha^2 - 2\alpha\beta - 1) \quad (3.16)$$

We note, for future reference, that derivatives of γ are related to derivatives of α and β as given below:

$$\frac{d\gamma}{d\zeta} = -(\alpha - \beta) \frac{d\alpha}{d\zeta} + \alpha \frac{d\beta}{d\zeta} \quad (3.17)$$

Equation (3.15), together with the corresponding approximation for the Blasius profile, are now substituted into the integral relations, equations (2.48) through (2.50). The algebraic manipulations are simplified by introducing the following notation:

$$F_1 = 1 = e^0(1) \quad (3.18)$$

$$F_2 = 1 - u_0 = e^{-\frac{A}{\zeta} y} \left(1 + \frac{B}{\zeta} y + \frac{C}{\zeta^2} y^2 + \frac{D}{\zeta^3} y^3 \right) \quad (3.19)$$

$$F_3 = 1 - u_1 = e^{-\alpha y} (1 + \beta y + \gamma y^2 + \delta y^3) \quad (3.20)$$

$$F_4 = \frac{\partial u_0}{\partial y} = \frac{1}{\zeta} e^{-\frac{A}{\zeta} y} \left[(A - B) + \frac{1}{\zeta} (AB - 2C)y + \frac{1}{\zeta^2} (AC - 3D)y^2 + \frac{1}{\zeta^3} ADy^3 \right] \quad (3.21)$$

$$F_5 = \frac{\partial u_1}{\partial y} = e^{-\alpha y} [(\alpha - \beta) + (\alpha\beta - 2\gamma)y + (\alpha\gamma - 3\delta)y^2 + \alpha\delta y^3] \quad (3.22)$$

Then, the substitution indicated above yields the following:

$$\left[\frac{d}{d\zeta} \int_0^\infty F_3(2F_2 - 1)dy = 2\zeta(\beta - \alpha) + 2\zeta \int_0^\infty F_3 dy + \frac{d}{d\zeta} \int_0^\infty F_2 dy \right. \quad (3.23)$$

$$\left. \frac{d}{d\zeta} \int_0^\infty F_3 \left(3F_2 - 1 - \frac{3}{2} F_2^2 \right) dy = 2\zeta \int_0^\infty [1(1 - F_2)F_3 - 2F_4F_5] dy \right. \\ \left. - \frac{d}{d\zeta} \int_0^\infty \left[\frac{3}{2} F_2^2 - 2F_2 \right] dy \right. \quad (3.24)$$

$$\left. \frac{d}{d\zeta} \int_0^\infty F_3 \left(\frac{4}{3} F_2^3 - 4F_2^2 + 4F_2 - 1 \right) dy \right. \\ \left. = 2\zeta \int_0^\infty [1F_3(1 - F_2)^2 - 2F_4^2(1 - F_3) - 4F_4F_5(1 - F_2)] dy \right. \\ \left. - \frac{d}{d\zeta} \int_0^\infty \left[4F_2^2 - 3F_2 - \frac{4}{3} F_2^3 \right] dy \right. \quad (3.25)$$

Many of the terms in the above equations can be simplified prior to evaluation of the integrals. Consider the left hand side terms in equations (3.23) through (3.25). These are all of the form given below:

$$\frac{d}{d\zeta} \int_0^\infty F_3 g(F_2) dy = \int_0^\infty \left[F_3 \frac{dg}{d\zeta} + g \frac{dF_3}{d\zeta} \right] dy \quad (3.26)$$

Note first, the derivative of F_3 can be written:

$$\frac{dF_3}{d\zeta} = F_6 \frac{d\alpha}{d\zeta} + F_7 \frac{d\beta}{d\zeta} + F_8 \frac{d\delta}{d\zeta} \quad (3.27)$$

where,

$$\left\{ \begin{array}{l} F_6 = \frac{\partial F_3}{\partial \alpha} = e^{-\alpha y} (-y - \alpha y^2 - \gamma y^3 - \delta y^4) \end{array} \right. \quad (3.28)$$

$$\left\{ \begin{array}{l} F_7 = \frac{\partial F_3}{\partial \beta} = e^{-\alpha y} (y + \alpha y^2) \end{array} \right. \quad (3.29)$$

$$\left\{ \begin{array}{l} F_8 = \frac{\partial F_3}{\partial \delta} = e^{-\alpha y} (y^3) \end{array} \right. \quad (3.30)$$

Also, the derivative of g becomes:

$$\frac{dg}{d\zeta} = \frac{dg}{dF_2} \frac{dF_2}{d\eta} \frac{d\eta}{d\zeta} = \frac{1}{\zeta} F_9 \frac{dg}{dF_2} \quad (3.31)$$

where,

$$F_9 = yF_4 \quad (3.32)$$

Recall, that when the integrand depends on η alone, the integration over y can be simply transformed to an integration over η .

Using the above relations in the momentum-integral equation gives the following result:

$$\begin{aligned} & \left[\int_0^\infty (2F_2 - 1)F_6 dy \right] \frac{d\alpha}{d\zeta} + \left[\int_0^\infty (2F_2 - 1)F_7 dy \right] \frac{d\beta}{d\zeta} + \left[\int_0^\infty (2F_2 - 1)F_8 dy \right] \frac{d\delta}{d\zeta} \\ & = 2\zeta(\beta - \alpha) + 2\zeta i \int_0^\infty F_3 dy + \int_0^\infty F_2 d\eta - \frac{2}{\zeta} \int_0^\infty F_3 F_9 dy \end{aligned} \quad (3.33)$$

Similar intermediate results are also obtained for the integral equations (3.24) and (3.25).

Again, the matrix notation and function definitions are introduced. We supplement the previous definitions by defining the complex integral function below:

$$G(I, J, K, L) = \int_0^\infty \sum_{i=0}^4 \sum_{j=0}^4 \sum_{k=0}^4 \sum_{l=0}^4 e^{-(S_I + S_J + S_K + S_L)y} y^{i+j+k+l} H_{Ii} H_{Jj} H_{Kk} H_{Ll} dy \quad (3.34)$$

Applying the integration formula, equation (2.83), gives

$$G(I, J, K, L) = \frac{H_{Ii} H_{Jj} H_{Kk} H_{Ll} [(i + j + k + l)!]}{[S_I + S_J + S_K + S_L]^{(i+j+k+l+1)}} \quad \begin{matrix} \text{sum on} \\ i, j, k, l \\ (0 \text{ to } 4) \end{matrix} \quad (3.35)$$

In equation (3.35) the following matrices are utilized:

$$S = \begin{bmatrix} 0 \\ A/\zeta \\ \alpha \\ A/\zeta \\ \alpha \\ \alpha \\ \alpha \\ \alpha \\ A/\zeta \end{bmatrix} \quad (3.36)$$

$$H = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 1 & B/\zeta & C/\zeta^2 & D/\zeta^3 & 0 \\ 1 & \beta & \gamma & \delta & 0 \\ (A - B)/\zeta & (AB - 2C)/\zeta^2 & (AC - 3D)/\zeta^3 & AD/\zeta^4 & 0 \\ (\alpha - \beta) & (\alpha\beta - 2\gamma) & (\alpha\gamma - 3\delta) & \alpha\delta & 0 \\ 0 & -1 & -\alpha & -\gamma & -\delta \\ 0 & 1 & \alpha & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ 0 & (A - B)/\zeta & (AB - 2C)/\zeta^2 & (AC - 3D)/\zeta^3 & AD/\zeta^4 \end{bmatrix} \quad (3.37)$$

Finally, with these definitions, the governing differential equations for the form functions rewritten in the standard form are below:

$$\begin{cases} P_{11} \frac{d\alpha}{d\zeta} + P_{12} \frac{d\beta}{d\zeta} + P_{13} \frac{d\delta}{d\zeta} = R_1 \end{cases} \quad (3.38)$$

$$\begin{cases} P_{21} \frac{d\alpha}{d\zeta} + P_{22} \frac{d\beta}{d\zeta} + P_{23} \frac{d\delta}{d\zeta} = R_2 \end{cases} \quad (3.39)$$

$$\begin{cases} P_{31} \frac{d\alpha}{d\zeta} + P_{32} \frac{d\beta}{d\zeta} + P_{33} \frac{d\delta}{d\zeta} = R_3 \end{cases} \quad (3.40)$$

where,

$$\begin{cases} P_{11} = 2G(6,2) - G(6,1) \end{cases} \quad (3.41)$$

$$\begin{cases} P_{12} = 2G(7,2) - G(7,1) \end{cases} \quad (3.42)$$

$$\begin{cases} P_{13} = 2G(8,2) - G(8,1) \end{cases} \quad (3.43)$$

$$\begin{cases} R_1 = 2\zeta(\beta - \alpha) + 2\zeta^4 G(3,1) + F(2,1) - \frac{2}{\zeta} G(9,3) \end{cases} \quad (3.44)$$

$$\left\{ \begin{aligned}
 P_{21} &= 3G(6,2) - G(6,1) - \frac{3}{2} G(6,2,2) & (3.45) \\
 P_{22} &= 3G(7,2) - G(7,1) - \frac{3}{2} G(7,2,2) & (3.46) \\
 P_{23} &= 3G(8,2) - G(8,1) - \frac{3}{2} G(8,2,2) & (3.47) \\
 R_2 &= -4\zeta G(5,4) + 2\zeta i [G(3,1) - G(3,2)] \\
 &\quad - \left[\frac{3}{2} F(2,2) - 2F(2,1) \right] \\
 &\quad - \frac{3}{\zeta} [G(9,3,1) - G(9,3,2)] & (3.48)
 \end{aligned} \right.$$

$$\left\{ \begin{aligned}
 P_{31} &= \frac{4}{3} G(6,2,2,2) - 4G(6,2,2) + 4G(6,2) - G(6,1) & (3.49) \\
 P_{32} &= \frac{4}{3} G(7,2,2,2) - 4G(7,2,2) + 4G(7,2) - G(7,1) & (3.50) \\
 P_{33} &= \frac{4}{3} G(8,2,2,2) - 4G(8,2,2) + 4G(8,2) - G(8,1) & (3.51) \\
 R_3 &= -4\zeta [G(4,4,1) - G(4,4,3) + 2G(5,4,1) - 2G(5,4,2)] \\
 &\quad + 2\zeta i [G(3,1) - 2G(3,2) + G(3,2,2)] \\
 &\quad - [4F(2,2) - 3F(2,1) - \frac{4}{3} F(2,2,2)] \\
 &\quad - \frac{4}{\zeta} [F(9,3,2,2) - 2F(9,3,2) + F(9,3)] & (3.52)
 \end{aligned} \right.$$

3.2.2. Solution

The governing equations for the four velocity profile form functions consist of one simple algebraic equation, plus a system of three complex nonlinear ordinary differential equations. Since the coefficients in equations (3.38) through (3.40) do not depend on derivatives

of (α, β, δ) , we apply Cramer's rule to solve simultaneously for the slopes of the form parameters. The results are of the form given below:

$$\left\{ \begin{array}{l} \frac{d\alpha}{d\zeta} = \theta_1(\alpha, \beta, \delta, \zeta) \\ \frac{d\beta}{d\zeta} = \theta_2(\alpha, \beta, \delta, \zeta) \\ \frac{d\delta}{d\zeta} = \theta_3(\alpha, \beta, \delta, \zeta) \end{array} \right. \quad (3.53)$$

$$\frac{d\beta}{d\zeta} = \theta_2(\alpha, \beta, \delta, \zeta) \quad (3.54)$$

$$\frac{d\delta}{d\zeta} = \theta_3(\alpha, \beta, \delta, \zeta) \quad (3.55)$$

The above equations are equivalent to six real first-order equations. Thus, six initial values are required to obtain the solution. The six initial values are the real and imaginary parts of (α, β, δ) at ζ equal to zero.

Recognize that, for low frequency values, the quasi-steady behavior of the functions (α, β, δ) is the following (compare equation (3.15) with equation (3.1)):

$$\alpha_q \sim a/\zeta \quad (3.56)$$

$$\beta_q \sim b/\zeta \quad (3.57)$$

$$\delta_q \sim d/\zeta^3 \quad (3.58)$$

Also, recall that the variable ζ is defined by

$$\zeta = \sqrt{\frac{\omega X}{U_0}} \quad (3.59)$$

Thus, we consider the quasi-steady solution as a small- ζ solution which determines the real values of $(\alpha_q, \beta_q, \delta_q)$. In fact the quasi-steady result can be viewed as the dominant term in expansions of the following form:

$$\begin{cases} \alpha = \frac{a}{\zeta} (1 + a_1 \zeta + a_2 \zeta^2 + \dots) + i \bar{a} \zeta (1 + \bar{a}_1 \zeta + \bar{a}_2 \zeta^2 + \dots) & (3.60) \\ \beta = \frac{b}{\zeta} (1 + b_1 \zeta + b_2 \zeta^2 + \dots) + i \bar{b} \zeta (1 + \bar{b}_1 \zeta + \bar{b}_2 \zeta^2 + \dots) & (3.61) \\ \delta = \frac{d}{\zeta^3} (1 + d_1 \zeta + d_2 \zeta^2 + \dots) + i \frac{\bar{d}}{\zeta} (1 + \bar{d}_1 \zeta + \bar{d}_2 \zeta^2 + \dots) & (3.62) \end{cases}$$

Then, the initial behavior of the imaginary parts of (α, β, δ) is $(\bar{a}\zeta, \bar{b}\zeta, \bar{d}/\zeta)$. Of course, the form of the expansions (3.60) through (3.62) requires that the initial conditions be applied at some small but non-zero value of ζ .

We determine the values of $(\bar{a}, \bar{b}, \bar{d})$ by first substituting the expansions, equations (3.60) through (3.62), into the system of differential equations (3.38) through (3.40). The resulting system is:

$$P_{11} \left(-\frac{a}{\zeta^2} + i\bar{a} \right) + P_{12} \left(-\frac{b}{\zeta^2} + i\bar{b} \right) + P_{13} \left(-\frac{3d}{\zeta^4} - \frac{i\bar{d}}{\zeta^2} \right) = R_1 \quad i=1,2,3 \quad (3.63)$$

where only the leading real and imaginary terms have been retained. The dominant real terms in these equations, for small values of ζ , yield three real equations for (a, b, d) . This, of course, regenerates the form parameters for the quasi-steady approximation. The imaginary parts of equations (3.63) are then used to determine the imaginary coefficients $(\bar{a}, \bar{b}, \bar{d})$. The method described in Appendix C was employed and the coefficients were evaluated for a value of $\zeta = 0.001$. Then, the limiting ($\zeta \rightarrow 0$) behavior of (α, β, δ) provides initial values for solving equations (3.53) through (3.55). This behavior is as follows:

$$\left\{ \begin{array}{l} \alpha = \frac{1.1813}{\zeta} + 0.3438 i\zeta \end{array} \right. \quad (3.64)$$

$$\left\{ \begin{array}{l} \beta = \frac{0.6913}{\zeta} - 0.5097 i\zeta \end{array} \right. \quad (3.65)$$

$$\left\{ \begin{array}{l} \delta = -\frac{0.2084}{\zeta^3} - 0.1603 \frac{1}{\zeta} \end{array} \right. \quad (3.66)$$

The system of equations, (3.53) through (3.55), was solved numerically using the Runge-Kutta formulas given in Appendix D. The initial values were obtained by evaluating equations (3.64) through (3.66) at small values of ζ .

The integration procedure is summarized in Table 5. Integrations 1 and 2 establish the starting value of $\zeta = 0.01$. Initial increment size is the largest value for which results do not change for changes in increment size. The overlapping ranges of ζ , integrations 3 through 6, were used to verify that increasing increment size did not effect results. Real and imaginary parts of the functions (α , β , δ) are presented graphically on Figures 8 and 9, respectively.

Trial	Initial ζ	Final ζ	Increment	Remarks
1	0.001	0.0012	0.00002	-----
2	.01	.012	.0002	Results differ from trial 1 in quasi-steady manner
3	.01	.046	.0002	Results match quasi-steady solution over entire range
4	.04	.1857	.0008	-----
5	.16	.664	.004	-----
6	.62	2.068	.008	-----

Table 5.² Summary of integration procedure for first-order velocity profile form parameters for flat plate boundary layer with oscillating free-stream.

² Each trial number represents a numerical integration from the initial to final values of ζ indicated. Initial values of the function (α, β, δ) for Trials 1 and 2 were based on the quasi-steady solution, equations (3.64) through (3.66). Both trials reproduced the quasi-steady solutions and thus established the initial values of ζ for Trial 2 to be sufficiently small. Trial 3 is a continuation of Trial 2, over a larger range of ζ values, and the quasi-steady values were reproduced over the entire range. Initial values of (α, β, δ) for Trials 4 through 6 were those computed from the previous trial. The computation was terminated (i.e., final value of ζ for Trial 6) when the resulting velocity profile substantially agreed with the Stokes flow profile.

Figure 8. - First-order velocity profile form parameter real parts for flat plate boundary layer with oscillating free-stream.

Figure 9. - First-order velocity profile form parameter imaginary parts for flat plate boundary layer with oscillating free stream.

3.3. Velocity profiles

Once the form parameters have been determined, the first-order velocity profiles are easily computed from equation (3.15). Recall that u_1 is the steady coefficient of the first-order velocity fluctuations. The expansion for the velocity component along the plate, equation (2.15), is given again below:

$$u = u_0(x,y) + \epsilon u_1(x,y)e^{it} + \mathcal{O}(\epsilon^2) \quad (3.67)$$

Thus, the real and imaginary parts of u_1 represent components of the velocity which are respectively in-phase and out-of-phase with the free-stream fluctuations. There is a phase angle associated with these components; and, we define a phase lead with respect to the free-stream variation as positive.

3.3.1. Profile results

We consider here the detailed first-order velocity profile results for the flat plate boundary layer. We examine the development of the profiles with increasing values of $\omega X/U_0$. That is, the development along the plate going downstream from the leading edge.

Recall that for small values of $\zeta = \sqrt{\omega X/U_0}$, the quasi-steady profile applies. That profile was shown to depend on the familiar Blasius similarity variable η . The departure from the similarity solution is indicated on Figure 10. We see that the deviation from quasi-steady behavior is mainly an increase in maximum velocity, with the maximum occurring at approximately the same value of η for all values of $\omega X/U_0$.

The development of the phase angle for small values of $\omega X/U_0$ is shown versus η on Figure 11. Recall that the quasi-steady flow

possesses only a real (or in-phase) velocity component, and therefore has zero phase angle everywhere. Generally there is a phase advance throughout the flow field. The acceleration force applies simultaneously throughout the region and the slower moving fluid near the wall responds faster than the main stream to this accelerating force.

The downstream development of the in-phase component and phase angle are shown on Figures 12 and 13. Note that the Stokes flow profile is approached most rapidly near the wall.

Computed first-order velocity results are compared with the experimental data of Hill and Stenning (17) on Figures 14 through 24. For small values of $\omega X/U_0$, results are plotted versus η ; whereas, for large $\omega X/U_0$ the normal coordinate $y/\sqrt{2}$ is used. The agreement between the analytical and experimental results is very good throughout the entire range of frequency parameter ($\omega X/U_0$).

Figure 10. - Development of in-phase velocity component along flat plate with oscillating free-stream (small ξ).

Figure 11. - Development of phase angle between in-phase and out-of-phase velocity components along flat plate with oscillating free-stream (small ζ).

Figure 12. - Development of in-phase velocity component along flat plate with oscillating free-stream (large ζ).

Figure 13. - Development of phase angle between in-phase and out-of-phase velocity components along flat plate with oscillating free-stream (large ζ).

Figure 14. $\omega U_0/\nu = 0.104$. Figure 15. $\omega U_0/\nu = 0.162$. Figure 16. $\omega U_0/\nu = 0.254$. Figure 17. $\omega U_0/\nu = 0.508$. Figure 18. $\omega U_0/\nu = 1.471$. Figure 19. $\omega U_0/\nu = 4.0$.

Figures 14 through 19. -

Development of in-phase velocity component along flat plate with oscillating free-stream. Circles are experimental data of Hill and Stenning (17).

Figure 20. - $\omega\delta_0/U_0 = 0.47$. Figure 21. - $\omega\delta_0/U_0 = 0.65$. Figure 22. - $\omega\delta_0/U_0 = 0.83$. Figure 23. - $\omega\delta_0/U_0 = 1.48$. Figure 24. - $\omega\delta_0/U_0 = 2.49$.

Figures 20 through 24. -

Development of phase angle between in-phase and out-of-phase velocity components along flat plate with oscillating free-stream. Circles are experimental data of Hill and Stenning (17).

3.2.2. Wall shear stress

The skin friction is related to the normal derivative of the velocity, evaluated at the wall; namely

$$\left(\frac{\partial u}{\partial y}\right)_{y=0} = \left(\frac{\partial u_0}{\partial y}\right)_{y=0} + \epsilon \left(\frac{\partial u_1}{\partial y}\right)_{y=0} e^{it} + \mathcal{O}(\epsilon^2) \quad (3.68)$$

Note that, the first order friction is oscillatory and therefore gives no net drag in the time-average sense. We define a first-order wall shear stress coefficient by normalizing the magnitude by the Blasius wall shear value. The result is:

$$C_\tau = \frac{(\partial u_1 / \partial y)_{y=0}}{(\partial u_B / \partial y)_{y=0}} \quad (3.69)$$

This is a complex coefficient and has the following associated phase angle:

$$\phi_\tau = \tan^{-1} \left(\frac{C_{\tau i}}{C_{\tau r}} \right) \quad (3.70)$$

Asymptotic values for the shear coefficient were given by Lighthill (6) as follows:

$$C_\tau = \begin{cases} [1.500 + 2.550 i \zeta^2] & \text{small } \zeta \\ [2.129 \zeta + 2.129 i \zeta] & \text{large } \zeta \end{cases} \quad (3.71)$$

$$C_\tau = \begin{cases} [1.500 + 2.550 i \zeta^2] & \text{small } \zeta \\ [2.129 \zeta + 2.129 i \zeta] & \text{large } \zeta \end{cases} \quad (3.72)$$

The real part of the first of these is a direct result of the quasi-steady profile expansion. The phase angle associated with equation (3.72) is 45° , which corresponds to the Stokes solution.

Asymptotic solutions were later extended by Illingworth (9), with the following results:

$$C_{\tau} = \begin{cases} [1.500 + 2.556 i\zeta^2] & \text{small } \zeta & (3.73) \\ [2.129 \zeta + i(2.129 \zeta - .3125/\zeta^2)] & \text{large } \zeta & (3.74) \end{cases}$$

These values and the associated phase angles are plotted on Figures 25 through 27 together with the values computed by the integral method. We see that the integral analysis provides a continuous description of the wall shear parameters throughout the range of frequency parameter $(\omega X/U_0)$.

The low-frequency values of the shear coefficient, as determined by the integral method, can be expressed in the form of equations (3.71) and (3.73) by using the quasi-steady results, equations (3.64) and (3.65), and the definition of the shear coefficient, equation (3.69). Thus, the present result is:

$$C_{\tau} = [1.476 + 2.571 i\zeta^2] \quad \text{small } \zeta \quad (3.75)$$

It is also to be noted that the Illingworth and Lighthill results for large ζ , equations (3.72) and (3.74), are asymptotic values which are valid as $\zeta \rightarrow \infty$. Consequently, the value of ζ in these equations does not have a definite origin and the results are to be viewed as asymptotic limits.

Figure 25. - Real part of first-order wall shear stress coefficient for flat plate boundary layer with oscillating free-stream.

Figure 26. - Imaginary part of first-order wall shear stress coefficient for flat plate boundary layer with oscillating free-stream.

Figure 27. - Phase advance of first order wall shear stress relative to free-stream oscillations for flat plate boundary layer.

CHAPTER IV

EFFECT OF OSCILLATIONS ON TIME AVERAGE BOUNDARY LAYER FLOW

The unsteady flow over a flat plate with oscillating free-stream was studied in the previous chapter. The dominant unsteady effect was to produce velocity fluctuations of order ϵ^1 in the boundary layer flow. Those fluctuations were of the same frequency as the free-stream fluctuations but varied in amplitude and phase throughout the layer.

We now consider the steady (time-average) effect of free-stream oscillations on the mean boundary layer flow. It will be seen that the order ϵ^2 flow velocity is comprised of fluctuations at twice the fundamental frequency plus a steady contribution to the mean flow. It is that steady contribution that is computed here by the integral method.

4.1. Governing equations

The governing equations for the steady effect of free-stream oscillations on the flat plate boundary layer flow are obtained by continuing the expansion of the basic flow equations (section 2.1.) through order ϵ^2 . That is, we assume the following expansions for the dimensionless velocity components:

$$\begin{cases} u = u_0(x,y) + \epsilon u_1(x,y)e^{it} + \epsilon^2 u_2(x,y,t) + \mathcal{O}(\epsilon^3) \\ v = v_0(x,y) + \epsilon v_1(x,y)e^{it} + \epsilon^2 v_2(x,y,t) + \mathcal{O}(\epsilon^3) \end{cases} \quad (4.1)$$

$$\begin{cases} v = v_0(x,y) + \epsilon v_1(x,y)e^{it} + \epsilon^2 v_2(x,y,t) + \mathcal{O}(\epsilon^3) \end{cases} \quad (4.2)$$

Then, substituting these expansions into the boundary layer equations (2.10) through (2.14), and equating terms of order ϵ^2 to zero, gives the system of equations below:

$$\left\{ \begin{aligned} & \frac{\partial u_2}{\partial x} + \frac{\partial v_2}{\partial y} = 0 & (4.3) \\ & \frac{\partial u_2}{\partial t} + \left(u_2 \frac{\partial u_0}{\partial x} + u_0 \frac{\partial u_2}{\partial x} \right) + \left(v_2 \frac{\partial u_0}{\partial y} + v_0 \frac{\partial u_2}{\partial y} \right) = \frac{\partial^2 u_2}{\partial y^2} \\ & \quad - \left(u_1 e^{it} \frac{\partial u_1 e^{it}}{\partial x} + v_1 e^{it} \frac{\partial u_1 e^{it}}{\partial y} \right) & (4.4) \\ & u_2(x,0,t) = 0 & (4.5) \\ & v_2(x,0,t) = 0 & (4.6) \\ & u_2(x,y,t) \rightarrow 0 \quad \text{as } y \rightarrow \infty & (4.7) \end{aligned} \right.$$

Consider the terms in equation (4.4) which are due to the first-order unsteady flow. We evaluate the real parts of the velocity fluctuations and compute terms in equation (4.4) typically as follows:

$$\begin{aligned} \text{Re}(u_1 e^{i\omega T}) \frac{\partial}{\partial x} [\text{Re}(u_1 e^{i\omega T})] &= \frac{1}{2} \left[u_{1r} \frac{\partial u_{1r}}{\partial x} + u_{1i} \frac{\partial u_{1i}}{\partial x} \right] \\ &+ \frac{1}{2} \left[u_{1r} \frac{\partial u_{1r}}{\partial x} - u_{1i} \frac{\partial u_{1i}}{\partial x} \right] \cos 2\omega T - \frac{1}{2} \left[u_{1i} \frac{\partial u_{1r}}{\partial x} + u_{1r} \frac{\partial u_{1i}}{\partial x} \right] \sin 2\omega T \end{aligned} \quad (4.8)$$

Thus, the effect of these terms is to produce harmonic fluctuations at twice the fundamental frequency plus a time-independent contribution.

The above result, equation (4.8), suggests second-order velocity components of the following form:

$$\begin{cases} u_2 = \bar{u}_2(x,y) + \tilde{u}_2(x,y,t) \\ v_2 = \bar{v}_2(x,y) + \tilde{v}_2(x,y,t) \end{cases} \quad (4.9)$$

$$(4.10)$$

Then, substituting these into the set of equations (4.3) through (4.7), we obtain the governing equations for the time-independent flow as follows:

$$\left\{ \begin{aligned} \frac{\partial \bar{u}_2}{\partial x} + \frac{\partial \bar{v}_2}{\partial y} &= 0 \end{aligned} \right. \quad (4.11)$$

$$\left\{ \begin{aligned} \left(\bar{u}_2 \frac{\partial u_0}{\partial x} + u_0 \frac{\partial \bar{u}_2}{\partial x} \right) + \left(\bar{v}_2 \frac{\partial u_0}{\partial y} + v_0 \frac{\partial \bar{u}_2}{\partial y} \right) &= \frac{\partial^2 \bar{u}_2}{\partial y^2} \\ - \frac{1}{2} \left(u_{1r} \frac{\partial u_{1r}}{\partial x} + u_{1i} \frac{\partial u_{1i}}{\partial x} + v_{1r} \frac{\partial u_{1r}}{\partial y} + v_{1i} \frac{\partial u_{1i}}{\partial y} \right) & \end{aligned} \right. \quad (4.12)$$

$$\bar{u}_2(x,0) = 0 \quad (4.13)$$

$$\bar{v}_2(x,0) = 0 \quad (4.14)$$

$$\bar{u}_2(x,y) \rightarrow 0 \quad \text{as} \quad y \rightarrow \infty \quad (4.15)$$

The structure of equations (4.11) and (4.12), together with the prescription of zero velocity components at the plate surface and free-stream indicates that the flow is "driven" by the u_1 -terms in equation (4.12). These terms provide an "effective" pressure gradient which

varies throughout the flow field in a manner as indicated on Figure 28. This driving force diminishes with increasing distance along the plate. Also, due to the sign change of the driving terms, we recognize the possibility of reversals in the second-order flow direction within the layer.

We utilize the integral method to obtain approximate solutions for the steady correction due to the flow oscillations. The compatibility and integral conditions are obtained by computing the time-independent terms of order ϵ^2 in the expansions indicated in Sections 2.3.1. and 2.3.2. The resulting equations are:

order ϵ^2 compatibility conditions;

$$\left\{ \begin{array}{l} [\bar{u}_{2yy}]_{y=0} = 0 \end{array} \right. \quad (4.16)$$

$$\left\{ \begin{array}{l} [\tau_{2yyy}]_{y=0} = 0 \end{array} \right. \quad (4.17)$$

Figure 28. - Development of first-order "driving" terms in second order momentum equation. Plotted versus y are values of $-\frac{1}{2}\left(u_{1r}\frac{\partial u_{1r}}{\partial x} + v_{1r}\frac{\partial u_{1r}}{\partial y} + u_{1i}\frac{\partial u_{1i}}{\partial x} + v_{1i}\frac{\partial u_{1i}}{\partial y}\right)$.

Order ε^2 integral relations;

$$\left\{ \begin{aligned} \frac{d}{d\zeta} \int_0^\infty \left[2u_0 \bar{u}_2 + \frac{1}{2} (u_{1r}^2 + u_{1i}^2) - \frac{1}{2} u_{1r} - \bar{u}_2 \right] dy = - 2\zeta \left(\frac{\partial \bar{u}_2}{\partial y} \right)_{y=0} \end{aligned} \right. \quad (4.18)$$

$$\left\{ \begin{aligned} & \frac{d}{d\zeta} \int_0^\infty \left[\frac{3}{2} u_0^2 \bar{u}_2 + \frac{3}{4} u_0 (u_{1r}^2 + u_{1i}^2) - \frac{1}{2} \bar{u}_2 - \frac{1}{2} u_{1r} - \frac{1}{4} u_0 \right] dy \\ & = \zeta \int_0^\infty u_{1i} dy - \zeta \int_0^\infty \left[4 \left(\frac{\partial u_0}{\partial y} \right) \left(\frac{\partial \bar{u}_2}{\partial y} \right) + \left(\frac{\partial u_{1r}}{\partial y} \right)^2 + \left(\frac{\partial u_{1i}}{\partial y} \right)^2 \right] dy \end{aligned} \right. \quad (4.19)$$

$$\left\{ \begin{aligned} & \frac{d}{d\zeta} \int_0^\infty \left[\frac{4}{3} u_0^3 \bar{u}_2 + u_0^2 (u_{1r}^2 + u_{1i}^2) - \frac{1}{3} \bar{u}_2 - \frac{1}{2} u_0 - \frac{1}{2} u_{1r} \right] dy \\ & = 2\zeta \int_0^\infty u_0 u_{1i} dy - 4\zeta \int_0^\infty \left[\frac{1}{2} u_0 \left(\frac{\partial u_{1i}}{\partial y} \right)^2 + \frac{1}{2} u_0 \left(\frac{\partial u_{1r}}{\partial y} \right)^2 \right. \\ & \quad \left. + 2u_0 \left(\frac{\partial u_0}{\partial y} \right) \left(\frac{\partial \bar{u}_2}{\partial y} \right) + u_{1r} \left(\frac{\partial u_0}{\partial y} \right) \left(\frac{\partial u_{1r}}{\partial y} \right) + u_{1i} \left(\frac{\partial u_0}{\partial y} \right) \left(\frac{\partial u_{1i}}{\partial y} \right) + \bar{u}_2 \left(\frac{\partial u_0}{\partial y} \right)^2 \right] dy \end{aligned} \right. \quad (4.20)$$

4.2. Quasi-steady limit

In Section 2.1.1, we obtained a first-order quasi-steady solution for low-frequency free-stream fluctuations. The Blasius velocity was expanded in a Taylor series for small amplitude fluctuations for the

case of low frequency velocity fluctuations. The first-order quasi-steady solution was identified as the first-order correction to the flat plate boundary layer flow, due to a perturbation in the magnitude of the free-stream velocity.

We now consider the second-order quasi-steady solution corresponding to the mean flow correction treated in this chapter. That solution is obtained from the ϵ^2 terms in the expansion, equation (2.34). The result is:

$$\bar{u}_{2Q} = \frac{\eta}{32} F_B'' (6 - \eta F_B) \quad (4.21)$$

This velocity is represented by the solid line on Figure 29. Note especially the change in direction of the second-order flow.

The second-order quasi-steady velocity profile (Fig. 29) exhibits the following qualitative behavior:

- (a) zero at wall,
- (b) approaches zero as $\eta \rightarrow \infty$,
- (c) has one intermediate zero.

These characteristics are also possessed by profiles of the following form:

$$\bar{u}_{2Q} = e^{-P\eta} (q_1 \eta + q_2 \eta^2 + \dots) \quad (4.22)$$

The number of terms to be retained in the approximation (4.22) will be determined by comparing the quasi-steady solution to results by the integral method.

Figure 29. - Second-order quasi-steady velocity profile approximations for flat plate boundary layer with oscillating free-stream.

4.2.1. Four parameter profiles

We first consider four parameter profiles of the form (4.22); namely,

$$\bar{u}_{2q} = e^{-p\eta}(q_1\eta + q_2\eta^2 + q_3\eta^3) \quad (4.23)$$

The profile parameters are determined by the integral method using three integral relations and one compatibility condition. The corresponding approximations for u_0 and u_1 are also employed.

The compatibility condition (4.16) gives the simple result below:

$$q_2 = pq_1 \quad (4.24)$$

The integral relations are obtained from equations (4.18) through (4.20) by the usual procedure for quasi-steady cases; that is,

- (a) introduce matrix notation,
- (b) transform integration over y to integration over η (Section 2.5),
- (c) use F - notation, equation (2.88), to obtain algebraic equations for the integral relations.

The additional definitions required are:

$$\left\{ \begin{array}{l} f_6 = \bar{u}_{2q} = e^{-p\eta} [q_1\eta + pq_1\eta^2 + q_3\eta^3] \\ f_7 = \frac{\partial \bar{u}_{2q}}{\partial \eta} = e^{-p\eta} [q_1 + pq_1\eta + (3q_3 - p^2q_1)\eta^2 - pq_3\eta^3] \end{array} \right. \quad (4.25)$$

$$(4.26)$$

Then, upon following the steps indicated above, we obtain the following:

$$\left[F(6,1) - 2F(6,2) + \frac{1}{2} F(4,4) - \frac{1}{2} F(4,1) \right] + [2q_1] = 0 \quad (4.27)$$

$$\left[F(6,1,1) - 3F(6,2,1) + \frac{3}{2} F(6,2,2) + \frac{3}{4} F(4,4,1) - F(4,1,1) \right. \\ \left. - \frac{3}{4} F(4,4,2) + \frac{3}{2} F(4,2,1) - \frac{1}{2} F(2,1,1) \right] \\ + [4F(7,3,1) + F(5,5,1)] = 0 \quad (4.28)$$

$$\left[F(6,1,1) - 4F(6,2,1) + 4F(6,2,2) - \frac{4}{3} F(6,2,2,2) \right. \\ \left. - \frac{3}{2} F(4,1,1) + 4F(4,2,1) - 2F(4,2,2) + F(4,4,1) - 2F(4,4,2) \right. \\ \left. + F(4,4,2,2) - \frac{3}{2} F(2,1,1) + F(2,2,1) \right] + 2[4F(7,3,1) + F(5,5,1) \\ - 4F(7,3,2) - F(5,5,2) + 2F(5,3,1) - 2F(5,4,3) + 2F(6,3,3)] = 0 \quad (4.29)$$

Values of the roots (p, q_1, q_3) of equations (4.27) through (4.29) were computed by the method of Appendix C. The results are:

$$(p, q_1, q_3) = (0.4320, .1063, -.002975) \quad (4.30)$$

The velocity profile corresponding to this quasi-steady approximation is shown by the long dash - short dash curve on Figure 29. The general behavior outlined earlier for the quasi-steady solution is exhibited by this approximation but the quantitative comparison is poor.

4.2.2. Five parameter profiles

In this section, a five parameter profile is assumed in an attempt to improve the approximation of the quasi-steady solution. That profile is:

$$\bar{u}_{2q} = e^{-p\eta}(q_1\eta + q_2\eta^2 + q_3\eta^3 + q_4\eta^4) \quad (4.31)$$

An additional condition is now required to determine the fifth parameter by the integral method. The addition of a fourth integral relation would introduce a fourth differential equation in the integral method. Also, note from equations (4.18) through (4.20) that a fourth integral equation would be very cumbersome. Thus, we introduce the compatibility requirement (4.17) as the added condition. For profiles of the form of equation (4.31), the compatibility conditions (4.16) and (4.17) imply:

$$\begin{cases} q_2 = pq_1 \\ q_3 = \frac{1}{2} p^2 q_1 \end{cases} \quad (4.32)$$

$$\quad \quad \quad (4.33)$$

The three integral equations (4.18) through (4.20), then determine the remaining parameters.

It was noted in Section 2.5 that conditions satisfied by terms of order ϵ^n must have been satisfied to orders $1, \epsilon^1, \dots, \epsilon^n$ individually. We emphasize this point by considering the expansion below:

$$\begin{aligned} M(x,y,t) &= M_0(x,y) + \epsilon M_1(x,y) \cos t + \epsilon^2 [\bar{M}_2(x,y) + \tilde{M}_2(x,y) \cos 2t] + \dots \\ &= 0 \end{aligned} \quad (4.34)$$

In order that this expansion yield zero values for all arbitrary small ϵ , we require:

$$\left\{ \begin{array}{l} M_0 = 0 \\ M_1 \cos t = 0 \\ \bar{M}_2 = 0 \\ \tilde{M}_2 \cos 2t = 0 \end{array} \right. \quad \begin{array}{l} (4.35) \\ (4.36) \\ (4.37) \\ (4.38) \end{array}$$

Now consider the time average of equation (4.34) over some suitable interval; such as,

$$\bar{M}(x,y) = \int_0^{2\pi} M(x,y,t) dt = 2\pi [M_0 + \epsilon^2 \bar{M}_2 + \dots] = 0 \quad (4.39)$$

Here, the conditions on M_0 and $\bar{M}_2$ are precisely equations (4.35) and (4.37); and the conditions (4.36) and (4.38) are not required. Based on this illustration, we see that for the case at hand, the profiles of u_0 and $\bar{u}_2$ must satisfy the same conditions, but any suitable approximation for u_1 may be employed.

A five parameter profile approximation for the Blasius solution was obtained by the integral method. The resulting profile, which satisfies three integral relations and two compatibility conditions, is:

$$u_0 = 1 - e^{-A\eta}(1 + B\eta + C\eta^2 + D\eta^3 + E\eta^4) \quad (4.40)$$

where,

$$(A,B,C,D,E) = (2.0534, 1.7208, 1.4253, .7419, .3795)$$

(4.41)

The excellent agreement between this approximation and the Blasius solution is shown in Table 6. The u_1 -velocity results, obtained in Chapter III, were used for subsequent calculations.

The extension of the four parameter profile calculation to five parameters is very straightforward. In fact, we need only define the f -matrix for five parameter profiles and then apply the results of the previous section. The new matrix definitions are:

$$\{s_1\} = \begin{bmatrix} 0 \\ A \\ A \\ a \\ a \\ p \\ p \end{bmatrix} \quad (4.42)$$

$$[h_{im}] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 1 & B & C & D & E \\ A - B & AB - 2C & AC - 3D & AD - 4E & AE \\ 1 & b & c & d & 0 \\ a - b & ab - 2c & ac - 3d & ad & 0 \\ 0 & q_1 & pq_1 & q_3 & q_4 \\ q_1 & pq_1 & q_3 & 4q_4 - pq_3 & -pq_4 \end{bmatrix} \quad (4.43)$$

Then, with the F -functions based on these values, the algebraic equations for the integral relations (4.27) through (4.29), apply as written.

$\eta = \frac{y}{\zeta}$	Blasius value	Approximate value	Percent error
0.20	0.06641	0.06641	-0.01
0.40	0.13277	0.13196	-0.61
0.60	0.19894	0.19637	-1.29
0.80	0.26471	0.26021	-1.70
1.00	0.32979	0.32419	-1.70
1.20	0.39378	0.38854	-1.33
1.40	0.45627	0.45284	-0.75
1.60	0.51676	0.51618	-0.11
1.80	0.57477	0.57742	0.46
2.00	0.62977	0.63540	0.89
2.20	0.68132	0.68916	1.15
2.40	0.72899	0.73802	1.24
2.60	0.77246	0.78158	1.18
2.80	0.81152	0.81975	1.01
3.00	0.84605	0.85268	0.78
3.20	0.87609	0.88066	0.52
3.40	0.90177	0.90414	0.26
3.60	0.92333	0.92360	0.03
3.80	0.94112	0.93955	-0.17
4.00	0.95552	0.95250	-0.32
4.20	0.96696	0.96291	-0.42
4.40	0.97587	0.97121	-0.48
4.60	0.98269	0.97778	-0.50
4.80	0.98779	0.98293	-0.49
5.00	0.99155	0.98696	-0.46
5.20	0.99425	0.99008	-0.42
5.40	0.99616	0.99249	-0.37
5.60	0.99748	0.99433	-0.32
5.80	0.99838	0.99574	-0.26
6.00	0.99898	0.99681	-0.22
6.20	0.99937	0.99762	-0.17
6.40	0.99961	0.99823	-0.14
6.60	0.99977	0.99869	-0.11
6.80	0.99987	0.99903	-0.08
7.00	0.99992	0.99929	-0.06

Table 6. Comparison of five parameter profile approximation, based on three integral relations and two compatibility conditions, with the Blasius profile.

The roots (p, q_1, q_4) of the algebraic equations, as determined by the method of Appendix C, are as follows:

$$(p, q_1, q_4) = (1.1699, .05626, -.01594) \quad (4.44)$$

The velocity profile based on this five parameter approximation is represented by the dash line curve on Figure 29. We note the agreement in location of peak and zero values between the quasi-steady solution and the five parameter approximation.

4.3. Form parameters

We have just seen that the essential features of the second-order quasi-steady solution can be described by five parameter profiles, with profile coefficients determined by the integral method. Thus, we assume general second-order mean flow profiles of the form:

$$\bar{u}_2 = e^{-\phi y} (\psi_1 y + \psi_2 y^2 + \psi_3 y^3 + \psi_4 y^4) \quad (4.45)$$

The form factors $(\phi, \psi_1, \psi_2, \psi_3, \psi_4)$ are functions of the variable $\zeta = \sqrt{\omega X/U_0}$. Thus, equation (4.45) generates velocity profiles as continuous functions of distance along the plate (X) and is valid for arbitrary frequency values (ω).

We now compute the five form parameters in equation (4.45) by the integral method using three integral relations and two compatibility conditions.

4.3.1. Governing equations

The governing equations for the form parameters are obtained from the two compatibility conditions (4.16) and (4.17), plus the three integral relations (4.18) through (4.20).

Substitution of the velocity profile (4.45) into the compatibility conditions yields the following algebraic equations:

$$\begin{cases} \psi_2 = \phi \psi_1 \end{cases} \quad (4.46)$$

$$\begin{cases} \psi_3 = \frac{1}{2} \phi^2 \psi_1 \end{cases} \quad (4.47)$$

We note that the integral relations involve the real and imaginary parts of the complex velocity u_1 . Terms involving the sum of the squares of the real and imaginary parts of u_1 can be simplified by noting the following relation between a complex function w and its complex conjugate w^* :

$$ww^* = w_r^2 + w_i^2 \quad (4.48)$$

where

$$\begin{cases} w = w_r + iw_i \end{cases} \quad (4.49)$$

$$\begin{cases} w^* = w_r - iw_i \end{cases} \quad (4.50)$$

Using the result (4.48) in the integral equations (4.18) through (4.20) gives:

$$\left\{ \frac{d}{d\zeta} \int_0^\infty \bar{u}_2 (2u_0 - 1) dy = \frac{1}{2} \operatorname{Re} \left\{ \frac{d}{d\zeta} \int_0^\infty u_1 dy \right\} - \frac{1}{2} \frac{d}{d\zeta} \int_0^\infty u_1 u_1^* dy - 2\zeta \left(\frac{\partial \bar{u}_2}{\partial y} \right)_{y=0} \right. \quad (4.51)$$

$$\left\{ \frac{d}{d\zeta} \int_0^\infty \frac{1}{2} \bar{u}_2 (3u_0^2 - 1) dy = \operatorname{Re} \left\{ \frac{d}{d\zeta} \int_0^\infty \frac{u_1}{2} dy \right\} - \frac{d}{d\zeta} \int_0^\infty \frac{3}{4} u_0 u_1 u_1^* dy + \frac{1}{4} \frac{d}{d\zeta} \int_0^\infty u_0 dy \right. \\ \left. + \zeta I_m \left\{ \int_0^\infty u_1 dy \right\} - 4\zeta \int_0^\infty \frac{\partial u_0}{\partial y} \frac{\partial \bar{u}_2}{\partial y} dy - \zeta \int_0^\infty \frac{\partial u_1}{\partial y} \frac{\partial u_1^*}{\partial y} dy \right. \quad (4.52)$$

$$\left\{ \frac{d}{d\zeta} \int_0^\infty \frac{1}{3} \bar{u}_2 (4u_0^3 - 1) dy = \operatorname{Re} \left\{ \frac{d}{d\zeta} \int_0^\infty \frac{u_1}{2} dy \right\} - \frac{d}{d\zeta} \int_0^\infty u_0^2 u_1 u_1^* dy + \frac{1}{2} \frac{d}{d\zeta} \int_0^\infty u_0^2 dy \right. \\ \left. + 2\zeta I_m \left\{ \int_0^\infty u_0 u_1 dy \right\} - 4\zeta \int_0^\infty \bar{u}_2 \left(\frac{\partial u_0}{\partial y} \right)^2 dy - 8\zeta \int_0^\infty u_0 \frac{\partial u_0}{\partial y} \frac{\partial \bar{u}_2}{\partial y} dy \right. \\ \left. - 2\zeta \int_0^\infty \left[u_0 \frac{\partial u_1}{\partial y} \frac{\partial u_1^*}{\partial y} + u_1 \frac{\partial u_0}{\partial y} \frac{\partial u_1^*}{\partial y} + u_1^* \frac{\partial u_0}{\partial y} \frac{\partial u_1}{\partial y} \right] dy \right. \quad (4.53)$$

We reduce the equations (4.51) through (4.53) by following the steps employed for the first-order solution; that is (refer to Section 3.2)

- (a) introduce matrix notation,
- (b) carry out indicated differentiation,
- (c) transform integrals over y to integrals over η when the integrand depends on η alone,
- (d) define the G -functions for the integration sums,
- (e) write the equations in standard form for first-order ordinary differential equations.

The matrices are redefined to fit the needs of this section as follows:

$$[F_1] = \begin{bmatrix} 1 \\ 1 - u_0 \\ 1 - u_1 \\ \pi_2 \\ \frac{\partial u_0}{\partial y} \\ \frac{\partial u_1}{\partial y} \\ \frac{\partial \bar{u}_2}{\partial y} \\ \frac{\partial u_1}{\partial \tau} \\ - \tau \frac{\partial u_0}{\partial \tau} \\ \frac{\partial \pi_2}{\partial \phi} \\ \frac{\partial \bar{u}_2}{\partial \psi_1} \\ \frac{\partial \bar{u}_2}{\partial \psi_4} \\ 1 - u_1^* \\ \partial u_1^* / \partial y \\ \partial u_1^* / \partial \tau \end{bmatrix} \quad (4.54)$$

where

$$F_i = \sum_{m=0}^5 e^{-S_i y_m H_{1m}} \quad (4.55)$$

and

$$S = \begin{bmatrix} 0 \\ A/\zeta \\ \alpha \\ \phi \\ A/\zeta \\ \alpha \\ \phi \\ \alpha \\ A/\zeta \\ \phi \\ \phi \\ \phi \\ \alpha^* \\ \alpha^* \\ \alpha^* \end{bmatrix} \quad (4.56)$$

$$H = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & B/\zeta & C/\zeta^2 & D/\zeta^3 & E/\zeta^4 & 0 \\ 1 & \beta & \gamma & \delta & 0 & 0 \\ 0 & \psi_1 & \phi\psi_1 & \psi_3 & \psi_4 & 0 \\ (A-B)/\zeta & (AB-2C)/\zeta^2 & (AC-3D)/\zeta^3 & (AD-4E)/\zeta^4 & AE/\zeta^5 & 0 \\ (\alpha-\beta) & (\alpha\beta-2\gamma) & (\alpha\beta-3\delta) & \alpha\delta & 0 & 0 \\ \psi_1 & \phi\psi_1 & \psi_3 & 4\psi_4-\psi_3\phi & -\psi_4\phi & 0 \\ 0 & (\alpha'-\beta') & \alpha(\alpha'-\beta') & (\gamma\alpha'-\delta') & \delta\alpha' & 0 \\ 0 & (A-B)/\zeta & (AB-2C)/\zeta^2 & (AC-3D)/\zeta^3 & (AD-4E)/\zeta^4 & AE/\zeta^5 \\ 0 & 0 & 0 & 0 & -\psi_3 & -\psi_4 \\ 0 & 1 & \phi & \frac{1}{2}\phi^2 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 1 & \beta^* & \gamma^* & \delta^* & 0 & 0 \\ (\alpha^*-\beta^*) & (\alpha^*\beta^*-2\gamma^*) & (\alpha^*\gamma^*-3\delta^*) & \alpha^*\beta^* & 0 & 0 \\ 0 & (\alpha^{*'}-\beta^{*'}) & \alpha^*(\alpha^{*'}-\beta^{*'}) & (\gamma^*\alpha^{*'}-\delta^{*'}) & \delta^*\alpha^{*'} & 0 \end{bmatrix}$$

(4.57)

Then, upon carrying out the steps outlined above, we obtain the following governing equations for the form functions:

$$\left\{ \bar{P}_{11} \frac{d\phi}{d\zeta} + \bar{P}_{12} \frac{d\psi_1}{d\zeta} + \bar{P}_{13} \frac{d\psi_4}{d\zeta} = \bar{R}_1 \right. \quad (4.58)$$

$$\left. \bar{P}_{21} \frac{d\phi}{d\zeta} + \bar{P}_{22} \frac{d\psi_1}{d\zeta} + \bar{P}_{23} \frac{d\psi_4}{d\zeta} = \bar{R}_2 \right. \quad (4.59)$$

$$\left. \bar{P}_{31} \frac{d\phi}{d\zeta} + \bar{P}_{32} \frac{d\psi_1}{d\zeta} + \bar{P}_{33} \frac{d\psi_4}{d\zeta} = \bar{R}_3 \right. \quad (4.60)$$

where

$$\left\{ \begin{aligned} \bar{P}_{11} &= G(10,1) - 2G(10,2) \\ \bar{P}_{12} &= G(11,1) - 2G(11,2) \\ \bar{P}_{13} &= G(12,1) - 2G(12,2) \end{aligned} \right. \quad (4.61)$$

$$\left. \begin{aligned} \bar{P}_{21} &= G(10,1) - 3G(10,2) + \frac{3}{2} G(10,2,2) \\ \bar{P}_{22} &= G(11,1) - 3G(11,2) + \frac{3}{2} G(11,2,2) \\ \bar{P}_{23} &= G(12,1) - 3G(12,2) + \frac{3}{2} G(12,2,2) \end{aligned} \right. \quad (4.62)$$

$$\left. \begin{aligned} \bar{P}_{31} &= G(10,1) - 3G(10,2) + \frac{3}{2} G(10,2,2) \\ \bar{P}_{32} &= G(11,1) - 3G(11,2) + \frac{3}{2} G(11,2,2) \\ \bar{P}_{33} &= G(12,1) - 3G(12,2) + \frac{3}{2} G(12,2,2) \end{aligned} \right. \quad (4.63)$$

$$\bar{R}_1 = -2\epsilon\psi_1 + \frac{2}{\epsilon} G(9,4) + \frac{1}{2} \operatorname{Re}[G(8,1)] + \frac{1}{2}[G(15,3) - G(15,1) + G(13,8) - G(8,1)]$$

(4.64)

$$\bar{P}_{21} = G(10,1) - 3G(10,2) + \frac{3}{2} G(10,2,2) \quad (4.65)$$

$$\bar{P}_{22} = G(11,1) - 3G(11,2) + \frac{3}{2} G(11,2,2) \quad (4.66)$$

$$\bar{P}_{23} = G(12,1) - 3G(12,2) + \frac{3}{2} G(12,2,2) \quad (4.67)$$

$$\bar{R}_2 = -\frac{3}{\epsilon}[G(9,4,1) - G(9,4,2)] - \epsilon G(14,6) + \frac{1}{2} \operatorname{Re}[G(8,1)]$$

$$+ \frac{3}{4\epsilon} [G(13,9,3) - G(13,9,1) - G(9,3,1) + G(9,1,1)]$$

$$- 4\epsilon G(7,5) - \epsilon I_m [G(3,1)] - \frac{1}{4} \bar{F}$$

$$- \frac{3}{4} [G(15,3,2) - G(15,3,1) - G(15,2,1) + G(15,1,1)]$$

$$+ G(13,8,2) - G(13,8,1) - G(8,2,1) + G(8,1,1)] \quad (4.68)$$

$$\bar{P}_{31} = G(10,1) - 4G(10,2) + 4G(10,2,2) - \frac{4}{3} G(10,2,2,2) \quad (4.69)$$

$$\bar{P}_{32} = G(11,1) - 4G(11,2) + 4G(11,2,2) - \frac{4}{3} G(11,2,2,2) \quad (4.70)$$

$$\bar{P}_{33} = G(12,1) - 4G(12,2) + 4G(12,2,2) - \frac{4}{3} G(12,2,2,2) \quad (4.71)$$

$$\begin{aligned} \bar{R}_3 = & \frac{4}{\zeta} [G(9,4,1) - 2G(9,4,2) + G(9,4,2,2)] + 2\zeta \text{Im}[G(3,2) - G(3,1) - G(2,1)] \\ & - 2\zeta [G(14,6,1) - G(14,6,2) + G(14,5,1) - G(14,5,3) + G(6,5,1) - G(13,6,5)] \\ & - [G(15,1) - 2G(15,2) + G(15,2,2) - G(15,3,1) + 2G(15,3,2) - G(15,3,2,2)] \\ & - [G(8,1) - 2G(8,2) + G(8,2,2) - G(13,8,1) + 2G(13,8,2) - G(13,8,2,2)] \\ & + \frac{2}{\zeta} [G(13,9,3) + G(9,1,1) - G(13,9,1) - G(9,3,1) - G(13,9,3,2) + G(13,9,2,1) \\ & + G(9,3,2,1) - G(9,2)] - 4\zeta [2G(7,5,1) - 2G(7,5,2) + G(5,5,4)] \\ & - \frac{1}{2} \bar{F} + \frac{1}{2} \text{Re}[G(8,1)] \end{aligned} \quad (4.72)$$

$$\bar{F} = (A^4 + A^3B + 2A^2C + 6AD + 24E)/A^5 \quad (4.73)$$

4.3.2. Solution

The system of equations (4.58) through (4.60) is solved simultaneously for the slopes of the form parameters. The result is of the form given below:

$$\begin{cases} \frac{d\phi}{d\zeta} = \bar{\theta}_1(\phi, \psi_1, \psi_4, \zeta) \end{cases} \quad (4.74)$$

$$\begin{cases} \frac{d\psi_1}{d\zeta} = \bar{\theta}_2(\phi, \psi_1, \psi_4, \zeta) \end{cases} \quad (4.75)$$

$$\begin{cases} \frac{d\psi_4}{d\zeta} = \bar{\theta}_3(\phi, \psi_1, \psi_4, \zeta) \end{cases} \quad (4.76)$$

The initial values of (ϕ, ψ_1, ψ_4) are computed from the quasi-steady approximation obtained in Section 4.2.2.; namely

$$\left\{ \begin{array}{l} \phi_q \sim p/\zeta \\ \psi_{1q} \sim q_1/\zeta \\ \psi_{4q} \sim q_4/\zeta^4 \end{array} \right. \quad (4.77)$$

$$\quad (4.78)$$

$$\quad (4.79)$$

The differential equations, (4.74) through (4.76), were solved numerically using the Runge-Kutta formulas given in Appendix D. The initial values were obtained by evaluating equations (4.77) through (4.79) at a small value of ζ . Values of the function (α, β, δ) and $(\alpha', \beta', \delta')$ were numerically input from the first-order solution obtained in Chapter III. The resulting functions (ϕ, ψ_1, ψ_4) are shown graphically on Figure 30.

4.3.3 Velocity profiles

The profiles of the mean flow velocity component are readily obtained from equation (4.45) once the form functions have been determined. The development of the velocity component along the plate is shown on Figure 31. The general behavior is as would be expected by examining the "driving" terms on Figure 28; namely, spreading of the effected range of y values, and decrease in peak magnitudes, with increasing values of x along the plate.

Figure 30. - Second-order velocity profile form parameters for flat plate boundary layer with oscillating free-stream.

Figure 31. - Steady second-order velocity parallel to flat plate with oscillating free-stream. Numbers on the curves are values of $(\omega X / U_0)$.

CHAPTER V

SUMMARY AND CONCLUSIONS

The integral method of analysis was investigated for unsteady laminar boundary layer flows, and detailed computations were made for a specific case. Some general observations are then made based on the results of that example.

The flow over a flat plate with a free-stream having small harmonic fluctuations about a uniform mean value was considered in detail. The basic solution for the steady flow was shown to be the familiar Blasius solution. Small local velocity fluctuations (of order ϵ) were found to exhibit a phase lead with respect to the free-stream oscillations. The second-order (ϵ^2) velocity was shown to consist of a time-independent contribution plus fluctuations at twice the fundamental frequency. The first-order fluctuations provide the "input" force to drive the second-order flow. The contribution of the steady second-order flow was found to diminish with increasing distance along the plate.

The integral analysis of the above special case revealed a procedure which is generalized for unsteady flows as follows:

(1) Obtain asymptotic solutions for limiting cases of the flow under consideration. (For oscillating flow, these are the quasi-steady and Stokes flow solutions.)

(2) Assume velocity profiles with sufficient generality to include the asymptotic solutions. The feasibility of these forms can be tested by curve fit approximation of the asymptotic solutions (e.g., method of least squares).

(3) Apply integral relations and compatibility conditions, as required, to determine the profile form parameters. An integral relation is a weighted average of the momentum equation with weight function u^m . A compatibility condition is the j^{th} derivative of the momentum equation, with the result then evaluated at the boundary. The "mixture" of these is determined to yield the best approximation for the asymptotic solutions.

As a by-product of the integral analysis, a method of simplifying the computations was devised. Most profile approximations involve polynomial representations. Then, since the integral relations require powers of the velocity, the algebraic manipulations become awkward. Matrix representation of the profile approximation yields concise expressions for the equations. A function definition can then be introduced for the integral sums in cases where a general integration formula is available.

The two basic questions which arise in the integral analysis of unsteady flows are: What are the best profile forms to assume? and; How are the profile factors best computed? Based on this work, we offer the following answers: Assume profile forms which have the capability of describing the asymptotic solutions; Determine the form factors by applying integral and compatibility conditions, the number and type to be determined for best approximation of the asymptotic solutions.

APPENDIX A

DERIVATION OF THE GENERAL INTEGRAL RELATIONS

The X-momentum equation (2.2) is multiplied by a non-negative power of the local axial velocity U^k and integrated in the direction normal to the plate from the surface to the free-stream. The result is

$$\int_0^\infty U^k \frac{\partial U}{\partial T} dY + \int_0^\infty \left(U^{k+1} \frac{\partial U}{\partial X} + U^k V \frac{\partial U}{\partial Y} \right) dY = \int_0^\infty U^k \frac{\partial U}{\partial T} dY + \nu \int_0^\infty U^k \frac{\partial^2 U}{\partial Y^2} dY \quad (A-1)$$

First consider the following integral:

$$I_1 = \int_0^\infty V U^k \frac{\partial U}{\partial Y} dY \quad (A-2)$$

We note that the V-velocity is related to the U-velocity by the continuity equation (2.1). Integrating the continuity relation in the normal direction gives

$$V = - \int_0^Y \frac{\partial U}{\partial X} dY \quad (A-3)$$

Then equation (A-2) can be rewritten as follows:

$$I_1 = - \int_0^\infty \left(\int_0^Y \frac{\partial U}{\partial X} dY \right) \frac{\partial}{\partial Y} \left(\frac{U^{k+1}}{k+1} \right) dY \quad (A-4)$$

Integrating equation (A-4) by parts we obtain

$$I_1 = - \frac{U_{\infty}^{k+1}}{k+1} \int_0^{\infty} \frac{\partial U}{\partial X} dY + \int_0^{\infty} \frac{\partial}{\partial X} \left[\frac{U^{k+2}}{(k+1)(k+2)} \right] dY \quad (A-5)$$

Next consider the integral

$$I_2 = \int_0^{\infty} U^k \frac{\partial^2 U}{\partial Y^2} dY \quad (A-6)$$

For $k = 0$, the integral is evaluated directly and the result is

$$I_2 = \left[\frac{\partial U}{\partial Y} \right]_0^{\infty} = - \left(\frac{\partial U}{\partial Y} \right)_{Y=0} \quad k = 0 \quad (A-7)$$

For $k \neq 0$, equation (A-6) is integrated by parts and we obtain

$$I_2 = - \int_0^{\infty} k U^{k-1} \left(\frac{\partial U}{\partial Y} \right)^2 dY \quad k > 0 \quad (A-8)$$

Finally, upon substituting the results (A-5), (A-7), and (A-8) into equation (A-1) we obtain the following general integral relation:

$$\begin{aligned} & \frac{d}{dX} \int_0^{\infty} \frac{U}{k+1} (U^{k+1} - U_{\infty}^{k+1}) dY \\ &= \begin{cases} \int_0^{\infty} U^k \frac{\partial}{\partial T} (U_{\infty} - U) dY - v \left(\frac{\partial U}{\partial Y} \right)_{Y=0} & k = 0 \\ \int_0^{\infty} U^k \frac{\partial}{\partial T} (U_{\infty} - U) dY - v k \int_0^{\infty} U^{k-1} \left(\frac{\partial U}{\partial Y} \right)^2 dY & k > 0 \end{cases} \end{aligned} \quad (A-9)$$

APPENDIX B

CURVE FIT BY METHOD OF LEAST SQUARES

In this Appendix we describe a method of curve fitting assumed velocity profile forms to known profiles which are represented by a set of m points $(w_1, z_1), (w_2, z_2), \dots, (w_m, z_m)$. The profiles to be fit have the following form:

$$w = 1 - e^{-\bar{A}z} (1 + B_1 z + B_2 z^2 + \dots + B_n z^n) \quad (B-1)$$

We select a value of $\bar{A}$ (say A_0) and note that the difference between the known velocity and the profile value at the point z_1 is

$$D_1 = w_1 - \left[1 - e^{-A_0 z_1} (1 + B_1 z_1 + B_2 z_1^2 + \dots + B_n z_1^n) \right] \quad (B-2)$$

Then, forming the sum of the squares of the differences, we define

$$E_D \equiv \sum_{i=1}^m D_i^2 \quad (B-3)$$

The function E_D is treated as the error which is to be minimized by varying $(B_1, B_2, \dots, B_n)$. We do this in the usual manner by equating the following partial derivatives to zero:

$$\left. \begin{aligned} \frac{\partial E_D}{\partial B_1} &= \sum_{i=1}^m 2 \left[w_i - 1 + e^{-A_0 z_i} (1 + B_1 z_i + \dots + B_n z_i^n) \right] z_i e^{-A_0 z_i} = 0 \\ \frac{\partial E_D}{\partial B_n} &= \sum_{i=1}^m 2 \left[w_i - 1 + e^{-A_0 z_i} (1 + B_1 z_i + \dots + B_n z_i^n) \right] z_i^n e^{-A_0 z_i} = 0 \end{aligned} \right\} \quad (B-4)$$

The equations (B-4) can be put in the following form:

$$\left. \begin{aligned} b_{11} B_1 + b_{12} B_2 + \dots + b_{1n} B_n &= C_1 \\ b_{n1} B_1 + b_{n2} B_2 + \dots + b_{nn} B_n &= C_n \end{aligned} \right\} \quad (B-5)$$

where all coefficients $b_{pq}(z_1, z_2, \dots, z_m; A_0)$ and $C_r(z_1, z_2, \dots, z_n; w_1, w_2, \dots, w_m; A_0)$ are known.

The system of algebraic equations (B-5) is solved simultaneously for the coefficients $B_1, B_2, \dots, B_n$. The error is then computed from equation (B-3) for the value of A_0 selected. The process is reported for different values of $\bar{A}$ and a graph of $E_D(\bar{A})$ versus $\bar{A}$ is constructed. The value of $\bar{A}$ which produces the minimum error is determined graphically, and the corresponding values of $B_1, B_2, \dots, B_n$ are computed.

The results presented here were based on a set of 40 points ($m = 40$), and accuracy of three significant figures.

APPENDIX C

METHOD OF SOLUTION FOR SYSTEMS OF NONLINEAR ALGEBRAIC EQUATIONS

The determination of the velocity profile form parameters often requires solving a system of nonlinear algebraic equations of following form:

$$g_1(A, B, C, \dots) = 0 \quad (C-1)$$

In this Appendix, the method employed in this work for all such calculations is presented.

First, consider the simple case of one equation of the type (C-1); that is,

$$g_1(A) = 0 \quad (C-2)$$

In this case, a graph of g_1 versus A is constructed and the appropriate root is selected.

Next consider two equations of the following form:

$$\begin{cases} g_1(A, B) = 0 & (C-3) \\ g_2(A, B) = 0 & (C-4) \end{cases}$$

A value of A ($A = A^*$) is picked, and the first equation is evaluated for that A^* for two selected values of B ; that is,

$$\begin{cases} g_1(A^*, B_1) = (g_1^*)_1 & (C-5) \\ g_1(A^*, B_2) = (g_1^*)_2 & (C-6) \end{cases}$$

Referring to Figure 32, the value of B for which g_1 is zero (with $A = A^*$) is computed by using the following approximation:

$$B^* = B_1 - (g_1^*)_1 \frac{B_2 - B_1}{(g_1^*)_2 - (g_1^*)_1} \quad (C-7)$$

The value of $g_2^*(A^*, B^*)$ is computed and graphed versus A^* to determine the solution set (A, B) . The process is repeated, with selected values of B chosen closer to the calculated root until the desired accuracy is achieved.

A system of three equations of the type (C-1) has the form given below:

$$\begin{cases} g_1(A, B, C) = 0 \end{cases} \quad (C-8)$$

$$\begin{cases} g_2(A, B, C) = 0 \end{cases} \quad (C-9)$$

$$\begin{cases} g_3(A, B, C) = 0 \end{cases} \quad (C-10)$$

A procedure is employed which is an extension of the above procedure for two equations. Assumed values of C are also required, and the linear representations shown on Figure 33 are utilized. The resulting equations for B^* and C^* are the following:

$$\begin{cases} C^* = C_1 - (g_2^*)_1 \frac{C_2 - C_1}{(g_2^*)_2 - (g_2^*)_1} \end{cases} \quad (C-11)$$

$$\begin{cases} B^* = B_1^{**} - (g_2^*)_1 \frac{B_2^{**} - B_1^{**}}{(g_2^*)_2 - (g_2^*)_1} \end{cases} \quad (C-12)$$

Now, a graph of g_3^* versus A^* is constructed to obtain the roots, and the procedure is continued to achieve the desired accuracy.

Figure 32. - Linear approximation for a non-linear function of one variable.

Figure 33. - Linear approximating for a nonlinear function of two variables.

APPENDIX D

FOURTH-ORDER RUNGE-KUTTA INTEGRATION FORMULAS

In this Appendix we list the Runge-Kutta formulas which were used to solve the systems of three coupled first-order ordinary differential equations of the form given below:

$$\left\{ \begin{array}{l} \frac{d\alpha}{d\zeta} = \theta_1(\alpha, \beta, \delta, \zeta) \\ \frac{d\beta}{d\zeta} = \theta_2(\alpha, \beta, \delta, \zeta) \\ \frac{d\delta}{d\zeta} = \theta_3(\alpha, \beta, \delta, \zeta) \end{array} \right. \quad \begin{array}{l} \text{(D-1)} \\ \text{(D-2)} \\ \text{(D-3)} \end{array}$$

The initial conditions are as follows:

$$\left\{ \begin{array}{l} \alpha(\zeta_0) = \alpha_0 \\ \beta(\zeta_0) = \beta_0 \\ \delta(\zeta_0) = \delta_0 \end{array} \right. \quad \begin{array}{l} \text{(D-4)} \\ \text{(D-5)} \\ \text{(D-6)} \end{array}$$

We apply a step-by-step procedure starting at ζ_0 and apply the following formulas (c.f. Levy and Baggott (32)):

$$\left\{ \begin{array}{l} \alpha_{n+1} = \alpha_n + \frac{1}{6} (k_0 + 2k_1 + 2k_2 + k_3) \\ \beta_{n+1} = \beta_n + \frac{1}{6} (\ell_0 + 2\ell_1 + 2\ell_2 + \ell_3) \\ \delta_{n+1} = \delta_n + \frac{1}{6} (m_0 + 2m_1 + 2m_2 + m_3) \end{array} \right. \quad \begin{array}{l} \text{(D-7)} \\ \text{(D-8)} \\ \text{(D-9)} \end{array}$$

where,

$$\left\{ \begin{array}{l} k_0 = \Delta \cdot \theta_1(\alpha_n, \beta_n, \delta_n, \zeta_n) \end{array} \right. \quad (D-10)$$

$$\left\{ \begin{array}{l} k_1 = \Delta \cdot \theta_1\left(\alpha_n + \frac{1}{2} k_0, \beta_n + \frac{1}{2} \ell_0, \delta_n + \frac{1}{2} m_0, \zeta_n + \frac{1}{2} \Delta\right) \end{array} \right. \quad (D-11)$$

$$\left\{ \begin{array}{l} k_2 = \Delta \cdot \theta_1\left(\alpha_n + \frac{1}{2} k_1, \beta_n + \frac{1}{2} \ell_1, \delta_n + \frac{1}{2} m_1, \zeta_n + \frac{1}{2} \Delta\right) \end{array} \right. \quad (D-12)$$

$$\left\{ \begin{array}{l} k_3 = \Delta \cdot \theta_1(\alpha_n + k_2, \beta_n + \ell_2, \delta_n + m_2, \zeta_n + \Delta) \end{array} \right. \quad (D-13)$$

$$\left\{ \begin{array}{l} \ell_0 = \Delta \cdot \theta_2(\alpha_n, \beta_n, \delta_n, \zeta_n) \end{array} \right. \quad (D-14)$$

$$\left\{ \begin{array}{l} \ell_1 = \Delta \cdot \theta_2\left(\alpha_n + \frac{1}{2} k_0, \beta_n + \frac{1}{2} \ell_0, \delta_n + \frac{1}{2} m_0, \zeta_n + \frac{1}{2} \Delta\right) \end{array} \right. \quad (D-15)$$

$$\left\{ \begin{array}{l} \ell_2 = \Delta \cdot \theta_2\left(\alpha_n + \frac{1}{2} k_1, \beta_n + \frac{1}{2} \ell_1, \delta_n + \frac{1}{2} m_1, \zeta_n + \frac{1}{2} \Delta\right) \end{array} \right. \quad (D-16)$$

$$\left\{ \begin{array}{l} \ell_3 = \Delta \cdot \theta_2(\alpha_n + k_2, \beta_n + \ell_2, \delta_n + m_2, \zeta_n + \Delta) \end{array} \right. \quad (D-17)$$

$$\left\{ \begin{array}{l} m_0 = \Delta \cdot \theta_3(\alpha_n, \beta_n, \delta_n, \zeta_n) \end{array} \right. \quad (D-18)$$

$$\left\{ \begin{array}{l} m_1 = \Delta \cdot \theta_3\left(\alpha_n + \frac{1}{2} k_0, \beta_n + \frac{1}{2} \ell_0, \delta_n + \frac{1}{2} m_0, \zeta_n + \frac{1}{2} \Delta\right) \end{array} \right. \quad (D-19)$$

$$\left\{ \begin{array}{l} m_2 = \Delta \cdot \theta_3\left(\alpha_n + \frac{1}{2} k_1, \beta_n + \frac{1}{2} \ell_1, \delta_n + \frac{1}{2} m_1, \zeta_n + \frac{1}{2} \Delta\right) \end{array} \right. \quad (D-20)$$

$$\left\{ \begin{array}{l} m_3 = \Delta \cdot \theta_3(\alpha_n + k_2, \beta_n + \ell_2, \delta_n + m_2, \zeta_n + \Delta) \end{array} \right. \quad (D-21)$$

In the fourth-order formulas given above we have defined:

$$\Delta = \zeta_{n+1} - \zeta_n \quad (D-22)$$

BIBLIOGRAPHY

1. Schlichting, H., Boundary Layer Theory, McGraw-Hill Book Company Inc., New York, New York, 1960.
2. Rott, N., "Theory of Time-Dependent Laminar Flows", in Theory of Laminar Flows, (F. K. Moore Editor), Princeton University Press, Princeton, New Jersey, 1964.
3. Stuart, J. T., "Unsteady Boundary Layers", in Laminar Boundary Layers, (L. Rosenhead Editor), Oxford University Press, Oxford, Great Britian, 1963.
4. Stewartson, K., "The Theory of Unsteady Laminar Boundary Layers", in Advances in Applied Mechanics, Vol. VI, (H. L. Dryden and Th. von Kármán Editors). Academic Press, New York, New York, 1960, pp. 1-37.
5. Moore, F. K., "Unsteady Laminar Boundary Layer Flow", NACA Technical Note, 2471, 1951.
6. Lighthill, M. J., "The Response of Laminar Skin Friction and Heat Transfer to Fluctuations in the Stream Velocity", Proc. Roy. Soc., A224, 1954, pp. 1-23.
7. Ostrach, S., "Compressible Laminar Boundary Layer and Heat Transfer For Unsteady Motions of a Flat Plate", NACA Technical Note, 3569, 1955.
8. Moore, F. K. and Ostrach, S., "Average Properties of Compressible Laminar Boundary Layer on Flat Plate with Unsteady Flight Velocity", NACA Technical Note, 3886, 1956.
9. Illingworth, C. R., "The Effects of a Sound Wave on the Compressible Boundary Layer on a Flat Plate", Journal of Fluid Mechanics, Vol. 3, 1958, pp. 471-493.
10. Glauert, M. B., "The Laminar Boundary Layer on Oscillating Plates and Cylinders", Journal of Fluid Mechanics, Vol. 1, 1956, pp. 97-110.

11. Stuart, J. T., "A Solution of the Navier-Stokes and Energy Equations Illustrating the Response of Skin Friction and Temperature of an Infinite Plate Thermometer to Fluctuations in the Stream Velocity", Proc. Roy. Soc., A231, 1955, pp. 116-130.
12. Rott, N. and Rosenzweig, M. L., "On the Response of the Laminar Boundary Layer to Small Fluctuations of the Free-Stream Velocity", Journal of the Aerospace Sciences, 1960, pp. 741-747.
13. Lin, C. C., "Motion in the Boundary Layer with a Rapidly Oscillating External Flow", Proc. 9th Intern. Congress Appl. Mech., Brussels, Vol. 4, 1957, pp. 155-167.
14. Nickerson, R. J., "The Effect of Free-Stream Oscillations on the Boundary Layers on a Flat Plate", WADC Technical Report, No. 57-481, 1958.
15. Kestin, J., Maeder, P. F., and Wang, H. E., "On Boundary Layers Associated with Oscillating Streams", Appl. Sci. Res., Section A, Vol. 10, 1961, pp. 1-22.
16. Gersten, K., "Heat Transfer in Laminar Boundary Layers with Oscillating Outer Flow", AGARDograph No. 97, 1965, pp. 423-475.
17. Hill, G and Stenning, A. H., "Laminar Boundary Layers in Oscillatory Flow", Journal of Applied Mechanics, September 1960, pp. 593-608.
18. McCroskey, W. J. and Yaggy, P. F., "Laminar Boundary Layers on Helicopter Rotors in Forward Flight", AIAA Journal, Vol. 6, No. 10, October, 1968, pp. 1919-1926.
19. Illingworth, C. R., "Unsteady Viscous Flow Due to a Rotating Blade", University of Wisconsin Mathematics Research Center, Technical Summary Report No. 801, July 1968.
20. Young, W. H. and Williams, III, J. C., "The Boundary Layer on Rotating Blades in Forward Flight", AIAA 8th Aerospace Sciences Meeting, Paper No. 70-49, January 1970.
21. Longuet-Higgins, M. S., "Mass Transport in Water Waves", Phil. Trans. Roy. Soc., A245, March 1953, pp. 535-581.
22. Johns, B., "On the Mass Transport Induced by Oscillatory Flowing a Turbulent Boundary Layer", Journal of Fluid Mechanics, Vol. 43, Part 1, 1970, pp. 177-185.
23. Moore, D., "The Mass Transport Velocity Induced by Free Oscillations at a Single Frequency", Geophysical Fluid Dynamics, Vol. 1, 1970, pp. 237-247.

24. Walz, A., Boundary Layers of Flow and Temperature, The M.I.T. Press, Cambridge, Mass., 1969.
25. Han, L. S., "Hydrodynamic Entrance Lengths for Incompressible Laminar Flow in Rectangular Ducts", Journal of Applied Mechanics Vol. 27, No. 3, September 1960, pp. 403-409.
26. Han, L. S. and Cooper, A. L., "Approximate Solutions of Two Internal Flow Problems - Solution by an Integral Method." Proc. of 4th U.S. Nat'l. Cong. of Appl. Mech., Vol. 2, ASME, 1962, pp. 1269-1278.
27. Tani, I., "On the Approximate Solution of the Laminar Boundary-Layer Equations", Journal of the Aeronautical Sciences, July 1954, pp. 487-495.
28. Head, M. R., "An Approximate Method of Calculating the Laminar Boundary Layer in Two-Dimensional Incompressible Flow", Aeronautical Research Council, Reports and Memoranda No. 3123, 1959.
29. Siegel, R., "Transient Free Convection From a Vertical Flat Plate", ASME Transactions, February 1958, pp. 347-359.
30. Rozin, L. A., "An Approximation Method For the Integration of the Equations of a Nonstationary Laminar Boundary Layer in an Incompressible Fluid", NASA Technical Translation, TT-F22, 1960.
31. Akamatsu, T., "The Two-Parameter Integral Method for Unsteady Laminar Incompressible Boundary Layer Over a Semi-Infinite Flat Plate", Bulletin of JSME, Vol. 11, No. 48, 1968, pp. 1091-1100.
32. Levy, H. and Baggott, E. A., "Numerical Solutions of Differential Equations", Dover Publications, New York, New York, 1950.