INFORMATION TO USERS

The most advanced technology has been used to photograph and reproduce this manuscript from the microfilm master. UMI films the text directly from the original or copy submitted. Thus, some thesis and dissertation copies are in typewriter face, while others may be from any type of computer printer.

The quality of this reproduction is dependent upon the quality of the copy submitted. Broken or indistinct print, colored or poor quality illustrations and photographs, print bleedthrough, substandard margins, and improper alignment can adversely affect reproduction.

In the unlikely event that the author did not send UMI a complete manuscript and there are missing pages, these will be noted. Also, if unauthorized copyright material had to be removed, a note will indicate the deletion.

Oversize materials (e.g., maps, drawings, charts) are reproduced by sectioning the original, beginning at the upper left-hand corner and continuing from left to right in equal sections with small overlaps. Each original is also photographed in one exposure and is included in reduced form at the back of the book. These are also available as one exposure on a standard 35mm slide or as a 17" x 23" black and white photographic print for an additional charge.

Photographs included in the original manuscript have been reproduced xerographically in this copy. Higher quality 6" x 9" black and white photographic prints are available for any photographs or illustrations appearing in this copy for an additional charge. Contact UMI directly to order.

University Microfilms International
A Bell & Howell Information Company
300 North Zeeb Road, Ann Arbor, MI 48106-1346 USA
313/761-4700 800/521-0600

Order Number 9011216

Master production scheduling in uncertain environments

Lin, Neng-Pai, Ph.D.

The Ohio State University, 1989

Copyright ©1989 by Lin, Neng-Pai. All rights reserved.

U·M·I
300 N. Zeeb Rd.
Ann Arbor, MI 48106

**MASTER PRODUCTION SCHEDULING
IN UNCERTAIN ENVIRONMENTS**

DISSERTATION

**Presented in Partial Fulfillment of the Requirements for
the Degree Doctor of Philosophy in the Graduate
School of the Ohio State University**

by

Neng-Pai Lin, B.E., M.A.

The Ohio State University

1989

Dissertation Committee:

Dr. L. J. Krajewski

Dr. W. C. Benton

Dr. K. Leong

Approved by

A handwritten signature in black ink, appearing to read 'L. J. Krajewski', written over a horizontal line.

**Dr. L. J. Krajewski
Advisor**

Graduate Program in Business Administration

Copyright by

Neng-Pai Lin

1989

To my parents

ACKNOWLEDGEMENTS

I express sincere appreciation and deep gratitude to Professor Lee Krajewski for his support and guidance throughout this research and the Ph.D. program. As my Dissertation Advisor and Committee Chairperson, his encouragement, intellectual stimulus, and patience has been a major source of strength in accomplishing this study. I shall always appreciate his advice and suggestions.

Professor W. C. Benton has been an active member of my dissertation committee and also my Academic advisor. I thank him for his encouragement and valuable comments during the Ph.D. program and throughout this research.

Professor Keong Leong also has been an active member of my dissertation committee. I thank him for his patience, support, and valuable suggestions while pursuing this research.

I am ever indebted to my wife, Su-Chen Hung, for her love, support, patience, and personal sacrifices. I thank my two lovely daughters, Eva, who has inspired me to pursue the Ph.D. degree, and Joanna, for their understanding.

VITA

June 1, 1953 Born - Tainan, Taiwan

1975 B. Engineering, National Taiwan University, Taipei, Taiwan

1975-1977 Second Lieutenant & Engineer, Republic of China Army, Taiwan

1977-1978 Structure Engineer, Sino-Tech Consulting Co., Taipei

1978-1980 Deputy Project Manager, Chao-Tai Real Estate Developer, Taipei

1980-1981 Project Manager, Ya-Ta Construction Co., Taipei

1981-1983 Financial Manager, Yuan-Jung Construction Co., Taipei

1983-1986 Project Manager, Fu-Tsu Construction Co., Taipei

1987 Graduate Research Assistant, Academic Faculty of Management Sciences, The Ohio State University, Columbus, Ohio, USA

1987-1989 Graduate Teaching Associate, Academic Faculty of Management Sciences, The Ohio State University, Columbus, Ohio, USA

PUBLICATIONS

"Strategy of Inspection Station Location." with L. J. Krajewski and J. Hutchison, Decision Sciences Institute National Conference Proceedings, Las Vegas, 1988.

"Master Production Scheduling in Uncertain Environments," with L. J. Krajewski, to appear in Decision Sciences Institute National Conference Proceedings, New Orleans, 1989.

FIELDS OF STUDY

Major Field: Productions & Operations Management

Minor Field: Computer & Information Science

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	iii
VITA	iv
LIST OF TABLES	ix
LIST OF FIGURES	x
CHAPTER	PAGE
I INTRODUCTION	1
1.1 Master Production Scheduling and Its Related Activities	4
1.1.1 Demand Management	4
1.1.2 Aggregate Production Planning	6
1.1.3 Final Assembly Scheduling	6
1.1.4 Master Scheduling Item Selection, Competitive Delivery Time, and Product Profile	7
1.1.5 Rough-Cut Capacity Planning	8
1.1.6 Master Production Scheduling	10
1.2 Master Production Scheduling in Uncertain Environments: The Rolling Schedule Procedure	12
1.2.1 MPS Time Intervals in a Rolling Schedule	12
1.2.2 Cumulative Lead Time	16
1.2.3 Rolling Schedule Procedure for the MPS	20
1.2.4 An Example: Union Fork and Hoe Co. Columbus, Ohio plant	21
1.3 Master Production Scheduling in Uncertain Environments: The MPS Change and Forecast Error Costs	23
1.3.1 Nervousness	24
1.3.2 MPS Change Cost	26
1.3.3 Forecast Error Cost	29
1.3.4 Summary	30
1.4 Research Objectives	31
1.5 Research Design	34
1.6 Contributions and Limitations of This Research	38
1.7 Outline of Research Presentation	39
II. LITERATURE REVIEW	40
2.1 Deterministic Environment with Static Schedule	42
2.2 Deterministic Environment with Rolling Schedule	44
2.2.1 Forecast Window	44
2.2.2 Frozen Interval	47

2.2.3	MPS Change	48
2.2.4	Lot-Sizing Rule (without MPS Change Cost)	49
2.2.5	Lot-Sizing Rule (with MPS Change Cost)	52
2.3	Uncertain Environment with Rolling Schedule	54
2.4	Summary	57
III.	MPS MODEL	61
3.1	Periodic Review System in a Rolling Schedule	65
3.2	Forecast Error Cost	69
3.3	MPS Change Cost	74
3.3.1	Unit Change Cost Function	74
3.3.2	Examples of the Unit Change Cost Function	76
3.3.3	Size of MPS Change	79
3.4	Setup and Inventory Holding Costs of the MSI	82
3.5	The MPS Model	83
IV.	EVALUATION OF THE MPS MODEL AND SENSITIVITY ANALYSIS ...	86
4.1	Rules for Choosing Time-Between-Orders, Replanning Interval, and Forecast Window	88
4.1.1	Time-Between-Orders for the POQ Rule	88
4.1.2	Replanning Interval and Forecast Window	89
4.2	Evaluation of the MPS Model	91
4.2.1	Simulation Model	92
4.2.2	Experimental Design	95
4.2.3	Procedure for Finding the BEST	100
4.2.4	Results of the Experiments	100
4.3	The Effects of F and R on TC	107
4.3.1	Experimental Design	107
4.3.2	Results	115
4.3.3	Discussion	118
4.4	The Effects of Environmental Factors on the BEST	120
4.4.1	Relationship Between the BEST and magnitude of Unit Change Cost	121
4.4.2	Relationship Between the BEST and CLT	126
4.4.3	Relationship Between the BEST and Other Factors	128
4.5	Conclusions	129
V.	MULTIPLE MSIs	131
5.1	MMPS Model	132
5.1.1	The MMPS Model	132
5.1.2	Evaluation of the MMPS Model	134
5.1.3	Effects of F and R on TTC	139
5.2	Rules for Choosing the Time-Between-Orders, Replanning Interval, and Forecast window	139
5.2.1	Time-Between-Orders for the POQ rule	139
5.2.2	Replanning Interval and Forecast Window	141
5.2.3	Evaluation of the Choice of $M=N_c$	141
5.2.4	Procedure for Finding the BEST-C	143

5.3	Cost Increase Due to Using the BEST-C	146
5.3.1	Cycle Deviation	147
5.3.2	Relationship Between COST-I and Cycle Deviation	147
5.3.3	Discussion	149
VI.	CONCLUSIONS	155
6.1	Rolling Schedule for Developing MPS	155
6.2	MMPS Model	156
6.3	Managerial Implications	158
6.4	Contributions	161
6.5	Future Research	163
	LIST OF REFERENCES	165
	APPENDIX	169

LIST OF TABLES

TABLE	PAGE
1.1 Weekly Master Production Schedule	11
1.2 Relationship Between Cumulative Lead Time and Other Time Intervals	17
1.3 MRP Nervousness	25
1.4 The Manufacturing Environment	35
2.1 Selected Articles on the MPS Problems	41
3.1 Notation	63
3.2 Differences Between the MPS Model and the Manufacturing Environment	85
4.1 Replanning Interval and MPS Changes	90
4.2 Experimental Factors	96
4.3 Evaluation of MPS Model - Normal Distribution	102
4.4 Evaluation of MPS Model - Uniform Distribution	103
4.5 Evaluation of MPS Model - TC	106
4.6 Adjustments for the Relationships Between the BEST and A_2 ($FU=1$, $N=2$)	122
5.1 Evaluation of MPS Model ($M=N-1$)	136
5.2 Evaluation of MPS Model ($M=N+1$)	137
5.3 Environments Where $BEST_1 \neq BEST_2$	138
5.4 Experimental Factors for the Evaluation of $M=I(N_c)$	144
5.5 Results of Evaluation of $M=I(N_c)$	145
5.6 Cycle Deviation Settings	150
5.7 Results of the COST-I	151

LIST OF FIGURES

FIGURES	PAGE
1.1 Master Production Scheduling and Related Activities	5
1.2 Product Profile	9
1.3 MPS Time Intervals in a Rolling Schedule	13
1.4 Relationship Between Execution Interval and Replanning Interval	15
1.5 Bills of Materials	19
1.6 Production Process in Union Plant	22
1.7 Unit Change Cost	28
3.1 Periodic Review System in a Rolling Schedule	66
3.2 Relationship Between Forecast Error and Frozen Interval	70
3.3 Forecast Error Cost When F/R is not an Integer	73
4.1 Simulation Flow Chart	93
4.2 Unit Change Cost Function	98
4.3 MPS Model Flow Chart	101
4.4 Effects of F and R on TC	109
4.5 Relationship Between the BEST and A_2	123
4.6 Unit Change Cost Function (CLT=17)	125
4.7 Relationship Between the BEST and CLT	127
5.1 Relationship Between CD and COST-I	152

CHAPTER I

INTRODUCTION

Production and operations planning in organizations quite often is a multi-level process that includes demand management, aggregate production planning, final assembly scheduling, master production scheduling, material requirements planning, and capacity planning. Among them master production scheduling is one of the most important activities. It takes the outputs from demand management and aggregate production planning as inputs to determine the master production schedules which specify the lot sizes for master scheduling items. A master scheduling item (MSI) is an item that is incorporated in the master production schedule. The master production scheduling then passes the lot-sizing decisions to the material requirements planning (MRP) system. The master production schedule (MPS) is the key input to the MRP system. Orlicky (1975) states "...the master production schedule constitutes the input that 'drives' it (MRP system). It is the prime input on which an MRP system depends for its real effectiveness and usefulness." We can see that the MPS is crucial to the success of the whole production system.

Although master production scheduling has been studied extensively, most researchers assume a deterministic environment and consider master production scheduling as an independent activity. Research about master production scheduling in the real world, where demand is uncertain, is lacking. In the uncertain environment, the MPS is developed using demand forecasts. When there are forecast errors, the actual demands

may not be fully satisfied by a production rate based on the MPS. In order to keep a desired customer service level, the forecast errors must be handled in the appropriate way.

There are several options that can be used to handle the forecast errors of the MSI. The first one is to replan the MPS *every period* using the newest updated demand data. This procedure was referred to as a "rolling schedule" in Baker (1977), and a "flexible scheduling" in Yano and Carlson (1985). In this option, the MPS in each planning cycle is changed to respond to new customer requirements. These MPS changes induce unstable schedules of components and raw materials through the MRP system, and may cause extra costs. The second option is to freeze the *entire* MPS and keep enough safety stock to cover the expected forecast errors. This procedure was called the "fixed scheduling" in Yano and Carlson (1985). This option avoids the MPS changes but increases the inventory holding cost. Both options are costly.

Most firms use a procedure which includes the *principles* of these two options to develop the MPS. They replan the MPS periodically and freeze a portion of the MPS in each planning cycle. This procedure includes the above two options. In this study, this procedure is called a **rolling schedule**. The rolling schedule procedure not only allows the MPS changes, but also carries some safety stock for the item. We call the cost associated with the MPS changes in a rolling schedule the "MPS change cost" and the cost associated with carrying the safety stock the "forecast error cost." The MPS change and forecast error costs will be discussed in detail in Section 1.3.

The performance of a rolling schedule procedure depends on two decisions. The first decision is how often should the MPS be replanned. The second decision is how many periods should the MPS be frozen in each planning cycle. We call the first decision the choice of the "replanning interval" and the second decision the choice of the "frozen interval." These two time intervals will be discussed in detail in Section 1.2.1. There is a tradeoff between these two decisions. For example, in order to reach a desired service

level, the firm can either replan the MPS more frequently, which will reduce the required safety stock but increase the MPS changes, or freeze a larger portion of the MPS, which will reduce the MPS changes but increase the required safety stock. One question emerges: In an uncertain environment with a rolling schedule, how often should the MPS be replanned and how many periods should the MPS be frozen so that the total cost is minimized?

This dissertation seeks answers to the above question. It develops a heuristic model that approximates the *expected* system cost of an MPS which is determined using a rolling schedule. The MPS in this dissertation is given as the quantity that must be finished on the date specified. The model defines a mathematical relationship between the system costs and environmental factors. It expresses the expected average system cost as a function of frozen and replanning intervals, and other environmental factors. The model can be used to find the best combination of frozen and replanning intervals that minimize the expected system cost. Based on the model, this research will provide the guidelines for choosing the frozen and replanning intervals for an MPS in the short term and long term. This dissertation also considers the environments with multiple MSIs and provides guidelines for choosing the *common* frozen and replanning intervals for *all* MSIs.

In order to understand the problems associated with the MPS in uncertain environments, Section 1.1 briefly describes master production scheduling as well as its related activities. Section 1.2 discusses the rolling schedule procedure for developing the MPS in uncertain environments. Section 1.3 addresses the costs needed to be considered during the development of the MPS, and the interaction between these costs and various environmental factors. Section 1.4 presents the objectives of this dissertation, followed by the research design in Section 1.5. The contributions and limitations of this research are described in Section 1.6. Finally, Section 1.7 provides the outline of the remainder of the dissertation.

1.1 Master Production Scheduling and Its Related Activities

Figure 1.1 illustrates an example of the relationship of master production scheduling to other activities. The arrows indicate the flows of information and feedback among these activities. Note that Figure 1.1 does not intend to represent all possible production systems. Relationships other than that shown in Figure 1.1 are possible. For example, aggregate production planning may not be necessary for a make-to-order small job shop. This section briefly describes master production scheduling as well as its related activities shown in Figure 1.1, starting from demand management down to rough-cut capacity planning. The descriptions in Section 1.1 are not intended to cover all possible activities. Activities different from that described in Section 1.1 are possible. For example, although most make-to-stock firms typically select end items as the master scheduling items, some firms use groups of end items as the master scheduling items. One such example is the Ethan Allen Furniture Company described in Berry et al. (1979).

1.1.1 Demand management

Demand management involves customer demand forecasting, customer order entry, and order promising. These customer demands and orders may take the form of forecasts as well as actual customer orders, interplant requirements, warehouse requirements, and service part demands. In most production systems there are many end items. Often it is not tractable to forecast demands for all individual end items. The forecasts of products that have similar demand, processing, labor, and materials requirements usually are grouped together to get product family forecasts. These product family forecasts are used for preparing the aggregate production plan and for estimating the production requirements for individual end items in preparing the MPS. Order entry involves the receipt of

Figure 1.1
Master Production Scheduling and Related Activities

customer orders which are summarized and classified in terms of end items and promise dates. They represent the actual demands for individual end items.

1.1.2 Aggregate production planning

Aggregate production planning determines the aggregate levels of production rates, work-force levels, and inventory investments which take into consideration customer requirements and capacity limitations. The term "aggregate" implies the aggregations of products, resources, and time. The aggregate production plan balances conflicting objectives such as maximizing customer service, minimizing inventory investment, maintaining a stable work force, minimizing production cost, and maximizing profit. It usually covers a horizon of one year. The aggregated production rates of the product families are disaggregated into production rates of individual end items. This information is used to prepare the final assembly schedule or MPS.

1.1.3 Final assembly scheduling

The final assembly schedule specifies the schedule of final assembly, testing, and packing operations for end items. It represents a commitment to produce specific end-item configurations to satisfy customer demands. These customer demands are based upon actual customer orders generated from demand management. The final assembly schedule is constrained by the availability of components provided by the master production schedule. In a make-to-stock environment, the final assembly schedule is usually combined with the master production schedule. In other environments, how the final assembly schedule is linked with the master production schedule and demand management will be explained in the next section.

1.1.4 Master scheduling item selection, competitive delivery time, and product profile

The MSI can be at the end item level, component level, or raw material level. A survey reported by Schroeder et al. (1981) indicated that the average MRP system user has about six bill-of-material (BOM) levels. When there are many BOM levels, the MSI needs to be selected from these BOM levels.

The selection of the MSI depends on two factors, among others. The first one is the **competitive delivery time**. The competitive delivery time of an end item represents the delivery lead time that customers desire for that item. Often the MSI and the components *below* the MSI in the BOM (the components closer to the raw material state) are make-to-stock. The components *above* the MSI in the BOM are make-to-order or assemble-to-order. Hence the selection of the MSI in part determines the **response time** relative to customer demands for the end items. The response time is the time interval from the period a customer order is received to the period the order quantity is shipped to the customer. The closer the MSI is to the finished state, the shorter the response time. If the response time of an end item is longer than the competitive delivery time of that item, it must be cut down to equal or less than the competitive delivery time. One way to reduce the response time is to move the MSI *up* through the BOM, that is, master schedule the items closer to the finished state. The tradeoff of moving the MSI up through the BOM is shorter response time versus higher inventory investment. From this perspective, the selection of the MSI is done with recognition of the need to compete on the basis of competitive delivery time.

Another consideration in selecting the MSI is the total number of them. The gross requirements of the MSI are usually determined by forecasts. Malko (1980) indicated the key for selecting the MSI is to identify the least number of items that need demand forecasting (independent demands) and then calculate the demands of all other items

(dependent demands) from the forecasts of those few items. From this perspective, the selection of the MSI depends on the **product profile** of the production system.

The product profile of a production system is a shape that describes the numerical quantities of end items related to intermediate items (subassemblies, assemblies, components) and raw materials. Figure 1.2 indicates three typical product profiles. The make-to-stock type illustrates a production system which produces a limited number of end items with no or few options. In this environment, a firm usually selects end items as master scheduling items, and holds most inventory at the end-item level. Final assembly schedule is not necessary. The assemble-to-order type illustrates a production system which produces many end items with many options from relatively few subassemblies. In this environment, a firm usually selects subassemblies as master scheduling items, and holds most inventory at the subassembly level. Final assembly schedule is used to determine assembly requirements for end items. The make-to-order type illustrates a production system that produces many different end items from few raw materials. In this case, a firm usually selects specific customer orders or raw materials as master scheduling items, and holds most inventory at the raw material level.

1.1.5 Rough-cut capacity planning

Rough-cut capacity planning checks the feasibility of the developed MPS relative to the available resources of the firm. It analyzes the MPS to determine capacity problems at critical production facilities. It is called ***rough-cut*** because it is intended to provide only an approximation of actual resource requirements. There are many rough-cut capacity planning techniques. Berry et al. (1982) describe in detail three of them, namely, Capacity Planning using Overall Factors (CPOF), Capacity Bills, and Resource Profiles.

Figure 1.2 Product Profile

The results of rough-cut capacity planning sometimes lead to changes in the MPS in order to accommodate the capacity limitations of the critical facilities, or adjustments of capacity to maintain the MPS.

1.1.6 Master production scheduling

Once the MSI is selected, the master production schedule is executed to determine the lot sizes for the MSI. The objective of the lot-sizing decision is to minimize total inventory costs and still satisfy customer requirements. The efficiency of these decisions depends on the lot-sizing rule and the time horizons used for this rule. These time horizons will be discussed in Section 1.2.1. How to choose proper time horizons for an MPS depends on several factors. In general, an MPS typically covers a time horizon so that there is enough information for the planning of activities from procuring the raw materials to finishing the MSI.

Master production scheduling also sets due dates for the completion of production orders and provides the basis for determining the resources required to support the production plan. The sum of the MPS across all items in a product family is usually equal to the aggregate production rate for that product family. The MPS is subject to change if capacity limitations from the rough-cut capacity analysis are discovered.

How the MPS is linked together with the aggregate production plan and capacity limitations can be explained by an example shown in Table 1.1. In this example, the company produces different types of baggage. All products are made to stock and have a lead time equal to zero. For production planning purposes, the entire line of products are grouped into several families based on the size of the baggage. One in particular, the 26-inch family, includes three different end items, namely Red, Brown, and Green. The production plan for the 26-inch family calls for 1200 units in June and 1500 units in July.

Table 1.1 Weekly Master Production Schedule

Product	June				July			
	Week				Week			
	1	2	3	4	5	6	7	8
Red		230		230		240		240
Brown	150	150	150	150	225	225	225	225
Green	70		70		60		60	
Monthly Total	1200				1500			

Table 1.1 illustrates one possible master production schedule for the family. It specifies the quantities to be produced in weekly buckets for all end items. Notice the sum of the MPS equals 1200 units in June and 1500 units in July. The feasibility of the MPS is then checked using rough-cut capacity planning. When capacity limitations are discovered, the MPS needs to be adjusted. For example, if the maximal capacity in week 6 is only 225 units of Brown and 200 units of Red, 40 units of Red must be produced in week 5 or earlier.

1.2 Master Production Scheduling in Uncertain Environments: The Rolling Schedule Procedure

In uncertain environments, a rolling schedule is usually utilized for determining the MPS. This section describes the rolling schedule procedure. Section 1.2.1 defines the MPS time intervals in a rolling schedule. Section 1.2.2 defines the cumulative lead time of an MSI and discusses how it relates to other time intervals. The rolling schedule procedure for determining the MPS is then summarized in Section 1.2.3. Finally, Section 1.2.4 presents an example that demonstrates this procedure.

1.2.1 MPS time intervals in a rolling schedule

In order to fully comprehend the complexity of implementing a rolling schedule procedure for the MPS, several important time intervals need to be defined. Figure 1.3 shows these time intervals. The **production horizon** is the entire time interval that the MSI is planned and produced. Our purpose is to minimize the system costs within the entire production horizon. The time between two successive replannings of the MPS is called the **replanning interval**. How often the MPS is replanned is determined by the replanning

Figure 1.3 MPS Time Intervals in a Rolling Schedule

interval. In each planning cycle, the MPS within a finite number of periods, called the **forecast window**, is determined using the newly updated forecast data.

The last step in producing the MSI usually includes assembling several components together. In order to have enough time to assemble these components for the MSI, the MPS is usually determined several periods before it is implemented. In other words, the forecast window starts several periods after the **current period**. The current period here is the period in which the MPS is replanned. For example, in Figure 1.3, period T_1 is the current period for the first planning cycle and T_3 is the current period for the second planning cycle. The time interval between the current period and the start of the forecast window is called the **planning lead time**.

Once an MPS within the forecast window is developed, usually only the decisions of the first or first few periods, called the **execution interval**, are actually frozen and implemented. Consequently, the MPS within the planning lead time and execution interval is frozen after the MPS is replanned. The time interval including the planning lead time and the execution interval is called the **frozen interval**. In Figure 1.3, the frozen interval for planning cycle 1 is from T_1 to T_4 (also from T_3 to T_5 for planning cycle 2). The other part of the forecast window, that is, the periods beyond the execution interval, is called the **free interval**. The MPS within the free interval will be modified in the next planning cycle based on the new MPS.

The execution interval is strongly related to the replanning interval. If the frozen interval is kept constant as the MPS is rolled ahead, the execution interval eventually equals the replanning interval even though these two time intervals may not be the same at the beginning of the rolling schedule. The example in Figure 1.4 demonstrates the relationship between these two time intervals. In Figure 1.4, the frozen interval is 8 periods. The replanning interval is 4 periods. At the beginning of the rolling schedule, the execution interval is 5 periods and the planning lead time is 3 periods. As the MPS is rolled ahead,

Figure 1.4 Relationship Between Execution Interval and Replanning Interval

the new frozen interval still covers 8 periods, which is from period 5 to period 12. The new planning lead time is from period 5 to period 8, and equals 4 periods. The new execution interval is the newly added frozen periods to the schedule, which is from period 9 to period 12, and equals 4 periods. The new execution interval differs from the beginning execution interval, but equals the replanning interval. Therefore, in this research, the execution interval will also be called replanning interval.

1.2.2 Cumulative lead time

In order to allow proper advance planning for the components and raw materials, the forecast window depends on the **cumulative lead time** of the MSI and other time intervals. The cumulative lead time is the time interval from the *planning* of the procurement of raw materials to the completion of the MSI. Its definition will be explained later in this section. The relationship between the cumulative lead time and other time intervals is also shown in Figure 1.3. As shown in this figure, the forecast window in planning cycle 1 covers a time interval up to period T_7 , which is beyond the ending period of the cumulative lead time in planning cycle 2 (T_6). This relationship can be expressed as:

$$\begin{aligned} \text{Planning lead time} + \text{Forecast window} &\geq \text{Replanning interval} \\ &+ \text{Cumulative lead time} \end{aligned} \quad (1.1)$$

Equation (1.1) can be rewritten as:

$$\begin{aligned} \text{Forecast window} &\geq \text{Replanning interval} + \text{Cumulative lead time} \\ &- \text{Planning lead time} \end{aligned} \quad (1.2)$$

The rationale of this relationship can be explained by Table 1.2. In this table, planning lead time equals 2, replanning interval equals 2, cumulative lead time equals 6, and the current period for planning cycle 1 is period 1, and lot-sizing rule is lot-for-lot (L4L). According to equation (1.2), the forecast window should be greater than or equal to $(2+6-2)$, which is 6. If the forecast window is less than 6 and equal to 5, as shown in

**Table 1.2 Relationship Between Cumulative Lead Time
and Other Time Intervals**

Period	1	2	3	4	5	6	7	8	9	10
Gross Requirement	0	0	10	10	10	10	10	10	10	10
MPS in Planning Cycle 1	#		10	10	10	10	10			
MPS in Planning Cycle 2			#		10	10	10	10	10	

(a)

Period	1	2	3	4	5	6	7	8	9	10
Gross Requirement	0	0	10	10	10	10	10	10	10	10
MPS in Planning Cycle 1	#		10	10	10	10	10	10		
MPS in Planning Cycle 2			#		10	10	10	10	10	10

(b)

#: Current Period

Table 1.2(a), a new order with 10 units will be needed for period 8 in planning cycle 2. But the time interval between the current period of planning cycle 2, which is period 3, and period 8 is only 5 periods. This time interval is less than the cumulative lead time of the MSI. Consequently, this new order can not be finished by a "normal" process. On the other hand, if the forecast window is 6, as shown in Table 1.2(b), the order for period 8 will be scheduled in planning cycle 1 and will have enough lead time to be finished.

The cumulative lead time here includes not only the lead time for procurement/manufacturing, but also the proper planning horizon for the lot-sizing decisions. The rationale is: without the proper planning horizon, the lot-sizing decisions of components may have high setup and inventory holding costs. The proper planning horizon for an item depends on its lot-sizing rule and demand pattern. In the following discussions, the planning horizons for all items are assumed known and given.

We use two MSIs with their BOM structures shown in Figure 1.5 to explain how to calculate the cumulative lead time for an MSI. In both cases item 1 represents the MSI. The planning horizons for the MSI and all intermediate items are assumed to be zero. The planning horizons for the raw materials are shown in the figure. In Figure 1.5(a), the cumulative lead time of item 1 equals the sum of the manufacturing/procurement lead times (LT_i) for items 1, 2, 3, 4, and 5 plus an appropriate planning horizon for lot-sizing decisions of the raw material, item 5 (PH_5), and equals $(3+3+3+3+3+6)$, which is 21. When the MSI has more than one component, as shown in figure 1.5(b), the cumulative lead time of item 1 equals:

$$\text{Cumulative lead time} = \text{maximum} \{LT_1 + (LT_i + PH_i)\}, i=2,3,4,5,$$

where LT_i is the manufacturing/procurement lead time for item i and PH_i is the planning horizon for item i . Consequently, the cumulative lead time of the MSI in Figure 1.5(b) equals $[\text{maximum} \{(3+3+6), (3+3+4), (3+3+4), (3+3+6)\}]$, which is 12.

* LT_i is the manufacturing/procurement lead time for item i .

** PH_i is the planning horizon for item i .

Figure 1.5 Bills of Materials

1.2.3 Rolling schedule procedure for the MPS

In a rolling schedule, the time intervals described in Sections 1.2.1 and 1.2.2 must be assigned before the MPS is developed. Some of these time intervals are determined according to the production system characteristics. For example, the production horizon depends on the manufacturing strategy. The cumulative lead time depends on the BOM structure of the MSI and the lot-sizing rule. The free interval equals the forecast window minus the replanning interval. The replanning interval, frozen interval, and planning lead time are interdependent. The frozen interval equals the sum of the planning lead time and replanning interval. Consequently, there are actually three variable time intervals - the forecast window, frozen interval, and replanning interval - in a rolling schedule procedure.

In summary, the rolling schedule procedure for determining the MPS includes the following steps:

- 1) Select a lot-sizing rule. Determine the forecast window, frozen interval, and replanning interval before the rolling schedule is implemented.
- 2) Forecast the demands within the forecast window a "planning lead time" interval before the MSI is actually scheduled.
- 3) Based on the demand forecasts, determine the MPS within the forecast window using the lot-sizing rule.
- 4) Implement the MPS within the execution interval.
- 5) Roll the MPS ahead based on the replanning interval. Repeat steps (2) and (3). Update the MPS within the free interval of the previous planning cycle. Repeat step (4).
- 6) Repeat step (5) until the entire production horizon is covered.

1.2.4 An example: Union Fork and Hoe Co. Columbus, Ohio plant

In this section, we present an example, Union Fork and Hoe Co. Columbus, Ohio plant, that demonstrates the procedure for developing the MPS. Union Fork and Hoe Company is a hand tool producer established in 1890 with headquarters in Columbus, Ohio. Union's products include shovels, spades, scoops, pushers, scrapers, rakes, hoes, forks, hooks, and other small hand tools. Union has two manufacturing plants and eight handle plants. The manufacturing plants produce all finished products and components except wooden handles, which are supplied from the handle plants. Finished products are shipped to distribution centers and then customers.

The plant in Columbus, Ohio employs about 600 people and produces 1400 end items with about 4200 components and raw materials. End items include finished products that are shipped directly to distribution centers and various types of metal "heads" for hand tools that are sold to other manufacturers of garden tools. Annual sales are between 50 and 100 million dollars. Typical production lead time is 3-6 weeks. Typical assembly lead time is 1 week. The plant holds 6-8 weeks finished good inventory, 4 weeks work-in-process inventory, and 8 weeks raw material inventory.

The simplified flow diagram in Figure 1.6 illustrates the production process of the Columbus plant. Most operations are performed in the forge and assembly departments. Production in the forge department is batch oriented. There are several individual machines which are arranged in a flow-shop type layout. There are also four machine cells where several machines are grouped together. These cells combine components together to produce different types of metal "heads" that are used for different finished products. Each machine cell is dedicated to produce several heads. These metal heads are selected as master scheduling items. The assembly department assembles metal heads and wooden handles together as finished products and works to a final assembly schedule. It also performs labelling and packing activities.

Figure 1.6 Production Process in Union plant

The master production schedule determines the lot sizes for the metal heads. Annual production requirements of these items are determined as:

$$\begin{aligned} \text{annual production requirement} &= \text{annual forecasted sales} - \text{beginning inventory} \\ &+ \text{desired ending inventory} \end{aligned}$$

The annual production requirement divided by annual workdays becomes the daily production requirement. The forecast window for the MPS is three months. The MPS is replanned monthly, that is, the replanning interval is one month. At each planning cycle the master production scheduler determines a three-month MPS, 15 days in advance, that is, the planning lead time is 15 days. For example, the MPS from August 1 to October 31 is determined on July 15. Once the MPS is determined, it is not changed until the next planning cycle, that is, the frozen interval is one month and 15 days. The MPS is rolled ahead and the same procedure is applied.

1.3 Master Production Scheduling in Uncertain Environments:

The MPS Change and Forecast Error Costs

When utilizing a rolling schedule, the MPS within free interval is subject to change. These MPS changes may incur extra costs. The cost associated with the MPS changes in a rolling schedule is called the "MPS change cost." However, the MPS within the frozen interval is fixed. Some safety stock must be carried to provide the desired amount of protection against stockouts within this interval. The cost associated with carrying the safety stock is called the "forecast error cost." The following sections discuss these two costs and the interactions between them and environmental factors. Section 1.3.1 describes the MRP nervousness caused by MPS changes, followed by a discussion of the MPS change cost. Section 1.3.3 presents the forecast error cost. Finally, Section 1.3.4 provides the summary.

1.3.1 Nervousness

The MPS within the free interval may be changed in the next planning cycle as the MPS is rolled ahead. When MRP is used as the materials planning and control system, the MRP logic derives the gross requirements of a component from the lot-sizing decisions of its parents. The lot size changes of an MSI cause changes in the timing and lot size of its components and hence other components and raw materials down through the BOM. In this way, the MPS changes cause **nervousness** in the MRP system.

Nervousness is a term that describes the sensitivity of a production schedule to changes in the timing and size of parent item lots. Mather (1977) presents an example to demonstrate MRP nervousness caused by MPS changes. Part of the example is shown in Table 1.3. In this example, there are three BOM levels consisting of an end item, a subassembly, and a raw material. Each end item needs one unit of subassembly and each subassembly needs one unit of raw material. We assume the lead time for the end item equals zero and the MPS for the end item is shown at the top of Table 1.3. The planned order releases (POR) for the subassembly and raw material are calculated using the MRP logic and lot-for-lot (L4L) rule, and shown in Table 1.3(a). When the MPS in period 2 is changed from 20 to 40, it alters the requirements of the subassembly and raw material. Using the same MRP logic, the planned order releases (PORs) for the subassembly and raw material are recalculated and shown in Table 1.3(b). Notice the PORs for both the subassembly and raw material have been changed. Two new setups are required. Also, the scheduled receipt of 30 for raw material in period 3 is now required in period 1. This change may incur extra costs.

In general, nervousness resulting from the MPS changes takes three forms. In the first form, the lot sizes are changed for those periods in which setups are already scheduled. In the second form, new setups are incurred for the periods in which they were not previously scheduled. The example in Table 1.3 demonstrates this situation.

Table 1.3 MRP Nervousness

End item		1	2	3	4	5	6	7	8
Period									
Master Production Schedule		0	20	0	30	0	25	0	35
Subassembly Lead Time = 1 week Lot Size = Lot for Lot									
Gross requirement		0	20	0	30	0	25	0	35
On Hand (10)			10						
Scheduled Receipts									
Net Requirement					30		25		35
POR				30		25		35	
Raw Material Lead Time = 2 weeks Lot Size = Lot for Lot									
Gross requirement		0	0	30	0	25	0	35	0
On Hand				30					
Scheduled Receipts				30					
Net Requirement						25		35	
POR				25		35			

(a)

End item		1	2	3	4	5	6	7	8
Period									
Master Production Schedule		0	40	0	30	0	25	0	35
Subassembly Lead Time = 1 week Lot Size = Lot for Lot									
Gross requirement		0	40	0	30	0	25	0	35
On Hand (10)			10						
Scheduled Receipts			20		30		25		35
Net Requirement									
POR		20		30		25		35	
(New setup)									
Raw Material Lead Time = 2 weeks Lot Size = Lot for Lot									
Gross requirement		20	0	30	0	25	0	35	0
On Hand				30					
Scheduled Receipts			Expedite	30					
Net Requirement		20		20		25		35	
POR		20		25		35			
(New setup)									

(b)

Source: Mather, H., "Reschedule the Reschedules You Just Rescheduled - Way of Life for MRP?," Production & Inventory Management, Vol 18, No 1, 1977, 60-79.

Setups are required in period 1 for both the subassembly and raw material. In the third form, expedite action notices are required to speed up the scheduled receipts. The example in Table 1.3(b) also represents this form in which an expedite action notice is required for the raw material.

1.3.2 MPS change cost

Each form of nervousness has its associated costs. These costs may include additional paperwork, computer time, setup cost, overtime, and expedite costs. The degree of MRP nervousness, that is, the number of lot size changes, new setups, and expedite action notices required due to the MPS changes, multiplied by the costs associated with each form of nervousness, becomes the total cost of nervousness. Since this cost comes from MPS changes, it is called the **MPS change cost**.

The degree of nervousness depends on the lot-sizing rule used, the BOM structure of the MSI, and the magnitude of the MPS change. For an MSI with a given lot-sizing rule and BOM structure, the degree of nervousness due to an MPS change depends on the magnitude of the MPS change. A lot size increase from 10 to 30 should cause greater costs than a lot size increase from 10 to 20. We define the total cost of nervousness associated with a one-unit change in the lot size of an MSI the **unit change cost**. The unit change cost here is an approximation. The MPS change cost for the lot size increase from 0 to 20 may be less than twice of that for the lot size increase from 0 to 10, because both changes need one new setup. Also, the unit change cost for the lot size increase may be different from that for the lot size decrease. Here we assume both are the same. The MPS change cost equals the unit change cost times the size of the MPS change.

The unit change cost is expected to depend on the number of periods in the future for which the MPS change occurs. Due to the lead time required for preparing the components and raw materials, an MPS change closer to the current period will have more chance to

require an expedite action notice or a new setup for its components and raw materials. In general, we assume that the MPS changes closer to the current period cost more than those further away and MPS changes beyond the cumulative lead time of the MSI can be managed without any extra costs.

This assumption can also be verified by the policies used in practice for managing MPS changes. Many companies use time fences to establish guidelines for the kinds of MPS changes that can be made in various periods. Usually the closer the period is to the current period, the more rigid the MPS for that period. For example, Black and Decker Co. described in Berry et al. (1979) uses three time fences to manage MPS changes. For 0-8 weeks, the MPS changes are very unlikely. For 8-13 weeks, only minor MPS changes will be accepted. For 13-26 weeks the MPS changes are negotiable. For the periods longer than 26 weeks, the MPS is free to change as long as it is consistent with the aggregate production plan. Based on this assumption, we describe the unit change cost for period t , $U_1(t)$, as a function of the time interval (v_1) between the current period, t , and period t that experiences an MPS change:

$$U_1(t) \text{ (Unit change cost for period } t) = f_m(v_1), \quad (1.3)$$

where $v_1 = t - t_1$. Figure 1.7(a) describes one possible relationship between the unit change cost and the time interval (v_1).

When utilizing a rolling schedule, the MPS within the planning lead time is frozen before the MPS is replanned each planning cycle. Only the MPS after the planning lead time is subject to change. The unit change cost for the periods within the free interval in each planning cycle depends not only on the function $f_m(v_1)$ but also on the planning lead time. Figure 1.7(b) shows a rolling schedule. The unit change cost for the periods within the free interval in each planning cycle is shown in Figure 1.7(c).

Another factor about the MPS change cost is the size of the MPS change. The size of the MPS change depends on the forecast error, planning lead time, and replanning interval,

Figure 1.7 Unit Change Cost

among others, and will be discussed in Chapter 3, Section 3.3.2. Hence the MPS change cost is affected by the planning lead time and replanning interval, or the frozen and replanning intervals, when a rolling schedule is implemented.

1.3.3 Forecast error cost

In an uncertain environment, actual demands may be different from demand forecasts. These differences are called forecast errors. Usually the MPS is developed using the requirements from demand forecasts. The actual demands may not be totally satisfied by the MPS if the actual demands are higher than the demand forecasts. In a rolling schedule, the MPS within the frozen interval is fixed even though the actual demands may turn out to be higher than the forecasts. When this happens, a firm can either carry safety stock or allow stockouts. The cost associated with stockouts and safety stock inventory due to forecast error is called the **forecast error cost**. Given a desired customer service level, the forecast error cost in this study is assumed to be the cost of carrying the safety stock required to satisfy the service level. The required safety stock depends on the magnitude of forecast error. Larger forecast errors induce more safety stock. The relationship can be expressed as:

$$(\text{Required safety stock})_t = f_1(\text{Forecast error})_t \quad (1.4)$$

The magnitude of forecast error depends on the time interval (u) between the current period, t , and the forecast period t . The demand forecast for the period five weeks from now should be more "accurate" than the demand forecast for the period ten weeks from now. In other words, *the expected forecast error is a function of the time interval (u)*:

$$(\text{Forecast error})_t = f_2(u) \quad (1.5)$$

where $(\text{Forecast error})_t$ is the expected forecast error for period t and $u=t-t$. From equations (1.2) and (1.3), the required safety stock can be expressed as a function of u , assuming a fixed customer service level, and:

$$(\text{Required safety stock})_t = f_1(f_2(u)) = f_3(u) \quad (1.6)$$

When utilizing a rolling schedule, the MPS within the frozen interval (F) is fixed. The forecast error cost equals the cost of carrying the required safety stock due to the forecast errors within the entire interval F :

$$\text{Forecast error cost} = h \left\{ \sum_{t=1}^{t+F} (\text{Required safety stock})_t \right\} = h \left\{ \sum_{u=1}^F f_3(u) \right\}, \quad (1.7)$$

where h is the inventory holding cost. Equation (1.7) shows that the forecast error cost depends on the frozen interval.

1.3.4 Summary

Combining all discussions together, in an uncertain environment with a rolling schedule, in order to achieve a desired service level, we can replan the MPS more frequently or freeze a larger portion of the MPS. The first option will reduce the forecast error cost but increase the MPS change cost, while the second option will reduce the MPS change cost but increase the forecast error cost. For an environment with fixed environmental factors, the sum of the MPS change cost and forecast error cost depends on the choices of two decision variables: the frozen interval, and replanning interval. The system costs can be reduced by assigning appropriate frozen and replanning intervals before a rolling schedule is implemented.

1.4 Research Objectives

This research studies master production scheduling in uncertain environments where the MPS is determined using a rolling schedule procedure. It focuses on the choices of frozen and replanning intervals for the MPS. When utilizing a rolling schedule, the MPS changes based on the sizes which are derived from demand forecasts, and the required safety stock for a fixed service level is based on forecast errors. In the real world, the demand forecasts and forecast errors change from one planning cycle to another. Consequently, the lot-sizing decision, the MPS change, the required safety stock, and hence the system costs are changed from one planning cycle to another. It is very difficult to calculate the *exact* system costs.

This research develops a heuristic model that *approximates* the expected average system cost of an MPS which is determined using a rolling schedule procedure. This model defines a mathematical relationship between the system costs and environmental factors. It expresses the expected average system cost as a function of the frozen and replanning intervals of the MPS, and other environmental factors. Based on tests carried out on the heuristic model, we can better understand the consequences of the choices of frozen and replanning intervals on total cost. Using this model, we can also find the best combination of frozen and replanning intervals for an MSI that minimizes total cost. The results from this model are used to develop guidelines for managing the MPS in uncertain environments.

The objectives of this research are quite different from previous research in several dimensions. Most previous studies about the rolling schedule focus on deterministic environments. They missed one key point regarding the rolling schedule: The main motivation for utilizing a rolling schedule is the existence of uncertain demands. This research focuses on the uncertain environments. Many previous studies focus on the

forecast window and lot-sizing rule, considering setup and inventory holding costs. This research addresses the choices of frozen and replanning intervals, considering not only the setup and inventory holding costs, but also the forecast error and MPS change costs. While a few studies on the frozen interval or replanning interval exist, they ignore the planning lead time and assume the frozen interval equals the replanning interval. This research distinguishes the frozen interval from the replanning interval and considers them as two separate decision variables to be determined simultaneously.

Previous research about the MPS in uncertain environments assumes that the magnitude of the forecast error is independent of the time interval between the current period and the forecast period. In fact, the demand forecasts for periods closer to the current period may be more accurate. This research considers this relationship and expresses the forecast error as a function of the time interval between the current period and the forecast period. In addition, most previous research assumes a single MSI environment. This research is extended to the environment with multiple MSIs.

Most previous articles use simulation experiments as the methodology. The frozen and replanning intervals are usually fixed to several specific values. This research uses a heuristic approach that yields many key insights into these problems. The frozen and replanning intervals can be any integral values. Also, previous research indicates that there is a tradeoff between carrying more safety stock and replanning the MPS more frequently. While this knowledge is important, it misses the important aspect of how to balance this tradeoff. The model derived in this research can be used to find the time intervals which balance the tradeoff.

Based on the heuristic model, this research examines 1) the consequence of the choices of time intervals on total cost, assuming all environmental factors are fixed, and 2) the relationship between the *best* choices of time intervals and various environmental factors, assuming the environmental factors have changed. According to the results from

the first and second analysis, this research develops guidelines for choosing the frozen and replanning intervals in the short term and long term, respectively.

Finally, the research is extended to the environment with multiple MSIs to answer two questions. In an environment with multiple MSIs, each MSI has its own best frozen and replanning intervals. If *common* frozen and replanning intervals are used for all MSIs, what are the best common time intervals? Second, the total cost for all MSIs may be increased by using common time intervals for all MSIs, instead of using their own best time intervals. What is the relationship between this cost increase and various environmental factors?

The environments and methodology in this research will be discussed in detail in Section 1.5. In summary, this research has the following objectives:

- 1) Investigate the problems and costs associated with developing the MPS in uncertain environments using a rolling schedule.
- 2) Based on the knowledge gained from (1), develop a heuristic model that describes the mathematical relationship between the system costs, frozen and replanning intervals, and other environmental factors.
- 3) Test the performance of this heuristic model. After the performance test, use the model for sensitivity analysis. In the sensitivity analysis, investigate the consequences of the choices of frozen and replanning intervals on system costs, and the relationship between the environmental factors and the best combination of frozen and replanning intervals.
- 4) Use the results of the sensitivity analysis to develop guidelines for managing the MPS in uncertain environments.
- 5) Extend this research to the environment with multiple MSIs to examine the best common frozen and replanning intervals for all MSIs, and the cost increase due to using common time intervals for all MSIs.

1.5 Research Design

This research focuses on an uncertain environment, called the **Manufacturing environment**, where the MPS is determined using a rolling schedule. The characteristics of this environment are summarized in Table 1.4. The demand is assumed uncertain. In practice, the actual demands and forecast errors of an MSI may be erratic. In the Manufacturing environment, we assume they can be characterized by some statistical properties based on the historical data. The actual demand distribution for each period in the future is assumed to be identical and independent. There are no trends or seasonalities. The forecast is unbiased, that is, the forecast error for each period has a distribution with a mean of zero. The standard deviation of the forecast error distribution varies from period to period and is an increasing function of the time interval (u) for that period.

Capacity constraints are ignored. The number of MSI is unlimited but the demands and forecast errors of these MSIs are independent of each other. The service level is determined a priori and fixed through the production horizon. It determines the required safety stock for each MSI. There are no lost sales. The unsatisfied MSI demand is completely backlogged and is satisfied on a first-come-first-serve (FCFS) basis in the next period.

The MPS is developed using a rolling schedule. The frozen and replanning intervals are determined a priori and fixed through the production horizon. In a rolling schedule, the MPS is replanned every replanning interval (R) periods. Several new orders are placed for the demand forecasts within forecast window (T) and the first new order is expected to arrive a planning lead time (L) periods later. This essentially is a periodic review inventory control system with a review interval equal to R periods and a lead time equal to L periods. However, it is different from the traditional periodic review systems in two ways. First,

Table 1.4 The Manufacturing Environment

Demand	Uncertain; follows an empirical distribution, with known mean and variance; identical and independent distribution from period to period; no trends or seasonalities.
Forecast errors	Unbiased forecast; distribution of errors each period has a mean of zero and a standard deviation that is an increasing function of the time interval (u).
Capacity constraints	No capacity constraints on production of the MSIs.
Number of MSI	Unlimited; demands and forecast errors of these MSIs are independent of each other.
Service level	Determined a priori; fixed through production horizon; determines safety stock for each MSI; backlogged demand is satisfied on a FCFS basis in the next period.
MPS procedure	MPS is developed using a rolling schedule procedure; frozen and replanning intervals are determined a priori and fixed through production horizon; MPS and inventory position is reviewed periodically with a review interval equal to the replanning interval and a lead time equal to the planning lead time; order quantity in each planning cycle equals target inventory level (demand forecasts plus safety stock) minus inventory position (on-hand inventory plus scheduled receipts [or minus backorders]).
Lot-sizing rule	POQ rule for the lot sizes within the forecast window; time-between-orders determined based on the MSI's cost structure.

Table 1.4 (continued)

System costs	<p data-bbox="548 403 1404 535">Include MPS change, setup, and inventory holding costs; determined on a period by period basis according to the following procedure:</p> <ol data-bbox="548 546 1404 1560" style="list-style-type: none"> <li data-bbox="548 546 1404 588">1) Choose the frozen and replanning intervals for the MPS. <li data-bbox="548 598 1404 640">2) Assign a safety stock level based on the desired service level. <li data-bbox="548 651 1404 735">3) Review the current on-hand inventory and calculate the inventory position. <li data-bbox="548 745 1404 787">4) Forecast the demands within the forecast window. <li data-bbox="548 798 1404 840">5) Calculate the target inventory level. <li data-bbox="548 850 1404 892">6) Calculate the quantity adjustment for the first order. <li data-bbox="548 903 1404 945">7) Determine the MPS within the forecast window. <li data-bbox="548 955 1404 1039">8) Compute the MPS changes within the free interval of the previous planning cycle. <li data-bbox="548 1050 1404 1134">9) Based on the MPS changes, compute the MPS change cost for this planning cycle. <li data-bbox="548 1144 1404 1186">10) Implement the MPS within the replanning interval. <li data-bbox="548 1197 1404 1281">11) Based on the MPS within the replanning interval, compute the setup and inventory holding costs for this planning cycle. <li data-bbox="548 1291 1404 1333">12) Receive the actual demands within the replanning interval. <li data-bbox="548 1344 1404 1428">13) Ship (or backlog) the actual demands; update the on-hand inventory (or backorders); record the actual service level. <li data-bbox="548 1438 1404 1522">14) Compare the actual service level to the desired service level; make necessary adjustments for the safety stock level. <li data-bbox="548 1533 1404 1560">15) Repeat (3) through (14).
---------------------	---

there may be more than one order, rather than exactly one as in a traditional periodic review system, placed in each planning cycle. Second, the target inventory level depends on the demand forecasts. We assume the demand forecasts vary from period to period. Consequently, the target inventory level varies from cycle to cycle.

In this system, like a traditional periodic review system, the inventory position is reviewed at the start of each planning cycle. The total order quantity of new orders equals the target inventory level for that planning cycle minus the current inventory position, where the target inventory level equals forecasts plus safety stock and the inventory position equals on-hand inventory plus scheduled receipts (or minus backorders). Once the total order quantity is determined, the order quantity for each individual order is determined using a lot-sizing rule.

A modified POQ rule is chosen as the lot-sizing rule. This rule is similar to the usual POQ rule in that every order covers M periods of requirements, where M is the time-between-orders for the POQ rule. The only difference is that the order quantity for the first order is adjusted based on the actual demands. How to adjust this quantity will be discussed in Chapter 3, Section 3.1. There are three reasons for choosing the POQ rule. First, from the practical perspective, a survey by Wemmerlov (1979) shows that the POQ rule is one of the most popular lot-sizing rules among the MRP users. Second, from the theoretical perspective, Lee and Adam (1986) finds that, for an MRP system with forecast errors introduced from the MPS, the POQ rule appears to be the best lot-sizing rule overall. Finally, from our preliminary study, we found that the POQ rule significantly reduced the MPS changes when compared to the Wagner-Whitin algorithm.

The system costs include the MPS change, setup, and inventory holding costs of the MSI. The procedure for calculating these costs is also summarized in Table 1.4. These costs is calculated on a period by period basis. Their amount depends on the actual

demands and forecast errors. Since the actual demands and forecast errors vary from period to period, the system costs also vary from period to period.

1.6 Contributions and Limitations of This Research

This research examines the development and control of the MPS in uncertain environments. The results provide guidelines for the choices of frozen and replanning intervals in the short term and long term. The contributions include:

- 1) The environment in this research is richer than previous research. The specialties of the environment include uncertain demands, multiple MSIs, and forecast error dependent on time.
- 2) This research examines the choices of frozen and replanning intervals. Instead of ignoring the planning lead time, the frozen interval is distinguished from the replanning interval. These two time intervals are considered as two decision variables in the model.
- 3) This research uses a heuristic approach that yields many key insights into the problems.
- 4) Finally, this research develops guidelines for managing the MPS in the short term and long term.

The limitations of this research come from the assumptions. This research does not consider capacity constraints. When there are capacity constraints, a longer frozen interval may be desirable because it helps to smooth the capacity requirements. Whether or not this hypothesis is true and how the choices of time intervals are affected by the "tightness" of capacity are not investigated in this research. Another limitation is the demand pattern. Although the demand is uncertain in this research, the mean of the demand distribution is

constant. In some environments, demand may be seasonal or have trend. The models do not include these two situations.

1.7 Outline of Research Presentation

In this chapter, we have described the procedure for developing the MPS in uncertain environments, and the costs associated with developing it. We have also described the objectives, research design, contributions, and limitations of this research. The literature related to this research will be reviewed in Chapter 2.

In Chapter 3, we will develop the heuristic model which describes the relationship between the system cost and environmental factors. The performance of the model will be tested in Chapter 4. Chapter 4 also presents the sensitivity analysis and the guidelines for managing the MPS. Chapter 5 addresses environments with multiple MSIs. Finally, Chapter 6 contains the conclusions and major findings of this study.

CHAPTER II

LITERATURE REVIEW

The literature about the MPS in uncertain environments is limited. Most articles have concentrated on the MPS in deterministic environments. The research on both environments, deterministic or uncertain, can be classified into two parts: using a static schedule or using a rolling schedule. Since our research investigates the MPS in uncertain environments with a rolling schedule, this literature review will focus on the literature about the MPS with a rolling schedule. Deterministic environments are discussed in Section 2.2 and uncertain environments in Section 2.3, respectively. For the literature about the MPS using a static schedule, we will only review one article that relates to the methodology of this research. This article is discussed in Section 2.1.

All articles in Sections 2.1, 2.2, and 2.3 are summarized in Table 2.1. These articles deal with different problems, including the forecast window, frozen interval, MPS change, lot-sizing rules (which can either consider the MPS change cost or not), and the tradeoff between safety stock and replanning interval. Table 2.1 categorizes these articles based on the environment and the main issues they address. Finally, Section 2.4 is the summary. It should be pointed out that terminology in the MPS literature is not standard and some articles use the same term to indicate different meanings. In the following sections, we shall use the terms as defined in Chapter 1.

Table 2.1
Selected Articles on the MPS Problems

Environment	Article	Problems					
		T ¹	F ²	C ³	LS ⁴	LSW ⁵	SS&R ⁶
C/S ⁷	Schwarz (1972)				*		
C/R ⁸	Baker (1977)	*					
	Carlson et al. (1982)	*					
	Chung & Krajewski (1984)	*					
	Chung & Krajewski (1986)		*				
	Sridharan et al. (1987)		*				
	Blackburn et al. (1986)			*			
	Sridharan et al. (1988)			*			
	Blackburn & Millen (1980)				*		
	Chand (1982)				*		
	Huang & Ong (1984)				*		
	Sung & Park (1987)				*		
	Blackburn & Millen (1982)				*		
	Carlson et al. (1979)					*	
	Kropp et al. (1983)					*	
	Kropp & Carlson (1984)					*	
U/R ⁹	Wemmerlov & Whybark (1984)				*		
	Sridharan & Berry (1988)						*
	Yano & Carlson (1985)						*
	Carlson & Yano (1986)						*

Problems

- 1: Forecast window
- 2: Frozen interval
- 3: MPS change
- 4: Lot-sizing rule (without MPS change cost)
- 5: Lot-sizing rule (with MPS change cost)
- 6: Tradeoff between safety stock and replanning interval

Environments

- 7: Certain environment with a static schedule
- 8: Certain environment with a rolling schedule
- 9: Uncertain environment with a rolling schedule

2.1 Deterministic Environment with Static Schedule

In this environment we review one article that relates to the methodology of this research. Schwarz (1972) investigates the average cost per period in a deterministic environment with a static schedule. In his model, he assumes that the forecast window is finite, the demand is constant, the average cost includes only setup and inventory holding costs, and there is only one item. The objective of his model is to determine the optimal order policy, that is, the number of orders and the lot size for each order, that minimizes the cost per period for that item. A two-step procedure is used for determining the optimal order policy. In the first step, the number of orders is fixed and the best lot size for each order is determined based on the fixed number of orders. In the second step, the best number of orders is determined.

His model considers a generalized manufacturing lot-sizing problem, which includes the order lot-sizing problem. Let p , S , k , h , and d be the production rate, setup time, setup cost, inventory holding cost, and demand rate, respectively. Note the order lot-sizing problem is a special case of the manufacturing lot-sizing problem with $p=\infty$ and $S=0$. Let t_i be the time interval between the $(i-1)$ th and i th orders. Let $C(t_i)$ be the total incremental cost within the time interval t_i . $C(t_i)$ includes setup and inventory holding costs. There is exactly one setup within t_i . The average inventory level equals $d(1-d/p)t_i/2$. Consequently, $C(t_i)$ equals:

$$C(t_i) = k + (hd(1-d/p)t_i^2)/2 \quad (2.1)$$

Let there be n orders within T and $C^n(0,T)$ be the total incremental cost over the entire forecast window $[0,T]$ for the given number of orders, n . $C^n(0,T)$ equals:

$$C^n(0,T) = \sum_{i=1}^n C(t_i) \quad (2.2)$$

The problem of determining the optimal lot sizes for these n orders can be viewed as the following model:

$$\text{Min } C^n(0,T) \quad (2.3)$$

$$\text{s.t. } \sum_{i=1}^n t_i = T \quad (2.4)$$

$$t_i(1-d/p) \geq S, i=1, \dots, n \quad (2.5)$$

In the ordering lot-sizing problem, $p=\infty$ and $S=0$. Consequently, constraint (2.5) can be ignored and $(d/p)=0$. Using a Lagrangian multiplier, λ , to relax the constraint (2.4), this model can be expressed as:

$$\begin{aligned} \text{Min } f(t_1, t_2, \dots, t_n, \lambda) &= C^n(0,T) - \lambda(T - \sum_{i=1}^n t_i) \\ &= \sum_{i=1}^n [k + (hdt_i^2)/2] - \lambda(T - \sum_{i=1}^n t_i) \end{aligned} \quad (2.6)$$

After partially differentiating function $f(t_1, t_2, \dots, t_n, \lambda)$ by t_i , we get:

$$\frac{\partial(f(t_1, t_2, \dots, t_n, \lambda))}{\partial(t_i)} = hdt_i + \lambda, i = 1, 2, \dots, n \quad (2.7)$$

From equation (2.7), it is clear that in the optimal solution, all of the t_i must be equal. Since we must make n orders over T time periods, $t_i=T/n$. Equation (2.2) can be expressed as:

$$\begin{aligned} C^n(0,T) &= \sum_{i=1}^n [k + (hdt_i^2)/2] \\ &= nk + hdT^2/(2n) \end{aligned} \quad (2.8)$$

Equation (2.8) indicates that the cost per period is a function of n and T . By drawing the curves of equation (2.8), the author found the following results:

- 1) For a finite forecast window T , the optimal lot-sizing policy is to order n^* equal lots, where n^* is the smallest integer satisfying

$$n(n+1) \geq dhT^2/2k.$$

- 2) Under the optimal lot-sizing policy, the average cost per period for a finite forecast window T , AC_T , is

$$AC_T = n^*k/T + dhT/2n^*.$$

- 3) When T is an integral multiple of $\sqrt{2k/dh}$, the value of AC_T equals the economic order quantity (EOQ) cost per period.

Result (3) indicates that when T is an integral multiple of $\sqrt{2k/dh}$, the average cost per period, AC_T , is the lowest. In our research, we will use this result to determine the time-between-orders for the POQ rule.

2.2 Deterministic Environment with Rolling Schedule

Research about the MPS in a deterministic environment with a rolling schedule are listed in Table 2.1. This research assumes that there is no planning lead time and the frozen interval equals the replanning interval. In the following sections, the articles that study the same problem will be discussed together, starting with the articles addressing the forecast window.

2.2.1 Forecast window

Several articles study the impacts of the choice of forecast window on the total inventory cost of the MSI using a rolling schedule procedure. The total cost includes only the setup and inventory holding costs. These articles aim to find an "appropriate" forecast window for an environment with a predetermined cost structure. They assume the replanning interval and frozen interval are one period.

One of the first articles about rolling schedules is by Baker (1977). Traditional lot-sizing rules are developed assuming a static schedule. How these rules perform in a rolling

schedule is not clear. Baker (1977) evaluates the performance of a traditional lot-sizing rule, the Wagner-Whitin algorithm, when implemented in a rolling schedule. The measure of effectiveness for this rule is the ratio of the cost of the rolling schedule, C_r , to the cost of the theoretically optimal static schedule for the same problem, C_o . Both costs are based on 48-period schedules. The C_r value is determined by solving a series of T-period problems using the Wagner-Whitin algorithm, where T is the forecast window, each time saving the first period solution, until a vector of 48 decisions has been formed. The C_o value is determined by applying the Wagner-Whitin algorithm for the entire 48-period problem.

The methodology for this research is simulation experiments. There are three factors in the experiments: forecast window, cost structure, and demand pattern, each with several levels. The forecast window has six levels: T=2, 4, 6, 8, 10, and 12. The demand pattern has four levels: uniform, trend, seasonal, and trend-seasonal. The cost structure is represented by the "natural cycle," N. The natural cycle is defined as:

$$N = \sqrt{2k/dh} \quad (2.9)$$

where k is the setup cost, h is the inventory holding cost and d is average demand. The natural cycle also has six levels: N=2, 4, 6, 8, 10, and 12.

The experimental results showed that when $T < N$, the ratio C_r/C_o is a function of T and N, that is,

$$C_r/C_o = f(N,T) = 1/2 (N/T + T/N) \quad (2.10)$$

On the other hand, in most cases forecast windows of $T > N$ yield efficiencies in the range of 1%-6% above optimum when a uniform or trend demand pattern is present, and in the range of 1%-10% above optimum when a seasonal demand pattern is present. These results suggest that the forecast window should be at least as large as the natural cycle if rolling schedules are to be used most effectively. More specifically, for uniform or trend demand patterns without seasonal effects, the most appropriate forecast window is usually the natural cycle itself.

Motivated by the finding of Baker (1977) that the forecast window should be at least as large as the natural cycle if rolling schedules are to be used most effectively, Carlson et al. (1982) extend the forecast window using a five-period moving average forecasting method for the cases where the time interval with available forecast data is shorter than natural cycle. The results showed that, when the original forecast window is shorter than the natural cycle, the performance of the Wagner-Whitin algorithm performance is significantly improved by extending the forecast window.

The results from Baker (1977) and Carlson et al. (1982) confirm the conclusion of Schwarz (1972), which indicates that the most appropriate forecast window to minimize the setup and inventory holding costs is the natural cycle. Based on these results, in our research, the natural cycle will be chosen as the time-between-orders of the POQ rule.

Chung and Krajewski (1984) investigate the issues of forecast window for the MPS in a hierarchical production planning environment. They focus on make-to-stock companies that face capacity constraints and a seasonal demand for their products. Due to the capacity constraints, traditional lot-sizing rules are not suitable for this research. They hence formulate the aggregate production planning problem and the master production scheduling problem as two separate mathematical programs to approximate the two-stage process in a hierarchical production planning environment. They use a rolling schedule incorporating a single pass procedure. In the single pass procedure, the results of aggregate production planning are passed to the master production scheduling model once per month and the results of the master production scheduling model are passed back to the aggregate production planning model for the next planning cycle.

The results show that when the companies have high workforce smoothing costs with low setup costs or low workforce smoothing costs with high setup costs, the forecast window for the MPS should be the same as that for aggregate production planning. They

also conclude that the cost structure has an impact on the appropriate planning horizon for both aggregate production planning and master production planning.

2.2.2 Frozen interval

While the MPS is replanned every period in Chung and Krajewski (1984), **Chung and Krajewski (1986)** address the issue of frozen interval for the MPS, using the same environment and mathematical models as that in Chung and Krajewski (1984). The experimental results show that, except for the case of high workforce smoothing costs and high setup costs, the MPS need not to be replanned every period. The results of Chung and Krajewski (1984 and 1986) suggest that cost structure is an important environmental factor for choosing the time intervals in a rolling schedule. In the sensitivity analysis of this research, the cost structure will be chosen as an experimental factor.

Sridharan et al. (1987) use simulation experiments to examine the impact of the choice of the frozen interval on setup cost and inventory holding cost of the MSI. They apply two methods of freezing the MPS: a period based method that freezes the next P periods of the MPS and an order based method that freezes the next J future MPS orders. Like Baker (1977), they use the Wagner-Whitin algorithm as the lot-sizing rule and the natural cycle for the cost structure. The demand pattern is uniformly distributed with lumpiness. Forecast windows are expressed as a multiple (K) of the natural cycle (N). A cost error is used to measure the effectiveness of the rolling schedule. The cost error describes the percentage increase in the combined setup and inventory holding cost for a particular experiment in relation to an optimal cost.

Two sets of simulation experiments are conducted; one for each method of freezing the MPS. There are five factors for each experiment: lumpiness of demand, coefficient of variation of demand, cost structure, forecast window, and frozen interval. The experimental results are then used to develop regression models to estimate the cost error

by a two-stage procedure. The first step predicts the cost error as a function of the forecast window, assuming the frozen interval equals the entire forecast window. The second step estimates the cost error produced when a given fraction of the forecast window is frozen, as a fraction of the cost error due to freezing the entire forecast window.

Although not pointed out by the authors, this two-stage procedure implies that there is no interaction between the frozen interval and forecast window. That is, the consequences of the choice of frozen interval as a proportion of the forecast window is independent of the forecast window decision. They conclude that freezing up to 50% of the forecast window has a marginal effect on setup and inventory holding costs. They also conclude that when long frozen intervals are used, the method of freezing the MPS using a period based technique is relatively more costly than the order based alternative.

2.2.3 MPS change

MPS change causes nervousness in an MRP system and hence MPS change costs. It is desirable to have a stable MPS. **Blackburn et al. (1986)** evaluate five different strategies to dampen the MPS change. These five strategies are: 1) Freezing the entire forecast window, 2) Using lot-for-lot for all components and raw materials, 3) Carrying safety stocks for the MSI, 4) Extending the forecast window, and 5) Using the modified Wagner-Whitin algorithm of **Carlson et al. (1979)** which includes the MPS change cost in the setup cost. **Blackburn et al.** use simulation and design experiments with five experimental factors: the strategy to dampen the MPS change, BOM structure of the MSI, lot-sizing rule, demand variation, and forecast window. In all the aforementioned strategies except the first, the replanning interval and frozen interval are one period. For each strategy, they measure the degree of MPS change and the sum of setup and inventory holding costs. The results indicate that 1) there is a tradeoff between cost effectiveness and

MPS change and 2) under most conditions, the strategies of incorporating a change cost to discourage MPS changes or freezing the entire forecast window dominate other strategies.

Sridharan et al. (1988) build upon their earlier study to address the impact of three decision variables on MPS changes in a make-to-stock environment: forecast window, frozen interval, and method of freezing the MPS. Intuitively, MPS changes within the periods closer to the current period should be more difficult or costly. Also, MPS changes can be either increases or decreases in quantity. For these two reasons, the authors use a weighted average of the absolute values of the MPS change that applies decreasing weights to schedule changes in periods of increasing distance in the future to measure MPS instability.

Experimental results show that freezing the MPS provides a rapid reduction in schedule instability when the frozen proportion of forecast window exceeds 50 percent. The results also show that the period-based freezing method produces less stable schedules relative to the order-based freezing method. By reducing the setup cost, hence reducing the natural cycle, the MPS change can be damped.

The results of **Sridharan et al. (1987)** suggest that setup and inventory holding costs are affected by the choice of frozen interval. The results of **Blackburn et al. (1986)** and **Sridharan et al. (1988)** suggest that frozen interval has an impact on MPS change and hence MPS change cost. In our research, the frozen interval is a decision variable. One of the objectives of this research is to find an appropriate frozen interval to reduce the system costs, including setup, inventory holding, MPS change, and forecast error costs.

2.2.4 Lot-sizing rule (without MPS change cost)

Each of the articles discussed in Section 2.2.1, Section 2.2.2, and Section 2.2.3 uses a specific lot-sizing rule. The efficiency of these rules are not investigated in those articles. Several articles have compared the performances of different lot-sizing rules. These articles

are discussed below. Like the articles about the forecast window, these articles assume there is no planning lead time and both the replanning interval and frozen interval equal one period.

Blackburn and Millen (1980) compare the performance of the Wagner-Whitin algorithm to three other lot-sizing rules: Part-Period-Cost-Balancing (PP), Silver-Meal (SM), and modified Silver-Meal (MSM) in a rolling schedule using simulation experiments, each covering 300 periods. The experimental factors include the forecast window, cost structure, variance of the demand distribution and lot-sizing rule. In the experiments, the demand patterns include uniform and normal distributions, both with lumpiness. Based on the experimental results, the authors conclude that when the forecast window is small, either the Silver-Meal heuristic or the modified Silver-Meal method should be used rather than the Wagner-Whitin algorithm for reasons of cost effectiveness. This conclusion is consistent with that in Baker (1977), which points out the forecast window should be at least as long as the natural cycle when the Wagner-Whitin algorithm is used.

Motivated by the finding of Blackburn and Millen (1980), **Chand (1982)** presents a modification of the Wagner-Whitin algorithm for a rolling schedule procedure. The modified algorithm selects the first period production from a set, called $P(N)$. The $P(N)$ set = $\{P_1(j(N)), P_1(j(N)+1), \dots, P_1(N-1)\}$, where $P_t(i)$ denotes period t production in an optimal i -period solution and $j(N)$ is the next to last regeneration point in the N -period optimal solution. The regeneration point is a period, t , with $I_t=0$, where I_t denotes inventory at the end of period t . Let $R(N)$ denote the regeneration set and $R(N) = \{j(N), j(N)+1, \dots, N-1\}$, and $C(t)$ denote the minimum cost of the t -period problem with $I_t=0$. The modified algorithm selects the first period production quantity using the following steps:

- 1) Find $C(t)/t$ for all $t \in R(N)$.
- 2) Find the largest period $k \in R(N)$ set such that

$$C(k)/k = \min \{C(t)/t\}, \text{ where } t \in R(N).$$

- 3) Set first period production equal to $P_1(k)$.

The results show that the modified Wagner-Whitin algorithm outperforms the Silver-Meal heuristic in all cases and the difference in the cost performance of these two algorithms increases with increasing demand variance.

Blackburn and Millen (1982) compare the performances of different lot-sizing rules under multi-level rolling schedule conditions. They first present three cost modification methods for the multi-level product structures used in their research. These methods are combined with Wagner-Whitin and Silver-Meal algorithms to yield six new heuristics. A total of eight lot-sizing rules are used, including these six new heuristics and unmodified Wagner-Whitin and Silver-Meal algorithms. They conclude that the heuristics with cost modifications perform better than unmodified algorithms. They also conclude that the Silver-Meal algorithm should be used with a rolling schedule.

The results of Blackburn and Millen (1980 and 1982) suggest that, in a rolling schedule procedure, the Wagner-Whitin algorithm is not cost effective. In our research, the POQ rule, rather than the Wagner-Whitin algorithm, is used as the lot-sizing rule.

Sung and Park (1987) consider a special single-facility, multiple-product production system in rolling schedule situations. They assume that all products are produced each production cycle and each product always takes a fixed portion of the total production amount in each production period. Following these assumptions, they develop a model for the problem of minimizing the total setup and inventory holding costs and present a planning-horizon theorem similar to that of Wagner and Whitin (1958) for the problem in a static situation. They then utilize the model and theorem to develop a heuristic procedure for selecting the first-period production amount in rolling schedule situations. This heuristic is similar to that of Chand (1982). The effectiveness of this heuristic is

tested using simulation experiments. The experimental results show that the heuristic outperforms that in Baker (1977) in most cases.

2.2.5 Lot-sizing rule (with MPS change cost)

The articles in Section 2.2.4 evaluate the "existing" lot-sizing rules which were developed for a static schedule. These existing rules consider setup and inventory holding costs. In this section, we discuss several articles that have developed new lot-sizing rules for a rolling schedule. These new rules consider not only setup and inventory holding costs, but also MPS change cost. The objective of these new rules is to balance the tradeoff between the MPS change cost and the possible setup and inventory holding cost increases due to freezing the MPS.

Carlson et al. (1979) develop a modified Wagner-Whitin algorithm that balances these two costs for a deterministic demand environment. The authors assume an MPS already exists and also limit attention to the case in which the MPS change is from no setup in a period to a setup. They also assume the cost of a new setup, V_k , is a function of time and is known. That is,

$$\begin{aligned} V_k = \text{MPS change cost} &= \infty, & k=1,2,\dots,p; \\ &= f(k), & k=p+1,p+2,\dots,r; \\ &= 0, & k=r+1,r+2,\dots,N \end{aligned} \tag{2.11}$$

where p and r are two time fences.

They define a new cost coefficient which includes both the setup cost and MPS change cost so that the total cost equation is structurally identical to that of the Wagner-Whitin problem. The Wagner-Whitin algorithm can then be applied to this new problem. Although they present this modified Wagner-Whitin algorithm, it is optimal only in a static situation.

Following the same logic as that in Carlson et al. (1979), **Kropp et al. (1983)** develop three other lot-sizing rules that also include MPS change costs: modified Silver-Meal 1, modified Silver-Meal 2, and Part-Period-Balancing. The performance of the modified Wagner-Whitin algorithm presented in Carlson et al. (1979) is compared with the three heuristics using simulation experiments. They find that the modified Silver-Meal heuristic is only slightly more costly than the modified Wagner-Whitin algorithm and that the modified Part-Period-Balancing heuristic performs both poorly and erratically. They also evaluate the cost improvements resulting from change-cost adjustment. Change-cost adjustment means incorporating the MPS change cost in the setup cost. The result shows that the change-cost adjustment improves all algorithms except the Part-Period-Balancing heuristic.

Kropp and Carlson (1984) extend the algorithm developed in Carlson et al. (1979) to include not only the case in which the MPS change is from no setup in a period to a setup, but also the case in which the MPS change is from a setup in a period to no setup. They consider a general case which includes the possibilities of adding and cancelling setups. Like the algorithm presented in Carlson et al. (1979), this algorithm is optimal only for static environments. The performance of this algorithm in rolling schedule environments is not tested.

The algorithms presented in Carlson et al. (1979) and Kropp and Carlson (1984) assume deterministic environments. Also, they do not consider the consequences of the choices of frozen and replanning intervals. In our research, the demand is uncertain and the system costs include forecast error cost, which was not considered in the algorithms presented in Carlson et al. (1979) and Kropp and Carlson (1984). Meanwhile, the frozen and replanning intervals are considered as decision variables, rather than fixed factors. These algorithms can not be used for our research.

2.3 Uncertain Environment with Rolling Schedule

In this environment, we review four articles. These articles are also summarized in Table 2.1. The first article, Wemmerlov and Whybark (1984), examines the performance of different lot-sizing rules in an uncertain environment with a rolling schedule. The other three articles investigate the tradeoff between two approaches to deal with uncertain demand: carrying more safety stock or replanning the MPS more frequently.

Wemmerlov and Whybark (1984) use a simulation model to evaluate the performance of 14 different lot-sizing rules when demand is uncertain. In their model, to avoid any stockout due to forecast errors, enough safety stock is carried to achieve a 100% service level in all situations. These 14 rules are ranked based on their cost performances. The system costs include setup and inventory holding costs. The possible cost increases due to MPS changes are ignored. The results show that the ranking of these rules under uncertainty is very different from the ranking under a deterministic environment. Important conclusions include: 1) relative cost performance is strongly affected by the introduction of forecast errors, but not the magnitude of these forecast errors, 2) the Wagner-Whitin algorithm loses its position as the least cost rule, and 3) the differences among the performances of these rules are quite small, compared to that in the deterministic environment. The results are similar to those of Blackburn and Millen (1980 and 1982), which suggest that the Wagner-Whitin algorithm is not cost effective in a rolling schedule.

Sridharan and Berry (1988) extend the research of Sridharan et al. (1987, and 1988) to an environment with demand uncertainty. They study the effects of four decision variables on MPS change, setup cost and inventory holding cost with a fixed service level constraint. The four decision variables are forecast window, frozen interval, replanning interval, and methods of freezing the MPS. The freezing methods include the period based method and order based method, as described in Sridharan et al. (1987). The simulation

model is similar to that in Sridharan et al. (1987) except that the demand is uncertain in this research. The safety stock is assigned so that the desired service level is achieved.

They conclude that frequent replanning is undesirable and longer forecast window is not always better. They also find that there is a tradeoff between the cost reduction and MPS stability. Freezing a greater portion of the MPS greatly reduces the MPS change. However, it also produces a large increase in the cost. Another conclusion is about the importance of demand forecast. They conclude that, by improving the forecasts, one can not only reduce the cost increase associated with freezing the MPS, but also improve the stability of the schedule.

Even though this article finds that there is a tradeoff between the cost reduction and MPS stability, how to balance this tradeoff is not clear in this article. In our research, we will develop a heuristic model that can be used to find an appropriate frozen and replanning intervals which balance this tradeoff.

Yano and Carlson (1985) use a simulation model to examine the performances of several extreme scheduling policies for an end item and its two components in a two-level BOM structure. These policies include: 1) use "fixed" scheduling for all items on both BOM levels, 2) use "flexible" scheduling for all items on both BOM levels, and 3) use fixed scheduling for the end item and flexible scheduling for all components on the second BOM level. In the fixed schedule, the timing (but not the quantity) of all orders is fixed for a period of time equal to the largest integral multiple of the item's natural cycle less than the length of the forecast window. Emergency setups are not allowed within this time interval. In the flexible scheduling, the MPS is replanned each period.

In the simulation model, the actual demand is stationary and is normally distributed. The demand forecast equals the mean of the actual demand distribution. When there is a new setup, a safety stock in the amount of $k_i\sqrt{t_i+L_i}\sigma$ is added to the production quantity, where k_i is the safety stock multiplier for item i , t_i is the time until next planned setup for

item i , L_i is the lead time for item i , and σ is the standard deviation of end-item demand in a single period. The value of k_i is adjusted so that the desired service level is achieved. The Wagner-Whitin algorithm is used as the lot-sizing rule. The choice of the lot-sizing rule actually does not make any difference because the demand forecast is constant. The results show that the flexible scheduling is not cost-effective compared with the fixed scheduling.

Carlson and Yano (1986) develop a heuristic algorithm for setting safety stock levels for an item and its components. For each item, safety stock is calculated using the equation $k_i\sqrt{T_i+L_i}\sigma$, where k_i , L_i , and σ have the same definitions as that in Yano and Carlson (1985) and T_i is the natural cycle for item i . This research is limited to one situation in which the item on the first BOM level uses a "fixed" scheduling policy and all other items use a "flexible" scheduling policy. These two scheduling policies are identical to that in Yano and Carlson (1985). The algorithm is developed in a periodic review framework. It is used to search the "best" k_i that balance the tradeoff between the cost of carrying more safety stock and the MPS change cost.

In searching the best k_i , the algorithm uses two different values for unit inventory holding cost and produces two different values for k_i , a "lower" bound and an "upper" bound. This algorithm is tested using a simulation experiment with an item having a two-level BOM structure and constant demand forecasts. The experimental results show that the safety stock level determined by the algorithm to be the upper bound is close to the minimum cost solution.

The algorithm developed by Carlson and Yano (1986) can be used to balance the tradeoff between safety stock and MPS change (or replanning interval). But this algorithm is limited to a specific situation in which the item on the first BOM level uses a fixed scheduling policy and all other items use a flexible scheduling policy. In our research, the scheduling policy is not fixed and frozen and replanning intervals can be any integral value.

2.4 Summary

This section summarizes the important results of the articles reviewed in this chapter. It then discusses the limitations of previous research and the directions for future research. The important results include:

- 1) For a single MSI environment, the forecast window should be an integral multiple of the MSI's natural cycle, as shown in Baker (1977) and Carlson et al. (1982).
- 2) Freezing the entire forecast window is a good strategy to dampen the MPS changes and reduce total system costs, as shown in Yano and Carlson (1985), and Blackburn et al. (1986).
- 3) Freezing up to 50% of the forecast window has a marginal effect on the setup and inventory holding costs, as shown in Sridharan et al. (1987).
- 4) Frequently replanning the MPS is undesirable, as shown in Yano and Carlson (1985) and Sridharan and Berry (1988).
- 5) The choice of the lot-sizing rules is less important for an uncertain environment with a rolling schedule, as shown in Wemmerlov and Whybark (1984).
- 6) The Wagner-Whitin algorithm is not the best lot-sizing rule in a rolling schedule, as shown in Blackburn and Millen (1982), and Wemmerlov and Whybark (1984).
- 7) There is a tradeoff between the amount of safety stock and MPS change, as shown in Blackburn et al. (1986) and Sridharan and Berry (1988).
- 8) The cost structure affects the choices of forecast window and frozen interval, as shown in Chung and Krajewski (1984, 1986).

After reviewing these articles, several statements can be made with regarding to the limitations of their research environments, problems, and methodology. These limitations also imply the directions for future research.

- 1) Most articles study the MPS in deterministic environments with a rolling schedule. While the results from deterministic environments may be useful for understanding the problem in uncertain environments, they missed one key point regarding the rolling schedule: One reason why a rolling schedule is utilized is because of uncertainty. The results from these articles are limited to the situation where demands are deterministic. More research about the MPS in uncertain environments needs to be done.
- 2) A firm usually has more than one master scheduling item (MSI). When there are multiple MSIs, the problem may be different from the single MSI environment. For example, managers may desire a common replanning interval for all MSIs. How to determine this common interval is an important issue. Most articles in previous research consider single MSI environments. Future research needs to consider the problems in the environment with multiple MSIs.
- 3) Many articles study the forecast window and lot-sizing problems, considering only the setup and inventory holding costs. While these two costs are important in a static schedule, they are less important in a rolling schedule. Wemmerlov and Whybark (1984) show that, in uncertain environments, the differences between the 14 lot-sizing rules investigated in their study are quite small. In a rolling schedule, we need to consider two other costs: forecast error cost and MPS change cost. Future research needs to include these two costs and focus on the choices of frozen and replanning intervals.
- 4) In a rolling schedule, the frozen interval equals the replanning interval plus planning lead time, as discussed in Chapter 1, Section 1.2.1. In the previous research, most articles ignore the planning lead time and assume that the frozen interval is equal to the replanning interval. In future research, these two time

intervals need to be distinguished and considered as two separate decision variables to be determined simultaneously.

- 5) In most situations, the magnitude of the forecast error depends on the time interval between the current period and the forecast period. The demand forecast for the period five weeks from now should be more "accurate" than the demand forecast for the period ten weeks from now. This is one reason why managers sometimes prefer a short frozen interval. Most articles about the MPS in uncertain environments assume the forecast error is independent of the above time interval. Future research needs to consider the relationship between the magnitude of forecast error and time interval.
- 6) Most articles use simulation as the methodology. Three exceptions are Carlson et al. (1979), Kropp and Carlson (1984), and Carlson and Yano (1986). Among these three, the first two are about the lot-sizing rule and consider deterministic demands. They are less attractive for MPS problems in uncertain environments using a rolling schedule. The last one, Carlson and Yano (1986), limits the study to a specific situation in which the item on the first BOM level uses a "fixed" scheduling policy and all other items use a "flexible" scheduling policy. These two scheduling policies are extreme. Many firms use a scheduling policy that is not so "extreme" as the fixed or the flexible scheduling policy. For example, they may use a forecast window equal to 25 weeks and a replanning interval equal to 4 weeks. Whether or not the algorithm presented in Carlson and Yano (1986) is efficient for these firms is not clear. More in-depth analytical research needs to be done to derive more general conclusions.
- 7) Previous results indicate that there is a tradeoff between the amount of safety stock and MPS change. In other words, there is a tradeoff between the forecast error cost and the MPS change cost. This result is intuitive. A more important

issue is *how* to balance the tradeoff. Future research should derive the guidelines for choosing the frozen and replanning intervals that aim to minimize the total cost.

In summary, future research should focus on the MPS in uncertain environments with multiple MSIs. It should distinguish the frozen interval from the replanning interval and consider both as two separate decision variables to be determined simultaneously. It also needs to realize the relationship between the magnitude of forecast error and time interval. The research should use an analytical approach that takes in-depth knowledge of the problems.

In Chapter 3 we will derive a model for the MPS in uncertain environments using a rolling schedule. This model considers the frozen interval and replanning interval as two separate decision variables. It can be used to determine these two intervals simultaneously to balance the tradeoff between the forecast error cost and MPS change cost. It also realizes the relationship between the magnitude of forecast error and time interval. During the development of this model, we will discuss the forecast error cost and MPS change cost in detail. The model is then used for choosing the best combination of frozen and replanning intervals that minimizes the total system cost.

CHAPTER III

MPS MODEL

In Chapter 1 we have discussed that, in an uncertain environment with a rolling schedule, in order to achieve a desired service level, we can replan the MPS more frequently or freeze a larger portion of the MPS in each planning cycle. The first option will reduce the forecast error cost but increase the MPS change cost, while the second option will reduce the MPS change cost but increase the forecast error cost. For an environment with fixed environmental factors, the sum of the MPS change cost and forecast error cost depends on two decision variables: the frozen interval and replanning interval. By choosing appropriate frozen and replanning intervals, we can balance the tradeoff between these two costs and minimize total system cost. Besides these two costs, two other types of system cost are setup and inventory holding costs of the MSI. In order to have a better understanding of the relationship between the system cost and environmental factors, we separate the forecast error cost from the inventory holding cost.

The frozen and replanning intervals need to be determined before a rolling schedule is implemented. To evaluate the performance of a specific combination of frozen and replanning intervals, this chapter develops a mathematical model, called the **MPS model**. This model is a heuristic that expresses the *expected* average system cost per period as a function of frozen and replanning intervals, and other environmental factors. For an MSI with fixed environmental factors, the MPS model can be used to estimate the cost per period of the MSI associated with any choice of frozen and replanning intervals. Using

this model we can find the best combination of frozen and replanning intervals that minimizes the expected cost per period.

The MPS model focuses on the Manufacturing environment, which was described in Chapter 1, Section 1.5 and Table 1.4. In addition to the assumptions in the Manufacturing environment, the MPS model assumes that the forecast errors are normally distributed. This assumption is consistent with that used in Hax and Candea (1984, Chap. 4). The MPS model also assumes that there is only one MSI. The major difference between the MPS model and the Manufacturing environment is the procedure for calculating the system costs. In the Manufacturing environment, the system costs are determined on a period by period basis according to the actual demand and forecast error in each period, using the procedure described in Chapter 1, Section 1.5 and Table 1.4. In the MPS model, the expected system costs are estimated based on the statistical properties of the demand and forecast error, that is, the mean and standard deviation of the demand and forecast error distributions.

In the Manufacturing environment, the MPS is determined using a rolling schedule procedure, which is a periodic review inventory control system. The principles of this system have been described in Chapter 1, Section 1.5 and Table 1.4. The next section discusses the details of the periodic review system in a rolling schedule. Section 3.2 examines the relationship between the forecast error cost and time intervals, while Section 3.3 investigates the relationship between the MPS change cost and time intervals. Section 3.4 discusses the average setup and inventory holding costs of the MSI. Finally, Section 3.5 presents the MPS model and discusses the applications of this model. Part of the notation used in this research is shown in Table 3.1.

Table 3.1 Notation**Time Intervals**

T	Forecast window.
R	Replanning interval.
F	Frozen interval.
L	Planning lead time.
t	Current period.
u	The time interval between current period and forecast period.
v_1	The time interval between current period and the period that the MPS changes.
M	Time-between-orders for the POQ rule.

Demand Parameters

d_t	Actual demand for period t .
D_t	Demand forecast for period t .
$\underline{d}$	Mean of d_t and D_t .
σ^2	Variance of d_t .
e_t	Forecast error for period t ($e_t = D_t - d_t$).
$\sigma_e(u)$	Forecast error standard deviation function.
$f_e(u)$	Forecast error variance function $\{f_e(u) = [\sigma_e(u)]^2\}$.

Table 3.1 (continued)**System Parameters**

h	Inventory holding cost per period.
k	Unit setup cost.
g	Customer service level.
N	Natural cycle ($N=\sqrt{2k/dh}$).
$f_m(v_1)$	Unit change cost function.
$U_1(t)$	Unit change cost for period t .
CLT	Cumulative lead time for the master scheduling item (MSI).
SS_g	Desired safety stock level associated with a fixed cycle service level g .
CF	Forecast error cost per period.
CM	MPS change cost per period.
TC	Total system cost per period.

3.1 Periodic Review System in a Rolling Schedule

This section discusses the details of the periodic review system in a rolling schedule. In addition to the notation shown in Table 3.1, other notation used in this section is summarized as below. Part of the notation refers to Figure 3.1.

Notation:

t_{i0} = Starting period for planning cycle i .

t_{i1} = Starting period of the forecast window in planning cycle i .

t_{i2} = Ending period of the forecast window in planning cycle i .

IP_i = Inventory position at the start of planning cycle i .

Q_i = Total order quantity, that is, the sum of all orders over the entire time interval R in planning cycle i .

TI_i = Target inventory level for planning cycle i .

B_{i1} = Order quantity for the first order of time interval R in planning cycle i .

σ_F = Standard deviation of forecast error during the frozen interval (F), where $F=R+L$.

ON_i = On-hand inventory at the start of planning cycle i (negative ON_i represents backorders).

O_k = Order quantity (lot size) received at the start of period k .

A_k = Actual demand in period k .

SR_i = Total scheduled receipts (open orders) within L in planning cycle i .

$(D_F)_i$ = Total demand forecast for time period F in planning cycle i .

$(D_L)_i$ = Total demand forecast for time period L in planning cycle i .

$(D_R)_i$ = Total demand forecast for time period R in planning cycle i .

AD_i = Quantity adjustment for the first order of R in planning cycle i .

Figure 3.1 Periodic Review System in a Rolling Schedule

Like a traditional periodic review system, the inventory position (IP_i) is reviewed at the start of planning cycle i and the total order quantity (Q_i) of new orders within R is set equal to $(TI_i - IP_i)$, where TI_i is the target inventory level for planning cycle i . Once the Q_i is determined, we assume the order quantity for each individual order is determined using a modified periodic-order-quantity (POQ) lot-sizing rule. The modified POQ rule is similar to the usual POQ rule in that every order covers M periods of requirements, where M is the time-between-orders for the POQ rule. The only difference is that the order quantity for the first order (B_{i1}) is adjusted using a quantity equal to AD_i . The purpose of this quantity adjustment and the calculation of AD_i will be discussed later in this section.

In summary, the lot sizes within T in planning cycle i are determined using the following steps:

- 1) Calculate the associated desired safety stock level (SS_g) based on the desired cycle service level (g);
- 2) Review the current on-hand inventory (ON_i);
- 3) Calculate the inventory position (IP_i);
- 4) Calculate the target inventory level (TI_i);
- 5) Calculate the quantity adjustment for the first order (AD_i);
- 6) Determine the lot sizes for the entire T using the modified POQ rule.

In step one, the desired safety stock level (SS_g) equals the standard deviation of forecast error during F periods times the z value (z_g) associated with the desired cycle service level (g):

$$SS_g = z_g \sigma_F. \quad (3.1)$$

The value of σ_F depends on F and R , among others. How to calculate σ_F will be discussed in Section 3.2.

The inventory position is reviewed just before the start of each planning cycle. The on-hand inventory before the start of planning cycle i (ON_i) equals the on-hand inventory

before the start of planning cycle $i-1$ ($ON_{(i-1)}$) plus the change of inventory level within a time interval between the starting period of planning cycle $i-1$, which is $t_{(i-1)0}$, and the ending period of planning cycle $i-1$, which is $t_{i0} - 1$. [Note there are R periods in total between $t_{(i-1)0}$ and $t_{i0} - 1$. Period t_{i0} is excluded from this time interval because the inventory position in planning cycle i is reviewed before the start of period t_{i0} .] The change in inventory level equals the order quantity received minus the actual demand for the time interval between $t_{(i-1)0}$ and $t_{i0} - 1$. Hence ON_i equals:

$$ON_i = ON_{(i-1)} + \sum_{k=t_{(i-1)0}}^{t_{i0}-1} [O_k - A_k] \quad (3.2)$$

The inventory position (IP_i) equals the on-hand inventory plus scheduled receipts within the planning lead time (SR_i):

$$IP_i = ON_i + SR_i \quad (3.3)$$

The target inventory level (TI_i) equals demand forecasts within the frozen interval $((DF)_i)$ plus the desired safety stock:

$$TI_i = (DF)_i + SS_g, \quad (3.4)$$

Equation (3.4) means that the safety stock level always equals SS_g at the beginning of each planning cycle so that the service level is kept consistent throughout all cycles. Note $(DF)_i$ varies from cycle to cycle in this study. Consequently, TI_i varies from cycle to cycle. This is different from a traditional periodic review system where the target inventory level is usually fixed.

The total required order quantity (Q_i) over R in planning cycle i equals the target inventory level minus inventory position:

$$Q_i = TI_i - IP_i \quad (3.5)$$

From equations (3.3), (3.4), and (3.5), Q_i can further be expressed as:

$$Q_i = [(DF)_i + SS_g] - (ON_i + SR_i)$$

$$\begin{aligned}
&= (D_R)_i + [(D_L)_i + SS_g - ON_i - SR_i] \\
&= (D_R)_i + AD_i
\end{aligned} \tag{3.6}$$

where

$$AD_i = (D_L)_i + SS_g - ON_i - SR_i \tag{3.7}$$

Equation (3.6) means that, in planning cycle i , the total order quantity over the entire R equals the total forecast during R plus AD_i . In order to hold this property, the lot sizes within T_i are first determined using the traditional POQ rule. Each lot covers M period requirements. A value equal to AD_i is then added to the first order.

3.2 Forecast Error Cost

In this study, the forecast error cost is the cost for carrying a safety stock level required to satisfy a desired cycle service level. When utilizing a rolling schedule, the MPS within the frozen interval (F) is fixed. The safety stock needs to provide the desired amount of protection against stockouts within the entire time interval F . We assume that the forecast error for period t (e_t) has a normal distribution with a mean of zero and a variance of $f_e(u)$, where $u=t-\underline{t}$ and $\underline{t}$ is the current period (as defined in Chapter 1, Section 1.2.1). The function $f_e(u)$ is called the **forecast error variance function**. It can be of any form. In general, the value of $f_e(u)$ gets larger as the time interval u becomes longer.

The required safety stock depends on the standard deviation of the forecast error within F (σ_F), as shown in equation (3.1). The value of σ_F depends on F , R , and $f_e(u)$. We use Figure 3.2 to explain this relationship. Figure 3.2(a) shows three planning cycles in a rolling schedule where L equals 4 periods and R equals 2 periods. The frozen interval in planning cycle 3 includes periods 5 through 10 and equals three 2-period time intervals. Let F_1 , F_2 , and F_3 , represent these three time intervals where F_1 includes periods 5 and 6,

(a) A rolling schedule

(b) Variance of forecast error for time interval F_1 (c) Variance of forecast error for time interval F

Figure 3.2 Relationship Between Forecast Error and Frozen Interval

F_2 includes periods 7 and 8, and F_3 includes periods 9 and 10. The MPS for time interval F_1 is determined at the beginning of period 1 in planning cycle 1. The time interval (u) for the beginning period of F_1 equals four periods. The variance of the forecast error for each individual period in F_1 depends on the time interval (u) for that period and the forecast error variance function, $f_e(u)$, as shown in Figure 3.2(b). Figure 3.2(b) shows a forecast error variance function and the variances of the forecast errors for all periods in F_1 . These variances are represented by the shaded area.

The MPS for time interval F_2 is determined at the beginning of period 3 in planning cycle 2. The time interval (u) for the beginning period of F_2 is also four periods. Hence the variance of the forecast error for each period in F_2 is the same as that for the corresponding period in F_1 . In general, the MPS for the beginning period of each R-period time interval within F is always determined L periods earlier. All R-period time intervals have the same *shape* of the variance of forecast error function. The number of R-period time intervals within F equals F/R . Consequently, the variances of the forecast errors for all periods within the entire F can be represented by a shape which equals the sum of (F/R) identical shapes and each shape is the same as the shaded area in Figure 3.2(b). This shape is shown in Figure 3.2(c) and is represented by the shaded area.

The above concepts can be used to calculate the forecast error cost. Since the forecast error for each period (e_t) is independently normally distributed, the variance of the total forecast error for each R-period time interval is the sum of the variances of the forecast error for each individual period belonging to this time interval. The MPS for each R-period time interval is determined L periods earlier. Therefore, the time interval (u) for the beginning period of this interval equals L and the time interval (u) for the ending period of this interval equals $(L+R-1)$, or $(F-1)$. [Note there are $((F-1)-L+1=R)$ periods within this time interval.] The distribution of the total forecast error for each R-period time interval is a

normal distribution with mean zero and variance $\sum_{u=L}^{F-1} f_e(u)$. Consequently, the variance of the total forecast error within the entire F, σ_F^2 , equals:

$$\sigma_F^2 = \frac{F}{R} * \sum_{u=L}^{F-1} f_e(u). \quad (3.8)$$

Equation (3.8) holds only when F/R is an integer. When F/R is not an integer, as shown in Figure 3.3, equation (3.8) needs to be slightly adjusted. In Figure 3.3, R equals 3 periods, L equals 5 periods, and F equals 8 periods. The frozen interval in planning cycle 3 includes periods 7 through 14. The MPS in periods 12, 13, and 14 are determined at the beginning of period 7, which is 5 (or L) periods before. The variance of the total forecast error for these periods equals $\sum_{u=L}^{F-1} f_e(u)$. The MPS in periods 9, 10, and 11 are also

determined L periods earlier. The variance of the total forecast error for these periods is also $\sum_{u=L}^{F-1} f_e(u)$. But the MPS in periods 7 and 8 are determined at the beginning of period 1.

In other words, the MPS for period 7 is determined 6 (or F-2) periods before, and the MPS for period 8 is determined 7 (or F-1) periods before. The variance of the total forecast error for periods 7 and 8 equals $\sum_{u=(F-2)}^{F-1} f_e(u)$.

In general, when F/R is not an integer, the variance of the total forecast error within the entire F, σ_F^2 , is different from equation (3.8). In this situation, we can let $F=B*R+C$, where B and C are integers and $R > C \geq 1$, and replace equation (3.8) by equation (3.9):

$$\sigma_F^2 = B \sum_{u=L}^{F-1} f_e(u) + \sum_{u=(F-C)}^{F-1} f_e(u) \quad (3.9)$$

Given a fixed customer service level g, the total required safety stock for the entire F, SS_g , is:

$$SS_g = z_g \sigma_F \quad (3.10)$$

The forecast error cost per period, CF, is:

**Figure 3.3 Forecast Error Cost
When F/R is not an Integer**

$$CF = h SS_g = h z_g \sigma_F, \quad (3.11)$$

where h is the inventory holding cost for the MSI.

3.3 MPS Change Cost

The MPS change cost of an MSI is the cost of the MRP nervousness induced by MPS changes, as discussed in Chapter 1, Section 1.3.2. This cost may include additional paperwork, computer time, setup cost, overtime, and expedite costs. In a rolling schedule, the MPS change cost for a period equals the unit change cost times the average size of the MPS change in that period. The unit change cost for period t , $U_1(t)$, depends on the time interval (v_1) between the current period and period t , and the **unit change cost function**, $f_m(v_1)$, of the MSI. As shown in Chapter 1, Section 1.3.2, $U_1(t) = f_m(v_1)$, where $v_1 = t - t_1$. Each MSI has its own $f_m(v_1)$. The next section describes a procedure to estimate $f_m(v_1)$. Section 3.3.2 shows two examples of $f_m(v_1)$. Finally, Section 3.3.3 presents an equation that approximates the average size of MPS change, and an equation for the MPS change cost.

3.3.1 Unit change cost function

The unit change cost function of an MSI describes the unit change cost as a function of time interval (v_1). It depends on the lot-sizing rule used and the MSI's BOM structure. Given a lot-sizing rule and BOM structure, the unit change cost function of the MSI can be approximated, starting from the lowest level of the BOM (purchased items) and proceeding to the level of the MSI itself.

For a purchased item in a BOM structure, the costs associated with a lot size change depend on the magnitude of the lot size change, among other factors. Define a **unit** lot size change cost to be the cost associated with a one-unit lot size change. Given a cost structure

and lead time for a purchased item i , the unit lot size change cost, $U_i(t_i)$, depends on the time interval (v_i) between the current period t and period t_i in which the lot size of purchased item i changes:

$$U_i(t_i) = E_i(v_i), \quad (3.12)$$

where $v_i = t_i - t$. The function $E_i(v_i)$ is called the unit lot size change cost function. It is based on the cost structure and lead time of purchased item i .

The unit lot size change cost of an intermediate item can be derived using equation (3.12). For an intermediate item in the BOM of an MSI, there may be several other intermediate items or purchased items as its components, called the **immediate components** of that item. The lot size change of an intermediate item may cause lot size changes of its immediate components down through the BOM, depending on the lot-sizing rules in use. [In this study we assume dynamic rules, in particular the L4L rule, are being used for all assemblies and components.] In this way, the unit lot size change cost of that item includes not only the cost increases through its own production process due to the one-unit lot size change, but also the associated lot size change costs of its immediate components.

Define the **echelon** unit lot size change cost to be the cost due to a one-unit lot size change in an item's own production process. By this definition, the function $E_i(v_i)$ in equation (3.12) is also an echelon unit lot size change cost function of purchased item i because a purchase item does not have any immediate component. Let $E_j(v_j)$ to be the echelon unit lot size change cost function of item j . When the lot-sizing rule is lot-for-lot (L4L) for all of its immediate components, a one-unit lot size change of item j will cause an one-unit lot size change for all of its immediate components. The unit lot size change cost of item j , $U_j(t_j)$, equals:

$$U_j(t_j) = E_j(v_j) + \sum_{k \in S_j} \{q(k) * U_k[v_j - (LT)_j]\}, \quad (3.13)$$

where $v_j = t_j - t$, S_j is the set of immediate components of item j , $q(k)$ is the usage quantity of item k for one unit of item j , and $(LT)_j$ is the lead time for item j .

In order to provide proper advance planning for item j , $(LT)_j$ includes not only the manufacture/procurement lead time for item j , LT_j , but also the proper planning horizon for the lot-sizing decisions of item j , PH_j . In other words, $(LT)_j = LT_j + PH_j$. From equation (3.13), the unit change cost function of the MSI can be calculated using its echelon unit lot size change cost, the MSI's BOM structure, and the unit lot size change costs of its immediate components.

3.3.2 Examples of the unit change cost function

We now use two MSIs with their BOMs shown in Figure 1.2.3(a) and 1.2.3(b) on page 19 to explain how to derive the unit change cost function, $f_m(v_1)$. In both cases, item 1 represents the MSI. We assume that the planning horizons for all intermediate items, namely, items 2, 3, and 4 of the MSI in Figure 1.2.3(a), are zero. Consequently, the lead times for these items equal their manufacturing lead times, which is LT_i in Figure 1.2.3. The lead time of all purchased items, namely, item 5 of the MSI in Figure 1.2.3(a) and items 2, 3, 4, and 5 of the MSI in Figure 1.2.3(b), equal their planning horizons, PH_i , plus procurement lead times, LT_i .

The unit lot size change cost function for item 5 and echelon unit lot size change cost functions for item 1, 2, 3, and 4 of the BOM structure in Figure 1.2.3(a) are known and shown below:

$$\begin{aligned}
 \text{a) } E_1(v_1) &= \infty & v_1 < 3, \\
 &= 0 & 3 \leq v_1; \\
 \text{b) } E_j(v_j) &= 1.5 & v_j \leq 0, \\
 &= 1.5 - 0.5 v_j & 0 < v_j \leq 3,
 \end{aligned} \tag{3.14}$$

$$\begin{aligned}
 &= 0 & 3 < v_j, \\
 &\text{where } j = 2, 3, 4;
 \end{aligned} \tag{3.15}$$

$$\begin{aligned}
 \text{c) } E_5(v_5) &= 1.5 & v_5 \leq 0, \\
 &= 1.5 - 0.167 v_5 & 0 < v_5 \leq 9, \\
 &= 0 & 9 < v_5.
 \end{aligned} \tag{3.16}$$

The echelon unit change cost function for the MSI, $E_1(v_1)$, needs more explanation. The production of an MSI usually includes the final assembly of its immediate components. It is very difficult to make a lot size change after the lot has been set up. In other words, it is very undesirable to have an MPS change within the MSI's assembly lead time. We assume the echelon unit lot size change cost for the MSI is infinite in the example if v_1 is less than the MSI's assembly lead time, and equals zero otherwise.

From equation (3.13), the unit change cost function of the MSI equals:

$$\begin{aligned}
 f_m(v_1) &= E_1(v_1) + U_2(v_1 - \underline{LT})_1 \\
 &= E_1(v_1) + E_2(v_1 - 3) + U_3(v_1 - 3 - (LT)_2) \\
 &= E_1(v_1) + E_2(v_1 - 3) + E_3(v_1 - 6) + U_4(v_1 - 6 - (LT)_3) \\
 &= E_1(v_1) + E_2(v_1 - 3) + E_3(v_1 - 6) + E_4(v_1 - 9) + E_5(v_1 - 9 - (LT)_4) \\
 &= E_1(v_1) + E_2(v_1 - 3) + E_3(v_1 - 6) + E_4(v_1 - 9) + E_5(v_1 - 12).
 \end{aligned} \tag{3.17}$$

For example,

$$\begin{aligned}
 f_m(10) &= E_1(10) + E_2(7) + E_3(4) + E_4(1) + E_5(-2) \\
 &= 0 + 0 + 0 + (1.5 - 0.5) + 1.5 \\
 &= 2.5
 \end{aligned}$$

In general, the unit change cost function for the MSI shown in Figure 1.2.3(a) has the following form:

$$\begin{aligned}
 f_m(v_1) &= \infty & v_1 < 3 \\
 &= 6 - 0.5 (v_1 - 3) & 3 \leq v_1 \leq 12
 \end{aligned}$$

$$\begin{aligned}
&= 1.5 - 0.167 (v_1 - 12) & 12 < v_1 < 21 \\
&= 0 & 21 \leq v_1
\end{aligned} \tag{3.18}$$

The unit lot size change cost functions for items 2, 3, 4, and 5, and echelon unit lot size change cost function for item 1 of the BOM structure in Figure 1.2.3(b) are also known and shown below:

$$\begin{aligned}
\text{a) } E_1(v_1) &= \infty & v_1 < 3, \\
&= 0 & 3 \leq v_1;
\end{aligned} \tag{3.19}$$

$$\begin{aligned}
\text{b) } E_2(v_2) &= 1.5 & v_2 \leq 0 \\
&= 1.5 - 0.167 v_2 & 0 < v_2 < 9 \\
&= 0 & 9 \leq v_2;
\end{aligned} \tag{3.20}$$

$$\begin{aligned}
\text{c) } E_3(v_3) &= 1.5 & v_3 \leq 0 \\
&= 1.5 - 0.214 v_3 & 0 < v_3 < 7 \\
&= 0 & 7 \leq v_3;
\end{aligned} \tag{3.21}$$

$$\text{d) } E_4(v_4) = E_3(v_3); \tag{3.22}$$

$$\text{e) } E_5(v_5) = E_2(v_2). \tag{3.23}$$

The unit change cost function of the MSI equals:

$$f_m(v_1) = E_1(v_1) + E_2(v_1 - 3) + E_3(v_1 - 3) + E_4(v_1 - 3) + E_5(v_1 - 3). \tag{3.24}$$

In general, the unit change cost function for the MSI shown in Figure 1.2.3(b) has the following form:

$$\begin{aligned}
f_m(v_1) &= \infty & v_1 < 3 \\
&= 6 - 0.762 (v_1 - 3) & 3 \leq v_1 \leq 10 \\
&= 0.667 - 0.333 (v_1 - 10) & 10 < v_1 < 12 \\
&= 0 & 12 \leq v_1.
\end{aligned} \tag{3.25}$$

3.3.2 Size of MPS change

The size of the MPS changes for lots within the free interval [defined earlier in Chapter 1, Section 1.2.1.] in each planning cycle depends on the planning lead time and replanning interval. This relationship will be explained by Figure 3.1, using two planning cycles. In Figure 3.1, period t_{21} represents the starting period of the forecast window for the second planning cycle. Let e_{10} and e_{20} represent the forecast errors for period t_{21} incurred in the first and second planning cycles, respectively. The variables e_{10} and e_{20} are normally distributed with mean zero and variances $f_e(L+R)$ and $f_e(L)$, respectively. Let w_0 be the size of the demand forecast change for period t_{21} in going from the first planning cycle to the second planning cycle. That is, $w_0 = e_{10} - e_{20}$. The variable w_0 is normally distributed with mean zero and variance $f_e(L+R) + f_e(L)$. Also, let t_{2a} represent the period that is " a " periods after t_{21} , and w_a be the size of demand forecast change for period t_{2a} between the first planning cycle and the second planning cycle. Variable w_a is normally distributed with mean zero and variance $f_e(L+R+a) + f_e(L+a)$.

Let Z_1 be the size of the MPS change for the first order within the free interval of the first planning cycle (time interval $[t_{21}, t_{12}]$ in Figure 3.1). There are two factors that affect the magnitude of Z_1 . The first one is the demand forecast change represented by w_a , as described above. The second one is the quantity adjustment (AD_i) for the first order (B_{11}) before the start of each planning cycle, as described in Section 3.1, equation (3.7). By substituting equation (3.2) for ON_i , equation (3.7) can be rewritten as:

$$\begin{aligned}
 AD_i &= (DL)_i + SS_g - ON_{(i-1)} - \sum_{k=t_{(i-1)0}}^{t_{i0}-1} [O_k - A_k] - SR_i \\
 &= [(DL)_i + SS_g - ON_{(i-1)} - SR_i] - \sum_{k=t_{(i-1)0}}^{t_{i0}-1} [O_k - A_k]
 \end{aligned} \tag{3.26}$$

The variance of variable AD_i depends on the variance of the sum $(\sum_{k=t_{(i-1)0}}^{t_{i0}-1} [O_k - A_k])$ and the variance of the term $((D_L)_i + SS_g - ON_{(i-1)} - SR_i)$. The term $((D_L)_i + SS_g - ON_{(i-1)} - SR_i)$ includes variables $(D_L)_i$, $ON_{(i-1)}$, and SR_i . These three variables are interdependent. The interdependency makes it complex to derive the variance of the term $((D_L)_i + SS_g - ON_{(i-1)} - SR_i)$. During the development of the MPS model, we have done preliminary experiments which omitted this variance and simply based the variance of AD_i on $(\sum_{k=t_{(i-1)0}}^{t_{i0}-1} [O_k - A_k])$. The results show that the effects of this omission are not significant.

Consequently, to approximate the variance of AD_i , we will ignore the variance of the variable $((D_L)_i + SS_g - ON_{(i-1)} - SR_i)$.

The sum $(\sum_{k=t_{(i-1)0}}^{t_{i0}-1} [O_k - A_k])$ is the total forecast error within a time interval of R periods. It is a normally distributed random variable with mean zero and variance $\sum_{u=L}^{F-1} f_e(u)$,

as shown in Section 3.2. Therefore, we assume the variable AD_i is also a normally distributed random variable with mean zero and variance $\sum_{u=L}^{F-1} f_e(u)$. Since we use the POQ

rule with $TBO=M$, the first order covers a time interval of M periods starting from t_{21} to $t_{2(M-1)}$ and $Z_1 = \sum_{i=0}^{M-1} w_i + AD_i$. Consequently, the variable Z_1 is normally distributed with

mean zero and variance S_1^2 , where

$$S_1^2 = \left[\sum_{a=0}^{M-1} \{f_e(L+R+a) + f_e(L+a)\} \right] + \left[\sum_{u=L}^{F-1} f_e(u) \right]. \quad (3.27)$$

The value of Z_1 can be positive or negative. Either way causes an MPS change and consequently increases the MPS change cost. The expected size of the MPS change for the first order equals:

$$\int_{-\infty}^{\infty} |Z_1| \text{ (p.d.f. of } Z_1) d(Z_1), \quad (3.28)$$

where $|Z_1|$ is the absolute value of Z_1 . Due to symmetry, equation (3.28) can be rewritten as:

$$\begin{aligned}
 & 2 \int_0^{\infty} Z_1 [N \sim (0, S_1^2)] d(Z_1) \\
 &= 2 \int_0^{\infty} Z_1 \left\{ \frac{1}{S_1 \sqrt{2\pi}} \exp[-Z_1^2/2S_1^2] \right\} d(Z_1) \\
 &= \frac{2}{S_1 \sqrt{2\pi}} \int_0^{\infty} Z_1 \exp[-Z_1^2/2S_1^2] d(Z_1) \tag{3.29}
 \end{aligned}$$

From Franklin (1944), Chapter VI,

$$\int_0^{\infty} x^a \exp^{-bx^c} dx = \frac{\Gamma\left(\frac{a+1}{c}\right)}{cb^{(a+1)/c}}, \text{ if } a > -1, b > 0, \text{ and } c > 0, \tag{3.30}$$

where $\Gamma(y)$ is a Gamma function. Let $a = 1$, $b = \frac{1}{2S_1^2}$, $c = 2$, and $x = Z_1$, then equation (3.29) becomes:

$$\frac{2}{S_1 \sqrt{2\pi}} * \frac{\Gamma(1)}{2 * \left(\frac{1}{2S_1^2}\right)} = \frac{2S_1}{\sqrt{2\pi}} = S_1 \sqrt{\frac{2}{\pi}}. \tag{3.31}$$

The MPS change cost equals the unit change cost multiplied by the size of the MPS change. The time interval (v_1) between the current period and the first order equals L periods. Hence, the MPS change cost for the first order equals:

$$f_m(L) S_1 \sqrt{\frac{2}{\pi}}. \tag{3.32}$$

The second order covers a time interval of M periods starting from period t_{2M} to $t_{2(M-1)}$, and $v_1 = L + M$ for the second order. The MPS change cost for the second order equals:

$$f_m(L+M) S_2 \sqrt{\frac{2}{\pi}}, \tag{3.33}$$

where

$$S_2^2 = \sum_{a=M}^{2M-1} \{f_e(L+R+a) + f_e(L+a)\}.$$

There are G orders in total within the free interval, where $G \cdot M \leq CLT - L < (G+1)M$ and CLT is the cumulative lead time of the MSI. Therefore, the total MPS change cost per planning cycle equals:

$$\sum_{p=1}^G \{f_m(L+(p-1)M)\} S_p \sqrt{\frac{2}{\pi}} \quad (3.34)$$

where

$$S_1^2 = \left[\sum_{a=0}^{M-1} \{f_e(L+R+a) + f_e(L+a)\} \right] + \left[\sum_{u=L}^{F-1} f_e(u) \right], \text{ and}$$

$$S_p^2 = \sum_{a=(p-1)M}^{pM-1} \{f_e(L+R+a) + f_e(L+a)\}, \quad p \geq 2.$$

The MPS change cost per period, CM , equals:

$$CM = \left\{ \sum_{p=1}^G \{f_m(L+(p-1)M)\} S_p \sqrt{\frac{2}{\pi}} \right\} / R \quad (3.35)$$

3.4 Setup and inventory holding costs of the MSI

The expected setup and inventory holding costs depends on the TBO of the POQ rule (or M), and unit setup and inventory holding costs. There is one setup per M periods. Assume $\underline{d}$ is the mean of the demand distribution. The expected inventory level for the period that is " b " periods after the setup period can be approximated as $(M-b)\underline{d}$. Consequently, the expected setup and inventory holding costs per period, SH , can be approximated as:

$$SH = [k + h \underline{d} \left\{ \sum_{b=1}^M (b-1) \right\}] / M, \quad (3.36)$$

where k is the setup cost.

3.5 The MPS Model

The cost per period, TC , for an MSI in a rolling schedule includes the forecast error cost per period, MPS change cost per period, setup and inventory holding costs of the MSI per period. Combining Equations (3.11), (3.35), and (3.36) together, TC can be estimated using a function of frozen interval, replanning interval, and other environmental factors:

$$TC = CF + CM + SH$$

$$= h z_g \sigma_F + \left\{ \sum_{p=1}^G \{f_m(L+(p-1)M)\} S_p \sqrt{\frac{2}{\pi}} \right\} / R + [k + h d \{ \sum_{b=1}^M (b-1) \}] / M \quad (3.37)$$

where G is an integer such that $G \cdot M \leq CLT - L < (G+1)M$;

$$\begin{aligned} \sigma_F^2 &= \frac{F}{R} * \sum_{u=L}^{F-1} f_e(u), & \text{if } F/R \text{ is an integer, or} \\ &= B * \sum_{u=L}^{F-1} f_e(u) + \sum_{u=(F-C)}^{F-1} f_e(u), & \text{if } F/R \text{ is not an integer and } F=B \cdot R+C, \text{ where} \end{aligned}$$

B and C are integers and $R > C \geq 1$;

$$S_1^2 = \left[\sum_{a=0}^{M-1} \{f_e(L+R+a) + f_e(L+a)\} \right] + \left[\sum_{u=L}^{F-1} f_e(u) \right]; \text{ and}$$

$$S_p^2 = \sum_{a=(p-1)M}^{pM-1} \{f_e(L+R+a) + f_e(L+a)\}, \text{ if } p \geq 2.$$

Equation (3.37) is called the MPS model. This model indicates that the cost per period (TC) depends on the choices of R and F , and other environmental factors. These factors include setup cost (k), inventory holding cost (h), demand mean ($\underline{d}$), cycle service

level (g), BOM structure of the MSI (including the CLT and unit change cost function, $f_m(v_1)$), forecast error variance function ($f_e(u)$), and the time-between-orders (M). [When there is only one MSI, the value of M depends on k and h . Here we let M be another factor so that the MPS model can be applied to more general situations, such as environments with multiple MSIs.] When utilizing a rolling schedule, the MPS model can be used to estimate the cost per period associated with any combination of R and F .

In the next chapter, this model will be used for sensitivity analysis:

- 1) In the short term, an MSI has fixed environmental factors including k , h , d , g , BOM structure, $f_e(u)$, and M . The cost per period of this MSI (TC) depends on the choices of R and F . This model can be used to estimate the value of TC for any combination of R and F , and evaluate the consequences of the choices of R and F on TC. The best choices of R and F also can be found from this model.
- 2) In the long term, the environmental factors may change. Consequently, the best choices of R and F for the new environment may be different from that for the old environment. This model can be used to see how sensitive the best choices of R and F are to changes in environmental factors.

While the MPS model aims to define the mathematical relationship for the Manufacturing environment, it makes several assumptions and simplifications. The differences between the MPS model and the Manufacturing environment are summarized in Table 3.2. In the next chapter, the performance of the MPS model will be evaluated using simulation experiments.

**Table 3.2 Differences Between the MPS Model
and the Manufacturing Environment**

	Manufacturing Environment	MPS Model
Forecast errors	No constraints on the type of distribution.	Forecast errors are normally distributed.
MPS procedure	Rolling schedule procedure is used as described in Table 1.4.	The rolling schedule procedure is approximated using expected values without proceeding period to period.
System costs	Determined on a period by period basis according to the procedure described in Table 1.4.	Determined based on the means and standard deviations of the demand and forecast error distributions. The variance of variable $((D_L)_i + SS_g - ON_{(i-1)} - SR_i)$ is omitted in calculating the MPS change cost.

CHAPTER IV

EVALUATION OF THE MPS MODEL AND SENSITIVITY ANALYSIS

We have developed a heuristic model, called the MPS model. This model indicates that, in the Manufacturing environment, which is an uncertain environment with a rolling schedule as described in Chapter 1, Section 1.5 and Table 1.4, the cost per period of an MSI depends on the choices of time intervals F and R , and other environmental factors. For an MSI with fixed environmental factors, we can reduce the cost per period for the MSI by choosing an appropriate F and R . For simplicity, in the following discussion, we will call the combination of F and R that minimizes the cost per period (TC) of an MSI the **BEST** of the MSI.

In this chapter, we will present a sensitivity analysis and develop guidelines for the choices of F and R for an MSI. The guidelines consist of two parts, one is for the short term decisions and the other is for the long term decisions. In the short term, the values of environmental factors for an MSI are fixed. The **BEST** of this MSI can be found using the MPS model. These time intervals minimize the *production* cost. But production is not the only activity in a firm. The MPS is used not only for production planning, but also for other purposes, such as providing inputs to marketing. For example, the marketing department uses the MPS to set due dates for new orders.

The **BEST** found using the MPS model may not be the best time intervals from the marketing point of view. Marketing department may prefer to have a short frozen interval so that it can quickly respond to customer requirements, while the production department

may prefer a longer frozen interval to reduce the schedule instability. It is possible that managers need to choose a combination of F and R that is different from the BEST. The problem is: how much higher will the value of TC be if the time intervals are switched away from the BEST.

In order to answer the above question we need to understand the effects of the choices of F and R on TC. These effects depend on the characteristics of an environment. When the values of all environmental factors are known, we can apply the MPS model to find these effects. But the values of some environmental factors, such as unit change costs, may not be obvious. We need some guidelines that describe the relationships between TC and the choices of F and R. These guidelines will help managers choose the appropriate F's and R's even though some information is lacking.

In the long term, the environmental factors themselves may change. For example, demand forecasts may become more reliable as the MST's life cycle switches from a growth stage to a mature stage. Consequently, the magnitude of forecast errors may be changed. The BEST for the new environment may be different from the BEST for the old environment. We want to understand how sensitive the changes of the BEST are to the changes in environmental factors. Four of the more important environmental factors are selected for this purpose: cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error.

Before the MPS model is used for the sensitivity analysis, its performance will be evaluated using simulation experiments because the MPS model is an abstraction of Manufacturing environment. The results from the MPS model are compared with the results from simulation models of the Manufacturing environment. During the evaluation, two measures are used to test the accuracy of the MPS model: the BEST of an environment and the associated TC for any combination of F and R.

In Section 4.1, we will discuss several heuristic rules that will be applied to choose the replanning interval, forecast window, and time-between-orders for the POQ rule in the experiments. Section 4.2 describes the simulation model, the experimental design, and the results of the MPS model evaluation. Section 4.3 investigates the effects of the choices of F and R on TC. The effects of environmental factors on the BEST are presented in Section 4.4. Finally, Section 4.5 provides the conclusions.

4.1 Rules for Choosing Time-Between-Orders, Replanning Interval, and Forecast Window

In the experiments for evaluating the MPS model, the time-between-orders for the POQ rule, replanning interval, and forecast window are selected according to several heuristic rules. This section discusses the rationale of these rules. Section 4.1.1 describes the rule for choosing the time-between-orders (M) of the POQ rule, followed by the rules for choosing R and T in Section 4.1.2.

4.1.1 Time-between-orders for the POQ rule

The choice of time-between-orders for the POQ rule is based on the results of Schwarz (1972). Schwarz investigates the average cost per period in a static environment without considering a rolling schedule. In his model, he assumes that the forecast window is finite and the demand is constant. The average cost includes setup and inventory holding costs, assuming an optimal order policy is applied within the forecast window. His results are:

- 1) For a finite forecast window T, the optimal lot-sizing policy is to order n^* equal lots, where n^* is the smallest integer satisfying

$$n(n+1) \geq dhT^2/2k,$$

and d is the constant demand rate per period, h is the inventory holding cost per period, and k is the setup cost.

- 2) Under the optimal lot-sizing policy, the average cost per period for a finite forecast window T , AC_T , is

$$AC_T = n \cdot k / T + dhT / 2n.$$

- 3) When T is an integral multiple of $\sqrt{2k/dh}$, the value of AC_T equals the economic order quantity (EOQ) cost per period.

The parameter $\sqrt{2k/dh}$ is called the **natural cycle** by Baker (1977). We use the same term for this parameter. The EOQ cost in result (3) is the lowest cost per period under the assumptions above. Result (3) indicates that when T is an integral multiple of $\sqrt{2k/dh}$, the average cost per period, AC_T , is the lowest. Hence any integral multiple of the natural cycle is the optimal forecast window in a static environment with constant demand. In our environment, the demand forecast distributions have constant mean, which equals $\underline{d}$. By choosing POQ as the lot-sizing rule, the forecast window for each order is a time interval equal to the time-between-orders. Let $N = \sqrt{2k/\underline{d}h}$ where we substitute $\underline{d}$ for the known, uniform demand rate d . In order to minimize the *expected* setup and inventory holding costs, it is reasonable to choose N as a forecast window. Note this rule is consistent with the results of Baker (1977), Blackburn and Millen (1980), and Carlson et al. (1982). Consequently, when there is only one MSI, we set $M=N$.

4.1.2 Replanning interval and forecast window

Preliminary investigations indicate that, in uncertain environments, the MPS changes are increased significantly when R is not an integral multiple of M . A simple example shown in Table 4.1 demonstrates this situation, where $M=2$, $L=0$, and $T=8$. It shows that when R equals 3, the MPS changes between two planning cycles are 12, -20, 18, -20, and

Table 4.1 Replanning Interval and MPS changes

Period	1	2	3	4	5	6	7	8	9	10	11	12
Forecasts for cycle 1	10	10	10	10	10	10	10	10				
Forecasts for cycle 2				11	11	8	10	10	10	10	10	
MPS for cycle 1	20		20		20		20					
MPS for cycle 2				12		18		20		20		
MPS change				12	-20	18	-20	20				

(a) $R = 3$

Period	1	2	3	4	5	6	7	8	9	10	11	12
Forecasts for cycle 1	10	10	10	10	10	10	10	10				
Forecasts for cycle 2			11	11	11	8	10	10	10	10		
MPS for cycle 1	20		20		20		20					
MPS for cycle 2			22		19		20		20			
MPS change			2	0	-1	0	0	0				

(b) $R = 2$

Period	1	2	3	4	5	6	7	8	9	10	11	12
Forecasts for cycle 1	10	10	10	10	10	10	10	10				
Forecasts for cycle 2					11	8	10	10	10	10	10	10
MPS for cycle 1	20		20		20		20					
MPS for cycle 2					19		20		20		20	
MPS change					-1	0	0	0				

(c) $R = 4$

20 for periods 4 through 8, respectively. When R equals 2 or 4, the MPS changes are much smaller. Therefore, we choose an integral multiple of M for R .

When the POQ rule is chosen for the lot-sizing decisions in static environments without rolling schedules, each lot size is determined using the forecast data in a time interval equal to M periods. Even though a forecast window longer than M periods is used, the lot-sizing decisions are still the same. Therefore, the appropriate forecast window for the POQ rule is a time interval equal to M periods. On the other hand, equation (1.2) in Chapter 1, Section 1.2.1 indicates the value of T in a rolling schedule should be:

$$T \geq R + CLT - L$$

where CLT is the cumulative lead time of the MSI and $L = F - R$. Hence, the lower bound of T for the POQ rule in a rolling schedule is:

$$T_{\min} = \max \{M, R + CLT - L\}.$$

However, in order to reduce the MPS changes, it is reasonable to choose a T that covers an integral number of orders. We shall let $T = p_1 * M$, where p_1 is an integer such that T is at least as large as its lower bound.

Based on the above analysis, the following rules are applied in the search for the BEST for environments with a single MSI:

- 1) $M = N = \sqrt{2k/dh}$.
- 2) $R = q * N$, where q is an integer.
- 3) $T = p_1 * N$, where p_1 is an integer, and $T \geq \max \{N, R + CLT - L\}$.

4.2 Evaluation of the MPS Model

The performance of the MPS model is evaluated using simulation experiments that simulate the Manufacturing environment. In the Manufacturing environment, there are no restrictions for the type of demand and forecast error distributions. In the experiments,

these distributions are assumed to be normal or uniform. These two distributions are chosen because they were widely used in previous research, such as Baker (1977), Blackburn and Millen (1980), Yano and Carlson (1985), and Sridharan and Berry (1988). Consequently, we use two experiments that are identical except for their demand and forecast error distributions. The first one assumes that the actual demands and forecast errors are normally distributed, while the other assumes that they are uniformly distributed. Each experiment has four experimental factors with two levels for each factor. This yields 16 environments in each experiment.

The simulation model for the first experiment is called the Normal-Simulation model and that for the second experiment is called the Uniform-Simulation model. These two models are identical except for the procedure to generate the demands and forecast errors. We will only discuss the Normal-Simulation model in Section 4.2.1. Section 4.2.2 describes the experimental design. Section 4.2.3 describes the procedure for finding the BEST. The results of the experiments are presented in Section 4.2.4.

4.2.1 Simulation Model

The Normal-Simulation model is a computer program written in FORTRAN 77. The logic of the simulation model is demonstrated in Figure 4.1. The simulation model starts off by reading in the environmental factors including the inventory holding cost, setup cost, mean and standard deviation of the actual demand distribution, forecast error variance function, BOM structure, and desired cycle service level. It then assigns a replanning interval (R), planning lead time (L), and forecast window (T). The desired safety stock (SS_g) is calculated using Equations (3.10) in Section 3.2. A value of SS_g is added to the demand forecast of the first period. This quantity adjustment for the first period forecast ensures that there is an inventory level equal to SS_g at the start of the production horizon.

Figure 4.1 Simulation Flow Chart

The actual demands and forecast errors are randomly generated according to their distributions. The demand forecast equals the actual demand plus the forecast error. The mechanism for generating normally distributed random variables is the Box-Muller method (Bratley et al. 1987). The lot sizes within the forecast window are then determined using the modified periodic order quantity (POQ) rule, as described in Section 3.1. The MPS changes within the free interval, MPS change cost (CM), and setup and inventory holding costs (SH) associated with these lot sizes are calculated and recorded using the procedure described in Chapter 1, Table 1.4.

The percentage of stockouts is also measured. This record is used to check with the desired service level. The quantity of on-hand inventory is then updated based on the lot sizes and actual demands, as shown in Section 3.1, equation (3.2). The quantity adjustment ($AD_{(i+1)}$) for the first order in the next planning cycle is calculated using equation (3.7). The MPS is then rolled ahead according to the replanning interval until the entire production horizon is covered. The production horizon (PH) equals 4000 periods. The cost per period (TC) associated with the assigned time intervals is then computed and recorded.

The number of replications (REPL) equals 5 and the above procedure is repeated 5 times for each combination of R and F. In order to eliminate the transient effects of start-up, the initial conditions are reassigned before the starting of each replication and 200 periods are completed before statistics are collected. The initial conditions include initial inventory, scheduled receipts, backorders, and cost per period. All of these values are set to zero. After finishing all replications, the mean and standard deviation of all TCs from the replications are calculated and recorded. The mean of the TCs represents the performance measure for a given combination of R, F, and T.

The simulation model then assigns new values for R, F, and T. Based on these new time intervals, it repeats the entire procedure and calculates the associated TC. The

associated TC is compared with the current lowest TC. If it is lower than the current lowest TC, it replaces the lowest TC as the temporary best solution. The procedure is repeated until all combinations of time intervals are investigated. The combination of F and R with the lowest TC (the BEST) and its associated TC are then printed.

4.2.2 Experimental design

The experiment was designed to examine the effects of four factors: cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. These factors are identical to those that will be used in the sensitivity analysis. The cost structure is chosen because the results from Chung and Krajewski (1986) show that the choice of F depends on the cost structure. The BOM structure and magnitude of unit change cost are chosen because they have direct impacts on the unit change cost, hence the MPS change cost. The magnitude of forecast error is chosen because it has direct effects of the forecast error cost. Each factor has two levels, as shown in Table 4.2. This yields 16 environments in total.

The cost structure is represented by the item's natural cycle. The natural cycle depends on demand mean, inventory holding cost, and setup cost. In the experiment, the demand mean and inventory holding cost are fixed, but the setup cost is changed to yield two levels of cost structure. In all environments, the demand mean equals 50 and the inventory holding cost equals one. The setup cost is 100 for the low setting and 400 for the high setting. The setup cost together with the inventory holding cost and average demand determines the natural cycle of the MSI, which equals 2 for the low setting and 4 for the high setting. These two values have been used in previous research, such as Yano and Carlson (1985).

Table 4.2 Experimental Factors**a) Cost structure**

Low: setup cost = 100, natural cycle = 2

High: setup cost = 400, natural cycle = 4

b) BOM structure

Low: as shown in Figure 1.5(b); CLT = 12, and

$$f_m(v_1) = A_2 * f_1(v_1), \text{ where}$$

$$\begin{aligned} f_1(v_1) &= \infty & v_1 < 3 \\ &= 10 - 1.27 (v_1 - 3) & 3 \leq v_1 \leq 10 \\ &= 1.111 - 0.555 (v_1 - 10) & 10 < v_1 < 12 \\ &= 0 & 12 \leq v_1. \end{aligned}$$

High: as shown in Figure 1.5(a); CLT = 21, and

$$f_m(v_1) = A_2 * f_2(v_1), \text{ where}$$

$$\begin{aligned} f_2(v_1) &= \infty & v_1 < 3 \\ &= 10 - 0.833 (v_1 - 3) & 3 \leq v_1 \leq 12 \\ &= 2.5 - 0.278 (v_1 - 12) & 12 < v_1 < 21 \\ &= 0 & 21 \leq v_1 \end{aligned}$$

c) Magnitude of unit change cost

Low: $A_2 = 0.2$

High: $A_2 = 2.0$

d) Magnitude of forecast error

Low: $\sigma_e(u) = 0.15 u$

High: $\sigma_e(u) = 0.15 u^{1.3}$

Two extreme BOM structures as shown in Figure 1.5 are chosen for testing the MPS model. These two BOM structures have been studied in previous research, such as Graves (1981), Blackburn and Millen (1982), and Benton and Srivastava (1985). The BOM structure determines the CLT and the *shape* of unit change cost function ($f_m(v_1)$) of the MSI as described in Section 1.2.2 and Section 3.3. The shape of $f_m(v_1)$ describes the relationship between $f_m(v_1)$ and the BOM structure. In the low setting of the BOM structure, CLT equals 12 and the shape of $f_m(v_1)$ is that of $f_1(v_1)$. In the high setting, CLT equals 21 and the shape of $f_m(v_1)$ is that of $f_2(v_1)$. Functions $f_1(v_1)$ and $f_2(v_1)$ are shown in Table 4.2.

Even though the BOM structure is kept the same, the unit change cost function of an MSI may be changed by reducing the setup and inventory holding costs of its components. In order to include this situation, we let the unit change cost function, $f_m(v_1)$, equal the shape of $f_1(v_1)$ or $f_2(v_1)$ multiplied by a parameter, A_2 . By changing the values of A_2 , we can change the value of $f_m(v_1)$ even though the BOM structure is kept the same. The value of A_2 is called the magnitude of unit change cost. Two values are selected for this factor. The value of A_2 equals 0.2, which is close to zero, in the low setting and 2.0, which is double of the normal situation, in the high setting. We consider this range of A_2 sufficiently large to cover many reasonable situations. Figure 4.2 shows the graphs of functions $f_1(v_1)$ and $f_2(v_1)$, where line (BOM=L, $A_2=1$) represents $f_1(v_1)$ and line (BOM=H, $A_2=1$) represents $f_2(v_1)$. It also shows the graphs of two other unit change cost functions, $f_m(v_1) = 2 f_1(v_1)$, which is the line (BOM=L, $A_2=2$), and $f_m(v_1) = 2 f_2(v_1)$, which is the line (BOM=H, $A_2=2$).

Forecasts are less reliable in some environments than in others. The magnitude of the forecast error is represented by the forecast error standard deviation function, $\sigma_e(u)$ [$\sigma_e(u)=(f_e(u))^{0.5}$]. This factor is a new setting, compared to previous research. In previous research about uncertain environments, forecast error standard deviation (S.D.) is

Figure 4.2 Unit Change Cost Function

assumed to be independent of the time and is fixed throughout all periods. Among them Yano and Carlson (1985, and 1987) used three values for S.D. and the ratio of (S.D.)/(demand mean) were 0.05, 0.15, and 0.25. Sridharan and Berry (1988) selected two values for S.D. and the ratio of (S.D.)/(demand mean) were 0.15 and 0.3.

In our study, two types of forecast error standard deviation functions are used to represent two different situations. In both cases the forecast error standard deviation is a function of time interval (u). The first one is a linear increasing function, which represents the situations that the expected forecast error is increased steadily, and the second one is a polynomial increasing function, which represents high forecast error situations. The values of these two functions are selected based on previous research. The maximum ratio of (S.D.)/(demand mean) in the first function is about the low setting in previous research and the maximum ratio of (S.D.)/(demand mean) in the second function is about the high setting in previous research. Since these two functions are increasing functions, the maximum ratio of (S.D.)/(demand mean) appears when the time interval (u) is maximum. In our experiment, the maximum time interval (u) equals 37 and the demand mean equals 50. We select $\sigma_e(u) = 0.15u$ as the linear function and $\sigma_e(u) = 0.15 u^{1.3}$ as the polynomial function. The maximum ratio of (S.D.)/(demand mean) in the first function equals $(0.15 \times 37)/50 = 0.111$, which is about the average of the low settings in Yano and Carlson (1985) and Sridharan and Berry (1988). The maximum ratio of (S.D.)/(demand mean) in the second function equals $(0.15 \times 37^{1.3})/50 = 0.328$, which is about the high setting in Sridharan and Berry (1988).

Other factors include the standard deviation of demand distribution (σ) and cycle service level (g). The values of these two factors are fixed in all environments. The value of σ is fixed because TC in the MPS model is independent of σ . Preliminary experiments indicate that the relationship between F , R , and TC is about the same for different g values from 60% through 95%. Consequently, g is fixed to 90%. The value of σ is based on

previous research. In previous research, Blackburn and Millen (1982) selected the value for σ such that (σ/d) equals 0.2. Sridharan et al. (1987) used three values for σ such that (σ/d) equals 0.1443, 0.2165, and 0.433. In our experiment, σ equals 20 and (σ/d) equals 0.2.

The values for the low setting and high setting in each experimental factor also coordinate with the sensitivity analysis. During the sensitivity analysis, the values of each factor will be changed from the low setting to the high setting of this factor.

4.2.3 Procedure for finding the BEST

In the search for the BEST of an environment, we apply the rules derived in Section 4.1. We let $M=N$ and $R=1N, 2N, 3N$, and $4N$. These rules are applied to both the simulation models and the MPS model. The procedure for utilizing the MPS model is demonstrated in Figure 4.3. The associated TC for any combination of F and R , and the BEST of an environment derived from the MPS model is compared with that derived from the simulation models. The results are summarized in Tables 4.3, 4.4, and 4.5.

4.2.4 Results of the experiments

In Tables 4.3 and 4.4, environments are named according to their four experimental settings in the sequence of cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. A capital "L" means a low setting and a capital "H" means a high setting for the factor values shown in Table 4.2. For example, environment LHLL is an environment having Low cost structure, High BOM structure, Low magnitude of unit change cost, and Low magnitude of forecast error.

Tables 4.3 and 4.4 show the results from the MPS model. These results include the best combination of time intervals (BEST1), and its associated setup and inventory holding costs (SH1), MPS change cost (CM1) and cost per period (TC1). Here SH1 includes the

Figure 4.3 MPS Model Flow Chart

Table 4.3 Evaluation of MPS Model - Normal Distribution

Environment*	MPS Model				Normal-Simulation Model						TC2-TC1 TC1 (%)	Z _g '	TC3	TC2-TC3 TC3 (%)
	BEST1	SH1	CM1	TC1	BEST2	SH2	CM2	TC2	σ_{TC2}	g' (%)				
LHHL	R=2, F=22	93.50	1.73	95.22	R=2, F=22	93.14	1.73	94.88	0.76	90.7	- 0.4	1.323	95.81	- 1.0
HHHL	R=4, F=21	191.40	4.60	195.99	R=4, F=21	191.31	4.55	195.86	0.59	90.0	- 0.1	1.282	195.99	- 0.1
LLHL	R=2, F=13	83.01	1.99	84.99	R=2, F=13	83.08	1.97	85.04	0.41	89.5	0.1	1.253	84.81	0.3
HLHL	R=4, F=15	184.42	1.61	186.03	R=4, F=14	182.98	3.00	185.98	0.29	89.9	0.0	1.282	186.03	0.0
LHLL	R=6, F=9	78.59	3.72	82.31	R=6, F=9	78.49	3.74	82.23	0.24	89.1	- 0.1	1.232	82.17	0.1
HHLL	R=4, F=7	177.46	4.07	181.53	R=4, F=7	177.50	4.09	181.58	0.13	90.2	0.0	1.293	181.55	0.0
LLLL	R=4, F=7	77.46	2.59	80.04	R=4, F=7	77.47	2.59	80.06	0.16	89.8	0.0	1.270	80.02	0.1
HLLL	R=4, F=7	177.46	2.32	179.78	R=4, F=7	177.35	2.32	179.67	0.61	89.5	- 0.1	1.253	179.72	0.0
LHHH	R=2, F=21	116.99	8.11	125.10	R=2, F=21	115.82	8.07	123.89	2.54	89.1	- 1.0	1.232	123.46	0.3
HHHH	R=4, F=21	214.47	11.34	225.81	R=4, F=21	213.85	11.46	225.31	1.20	90.2	- 0.2	1.293	226.15	- 0.4
LLHH	R=2, F=13	91.69	4.22	95.92	R=2, F=13	91.62	4.22	95.84	1.07	90.0	- 0.1	1.282	95.92	- 0.1
HLHH	R=4, F=15	195.22	3.59	198.81	R=4, F=15	195.47	3.59	199.06	0.74	89.7	0.1	1.264	198.53	- 0.3
LHLH	R=4, F=7	79.00	10.05	89.05	R=4, F=7	79.07	10.06	89.13	0.27	90.8	0.1	1.329	89.20	- 0.1
HHLH	R=4, F=7	179.00	8.54	187.55	R=4, F=7	178.79	8.48	187.27	0.18	89.8	- 0.2	1.270	187.51	- 0.1
LLLH	R=4, F=7	79.00	4.91	83.91	R=4, F=7	78.98	4.95	83.93	0.14	90.0	0.0	1.282	83.91	0.0
HLLH	R=4, F=7	179.00	4.51	183.51	R=4, F=7	178.95	4.48	183.43	0.40	90.0	0.0	1.282	183.51	0.0

* The environments are named according to their four experimental settings in the sequence of cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. A capital "L" means a low setting and a capital "H" means a high setting.

Table 4.4 Evaluation of MPS Model - Uniform Distribution

Environment	MPS Model				Uniform-Simulation Model						$\frac{TC2-TC1}{TC1}(\%)$	$Z_{g'}$	TC3	$\frac{TC2-TC3}{TC3}(\%)$
	BEST1	SH1	CM1	TC1	BEST2	SH2	CM2	TC2	σ_{TC2}	$g'(\%)$				
LHHL	R=2, F=22	93.50	1.73	95.22	R=2, F=22	93.48	1.74	95.22	1.00	89.9	0.0	1.282	95.22	0.0
HHHL	R=4, F=21	191.40	4.60	195.99	R=4, F=21	190.48	4.68	195.16	1.11	87.9	- 0.4	1.170	194.56	0.3
LLHL	R=2, F=13	83.01	1.99	84.99	R=2, F=13	83.05	1.99	85.04	0.16	90.2	0.1	1.293	85.06	0.0
HLHL	R=4, F=15	184.42	1.61	186.03	R=4, F=15	184.41	1.59	186.01	0.51	90.7	0.0	1.323	186.33	0.2
LHLL	R=6, F=9	78.59	3.72	82.31	R=4, F=7	77.40	4.91	82.31	0.14	89.7	0.0	1.264	82.26	0.1
HHLL	R=4, F=7	177.46	4.07	181.53	R=4, F=7	177.38	4.12	181.50	0.36	89.7	0.0	1.264	181.50	0.0
LLLL	R=4, F=7	77.46	2.59	80.04	R=4, F=7	77.47	2.61	80.00	0.11	88.6	0.0	1.205	79.89	0.1
HLLL	R=4, F=7	177.46	2.32	179.78	R=4, F=7	177.51	2.34	179.85	0.29	90.4	0.0	1.305	179.82	0.0
LHHH	R=2, F=21	116.99	8.11	125.10	R=2, F=21	116.02	8.09	123.89	2.48	89.1	- 1.0	1.232	123.46	0.3
HHHH	R=4, F=21	214.47	11.34	225.81	R=4, F=21	211.96	11.58	223.54	3.05	88.5	- 1.0	1.200	223.29	0.1
LLHH	R=2, F=13	91.69	4.22	95.92	R=2, F=13	91.97	4.21	96.17	0.59	90.8	0.3	1.329	96.53	- 0.4
HLHH	R=4, F=15	195.22	3.59	198.81	R=4, F=15	195.09	3.65	198.75	0.39	89.2	0.0	1.238	198.12	0.3
LHLH	R=4, F=7	79.00	10.05	89.05	R=4, F=7	78.95	10.23	89.18	0.11	89.6	0.1	1.259	88.98	0.2
HHLH	R=4, F=7	179.00	8.54	187.55	R=4, F=7	178.81	8.60	187.41	0.25	89.7	- 0.1	1.265	187.50	- 0.1
LLLH	R=4, F=7	79.00	4.91	83.91	R=4, F=7	79.01	4.98	83.99	0.10	89.4	0.1	1.248	83.91	0.0
HLLH	R=4, F=7	179.00	4.51	183.51	R=4, F=7	178.75	4.53	183.29	0.10	88.1	- 0.1	1.180	183.51	- 0.1

* The environments are named according to their four experimental settings in the sequence of cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. A capital "L" means a low setting and a capital "H" means a high setting.

forecast error cost, which is the inventory holding cost for the required safety stock. Tables 4.3 and 4.4 also show the results from the Normal-Simulation model and Uniform-Simulation model, respectively. The results include BEST2, SH2, CM2, TC2, standard deviation of TC2 (σ_{TC2}), and actual cycle service level (g').

Tables 4.3 and 4.4 show that the actual cycle service levels (g') are slightly different from our target cycle service level, which is 90%. In order to make an objective comparison, we adjust the value of TC1 based on the value of g' from the simulations model. This adjustment includes two steps: First, we calculate the required safety stock ($SS_{g'}$) when the service level equals g' :

$$SS_{g'} = z_{g'} \sigma_F, \quad (4.1)$$

where $z_{g'}$ is the standard normal random variable associated with g' and σ_F is the standard deviation of the total forecast error within F. From equation (3.10) we get:

$$\sigma_F = \frac{SS_g}{z_g}. \quad (4.2)$$

From equation (4.2), we can rewrite equation (4.1) as:

$$SS_{g'} = z_{g'} \frac{SS_g}{z_g} = SS_g \frac{z_{g'}}{z_g} \quad (4.3)$$

After $SS_{g'}$ is calculated, the new cost per period (TC3) is then adjusted using the following equation:

$$TC3 = TC1 + h (SS_{g'} - SS_g) \quad (4.4)$$

We now use an example to demonstrate this procedure. In environment LHHL, the actual cycle service level (g') from the simulation model is 90.7%. The standard normal random variable associated with 90.7% ($z_{g'}$) equals 1.323. The desired cycle service level (g) equals 90%. The standard normal random variable associated with 90% service level (z_g) equals 1.282. The value of SS_g equals 18.50. The new safety stock ($SS_{g'}$) equals:

$$SS_{g'} = 18.50 \left(\frac{1.323}{1.282} \right) = 19.09$$

Since the cost per period (TC1) equals 95.22, the new cost per period (TC3) equals:

$$TC3 = (95.22 - 18.50) + 19.09 = 95.81$$

As shown in Table 4.3, BEST1 is identical to BEST2 in 15 out of 16 environments. The only environment that two BESTs are not identical is environment HLHL. In this environment, BEST1 is (R=4, F=15) while BEST2 is (R=4, F=14). Even though the combination (R=4, F=15) is not the BEST in the simulation model, it is the second best time interval combination. The cost per period (TC) for this combination equals 186.01, which is only 0.02% higher than TC for the BEST2. With a 95% confidence interval, we cannot conclude that the BEST2 has a lower TC than the combination (R=4, F=15). In general, not only are the BESTs from the two models identical, but also the TCs associated with these two BESTs are very close. Table 4.3 shows that the percentage differences between TC2 and TC3 are within 1% in all 16 environments, and within 0.4% in all but one case.

Similar results are also found in Table 4.4. As shown in Table 4.4, BEST1 is identical to BEST2 in 15 out of 16 environments. The only environment that the two BESTs are not identical is environment LHLL. In this environment, BEST1 is (R=6, F=9) while BEST2 is (R=4, F=7). Even though the combination (R=6, F=9) is not the BEST in the simulation model, it is the second best time interval combination. The cost per period (TC) for this combination equals 82.44, which is only 0.16% higher than TC for the BEST2. With a 95% confidence interval, we cannot conclude that the BEST2 has a lower TC than the combination (R=4, F=15). Table 4.4 also shows that the differences between TC2 and TC3 are within 0.4%, in all 16 environments.

We then compare the TCs from the two models associated with other combinations of F and R. Table 4.5 summarizes the results from environment LLHH. In this table, TC1 is the value of TC from the MPS model and TC2 is the value of TC from the simulation

Table 4.5 Evaluation of MPS Model - TC

	R = 2			R = 4			R = 6			R = 8		
L	TC2	TC1	DIF(%)	TC2	TC1	DIF(%)	TC2	TC1	DIF(%)	TC2	TC1	DIF(%)
3	153.7	153.5	0.1	128.1	128.1	0.0	123.1	122.8	0.2	122.4	122.6	- 0.2
4	144.3	144.7	- 0.3	122.5	122.6	- 0.1	118.0	118.4	- 0.3	118.9	118.7	0.2
5	138.7	139.0	- 0.2	120.0	119.4	0.6	115.4	115.5	- 0.1	115.7	116.2	- 0.4
6	128.1	128.2	- 0.1	113.8	113.5	0.3	111.0	110.8	0.2	112.4	112.3	0.1
7	121.4	121.4	0.0	109.6	109.8	- 0.2	108.1	108.6	- 0.5	110.0	110.0	0.0
8	110.5	110.6	- 0.1	103.5	104.0	- 0.5	104.2	104.8	- 0.6	107.1	106.5	0.6
9	105.2	105.0	0.2	101.9	101.5	0.4	102.7	103.1	- 0.4	105.8	105.8	0.0
10	97.0	96.8	0.2	97.6	97.5	0.1	100.9	100.4	0.5	104.3	104.2	0.1
11	95.8	95.9	- 0.1	98.0	97.9	0.1	101.2	101.3	- 0.1	105.5	105.8	- 0.3

model. $DIF(\%)$ is the percentage difference between TC1 and TC2, that is,

$$DIF(\%) = \left(\frac{TC2 - TC1}{TC1} \right) 100\% \quad (4.5)$$

Table 4.5 shows that the largest percentage difference between TC1 and TC2 for any combination of F and R is only 0.6%. Similar results are available for the other environments. Based on the results from Table 4.3, 4.4, and 4.5, in the following sensitivity analysis, we will use the MPS model to estimate the cost per period and find the BEST of an environment.

4.3 The Effects of F and R on TC

This section investigates the effects of the choices of F and R on TC, assuming other environmental factors are fixed. These effects depend on the MPS change cost and forecast error cost. Two of the most important environmental factors that have direct effects on the MPS change cost and forecast error cost are the unit change cost and magnitude of forecast error. The unit change cost depends on the *shape* of unit change cost function ($f_m(v_1)$) and the value of parameter A_2 . The shape of $f_m(v_1)$ depends on the value of CLT. Eventually, the unit change cost depends on the values of A_2 and CLT, as shown in Figure 4.2. Therefore, we suspect that the effects of the choices of F and R on TC depend on three factors: the value of CLT, the value of A_2 , and the magnitude of forecast error. Section 4.3.1 describes the experiment design for this study. The results are presented in Section 4.3.2, while Section 4.3.3 discusses the implication of these results.

4.3.1 Experimental design

In order to cover a variety of environments with different values of these three factors, we investigate 8 environments from the 16 environments of the experimental

design in Section 4.2.2. Each of these 8 environments has a either low or high setting for each of these three factors. Preliminary experiments show that the cost structure has only minor effects on the relationship between F, R, and TC. Therefore, the cost structures in all 8 environments are fixed to a value which is equal to the low setting of this factor in Table 4.2. These 8 environments are LHHL, LHHH, LHLL, LHLH, LLHL, LLHH, LLLL, and LLLH. The results of these environments are presented in Figure 4.4 (a), (b), (c), (d), (e), (f), (g) and (h). All graphs in Figure 4.4 are of the same scale. There are four curves in each graph, respectively. Each curve represents the relationship for a certain value of R, which equals 2, 4, 6, or 8. Each dot in the curves represents a TC associated with a combination of F and R.

We also investigate two other environments with *moderate* values of CLT and A_2 . The only difference between these two environments is the magnitude of forecast error. One has a $\sigma_e(u)$ equal to the low setting of the magnitude of forecast error (or $0.15u$) while the other has a $\sigma_e(u)$ equal to the high setting (or $0.15u^{1.3}$) in Table 4.2. Other environmental factors in both environments are the same. These factors are: a cost structure and a demand pattern such that N equals 2, a BOM structure which is the same as that in Figure 1.5(a) except for the value of CLT; CLT equals 17 which is about the midpoint of the low setting (or 12) and the high setting (or 21) in Table 4.2, and an A_2 equals one which is also about the midpoint of the low setting (or 0.2) and the high setting (or 2) in Table 4.2. These settings make the unit change cost function of these two environments, $f_m(v_1)$, equal to:

$$\begin{aligned}
 f_m(v_1) &= \infty & v_1 < 2.4 \\
 &= 10 - 1.027 (v_1 - 2.4) & 2.4 \leq v_1 \leq 9.7 \\
 &= 2.5 - 0.343 (v_1 - 7.3) & 9.7 < v_1 < 17 \\
 &= 0 & 17 \leq v_1
 \end{aligned} \tag{4.6}$$

(a) Environment LHHL

Figure 4.4 Effects of F and R on TC

(b) Environment LHHH

Figure 4.4 (continued)

(c) Environment LHLL

(d) Environment LHLH

Figure 4.4 (continued).

(e) Environment LLHL

(f) Environment LLHH

Figure 4.4 (continued)

(g) Environment LLLL

(h) Environment LLLH

Figure 4.4 (continued)

(i) Environment (FU=1)

(j) Environment (FU=2)

Figure 4.4 (continued)

The results from these two environments are summarized in Figure 4.4 (i) and (j). The environment with the low setting of $\sigma_e(u)$ is called "FU=1", and the other with the high setting of $\sigma_e(u)$ is called "FU=2".

4.3.2 Results

Based on the results from these 10 environments shown in Figure 4.4, several characteristics about the effects of the choices of F and R on TC are observed. Some effects depend on the factor settings of the environment. These factors include the magnitude of forecast error, the value of A_2 , and the value of CLT. In the following discussions, we first present common phenomena that exist in most environments, regardless of their factor settings. We then compare the effects of each factor on the relationship between TC and the choices of F and R.

- 1) In all 10 environments investigated, the value of TC depends on the value of F, regardless of the value of R.
- 2) In most environments (environments LHHL, LHHH, LHLL, LHLH, LLLH, FU=1, and FU=2), when F is small, the value of TC is higher when R equals 2 than when R equals 4 or 6. This difference shrinks as F gets larger. When F gets larger, the differences among the values of TC for R equals 2, 4, 6, and 8 become smaller.
- 3) In the environments with moderate values of CLT and A_2 (environments FU=1 and FU=2), there is a range of F values where the value of TC is close to the minimum value of TC. TC is not sensitive to F within this range. The range becomes narrower as the forecast error gets higher. With FU=1, the range is about $13 \leq F \leq 18$. With FU=2, the range is about $12 \leq F \leq 15$. This range are also found in two other environments (LHHL and LHHH). The range is about $20 \leq F \leq 25$ in environment LHHL and about $20 \leq F \leq 23$ in environment LHHH.

- 4) The effect of the magnitude of forecast error: To understand this effect, we compare the environments having low forecast errors with the environments having high forecast errors pair by pair:

LHHL (Figure 4.4(a)) versus LHHH (Figure 4.4(b)),
 LHLL (Figure 4.4(c)) versus LHLH (Figure 4.4(d)),
 LLHL (Figure 4.4(e)) versus LLHH (Figure 4.4(f)),
 LLLL (Figure 4.4(g)) versus LLLH (Figure 4.4(h)), and
 FU=1 (Figure 4.4(i)) versus FU=2 (Figure 4.4(j)).

In all pairs, the best F value in both the environments having low forecast errors and those having high forecast errors are about the same. A measure of the difference between two environments in each pair is the change ratio of TC due to a change in F. The value of TC changes faster when the forecast errors are high. This indicates that TC is more sensitive to the choice of F when forecast errors are high.

- 5) The effect of the value of A_2 : For this effect, we compare the environments having a high value of A_2 with the environments having a low value of A_2 pair by pair:

LHHL (Figure 4.4(a)) versus LHLL (Figure 4.4(c)),
 LHHH (Figure 4.4(b)) versus LHLH (Figure 4.4(d)),
 LLHL (Figure 4.4(e)) versus LLLL (Figure 4.6(g)), and
 LLHH (Figure 4.6(f)) versus LLLH (Figure 4.6(h)).

In all pairs, for the environment with a high value of A_2 , the value of TC decreases as F increases until a certain value (which equals about 22 when CLT=21 and about 13 when CLT=12). On the contrary, the value of TC increases as F increases for the environment with a low value of A_2 .

- 6) The effect of the value of CLT: For this effect, we compare the environments having a large CLT with the environments having a small CLT pair by pair:

LHHL (Figure 4.4(a)) versus LLHL (Figure 4.4(e)),

LHHH (Figure 4.4(b)) versus LLHH (Figure 4.4(f)),

LHLL (Figure 4.4(c)) versus LLLL (Figure 4.4(g)), and

LHLH (Figure 4.4(d)) versus LLLH (Figure 4.4(h)).

When the value of A_2 is low [pairs (LHLL, LLLL) and (LHLH, LLLH)], both the environments having a large CLT and that having a small CLT demonstrate a very similar relationship between TC and the choices of F and R.

When the value of A_2 is high [pairs (LHHL, LLHL) and (LHHH, LLHH)], the relationship in the environment having a large CLT is quite different from that in the environment having a small CLT. In each of the environments with a large CLT (LHHL and LHHH), there is a range of F values where the differences among the values of TC for R equals 2, 4, 6, and 8 are not significant. The range is about $20 \leq F \leq 25$ in environment LHHL and about $20 \leq F \leq 23$ in environment LHHH. Both ranges include the F value of the BEST. On the contrary, in the environments with a small CLT (LLHL and LLHH), this range does not exist. The relationship between TC and the choices of F and R in these two environments is quite different from that in the other six environments. In the other environments, when F is large, the difference among the values of TC for R equals 2, 4, 6, and 8 is not quite small. On the other hand, in these two environments, the value of TC depends not only on F, but also on R. Even though the F value is the same, the values of TC are quite different if the R values are different. For example, in environment LLHH, when F equals 13, TC is about 96 for R=2, 102 for R=4, 108 for R=6, and 116 for R=8.

4.3.3 Discussion

We have investigated the effects of the choices of F and R on TC for the environments with the assumptions described in Table 1.4. The results from this experiment may not hold in other environments where there are capacity constraints or demand patterns other than that described in Table 1.4. Nevertheless, these results may be helpful in understanding the problems and provide guidelines for future study in more realistic environments. In this section, we discuss the implication of these results.

The fundamental question is: Are the choices of F and R important? The results show that the value of TC depends on the value of F in all environments investigated in our experiments. Also, TC is more sensitive to the choice of F when forecast error gets higher. It appears that managers need to choose an appropriate F for the MPS.

The effect of the choice of R is complex. It depends on the magnitude of unit change cost and the values of F and CLT . When the magnitude of unit change cost is low or CLT is high, the effect of the choice of R depends on the value of F . In this situation, when F is small, replanning frequently ($R=2$) causes high TC . This result is consistent with the findings in previous research, such as Yano and Carlson (1985) and Sridharan and Berry (1988). On the other hand, when F is large, the choice of R has minor effects on TC . When the magnitude of unit change cost is high and CLT is small (environments LLHL and LLHH), the choice of R has effects on TC , regardless of the value of F .

One possible explanation for these results is described below: In general, the value of TC depends on the choices of F and R . When F is large, the effects of F dominate the effects of R and the choice of R becomes less important. But in environments LLHL and LLHH, the value of CLT is small. Therefore, the value of F is relatively small and the effects of F do not dominate the effects of R . Consequently, the choices of F and R are both important. In summary, when the environment has a high magnitude of unit change cost, or when the value of F is small, the choice of R affects TC . When the magnitude of

unit change cost is low and the value of F is high, the effects of the choice of R is less than that of the choice of F .

Another issue is: What is the cost penalty for switching the time intervals away from the BEST? The results suggest that, in the environments with moderate values of CLT and A_2 , there is a range of F values where the values of TC are close to the minimum value of TC . The time intervals can be switched away from the BEST within certain limits. This range depends on the magnitude of forecast error. It is narrower when the magnitude of forecast error is high than when the magnitude of forecast error is low. On the contrary, when the values of CLT and A_2 are large or small, the value of TC is sensitive to the value of F . Managers need to carefully evaluate the possible increases in manufacturing costs before switching the time intervals away from the BEST.

The results also demonstrate the effects of environmental factors. The magnitude of unit change cost affects the BEST. When the unit change cost is high, the results indicate we should freeze longer to reduce the MPS change cost. Consequently, the value of F in the BEST for the environments with a high value of A_2 is larger than that for the environments with a low value of A_2 . On the other hand, the results from this experiment suggest that the forecast error has minor effects on the choices of F and R . If the forecast errors are changed within a certain limit (for example, from $FU=1$ to $FU=2$), managers can keep the same F and R for the MPS. More studies about the effects of environmental factors on the BEST will be presented in Section 4.4.

The result that the forecast error has minor effects on the BEST may surprise managers. Intuitively, managers may expect a shorter frozen interval for higher forecast errors because more safety stock is required for the same frozen interval when the forecast errors are higher. In reality, the BEST of an environment is the combination of F and R that balance the MPS change cost and forecast error cost simultaneously. When the forecast error increases, it increases the required safety stock *and* the size of MPS changes.

In other words, it increases not only the forecast error cost, but also the MPS change cost. The relationship between F , R , and TC is about the same. Consequently, the BEST stays about the same and only the scale of TC is changed.

4.4 The Effects of Environmental Factors on the BEST

In this section, we investigate how the BEST changes as the values of environmental factors change. The results from this analysis will be used to develop guidelines for choosing F and R in the long term. We focus on four environmental factors: cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. The reasons for selecting these four factors are the same as that described in Section 4.2.4.

Among these four factors, the values of cost structure and magnitude of forecast error are fixed in two settings: low and high. These settings are identical to the low and high settings for these two factors in Table 4.2. The cost structure is selected such that N equals 2 or 4. The forecast error standard deviation function, $\sigma_e(u)$, is selected to be $0.15u$ ($FU=1$) or $0.15u^{1.3}$ ($FU=2$). These settings yield four combinations for these two factors, namely, ($FU=1$, $N=2$), ($FU=2$, $N=2$), ($FU=1$, $N=4$), and ($FU=2$, $N=4$). We study two experiments for each combination. For the two experiments in each combination, the first one investigates how the BEST changes as the magnitude of unit change cost varies and the second one studies how the BEST changes as the value of CLT changes.

Based on the results from these experiments, the relationship between the BEST and magnitude of unit change cost will be discussed in Section 4.4.1. Section 4.4.2 describes the relationship between the BEST and CLT . The relationship between the BEST and two other factors, the cost structure and magnitude of forecast error, are presented in Section 4.4.3. Finally, Section 4.4.4 provides the summary.

4.4.1 Relationship between the BEST and magnitude of unit change cost

In the first experiment, we study the effect of the magnitude of unit change cost. The BOM structure is fixed in all environments but the magnitude of unit change cost is changed. The fixed BOM is similar to the high setting in Table 4.2 except that the value of CLT is 17 rather than 21. The unit change cost function, $f_m(v_1)$, equals:

$$f_m(v_1) = A_2 f_3(v_1), \text{ where} \quad (4.5)$$

$$\begin{aligned} f_3(v_1) &= \infty & v_1 < 2.4 \\ &= 10 - 1.027 (v_1 - 2.4) & 2.4 \leq v_1 \leq 9.7 \\ &= 2.5 - 0.343 (v_1 - 7.3) & 9.7 < v_1 < 17 \\ &= 0 & 17 \leq v_1 \end{aligned} \quad (4.8)$$

The changes of the magnitude of unit change cost are made by changing the values of parameter A_2 . We use ten different values of A_2 , one for each environment. These values are increased by 0.2 each time from 0.2 through 2.0. The BEST for each environment is then found using the MPS model. Table 4.6 shows the BEST of all environments in the combination (FU=1, N=2). The graphical representations of Table 4.6 are shown in Figure 4.5. This figure also includes the results from the other three combinations.

The presentations in Table 4.6 and Figure 4.5 need some explanation. Each environment has its own BEST. The BEST of all environments in combination (FU=1, N=2) are shown in Table 4.6(a). As shown in this table, the F value of the BEST in an environment may be the same as that in the other environment. For example, for the combination (FU=1, N=2), the F value of the BEST in the environment where A_2 equals 1.2 is the same as that in another environment where A_2 equals 1.4. Both environments have a F equal to 17. In these situations, instead of plotting all (A_2, F) points, such as points (1.2, 17) and (1.4, 17), we use the average value of these A_2 s as the A_2 for that F value and plot only one point in Figure 4.5. For example, we would plot (1.3, 17). This

**Table 4.6 Adjustments for the Relationships
Between the BEST and A₂ (FU=1, N=2)**

a) Original relationships b) Adjusted relationships

A₂	F	R	A₂	F	R
0.2	7	4	0.2	7	4
0.3			0.3		
0.4	9	6	0.4	9	
0.5			0.5		6
0.6	12	6	0.6	12	
0.7			0.7		
0.8	14	4	0.8	14	
0.9			0.9		4
1.0	15	4	1.0	15	
1.1			1.1		
1.2	17	2	1.2		
1.3			1.3	17	
1.4	17	2	1.4		
1.5			1.5		
1.6	18	2	1.6		2
1.7			1.7		
1.8	18	2	1.8	18	
1.9			1.9		
2.0	18	2	2.0

Figure 4.5 Relationship Between the BEST and A_2

adjustment simplifies the lines in the figure but still keeps the *essence* of the relationship. The same adjustment is also made for R.

In Figure 4.5, the x-coordinate represents the values of A_2 and the y-coordinate represents the values of both F and R. There are two sets of lines in each figure with four lines in each set. The upper set represents the values of F in the BEST while the lower one is the values of R in the BEST. Each dot on the lines represents an F (or R) in the BEST of an environment with a specific value of A_2 . Consequently, each line in a set represents the changes in F (or R) in an combination.

As shown in Figure 4.5, the value of F increases when A_2 gets larger. This result is consistent with result (3) in Section 4.3.2. It implies that the frozen interval should be increased as the magnitude of unit change cost increases. On the other hand, the changes of R in Figure 4.5 are different from that of F. The value of R increases as the value of A_2 increases from 0.2 to about 0.6. It then decreases as the value of A_2 continues to increase from about 0.6 to about 1.7. This result is predictable even though it seems counterintuitive.

Replanning the MPS frequently will introduce more MPS changes. Intuitively, we would expect to replan the MPS less frequently to reduce the MPS changes when the value of A_2 , hence the unit change cost, gets higher. But in our environments the shape of unit change cost function is that of $f_3(v_1)$ in equation (4.8). The function $f_3(v_1)$ is shown in Figure 4.6. The value of $f_3(v_1)$ decreases rapidly when v_1 increases from 2.4 to 9.7. The reduction rate of $f_3(v_1)$ diminishes as v_1 gets larger than 9.7. There is a *kink* at the point of ($v_1=9.7$). Since the MPS is not changed within the planning lead time, if we choose a planning lead time with a value larger than 9.7, we can significantly reduce the unit change cost of the MPS changes in each planning cycle and hence the MPS change cost.

The reduction of the MPS change cost depends on the value of A_2 . Larger A_2 means higher value of unit change cost hence more reduction in the MPS change cost.

Figure 4.6 Unit Change Cost Function ($CLT=17$)

Consequently, the advantage of increasing the value of L is amplified by the value of A_2 . When A_2 is large enough, such as 0.6 in our case, there is an advantage to increase L . Since F equals L plus R , for a fixed value of F , we can increase the value of L by decreasing the value of R . Consequently, R starts to decrease as the value of A_2 increases from 0.6 to 1.7.

This result implies that not only the value of A_2 , but also the shape of unit change cost function is an important factor in choosing a F and R . The shape of unit change cost function depends on the BOM structure, including all components' lead times. Even though the CLT and A_2 of an MSI is kept the same, the changes in the MSI's BOM structure may cause changes of the shape of unit change cost function, hence the BEST, especially the choice of R .

4.4.2 Relationship between the BEST and CLT

For the second experiment, we also study ten environments for each combination of magnitude of forecast error and cost structure. The magnitude of the unit change cost (parameter A_2) is fixed in all environments but the value of CLT is changed. The value of A_2 is set equal to one. For the value of CLT, we use ten BOMs, one for each environment, which are similar to the high setting in Table 4.2 except for the values of their CLTs. The values of CLTs in these ten BOMs are increased by one consecutively from 12 through 21. The results from this experiment are shown in Figure 4.7. The presentations in Figure 4.7 are similar to that in Figure 4.5. Each dot in Figure 4.7 represents a value of F (or R) in the BEST of an environment with a specific value of CLT. The same adjustment for the relationship between F and CLT, and the relationship between R and CLT as that in Figure 4.5 is also applied for Figure 4.7.

As in Figure 4.5, Figure 4.7 shows that the value of F increases as CLT increases in most cases. The two exceptions are: 1) when CLT changes from 13 to 14 in combination

Figure 4.7 Relationship Between the BEST and CLT

(FU=1, N=2), and 2) when CLT changes from 19 to 20 in combination (FU=2, N=4). In the first case, F changes from 13 to 12 as CLT changes from 13 to 14. When CLT equals 14 and F=13, the value of TC equals 85.61. This is the second best and is very close to TC when F=12, which is 85.51. The same situation happens in the second case. The value of TC when F=16 equals 210.70. This is also the second best and is very close to TC when F=12, which is 210.67. It is reasonable to conclude that the value of F increases as CLT increases. This result is very similar to the result in Section 4.4.1. When the value of CLT gets larger, the unit change cost is increased even though the value of A_2 is fixed. Consequently, we should utilize longer frozen intervals to reduce the MPS change cost. Figure 4.7 also shows that the value of R increases as CLT increases. Replanning the MPS frequently will introduce more MPS changes. When CLT, hence the unit change cost, increases, more MPS changes cause even higher MPS change cost. In this situation, we should increase R to reduce the replanning frequency. This result is consistent with the result in Section 4.3 and previous research, such as Yano and Carlson (1985) and Sridharan and Berry (1988), which indicates that replanning frequently causes high TC and is not desirable.

4.4.3 Relationship between the BEST and other factors

Figure 4.5 shows that the value of F decreases only slightly as the magnitude of forecast error is increased from (FU=1) to (FU=2) for the entire range of A_2 . This result is consistent with result (3) in Section 4.3.1 and result (2) in Section 4.3.2. The same situation occurs as the cost structure is changed from (N=2) to (N=4). Figure 4.7 also demonstrates similar results. These results imply that forecast error and cost structure have relatively small effects on the choices of F and R.

The result that the cost structure has small effects on the choice of F seems to contradict the study by Chung and Krajewski (1986). They find that the cost structure

effects the choice of F . But the environment in their study is different from that in this research. They assume a deterministic environment and incorporate master production scheduling with production planning. Their cost structure is different from that in this research also. They consider workforce smoothing, setup, and inventory holding costs. In the experiments of this research, the cost structure includes setup and inventory holding costs. These results seem to suggest that the importance of the cost structure for the choices of F and R depends on the type of environment. More study is needed before making a conclusion about the effects of the cost structure.

4.5 Conclusions

In this chapter, we have evaluated the performance of the MPS model. The results show that this model can be used to estimate TC for a wide range of F and R values, and find the BEST for the Manufacturing environment with a single MSI. We have also investigated and discussed the effects of the choices of F and R on TC, and the effects of environmental factors on the BEST.

Based on the investigations and limitations of these experiments, we find that the choice of F affects TC. But the effects of the choice of R on TC is situational. We also find that, in some environments, F and R can be switched away from the BEST within certain limits. Other findings include the effects of environmental factors. The value of F should be increased as the value of A_2 or CLT increases. The BOM structure also has effects on the choice of R . Even though the CLT of an MSI is kept the same, a change in the MSI's BOM structure may cause a change of R value in its BEST. On the other hand, the cost structure and forecast error have minor effects on the choices of F and R .

Some of these findings are new. For example, the importance of R is situational and the BOM structure has effects on the choices of F and R . Some are consistent with

previous research. For example, replanning frequently is not desirable. Some contradict previous research. For example, the cost structure has minor effects on the choices of F and R .

The results in this chapter are based on an assumption: there is only one MSI. In the next chapter, this research will be extended to the environments with multiple MSIs. In these environments, we will examine the effects for choosing common time intervals for all MSIs and the procedure to find the best common time intervals.

CHAPTER V

MULTIPLE MSIs

In Chapter 3 we have presented a model, called the MPS model, that can be used for finding the BEST of an MSI. The model assumes that the environment has only one single MSI. In most environments, however, there are many MSIs. For example, Berry et al. (1979) reported that the Pfizer, Inc. Pennsylvania plant has 50 MSIs, the Black and Decker Co. Maryland plant has 3100 MSIs, and the Dow Corning Corporation has 4000 MSIs. These MSIs may have different setup costs, inventory holding costs, unit change costs, and hence different individual BESTs. Production planning would be very complex and difficult to control if a specific BEST is used for each individual MSI. A better way is to find a *common* combination of F and R and apply it to all MSIs.

This chapter considers the environments with multiple MSIs where common time intervals are used for all MSIs. It presents a heuristic model, called the MMPS model, for these environments. The MMPS model is an extension of the MPS model. It expresses the expected cumulative average system cost of all MSIs as a function of frozen and replanning intervals, and other environmental factors. This model is presented in Section 5.1. Section 5.1 also evaluates the performance of this model. Under the assumption that the demands and forecast errors of the MSIs are independent of each other, the MMPS model can be used to estimate the system costs for any combination of F and R, and find the best common combination of F and R that minimizes the cumulative average system cost for all MSIs. For simplicity, in the following discussion, the best *common* combination of F and R will be called the **BEST-C**, and the cumulative average system

cost per period for all MSIs will be called the **TTC**. Section 5.2 discusses several heuristic rules that are applied to the procedure for finding the **BEST-C**.

When we use a common combination of **F** and **R** for all MSIs, we may gain a cost advantage due to the reduction in the complexity of the planning and control processes. On the other hand, the common **F** and **R** may be different from the individual **BESTs**. Consequently, the cumulative average system cost per period for all MSIs may be higher than when we use a specific **BEST** for each individual MSI. There is a cost penalty for using common time intervals. The amount of this cost penalty depends on environmental factors. By investigating the relationship between the cost penalty and environmental factors, we may have a better understanding about what situations should common time intervals be used for all MSIs. This relationship is discussed in Section 5.3.

5.1 MMPS Model

This section describes the assumptions of the **MMPS** model and the model itself. The performance of this model is evaluated in Section 5.1.2.

5.1.1 The MMPS model

This model focuses on the Manufacturing environment (described in Chapter 1, Section 1.5 and Table 1.4). We assume that the demands and forecast errors for each MSI are independent of those for other MSIs. The **POQ** rule is used for all MSIs and each MSI has the same time-between-orders (**M**). A common combination of **F** and **R** is used for all MSIs. The capacity constraints are ignored. Since there are no capacity constraints, the lot-sizing decisions for one MSI are independent of those for other MSIs. Therefore, the **MPS** change, forecast error, setup, and inventory holding costs of an MSI are independent of those of the other MSIs. In other words, the relationship between the cost per period for

item j (TC_j) [as defined in Chapter 3, equation (3.37)] and its environmental factors is the same as that in the environment when there is only item j . After a common combination of time intervals is selected for all MSIs, we can *independently* compute the associated value of TC_j for each individual MSI. The sum of these TC_j 's becomes TTC.

The value of TC_j can be estimated using the MPS model. Consequently, for an environment with m MSIs, each has the same F and R , the value of TTC can be expressed as the following equation:

$$\begin{aligned}
 TTC &= \sum_{j=1}^m TC_j \\
 &= \sum_{j=1}^m \{ h_j z_{(g)_j} (\sigma_F)_j \} + \left[\sum_{j=1}^m \left\{ \sum_{p=1}^{G_j} (f_m)_j (L+(p-1)M) (S_p)_j \sqrt{\frac{2}{\pi}} \right\} \right] / R \\
 &\quad + \left\{ \sum_{j=1}^m [k_j + h_j d_j \left\{ \sum_{b=1}^M (b-1) \right\}] \right\} / M
 \end{aligned} \tag{5.1}$$

where G_j is an integer such that $G_j * M \leq CLT_j - L < (G_j + 1)M$, and CLT_j is the cumulative lead time for item j ;

$$\begin{aligned}
 (\sigma_F)_j^2 &= \frac{F}{R} * \sum_{u=L}^{F-1} (f_e)_j(u), & \text{if } F/R \text{ is an integer, or} \\
 &= B * \sum_{u=L}^{F-1} (f_e)_j(u) + \sum_{u=(F-C)}^{F-1} (f_e)_j(u), & \text{if } F/R \text{ is not an integer and } F=B*R+C,
 \end{aligned}$$

where B and C are integers and $R > C \geq 1$;

$$(S_1)_j^2 = \left[\sum_{a=0}^{M-1} \{ (f_e)_j(L+R+a) + (f_e)_j(L+a) \} \right] + \left[\sum_{u=L}^{F-1} (f_e)_j(u) \right]; \text{ and}$$

$$(S_p)_j^2 = \sum_{a=(p-1)M}^{pM-1} \{ (f_e)_j(L+R+a) + (f_e)_j(L+a) \}, \text{ if } p \geq 2.$$

Equation (5.1) is called the MMPS model. In this model, k_j is the setup cost for item j , h_j is the inventory holding cost for item j , d_j is the demand mean for item j , $(g)_j$ is the cycle service level for item j , $(f_m)_j(v_1)$ is the unit change cost function for item j , and $(f_e)_j(u)$ is the forecast error variance function for item j . The MMPS model indicates that the cumulative system cost per period (TTC) depends on the choices of R and F , and other environmental factors.

5.1.2 Evaluation of the MMPS model

As shown in the MMPS model, TTC equals the sum of TC_j 's, where TC_j is computed using the MPS model. In order to evaluate the accuracy of the MMPS model in estimating TTC, we can evaluate the accuracy of the MPS model in estimating TC_j because if the MPS model is accurate in estimating the value of TC , the MMP model should also be accurate in estimating the sum of TC_j 's (or TTC). The performance of the MPS model has been verified in Chapter 4, Section 4.2 for the situation when M equals N . In the MMPS model, however, the value of M may be different from the individual N_j 's. In order to include this situation, we need to evaluate the performance of the MPS model when M is different from N .

The Normal-Simulation model (described in Chapter 4, Section 4.2.1) is used to evaluate the performance of the MPS model. We use two similar experiments. In the first experiment M equals $(N-1)$ while in the second one M equals $(N+1)$. The M values in these two experiments together with those in the experiments of Chapter 4, Section 4.2 cover a range of 1 through 5, which has included all M values that will be used in other experiments of this chapter. Both experiments have 16 environments with the same experimental design as that in Chapter 4, Section 4.2.2. The results of the first experiment are shown in Table 5.1 while Table 5.2. shows the results from the second experiment.

The notation in Tables 5.1 and 5.2 is identical to that in Tables 4.2.2 and 4.2.3, and was explained in Chapter 4, Section 4.2.3.

As shown in Table 5.1, when M equals $(N-1)$, BEST1 is identical to BEST2 in 12 out of 16 environments. Meanwhile, when M equals $(N+1)$, BEST1 is identical to BEST2 in 14 out of 16 environments as shown in Table 5.2. There are six environments in total in which BEST1 is not identical to BEST2. In all six environments, BEST1 is the second best combination of time intervals in the simulation model and the difference between the TC of BEST1 and the TC of BEST2 is very small, compared to their standard deviations, which are shown in Table 5.3. Table 5.3 summarizes and analyzes the results of these six environments.

In Table 5.3, TC2 is the value of TC from the simulation model when the combination of time intervals is BEST2, TC4 is the value of TC from the simulation model when the combination of time intervals is BEST1, σ_{TC} is the standard deviation of the random variable $(TC4-TC2)$ and equal to $\sqrt{\sigma_{TC2}^2 + \sigma_{TC4}^2}$, DIF is the value of $(TC4-TC2)$, and z equals DIF/σ_{TC} . Table 5.3 shows that the value of z is less than 0.6 in all of the six environments. With 95% confidence we can not reject the hypothesis that BEST1 and BEST2 have the same value of TC. Tables 5.1 and 5.2 also show that the percentage differences between TC2 and TC1, and TC2 and TC3 are within 1% in all environments of both experiments. These results suggest that the MPS model can be used to estimate the value of TC even though M is different from N . Consequently, we will use the MMPS model to estimate the value of TTC and find the BEST-C for an environment with multiple MSIs.

Table 5.1 Evaluation of MPS Model (M=N-1)

Environment*	MPS Model				Normal-Simulation Model						$\frac{TC2-TC1}{TC1}(\%)$	$Z_{g'}$	TC3	$\frac{TC2-TC3}{TC3}(\%)$
	BEST1	SH1	CM1	TC1	BEST2	SH2	CM2	TC2	σ_{TC2}	$g'(\%)$				
LHHL	R=2, F=22	118.50	1.38	119.88	R=3, F=23	119.05	1.05	120.10	1.05	88.9	0.2	1.222	119.01	0.9
HHHL	R=3, F=21	200.09	4.00	204.09	R=3, F=22	201.02	2.81	203.83	0.92	89.2	- 0.1	1.237	203.50	0.2
LLHL	R=2, F=13	108.01	1.56	109.57	R=2, F=13	107.93	1.56	109.49	0.24	90.4	- 0.1	1.305	109.71	- 0.2
HLHL	R=3, F=14	192.04	1.74	193.78	R=3, F=14	192.17	1.72	193.90	0.52	90.0	0.1	1.282	193.78	0.1
LHLL	R=4, F=7	102.46	6.32	108.77	R=4, F=7	102.47	6.34	108.81	0.10	89.6	0.0	1.259	108.73	0.1
HHLL	R=6, F=9	186.92	3.25	190.17	R=6, F=9	186.98	3.24	190.22	0.13	90.0	0.0	1.282	190.17	0.0
LLLL	R=4, F=7	102.46	3.18	105.63	R=4, F=7	102.41	3.17	105.58	0.02	89.8	0.0	1.270	105.61	0.0
HLLL	R=3, F=6	185.26	2.85	188.10	R=3, F=6	185.27	2.88	188.15	0.37	89.0	0.0	1.226	188.02	0.1
LHHH	R=1, F=21	143.29	5.78	149.08	R=3, F=23	146.23	2.63	148.86	4.12	89.1	- 0.1	1.232	147.39	1.0
HHHH	R=3, F=21	223.91	9.87	233.78	R=3, F=21	224.86	9.87	234.72	2.38	90.3	0.4	1.300	234.35	0.2
LLHH	R=2, F=13	116.69	3.29	119.98	R=2, F=13	117.01	3.30	120.30	0.58	90.7	0.3	1.322	120.50	- 0.2
HLHH	R=3, F=14	201.75	3.79	205.54	R=3, F=14	201.41	3.77	205.18	1.10	90.0	- 0.2	1.282	205.54	- 0.2
LHLH	R=4, F=7	104.00	12.99	117.00	R=4, F=7	103.94	13.00	116.94	0.24	89.8	- 0.1	1.270	116.96	0.0
HHLH	R=6, F=9	189.69	6.97	196.66	R=6, F=9	189.82	6.92	196.74	0.45	89.6	0.0	1.259	196.55	0.1
LLLH	R=3, F=6	102.98	6.99	109.97	R=4, F=7	104.00	6.00	110.00	0.09	89.7	0.0	1.265	109.93	0.1
HLLH	R=3, F=6	186.31	5.32	191.63	R=3, F=6	186.29	5.32	191.61	0.17	89.9	0.0	1.282	191.63	0.0

* The environments are named according to their four experimental settings in the sequence of cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. A capital "L" means a low setting and a capital "H" means a high setting.

Table 5.2 Evaluation of MPS Model (M=N+1)

Environment*	MPS Model				Normal-Simulation Model						$\frac{TC2-TC1}{TC1}(\%)$	$Z_{g'}$	TC3	$\frac{TC2-TC3}{TC3}(\%)$
	BEST1	SH1	CM1	TC1	BEST2	SH2	CM2	TC2	σ_{TC2}	$g'(\%)$				
LHHL	R=3, F=21	100.09	4.00	104.09	R=3, F=23	101.95	1.45	103.40	0.64	88.5	- 0.7	1.200	103.02	0.4
HHHL	R=5, F=21	196.00	5.11	201.11	R=5, F=21	195.86	5.12	200.98	0.89	89.3	- 0.1	1.242	200.61	0.2
LLHL	R=3, F=14	92.04	1.74	93.78	R=3, F=14	91.74	1.74	93.48	0.26	88.3	- 0.3	1.190	93.16	0.3
HLHL	R=5, F=16	190.16	1.54	191.69	R=5, F=16	189.91	1.56	191.47	1.05	89.8	- 0.1	1.270	191.59	- 0.1
LHLL	R=6, F=9	86.92	3.25	90.17	R=6, F=9	86.77	3.25	90.02	0.15	88.6	- 0.2	1.205	89.95	0.1
HHLL	R=5, F=8	183.01	3.35	186.36	R=5, F=8	183.33	3.35	186.67	0.26	89.5	0.2	1.253	186.29	0.4
LLLL	R=3, F=6	85.26	2.85	88.10	R=3, F=6	85.32	2.86	88.18	0.14	90.5	0.1	1.310	88.14	0.0
HLLL	R=5, F=8	183.01	2.05	185.06	R=5, F=8	183.16	2.05	185.22	0.40	90.5	0.1	1.310	185.13	0.1
LHHH	R=3, F=21	123.91	9.87	133.78	R=3, F=22	128.19	6.90	135.09	1.73	90.5	1.0	1.310	134.67	0.3
HHHH	R=5, F=21	218.26	12.63	230.89	R=5, F=21	216.94	12.72	229.66	2.00	88.8	- 0.5	1.215	228.89	0.3
LLHH	R=3, F=14	101.75	3.79	105.54	R=3, F=14	102.08	3.80	105.88	0.90	89.2	0.3	1.237	104.89	0.9
HLHH	R=5, F=15	199.10	6.42	205.53	R=5, F=15	199.23	6.35	205.58	1.07	90.4	0.0	1.305	205.87	- 0.1
LHLH	R=6, F=9	89.69	6.97	96.66	R=6, F=9	89.61	6.97	96.58	0.30	89.2	- 0.1	1.237	96.44	0.1
HHLH	R=5, F=8	185.13	7.19	192.32	R=5, F=8	185.28	7.24	192.53	0.35	91.1	0.1	1.340	192.55	0.0
LLLH	R=3, F=6	86.31	5.32	91.63	R=3, F=6	86.41	5.30	91.71	0.33	89.7	0.1	1.264	91.59	0.1
HLLH	R=5, F=8	185.13	4.10	189.23	R=5, F=8	184.60	4.05	188.65	0.28	90.2	- 0.3	1.293	189.27	- 0.7

* The environments are named according to their four experimental settings in the sequence of cost structure, BOM structure, magnitude of unit change cost, and magnitude of forecast error. A capital "L" means a low setting and a capital "H" means a high setting.

Table 5.3 Environments where BEST1≠BEST2

M	Environment	BEST2	TC2	σ_{TC2}	BEST1	TC4	σ_{TC4}	σ_{TC}	DIF	z
N-1	LHHL	R=3, F=23	120.10	1.05	R=2, F=22	120.30	1.31	1.68	0.2	0.12
N-1	HHHL	R=3, F=22	203.83	0.92	R=3, F=21	204.28	0.31	0.97	0.45	0.46
N-1	LHHH	R=3, F=23	148.86	4.12	R=1, F=21	151.05	1.84	4.51	2.19	0.49
N-1	LLLH	R=4, F=7	110.00	0.09	R=3, F=6	110.02	0.13	0.16	0.02	0.13
N+1	LHHL	R=3, F=23	103.40	0.64	R=3, F=21	104.15	1.10	1.27	0.75	0.59
N+1	LHHH	R=3, F=22	135.09	1.73	R=3, F=21	135.48	2.91	3.39	0.39	0.12

5.1.3 Effects of F and R on TTC

Based on the assumptions in the MMPS and MPS models, for a given combination of F, R, and M, TTC is a sum of several TCs. Therefore, for a given M value, the relationship between F, R, and TTC should be similar to that between F, R, and TC. In Chapter 4, we have investigated the effects of F and R on TC, assuming M equals the item's natural cycle. In the MMPS model, the M value may be different from the item's natural cycle, but the results from the experiments in Section 5.1.2, where $M=N-1$ and $M=N+1$ indicate that the relationship between F, R, and TC when $M=N-1$ or $M=N+1$ is similar to that when $M=N$. Consequently, under the assumptions in the MMPS model and the limitations of our experiments, the effects of F and R on TTC when there are multiple MSIs may be similar to the effects of F and R on TC when there is one MSI.

5.2 Rules for Choosing the Time-Between-Orders, Replanning Interval, and Forecast window

As in the single MSI environments, in the search for the BEST-C of the multiple MSI environments, the time-between-orders, replanning interval, and forecast window are selected according to several heuristic rules. This section discusses the rationale of these rules. Section 5.2.1 discusses the rule for choosing the time-between-orders (M). Section 5.2.2 presents the rule for choosing R and T. The performance of the rule for choosing M is evaluated in Section 5.2.3. Finally, Section 5.2.4 presents a procedure for finding the BEST-C.

5.2.1 Time-between-orders for the POQ rule

In a single MSI environment, we set M equal to N. This rule is based on the results of Schwarz (1972). It needs to be modified when there are multiple MSIs because these

MSIs may have different N_s . In order to find the rule for choosing M , we extend the model in Schwarz (1972) to include more than one item. The new model and its solution procedure are shown in Appendix. Here we only present the results. For an environment with m items, assuming each item has the same number of orders and the same order timing for each order within a finite forecast window T , we have the following results:

- 1) For a finite forecast window T , the optimal lot-sizing policy is to order n^* equal lots for each individual item, where n^* is the smallest integer satisfying

$$n(n+1) \geq HDT^2/2K, \quad (5.2)$$

$$K = \sum_{j=1}^m k_j, \quad (5.3)$$

$$HD = \sum_{j=1}^m (h_j d_j), \text{ where} \quad (5.4)$$

d_j = the constant demand rate per period for item j ,

h_j = the inventory holding cost per period for item j , and

k_j = the setup cost for item j .

- 2) Under the optimal lot-sizing policy, the average cost per period for a finite forecast window T , A_T , is

$$A_T = n^*K/T + HDT/2n^*. \quad (5.5)$$

- 3) When T is an integral multiple of $\sqrt{2K/HD}$, the value of A_T equals the total economic order quantity (EOQ) cost per period for all items.

We call the parameter $\sqrt{2K/HD}$ the **common natural cycle** (N_c). With the same rationale as that in Section 4.1.1, we choose N_c as a forecast window and set M equal to N_c when N_c is an integer. If N_c is not an integer, we choose its nearest integer as M .

5.2.2 Replanning interval and forecast window

After M is selected, the lot sizes are determined so that each lot will cover an M -period requirement. As mentioned earlier, the lot-sizing decisions for one MSI are independent of that for another MSI when there are no capacity constraints. However, the MPS changes for each individual MSI may be significantly increased when R is not an integral multiple of M , as shown in Chapter 4, Section 4.1.2. Consequently, we should choose R to be an integral multiple of M for all MSIs.

The choice of T is also similar to that in the single MSI environments. The only difference is the value of the lower bound of T . In the single MSI environments, there is only one CLT and $T_{\min} = \max\{M, R + \text{CLT} - L\}$. When there are multiple MSIs, their BOM structures, hence CLTs, may not be identical. Therefore, their required lower bound for T may not be identical. The required lower bound of T for item j , $(T_{\min})_j$, equals:

$$(T_{\min})_j = \max\{M, R + \text{CLT}_j - L\} \quad (5.6)$$

The required lower bound of T for *all* MSIs should be the largest $(T_{\min})_j$ and equals:

$$\begin{aligned} T_{\min} &= \max\{(T_{\min})_j\} \\ &= \max\{M, R + \max\{\text{CLT}_j\} - L\} \\ &= \max\{M, R + \text{MAXCLT} - L\} \end{aligned} \quad (5.7)$$

where $\text{MAXCLT} = \max\{\text{CLT}_j\}$.

5.2.3 Evaluation of the choice of $M = N_c$

The rule derived in Section 5.2.1 for choosing the value of M only considers the setup and inventory holding costs. In the MMPS model, the total cost includes not only these two costs, but also the MPS change and forecast error costs. We want to test whether or not this rule is a good choice for this model. We hypothesize that the BEST-C always has an M with a value equal to the nearest integer of N_c . This hypothesis was tested using an experiment with three MSIs in each environment. The environments in this

experiment have the same assumptions as that in the Manufacturing environment, which was described in Table 1.4.

For all MSIs in the experiment, inventory holding cost (h) equals one, the mean of the demand distribution ($\underline{d}$) equals 50, the standard deviation of demand distribution (σ) equals 10, the cycle service level equals 90%, and the forecast error standard deviation ($\sigma_e(u)$) equals $0.15u$. Also, each MSI has a BOM structure that is similar to the high setting in Table 4.2.1. The shape of the unit change cost is identical to that of $f_2(v_1)$ in Table 4.2.1, but the value of CLT for each MSI is an experimental factor as described below.

We choose three factors for experimentation: the cost structure, value of CLT_j , and value of $(A_2)_j$. The results from the experiments with a single MSI show that two of the most important environmental factors are CLT and A_2 . These two factors should also be important in an environment with multiple MSIs. The purpose of this experiment is to test whether the BEST-C has an M with a value equal to the nearest integer of N_c . The value of N_c depends on the cost structure of these MSIs. Therefore, we choose the cost structure as another experimental factor. Each factor has three levels. This yields 27 environments in total. The experimental factors and their settings are shown in Table 5.4.

In the cost structure, the setup cost for each MSI was selected so that the value of N_c equals 3.44, 3.56, and 4 in the low, medium, and high settings, respectively. Since we are testing whether the value of M should be the nearest integer of N_c , we choose these three N_c s so that one is an integer, and the other two are very close but their nearest integers are different. The value of N_c in the medium setting, 3.56, is only slightly larger than 3.5 and its nearest integer is 4. while the value of N_c in the low setting, 3.44, is only slightly smaller than 3.5 and its nearest integer is 3.

For the values of CLT_j , all items have a CLT equal to 12 in the low setting and a CLT equal to 21 in the high setting. In the medium setting, we let CLT_1 equal to 12, CLT_2

equal to 17, and CLT_3 equal to 21. Other medium settings are possible, such as CLT_1 , CLT_2 , and CLT_3 all equal to 17, but the settings in Table 5.6 represent a reasonable environment to evaluate the choice of $M=N_c$. Similar settings are used for the value of A_2 . In the low setting, all items have the same value of A_2 , which is equal to 0.2. In the high setting, all items have an A_2 equal to 2.0. In the medium setting, $(A_2)_1$ equals 0.2, $(A_2)_2$ equals 1.0, and $(A_2)_3$ equals 2.0.

For each experiment, the value of M is changed from the smallest N_j , which is 2, through the largest N_j , which is 5. In all environments of the following experiments, this range (from 2 to 5) has covered the nearest integer of N_c [$I(N_c)$], its next large integer [$I(N_c)+1$], and its next small integer [$I(N_c)-1$]. After M is selected, the values of R and T are selected using the rules in Section 5.2.2. The BEST-Cs of these 27 environments are shown in Table 5.5. In this table, environments are named according to their three experimental settings in the sequence of cost structure, value of CLT_j , and value of $(A_2)_j$. A capital "L" means a low setting, a capital "M" means a medium setting, and a capital "H" means a high setting. For example, environment LHM is an environment having Low cost structure, High value of CLT_j , and Medium value of $(A_2)_j$. $I(N_c)$ represents the nearest integer of N_c . Table 5.5 shows that the value of M in the BEST-C equals $I(N_c)$ in all environments. These results suggest that we can choose the nearest integer of N_c as M in environments with multiple MSIs.

5.2.4 Procedure for finding the BEST-C

From the results of the above three sections, the following procedure will be applied in the search for the BEST-C of an environment with multiple MSIs:

- 1) Calculate $N_c (= \sqrt{2K/HD})$. Let M equal to (N_c) .
- 2) Let $R = q*M$, where q is an integer, and $T = p_1*M$, where p_1 is an integer, and $T \geq \max \{M, R+MAXCLT-L\}$.

Table 5.4 Experimental Factors for the Evaluation of $M=I(N_c)$ **a) Cost structure**

Low:	Item	1	2	3	$N_c = 3.44$
	k_j	100	160	625	
	N_j	2.0	2.35	5.0	
Medium:	Item	1	2	3	$N_c = 3.56$
	k_j	100	225	625	
	N_j	2.0	3	5.0	
High:	Item	1	2	3	$N_c = 4.0$
	k_j	100	475	625	
	N_j	2.0	4.36	5.0	

b) Value of CLT_j

Low:	Item	1	2	3
	CLT_j	12	12	12
Medium:	Item	1	2	3
	CLT_j	12	17	21
High:	Item	1	2	3
	CLT_j	21	21	21

c) Value of $(A_2)_j$

Low:	Item	1	2	3
	$(A_2)_j$	0.2	0.2	0.2
Medium:	Item	1	2	3
	$(A_2)_j$	0.2	1.0	2.0
High:	Item	1	2	3
	$(A_2)_j$	2.0	2.0	2.0

Table 5.5 Results of Evaluation of $M=I(N_c)$

Environment*	N_c	$I(N_c)$	BEST-C	TC
LLL	3.44	3	M=3, R=3, F=6	456.74
LLM	3.44	3	M=3, R=3, F=12	471.26
LLH	3.44	3	M=3, R=3, F=14	475.69
LML	3.44	3	M=3, R=3, F=6	461.76
LMM	3.44	3	M=3, R=6, F=18	493.51
LMH	3.44	3	M=3, R=6, F=18	495.99
LHL	3.44	3	M=3, R=6, F=9	465.51
LHM	3.44	3	M=3, R=6, F=18	497.20
LHH	3.44	3	M=3, R=3, F=21	507.28
MLL	3.56	4	M=4, R=4, F=7	474.70
MLM	3.56	4	M=4, R=4, F=12	488.74
MLH	3.56	4	M=4, R=4, F=12	494.98
MML	3.56	4	M=4, R=4, F=7	478.46
MMM	3.56	4	M=4, R=4, F=16	510.49
MMH	3.56	4	M=4, R=4, F=17	513.10
MHL	3.56	4	M=4, R=4, F=7	482.08
MHM	3.56	4	M=4, R=8, F=16	515.24
MHH	3.56	4	M=4, R=4, F=21	525.48
HLL	4.00	4	M=4, R=4, F=7	537.20
HLM	4.00	4	M=4, R=4, F=12	551.24
HLH	4.00	4	M=4, R=4, F=12	557.48
HML	4.00	4	M=4, R=4, F=7	540.96
HMM	4.00	4	M=4, R=4, F=16	572.99
HMH	4.00	4	M=4, R=4, F=17	575.60
HHL	4.00	4	M=4, R=4, F=7	544.58
HHM	4.00	4	M=4, R=8, F=16	577.74
HHH	4.00	4	M=4, R=4, F=21	587.94

* The environments are named according to their three experimental settings in the sequence of cost structure, value of CLT_j , and value of $(A_2)_j$. A capital "L" means a low setting, a capital "M" means a medium setting, and a capital "H" means a high setting.

- 3) Given a combination of R, F, and T, apply the MMPS model to calculate the value of TTC.
- 4) Select the combination with the lowest TTC as the BEST-C.

5.3 Cost Increase Due to Using the BEST-C

In an environment with multiple MSIs, we can apply the procedure presented in Section 5.2.4 to find the BEST-C. As mentioned before, the BEST-C may be different from the BESTs for individual MSIs. If it is used for all MSIs, the associated TTC may be higher than when a specific BEST is used for each individual MSI. There is a cost increase. Let **COST-I** represent this cost increase. **COST-I** equals:

$$\text{COST-I} = \text{OP}(\text{TTC}) - \sum_{j=1}^m (\text{OPTC})_j, \quad (5.8)$$

where $\text{OP}(\text{TTC})$ is the cumulative cost per period for all MSIs when the BEST-C is used as the common time intervals, m is the number of MSIs, and $(\text{OPTC})_j$ is the TC for item j when the best combination of time intervals, $(\text{BEST})_j$, is used for this item.

The magnitude of **COST-I** depends on the cost structure deviation of the MSIs. If two MSIs have the same cost structure, their BESTs are the same and the BEST-C for these two MSIs is identical to the BEST. Consequently, there is no cost increase when we use the BEST-C for these two MSIs. On the other hand, a group of two MSIs, where one has an N (or M) equal to 2 and the other with an N (or M) equal to 5, may have a BEST-C that has an M different from 2 or 5. There will be a cost penalty when BEST-C is used for these MSIs.

This section investigates the relationship between **COST-I** and the cost structure deviation of the MSIs. Based on the relationship, we provide guidelines for managers to decide whether or not to use common time intervals for all MSIs. The cost structure

deviation for a group of MSIs is measured using an indicator called **cycle deviation**. Section 5.3.1 defines the cycle deviation and presents an equation for calculating the cycle deviation for a group of MSIs. Section 5.3.2 describes the relationship between the COST-I and cycle deviation, while Section 5.3.3 discusses the results.

5.3.1 Cycle deviation

When there are multiple MSIs, each MSI has its own cost structure and natural cycle. The best M for an MSI is its natural cycle. When the BEST-C is used for all MSIs, the M for item j equals N_c rather than its own natural cycle (N_j). We hypothesize that there is a relationship between the cost increase for item j and the difference of N_c and N_j . In other words, the magnitude of the COST-I depends on the difference between N_c and N_j . The larger the difference is, the higher the cost increase for this MSI will be. We call the difference between N_c and N_j the **cycle deviation** for item j , and use the following equation to compute the cycle deviation (CD) for a group of MSIs:

$$CD = \frac{\sum_{j=1}^m |N_j - N_c|}{m}, \quad (5.9)$$

where m is the number of MSIs, N_j is the natural cycle of item j , N_c is the common natural cycle, and $|N_j - N_c|$ is the absolute value of $(N_j - N_c)$.

5.3.2 Relationship between COST-I and cycle deviation

In this section we investigate the relationship between the COST-I and cycle deviation. The results in the single MSI environments suggest that two of the most important factors which affect the system costs are the values of CLT and A_2 . Therefore, in the experiment, there are 5 environments, each with specific settings for its CLT and A_2 . The first environment is called environment MM. All MSIs belonging to environment MM

have the same CLT equal to 17, which is about the midpoint between 12 and 21, and the same A_2 equal to 1.0, which is also about the midpoint between 0.2 and 2.0. In the second environment, LL, all MSIs have the same CLT equal to 12 and the same A_2 equal to 0.2. In the third environment, HL, all MSIs have the same CLT equal to 21 and the same A_2 equal to 0.2. In the fourth environment, LH, all MSIs have the same CLT equal to 12 and the same A_2 equal to 2.0. In the fifth environment, HH, all MSIs have the same CLT equal to 21 and the same A_2 equal to 2.0.

Each environment has the same five groups of MSIs, call them groups 1, 2, 3, 4, and 5. Each group has three MSIs. All MSIs in the same group have the same factors except for their setup costs. Consequently, the setup costs determine the MSIs' natural cycles and hence the cycle deviation of the group. The setup costs and cycle deviations for groups 1, 2, 3, 4, and 5 are shown in Table 5.6. These setup costs are chosen so that the cycle deviation is increased by $(0.8/3)$ each time from $(0.8/3)$ in group 1 through $5(0.8/3)$ in group 5.

The common factors for the MSIs in the same group include: inventory holding cost (h) (\$1 per unit per period), the mean of the demand distribution ($\underline{d}$) (50 units per period), the standard deviation of demand distribution (σ) (10 units), the cycle service level (90%), the forecast error standard deviation ($\sigma_e(u)$) ($0.15u$), and the shape of the unit change cost function which is the same as that of $f_2(v_1)$ in Table 4.2.1.

The procedure presented in Section 5.2.4 is applied to each group to find the BEST-C and the OP(TTC) of that group. The $(BEST)_j$ and $(OPTC)_j$ for each individual MSI are then found using the MPS model. The value of COST-I is calculated using equation (5.8). The results for the five groups in each individual environment are summarized in Table 5.7. Table 5.7 shows that COST-I has a minimum value of 0% in group 1 and a maximum value of 8.7% in the most *hostile* group (group 5) where N_j s have the widest range from 1.46 to 5.47.

The relationship between the cost deviation and COST-I in each environment is then plotted in Figure 5.1. In Figure 5.1, the x-coordinate represents the cycle deviation with an unit equal to $(0.8/3)$. Figure 5.1 shows that the relationship between the cost deviation and COST-I is almost identical for all environments in this experiment. When the cycle deviation is small (less than $(0.8/3)$ in this case), the value of COST-I equals zero. As the cycle deviation increases, COST-I increases with an almost linear proportion.

5.3.3 Discussion

In this section we have investigated the relationship between the COST-I and cycle deviation for the environments with multiple MSIs. The results indicate:

- 1) This relationship is almost identical for all environments in this experiment.
- 2) When the cycle deviation is small, the value of COST-I equals zero.
- 3) As the cycle deviation increases, COST-I increases in an almost linear proportion.
- 4) In this experiment, COST-I has a maximum value of 8.7% in the most hostile environment where N_j s have the widest range from 1.46 to 5.47.

These results are based on environments with several assumptions, as described in Table 1.4. The results may not hold when the environments are more realistic. Here we discuss the implication of these results under the limitations of our experiment. The linear relationship between the COST-I and cycle deviation is unexpected. We expect that the COST-I will increase as the cycle deviation increases because, under this situation, the difference between the common natural cycle and the individual BEST for each item gets larger. On the other hand, we suspect that this relationship is more complex than a linear function because the MMPS model is not a simple linear function. Whether or not this relationship hold in other environments needs more study.

Result (2) suggests that we can use common time intervals for all MSIs when the cycle deviation is small. On the other hand, when the cycle deviation is high, whether the

Table 5.6 Cycle Deviation Settings**a) Group 1**

Item	1	2	3	$N_c = 4.0$
k_j	320	400	480	
N_j	3.58	4.00	4.38	Cycle deviation = 1 $\left(\frac{0.8}{3}\right)$

b) Group 2

Item	1	2	3	$N_c = 4.0$
k_j	243	400	557	
N_j	3.12	4.00	4.72	Cycle deviation = 2 $\left(\frac{0.8}{3}\right)$

c) Group 3

Item	1	2	3	$N_c = 4.0$
k_j	171	400	629	
N_j	2.62	4.00	5.02	Cycle deviation = 3 $\left(\frac{0.8}{3}\right)$

d) Group 4

Item	1	2	3	$N_c = 4.0$
k_j	106	400	694	
N_j	2.06	4.00	5.27	Cycle deviation = 4 $\left(\frac{0.8}{3}\right)$

e) Group 5

Item	1	2	3	$N_c = 4.0$
k_j	53	400	747	
N_j	1.46	4.00	5.47	Cycle deviation = 5 $\left(\frac{0.8}{3}\right)$

Table 5.7 Result of the COST-I

Environment	Group	Cycle Deviation (0.8/3)	OP(TTC)	(OPTC) _j				COST-I(%)
				Item 1	Item 2	Item 3	Sum	
MM	1	1	564.58	168.19	188.19	208.19	564.58	0.0
	2	2	564.58	144.60	188.19	224.53	557.32	1.3
	3	3	564.58	120.60	188.19	238.93	547.72	3.0
	4	4	564.58	91.71	188.19	251.93	531.83	5.8
	5	5	564.58	66.85	188.19	262.53	517.57	8.3
LL	1	1	537.20	159.07	179.07	199.07	537.20	0.0
	2	2	537.20	134.91	179.07	215.87	529.85	1.4
	3	3	537.20	110.91	179.07	230.27	520.25	3.2
	4	4	537.20	82.23	179.07	243.27	504.57	6.1
	5	5	537.20	57.52	179.07	253.87	490.46	8.7
HL	1	1	544.58	161.53	181.53	201.53	544.58	0.0
	2	2	544.58	137.84	181.53	217.76	537.13	1.4
	3	3	544.58	113.84	181.53	232.16	527.53	3.1
	4	4	544.58	85.31	181.53	245.16	512.00	6.0
	5	5	544.58	61.77	181.53	255.76	499.06	8.4
LH	1	1	557.48	165.83	185.83	205.83	557.48	0.0
	2	2	557.48	141.23	185.83	222.60	549.66	0.9
	3	3	557.48	117.23	185.83	237.00	540.06	3.1
	4	4	557.48	87.75	185.83	250.00	523.58	6.1
	5	5	557.48	62.38	185.83	260.60	508.81	8.7
HH	1	1	587.98	175.99	195.99	215.99	587.98	0.0
	2	2	587.98	151.76	195.99	232.51	580.26	1.3
	3	3	587.98	127.76	195.99	246.91	570.66	2.9
	4	4	587.98	98.22	195.99	259.91	554.12	5.8
	5	5	587.98	72.88	195.99	270.51	539.38	8.3

Figure 5.1 Relationship Between CD and COST

common time intervals should be used may depend on the *value* of these MSIs. A high value MSI means an MSI having high MPS change cost, setup and inventory holding costs. The results show that COST-I has a maximum value of 8.7% in the most hostile environment. Whether or not 8.7% of the total cost is a large amount depends on the amount of total cost, which depends on the number of MSIs and the MPS change, setup and inventory holding costs of these MSIs. For the MSIs with high MPS change, setup and inventory holding costs, the amount of total cost, hence the COST-I, is relative high.

On the contrary, the cost advantage of using a BEST-C for all MSIs is the reduction in the complexity of the planning and control processes. This advantage may depend on the number of MSIs in the group, but rarely the value of these MSIs. The more the number is, the larger the advantage may be. For a group of MSIs having the same number of MSIs, the more valuable the MSIs are, the higher the MPS change, setup and inventory holding costs, the amount of total cost, and hence the COST-I will be. But the cost advantage may be about the same. In other words, when the cycle deviation is high and the MSIs have high value, using the common time intervals is less desirable. In this situation, we can split the entire group of MSIs, put the MSIs with similar cost structure, hence similar natural cycle, into a product family, and use a common combination of time intervals for each product family. This will reduce the total cycle deviation, hence the total COST-I.

Based on the above discussions and based on the assumptions of the environments studied, we suggest that:

- 1) When the cycle deviation is low, the common time intervals can be used.
- 2) When the cycle deviation is high and the MSIs are less expensive, the common time intervals may be used.
- 3) When the cycle deviation is high and the MSIs are expensive, managers should consider to group these MSIs into product families and use a common

combination of time intervals for each product family, rather than use a common combination of time intervals for all MSIs.

In the next chapter, we will summarize the the major findings of this research and discuss the managerial implication. Contributions and issues for future research are also provided.

CHAPTER VI

CONCLUSIONS

This research addresses master production scheduling in uncertain environments. A heuristic model that describes the relationship between the system costs and environmental factors has been developed along with a procedure for finding the best frozen interval (F) and replanning interval (R) for an environment. In addition, the implications of the choices of F and R on total cost have been analyzed. Guidelines for choosing F and R in the short term decisions and the long term decisions are presented. In this chapter, we will summarize these contributions and discuss the managerial implications of the results of this research. Issues for future research are also addressed.

6.1 Rolling Schedule for Developing the MPS

In uncertain environments, the MPS is developed using demand forecasts. When there are forecast errors, the actual demand may not be fully satisfied by a production rate based on the MPS. In order to handle this situation, many firms use a **rolling schedule** procedure to develop the MPS. In a rolling schedule, the MPS is replanned periodically and a portion of the MPS is frozen in each planning cycle. Many time intervals in master production scheduling need to be determined before implementation of a rolling schedule. Two of the more critical ones are the replanning interval and frozen interval. The **replanning interval** is the time interval between two successive replannings of the MPS. The **frozen interval** is a time interval within which the MPS is frozen after the MPS is replanned in each planning cycle.

The procedure for determining the MPS in a rolling schedule includes the following steps:

- 1) Select a lot-sizing rule for the MSI. Determine the forecast window, frozen interval, and replanning interval.
- 2) Forecast the demand within the forecast window a "planning lead time" interval before the MPS is actually scheduled. The planning lead time (L) equals the frozen interval minus the replanning interval.
- 3) Based on the demand forecast, determine the MPS within the forecast window using the lot-sizing rule.
- 4) Implement the MPS within the replanning interval.
- 5) Roll the MPS ahead based on the replanning interval. Repeat steps (2) and (3). Update the MPS within the "free interval" of the previous planning cycle. The free interval equals the forecast window minus the replanning interval. Repeat step (4).
- 6) Repeat step (5) until the entire production horizon is covered.

6.2 MMPS Model

The performance of an MPS depends on the choices of F and R , among others. For the environments with multiple MSIs, a common combination of F and R is usually used for all MSIs. In order to find an appropriate F and R for all MSIs, we need to evaluate the performance of any combination of F and R . One way to evaluate the performance of a combination of F and R is to estimate the cumulative average system cost of all MSIs (TTC) as a function of F and R . This research develops a mathematical model, called the **MMPS model**, that estimates TTC for any given F and R . The MMPS model expresses TTC as a function of F , R , and other environmental factors, including setup cost (k_j),

inventory holding cost (h_j), demand mean ($\underline{d}_j$), cycle service level (g_j), BOM structure of the MSI [including CLT_j and unit change cost function, $(f_m)_j(v_1)$], forecast error variance function $[(f_e)_j(u)]$, and time-between-orders (M) for the POQ rule. In this model, demand for each period is assumed to be identical and independent. Forecast errors are assumed to be normally distributed.

$$\begin{aligned} TTC = & \sum_{j=1}^m \{h_j z(g_j) (\sigma_F)_j\} + \left[\sum_{j=1}^m \left\{ \sum_{p=1}^{G_j} (f_m)_j(L+(p-1)M) (S_p)_j \sqrt{\frac{2}{\pi}} \right\} \right] / R \\ & + \left\{ \sum_{j=1}^m [k_j + h_j \underline{d}_j \left\{ \sum_{b=1}^M (b-1) \right\}] \right\} / M \end{aligned} \quad (6.1)$$

where G_j is an integer such that $G_j * M \leq CLT_j - L < (G_j + 1)M$, and CLT_j is the cumulative lead time for item j ;

$$\begin{aligned} (\sigma_F)_j^2 &= \frac{F}{R} * \sum_{u=L}^{F-1} (f_e)_j(u), & \text{if } F/R \text{ is an integer, or} \\ &= B * \sum_{u=L}^{F-1} (f_e)_j(u) + \sum_{u=(F-C)}^{F-1} (f_e)_j(u), & \text{if } F/R \text{ is not an integer and } F=B*R+C, \end{aligned}$$

where B and C are integers and $R > C \geq 1$;

$$(S_1)_j^2 = \left[\sum_{a=0}^{M-1} \{(f_e)_j(L+R+a) + (f_e)_j(L+a)\} \right] + \left[\sum_{u=L}^{F-1} (f_e)_j(u) \right]; \text{ and}$$

$$(S_p)_j^2 = \sum_{a=(p-1)M}^{pM-1} \{(f_e)_j(L+R+a) + (f_e)_j(L+a)\}, \text{ if } p \geq 2.$$

The MMPS model is a heuristic that approximates the *expected* cumulative cost per period. The performance of this model has been tested. The results suggest that this model can be used to estimate TTC and find the best combination of F and R for all MSIs.

The best time intervals have some specific properties. Based on these properties, the following procedure has been developed for finding the best F and R:

- 1) Calculate the common natural cycle (N_c). $N_c = \sqrt{2K/HD}$, where $K = \sum_{j=1}^m k_j$,
 $HD = \sum_{j=1}^m (h_j d_j)$, m is the number of master scheduling items (MSI), d_j is the constant demand rate per period for item j , h_j is the inventory holding cost per period for item j , and k_j is the setup cost for item j .
- 2) Set M equal the nearest integer of N_c .
- 3) Set $R = q*M$, where q is an integer.
- 4) Set $T = p_1*M$, and $T \geq \max\{M, R + \max[CLT_j] - L\}$, where p_1 is an integer.
- 5) Given a combination of F and R , apply the MMPS model to compute TTC.
- 6) Select the combination with the lowest TTC as the best time intervals using a search of all feasible values of F and R .

6.3 Managerial Implications

In order to handle the uncertain demands, we can replan the MPS more frequently, which will increase the MPS change cost, or freeze a larger portion of the MPS, which will increase the forecast error cost. For an environment with fixed environmental factors, these two costs depend on the choices of two decision variables: F and R . The total cost can be reduced by assigning an appropriate F and R before a rolling schedule is implemented.

While finding F and R that minimize TTC is reasonable from the perspective of manufacturing, it is recognized that production is not the only activity in a firm. The MPS is used not only for production planning, but also for other purposes, such as providing

inputs to marketing. It is possible that managers need to choose a combination of F and R that is different from the best F and R . A managerial consideration is: How much higher will the value of TC be if the time intervals are switched away from the best F and R ?

In the long term, the environmental factors may be changed. The best F and R for the new environment may be different from the best F and R for the old environment. We need to understand the sensitivity of F and R to changes of environmental factors. This knowledge will provide managers guidelines for choosing F and R in the long term decisions.

When a firm has multiple MSIs, a common F and R is usually used not for a single MSI, but for many MSIs. A cost advantage of using a common F and R is the reduction in the complexity of the planning and control processes. On the other hand, the common F and R may be different from the individual best F s and R s. Consequently, the cumulative total TC 's for all MSIs may be higher than when a specific best F and R is used for each individual MSI. Another managerial issue is: Under what situations should managers use a common combination of time intervals for all MSIs, rather a specific F and R for each individual MSI?

The sensitivity analysis and experiments in Chapters 4 and 5 focus on the environments with the assumptions described in Table 1.4. These assumptions include no capacity constraints, the demands and forecast errors of the MSIs are independent of each other, no trends and seasonalities. The results from these sensitivity analysis and experiments may not hold in more realistic environments. Nevertheless, these results may provide knowledge and guidelines for future research in more realistic environments. These results are given below:

- 1) The value of TC depended on the value of F in all environments we tested. The choice of F was important. The value of TC is even more sensitive to the choice of F as the forecast error increased.

- 2) The effects of the choice of R were situational. When the environment had a high magnitude of unit change cost, or when the value of F was small, the choice of R had effects on TC. On the contrary, when the magnitude of unit change cost was moderate or low, *and* the value of F was high, the choice of R had only minor effects on TC.
- 3) In the environments with moderate magnitude of unit change cost and moderate cumulative lead time (CLT), there was a range of F values where the value of TC was close to the minimum value of TC. It is conceivable that managers could switch the time intervals away from the best F and R without large cost increases within a certain range. This range depended on the magnitude of forecast errors. The range was narrower when the magnitude of forecast errors was high rather than low.
- 4) In the environments with extreme magnitude of unit change cost and extreme CLT, the value of TC was sensitive to the value of F. Managers should carefully evaluate the possible increases in production costs before switching the time intervals away from the best F and R.
- 5) When the magnitude of unit change cost was changed from low to high, or the CLT was changed from low to high, it was more cost effective to freeze the MPS longer to reduce the MPS change cost.
- 6) Even though the CLT of an MSI was kept the same, the change in the MSI's bill of materials (BOM) structure could cause the change of its best F and R, especially the choice of R. The BOM structure included the manufacturing/procurement lead times for the components and raw materials.
- 7) In most cases, replanning frequently ($R=2$) was not desirable.
- 8) The cost structure and forecast error had less effect on the best value of F and R, compared to the magnitude of unit change cost and CLT.

- 9) For a group of MSIs, when the cycle deviation of the group (the difference between the cost structures of the MSIs) was low, or when the cycle deviation was high and the MSIs were not expensive, the common time intervals were desirable.
- 10) When the cycle deviation was high and the MSIs were expensive, splitting the MSIs into several product families and use a common combination of time intervals for each product family, rather than use a common combination of time intervals for all MSIs might be a cost effective strategy. A product family consists of the MSIs with similar cost structure.

6.4 Contributions

This research has developed a heuristic model for the MPS in uncertain environments using a rolling schedule. It focuses on the Manufacturing environment (described in Section 1.5 and Table 1.4), which assumes no trends or seasonalities, no capacity constraints, and the demands and forecast errors of the MSIs are independent of each other. This model estimates the average system cost according to the relationship between the system costs and the choices of F and R . It expresses the expected cost per period as a function of F , R , and other environmental factors. Based on the model, this research presents a procedure for finding the best F and R for the Manufacturing environment. It also investigates several managerial issues for selected environments, including how the choices of F and R effect the total cost, how sensitive the changes of the best F and R are to the changes of environmental factors, and when should the common time intervals be used. Based on the results for the environments included, this research has presented guidelines for choosing the F and R in the short term decisions and long term decisions. This research has extended previous research in several dimensions:

- 1) **The environments:** Most previous studies about the MPS in a rolling schedule focus on deterministic environments. This research focuses on uncertain environments. Previous research about the MPS in uncertain environments assumes that the magnitude of the forecast error is independent of the time interval between the current period and the forecast period. This research considers the dependency of the forecast error on the time interval between the current period and the forecast period. Based on the knowledge of the problems in this environment, we have provided a general framework for the MPS problems using a rolling schedule. This framework includes most important MPS time intervals.
- 2) **The problems:** Many studies address the choices of forecast window and lot-sizing rule, considering only the setup and inventory holding costs. This research focuses on the choices of frozen interval and replanning interval, considering not only the setup and inventory holding costs, but also the forecast error cost and MPS change cost. While a few articles have studied the frozen interval or replanning interval, they ignore the planning lead time and assume the frozen interval equals the replanning interval. This research distinguishes the frozen interval from the replanning interval and considers them as two decision variables to be determined simultaneously.
- 3) **The methodology:** Most research studies of rolling schedules use simulation experiments as the methodology. This research uses an algorithm approach that utilizes an in-depth knowledge of the problem. The heuristic model derived in this research can be used to estimate the associated system costs for *any* combination of F and R, and find the time intervals that balance the tradeoff between the forecast error cost and MPS change cost.
- 4) **The results:** This research has investigated several managerial issues for selected environments, including how the choices of F and R affect total cost, how

sensitive the changes of the best F and R are to the changes of environmental factors, and when should common time intervals be used. Based on the results, this research has presented guidelines for choosing the F and R in the short term and long term for these environments investigated in this research.

6.5 Future Research

The development and management of the MPS in an uncertain environment is crucial to the success of the entire MRP system. This research has clearly defined the problems. Based on the model presented in this research and the results from the sensitivity analysis and experiments, future research can be extended to more realistic environments.

This research does not consider capacity constraints. When there are capacity constraints, the relationship between the system cost and the choices of F and R may be different from that in this research, especially for the environments with multiple MSIs. This relationship may also depend on the "tightness" of the capacity. How the tightness of the capacity affects the choices of F and R needs more investigation.

Although the demand is uncertain in this research, the mean of the demand distribution is assumed to be constant. In some environments, demand may be seasonal or trend. In these two situations, the relationship between the MPS change cost and the choices of F and R may be different from that in this research. A more sophisticated model that includes these two situations needs to be developed.

The experimental design and sensitivity analysis in this research use hypothetical data. The data may be different from that in the real world. The next step should be to collect real data from companies and use these data to evaluate the MMPS model and analyze the sensitivity of TTC to the choices of F and R .

The system costs depend on the lot-sizing rule used. This research choose the POQ as the lot-sizing rule. Some firms may use other rules, such as fixed order quantity. The performance of the MMPS model may be different when the lot-sizing rule is different. How robust the MMPS model is to the lot-sizing rule needs more study.

This research has made several assumptions for the unit change cost, including the relationship between the unit change cost function and time interval (v_1), and the linear relationship between the size of MPS change and the MPS change cost. It also assume that the unit change cost function is known. The next step may use a simulation model and input data from the real world to verify these assumptions.

LIST OF REFERENCES

- Baker, K. R., "An Experimental Study of the Effectiveness of Rolling Schedules in Production Planning," Decision Sciences, Vol. 8, No. 1, pp. 19-27.
- Benton, W. C. and R. Srivastava, "Product Structure Complexity and Multilevel Lot Sizing Using Alternative Costing Policies," Decision Sciences, Vol. 16, No. 3, 1985, pp. 357-369.
- Berry, W. L., T. G. Schmitt, and T. E. Vollmann, "Capacity Planning Techniques for Manufacturing Control Systems: Information Requirements and Operational Features," Journal of Operations Management, Vol. 3, No. 1, 1982, pp. 13-25.
- Berry, W. L., T. E. Vollmann, and D. C. Whybark, Master Production Scheduling: Principles and Practice, American Production and Inventory Control Society, 1979.
- Blackburn, J. D., D. H. Kropp and R. A. Millen, "A Comparison of Strategies to Dampen Nervousness in MRP Systems," Management Science, Vol. 32, No. 4, 1986, pp. 413-429.
- Blackburn, J. D. and R. A. Millen, "Heuristic Lot-Sizing Performance in a Rolling-Schedule Environment," Decision Sciences, Vol. 11, No. 4, 1980, pp. 691-701.
- Blackburn, J. D. and R. A. Millen, "Improved Heuristics for Multi-Stage Requirements Planning Systems," Management Science, Vol. 28, No. 1, 1982, pp. 44-56.
- Blackburn, J. D. and R. A. Millen, "The Impact of a Rolling Schedule in a Multi-Level MRP System," Journal of Operations Management, Vol. 2, No. 2, 1982, pp. 125-135.
- Bratley, P., B. L. Fox, and L. E. Schrage, A Guide to Simulation, 2nd. Ed., Springer-Verlag, New York, NY, 1987.
- Carlson, R. C., S. L. Beckman and D. H. Kropp, "The Effectiveness of Extending the Horizon in Rolling Production Scheduling," Decision Sciences, Vol. 13, No. 1, 1982, pp. 129-146.
- Carlson, R. C., J. V. Jucker and D. H. Kropp, "Less Nervous MRP Systems: A Dynamic Economic Lot-Sizing Approach," Management Science, Vol. 25, No. 8, 1979, pp. 754-761.
- Carlson, R. C. and C. A. Yano, "Safety Stocks in MRP - Systems with Emergency Setups for Components," Management Science, Vol. 32, No. 4, 1986, pp. 403-412.

Chand, S., "A Note on Dynamic Lot Sizing in a Rolling-Horizon Environment," Decision Sciences, Vol. 13, No. 1, 1982, pp. 113-119.

Chung, C.-H. and L. J. Krajewski, "Planning Horizons for Master Production Scheduling," Journal of Operations Management, Vol. 4, No. 4, 1984, pp. 389-406.

Chung, C.-H. and L. J. Krajewski, "Replanning Frequencies for Master Production Scheduling," Decision Sciences, Vol. 17, No. 2, 1986, pp.

Chung, C.-H. and L. J. Krajewski, "Interfacing Aggregate Plans and Master Production Schedules via a Rolling Horizon Feedback Procedure," Omega, Vol. 15, No. 5, 1987, pp. 401-409.

Franklin, P., Methods of Advanced Calculus, 1st. Ed., McGraw-Hill Book Company, Inc. New York and London, 1944.

Grave, S. C., "Multi-Stage Lot-Sizing: An Iterative Procedure," Chapter 4 in Schwarz, L. B. (ed.) Multi-Level Production/Inventory Control Systems: Theory and Practice, North-Holland, 1981.

Hax, A. C. and D. Candea, Production and Inventory Management, Prentice-Hall, Inc., Englewood Cliffs, N.J., 1984.

Huang, H. C. and H. L. Ong, "Expected Performance of Some Lot-Sizing Heuristics in a Rolling-Schedule Environment," IIE Transactions, Vol. 16, No. 3, 1984, pp. 248-256.

Keim, S., "It's All a Matter of Timing," APICS 1984 Conference Proceedings, pp. 137-139.

Krajewski, L. J. and L. P. Ritzman, Operations Management: Strategy and Analysis, Addison Wesley Publishing Co., Reading, MA, 1987.

Kropp, D. H. and R. C. Carlson, "A Lot-Sizing Algorithm for Reducing Nervousness in MRP Systems," Management Science, Vol. 30, No. 2, 1984, pp. 240-244.

Kropp, D. H., R. C. Carlson and J. V. Jucker, "Heuristic Lot-Sizing Approaches for Dealing with MRP System Nervousness," Decision Sciences, Vol. 14, No. 2, 1983, pp. 156-169.

Lee, T. L. and E. E. Adam, "Forecasting Error Evaluation in Material Requirements Planning (MRP) Production-Inventory Systems," Management Science, Vol. 32, No. 9, 1986, pp. 1186-1205.

Lee, T. L., E. E. Adam, and R. J. Ebert, "An Evaluation of Forecast Error in Master Production Scheduling for Material Requirements Planning Systems," Decision Sciences, Vol. 18, No. 2, 1987, pp. 292-307.

Malko, R. W., "Master Scheduling: A Key to Results," APICS 1980 Conference Proceedings, pp. 408-412.

Mather, H., "Reschedule the Reschedules You Just Rescheduled - Way of Life for MRP?," Production & Inventory Management, Vol. 18, No. 1, 1977, pp. 60-79.

McCormick, R., "Master Production Scheduling - The Fundamental Concepts," APICS 1980 Conference Proceedings, pp. 400-403.

Orlicky, J., Material Requirements Planning, McGraw-Hill Book Co., New York, NY, 1975.

Pohlen, M. F., "The Freeze Fence: The Balancing Point Between Management Strategy and Operating Control," APICS 1985 Conference Proceedings, pp. 66-69.

Proud, J. F., "Controlling the Master Schedule," Production & Inventory Management, Vol. 22, No. 2, 1981, pp. 78-90.

Proud, J. F., "Master Scheduling Requires Time Fences," APICS 1981 Conference Proceedings, pp. 61-65.

Schroeder, R. G., J. C. Anderson, S. E. Tupy, and E. M. White, "A Study of MRP Benefits and Costs," Journal of Operations Management, Vol. 2, No. 1, 1981, pp. 1-9.

Schwartz, L. B., "Economic Order Quantities for Products with Finite Demand Horizons," AIIE Transactions, Vol. 4, No. 3, 1972, pp. 234-237.

Sridharan, V. and W. L. Berry, "An Analysis of the Cost-Schedule Stability Trade-offs for Freezing the Master Production Schedule Under Uncertainty in a Rolling Schedule Environment," DSI 1988 National Conference Preceeding.

Sridharan, V., W. L. Berry, and V. Udayabhanu, "Freezing the Master Production Schedule Under Rolling Planning Horizons," Management Science, Vol. 33, No. 9, 1987, pp. 1137-1149.

Sridharan, V., W. L. Berry, and V. Udayabhanu, "Measuring Master Production Schedule Stability Under Rolling Planning Horizons," Decision Sciences, Vol. 19 No. 2, 1988, pp. 147-166.

Sung, C. S. and Y. S. Park, "Dynamic Lot Sizing for a Single-Facility Multiproduct Problem in a Rolling-Horizon Environment," Decision Sciences, Vol. 18 No. 2, 1987, pp. 266-278.

Tincher, M. G., "Master Scheduling - The Bridge Between Marketing & Manufacturing," APICS 1981 Conference Proceedings, pp. 57-60.

Tincher, M. G., "Master Scheduling and Final Assembly Scheduling: What's the Difference," APICS 1986 Conference Proceedings, pp. 94-96.

Vollmann, T. E., W. L. Berry, and D. C. Whybark, Manufacturing Planning and Inventory Control Systems, Richard D. Irwin, Homewood, IL., 1988.

Wagner, H. M., and T. M. Whitin, "Dynamic Version of the Economic Lot Size Model," Management Science, Vol. 5, No. 1, 1958, pp. 89-96.

Wemmerlov, U., "Design Factors in MRP Systems: A Limited Survey," Production & Inventory Management, Vol. 20, No. 4, 1979, pp. 15-35.

Wemmerlov, U. and D. C. Whybark, "Lot-sizing under uncertainty in a rolling schedule environment," International Journal of Production Research, Vol. 22, No. 3, 1984, pp. 467-484.

Yano, C. A. and R. C. Carlson, "An Analysis of Scheduling Policies in Multiechelon Production System," IIE Transactions, Vol. 17, No. 4, 1985, pp. 370-377.

Yano, C. A. and R. C. Carlson, "Interaction Between Frequency of Rescheduling and the Role of Safety Stock in Material Requirements Planning Systems," International Journal of Production Research, Vol. 25, No. 2, 1987, pp. 221-232.

APPENDIX

In this appendix, we extend the model in Schwarz (1972) to include more than one item. The objective of this new model is to determine the optimal order policy, that is, the number of orders and the lot size for each order that minimize total cost per period for all items. Since we use the same time intervals for all MSIs, we assume that all items have the same number of orders within T , and the same order timing for each order. All other assumptions are the same as that in Schwarz (1972), that is, demand for each individual item is constant, T is finite, and the cost per period includes only the setup and inventory holding costs.

A two-step procedure is used for determining the optimal order policy. In the first step, we fix the number of orders and determine the best lot size for each order. In the second step, we determine the best number of orders. Let there be m items in total and let k_j , h_j , and d_j be the setup cost, inventory holding cost, and demand rate respectively for item j . Let t_i be the time interval between the $(i-1)$ th and i th orders. Let $C_j(t_i)$ be the total incremental cost for item j within the time interval t_i . $C_j(t_i)$ includes setup and inventory holding costs. There is exactly one setup within t_i . The average inventory level is the order quantity divided by 2 and equal to $d_j t_i / 2$. Consequently, $C_j(t_i)$ equals:

$$C_j(t_i) = k_j + (h_j d_j t_i^2)/2 \quad (\text{A.1})$$

Let there be n orders within T and let $C^n(0,T)$ be the total incremental cost over the entire forecast window $[0,T]$ for the given number of orders, n . $C^n(0,T)$ equals:

$$C^n(0,T) = \sum_{j=1}^m \sum_{i=1}^n C_j(t_i) \quad (\text{A.2})$$

The problem of determining the optimal lot sizes for these n orders can be viewed as the following model:

$$\begin{aligned} \text{Min } C^n(0, T) \\ \text{s.t. } \sum_{i=1}^n t_i = T \end{aligned} \quad (\text{A.3})$$

Using a Lagrangian multiplier, λ , to relax the constraint (A.3), this model is further expressed as:

$$\begin{aligned} \text{Min } f(t_1, t_2, \dots, t_n, \lambda) &= C^n(0, T) - \lambda(T - \sum_{i=1}^n t_i) \\ &= \sum_{j=1}^m \sum_{i=1}^n [k_j + (h_j d_j t_i^2)/2] - \lambda(T - \sum_{i=1}^n t_i) \end{aligned} \quad (\text{A.4})$$

After partially differentiating function $f(t_1, t_2, \dots, t_n, \lambda)$ by t_i , we get:

$$\frac{\partial(f(t_1, t_2, \dots, t_n, \lambda))}{\partial(t_i)} = (\sum_{j=1}^m h_j d_j) t_i + \lambda, \quad i = 1, 2, \dots, n \quad (\text{A.5})$$

In order to minimize the value of $f(t_1, t_2, \dots, t_n, \lambda)$, we let

$$(\sum_{j=1}^m h_j d_j) t_i + \lambda = 0, \quad i = 1, 2, \dots, n \quad (\text{A.6})$$

From equation (A.6) we have

$$t_i = \frac{\lambda}{\sum_{j=1}^m (h_j d_j)}, \quad i = 1, 2, \dots, n \quad (\text{A.7})$$

Note that the value of $\sum_{j=1}^m (h_j d_j)$ is the same for all values of i . From equation (A.7), we have

$$t_1 = t_2 = \dots = t_n = T/n \quad (\text{A.8})$$

Equation (A.8) means that, in the optimal order policy, all time intervals t_i have the same length which equals T/n , where n is the number of orders.

Based on the above result, we now determine the optimal number of orders, n^* . When there are n orders within T , $t_i = T/n$. $C^n(0,T)$ can be expressed as:

$$\begin{aligned}
 C^n(0,T) &= \sum_{j=1}^m \sum_{i=1}^n C_j(t_i) \\
 &= \sum_{j=1}^m \sum_{i=1}^n C_j(T/n) \\
 &= \sum_{j=1}^m \sum_{i=1}^n [k_j + (h_j d_j (T/n)^2)/2] \\
 &= \sum_{j=1}^m [nk_j + (h_j d_j T^2)/(2n)] \\
 &= n \sum_{j=1}^m k_j + \frac{T^2}{2n} \sum_{j=1}^m h_j d_j \\
 &= n K + \frac{T^2}{2n} HD
 \end{aligned} \tag{A.9}$$

where $K = \sum_{j=1}^m k_j$ and $HD = \sum_{j=1}^m h_j d_j$

Equation (A.9) has the same form as the equation in Schwarz (1972) that is used to compute the total incremental cost over the entire forecast window $[0,T]$ when there are n orders. The only difference between these two equations is the values of the parameters. The parameters " k " and " hd " in Schwarz (1972) are replaced by " K " and " HD " in equation (A.9). Using the same logic and procedure as that shown in Schwarz (1972), we get the following results for an environment with m items, assuming each item has the same number of orders and the same order timing for each order within a finite forecast window T :

- 1) For a finite forecast window T , the optimal lot-sizing policy is to order n^* equal lots for each individual item, where n^* is the smallest integer satisfying

$$n(n+1) \geq HDT^2/2K,$$

and $K = \sum_{j=1}^m k_j$, $HD = \sum_{j=1}^m (h_j d_j)$, d_j is the constant demand rate per period for item j , h_j is the inventory holding cost per period for item j , and k_j is the setup cost for item j .

- 2) Under the optimal lot-sizing policy, the average cost per period for a finite forecast window T , A_T , is

$$A_T = n^*K/T + HDT/2n^*.$$

- 3) When T is an integral multiple of $\sqrt{2K/HD}$, the value of A_T equals the total economic order quantity (EOQ) cost per period for all items.