A Thesis

entitled

A Novel Approach to Air Corridor Estimation and Visualization for Autonomous
Multi-UAV Flights

by

Aasim Kamal

Submitted to the Graduate Faculty as partial fulfillment of the requirements for the
Master of Science Degree in Computer Science Engineering

Dr. Ahmad Y. Javaid, Committee Chair

Dr. Vijay K. Devabhaktuni, Committee Co-Chair

Dr. Devinder Kaur, Committee Member

Dr. Cyndee Gruden, Dean
College of Graduate Studies

The University of Toledo

May 2019

Copyright 2019, Aasim Kamal

This document is copyrighted material. Under copyright law, no parts of this document may be reproduced without the expressed permission of the author.

An Abstract of
A Novel Approach to Air Corridor Estimation and Visualization for Autonomous
Multi-UAV Flights

by
Aasim Kamal

Submitted to the Graduate Faculty as partial fulfillment of the requirements for the
Master of Science Degree in Computer Science Engineering

The University of Toledo
May 2019

The world is on the brink of an era of Unmanned Aerial Vehicles (UAVs), widely known to public as drones, where we will get to experience multiple UAVs flying in the national airspace carrying out diverse tasks such as monitoring, surveillance, product deliveries, law enforcement, fertilizing crop fields, aerial photography, and transport. In such scenarios, where multiple UAVs are flying in a smaller airspace, there is a possibility of collisions, path overlaps, mix-ups, and uncertainties as far as their flying routes are concerned. These flying routes could be inside constructed air corridors where the UAVs would be allotted to fly, similar to the air corridors of commercial aircraft. There is a growing need to identify and construct these air corridors for UAVs to fly in their respective corridors to avoid such mishaps as is what is done with commercial airplanes. The airplanes fly in their designated air corridors from one location to another without any uncertainty. It would be really useful to devise and design such a system for multiple UAVs as well, that would be able to construct air corridors for them to fly through.

This served as the primary motivation behind proposing a novel approach to estimate and visualize air corridors for autonomous multi-UAV flights in an airspace. In addition to it, we studied various popular uncertainty visualization techniques and came up with a cutting-edge way to incorporate uncertainty into the visualization of

the air corridors. Furthermore, we provide a standalone web application with a user-friendly graphical user interface (GUI) developed using HTML5, CSS3, JavaScript and an open-source JavaScript library for visualizing world-class 3-D maps called *CesiumJS*. Subsequently, we present the estimation and visualization results and discuss possible application areas where the proposed technique could be put to use. Finally, we discuss the summarized research findings and future research directions.

Dedicated to my parents, Mrs. Shahnaz Badar and Dr. Mohammad Zaki Ahmad, and my wife, Mrs. Mahwish Khan, for their never-ending love, support, trust and patience.

Acknowledgments

I would like to express my deepest gratitude and appreciation for my advisor, Dr. Ahmad Y. Javaid, for his guidance, leadership, patience, and support during the course of my graduate studies. He not only provided me with excellent environment and facilities for my research but also helped me become a better person through his constant support at times when I was unproductive.

A special gratitude to my co-advisor, Dr. Vijay K. Devabhaktuni, whose contribution in stimulating suggestions and encouragement helped me carry out my research in a smooth manner. Furthermore, I would also like to thank my committee member, Dr. Devinder Kaur, for her guidance.

I would like to acknowledge the Electrical Engineering and Computer Science (EECS) department at the University of Toledo for giving me a tuition scholarship that helped me support myself financially. I would also like to extend my appreciation to the University of Toledo for giving me a platform to chase my dream and passion.

I would also like to express my appreciation to the Air Force Research Laboratory (AFRL) and SoarTech Inc. for providing me with the funding for the research assistantship. I would like to thank Jack Zaiantz and Bob Marinier for being great mentors and for guiding me with their valuable inputs and feedback throughout my research.

I cannot thank my parents enough for everything they have done for me. I would also like to thank my wife, Mahwish, for being a source of motivation. Finally, I would also like to acknowledge my sisters, brothers, and friends for their support.

Contents

Abstract	iii
Acknowledgments	vi
Contents	vii
List of Tables	xi
List of Figures	xii
List of Abbreviations	xvii
List of Symbols	xviii
1 Introduction	1
1.1 Problem Statement	2
1.2 Motivation	3
1.3 Objectives and Contributions	4
1.4 Dissertation Outline	4
2 Uncertainty Visualization Survey	6
2.1 The Concept of Uncertainty	8
2.1.1 Uncertainty Sources	14
2.1.1.1 Data Sampling Uncertainty	17
2.1.1.2 Modeling Uncertainty	17

2.1.1.3	Visualization Uncertainty	18
2.1.1.4	Decision Uncertainty	18
2.1.2	Uncertainty Visualization Process	20
2.2	Uncertainty Representation Approaches	20
2.2.1	Quantification Approach	22
2.2.1.1	Probability Theory	23
2.2.1.2	Evidence Theory	24
2.2.1.3	Possibility Theory	24
2.2.2	Visualization Approach	25
2.2.2.1	Uncertainty Visualization Techniques	25
2.2.2.2	Recent Advancements	31
2.2.3	Quantification to Visualization	38
2.3	Evaluation of Techniques	56
2.3.1	Theoretical Assessments	56
2.3.2	User Studies	57
2.4	Chapter Summary	57
3	Flight Data Visualization and Analysis	59
3.1	Overview	59
3.2	Dataset Description	62
3.3	Development Environment	63
3.3.1	Technology Stack	65
3.3.1.1	GeoJSON (geojson.io)	65
3.3.1.2	CesiumJS	65
3.3.1.3	NodeJS	66
3.3.1.4	HTML5, CSS3, and JavaScript	66
3.4	Results	66

3.4.1	Data Preprocessing	66
3.4.2	Visualization	68
3.4.3	Analysis	79
3.5	Chapter Summary	83
4	Multi-UAV Air Corridor Estimation and Visualization	84
4.1	Overview	84
4.2	Proposed Methodology	86
4.2.1	Algorithm	87
4.2.2	Extrapolation and Interpolation	94
4.3	Results	95
4.3.1	Experimental Setup	96
4.3.2	Dataset Creation	96
4.3.3	Visualization	97
4.3.4	Uncertainty Analysis	108
4.4	Possible Application Areas	111
4.4.1	University Campus Monitoring	111
4.4.2	Military Warfare	112
4.4.3	Agriculture	112
4.4.4	Photography	113
4.4.5	Product Delivery	113
4.4.6	Disaster Relief	113
4.4.7	Wildlife Conservation and Management	114
4.5	Chapter Summary	114
5	Conclusion and Future Works	116
5.1	Conclusion	116
5.2	Strengths and Limitations	117

5.3	Future Work	118
5.3.1	Air Corridor Estimation and Visualization	118
5.3.2	Uncertainty Visualization	119
	References	124
A	Application Code Snippets	144
A.1	Cesium Viewer and Terrain Provider	144
A.2	Compute Flight Path	145
A.3	Compute Reference Flight Path	148
A.4	Data Preprocessing in MATLAB	152

List of Tables

1.1	Research Products	4
2.1	Uncertainty taxonomy, extended and adapted from [25, 26].	10
2.2	Summary of the various uncertainty visualization techniques.	44

List of Figures

2-1	Uncertainty sources - Uncertainty results from sampling, modeling, visualization, and decision processes.	14
2-2	Haber and McNabb model depicting uncertainty visualization pipeline. .	16
2-3	Uncertainty visualization process integrates visualization of raw and uncertain data.	19
2-4	Several approaches to uncertainty representation.	21
2-5	Uncertainty at each point was calculated and mapped to the pseudo-color alpha value to encode uncertainty information and distinguish from surface geometry information. Reproduced from [73].	22
2-6	Different types of box plots depicting error information. Reproduced from [50].	26
2-7	2-D box-plot extension: Mean is visualized by the lowest flat surface and the standard deviation is visualized by the distortion seen. The difference between the quartiles is represented by the use of color. Furthermore, the variance between mean and median is visualized by the size of the upward bars, which have colors in sync with the base surface which itself represents mean. Reproduced from [91].	27
2-8	Magnitude, direction and length in glyphs depicting uncertainty. Reproduced from [70].	28
2-9	Arrow glyphs without uncertain information. Reproduced from [70]. . . .	29
2-10	The visual variables displaying uncertainty. Reproduced from [26].	31

2-11	Use of color gradient represents levels of uncertainty.	32
2-12	Noise in line graph denotes uncertainty.	33
2-13	Size and color of nodes represent uncertainty in big data. Reproduced from [72].	34
2-14	Squarified Treemaps. Reproduced from [117].	35
2-15	Consumer expenditure survey visualization using Bubble Treemaps indicating error and uncertainty through thickness of the contours and blur effect. Reproduced from [120].	36
2-16	Pie glyphs (top) and speckle glyphs (bottom) representing uncertainty in predictions made by Machine Learning models. Legends are shown in the right table. Reproduced from [124].	38
2-17	A visual analytics system called TopicPanorama (left). Dotted section illustrates an uncertainty glyph (middle). A and B represent incorrect matching, C and D show correct matching in matching result. Reproduced from [126].	39
2-18	Bubble Treemaps demonstrating how quantification can be used as a building block to visualization. Reproduced from [120].	40
2-19	Probabilistic graph layout of an uncertain network achieved using probabilistic graph and force-directed layout. Reproduced from [54].	41
2-20	Positional uncertainty visualized from variance values. Reproduced from [98].	41
2-21	Uncertainty quantification to visualization: Diagram illustrates the relationship between quantification and visualization.	43
3-1	Block diagram of flight data visualization process.	61
3-2	A snapshot of the geojson.io application showing how the data is collected in JSON format.	64

3-3	Flowchart of the data preprocessing stage.	67
3-4	Initial short trail of the single flight path (west view).	69
3-5	Initial short trail of the single flight path (top view).	69
3-6	Flight corridor visualization of the initial short trail of the single flight path (top view).	70
3-7	Full trail of the single flight path.	70
3-8	Air corridor visualization of the full trail of the single flight path.	71
3-9	ADS-B Exchange multiple flight dataset visualization with red squares depicting aircrafts at two distant locations.	72
3-10	ADS-B Exchange multiple flight dataset visualization with a flight path in pink color showing the two distant locations.	73
3-11	Single flight path data acquired from [151] split into multiple flight path data (side view).	74
3-12	Single flight path data acquired from [151] split into multiple flight path data (Close-up view from south-west).	74
3-13	Single flight path data acquired from [151] split into multiple flight path data (south view).	75
3-14	Single flight path data acquired from [151] split into multiple flight path data (top view).	75
3-15	Single flight path data acquired from [151] split into multiple flight path data (west view).	76
3-16	Visualization of our own flight data: flights at different altitude (top view).	76
3-17	Handcrafted data visualization: flights at different altitude (side view).	77
3-18	Handcrafted data visualization: altitude variation in flight routes (side view).	77
3-19	Handcrafted data visualization: altitude variation in flight routes (south-west side view).	78

3-20	Visualization of our own flight data: flights at different altitude (side view).	78
3-21	Visualization of our own flight data: flights at different altitude (side view).	79
3-22	Multiple flight paths visualization using our own created flight data (side view).	80
3-23	Multiple flight paths visualization using our own created flight data (east view).	80
3-24	Multiple flight paths visualization using our own created flight data (side view after being rotated 180 degrees clockwise).	81
3-25	Multiple flight paths visualization using our own created flight data (top-most View).	81
3-26	Multiple flight paths visualization using our own created flight data (top View).	82
3-27	Multiple Air corridors visualization using our own created flight data. . .	82
4-1	Overview of the research strategy.	85
4-2	UAV1 positions over time.	88
4-3	UAV2 positions over time.	88
4-4	Computed reference corridor from UAV1 and UAV2 positions.	89
4-5	Corridor slice over reference positions computed from UAV1 and UAV2 positions.	90
4-6	Reference corridor with all position slices computed and interpolated edges.	90
4-7	Air corridor averaging estimation algorithm	93
4-8	User input buttons offering several functionalities.	98
4-9	A closer look at the user input buttons.	99
4-10	Legend depicting the level of uncertainty from low to high.	100
4-11	Air corridors of 11 UAVs overlapping with each other (top view).	100

4-12	Air corridors of 11 UAVs overlapping with each other (side view from south-east).	101
4-13	Close view of the source where multiple UAVs are starting their flights . The white path in the center region is the estimated reference average path.	101
4-14	Corridors view from north-east.	102
4-15	Corridors view from south-west.	102
4-16	Multiple UAV flight paths from a given source to destination.	103
4-17	The estimated air corridor.	103
4-18	Air corridors without the flight paths.	104
4-19	Air corridors without the flight paths (north-west view).	104
4-20	Extrapolation: The red path is extrapolated and the extrapolated part is displayed by the blurred white path. The blur effect is added to denote the uncertainty in extrapolation.	105
4-21	Interpolation: The red path with 10 points initially were interpolated to 37 points, which is visualized as a blurred white path. The blur effect depicts the uncertainty in interpolation.	107
4-22	Uncertainty in the air corridors are being visualized here with the use of same color, color gradient effect and fading. The more prominent white in the below figure denotes the region of low uncertainty.	109
4-23	Error/Uncertainty in estimation of the air corridors.	110

List of Abbreviations

ADS-B	Automatic Dependent Surveillance - Broadcast
API	Application Programming Interface
ATC	Air Traffic Control
CDF	Cumulative Density Function
CSS	Cascading Style Sheet
CSV	Comma Separated Values
DSET	Dempster-Shafer Evidence Theory
FAA	Federal Aviation Administration
GIS	Geographic Information System
GPS	Global Positioning System
GUI	Graphical User Interface
HTML	Hypertext Markup Language
JS	JavaScript
JSON	JavaScript Object Notation
ML	Machine Learning
OU	Ohio University
PDF	Probability Density Function
UAS	Unmanned Aerial System
UAV	Unmanned Aerial Vehicle
UI	User Interface

List of Symbols

Ω	Total number of probable results of an arbitrary event
$P(A)$	Probability of the occurrence of any outcome
ϕ	Latitude
λ	Longitude

Chapter 1

Introduction

Unmanned Aerial Vehicles (UAVs), popularly known as drones, are pilotless aircrafts with no human pilot on-board. They are basically constituents of an unmanned aircraft system (UAS), comprising a UAV, a ground-based remote controller, and a framework of communications between the two. UAVs can function with varied levels of autonomous operation. For instance, they can either be remotely controlled by human operators or fly autonomously with the help of software aboard [1, 2]. UAVs are making big inroads into our lives nowadays. Originally meant to be used only in the military, they are now being increasingly used in commercial, recreational, and scientific applications [3], such as aerial surveillance [4], aerial photography [5], research and development [6], agriculture [7], surveying [8, 9, 10, 11, 12, 13], consumer product deliveries [14, 15, 16], drone racing [17], peacekeeping [18], disaster relief [19, 20, 21], and smuggling [22], owing to commercially available drones and their widespread production. The usage of drones has skyrocketed in recent years. It can be inferred from the fact that the number of UAV permits approved by the Federal Aviation Authority (FAA) has increased manifold since 2015 [23].

Due to this increasing popularity of drones, in the future we could see a number of UAVs flying together in an airspace engaging in activities such as monitoring, surveillance, photography, surveying, product deliveries, and drone racing. The group

of UAVs flying over a small area could be a part of next-generation multi-UAV systems. Such a scenario could lead to chaos if there is not a proper system in place. Air corridors can help them navigate safely in a small airspace. To fly safely, avoiding any collisions or mishaps, there is a need for us to design and develop next-generation multi-UAV systems, which would be able to create air corridors for multiple UAVs to fly through without any accidents. Such multi-UAV systems should be able to estimate and visualize the air corridors to navigate multiple drones safely.

With any computation or estimation comes uncertainty, which is a widespread phenomenon in mathematical calculations. Uncertainty visualization is one powerful way to effectively convey the uncertainty in calculations. Since the error is intrinsic to any estimation, it cannot be neglected, and, thus, it is essential to consider it in any research analysis. That being said, we included the error/uncertainty analysis in our research and attempted to visualize the uncertainty in our proposed framework. Failing to observe it in visualization can lead to flawed decision-making by the human operators. In most cases, visualization approaches reckon that the information represented is free from any error or unreliability; however, this is rarely true. The goal of uncertainty visualization is to minimize the errors in the judgment and represent the whole information as accurately as possible. In this research work, we are going to apply some of our findings of our survey on cutting-edge approaches to uncertainty visualization to our visualization results. One popular way to visualize uncertainty is the efficient use of color, blur, and fading. We have effectively used color, blur, and fading to depict uncertainty in our air corridors visualization.

1.1 Problem Statement

When multiple UAVs are flying in a constrained airspace, there are possibilities of UAVs flying in overlapping air corridors or outside the allotted corridors. For

instance, multiple UAVs designed to fly from a source to a destination at different times are meant to follow the exact allotted path and share the same flight corridor; however, due to on-the-go path planning and deflections owing to external factors like wind, enemy, etc., their actual traveled paths could vary slightly. The objective here is to estimate and visualize different air corridors along with the duration or volume of these air corridors and evaluate the strengths and weaknesses of the approach taken.

1.2 Motivation

Drones are gaining popularity with each passing day like never before. The world is entering an era of drones where we will get to experience multiple UAVs flying in the airspace carrying out tasks such as monitoring, surveillance, product deliveries and photography. In a scenario where multiple UAVs are flying together in a small airspace, there is a possibility of collision and path overlaps as far as their flying routes are concerned. There is a need to identify and detect air corridors for UAVs to fly in their respective corridors to avoid such mishaps, as is the case with commercial airplanes. The airplanes fly in a designated air corridor from one point to another without any confusion. It would be really useful to devise and design such a technology for multiple UAVs as well to be able to detect, estimate, and visualize air corridors for them to fly through. The idea of such a system motivated us to think in that direction and come up with proposed solution to tackle such cases. Such a monitoring system could be really useful for the UAV research community, as the possibilities of it are endless in terms of its application in diverse areas. The corridor estimation technology could be applied to several areas such as surveillance, monitoring systems, agriculture, etc., and it could really change the way we look at several possible applications of UAVs.

1.3 Objectives and Contributions

The objective of this research is to work out an approach that would estimate and visualize the air corridors for multiple UAV flights in an airspace for next-generation multi-UAV monitoring systems and evaluate the strengths and weaknesses of the approach taken. The contribution of our work is manifold, as is summarized below:

- A novel approach to estimation and visualization of air corridors in an airspace is introduced for a multi-UAV system.
- The uncertainty regions in the estimation of air corridors is visualized using a popular method of uncertainty visualization.
- The strengths and weaknesses of the proposed approach is also evaluated.
- The possible application areas of our research are also discussed.
- The products of the research are shown in Table 1.1.

Table 1.1: Research Products

Type	Contribution
Journal Paper (In Preparation)	A Novel Approach to Air Corridor Estimation and Visualization for Multi-UAV Autonomous Flights.
Journal Paper	Literature survey on recent advances and challenges in Uncertainty Visualization.
GitHub	https://github.com/aasimkamal/Thesis

1.4 Dissertation Outline

The thesis unfolds as follows:

Chapter 1 introduces the dissertation topic, the problem statement, and the motivation behind it. It also describes the research objective and the major contributions of this work. Finally, it gives a brief outline of the thesis.

Chapter 2 discusses uncertainty visualization in detail and surveys the state-of-the-art approaches to uncertainty visualization.

Chapter 3 presents flight data acquisition, its visualization and analysis. This chapter describes the various sources of flight data and data preprocessing stage, illustrates the flight data visualization results and sheds light on the analysis of the results.

Chapter 4 explains the proposed algorithm to estimate and visualize the air corridors of multiple UAVs flying in an airspace. It presents the implementation details and results of the proposed methodology. It also discusses in length the possible application areas where our proposed novel approach could be implemented.

Chapter 5 concludes the dissertation by summarizing major results and findings obtained in this research and gives recommendations for future work. It discusses possible extensions of our developed application.

Finally, the thesis ends with Appendix A, containing the JavaScript source code written to design and develop the air corridor estimation and visualization system.

Chapter 2

Uncertainty Visualization Survey

With the exponential rise in the size and complexity of data due to technological advancements, there has been a never before seen demand for more efficient representation of huge amounts of information, called big data. Data visualization involves the creation of visual representations of data using images, pictures, diagrams, or animations to communicate abstract and concrete messages. Data visualization has emerged as a very powerful tool to explore, manage, and understand these massive, extremely complex data sets. An effective visual representation of data can go a long way in making it more comprehensible and approachable to analysts and decision-makers and helping them to make better and more-informed decisions. Visualization, in most cases, is often thought to be exact visual representation of the actual information. However, that's not always possible in real-world scenarios, as no data are said to be fully reliable and complete. There is bound to be some degree of uncertainty associated with any kind of information. Uncertainty is present everywhere, such as economic uncertainties due to lack of clear measurements, weather uncertainties due to lack of accuracy in prediction, medical diagnosis uncertainties due to lack of precision, and sensor data uncertainties due to inaccuracy, error, or lack of completeness in measurements. The key challenge is to identify and understand the unpredictability involved with the given information and to efficiently visualize it. Therefore, uncer-

tainty visualization is a very important research issue, and consequently, a notable amount of literature is available on the topic [24].

The objective of this chapter is to review the cutting-edge methodologies in uncertainty representation and group them based on their approaches. To classify the uncertainty representation techniques into different approaches, we first introduce the concept of uncertainty in section 2.1. We also put forward a study of the uncertainty and the various sources that can lead to reliability issues in a system in the same section. Once a brief concept of error and uncertainty is established in section 2.1, the next step is to classify the representation techniques into various approaches. The several approaches to uncertainty representation are then discussed in detail in section 2.2. The notable representative works and their methodologies in the domain of uncertainty visualization are summarized in Table 2.2 toward the end of section 2.2. Section 2.3 then discusses the evaluation strategies, which can be used for the assessment of the representation methodologies. The literature survey on uncertainty visualization then concludes in the section 2.4.

The contribution of our work in the area of uncertainty visualization is summarized below:

- A new source of uncertainty called decision uncertainties is introduced in this thesis apart from the sources mentioned in various earlier literature.
- The uncertainty representation techniques have been grouped into two - quantification and visualization, which are further subdivided into various categories.
- The uncertainty visualization techniques along with their representative works, merits, and drawbacks have been summarized in a tabular form for the purpose of referral for visualization designers in the field.
- A discussion of open problems in the field and suggestions of possible future research directions have been presented.

2.1 The Concept of Uncertainty

Multiple definitions of uncertainty exist in the literature [25]. Different authors have their interpretations of uncertainty. Uncertainty is a hard and complex concept, which has multiple facets to it such as incompleteness, inconsistency, error and unreliability [26, 27]. It signifies incomplete information and an extent to which the lack of understanding about the quantity of error is the cause of doubt in final results [28]. Decision-makers come across different kinds of uncertainty and it is challenging to formally define uncertainty, as it covers various concepts such as error, inaccuracy, incompleteness, reliability, and inconsistency [29, 30]. In one of the earliest works in the area of uncertainty representation, uncertainty was classified as error, range, and statistical [31]. A measurement of the probability of errors was also termed as calculation of uncertainty [32, 33]. Error is only one of the elements of uncertainty and alone does not account for the whole of it. In fact, it is a broader extent of apprehension than is suggested by error alone [34]. Many other definitions exist as well such as users knowledge imperfections, the extent of clarity, reliability, precision, and ignorance, to name a few [35, 36, 37]. From what we have gathered so far, there is no precise and simple definition of uncertainty [38]. Information visualization has its classification of uncertainty owing to the work done by [39]. Incomplete information about the extent of error can also be defined as uncertainty [28]. [25] came up with their interesting idea of uncertainty in the area of Intelligence Analysis. Their taxonomy included uncertainty of nine kinds: “Accuracy/Error, Precision, Completeness, Consistency, Lineage, Currency/Timing, Credibility, Subjectivity, and Interrelatedness” [25]. In their work, they also discussed mapping of these nine different categories to different domains and quantitative representation using probabilistic approach. The proposed uncertainty typology, along with their domain examples, is summarized in Table 2.1. As seen in Table 2.1, the three components of information is mapped to the nine

types of uncertainty. Though their work was focused more in the area of intelligence analysis, it can be extended to other domains easily. An extension of their typology was proposed by [40] in their literature.

Despite the uncertainties associated with any information, data visualization has often assumed information to be mostly accurate. Uncertainty is always considered a difficult concept and consequently, visualization designers find it hard due to the practical problems in visualization construction and uncertainty modeling relative to decision-making. Uncertainties in any information may lead to faulty decision-making. For example, assume that analysts are trying to figure out the impact of a social networking website data breach. They would be only concerned with the number of people affected to gauge the immediate impact; however, other parameters such as who those people are or what their personal information like age, gender, race, ethnicity, etc. are, would be needed to assess the long-term impact of the data breach. Uncertainty in the same data affects the decision-making strategy of analysts in different ways [25].

Uncertainty can arise at all stages of a visualization process - at the data collection, the transformation, and the visualization process itself [31]. Integrating data visualization with the representation of unreliability is not a trivial task [41]. Several approaches, frameworks, and taxonomies have been proposed by researchers in the past to represent uncertainty in data visualization [31, 25, 42, 43, 44, 45, 46]. Some of the most important uncertainty formalisms were covered by [42]. They discussed numerical approaches and symbolic approaches for handling uncertainty and suggested that a hybrid approach is required to counter uncertainty in most problems. Uncertainty should never be confused with absence; while absence is a case of missing data, uncertainty can be defined as data that lies between falseness and truth [47]. [48] surveyed the newest uncertainty visualization methods and discussed visualizing uncertainty as well as the uncertainty of the visualization process itself. They

Table 2.1: Uncertainty taxonomy, extended and adapted from [25, 26].

Type	Explanation	Space	Time	Attribute
Accuracy/Error	difference between hands-on and inferences	coordinates., buildings	+/- 5 hours	counts, magnitudes
Precision	difference between hands-on and observation	1 degree	once per day	nearest 1000
Completeness	extent of the completeness of the knowledge or data	20% cloud cover	5 samples for 100	75% reporting
Consistency	extent of the regularity of the hands-on evaluation	from/for a place	5 say M; 2 say T	multiple classifiers

Type	Explanation	Space	Time	Attribute
Lineage	the pipeline of the hands on assessment	# of input sources	# of steps	transformations
Currency/Timing	temporal gaps between reality, data sampling and hands-on estimation	age of maps	$C = T_{present} - T_{info}$	census data
Credibility	data and hands-on accuracy	knowledge of place	reliability of model	U.S. analyst vs. informant
Subjectivity	extent to which the practical approach utilized	local $\leftrightarrow$ outsider	expert $\leftrightarrow$ trainee	fact $\leftrightarrow$ guess

Type	Explanation	Space	Time	Attribute
Inter-relatedness	extent to which information is un- biased or uninflu- enced	source prox- imity	time proximity	same author

pondered over why uncertainty is considered hard for the visualization designers and attributed it to practical problems in visualization construction and uncertainty modeling with respect to decision-making. These practical issues are the reasons why most visualizations do not represent uncertainty [49, 24].

Various sources of uncertainty can be attributed to the sampling of the data, modeling, mathematical operations on the data, and the visualization process itself [50]. There are several numerical approaches that can be used to tackle uncertainty. The unreliability in information can be portrayed by several mathematical approaches, e.g., possibility, probability, and Dempster-Shafer theories [42]. Probability Density Function (PDF), multi-value data or bounded data can also depict uncertainty [48]. A new approach was presented by [38], who tried depicting the course of uncertainties in analytical processes. In many diverse applications, analytical processes can lead to uncertainties in any stage [51, 52, 53]. Another novel approach in the area of uncertainty visualization of network has been recently proposed using probabilistic graph layout techniques [54]. An empirical evaluation of the uncertainty visualization in different domains was done by [39]. They suggested that by developing ways to incorporate uncertainty visualization as much as possible, one can make the end users better understand the data. Ignoring uncertainty in visualization can be deceptive to analysts, which can lead to faulty decisions [51, 49, 55, 25].

The concept of uncertainty is applicable in almost all areas, be it science, geography, cartography, medicine, business, and so on. In the beginning, representation of uncertainty received a lot of attention in the area of scientific visualization [31]. Later, researchers realized that there is a lack of certainty in other areas too like information visualization [56]. Visualization scientists and researchers have risen to the challenge of trying to understand uncertainty associated with data and efficiently representing this uncertainty along with the data. Hence, visualization of error and reliability has become an area of interest for a lot of researchers within the scientific visualization

and information visualization communities [57, 49, 58]. Uncertainty visualization was first implemented in Geographic Information Systems (GIS) [59]. Since then, a lot of work has been done in other areas as well, some of which are fluid flow, geography and medicine [60, 61, 29, 62]. The following sections will shed some light on the various uncertainty sources and how a concept of uncertainty can be put to visualization.

2.1.1 Uncertainty Sources

Figure 2-1: Uncertainty sources - Uncertainty results from sampling, modeling, visualization, and decision processes.

There are multiple sources of uncertainty in a system or a process. It is important to establish the source of uncertainty to represent uncertainty [63]. Uncertainty depends on the situation, and different scenarios can bring uncertainty in different ways. For example, an uncertainty can result in a data set from the way data are sampled or gathered or it may result due to data transformations at later stages. There

could also be discrepancies in the process itself, which might result in uncertainty. Several possible sources of error and uncertainty can be identified in a system such as sensors and their readings, simulations, observations, numerical transformations like interpolation and approximations [64]. Sources of uncertainty have been classified into three groups in the literature; namely, data sampling uncertainties, modeling, or simulation uncertainties and visualization uncertainties [50]. However, the three groups of uncertainty sources have a computational pipeline bias that can be stated as follows: uncertainty is a property of the relationship between data describing the world and the observed world and therefore accumulates as a phenomena is measured, data are propagated, and visualization is constructed. Looking at Table 2.1, a few of the uncertainty typologies can be better stated as follows: uncertainty is a property of the relationship between data and decision-maker. Specifically, uncertainty typologies such as completeness, credibility, subjectivity, and even inter-relatedness require knowledge of the decision-maker and decision to measure. For example, to measure the completeness of data, decision-makers need to formally define the decision, including expected decision strategy or decision criteria, for which the data will be used. Given that, there is a fourth source of uncertainty that needs to be considered. It should be a relationship between data and usage and can be named as decision uncertainties. Figure 2-1 shows the four sources of uncertainty and how they affect each other and is extended from [50].

Data and the relationship between data and usage both possess one or more types of uncertainty. Uncertainty is not only a property of data, but also a property of the decision-maker too. It is always a challenge to effectively visualize these different forms of uncertainty. Visualization researchers have often focused more on visual depictions of uncertainty than the various sources of uncertainty. However, some researchers have discussed the sources of uncertainty in their literature [31, 25, 44, 55, 65, 66, 67, 68]. Figure 2-2 illustrates the Haber and McNabb model, which

Figure 2-2: Haber and McNabb model depicting uncertainty visualization pipeline.

depicts data going through a pipeline structure [69]. The following sections briefly discuss the different sources of uncertainty and how they impact each other.

2.1.1.1 Data Sampling Uncertainty

The data gathering process can sometimes leave out a lot of information or gather more information than is required, and both the cases could lead to uncertainty in data [31]. Data collection is one of the prime causes of errors or unreliability in data [70]. Leaving out information in the data collection process can lead to gaps in values. Algorithms such as interpolation and extrapolation, which are generally used to fill in the missing values, could induce error and lead to uncertainty in data. Likewise, in the case of too much information, data scientists might get overloaded with the amount of information present. This could also lead to uncertainty in visualization due to the cluttered visualization resulting from data overload.

2.1.1.2 Modeling Uncertainty

Uncertainty in data can be predicted by components in computational models. The models are designed to estimate any variations in computations. For example, there could be potential errors in model inputs, or the model parameters could be wrong. Such cases lead to a range of predictions from different models. Such models may also give figures about the approximated inaccuracy through numerical values with their outputs. In a few cases, some models may give nominal or categorical predictions. Uncertainty can arise in mathematical or computational models and experimental results in several ways and hence, data modeling is a source of uncertainty [31, 30]. A few contexts through which uncertainty can enter a computational model are parameter uncertainty, algorithmic uncertainty, experimental uncertainty, and interpolation uncertainty to name a few.

2.1.1.3 Visualization Uncertainty

The visualization process itself can lead to uncertainty [70, 31]. The process influences the propagation and perception of uncertainty [30]. Processes like mapping data of one form, such as ordinal data, into another form, such as categorical data, can cause the data to lose fidelity and create uncertainty in the visualization. And mapping data from one type into another may not align with the users' mental models every time. Furthermore, users can sometimes find it really hard to discriminate between categorical sets when a rich ordinal data are mapped into a thousand colors. Additionally, it also depends on how the user perceives the given uncertainty visualization. Also, different individual abilities and levels of understanding in the intended audience can lead to different types of uncertainty in the visualization. In addition, data sampling and modeling uncertainties can lead to uncertainties in the resulting visualization. For example, too much data can lead to cluttered visualization and add to the uncertainties in the visualization. Likewise, computational models can give a range of nominal or categorical predictions and lead to variance in the visualization. So, the uncertainties resulting from data collection and design influence one another and contribute to uncertainties due to visualization.

2.1.1.4 Decision Uncertainty

Referring back to Table 2.1, most of the uncertainty typologies can be stated as follows: uncertainty is a property of the relationship between data and the decision-maker. Specifically, uncertainty typologies like completeness, credibility, subjectivity, and even interrelatedness require knowledge of both the decision-maker and the decision to measure. For example, to measure the completeness of data, decision-makers need to formally define the decision, including expected decision strategy or decision criteria, for which the data will be used. Given that, there is a fourth source of uncertainty that needs to be considered. It is a relationship between data and usage

Figure 2-3: Uncertainty visualization process integrates visualization of raw and uncertain data.

and can be termed as decision uncertainties.

2.1.2 Uncertainty Visualization Process

The concept of uncertainty put into visualization has also been described as a process where it is suggested that the visualization of normal data and unreliable data can be treated as separate processes integrated into one [71]. Figure 2-3 shows readers that the whole visualization process can be viewed as two different processes rolled into one. The raw data and uncertainty being a component of the raw data go through a transformation process to visualization on the screen. The visualization of the normal data and the uncertainty associated with it can be considered separate for a better understanding of the entire visualization process, as seen in Figure 2-3. The process basically tries to convey the flow of raw data and raw uncertainty in any visualization process and to show how data flows from acquisition to the final visualization. It is a general guideline for data flows in a visualization process and can be used to achieve any visualization task. Figure 2-3 illustrates and differentiates the two separate processes; data and uncertainty acquirement and the final picture.

2.2 Uncertainty Representation Approaches

There has been an extensive research on various approaches to uncertainty representation. One may conclude after an exhaustive literature survey that most of the approaches can be grouped into either of the two categories namely, quantification and visualization. Quantification approach mainly deals with modeling data uncertainty through various mathematical models. Visualization approach is the art of showing data uncertainty through data visualization. Figure 2-4 shows the two approaches to uncertainty representation as well as the various techniques under these two approaches. Many visualization designers have taken the route of a hybrid ap-

proach where they have tried to use the quantitative approaches in conjunction with one or more visualization approaches [54, 58, 72, 73, 74, 75]. For instance, in Figure 2-5, pseudo-coloring alpha value to encode the uncertainty levels was calculated based on the quantitative value of uncertainty at each point [73]. In this section, we first examine the relationship between the quantification and visualization approach and then present a brief study of the two approaches separately. This section ends with a summary table that outlines popular visualization techniques and considers their pros and cons.

Figure 2-4: Several approaches to uncertainty representation.

Figure 2-5: Uncertainty at each point was calculated and mapped to the pseudo-color alpha value to encode uncertainty information and distinguish from surface geometry information. Reproduced from [73].

2.2.1 Quantification Approach

The past few decades have seen the rise of various numerical models that have been used for identifying and quantifying uncertainty in data. The classical probability technique was the first one to be used to manage data uncertainty. It has since become one of the most applied techniques in the area of data uncertainty and its management. Later, other mathematical models came to the fore. Most notable are the Dempster-Shafer theory and the possibility theory. Apart from these models, numerous other numerical techniques like probabilistic logic, certainty factors, etc. were also introduced to tackle uncertainty [42].

The following sections will briefly discuss the hypotheses introduced to model the uncertain information: probability, possibility, and evidence theories. The three formal ideas are not very different from each other. They are, in fact, remarkably similar

to each other with a slight variation in the terms of their intended meanings and applications. Mostly, the real question is how to assign the degree of belief to various uncertain situations so that at least the most unambiguous ones can be separated. Belief is allocated to an occurring event on the basis of various factors. The formal theories discussed below assign belief to events using an assignment function. The assignment of belief depends on factors like the possibility of the event, subjective analysis by an individual, or statistics. Any belief is supposed to be a value between 0 and 1. The facts that are known to be false are assigned a value of 0, and 1 represents facts. Some theories like probability and evidence theory do not allow the amount of belief to be greater than 1. In other words, individuals are not supposed to believe in uncertain events more than they would have liked to believe in the case of certain events. Unlike probability and evidence theory, possibility theory does not have such limitations. So, an individual can believe in a set of alternative uncertain events [42]. The mathematical modeling of uncertainty can be used to quantify uncertainty and then put the quantified uncertainty to visualization. The below subsections shall discuss these formal theories in brief.

2.2.1.1 Probability Theory

In 1933, Andrey Nikolaevich Kolmogorov developed the probability measure, which is regarded as the classical probability theory. It has turned out to be the most popular model to tackle uncertainty. It has slowly developed into a more sophisticated model owing to extensive mathematical studies over the topic [42]. Kolmogorov introduced the concept of probability space. It is a set of three values:

$$(\Omega, F, P)$$

Ω and F here denote the total number of probable results of an arbitrary event and combinations of the total outcomes respectively. F is not void and $\Omega \in F$. P represents the probability of the occurrence of any outcomes corresponding to the event A . Probability can also be represented as follows:

$$0 \leq P(A) \leq 1 \text{ for } A \in F$$

2.2.1.2 Evidence Theory

Arthur Dempster and Glenn Shafer introduced the concept of Evidence theory to counter the restrictions of the classical probability theory. They wanted to get rid of the myth of completeness in classical probability theory [42]. To dispose of the concept of precision in classical probability theory, Dempster came up with the idea of indefinite probabilities in 1967. Such indistinct probabilities have multiple likelihood values instead of one value like probability theory. Each set of probability measures contains lower and upper probabilities. In 1976, Shafer called these lower and upper probabilities belief and plausibility. The combined efforts of Dempster and Shafer came to be widely recognized as Dempster-Shafer evidence theory (DSET).

2.2.1.3 Possibility Theory

[76] introduced a concept of possibility theory to build on the idea related to fuzzy sets [42]. Fuzzy sets could translate to a collection where values are a matter of degree rather than absolute numbers [77]. For example, a set of short people can be called a fuzzy set. Possibility function was defined by [77] as a membership function related to each fuzzy set. The possibility measure was the value of the least upper bound of the possibility function associated with fuzzy sets [50].

2.2.2 Visualization Approach

In addition to the above discussed numerical approaches to uncertainty representation, many researchers have also come up with a range of uncertainty visualization representation techniques to visualize various types of uncertainties associated with data. We are going to discuss some of the most popular cutting-edge uncertainty visualization techniques in this section. This section is further divided into two subsections to enable us to talk about the several uncertainty visualization techniques along with the recent cutting-edge research in uncertainty visualization in the areas of machine learning and big data.

2.2.2.1 Uncertainty Visualization Techniques

In this section, several popular state-of-the-art methods to visualize uncertainty will be discussed at length. These techniques attempt to integrate the visualization of error or uncertainty information along with the actual data, which earlier used to be ignored in data visualization.

Graphical Techniques Graphical methods are the most popular and traditional way of representing a large amount of data in a comprehensible manner. Graphical techniques such as box plots, scatter plots, and histograms not only help in representing data, but they also facilitate a better understanding of the data. Such techniques were first proposed by [78] to communicate features of a given data effectively. Box plots have been commonly used to display uncertainty in one-dimensional data [79, 80, 81, 82, 83, 78]. Box plots display the “minimum and maximum range values, the lower and upper quartiles and the median” [82]. Box plots can be modified to show various uncertainties in the data. One of the most common ways to display uncertainty is to make changes to the sides of the box plots to show density information [84]. There are many other variants of the box plots such as vase plot

[84], violin plot [85], box-percentile plot [86, 87], dot plots [88, 89], and sectioned density plots [90]. The many variants of box plots can be seen in Figure 2-6. Figure 2-7 demonstrates a 2-D box-plot extension where mean is visualized by the lowest flat surface and the standard deviation is visualized by the distortion seen. The difference between the quartiles is represented by the use of color. Furthermore, the variance between mean and median is visualized by the size of the upward bars, which have colors in sync with the base surface, which itself represents mean as discussed earlier.

Figure 2-6: Different types of box plots depicting error information. Reproduced from [50].

Glyphs Various frameworks, for instance, size, shape, color, and orientation as well as location, could be used to describe data in visualization using symbols known as glyphs. Since glyphs are of multivariate nature, they can be used to show uncertainty. The multivariate characteristics of glyphs were used in one work to show the distribution of three features in a data set [92]. Conical glyphs have been used where the radius is used to depict uncertain information [93]. Sometimes, attributes in glyphs can be modified to express unreliable information. In one such approach, an algorithm called the procedure generation algorithm was used to modify the properties of the glyphs already there in the visualization [58]. This work mainly emphasized the distortion of glyphs to visualize uncertainty and error. Sharp glyphs showed the area of low uncertainty with decreasing sharpness, hinting at increasing uncertainty.

Figure 2-7: 2-D box-plot extension: Mean is visualized by the lowest flat surface and the standard deviation is visualized by the distortion seen. The difference between the quartiles is represented by the use of color. Furthermore, the variance between mean and median is visualized by the size of the upward bars, which have colors in sync with the base surface which itself represents mean. Reproduced from [91].

Likewise, contours can also be used to depict unreliability [94, 62]. They can also be modified as glyphs to express information with errors [95, 96].

In many cases, glyphs are particularly used to visualize only uncertainty information in a dataset because not many data can be visualized using glyphs. An example where glyphs are only used to display unreliable information is the UISURF system [97]. Glyphs are used to denote magnitude and direction in a scene and can be used to add uncertainty in visualization. For example, glyphs can be used to show a hurricane on a map. Arrow glyphs, which represent both magnitude and direction, can be used for such purposes. Glyphs show information through their shape and color. Many applications make use of glyphs to depict uncertainty. Some are flow visualization, vector visualization, interpolation, and radiosity. Various kinds of glyph representations, such as “line, arrow, and ellipsoidal glyphs,” have been used to display unreliability in flow visualization, vector visualization, interpolation, radiosity,

and so on [98, 99, 100, 101, 102, 103, 70, 104, 105]. Since so many applications use glyphs to show uncertainty and glyphs are efficient to depict more than one piece of information at one time, they can very easily be extended to other applications [31]. An application of glyphs in depicting uncertainty is illustrated in Figure 2-8. In Figure 2-8, the magnitude, direction, and length of glyphs represent uncertainty in vector fields. A normal arrow glyph without any uncertainty information is shown in Figure 2-9, which can be compared with uncertainty glyphs depicted in Figure 2-8.

Figure 2-8: Magnitude, direction and length in glyphs depicting uncertainty. Reproduced from [70].

Geometry Many applications can visualize uncertainty with the inclusion of geometry to display. Using glyphs is also a method to add geometry; however, it is used to represent uncertainty discretely. When there is a requirement to display uncertain information continuously, it is more apt to use geometry in the visualized picture. There are a variety of techniques to add geometry to a rendered scene. Some of the

Figure 2-9: Arrow glyphs without uncertain information. Reproduced from [70].

prominent techniques are contour lines, isosurfaces, etc. Error in a scene can also be represented by modifying the existing geometry by distortion, scaling or rotation [31].

Attributes According to [31], uncertainty in a scene can be visualized by changing attributes such as the control of shading and coloring of geometry in the rendered scene. Various parameters can be mapped to unreliability with the control of color and shading.

Animation Animation is another technique that can be used to map unpredictability in information [31]. Confidence in given information can be mapped to different variables, including speed, blinking, motion, range, blur, duration, etc., to show the unreliability to the users [71]. The range of movement in different frames of animation can express a lack of certainty [106]. Since there are multiple parameters in animation to which uncertainty can be mapped, it is a powerful, innate, and unambiguous

method to display uncertainty to the end user without cluttering the display.

Probability Density Functions Quite a few methodologies are available today to display Probability Density Functions (PDFs) with spatial positions. Almost all of these methodologies focus on reducing the amount of data to investigate and display PDFs. To filter down the data, clustering techniques have been used, which in turn have also helped in determining features such as outliers in the data [107]. Multi-dimensional, time-varying, multi-variate PDFs mapped to 2-D or 3-D have also been shown by the use of Volume rendering and streamlines [108]. Other methods have also been used by researchers to show spatially varying distributions. In one of the works, the researchers investigated NASA satellite images and LIDAR datasets and mean of the data was encoded as a 2-D color map along with the use of standard deviation as a displacement value [109]. This work was essentially a case study on the specific data and similar work was carried out again by [110] in another paper.

A few other approaches have also been deployed to show spatially varying data. For example, slicing approach was used to show the distribution data and mean of the distribution functions was encoded onto a color mapped plane. Cutting surfaces near the boundaries allowed for the analysis of distribution data [91]. Sometimes, histograms are used to depict the density of the PDFs and color mapped spatial surfaces are used to plot the PDFs.

Visual Variables There are various other visualization techniques that can be employed to encode uncertainty. Various visual variables such as color, hue, brightness and saturation are commonly used to visualize uncertainty. Figure 2-10 illustrates different types of visual variables that can be used to indicate a lack of certainty. One of the techniques involves the use of color gradient. Color progression, or color gradient, is an effective way of showing the ambiguous region in a visualization. Figure 2-11 shows the area of uncertainty using color variation in a display.

Figure 2-10: The visual variables displaying uncertainty. Reproduced from [26].

In Figure 2-11, the solid orange line represents certain data. It is bounded by the progression of colors, which denote the confidence intervals of the data set. The lighter it gets, the more uncertainty it represents. The areas of lighter shade represent higher error or unreliability, and darker areas represent information with more confidence in them. Another technique that can be used to show uncertainty in a data visualization is noise-like pattern in a line curve. The noise represents the lack of certainty and the amount of error in the values. The use of such pattern in visualization is demonstrated in Figure 2-12.

2.2.2.2 Recent Advancements

Machine learning and big data have posed new challenges to uncertainty visualization due to the huge amount of data they process and generate. Any visualization intends to present a huge amount of data in a user-friendly and comprehensible manner; however, most of the visualization tends to ignore the uncertainties associated

Figure 2-11: Use of color gradient represents levels of uncertainty.

with the huge data [111]. In this section, we present a few instances of cutting-edge research that has taken place over the past five years in the area of machine learning and big data with respect to uncertainty visualization.

Uncertainty Visualization in Big Data Lately, a lot of research is going into visualizing uncertainties in big data. Some researchers have proposed uncertainty aware visual analytics frameworks in big data. One such notable work is the proposal of a framework for analyzing uncertainty in big data [72], which was inspired from an earlier work [112]. Karami designed a prototype for potent uncertainty visualization of KDD-CUP'99 traffic data [72]. The prototype was developed in MATLAB, and the uncertain input data was fed into the system, which was then visualized. Uncertainty was visualized by mapping the degree of uncertain information to the radius of nodes and the uncertainty levels to the color of the nodes. The developed prototype can be seen in Figure 2-13. The blue nodes show normal traffic, and the red nodes represent

Figure 2-12: Noise in line graph denotes uncertainty.

attack traffic. In the figure, the impurity of the color representation suggests the level of uncertainty. For instance, a full uncertainty of 100% is visualized by color at value 0.5 in the color bar. Likewise, the pure blue and red color indicate absolutely certain information. The uncertainty regions are represented by mapping color to the value of the amount of the uncertainty in the data.

Figure 2-13: Size and color of nodes represent uncertainty in big data. Reproduced from [72].

Tree maps are one of the popular methods to visualize hierarchical data. Most of the real-world data are hierarchical. Hence, representing hierarchical data in an effective way is quite important. Many approaches have been taken to represent such kind of data over the years [113]. A considerable amount of research has gone into this area, and it has matured quite a lot from earlier representations of treemaps. Conventional forms of treemaps did not have the option of adding additional information

to accommodate unreliable data [114]. In contrast to traditional treemaps, circular treemaps suffered from the problem of wastage of too much space [115]. Other traditional approaches to treemaps such as Voronoi treemaps [116] and squarified treemaps [117] were used for hierarchical data representation in a top-down fashion. However, they lacked feasibility to add extra variables to display uncertainty. Squarified treemaps are shown in Figure 2-14. A few researchers have also made use of a treemap layout algorithm for the display of hierarchy in data, but this also lacked scalability to encode uncertain data [118]. [119] described various ways to represent hierarchy in data via their survey.

Figure 2-14: Squarified Treemaps. Reproduced from [117].

[120] came out with an innovative approach to visualize hierarchical data laced with uncertainty using bubble treemaps. In this work, they made use of extra space to add more visual variables to visualize unreliability in the data. The authors tried to combine the hierarchical data along with the uncertainty in data in a single diagram. They also proved the reliability of their novel approach with the help of distinct cases - one of them being an example of a study on consumer spending. The approach of their work is unique, as it tried to use the display space effectively, introduced new

variables to encode uncertain data along with the other information, and described the relationship of uncertainty models with the hierarchical data.

Figure 2-15: Consumer expenditure survey visualization using Bubble Treemaps indicating error and uncertainty through thickness of the contours and blur effect. Reproduced from [120].

In Figure 2-15, the authors have tried to visualize the U.S. consumer expenditure survey data using the concept of bubble treemaps. The nodes and leaf sizes in the treemap are proportional to each item's value, and the contours' thickness is used to depict the model error. Furthermore, uncertainty in the data are portrayed through blur in the contours. The data categories represented by cyan and yellow have higher error and uncertainty and are consequently illustrated with a more intense blur.

Uncertainty visualization in Machine Learning Machine Learning (ML) is currently gaining momentum and being applied to a vast spectrum of data science, including data mining, text mining, human-computer interaction, data visualization, and computer graphics. Despite ML's application in many areas, most of the data scientists or end users think of ML models as black box and are unaware of how and

why they actually work [121, 122, 123]. Therefore, there is a call for systems that can help users comprehend the inner working mechanisms of ML models in a better way - and that's where visual analytics systems can play a great role.

Current research trends point to the direction of integration of ML, predictive models, regression models and visualization techniques to boost the illustration and comprehension of uncertainty in classification, prediction models or regression models. Figure 2-16 depicts predictions made about the occupation of individuals in a work, which attempts to visualize uncertainty in predictive models [124]. There are several classes of occupation predicted using input values, including age, gender, race, nationality, and income. It can be seen in Figure 2-16 that predictions are concentrated at certain places, which are indicated by localization of colors. The figure also suggests that some of the predictions have higher uncertainty or error, as the pie glyphs or speckle glyphs do not represent the actual colors of the main classes of occupation. It can also be inferred from the figure that the ML model has high error and less confidence.

As discussed previously in this section, visualization is being used to create explainable systems that can help ML experts to understand the know-how of ML models. One such example is illustrated in Figure 2-17 where Panorama Visualization can be seen in a data analytics system known as *TopicPanorama* [125]. The figure displays a visualization of the topics corresponding to respective software firms where uncommon topics related to distinct computer giants are visualized in contrasting colors and undistinguished topics are represented by the use of pie charts. The figure also shows an uncertainty glyph, which is used here to examine uncertain matches in matching results. The angle between the sliders in the uncertainty glyph is used to represent the degree of uncertainty. As seen in the figure, the uncertain matches have uncertainty glyphs and are represented by **A** and **B**. In contrast, the correct matching result is shown by **C** and **D** in the figure.

Figure 2-16: Pie glyphs (top) and speckle glyphs (bottom) representing uncertainty in predictions made by Machine Learning models. Legends are shown in the right table. Reproduced from [124].

2.2.3 Quantification to Visualization

In this era of machine learning and big data, there is a massive amount of work being performed to understand uncertainties or unknowns in data analytics. Because of this, visualization designers are trying to express the unknowns in different ways, using visualization as a tool after modeling and quantifying the uncertainties [54, 98]. Most of the uncertainty information can be expressed via probability density functions (PDFs); however, it is challenging to visualize the PDFs using the existing visualization approaches or the visualization is mostly limited to one-dimensional or

Figure 2-17: A visual analytics system called TopicPanorama (left). Dotted section illustrates an uncertainty glyph (middle). **A** and **B** represent incorrect matching, **C** and **D** show correct matching in matching result. Reproduced from [126].

two-dimensional displays. Because of this, assumptions are usually made about the data such as aggregating the data to a unique value, for example, standard deviation, to reduce the size or dimension of data. These single values can then be easily visualized without any visual clutter.

Another research study used the PDF as a building block and standard deviation for each node to obtain a distribution and then used them as inputs to visualize bubble treemaps for uncertainty [120]. The authors obtained a distribution for each node at the leaf level and then computed uncertainty to gauge the characteristics of the model toward the root level. Later, they drew a treemap layout, leaf circles and contours to encode uncertainty values. Figure 2-18 demonstrates their novel concept of bubble treemaps which is used to visualize hierarchical data and the uncertainty within it in the form of contours and blur using PDF as a building block.

There are several approaches to using quantitative uncertainty information in final visualization results. Some researchers have attempted to quantify uncertainty in

Figure 2-18: Bubble Treemaps demonstrating how quantification can be used as a building block to visualization. Reproduced from [120].

terms of cumulative density functions (CDFs) and quantile dotplots to estimate more accurate probability intervals and later visualized them to improve decision-making of end users in a transit system [127]. Another notable work that demonstrates relationship between uncertainty quantification and final visualization is probabilistic graph layout for the visualization of an uncertain network [54]. They computed a probabilistic graph of an uncertain network, then applied force-directed layout and visualized the uncertain network in the form of a probabilistic graph layout using visualization approaches such as node and edge splatting, edge bundling, clustering, node coloring and labeling, as illustrated in Figure 2-19.

Visualization designers have employed uncertainty quantification mapping to visualization tools. [98] tried to estimate and visualize positional uncertainty of large-scale astronomical data by taking into account square root of total separation between astronomical objects and earth, and also, square root of variation of parallax. Figure 2-20 demonstrates their work of visualizing positional uncertainty through the use

Figure 2-19: Probabilistic graph layout of an uncertain network achieved using probabilistic graph and force-directed layout. Reproduced from [54].

of visual cues (called the unified color-coding scheme) by computing the errors from variance values. There have been several other notable works [72, 58, 74, 75] that clearly demonstrate the relationship of uncertainty quantification with the visualization techniques as mentioned in section 2.2.

Figure 2-20: Positional uncertainty visualized from variance values. Reproduced from [98].

We can conclude from the above discussion that uncertainty quantification is used

in several visualization approaches. It can be inferred that quantitative uncertainty or error values are passed as input to a visualization tool, which in turn, visualizes the unknowns through several popular visualization techniques such as visual cues like color map, blur, fuzziness, hue, animation, etc. Figure 2-21 illustrates a general visualization system, which takes numerical values of uncertainty as input and produces a final visualization.

A detailed summary of the various uncertainty visualization techniques along with their advantages and disadvantages is presented in Table 2.2. The purpose of the tabular representation is to enable researchers to use it as a quick reference for popular uncertainty visualization methods.

Figure 2-21: Uncertainty quantification to visualization: Diagram illustrates the relationship between quantification and visualization.

Table 2.2: Summary of the various uncertainty visualization techniques.

Technique	Data Type	Merits	Drawbacks	Related Work
Bubble Treemaps	Hierarchical	Use of display space effectively, new variables to encode uncertain data, uncertainty model and data relation	Incompatible with dynamically changing or interactive data	[120]
Size, color variations of nodes	Categorical	Intuitive visualization, uncertainty can be easily spotted by color values and size of nodes	Lacked user evaluations, sub clusters did not reveal details	[72]
Pie chart glyphs, Speckle chart glyphs	Categorical	Pie or speckle chart glyph shapes fare better for understanding when several classes are predicted	No user study to support the hypothesis, early stages of research	[124]

Technique	Data Type	Merits	Drawbacks	Related Work
Probabilistic graph layout, node and edge splatting, edge bundling, clustering, node coloring and labeling	Categorical	Good for visualizing network uncertainty using graph visualization, benefits from the generality of the force-directed methods	Suffers from layout stability, layout ambiguity, visual distinction of nodes and computational scalability	[54]
Uncertainty glyph with sliders	Categorical	Angle between sliders represented uncertainty, easy to distinguish uncertain matches, consistent graph matching results	Visual clutter, limited screen space, not suitable for more than 4 graph matching results	[125]

Technique	Data Type	Merits	Drawbacks	Related Work
Unified color coding scheme, color map, error bars	Categorical	Contributed with well-defined user interface tools and visual cues to explore large-scale astrophysical data uncertainty, properly visualized all the data elements on the visual display, effective uncertainty visualization, enhanced data understanding by efficient and interactive uncertainty representations	Other large bodies of data were not incorporated	[98]

Technique	Data Type	Merits	Drawbacks	Related Work
Procedurally-generated annotations	Categorical	Density of amplitude modulation in annotation lines to mark the uncertainty in each grid, uncertainty is presented without distracting the viewers	Not extended for 3D space	[58]
Box Plots	Continuous	Efficient to present variance & uncertainty through quartiles & outliers	Cannot be used for 2D data	[79]
Static comparison, toggling	Spatial	Web-based survey was conducted to evaluate results, both techniques improve the efficiency of decision-making	Different user interpretation of different uncertainty displays was not determined	[128]

Technique	Data Type	Merits	Drawbacks	Related Work
Error Bars, Ambiguation	Categorical	Advocated the use of two distinct techniques error bars and ambiguation for distinct degree of uncertainty and distinct form of uncertainty, avoided the misrepresentation of uncertainty, addressed the issue of sudden jumps in graphical display of data and uncertainty	May not be appealing to the users	[51]
Non-photorealistic rendering	Geometric	Brings out more info from the converted geometric design	Absence of color to encode information	[129]
Violin Plots	Continuous	Extension of Boxplot, encodes frequency of values into x-axis	Not fit for 2D data	[85]

Technique	Data Type	Merits	Drawbacks	Related Work
Hue, Texture	Categorical	Isosurface rendering of multiresolution data efficient, error is easily spotted using hue, texture allows color to be used for another variate	Depicting data quality of Direct Volume Rendering is not possible	[130]
Range-Bar Charts	Categorical	Efficient error representation	Not fit for 2D data	[80]
Vase Plots	Continuous	Extension of Boxplot, adds density of values to x-axis of each plot	Not fit for 2D data	[84]
Color saturation value	Categorical	Areas of high uncertainty can be easily spotted	—	[131]
Box-Percentile Plots	Continuous	Efficient error representation	Not fit for 2D data	[86]

Technique	Data Type	Merits	Drawbacks	Related Work
Parallel ordinates, Scatterplot Matrices, Star Glyphs	Co- Multivariate	Analyzed the advantages & disadvantages of visual variables, evaluated the effectiveness of the visual variables, data quality types e.g., record, dimension, data value were identified, approaches like mapping quality information to a new dimension and visual variables were proposed	Other methods of multivariate data were not explored, more user studies should have been carried out, other methods for visualizing multivariate data were not explored, other data attributes besides quality information could be used	[132]
Dot Plots	Categorical	User-friendly error representation	Not fit for 2D data	[88]

Technique	Data Type	Merits	Drawbacks	Related Work
Color Mapping, Geometry	Sparse	Color scheme to show error & unreliability of 3D models, geometry to show confidence level, can be integrated with other visualized objects	Method allows for variability up to a certain extent	[105]
Sectioned Density Plots	Categorical	Easy and efficient error representation	Not fit for 2D data	[90]
Rainbow color map	Nominal	Analyzed the disadvantages of rainbow color maps, concluded that they confuse the end user by obscuring most of the information	—	[133]
Glyphs	Multi-Variate	Showed the distribution of the features in a dataset	—	[92]

Technique	Data Type	Merits	Drawbacks	Related Work
Conical Glyphs	Multi-Variate	Radius of cone used as variable to encode uncertainty	——	[93]
Natural textures distortion	Categorical	Effective use of natural textures in multivariate visualization	Feasibility issues, use of color with texture was not implemented	[134]
Blur	Categorical	Blur specified the level of uncertainty	——	[135]
Texture designs having varying shapes, sizes, or orientations	Categorical	Model accurately displayed the main vector field, variable shapes, sizes and orientation revealed uncertainty along with magnitude and direction of underlying vector field	Extension to three dimensions not investigated, hybrid techniques were not explored, perceptual issues, user studies were not conducted	[136]

Technique	Data Type	Merits	Drawbacks	Related Work
Point-based primitives, Pseudo color-ing, Shading	Volume	Very effective in revealing surface uncertainty along with surface geometry, efficient in visualizing uncertainty without distracting the users, multi-dimensional dataset displayed effectively, Intuitive method of representing uncertainty, fast and interactive	Parameters like refractive index and specular coefficient were not added	[73, 74]
Pseudo-color, Noise, Texture	Volume	Uncertainty information integrated into the volume rendering, effectively showed location and extent of uncertainty	Derived data produced during volume rendering was not used to depict uncertainty information	[75]

Technique	Data Type	Merits	Drawbacks	Related Work
Retinal variables position, and value	variables e.g., size	Cartographic Intuitive good performance in map reading tasks	Such visual variables needed to be more refined for use in other areas than cartography	[137]
New called PlanningLines	glyph Plan-	Temporal Novel method to show temporal uncertainty, illustrated the use of PlanningLines in another domain project management apart from medical treatment planning, empirical study was conducted to test the efficacy of the novel glyph	—	[138]

Technique	Data Type	Merits	Drawbacks	Related Work
Probability Density Functions (PDFs)	Interval	Distribution was mapped onto a color mapped plane, slicing approach was used to show the spatially varying distribution data	Not suitable for other types of data	[109, 91, 110]

2.3 Evaluation of Techniques

While some work has been done on evaluating visualizations, not much work has been done specifically on evaluating uncertainty in visualizations. The absence of legitimate assessment of techniques is a possible reasoning. The dearth of assessment was particularly evident in traditional visualization domains. Nevertheless, the latest trends suggest that the scientists in this field are indeed concentrating on the assessment aspects of it. The evaluation methods can be broken down mainly into two major classes:

- Theoretical assessment based on Edward Tufte’s theories such as graphical excellence or graphical integrity [139, 140, 141].
- User assessments based on the study of the impact of uncertainty visualization techniques on them [142, 55, 143].

2.3.1 Theoretical Assessments

Tufte, who is a pioneer in the field of data visualization, proposed two popular theories for a good visualization, graphical excellence, and graphical integrity.

- Specific guidelines were proposed by Tufte to achieve graphical excellence. Some of them include presenting large amount of data in small space, avoiding distortion, encouraging comparison of the data and so on.
- Tufte also proposed a few guidelines to achieve graphical integrity such as clear labeling of the data, representing numbers proportionally to the numerical quantities, and matching the number of data dimension with the number of information.

Apart from these popular theories, Tufte also proposed “data-ink maximization principle,” which stated that most chunks of data must be visualized using the lowest

quantity of ink possible [139, 140, 141]. Other authors, such as Bertin and Chambers, also contributed to the theoretical evaluation of the techniques. The assessment was based on Bertin’s and Chamber’s analysis of the brain, eye, and picture interaction. Bertin’s perceptual theories suggested a categorization of visual variables in the form of (x, y) planes and evident spots above the surface such as color, size, shape, orientation, and value [144, 137]. Another set of perceptual theories were introduced by Chambers, who presented a general technique for plot construction by reducing clutter, removing the structure from the data, and labeling the data to avoid distortion [145].

2.3.2 User Studies

Many task-based user studies were carried out to evaluate uncertainty visualization techniques. In fact, user-based evaluations are the most popular type of assessments [142, 55, 143].

2.4 Chapter Summary

We have surveyed the cutting-edge approaches to uncertainty representation in this chapter. The concept of uncertainty and the various sources of uncertainty were discussed. A new source of uncertainty named decision uncertainties was proposed apart from the sources from several literature. The approaches were grouped into two categories - mathematical and visualization, to make it easier for readers to distinguish between different methodologies of expressing uncertainty. We looked at both theoretical approaches and empirical approaches to visualizing uncertainty. Several popular uncertainty visualization techniques were summarized in tabular form, as a quick reference guide for the new researchers in the field. Popular evaluation methodologies to assess reliability and unpredictability representation techniques were also

talked about in this review. Open problems and future research directions were discussed in detail toward the end of the paper. One of the goals of this survey was to put forward insight into the topic of uncertainty visualization today. The idea was to convey what has been accomplished so far and what has been overlooked. For this reason, the principle idea of uncertainty was presented, as it is comprehended from the research papers. The offered viewpoint gives an intensive comprehension of uncertainty and its results on the information and scientific visualization fields. It indicates what is conceivable and accessible today and additionally offers a creative forecast of what is to follow in the coming years.

Chapter 3

Flight Data Visualization and Analysis

This chapter discusses the next step in the research after the literature survey on uncertainty visualization which was done primarily to incorporate uncertainty visualization techniques in the final implementation. The procurement and visualization of flight data were performed to analyze and assess further steps in the investigation to design and develop a system to estimate and visualize flight corridors for multiple UAVs in an airspace. In this step, the goal is to find and analyze an appropriate flight data set that could be used to visualize and assess the air corridors of a multiple drone scenario.

3.1 Overview

As discussed earlier in Chapter 1, the main objective of our research is to work out an approach to estimate and visualize air corridors of multiple UAV flights in the airspace. To achieve the final goal, there was a need to search for an appropriate flight data set and a map-based visualization engine, which was capable of visualizing flight data set on 3-D world-class maps. This step is aimed at giving a detailed insight into

the steps we took to achieve our aforementioned objective of finding an appropriate data set for our work and whether they met our desired expectations.

This chapter describes the representation of aircrafts' flights in a web browser using 3-D globes visualization technology CesiumJS. The challenge was to find the flight data for the visualization. An extensive study was carried out to find the flight data. Some online websites such as ADS-B Exchange [146], OpenSky Network [147] and CesiumJS [148] have aircraft flight data available to the researchers. Air traffic receiver networks such as ADS-B Exchange [146] and OpenSky Network [147] gather air traffic unfiltered data continuously round the clock. They collect and store the raw aircraft data forever and make it available to the researchers. With more than 10 trillion ADS-B and Mode S messages collected from more than 1,000 sensors around the world, the OpenSky Network exhibits the largest air traffic surveillance data set of its kind. They continuously collect data from more than 1,000 sensors in all parts of the world. Owing to their round-the-clock data collecting abilities, they have accumulated trillions of automatic dependent surveillance-broadcast (ADS-B) and Mode S messages, and are one of the largest databases for aircraft surveillance raw data. An aircraft establishes its location and frequently transmits it, allowing it to be traced in ADS-B, which is a surveillance technology [149]. Mode S is a surveillance technology in which a distinct address is allotted to each aircraft, enabling it to be interrogated [150]. Nykl et al. worked on wake turbulence testing of a UAV flight data in their work [151]. In another work, the authors visualized UAV flight data on a visualization tool, which they developed to represent UAV flights [152]. We acquired data sets from a few sources: (1) ADS-B Exchange, (2) CesiumJS, and (3) a wake turbulence testing data set from Nykl et al. [146, 148, 151, 152].

Starting from data collected from multiple sources as mentioned earlier, the visualization was performed using 3-D globe-based visualization engine CesiumJS [153]. The visualization enables the users to experience the flight virtually and interact with

Figure 3-1: Block diagram of flight data visualization process.

the representation of the flight data. Users can take advantage of the immersive visualization experience provided by CesiumJS through its visual interface. The entire process from data acquisition and preprocessing to the final visualization with the help of visualization technologies can be seen in Figure 3-1.

The intent here is to not only analyze the visualization outcomes but also decide what kind of data would be the best fit for a multi-UAV system to estimate the flight corridors. The representation of flights' data picked up from multiple sources as discussed previously can help us assess different data and enable us to opt for the right data for our work.

3.2 Dataset Description

The data set needed for the work was primarily a flight data set. The challenge was to find appropriate flight data that could be used for the visualization and assessment of air corridors for a group of aircraft. We started off with single flight data sets so that we could visualize their paths and flight corridors and then build from there. In the very beginning, we downloaded a single flight data set from CesiumJS forum [148], which was basically a hang-gliding flight log data. The data set had columns such as latitude, longitude, and altitude, and had about close to 2,000 rows. Since this data set was small and had only about 2,000 positions, we looked for bigger data sets with more position data. We acquired wake turbulence and testing single flight data set from Nykl et al. for their work performed at Ohio University (OU) in wake turbulence testing [151, 152]. The wake turbulence testing log file had about half a million data rows and had data attributes such as longitude, latitude, and altitude. We were mainly concerned with the position data entries such as latitude, longitude and GPS altitude.

For the purpose of our main objective, we required multiple flight data. However,

this data was from a single flight data set and could not support the objective, as we were trying to estimate the air corridors for a multiple flight scenario. So, multiple aircraft data sets were downloaded from ADS-B Exchange [146] and later put to visualization. The data size was huge; each data file had about 60 million data points. The data file format was JavaScript Object Notation (JSON). Each data point acts as an object in this format. Each object had a unique flight ID and details such as full flight trails, short flight trails, location coordinates, and altitude. The JSON data were then converted into MATLAB-friendly CSV format. The issue with this approach was that the multiple flight data sets had flight data from different airport locations, and the flight positions were distant and scattered. The kind of data required for the work must belong to a small airspace with a number of flights from a given source to a destination. For this reason, we handcrafted data in a small airspace using geojson.io application [154] and collected a set of latitudes and longitudes based on the paths drawn. The data were created assuming multiple UAVs flying in a small airspace at different times from a given source to a destination over the University of Toledo, Toledo, Ohio campus.

3.3 Development Environment

This section discusses the set of programming technologies and software used to accomplish the flight data visualization in an immersive 3-D format. To begin, a brief description of the technology stack used to perform the visualization is provided, and then each technology is explained in detail in subsequent subsections.

Figure 3-2: A snapshot of the geojson.io application showing how the data is collected in JSON format.

3.3.1 Technology Stack

The tools/libraries used to perform the experiments include geojson.io, CesiumJS, NodeJS, and web technologies such as HTML5, CSS3, and JavaScript. The following subsections discuss these tools and technologies in detail.

3.3.1.1 GeoJSON (geojson.io)

GeoJSON, which is based on JavaScript Object Notation is popularly known as JSON, is a format used for the representation of geographical features such as GPS locations, streets, countries, and routes [155]. geojson.io is a web application that supports GeoJSON rendering and editing in a web browser [154]. It was used to create UAV positions in airspace to handcraft our scenario and data. The GPS coordinates were collected in a JSON format. Figure 3-2 demonstrates the use of geojson.io application and how the data are collected in JSON format.

3.3.1.2 CesiumJS

CesiumJS is an open-source JavaScript library for state-of-the-art world-class 3-D globes and maps [153]. It is used to create 3-D shapes onto world-class maps for static and time dynamic contents with great performance and visualization quality. It is a geospatial 3-D mapping platform for creating 3-D spatial shapes. It is a web-based application for visualizing 3-D globes and 2-D maps in a web browser. It has powerful capabilities such as core, which performs mathematical operations, scene, which provides globes and map constructs, and renderer, which is an abstraction over WebGL. It includes user input features such as pan, zoom, rotate, map selection, camera, and location. It also allows users to select from a range of views: 2-D, 3-D, and Columbus. It supports dynamic data visualization and has custom application programming interfaces (APIs) to draw and visualize flight paths and air corridors.

3.3.1.3 NodeJS

Web applications require web servers, and CesiumJS is no different than other web applications. We installed **node.js** [156] and a package manager called **npm** [157] to run the node server to power our CesiumJS web application to render the 3-D contents onto our web application.

3.3.1.4 HTML5, CSS3, and JavaScript

We leveraged web technologies such as HTML5, CSS3, and JavaScript to style our web application and code the program logic for the visualization of different flight data that we acquired earlier. HTML5 and CSS3 were mainly used to style the web contents, and JavaScript was used to implement the flight path and corridor representation. JavaScript is a very efficient programming language that can leverage open-source JavaScript libraries such as CesiumJS and NodeJS.

3.4 Results

This section examines the results of the data-preprocessing step, showcases all the visualization results, and analyzes the results obtained from the perspective of the main objective of the work.

3.4.1 Data Preprocessing

Prior to visualization, data preprocessing was performed on data sets such as wake turbulence testing, flight log, and ADS-B Exchange flight data discussed earlier in Section 3.2. The hang-gliding flight data obtained from Cesium [148] was clean and did not require any data cleaning. The single flight data set obtained from Nykl et al. [151] and ADS-B Exchange [146] were huge and required data preprocessing. These data sets had more attributes than were required, so the resampling was done

Figure 3-3: Flowchart of the data preprocessing stage.

in MATLAB, and attributes such as longitude, latitude, and altitude were picked. The data sets also had redundant entries because data points were recorded every millisecond or second, so the resampling was performed to pick every n th row so that it would be feasible to visualize such huge data sets. The data sets containing half a million data points and 60 million data points were reduced to a size of about 5,000 data points. Algorithm 1 illustrates the data resampling technique employed in MATLAB to preprocess the flight data sets. The same algorithm is also demonstrated in Figure 3-3.

Algorithm 1: Pseudo-Code for Data Preprocessing

Input: Flight Dataset D
Output: Processed Dataset P
Step 1: Read flight log file
 $A = readFile()$
Step 2: select latitude, longitude and altitude from data
 $M = pickLocationAttributes()$
Step 3: select every n th row of the data
 $N = selectEveryNthRow()$
Step 4: Save processed data in csv format
 $csvwrite()$
return P

3.4.2 Visualization

The next step was to find an appropriate visualization engine after the data cleaning was done in MATLAB. CesiumJS graphics rendering engine was chosen as the best candidate for our visualization due to its capability to support spatial data and map-based visualization [153]. Web technologies such as HTML5, CSS3, and JavaScript were chosen as they could make full use of CesiumJS, which is an open-source JavaScript library.

The single aircraft data obtained from Nykl et al. [151] was first parsed, cleaned, and resampled in MATLAB to make it feasible for visualization. Afterward, this

Figure 3-4: Initial short trail of the single flight path (west view).

Figure 3-5: Initial short trail of the single flight path (top view).

Figure 3-6: Flight corridor visualization of the initial short trail of the single flight path (top view).

Figure 3-7: Full trail of the single flight path.

Figure 3-8: Air corridor visualization of the full trail of the single flight path.

parsed data were used to visualize the flight route and its air corridor. The single flight route visualization is shown in Figure 3-4, where an initial short trail of the flight data are only visualized. Figure 3-5 shows the top view of the short trail of the single flight data. After the flight path was visualized, the next step was to visualize the air corridor of the same flight path. The air corridor of the short trail of a single flight path is visualized in Figure 3-6. Likewise, we visualized the path and air corridor of the full trail of the same data. Figure 3-7 illustrates the full flight path of the single aircraft data obtained from [151]. The flight corridor of the same data was then visualized in Figure 3-8.

Since multiple flight data were essential to do the flight corridor analysis, multiple aircraft data were downloaded from ADS-B Exchange [146]. The data size was huge - each data file had about 60 million data points. The data file format was JavaScript Object Notation (JSON). Each data point acts as an object in this for-

Figure 3-9: ADS-B Exchange multiple flight dataset visualization with red squares depicting aircrafts at two distant locations.

mat. Each object had a unique flight ID and details such as full flight trails, short flight trails, location coordinates, and altitude. The JSON data was then converted into MATLAB-friendly CSV format. However, it did not give the desired visualization results as seen in Figure 3-9, as the aircrafts and their routes were scattered across the globe. The distant aircraft locations are illustrated by red squares in the same figure. Figure 3-10 emphasizes the distant locations of the aircrafts by depicting a pink path between the two locations. We needed the data of aircrafts that were confined to a much smaller airspace.

To overcome this challenge, two approaches were explored. First, the single flight data acquired from [151] were divided into multiple aircraft data assuming each division represents a different aircraft. This data were then resampled and cleaned in MATLAB and rendered in Cesium for flight path visualization. The visualization results are shown in Figure 3-11, where each color represents a separate path. Fig-

Figure 3-10: ADS-B Exchange multiple flight dataset visualization with a flight path in pink color showing the two distant locations.

ures 3-12, 3-13, 3-14, and 3-15 demonstrate different views, such as close-up view and south view, of the same data. The issue with this approach was that the data belonged to the same aircraft and hence it would not have been apt to base our analysis on such data.

Second, we created our own data in a small airspace using geojson.io application [154] and collected a set of latitudes and longitudes based on the paths drawn. The data were created assuming multiple UAVs flying in a small airspace over the University of Toledo. The data were then visualized in CesiumJS. Several flight paths were assumed and constructed, and the latitudes and longitudes of each point in every path were collected in the form of JSON format via the geojson.io application. These paths were then visualized at different altitudes in CesiumJS. The multiple visualization results with their various orientations can be seen in Figures 3-16, 3-17, 3-18, 3-19, 3-20, 3-21, 3-22, 3-23, 3-24, 3-25, and 3-26. The air corridors of multiple paths were

Figure 3-11: Single flight path data acquired from [151] split into multiple flight path data (side view).

Figure 3-12: Single flight path data acquired from [151] split into multiple flight path data (Close-up view from south-west).

Figure 3-13: Single flight path data acquired from [151] split into multiple flight path data (south view).

Figure 3-14: Single flight path data acquired from [151] split into multiple flight path data (top view).

Figure 3-15: Single flight path data acquired from [151] split into multiple flight path data (west view).

Figure 3-16: Visualization of our own flight data: flights at different altitude (top view).

Figure 3-17: Handcrafted data visualization: flights at different altitude (side view).

Figure 3-18: Handcrafted data visualization: altitude variation in flight routes (side view).

Figure 3-19: Handcrafted data visualization: altitude variation in flight routes (south-west side view).

Figure 3-20: Visualization of our own flight data: flights at different altitude (side view).

Figure 3-21: Visualization of our own flight data: flights at different altitude (side view).

then visualized using CesiumJS. The multiple flight paths at different altitudes and their corresponding air corridors are presented in Figures 3-22 and 3-27, respectively. This approach showed promise, as it gave visualization results that were limited to a small airspace. It was inferred from the various visualization results discussed above in this section that a multiple UAV flight scenario data can be created according to the requirements of the work and can be used for the estimation, and visualization of the flight corridors.

3.4.3 Analysis

From the results so far, we have gathered that the best approach to go forward in the estimation of flight corridors for multiple UAVs is creating our own UAV flight data set. Our requirement is to obtain a flight data where multiple aircrafts are flying in overlapping paths and corridors. Data sets obtained from various sources such as

Figure 3-22: Multiple flight paths visualization using our own created flight data (side view).

Figure 3-23: Multiple flight paths visualization using our own created flight data (east view).

Figure 3-24: Multiple flight paths visualization using our own created flight data (side view after being rotated 180 degrees clockwise).

Figure 3-25: Multiple flight paths visualization using our own created flight data (top-most View).

Figure 3-26: Multiple flight paths visualization using our own created flight data (top View).

Figure 3-27: Multiple Air corridors visualization using our own created flight data.

ADS-B Exchange [146] and Nykl et al. [151, 152] do not give us the desired results as discussed earlier. Therefore, the best possible way to go forward is to handcraft our own multiple UAV flight data and use it for the estimation and visualization of the air corridors.

3.5 Chapter Summary

This chapter presented the approach taken to meet the final objective after the literature acquisition on uncertainty visualization. The research steps such as acquiring the right flight data for our work, data preprocessing and the visualization of the data was discussed at length. The visualization results were presented and explained in detail. From the detailed discussions and the analysis of the flight data visualization results, we have concluded that the best approach to flight corridor estimation in an airspace is to create our own multiple flight data and utilize them for further research on air corridor estimation and visualization.

Chapter 4

Multi-UAV Air Corridor

Estimation and Visualization

UAVs are gaining popularity like never before. Due to the increasing popularity of drones, we could see several different types of UAVs flying in several airspaces engaging in activities such as monitoring, surveying, photography, and military combat in the future. A fleet of UAVs flying over a small area could be parts of next-generation multi-UAV systems. Such a scenario could lead to chaos if there is not a proper system in place. Flight air corridors can help drones navigate safely in a small airspace. To fly safely, avoiding any collisions or mishaps, there is a need for us to design and develop next-generation multi-UAV systems that can create air corridors on the spot for multiple UAVs to fly through them without any accidents.

4.1 Overview

When multiple UAVs are flying in a constrained airspace, there are possibilities of UAVs flying in overlapping air corridors or outside their allotted flight corridors. For instance, multiple UAVs designed to fly from a source to a destination at different times are meant to follow the exact allotted path; however, due to on-the-go path

Figure 4-1: Overview of the research strategy.

planning and deflections owing to external factors like wind and enemy, their actual traveled paths could vary. The objective here is to estimate and visualize reference air corridor from different flight corridors, visualize flight paths taken by multiple UAVs, and to find out whether these UAVs are flying in their allotted air corridors. The overview of the strategy to air corridor estimation and visualization system can be seen in Figure 4-1.

These next-generation multi-UAV systems will create air corridors on the spot to help potentially large groups of UAVs navigate safely. For example, a multi-UAV system might get set up to do persistent monitoring of a college campus over a weekend when a lot of parties, and potential bad behavior, are expected. Campus security would pick the observation locations and times, and the multi-UAV planner would assign UAVs to air corridors and observation points. Because the observation sites are picked by security, the multi-UAV system creates new corridors for the weekend's observation work. Once begun, the UAVs would constantly be going out, doing their

observations, and flying back to be re-charged. The UAVs have GPS, which is fairly but not perfectly precise. Terrain maps are easily available for the college campus, which would assist in planning their flights.

Multi-UAV systems, like all aviation systems, can make mistakes or have accidents happen. Therefore, technical monitoring technology is needed. This monitoring technology will take a feed of GPS positions from the UAVs as they fly and make sure that flight safety rules are applied correctly. One set of flight safety rules tests whether the UAVs have been provided with safe air corridors in which to fly and whether the UAVs are correctly staying within the corridors.

To be a good test, the monitoring system can be given the UAV positions and terrain maps as inputs; however, it cannot be given the multi-UAV system-generated air corridors. The monitoring system should, initially:

- estimate the air corridors based on the actual UAV positions, and
- visualize the estimated air corridors and UAV positions

To support this research, there is another step to simulate or obtain a set of UAV positions that will support the above two steps. The purpose of the research is to work out an approach to this and evaluate its strengths and weaknesses.

4.2 Proposed Methodology

In this section, we propose a methodology for the air corridor estimation and visualization system for multi-UAV flights. Initially, it was assumed that the multiple aircraft data procured from sources such as ADS-B Exchange [146] could be parsed effectively and used to visualize and assess multiple flight paths and air corridors, as discussed previously in Chapter 3. However, the results of the visualization of such data suggested that the earlier assumptions were weak and the hypotheses needed to

be reformulated. After the analysis, the hypotheses have gradually changed to the following ones:

- Creating own scenarios and thereby generating data from them can help to visualize multiple flight paths and air corridors more effectively in a small airspace.
- Own rules will be created to generate a list of scenarios where multiple UAVs are flying in a small airspace.
- The scenarios will be used to generate data sets which will be used later for visualization and assessment of the multiple paths and air corridors.

The above hypotheses present an overall picture of our proposed algorithm, which we discuss in the following subsection.

4.2.1 Algorithm

In this section, we are going to discuss our proposed algorithm. We assume that the UAVs' use of the corridors is overlapping, meaning that at least two UAVs follow each corridor. It is also assumed that our system has parameters that define a default height and width of a corridor. Our algorithm mainly relies on the averaging of estimated paths and corridors. The proposed approach is discussed step by step in more detail below.

- Let us assume here that there are two UAVs, UAV1 and UAV2, for the sake of simplicity. We start with two sets of overlapping position tracks, as shown in Figure 4-2 and Figure 4-3, for the respective UAVs.
- For a set of UAV paths as illustrated in Figure 4-2 and Figure 4-3, we find closest UAV 1 and UAV 2 positions and average them to generate a reference path. The approach pursued here is that we follow brown positions and find

Figure 4-2: UAV1 positions over time.

Figure 4-3: UAV2 positions over time.

Figure 4-4: Computed reference corridor from UAV1 and UAV2 positions.

the closest blue positions and then average the closest positions to calculate a reference position. This method is clearly demonstrated in Figure 4-4.

- Furthermore, we compute a corridor slice for each position on the reference path as seen in Figure 4-5. We assume that the position is perfectly in the center of the air corridor for each track and each UAV position. We compute and store the coordinates of the default sized corridor slice. Since the UAVs will fly similar, but not exactly the same paths, when following a corridor the slice coordinates for each UAV path will be different.
- In this step, we interpolate the geometry between each slice to have a closed form 3-D shape for the corridor as illustrated in Figure 4-6. In the end, we visualize the air corridors by rendering the 3-D shape to the terrain map that we have.
- The distance between the coordinates in the individual coordinate sets indicates

Figure 4-5: Corridor slice over reference positions computed from UAV1 and UAV2 positions.

Figure 4-6: Reference corridor with all position slices computed and interpolated edges.

the possible error/uncertainty in the estimation. The estimation error is also visualized using a graph plot along with the uncertainty visualization of the 3-D corridors with the use color, blur, and fading effects.

The above explained steps in the proposed methodology are also illustrated in a pseudo-code format in Algorithm 2. Algorithm 2 lists every step in the process and describes the method in a more comprehensive manner.

The proposed framework for the development of a novel approach to air corridor estimation and visualization for multi-UAV flights can also be seen in a block diagrammatic view in Figure 4-7. Figure 4-7 shows every step of the methodology with a block diagram. The input to each process in the method is shown by labeled arrows. Likewise, the output from every process is demonstrated by labeled arrows.

In Algorithm 2, the input is a set of UAV positions and the terrain map of the airspace used. The next step is to compute and store the coordinates of the default sized corridor slice for each UAV position for each UAV path for a set of n UAV paths. Then, we find the path with less number of UAV positions and walk down each UAV position to find closest UAV positions in another UAV path. Then, we calculate vector distance between the UAV positions and compute the midpoint of the vector distance. The next step is to compute a corridor slice for each position on the reference path and interpolate the geometry between each slice to have a closed form 3-D shape for the corridor. The distance between the coordinates in the individual coordinate sets indicates the possible error/uncertainty in the estimation. The last step is to visualize the air corridors by rendering the 3-D shape to the terrain map which was one of the inputs to the system. The output of Algorithm 2 is the 3-D air corridors through which a fleet of UAVs are meant to fly from a particular source to a particular destination.

Algorithm 2: Air Corridor Averaging Estimation Algorithm

Input: UAV Position Dataset $D = \{x_i, y_i, z_i\}_{i=1}^n$
Input: Terrain Map
Output: 3-D Air Corridors C
Step 1: Traverse each UAV Path
for $i \leftarrow 1$ **to** n **do**
 $numPositions \leftarrow computeNumberPositions()$
 Step 2: Find UAV Paths with lesser number of position data
 for $i \leftarrow 1$ **to** $numPositions.length$ **do**
 $unequalUAVPositionsInPaths \leftarrow$
 $findUnequalUAVPositionsInPaths()$
 end
 Step 3: Extrapolate the position data if data are insufficient
 if ($unequalUAVPositionsInPaths == true$) **then**
 $radius \leftarrow r$
 $radians \leftarrow Cesium.Math.toRadians(i)$ where $i = 1$ **to** n
 $extrapolatePositions()$
 end
 $position \leftarrow computeFlightPath()$
 Step 4: Traverse each UAV Position
 for $i \leftarrow 1$ **to** $position.length$ **do**
 Step 5: Compute mean reference position
 $meanReferencePosition \leftarrow \frac{\sum_{i=1}^n x_i, y_i, z_i}{n}$
 end
end
 Step 6: Draw each UAV flight path along with the reference path
 $DrawPathGeometry()$
 Step 7: Draw the air corridor slice over each reference point
 $defaultCorridorHeight \leftarrow h$
 $defaultCorridorWidth \leftarrow w$
 $DrawCorridorSlice()$
 Step 8: Draw the air corridor geometry over the reference path
 $DrawCorridorGeometry()$
 Step 9: Calculate the uncertainty in the estimation
 $calculateError = distance(meanReferencePosition, \{x_i, y_i, z_i\}_{i=1}^n)$
 Step 10: Visualize the 3-D air corridors
 $visualize3DAirCorridorGeometry()$
return C

Figure 4-7: Air corridor averaging estimation algorithm

4.2.2 Extrapolation and Interpolation

Extrapolation is a process of estimating data points beyond the observation range based on the existing trends and observation points. In contrast, interpolation is an action of predicting new data points in between known values.

There are cases where in the number of UAV positions available is different for each UAV. In such cases, when some of the UAV paths have a lesser number of position data available than other UAVs, we extrapolate or interpolate the position data which is discussed in the Algorithm 3. For instance, if one of the flight paths is shorter than the other in case of two UAVs, we perform extrapolation to obtain more data points for the estimation of the flight corridors. Conversely, if the number of position data is not same for two equal paths, interpolation is executed to acquire more location data points for the path with a lesser number of data points.

In this algorithm, it is assumed that the position data have only three parameters, namely, latitude, longitude, and altitude. The extrapolation or interpolation approach taken here is based on only these three parameters. It is built on the Haversine formula, which is used to extrapolate the GPS coordinates. The formula calculates the distance between two different points based on the latitude/longitude, bearing, velocity, radius, and angle between two points [158, 159, 160]. The Haversine formula is stated by the equation:

$$a = \sin^2(\delta\phi/2) + \cos\phi_1 \cdot \cos\phi_2 \cdot \sin^2(\delta\lambda/2)$$

$$c = 2 \cdot a \tan 2(\sqrt{a}, \sqrt{1-a})$$

$$d = R \cdot c$$

where ϕ is latitude, λ is longitude, R is earth radius (mean radius = 6,371km)

So, the extrapolation/interpolation approach was taken assuming a default radius

of the first UAV position and then the extrapolated/interpolated points were calculated based on the first UAV position, the radius, and the angle in radians between UAV positions of the path taken.

Considering our case where only three parameters namely, latitude, longitude, and altitude were available at our disposal, this seemed to be the best approach for obtaining the extra UAV positions. This is not the classic formula for extrapolation/interpolation; however, it works in this scenario where we have only latitude, longitude, and altitude as parameters, as it derives from the Haversine formula which is used to extrapolate the GPS coordinates.

Algorithm 3: Extrapolation Algorithm

Input: UAV Position Dataset $D = \{x_i, y_i, z_i\}_{i=1}^n$
Output: Extrapolated UAV Positions P
Step 1: Traverse each UAV Path
for $i \leftarrow 1$ **to** n **do**
 | $numPos \leftarrow computeNumberPositions()$
end
Step 2: Find UAV Paths with lesser number of position data
for $i \leftarrow 1$ **to** $numPos.length$ **do**
 | $lessNumPos \leftarrow findLessNumberPosition()$
end
Step 3: Extrapolate the position data
 $radius \leftarrow r$
 $radians \leftarrow Cesium.Math.toRadians(i)$ where $i = 1$ **to** n
 $P \leftarrow Cesium.Cartesian3.fromDegrees(x + (radius * Math.cos(radians)), y + (radius * Math.sin(radians)), z)$
return P

4.3 Results

This section explains the hardware and software setup for the research performed, talks about the process of UAV flight data set creation, provides results acquired by implementing the proposed algorithm on the created data set, gives detailed insights

into the results obtained, and also discusses the uncertainty analysis in the results briefly.

4.3.1 Experimental Setup

The experiment was carried out using Intel Core i7-6700HQ CPU @ 2.60GHz 4 with 16 GB RAM and NVIDIA GeForce GTX discrete graphics card of 4 GB vRAM. The system used is Microsoft Windows 10. One of the important steps in the implementation was to find an appropriate visualization engine. CesiumJS graphics rendering engine was chosen as the best candidate for our visualization due to its capability to support spatial data and map-based visualization [153]. We used JavaScript as our main programming language to code the proposed algorithm, as it leverages the JavaScript open-source libraries such as CesiumJS efficiently along with HTML5 and CSS to render our contents onto the screen effectively. We used node server to run our web application locally.

4.3.2 Dataset Creation

To support our research and implement the proposed algorithm, we needed UAV flight data in a small airspace. To achieve this, we downloaded flight data from several online sources such as ADS-B Exchange [146] and Cesium Forum [148] as discussed previously in detail in Chapter 3. However, the approach discussed earlier in Chapter 3 could not deliver the results we expected. So, it was decided that we would handcraft our own UAV flight data. To achieve this, we chose the University of Toledo airspace and created our own multiple UAV flights data using **geojson.io** application [154]. The flight data was created using the assumption that the use of the flight corridor is overlapping, meaning a set of UAVs follow each other. The GPS coordinates, namely, latitude and longitude, were collected based on the path drawn

on **geojson.io** application and fed into the designed system. This data was utilized for the implementation of our proposed algorithm.

4.3.3 Visualization

In this subsection, we are going to showcase all the visualization results of the implementation of our proposed system on the CesiumJS web application. The results will be explained with screenshots of different views and orientations of the developed representations.

After the results of Chapter 3 did not quite match up to the expectations, the first step was to obtain a set of UAV positions that would support the research as discussed earlier in data set creation. The data were created assuming multiple UAVs flying in a small airspace over the University of Toledo from one particular source to a specific destination. It was also assumed that the use of the air corridors are overlapping. In other words, a set of UAVs follow each other and fly from a predefined source and destination. The results of the proposed algorithm are discussed below.

To begin, we show a glimpse of the user interface developed to interact with the visualization. It is accomplished to allow the visualizations to be interactive. The user input buttons can be seen in Figure 4-8, where the developed custom buttons can be seen on the left side of the screen and the default user input controls provided by CesiumJS can be seen on the top right part of the screen. A closer look at the developed user input buttons is provided in Figure 4-9. The buttons are provided to enable the users to view respective UAV path and its actual air corridor. There are buttons, which show the users the estimated path and the air corridor. The UAV operator can also use the *Air Corridors* button to view all the air corridors at once without the flight paths. The uncertainty in the estimation can be measured with the help of a button named *Estimation Uncertainty*. There are three orientation buttons to experience different views and reset the entire view.

Figure 4-8: User input buttons offering several functionalities.

Figure 4-9: A closer look at the user input buttons.

In the user interface (UI), a legend was designed and developed to aid the human operator with the level of uncertainty in the visualization of the flight corridors. It depicts the level of uncertainty from low to high with the use of color gradient. It is achieved with the help of linear gradient of color white. This functionality is illustrated in Figure 4-10.

Next, multiple sets of overlapping flight paths were computed and visualized using our own data created earlier. For a set of UAV paths, the closest positions were found and their average was computed to generate a reference path. A corridor slice for each position on the reference path was computed, and the geometry between each slice was interpolated to have a closed form 3-D shape for the corridor. Finally, we visualized by rendering the 3-D shape to the map. The outcome of the visualization can be seen in Figure 4-11. The figure shows the top view of all the flight paths and air corridors. In the figure, the multiple UAV paths can be seen in different colors. There are 11 actual UAV paths along with a estimated reference average path in the figure and their flight

Figure 4-10: Legend depicting the level of uncertainty from low to high.

Figure 4-11: Air corridors of 11 UAVs overlapping with each other (top view).

Figure 4-12: Air corridors of 11 UAVs overlapping with each other (side view from south-east).

Figure 4-13: Close view of the source where multiple UAVs are starting their flights . The white path in the center region is the estimated reference average path.

Figure 4-14: Corridors view from north-east.

Figure 4-15: Corridors view from south-west.

Figure 4-16: Multiple UAV flight paths from a given source to destination.

Figure 4-17: The estimated air corridor.

Figure 4-18: Air corridors without the flight paths.

Figure 4-19: Air corridors without the flight paths (north-west view).

Figure 4-20: Extrapolation: The red path is extrapolated and the extrapolated part is displayed by the blurred white path. The blur effect is added to denote the uncertainty in extrapolation.

corridors are assumed to be overlapping. The side view from the south-east direction of the same visualization can be seen in Figure 4-12. The estimated reference average path can be seen clearly in side view in Figure 4-13, where the path in white color is the computed average path. All the UAVs are meant to fly from a certain source to destination, and that is why it is seen that their flight paths are similar. Owing to external factors such as wind and stability, their paths vary slightly; however, they are assumed to fly in the same air corridor, which is supposed to be estimated. The figure demonstrates 11 actual flight corridors over each path and an estimated reference corridor over the reference path. The estimated air corridor is clearly visible for the same scenario in Figure 4-10, where the more prominent white air corridor in the middle is the estimated corridor and the overlapping corridors around it are the actual ones. It can be noted in the figure that the actual air corridors are overlapping with each other. They also overlap with the estimated reference corridor. The use of same color, white, enables us to view the estimated flight corridor clearly along

with the other corridors. Since all the air corridors are overlapping, the usage of same color highlights the estimated corridor more. The estimated corridor stands out in the figure due to the more prominent white region. The gradient effect helps the human operator to distinguish the area of high uncertainty from the region of low uncertainty. The different views of the air corridors can be experienced with different angles of rotation and can be seen in Figures 4-14 and 4-15. The back view of the air corridors can be seen in the former figure while the front side view can be seen in the latter figure.

Figure 4-16 illustrates the multiple UAV flight paths with varying altitudes. It can be noted in the figure that the source and destination of all the flights are assumed to be the same. There can be slight variation in the originating point and destination point due to external factors such as wind. The figure shows 11 UAV paths and the estimated reference path in white color. The estimated reference air corridor is shown in Figure 4-17, where the estimated corridor is visualized over the estimated reference path.

We have also provided the functionality to view all the air corridors along with the estimated one without the flight paths. All the flight paths along with the estimated reference path are turned off to visualize only the flight corridors at once. The outcome of the functionality can be seen in Figure 4-18. Another view of the same visualization is shown in Figure 4-19, which shows the north-west side of the screen, that is, the back of the corridors.

Figures 4-20 and 4-21 show the implementation of extrapolation and interpolation, respectively, in cases where the number of UAV positions for a set of UAVs is not equal. In such cases, where the number of location data points is not sufficient, we extrapolate or interpolate the points depending upon the paths available. When the flight paths are equal and the number of position data are unequal, our algorithm implements the interpolation to fetch the extra location data to compute each refer-

Figure 4-21: Interpolation: The red path with 10 points initially were interpolated to 37 points, which is visualized as a blurred white path. The blur effect depicts the uncertainty in interpolation.

ence position. In cases where flight paths are unequal and sufficient location data are available, the algorithm carries out extrapolation to obtain extra position data to be able to calculate the reference positions.

In Figure 4-20, the red path is shorter than the yellow path. There is not enough data points for the red path from source to destination, therefore, the path is incomplete. The extrapolation approach discussed earlier in Section 4.2, fetches the extra positions, which are shown in white. The extrapolated path is illustrated in blurred white color. The average reference path computed is shown in cyan color in

the figure.

The interpolation results can be seen in Figure 4-21. Contrary to the extrapolation case, the flight paths are equal in this scenario, which are shown by red and yellow paths. The red path does not have enough positions for our proposed algorithm to calculate the reference average path. The red path had 10 points initially and was interpolated with 37 points. The interpolated points and the path can be seen in blurred white. The average path was then computed and visualized by cyan. The flight corridors visualized can also be seen in the figure.

4.3.4 Uncertainty Analysis

Uncertainty around corridors is visualized using the color gradient effect in the visualization. Uncertainty is being visualized in Figures 4-11, 4-13, 4-18, 4-20, 4-21, and 4-22 by overlapping corridors with the use of color gradient effect. The more prominent white shows the area of possible air corridor and the faded area shows uncertainty around corridors. Color gradient effect is an effective way to distinguish regions of high uncertainty from those of low uncertainty. A legend was introduced, which is illustrated in Figure 4-10, to help the operator to distinguish between the region of high uncertainty and low uncertainty. The linear color gradient shows a smooth transition effect from the faded white to more solid white. This has been achieved by varying the alpha component of the RGBA value of white. It can also be observed in Figure 4-22, that the visibility of the flight paths can be turned off and only the air corridors can be visualized. This enables the depiction of the flight corridors and the uncertainty around them clearer. The level of uncertainty can also be gauged

Figure 4-22: Uncertainty in the air corridors are being visualized here with the use of same color, color gradient effect and fading. The more prominent white in the below figure denotes the region of low uncertainty.

Figure 4-23: Error/Uncertainty in estimation of the air corridors.

more effectively by turning off the flight paths. In addition to this, the estimated flight corridor can also be viewed in a lucid way.

The distance between the coordinates in the individual coordinate sets of the reference path and one of the UAV paths indicates the possible error/uncertainty in the estimation. The error/uncertainty in estimation is shown in Figure 4-23. The estimation error plot shows the relationship of distance between corresponding UAV positions on the reference path and one of the UAV paths versus the number of UAV positions. It also shows the UAV position with the highest error in estimation and also the position with the lowest error in estimation. Since the estimation error plot was developed using JavaScript, it has a functionality of tooltip that shows the exact estimation error of all the UAVs in meters when the user hovers the computer mouse over each UAV position. The estimation uncertainty plot can give a good idea to the operator about how the UAVs fly with respect to each other and the estimated reference air corridor.

4.4 Possible Application Areas

In this section, we discuss some of the possible application areas where our proposed system can be put into effect.

4.4.1 University Campus Monitoring

The next-generation multi-UAV system we proposed in this work is well suited to monitoring a university campus. Such a system would enhance the security and safety of the campus. The UAVs might get set up to fly in their estimated visualized air corridors and report any illegal or unlawful activities, such as drug abuse, weapon use, robbery, unlawful student parties, bullying and so on. This would keep the bad activities in check at campus and ensure the security and safety of the students. Such

systems would also assist the university campus police in their daily operations.

4.4.2 Military Warfare

The next-generation multi-UAV system we discussed in this work is ideally suited for multiple UAVs engaged in a combat in an airspace. In warfare, there are situations where multiple UAVs are engaging in combat, and they are designated to fly at different times along similar routes to engage in such combat. Such a situation warrants a system where the UAVs are supposed to fly in their allotted air corridors, do their job, and come back to the origin point. Having air corridors would also help detect any unusual behaviors such as an enemy UAV trying to get into the air corridors, or if a UAV is flying involving a lot of deflection from the air corridors, which could mean the UAV might belong to an enemy and does not know the exact path. Such a thing might happen due to external factors like wind or situations like a UAV is trying to duck an attack by an enemy UAV. A system such as we proposed could be a great solution for multiple UAVs flying in an airspace for combat.

4.4.3 Agriculture

The next-generation multi-UAV system earlier proposed can be used in the field of agriculture. The air corridors would make sure that the UAVs fly their planned paths, do their jobs, and come back to the originating station. Multiple UAVs can fly and monitor the crops at different times of day. The UAVs can also be set up to do an automated fertilization of the crops or be a part of an automated sprinkler system. The air corridor system would help to ensure that the UAVs fly in their allotted corridors and do their job efficiently in the least amount of time. Such a system would also help in proper routing of the UAVs over agricultural land and avoid any mishaps. Such automated multi-UAV systems could lead to better productivity of

crops.

4.4.4 Photography

Multi-UAV systems can also be used for aerial photography. Drones are increasingly gaining popularity for aerial photography. These drones are well equipped with high-resolution cameras that can take high-definition pictures and videos. Multiple drones with such cameras can be used to record high-profile events like football games, other sports, weddings, concerts, political events, and so on. It can take recording of such events to a whole new level by providing shots from different angles. Implementing our proposed prototype can help navigate these UAVs in a more systematic way. The defined air corridors would also make the whole system less accident-prone.

4.4.5 Product Delivery

Nowadays, drones are being used by big e-commerce companies like Amazon to deliver products to customers. Such a service could get a boost if they used a proper system in which drones have allocated air corridors, and multiple drones could navigate through them safely avoiding any collisions. It would increase the reliability of product delivery. In addition, it would also mean reduced costs due to fewer accidents that might happen due to collisions if the drones were to fly without any air corridors estimated for them. Our proposed system could be implemented by online retailers to deliver products to customers in particular areas, with the help of drones.

4.4.6 Disaster Relief

Our proposed multi-UAV system is ideally suited for disaster relief operations over an area. Currently, UAVs are being used in disaster and rescue operations. Our system could help set up a drones to fly over an area at different times and engage in

rescue operations during a crisis. The air corridors would help in covering the entire disaster-hit area with designated UAV routes, where in the drones can fly at their allotted times and carry out rescue operations. The multi-UAV system can prevent mishaps from happening and help in keeping a tab on all the drones involved in the relief activities.

4.4.7 Wildlife Conservation and Management

Our proposed methodology for multi-UAV systems can be put into use in the area of wildlife conservation and management. In fact, UAVs are already taking off in wildlife protection and being used to monitor protected areas, collect wildlife data, and nab poachers. Since drones operate at a much a lower cost than helicopters, they are being increasingly used in wildlife conservation and management. Multi-UAV systems like ours can really help navigate the multiple drones safely in air over forests and aid in cutting costs due to fewer accidents. Such a system would be a lot safer for the lives of animals and forests, as it could prevent mishap. Moreover, multiple UAVs flying over wildlife without air corridors would be dangerous for wildfire as accidents could lead to fire. If the UAVs are designed to fly in allotted air corridors, it would be devoid of disasters and lead to safer monitoring over wildlife.

4.5 Chapter Summary

This chapter gave us a detailed insight into the implementation aspect of the research. It discussed the overview of the air corridor estimation and visualization system. It presented a novel methodology to estimate and visualize the reference air corridor based on the available UAV flight data. The novel approach is shown in the form of an algorithm, and each step is explained in detail. It also discussed the extrapolation approach in the algorithm. It also discussed how the multiple UAV

flights data was created for the purpose of the research. We also showcased the visualization results and discussed them in detail. We also came up with a novel way to incorporate uncertainty visualization in the air corridors representation and explained the uncertainty aspect in the estimation of the UAV flight corridor.

Chapter 5

Conclusion and Future Works

5.1 Conclusion

The purpose of this work was to propose an algorithm to estimate and visualize the air corridors of a multiple UAV system in an airspace and evaluate the strengths and weaknesses of the approach taken.

Through this work, we have tried to implement a future monitoring system that can be used by organizations such as the military and universities to deploy a multi-UAV system in a small airspace to engage in tasks such as monitoring, surveillance, surveying, and aerial photography. Our proposed algorithm is designed for a constrained airspace where we estimate air corridors for multiple UAVs in the airspace. The monitoring system can be installed in a small airspace and used to estimate, visualize, and analyze flight corridors for multiple UAVs flying in overlapping air corridors at different times.

As for the research, we have finalized the data and final implementation based on our initial findings on wake turbulence testing data set [151] and ADS-B Exchange data sets [146]. The wake turbulence testing data set was created for a single flight and it did not cater our needs of a multiple flight data set. To overcome this issue, we downloaded data from ADS-B Exchange, which was a real-world data of multiple

flights over a period of time. We visualized the air corridors of these multiple flights; however, our findings were not in sync with what we were trying to achieve for a multi-UAV scenario in a small airspace. The ADS-B Exchange data set was very scattered and the flight data were from different airport locations, which were far-off from each other. The air corridors we visualized were very far from each other, thus making it difficult for us to estimate the air corridors based on our proposed methodology. Therefore, we used our own data on a small airspace to implement our proposed algorithm.

5.2 Strengths and Limitations

The strengths of our proposed methodology and visualization techniques are manifold. To begin with, the proposed algorithm is one of a kind, and such an approach has never been implemented before. Next, the algorithm also handles cases where interpolation and extrapolation are required and provides the system with extrapolated or interpolated UAV positions when the number of positions is less than what is required in any of the UAV paths. Additionally, the method also computes the uncertainty in the estimation and visualizes the uncertainty with the state-of-the-art approach. Furthermore, the visualization of the air corridors leverages the latest technologies and cutting-edge visualization techniques. Finally, the multi-UAV systems we have put forward in this work can be used in many applications, such as surveillance, product deliveries, and photography.

There are a few limitations of our proposed algorithm that need a mention here. To start with, the implementation uses our own flight data and not the real-world complex flight data. We are not sure how the algorithm would behave if implemented on a real data. The working behavior of the methodology on real-world data is unknown to us. In addition to this, the approach taken can employ only three UAV

location attributes, namely, latitude, longitude, and altitude, and build its estimation based on just these parameters. Likewise, the interpolation and extrapolation approaches discussed in Chapter 4 use only GPS coordinates and altitude for their computation. Finally, the multi-UAV system proposed here can only be implemented for post-flight scenarios, as it makes use of the flight data already available. This system would not work for a real-time feed of the UAV positions.

5.3 Future Work

This section proposes future research directions in the area of air corridor estimation and visualization and uncertainty visualization in separate subsections.

5.3.1 Air Corridor Estimation and Visualization

Future research directions in air corridor estimation and visualization systems are summarized below:

- **Real-World Data:** Although this research was carried out using our own created data, future works could include implementing the system on real-world data, such as air traffic control data of an airport that would help us analyze the air corridors and make it more feasible for a real-world application. The use of complex real-world data would make the system capable of handling real-world scenarios.
- **Real-Time System:** Future works could also consider implementing such a system for a real-time data feed. This research attempts to estimate and visualize the air corridors based on data obtained post-flight. We could implement the proposed system on a real-time UAV flight data, which would create air corridors on the spot.

- **Reverse Path Estimation:** In this thesis, we proposed air corridors estimation from the UAV positions obtained initially and the UAV paths computed taking those positions into account. In contrast, we could also carry out the reverse estimation of all possible UAV paths from the air corridors computed and visualized. This would help validate the estimation of the air corridor by analyzing all possible UAV paths that could pass through an air corridor. Such a reverse estimation could help us in the validation of our proposed approach.
- **Visual Dashboard:** We could also develop a dashboard, which could give us visuals of the UAV traffic going around the airspace and generate alerts when an unusual activity is detected. The detection system could be deployed on an airspace where it would estimate the air corridors on the go and try to visualize them for the human operators to understand the behavior of flights and identify any suspicious or unusual activity.

5.3.2 Uncertainty Visualization

From what we have gathered so far, the uncertainty visualization has certainly taken giant strides over the past few decades in the area of data science. The available literature gives an overview of what is available today and what the open problems are. The open problems in uncertainty visualization exist in multiple fields of data and information analysis and need to be talked about at length to make existing and new data scientists aware of the issues and give them a head start. This section mainly attempts to look at these open problems and discuss them in detail. The missing solutions range from incompleteness in the involvement of perceptual and cognitive senses to the inefficacy of the methodologies employing comparison of results to determine the reliability [41, 40, 161, 162].

- **Integrated Views:** Uncertainty at times may require comparison of different

visualizations to reach a conclusion. Areas like the weather forecast or medical imaging may involve comparison of various results to reach a conclusion [163, 164]. A comparison is needed to detect similarities or differences for decision-making. Comparative visualization techniques are employed to achieve that [165]. If a lot of information is added to the view, it becomes cluttered and difficult to comprehend. Likewise, 3-D visualization techniques may be used to show a few parameters, say three or four, instead of all of them [166, 167, 168]. These constraints pose challenges in depicting uncertainty in visualization in such areas. Future research can be performed in the area of comparative visualization. Topics of research could range from depicting many data sets simultaneously without clutter to integrated views.

- **User Interaction:** Another possible future direction of research is the focus on users interaction, where users can control when information related to error or unreliability is displayed and how a visual balance of data and the errors associated with are achievable when the entire data are visualized at once.
- **Perceptual Improvements:** Visualization, in general, is all about colors to depict data. People with color blindness might be overwhelmed and challenged to understand data through visualization. Such a case leads to uncertainty in visualization. Aside from the usual uncertainty sources, for example, sampling uncertainty, modeling uncertainty, or uncertainty through visualization, uncertainties like these come from the viewers and their ambiguous interpretations of the visualization. In such cases, display of additional information like uncertainty information in the visualization could add to the ambiguity making decision-making even more difficult. More research is needed in this area to make visualizations efficient for individuals with a color deficiency or any other perceptual implications.

- **Reasoning Integration:** There is a lot of complexity and analytic gaps in the reasoning process. Because of this, integration of data and reasoning visualization is likely to bring good results in terms of cognitive support. This integration would help to realize the exact depiction of the whole logical system, thereby reducing gaps concerning analysis and understanding. Otherwise, it would be challenging to observe the impact of gaps in the integrated analytic system.
- **Less Clutter:** Another open problem is the ever-growing data in modern times that needs to be visualized. Because of this, uncertainty visualization techniques have to be applied to big data. The display of uncertainty along with the data already results in a cluttered view. This presents a new challenge of representing more data with higher dimensional uncertainties in a display. Furthermore, the existing techniques exist in only a few areas such as cartography, volume and flow visualization. Other areas need attention too when it comes to applying these techniques. Moreover, there is a need to focus on the evaluation of such techniques. For example, a data scientist must be able to tell when and for what data which techniques are more applicable.
- **Empirical Evaluation:** There is more work to be performed when it comes to empirical evaluation of the uncertainty visualization. Most of the earlier works discuss uncertainty visualization from the theoretical viewpoint. There is a lack of actual implementation strategies in previous works to represent uncertainty in data visualization. Very few research papers describe how we can implement different typologies of uncertainty visualization. Future research works can focus on various implementation strategies for uncertainty visualization keeping the new researchers in mind.
- **Machine Learning:** Ongoing research has shown immense promise in the in-

tegration of machine learning (ML) and uncertainty visualization techniques to enhance the ability to understand the uncertainty in ML models, be it in predictive models or classification models. Owing to this, there is a need to design better alternative uncertainty visualization techniques to make ML models more comprehensible for the analysts. To design alternative visualization techniques, future research is required in the area of dimension reduction methods as well. Furthermore, ML models need to be improved further to make better predictive models to improve the whole uncertainty visualization experience in ML. Extensive user studies also need to be carried out to evaluate the alternate visualization methods.

As discussed earlier in the paper, visual analytics systems can improve human understanding of the ML models; however, it can also introduce uncertainties into the whole analytics process. Research shows that uncertainty awareness can lead to better decision-making [169]. Therefore, it is essential to measure and estimate uncertainties, which is very challenging. One possible future research direction is to investigate and design visual analytics systems that quantify uncertainties at each stage of an interactive model such as data processing, training, visualization and testing. Such systems can help ML experts understand the ML models inside out, which in turn will help them improve the models.

Moreover, any interactive model depends on both the systems as well as the users for it to work comprehensively. An uncertain result may lead to incorrect decision-making, which will affect the quality of the entire system. Another interesting research direction is to find efficient ways to model different types of uncertainties in an integrated system. For example, in the scenario discussed above, possible research direction is how to model separate uncertainties associated with the system and the user in a unified system.

- **Big Data:** A considerable amount of investigation is ongoing in the world of big data relating to uncertainty visualization. Since big data has large amounts of reliability issues, it is important to discover efficient visual techniques to understand the uncertainty associated with big data which in turn will lead to better understanding of the data. It is also vital to focus on user evaluations to assess the alternative uncertainty visualization techniques of big data to investigate and come up with the best options. Besides, more research can be performed to improve the existing uncertainty-aware big data visual analytics systems.

References

- [1] “Unmanned aerial vehicle - wikipedia.” https://en.wikipedia.org/wiki/Unmanned_aerial_vehicle. (Accessed on 11/06/2018).
- [2] “Microsoft word - circ.328.alltext.en.docx.” https://www.icao.int/Meetings/UAS/Documents/Circular%20328_en.pdf. (Accessed on 11/06/2018).
- [3] U. E. Franke, “Civilian drones: Fixing an image problem?,” *ISN Blog. International Relations and Security Network. Retrieved*, vol. 5, 2015.
- [4] “Drones in law enforcement: How, where and when they’re used - the drive.” <http://www.thedrive.com/aerial/15092/drones-in-law-enforcement-how-where-and-when-theyre-used>. (Accessed on 11/06/2018).
- [5] “Aerial photography has changed the world. drones are just the latest example — time.” <http://time.com/5281295/aerial-photography-history-drones/>. (Accessed on 11/06/2018).
- [6] “How drones are advancing scientific research.” <https://blogs.ei.columbia.edu/2017/06/16/how-drones-are-advancing-scientific-research/>. (Accessed on 11/06/2018).
- [7] “Commercial drones are here: The future of unmanned aerial systems — mckinsey.” <https://www.mckinsey.com/industries/capital-projects-and-infrastructure/our-insights/commercial-drones-are-here-the-future-of-unmanned-aerial-systems>. (Accessed on 11/06/2018).

- [8] “Questuav — drones for surveying.” <https://www.questuav.com/industries/surveying/>. (Accessed on 11/06/2018).
- [9] “The usage of commercial drones for land surveying — alti.” <https://www.altiuas.com/usage-commercial-drones-land-surveying/>. (Accessed on 11/06/2018).
- [10] “Drones are thriving in some areas of surveying — 2018-01-24 — point of beginning.” <https://www.pobonline.com/articles/101235-drones-are-thriving-in-some-areas-of-surveying>. (Accessed on 11/06/2018).
- [11] “How drones are advancing civil engineering and surveying — computerworld.” <https://www.computerworld.com/article/3199631/enterprise-applications/how-drones-are-advancing-civil-engineering-and-surveying.html>. (Accessed on 11/06/2018).
- [12] “The truth about drones in mapping and surveying.” <https://droneanalyst.com/2016/07/27/the-truth-about-drones-in-mapping-and-surveying>. (Accessed on 11/06/2018).
- [13] “Drones changing the game for topographic surveying — propeller.” <https://www.propelleraero.com/blog/drones-changing-game-topographic-surveying/>. (Accessed on 11/06/2018).
- [14] “Amazon.com: Prime air.” <https://www.amazon.com/Amazon-Prime-Air/b?ie=UTF8&node=8037720011>. (Accessed on 11/06/2018).
- [15] “Amazon delivered its first customer package by drone.” <https://www.usatoday.com/story/tech/news/2016/12/14/amazon-delivered-its-first-customer-package-drone/95401366/>. (Accessed on 11/06/2018).

- [16] “Amazon and ups are betting big on drone delivery - business insider.” <https://www.businessinsider.com/amazon-and-ups-are-betting-big-on-drone-delivery-2018-3>. (Accessed on 11/06/2018).
- [17] “The history of drones: a wonderful, fascinating story over 235+ years.” <https://www.dronesbuy.net/history-of-drones/>. (Accessed on 11/06/2018).
- [18] C. Kennedy and J. I. Rogers, “Virtuous drones?,” *The International Journal of Human Rights*, vol. 19, no. 2, pp. 211–227, 2015.
- [19] “Hurricanes show why drones are the future of disaster relief.” <https://www.nbcnews.com/mach/science/hurricanes-show-why-drones-are-future-disaster-relief-ncna799961>. (Accessed on 11/06/2018).
- [20] “Humanitarian in the sky: drones for disaster response — virgin.” <https://www.virgin.com/virgin-unite/business-innovation/humanitarian-sky-drones-disaster-response>. (Accessed on 11/06/2018).
- [21] “American red cross is launching a drone disaster-relief program.” <https://www.engadget.com/2017/09/08/american-red-cross-drone-disaster-relief-program/>. (Accessed on 11/06/2018).
- [22] “Drones smuggling porn, drugs to inmates around the world — fox news.” <https://www.foxnews.com/us/drones-smuggling-porn-drugs-to-inmates-around-the-world>. (Accessed on 11/06/2018).
- [23] “A history of commercial drones - business insider.” <https://www.businessinsider.com/a-history-of-commercial-drones-2016-12>. (Accessed on 11/06/2018).
- [24] C. Johnson, “Top scientific visualization research problems,” *IEEE Computer Graphics and Applications*, vol. 24, no. 4, pp. 13–17, 2004.

- [25] J. Thomson, E. Hetzler, A. MacEachren, M. Gahegan, and M. Pavel, “A typology for visualizing uncertainty,” in *Electronic Imaging 2005*, pp. 146–157, International Society for Optics and Photonics, 2005.
- [26] A. M. MacEachren, R. E. Roth, J. O’Brien, B. Li, D. Swingley, and M. Gahegan, “Visual semiotics & uncertainty visualization: An empirical study,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 18, no. 12, pp. 2496–2505, 2012.
- [27] D. Sinton, “The inherent structure of information as a constraint to analysis: Mapped thematic data as a case study,” *Harvard papers on geographic information systems*, vol. 6, pp. 1–17, 1978.
- [28] G. J. Hunter and M. Goodchild, “Managing uncertainty in spatial databases: Putting theory into practice,” in *Papers from the Annual Conference-Urban and Regional Information Systems Association*, pp. 15–15, Urisa Urban and Regional Information Systems, 1993.
- [29] A. M. MacEachren, A. Robinson, S. Hopper, S. Gardner, R. Murray, M. Gahegan, and E. Hetzler, “Visualizing geospatial information uncertainty: What we know and what we need to know,” *Cartography and Geographic Information Science*, vol. 32, no. 3, pp. 139–160, 2005.
- [30] M. Riveiro, “Evaluation of uncertainty visualization techniques for information fusion,” in *Information Fusion, 2007 10th International Conference on*, pp. 1–8, IEEE, 2007.
- [31] A. T. Pang, C. M. Wittenbrink, and S. K. Lodha, “Approaches to uncertainty visualization,” *The Visual Computer*, vol. 13, no. 8, pp. 370–390, 1997.
- [32] G. M. Foody and P. M. Atkinson, *Uncertainty in remote sensing and GIS*. John Wiley & Sons, 2003.

- [33] J. L. Dungan, D. Kao, and A. Pang, “The uncertainty visualization problem in remote sensing analysis,” in *Geoscience and Remote Sensing Symposium, 2002. IGARSS’02. 2002 IEEE International*, vol. 2, pp. 729–731, IEEE, 2002.
- [34] M. Gahegan and M. Ehlers, “A framework for the modelling of uncertainty between remote sensing and geographic information systems,” *ISPRS Journal of Photogrammetry and Remote Sensing*, vol. 55, no. 3, pp. 176–188, 2000.
- [35] M. Crosetto, J. A. M. Ruiz, and B. Crippa, “Uncertainty propagation in models driven by remotely sensed data,” *Remote Sensing of Environment*, vol. 76, no. 3, pp. 373–385, 2001.
- [36] M. Duckham, K. Mason, J. Stell, and M. Worboys, “A formal approach to imperfection in geographic information,” *Computers, environment and urban systems*, vol. 25, no. 1, pp. 89–103, 2001.
- [37] N. Gershon, “Visualization of an imperfect world,” *IEEE Computer Graphics and Applications*, vol. 18, no. 4, pp. 43–45, 1998.
- [38] Y. Wu, G.-X. Yuan, and K.-L. Ma, “Visualizing flow of uncertainty through analytical processes,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 18, no. 12, pp. 2526–2535, 2012.
- [39] M. Skeels, B. Lee, G. Smith, and G. G. Robertson, “Revealing uncertainty for information visualization,” *Information Visualization*, vol. 9, no. 1, pp. 70–81, 2010.
- [40] T. Zuk and S. Carpendale, “Visualization of uncertainty and reasoning,” in *Smart graphics*, pp. 164–177, Springer, 2007.
- [41] T. Zuk and S. Carpendale, “Theoretical analysis of uncertainty visualizations,”

- in *Electronic Imaging 2006*, pp. 606007–606007, International Society for Optics and Photonics, 2006.
- [42] S. Parsons and A. Hunter, “A review of uncertainty handling formalisms,” in *Applications of uncertainty formalisms*, pp. 8–37, Springer, 1998.
 - [43] K. W. Brodlie, L. Carpenter, R. Earnshaw, J. R. Gallop, R. J. Hubbard, A. Mumford, C. Osland, and P. Quarendon, “Scientific visualization: techniques and applications,” 1992.
 - [44] B. P. Buttenfield and J. H. Ganter, “Visualization and gis: What should we see? what might we miss,” in *Proceedings of the 4th International Symposium on Spatial Data Handling*, vol. 1, pp. 307–316, 1990.
 - [45] B. Buttenfield and M. K. Beard, “Graphical and geographical components of data quality,” *Visualization in geographic information systems*, pp. 150–157, 1994.
 - [46] A. M. MacEachren, “Visualizing uncertain information,” *Cartographic Perspectives*, no. 13, pp. 10–19, 1992.
 - [47] M. Smithson, “Ignorance and uncertainty: Emerging paradigms,” 1989.
 - [48] K. Brodlie, R. A. Osorio, and A. Lopes, “A review of uncertainty in data visualization,” in *Expanding the frontiers of visual analytics and visualization*, pp. 81–109, Springer, 2012.
 - [49] C. R. Johnson and A. R. Sanderson, “A next step: Visualizing errors and uncertainty,” *IEEE Computer Graphics and Applications*, vol. 23, no. 5, pp. 6–10, 2003.

- [50] G.-P. Bonneau, H.-C. Hege, C. R. Johnson, M. M. Oliveira, K. Potter, P. Rheingans, and T. Schultz, “Overview and state-of-the-art of uncertainty visualization,” in *Scientific Visualization*, pp. 3–27, Springer, 2014.
- [51] C. Olston and J. D. Mackinlay, “Visualizing data with bounded uncertainty,” in *Information Visualization, 2002. INFOVIS 2002. IEEE Symposium on*, pp. 37–40, IEEE, 2002.
- [52] A. Slingsby, J. Dykes, and J. Wood, “Exploring uncertainty in geodemographics with interactive graphics,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 17, no. 12, pp. 2545–2554, 2011.
- [53] Y. Wu, F. Wei, S. Liu, N. Au, W. Cui, H. Zhou, and H. Qu, “Opinionseer: interactive visualization of hotel customer feedback,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 16, no. 6, pp. 1109–1118, 2010.
- [54] C. Schulz, A. Nocaj, J. Goertler, O. Deussen, U. Brandes, and D. Weiskopf, “Probabilistic graph layout for uncertain network visualization,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 23, no. 1, pp. 531–540, 2017.
- [55] S. Deitrick and R. Edsall, “The influence of uncertainty visualization on decision making: An empirical evaluation,” in *Progress in spatial data handling*, pp. 719–738, Springer, 2006.
- [56] C. C. Aggarwal and S. Y. Philip, “A survey of uncertain data algorithms and applications,” *IEEE Transactions on Knowledge and Data Engineering*, vol. 21, no. 5, pp. 609–623, 2009.
- [57] J. L. Dungan, D. L. Kao, and A. Pang, “Modeling and visualizing uncertainty in continuous variables predicted using remotely sensed data,” in *Geoscience*

- and Remote Sensing Symposium, 2003. IGARSS'03. Proceedings. 2003 IEEE International*, vol. 5, pp. 3017–3019, IEEE, 2003.
- [58] A. Cedilnik and P. Rheingans, “Procedural annotation of uncertain information,” in *Proceedings of the conference on Visualization'00*, pp. 77–83, IEEE Computer Society Press, 2000.
 - [59] H. M. Hearnshaw and D. J. Unwin, “Visualization in geographical information systems,” 1994.
 - [60] M. Hlawatsch, P. Leube, W. Nowak, and D. Weiskopf, “Flow radar glyphsstatic visualization of unsteady flow with uncertainty,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 17, no. 12, pp. 1949–1958, 2011.
 - [61] T. Zukab, J. Downtonb, D. Grayb, S. Carpendalea, and J. Liangb, “Exploration of uncertainty in bidirectional vector fields,” in *Proc. SPIE*,, 2008.
 - [62] J.-S. Prassni, T. Ropinski, and K. Hinrichs, “Uncertainty-aware guided volume segmentation,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 16, no. 6, pp. 1358–1365, 2010.
 - [63] A. Masalonis, S. Mulgund, L. Song, C. Wanke, and S. Zobell, “Using probabilistic demand predictions for traffic flow management decision support,” in *AIAA Guidance, Navigation, and Control Conference and Exhibit*, p. 5231, 2004.
 - [64] K. Jää-Aro, “Lecture notes: Visualisation of uncertainty,” *KTH. Stockholm*, 2006.
 - [65] A. Pang, J. J. Furman, and W. Nuss, “Data quality issues in visualization,” in *IS&T/SPIE 1994 International Symposium on Electronic Imaging: Science and Technology*, pp. 12–23, International Society for Optics and Photonics, 1994.

- [66] H. Couclelis, “The certainty of uncertainty: Gis and the limits of geographic knowledge,” *Transactions in GIS*, vol. 7, no. 2, pp. 165–175, 2003.
- [67] N. D. Gershon, “Visualization of fuzzy data using generalized animation,” in *Visualization, 1992. Visualization’92, Proceedings., IEEE Conference on*, pp. 268–273, IEEE, 1992.
- [68] N. Boukhelifa and D. J. Duke, “Uncertainty visualization: why might it fail?,” in *CHI’09 Extended Abstracts on Human Factors in Computing Systems*, pp. 4051–4056, ACM, 2009.
- [69] R. B. Haber and D. A. McNabb, “Visualization idioms: A conceptual model for scientific visualization systems,” *Visualization in scientific computing*, vol. 74, p. 93, 1990.
- [70] C. M. Wittenbrink, A. T. Pang, and S. K. Lodha, “Glyphs for visualizing uncertainty in vector fields,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 2, no. 3, pp. 266–279, 1996.
- [71] H. Griethe, H. Schumann, *et al.*, “The visualization of uncertain data: Methods and problems,” in *SimVis*, pp. 143–156, 2006.
- [72] A. Karami, “A framework for uncertainty-aware visual analytics in big data,” in *AIC*, pp. 146–155, 2015.
- [73] G. Grigoryan and P. Rheingans, “Probabilistic surfaces: Point based primitives to show surface uncertainty,” in *Proceedings of the conference on Visualization’02*, pp. 147–154, IEEE Computer Society, 2002.
- [74] G. Grigoryan and P. Rheingans, “Point-based probabilistic surfaces to show surface uncertainty,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 10, no. 5, pp. 564–573, 2004.

- [75] S. Djurcilov, K. Kim, P. F. Lermusiaux, and A. Pang, “Volume rendering data with uncertainty information,” in *Data Visualization 2001*, pp. 243–252, Springer, 2001.
- [76] L. A. Zadeh, “Fuzzy sets as a basis for a theory of possibility,” *Fuzzy sets and systems*, vol. 100, pp. 9–34, 1999.
- [77] L. A. Zadeh, “Fuzzy sets,” in *Fuzzy Sets, Fuzzy Logic, And Fuzzy Systems: Selected Papers by Lotfi A Zadeh*, pp. 394–432, World Scientific, 1996.
- [78] J. W. Tukey, “Exploratory data analysis,” 1977.
- [79] M. Frigge, D. C. Hoaglin, and B. Iglewicz, “Some implementations of the box-plot,” *The American Statistician*, vol. 43, no. 1, pp. 50–54, 1989.
- [80] K. W. Haemer, “Range-bar charts,” *The American Statistician*, vol. 2, no. 2, pp. 23–23, 1948.
- [81] M. E. Spear, “Charting statistics,” 1952.
- [82] K. Potter, H. Hagen, A. Kerren, and P. Dannenmann, “Methods for presenting statistical information: The box plot,” *Visualization of large and unstructured data sets*, vol. 4, pp. 97–106, 2006.
- [83] C. Choonpradub and D. McNeil, “Can the box plot be improved,” *Songklanakarin Journal of Science and Technology*, vol. 27, no. 3, pp. 649–657, 2005.
- [84] Y. Benjamini, “Opening the box of a boxplot,” *The American Statistician*, vol. 42, no. 4, pp. 257–262, 1988.
- [85] J. L. Hintze and R. D. Nelson, “Violin plots: a box plot-density trace synergism,” *The American Statistician*, vol. 52, no. 2, pp. 181–184, 1998.

- [86] K. Potter, J. Kniss, R. Riesenfeld, and C. R. Johnson, “Visualizing summary statistics and uncertainty,” in *Computer Graphics Forum*, vol. 29, pp. 823–832, Wiley Online Library, 2010.
- [87] K. Potter, *The visualization of uncertainty*. The University of Utah, 2010.
- [88] L. Wilkinson, “Dot plots,” *The American Statistician*, vol. 53, no. 3, pp. 276–281, 1999.
- [89] L. Wilkinson, “The grammar of graphics,” in *Handbook of Computational Statistics*, pp. 375–414, Springer, 2012.
- [90] D. J. Cohen and J. Cohen, “The sectioned density plot,” *The American Statistician*, vol. 60, no. 2, pp. 167–174, 2006.
- [91] D. Kao, A. Luo, J. L. Dungan, and A. Pang, “Visualizing spatially varying distribution data,” in *Information Visualisation, 2002. Proceedings. Sixth International Conference on*, pp. 219–225, IEEE, 2002.
- [92] E. B. Chlan and P. Rheingans, “Multivariate glyphs for multi-object clusters,” in *Information Visualization, 2005. INFOVIS 2005. IEEE Symposium on*, pp. 141–148, IEEE, 2005.
- [93] D. K. Jones, “Determining and visualizing uncertainty in estimates of fiber orientation from diffusion tensor mri,” *Magnetic Resonance in Medicine*, vol. 49, no. 1, pp. 7–12, 2003.
- [94] K. Potter, A. Wilson, P.-T. Bremer, D. Williams, C. Doutriaux, V. Pascucci, and C. R. Johnson, “Ensemble-vis: A framework for the statistical visualization of ensemble data,” in *Data Mining Workshops, 2009. ICDMW’09. IEEE International Conference on*, pp. 233–240, IEEE, 2009.

- [95] R. Allendes Osorio and K. W. Brodlie, “Contouring with uncertainty,” in *Theory and Practice of Computer Graphics 2008. Proceedings.*, pp. 59–66, Eurographics Association, 2008.
- [96] J. Sanyal, S. Zhang, J. Dyer, A. Mercer, P. Amburn, and R. Moorhead, “Noodles: A tool for visualization of numerical weather model ensemble uncertainty,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 16, no. 6, pp. 1421–1430, 2010.
- [97] A. J. Joseph, S. Lodha, J. Renteria, and A. Pang, “Uisurf: Visualizing uncertainty in isosurfaces,” Master’s thesis, University of California, Santa Cruz, 1998.
- [98] H. Li, C.-W. Fu, Y. Li, and A. Hanson, “Visualizing large-scale uncertainty in astrophysical data,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 13, no. 6, pp. 1640–1647, 2007.
- [99] S. K. Lodha, B. Sheehan, A. T. Pang, C. M. Wittenbrink, *et al.*, “Visualizing geometric uncertainty of surface interpolants,” in *Graphics Interface*, vol. 96, pp. 238–245, 1996.
- [100] S. K. Lodha, A. Pang, R. E. Sheehan, and C. M. Wittenbrink, “Uflow: Visualizing uncertainty in fluid flow,” in *Proceedings of the 7th conference on Visualization’96*, pp. 249–ff, IEEE Computer Society Press, 1996.
- [101] J. Sanyal, S. Zhang, G. Bhattacharya, P. Amburn, and R. Moorhead, “A user study to compare four uncertainty visualization methods for 1d and 2d datasets,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 15, no. 6, 2009.
- [102] G. S. Schmidt, S.-L. Chen, A. N. Bryden, M. A. Livingston, L. J. Rosenblum,

- and B. R. Osborn, “Multidimensional visual representations for underwater environmental uncertainty,” *IEEE Computer Graphics and Applications*, vol. 24, no. 5, pp. 56–65, 2004.
- [103] R. Stokking, I. G. Zubal, and M. A. Viergever, “Display of fused images: methods, interpretation, and diagnostic improvements,” in *Seminars in Nuclear Medicine*, vol. 33, pp. 219–227, Elsevier, 2003.
- [104] T. Zuk, J. Downton, D. Gray, S. Carpendale, and J. Liang, “Exploration of uncertainty in bidirectional vector fields,” in *Visualization and Data Analysis 2008*, vol. 6809, p. 68090B, International Society for Optics and Photonics, 2008.
- [105] B. Zehner, N. Watanabe, and O. Kolditz, “Visualization of gridded scalar data with uncertainty in geosciences,” *Computers & Geosciences*, vol. 36, no. 10, pp. 1268–1275, 2010.
- [106] R. Brown, “Animated visual vibrations as an uncertainty visualisation technique,” in *Proceedings of the 2nd international conference on Computer graphics and interactive techniques in Australasia and South East Asia*, pp. 84–89, ACM, 2004.
- [107] U. D. Bordoloi, D. L. Kao, and H.-W. Shen, “Visualization techniques for spatial probability density function data,” *Data Science Journal*, vol. 3, pp. 153–162, 2004.
- [108] A. Luo, D. Kao, and A. Pang, “Visualizing spatial distribution data sets,” in *VisSym*, vol. 3, pp. 29–38, 2003.
- [109] D. Kao, J. L. Dungan, and A. Pang, “Visualizing 2d probability distributions from eos satellite image-derived data sets: A case study,” in *Visualization, 2001. VIS’01. Proceedings*, pp. 457–589, IEEE, 2001.

- [110] D. L. Kao, M. G. Kramer, A. L. Love, J. L. Dungan, and A. T. Pang, “Visualizing distributions from multi-return lidar data to understand forest structure,” *The Cartographic Journal*, vol. 42, no. 1, pp. 35–47, 2005.
- [111] K. Potter, P. Rosen, and C. Johnson, “From quantification to visualization: A taxonomy of uncertainty visualization approaches,” *Uncertainty Quantification in Scientific Computing*, pp. 226–249, 2012.
- [112] C. D. Correa, Y.-H. Chan, and K.-L. Ma, “A framework for uncertainty-aware visual analytics,” in *Visual Analytics Science and Technology, 2009. VAST 2009. IEEE Symposium on*, pp. 51–58, IEEE, 2009.
- [113] H.-J. Schulz, “Treevis. net: A tree visualization reference,” *IEEE Computer Graphics and Applications*, vol. 31, no. 6, pp. 11–15, 2011.
- [114] B. Johnson and B. Shneiderman, “Tree-maps: A space-filling approach to the visualization of hierarchical information structures,” in *Proceedings of the 2nd conference on Visualization’91*, pp. 284–291, IEEE Computer Society Press, 1991.
- [115] H. Zhao and L. Lu, “Variational circular treemaps for interactive visualization of hierarchical data,” in *Visualization Symposium (PacificVis), 2015 IEEE Pacific*, pp. 81–85, IEEE, 2015.
- [116] M. Balzer, O. Deussen, and C. Lewerentz, “Voronoi treemaps for the visualization of software metrics,” in *Proceedings of the 2005 ACM symposium on Software visualization*, pp. 165–172, ACM, 2005.
- [117] M. Bruls, K. Huizing, and J. J. Van Wijk, “Squarified treemaps,” in *Data visualization 2000*, pp. 33–42, Springer, 2000.

- [118] D. Auber, C. Huet, A. Lambert, B. Renoust, A. Sallaberry, and A. Saulnier, “Gospermap: Using a gosper curve for laying out hierarchical data,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 19, no. 11, pp. 1820–1832, 2013.
- [119] H.-J. Schulz, S. Hadlak, and H. Schumann, “The design space of implicit hierarchy visualization: A survey,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 17, no. 4, pp. 393–411, 2011.
- [120] J. Görtler, C. Schulz, D. Weiskopf, and O. Deussen, “Bubble treemaps for uncertainty visualization,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 24, no. 1, pp. 719–728, 2018.
- [121] T. Mühlbacher, H. Piringer, S. Gratzl, M. Sedlmair, and M. Streit, “Opening the black box: Strategies for increased user involvement in existing algorithm implementations,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 20, no. 12, pp. 1643–1652, 2014.
- [122] M. Liu, J. Shi, Z. Li, C. Li, J. Zhu, and S. Liu, “Towards better analysis of deep convolutional neural networks,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 23, no. 1, pp. 91–100, 2017.
- [123] J.-D. Fekete, “Visual analytics infrastructures: From data management to exploration,” *Computer*, vol. 46, no. 7, pp. 22–29, 2013.
- [124] P. Rheingans, W. Brown, A. Morrow, D. Stull, K. Winner, *et al.*, “Visualizing uncertainty in predictive models,” in *Scientific Visualization*, pp. 61–69, Springer, 2014.
- [125] X. Wang, S. Liu, J. Liu, J. Chen, J. Zhu, and B. Guo, “Topicpanorama: A full picture of relevant topics,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 22, no. 12, pp. 2508–2521, 2016.

- [126] S. Liu, X. Wang, M. Liu, and J. Zhu, “Towards better analysis of machine learning models: A visual analytics perspective,” *Visual Informatics*, vol. 1, no. 1, pp. 48–56, 2017.
- [127] M. Fernandes, L. Walls, S. Munson, J. Hullman, M. Kay, *et al.*, “Uncertainty displays using quantile dotplots or cdfs improve transit decision-making,” 2018.
- [128] J. C. Aerts, K. C. Clarke, and A. D. Keuper, “Testing popular visualization techniques for representing model uncertainty,” *Cartography and Geographic Information Science*, vol. 30, no. 3, pp. 249–261, 2003.
- [129] T. Strothotte, M. Masuch, and T. Isenberg, “Visualizing knowledge about virtual reconstructions of ancient architecture,” in *cgi*, p. 36, IEEE, 1999.
- [130] P. J. Rhodes, R. S. Laramée, R. D. Bergeron, T. M. Sparr, *et al.*, “Uncertainty visualization methods in isosurface rendering,” in *Eurographics*, vol. 2003, pp. 83–88, 2003.
- [131] S. Diepenbrock, J.-S. Praßni, F. Lindemann, H.-W. Bothe, and T. Ropinski, “Interactive visualization techniques for neurosurgery planning,” in *Eurographics 2011, the 32th Annual Conference of the European Association for Computer Graphics, 11-15 April 2011, Llandudno, Wales, UK*, 2011.
- [132] Z. Xie, S. Huang, M. O. Ward, and E. A. Rundensteiner, “Exploratory visualization of multivariate data with variable quality,” in *Visual Analytics Science And Technology, 2006 IEEE Symposium On*, pp. 183–190, IEEE, 2006.
- [133] D. Borland and R. M. T. Ii, “Rainbow color map (still) considered harmful,” *IEEE computer graphics and applications*, vol. 27, no. 2, 2007.
- [134] V. Interrante, “Harnessing natural textures for multivariate visualization,” *IEEE Computer Graphics and Applications*, vol. 20, no. 6, pp. 6–11, 2000.

- [135] A. M. Bisantz, T. Kesevadas, P. Scott, D. Lee, S. Basapur, P. Bhide, P. Bhide, and P. Bhide, “Holistic battlespace visualization: advanced concepts in information visualization and cognitive studies,” *U. Buffalo*, 2002.
- [136] A. R. Sanderson, C. R. Johnson, and R. M. Kirby, “Display of vector fields using a reaction-diffusion model,” in *Proceedings of the conference on Visualization’04*, pp. 115–122, IEEE Computer Society, 2004.
- [137] J. Bertin, “Semiology of graphics: Diagrams, networks, maps (wj berg, trans.),” *Madison, WI: The University of Wisconsin Press, Ltd*, 1983.
- [138] W. Aigner, S. Miksch, B. Thurnher, and S. Biffl, “Planninglines: novel glyphs for representing temporal uncertainties and their evaluation,” in *Information Visualisation, 2005. Proceedings. Ninth International Conference on*, pp. 457–463, IEEE, 2005.
- [139] E. R. Tufte, “The visual display of quantitative information,” *Journal for Healthcare Quality*, vol. 7, no. 3, p. 15, 1985.
- [140] E. R. Tufte, S. R. McKay, W. Christian, and J. R. Matey, “Visual explanations: images and quantities, evidence and narrative,” 1998.
- [141] E. R. Tufte, “Envisioning information. 1990,” *Visual Explanations: Images and Quan*, 2006.
- [142] S. A. Deitrick, “Uncertainty visualization and decision making: Does visualizing uncertain information change decisions,” in *Proceedings of the XXIII International Cartographic Conference*, pp. 4–10, 2007.
- [143] T. S. Newman and W. Lee, “On visualizing uncertainty in volumetric data: techniques and their evaluation,” *Journal of Visual Languages & Computing*, vol. 15, no. 6, pp. 463–491, 2004.

- [144] J. Bertin, “Graphics and graphic information processing,” in *Readings in Information Visualization*, pp. 62–65, Morgan Kaufmann Publishers Inc., 1999.
- [145] J. M. Chambers, *Graphical methods for data analysis*. CRC Press, 2018.
- [146] “Ads-b exchange world’s largest co-op of unfiltered flight data.” <https://www.adsbexchange.com/#>. (Accessed on 10/29/2018).
- [147] “The opensky network.” <https://opensky-network.org/>. (Accessed on 11/18/2018).
- [148] “cesium-dev - google groups.” <https://groups.google.com/forum/#!forum/cesium-dev>. (Accessed on 10/29/2018).
- [149] “Automatic dependent surveillance broadcast - wikipedia.” https://en.wikipedia.org/wiki/Automatic_dependent_surveillance_%E2%80%93_93_broadcast. (Accessed on 11/18/2018).
- [150] “Mode s - skybrary aviation safety.” https://www.skybrary.aero/index.php/Mode_S. (Accessed on 11/18/2018).
- [151] S. Nykl, C. Mourning, N. Ghandi, and D. Chelberg, “A flight tested wake turbulence aware altimeter,” in *International Symposium on Visual Computing*, pp. 219–228, Springer, 2011.
- [152] S. Nykl, C. Mourning, E. Nykl, D. Chelberg, and T. Skidmore, “Jpals visualization tool,” in *Proceedings of the 2012 IEEE/ACM 16th International Symposium on Distributed Simulation and Real Time Applications*, pp. 3–10, IEEE Computer Society, 2012.
- [153] “Cesiumjs - geospatial 3d mapping and virtual globe platform.” <https://cesiumjs.org/index.html>. (Accessed on 10/29/2018).

- [154] “geojson.io.” <http://geojson.io/#map=2/20.0/0.0>. (Accessed on 10/29/2018).
- [155] “Geojson - wikipedia.” <https://en.wikipedia.org/wiki/GeoJSON>. (Accessed on 10/29/2018).
- [156] “Node.js.” <https://nodejs.org/en/>. (Accessed on 10/29/2018).
- [157] “npm.” <https://www.npmjs.com/>. (Accessed on 10/29/2018).
- [158] C. C. Robusto, “The cosine-haversine formula,” *The American Mathematical Monthly*, vol. 64, no. 1, pp. 38–40, 1957.
- [159] “Haversine formula - wikipedia.” https://en.wikipedia.org/wiki/Haversine_formula. (Accessed on 10/29/2018).
- [160] C. Veness, “Calculate distance and bearing between two latitude/longitude points using haversine formula in javascript,” *Movable Type Scripts*, 2011.
- [161] H.-G. Pagendarm and F. H. Post, *Comparative visualization: Approaches and examples*. Delft University of Technology, Faculty of Technical Mathematics and Informatics, 1995.
- [162] J.-P. Balabanian, I. Viola, and E. Gröller, “Interactive illustrative visualization of hierarchical volume data,” in *Proceedings of Graphics Interface 2010*, pp. 137–144, Canadian Information Processing Society, 2010.
- [163] M. M. Malik, C. Heinzl, and M. E. Groeller, “Comparative visualization for parameter studies of dataset series,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 16, no. 5, pp. 829–840, 2010.
- [164] M. Gleicher, D. Albers, R. Walker, I. Jusufi, C. D. Hansen, and J. C. Roberts, “Visual comparison for information visualization,” *Information Visualization*, vol. 10, no. 4, pp. 289–309, 2011.

- [165] T. Urness, V. Interrante, I. Marusic, E. Longmire, and B. Ganapathisubramani, “Effectively visualizing multi-valued flow data using color and texture,” in *Proceedings of the 14th IEEE Visualization 2003 (VIS’03)*, p. 16, IEEE Computer Society, 2003.
- [166] W. Cai and G. Sakas, “Data intermixing and multi-volume rendering,” in *Computer Graphics Forum*, vol. 18, pp. 359–368, Wiley Online Library, 1999.
- [167] R. Fuchs and H. Hauser, “Visualization of multi-variate scientific data,” in *Computer Graphics Forum*, vol. 28, pp. 1670–1690, Wiley Online Library, 2009.
- [168] H. Hagh-Shenas, S. Kim, V. Interrante, and C. Healey, “Weaving versus blending: a quantitative assessment of the information carrying capacities of two alternative methods for conveying multivariate data with color,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 13, no. 6, pp. 1270–1277, 2007.
- [169] D. Sacha, H. Senaratne, B. C. Kwon, G. Ellis, and D. A. Keim, “The role of uncertainty, awareness, and trust in visual analytics,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 22, no. 1, pp. 240–249, 2016.

Appendix A

Application Code Snippets

In this appendix, we present a few of the code fragments that contribute majorly to our application and that are important in the development of an air corridor estimation and visualization system.

A.1 Cesium Viewer and Terrain Provider

```
var viewer = new Cesium.Viewer('cesiumContainer', {
    shouldAnimate : true
});

var canvas = viewer.canvas;
// needed to put focus on the canvas
canvas.setAttribute('tabindex', '0');
canvas.addEventListener('click', function() {
    canvas.focus();
});
canvas.focus();
```

```
viewer.terrainProvider = Cesium.createWorldTerrain({
    requestWaterMask : true, // required for water effects
    requestVertexNormals : true // required for terrain
        lighting
});
```

Listing A.1: Cesium Viewer and Terrain Provider

A.2 Compute Flight Path

```
function computeFlightPath(lon, lat, radius, index, flag) {
    var count = 0;
    var pos = new Cesium.SampledPositionProperty();
    for (var i = 0; i <= 270; i += 10) {
        var radians = Cesium.Math.toRadians(i);
        var time = Cesium.JulianDate.addSeconds(start, i, new
            Cesium.JulianDate());
        var position = Cesium.Cartesian3.fromDegrees(lon + (
            radius * 1.5 * Math.cos(radians)), lat + (radius *
            Math.sin(radians)), Cesium.Math.nextRandomNumber
            () * 500 + 1750);
        pos.addSample(time, position);
        if(index === 1){
            a[count] = pos.getValue(time);
            var loc1 = pos.getValue(time);
            var locCarto1 = Cesium.Cartographic.fromCartesian
                (loc1);
```

```

var loclon1 = Cesium.Math.toDegrees(locCarto1.
    longitude);
var loclat1 = Cesium.Math.toDegrees(locCarto1.
    latitude);
var locheight1 = locCarto1.height; //height in
    metres
locLonArr1[count] = loclon1;
locLatArr1[count] = loclat1;
locHeightArr1[count] = locheight1 - (
    heightCorridor/2); //Waypoints at mid of the
    corridor as height is 400m
}
if(index === 2) {
    b[count] = pos.getValue(time);
    var loc2 = pos.getValue(time);
    var locCarto2 = Cesium.Cartographic.fromCartesian
        (loc2);
    var loclon2 = Cesium.Math.toDegrees(locCarto2.
        longitude);
    var loclat2 = Cesium.Math.toDegrees(locCarto2.
        latitude);
    var locheight2 = locCarto2.height; //height in
        metres
    locLonArr2[count] = loclon2;
    locLatArr2[count] = loclat2;

```

```

locHeightArr2[count] = locheight2 - (
    heightCorridor/2); //Waypoints at mid of the
    corridor as height is 400m
}

//Also create a point for each sample we generate.
if(index == 1 && flag == 0) {
    viewer.entities.add({
        position : position ,
        point : {
            pixelSize : 8,
            color : Cesium.Color.TRANSPARENT,
            outlineColor : Cesium.Color.YELLOW,
            outlineWidth : 3
        }
    });
}

if(index == 2 && flag == 0) {
    viewer.entities.add({
        position : position ,
        point : {
            pixelSize : 8,
            color : Cesium.Color.TRANSPARENT,
            outlineColor : Cesium.Color.RED,
            outlineWidth : 3
        }
    });
}

```

```

        });
    }
    count++;
}
return pos;
}

```

Listing A.2: Compute Flight Path

A.3 Compute Reference Flight Path

```

function computeFinalFlightPath(a, b, flag) {
    var count = 0
    var pos = new Cesium.SampledPositionProperty();
    //When no extrapolation/interpolation is required
    if (extp.length === 0) {
        for (var i = 0; i < b.length; i++) {
            var radians = Cesium.Math.toRadians(i*15);
            var time = Cesium.JulianDate.addSeconds(start, i,
                new Cesium.JulianDate());
            var position = Cesium.Cartesian3.fromElements(((a
                [i*3].x+b[i].x)/2), ((a[i*3].y+b[i].y)/2), ((a
                [i*3].z+b[i].z)/2));
            pos.addSample(time, position);
            var loc = pos.getValue(time);
            c[count] = position;
        }
    }
}

```

```

var locCarto = Cesium.Cartographic.fromCartesian(
    loc);
var loclon = Cesium.Math.toDegrees(locCarto.
    longitude);
var loclat = Cesium.Math.toDegrees(locCarto.
    latitude);
var locheight = locCarto.height; //height in
    metres
locLonArr[count] = loclon;
locLatArr[count] = loclat;
locHeightArr[count] = locheight - (heightCorridor
    /2); //Waypoints at mid of the corridor as
    height is 400m
//Also create a point for each sample we generate
    .
    if (flag == 0) {
        viewer.entities.add({
            position : position ,
            point : {
                pixelSize : 8,
                color : Cesium.Color.TRANSPARENT,
                outlineColor : Cesium.Color.CYAN,
                outlineWidth : 3
            }
        });
    }

```

```

        count1++;
    }
}

//When extrapolation/interpolation is required
if(extp.length > 0) {
    for (var i = 0; i < a.length; i++) {
        var radians = Cesium.Math.toRadians(i);
        var time = Cesium.JulianDate.addSeconds(start, i, new
            Cesium.JulianDate());
        var position1 = Cesium.Cartesian3.fromElements(((a[i]
            ].x+extp[i].x)/2), ((a[i].y+extp[i].y)/2), ((a[i].
            z+extp[i].z)/2));
        pos1.addSample(time, position1);
        var loc = pos1.getValue(time);
        c[count1] = position1;

        var locCarto = Cesium.Cartographic.fromCartesian(loc)
            ;

        var loclon = Cesium.Math.toDegrees(locCarto.
            longitude);
        var loclat = Cesium.Math.toDegrees(locCarto.
            latitude);
        var locheight = locCarto.height; //height in
            metres
        locLonArr[count1] = loclon;
    }
}

```

```

locLatArr[count1] = loclat;
locHeightArr[count1] = locheight - (
    heightCorridor/2); //Waypoints at mid of the
    corridor as height is 400m
//Also create a point for each sample we generate
    .
if (flag == 0) {
    viewer.entities.add({
        position : position1,
        point : {
            pixelSize : 8,
            color : Cesium.Color.TRANSPARENT,
            outlineColor : Cesium.Color.CYAN,
            outlineWidth : 3
        }
    });
}
count1++;
}
}

return pos1;
}

```

Listing A.3: Function to compute reference flight path

A.4 Data Preprocessing in MATLAB

```
clc;
clear all;
fileName = 'singleAircraftData.txt';
A = dlmread(fileName, '', [0 0 500934 2]);
M = A(200:200:end, :);
M(:, [1 2]) = M(:, [2 1]);
B = zeros(2504, 1);
count = 0;
for i = 1:2504
    B(i, 1) = count;
    count = count + 10;
end
P = [B M];
csvwrite('singleAircraftCSVData.txt', P);
```

Listing A.4: Data Preprocessing